Paper Reconstruction Evaluation: Evaluating Presentation and Hallucination in AI-written Papers

Abstract

This paper introduces the first systematic and verifiable evaluation framework for quantifying the quality and risks of papers written by modern coding agents. While AI-driven paper writing has become a growing concern, existing evaluations of AI-written papers remain largely subjective, relying on overall reviewer scores that are difficult to verify and not grounded in measurable scientific correctness. We introduce **Paper Reconstruction Evaluation** (PaperRecon), an evaluation framework in which an overview (overview.md) is created from an existing paper, after which an agent generates a full paper based on the overview and minimal additional resources, and the result is subsequently compared against the original paper. PaperRecon disentangles the evaluation of the AI-written papers into two orthogonal dimensions, **Presentation** and **Hallucination**, where Presentation is evaluated using a rubric and Hallucination is assessed via agentic evaluation grounded in the original paper source. For evaluation, we introduce **PaperWrite-Bench**, a benchmark of 51 papers from top-tier venues across diverse domains published after 2025. Our experiments reveal a clear trade-off: while both ClaudeCode and Codex improve with model advances, ClaudeCode achieves higher presentation quality at the cost of more than 10 hallucinations per paper on average, whereas Codex produces fewer hallucinations but lower presentation quality. This work takes a first step toward establishing verifiable evaluation frameworks for AI-driven paper writing and improving the understanding of its risks within the research community.

1 Introduction

As recent AI tools, exemplified by coding agents, continue to advance, it is increasingly important to rigorously evaluate how they automate the research process and the potential risks they introduce, in order to ensure sustainable AI-driven scientific progress (Miyai et al., 2026). In particular, recent incidents involve submissions of AI-written papers to academic venues (Liang et al., 2025; ICLR Program Chairs, 2025; Neubig, 2025). These submissions are likely to continue increasing alongside the rapid growth of AI Scientists in recent years (Intology, 2025; Weng et al., 2026; Miyai et al., 2026). To advance scientific progress while preserving academic integrity, it is essential for the research community to continuously monitor the progress and risks of AI-driven writing based on rigorous and reliable evaluation.

Evaluating the paper writing capability of AI agents is inherently challenging and has not been sufficiently addressed in prior work. Existing approaches have explored using AI reviewers to assess paper quality (Liu et al., 2024; Yamada et al., 2025; Weng et al., 2025; Zhu et al., 2025). However, these methods are inadequate, as they tend to assign higher scores to papers with more severe fabrications (Jiang et al., 2025; Miyai et al., 2026). While hallucinations in AI-written papers have been recognized, prior work has been limited to surface-level issues such as citation errors (Walters and Wilder, 2023; Ansari, 2026; Sakai et al., 2026) or individual hallucination cases (Yamada et al., 2025; Miyai et al., 2026), without enabling systematic evaluation.

We propose **Paper Reconstruction Evaluation** (PaperRecon), the first verifiable evaluation framework for measuring the paper writing capabilities of AI agents. The overview of PaperRecon is shown in Figure 1. PaperRecon first compresses an existing paper into a structured summary, `research_overview.md`, which retains only essential information. Given this compressed representation, along with other minimal resources (tables, figures, bib file), agents are tasked with reconstructing the original paper. This workflow of generating a paper from minimal inputs is equivalent to isolating the writing component of existing

Figure 1: **Paper Reconstruction Evaluation**. Given minimal resources derived from a original paper, a coding agent reconstructs the full paper. The generated paper is then compared with the original paper to evaluate writing performance along two complementary axes: presentation quality and hallucination. Here, after the Step 0, we perform careful human verification to ensure that the provided resources contain all necessary information.

AI Scientist systems (Yamada et al., 2025; Weng et al., 2026; Miyai et al., 2026). If agents can reliably reconstruct high-fidelity papers, this provides a strong signal of their writing capabilities.

The key strength of PaperRecon as an evaluation framework lies in its ability to enable precise assessment through direct comparison with the original paper. In particular, it decomposes the notion of writing quality into two orthogonal dimensions: **Presentation** and **Hallucination**. Presentation is evaluated using rubric evaluation (Fan et al., 2024; Phung et al., 2023; Arora et al., 2025), assessing how faithfully the key elements of the original paper are preserved in the reconstructed paper. Hallucinations are assessed via agentic evaluation grounded in the original paper source, enabling fine-grained detection of factual inconsistencies. This design allows PaperRecon to jointly evaluate both presentation quality and factual correctness in a unified and reliable manner.

For PaperRecon, we introduce **PaperWrite-Bench**, a benchmark constructed from 51 papers published after 2025. PaperWrite-Bench consists of papers from a diverse set of top-tier venues, including NeurIPS, ICLR, CVPR, ICCV, ACL, and ACMMM, providing broad coverage across research domains. This benchmark enables systematic and comprehensive evaluation of modern writing agents across realistic and diverse fields.

We evaluate recent powerful and widely used agents, including Claude Code (Anthropic, 2025a), Claude Code Agent Teams (Anthropic, 2026), and Codex (OpenAI, 2025), across a range of under-

lying models, from Claude Sonnet 4 (Anthropic, 2025b) and Claude Sonnet 4.6 (Anthropic, 2026) to GPT-5 (OpenAI, 2025) and GPT-5.4 (OpenAI, 2026). Our experiments yield the following key findings:

1. **Claude Code achieves higher presentation quality than Codex.** Claude Code better captures the key elements required for scientific writing across sections.

2. **Codex produces fewer hallucinations than Claude Code.** While Claude Code exhibits more than 10 hallucinations per paper on average, Codex limits this to around 3.

3. **Writing capability improves with model advances.** This also suggests that Paper Reconstruction Evaluation serves as a reliable metric for tracking progress in writing ability.

Our work makes the following contributions to the research community:

- **Paper Reconstruction Evaluation (PaperRecon):** We propose the first evaluation framework for scientific writing, Paper Reconstruction Evaluation, which measures the quality of paper reconstruction from compressed representations, along with a detailed evaluation protocol.

- **PaperWrite-Bench:** We introduce PaperWrite-Bench, a benchmark constructed from recent papers across diverse

research domains, enabling comprehensive evaluation of agents' ability to reconstruct papers from minimal information.

- **Quantitative analysis of presentation and hallucination:** We provide a systematic evaluation of modern agents across both Presentation and Hallucination, quantifying how their capabilities evolve with model advances. Our results offer insights into the current state and trade-offs of AI-driven scientific writing.

2 Related Work

AI-driven Research Automation. Recent progress in AI has accelerated efforts to automate various stages of the research process (Si et al., 2025b,a; Asai et al., 2026; Novikov et al., 2025; Weng et al., 2025; Villaescusa-Navarro et al., 2025; Mitchener et al., 2025; Zhuang et al., 2025; Lin et al., 2023; Gottweis et al., 2025), as well as end-to-end research pipelines (Lu et al., 2024; Intology, 2025; Tang et al., 2025; Miyai et al., 2026). However, recent work highlights the growing importance of carefully understanding the risks associated with increasingly capable AI scientists (Miyai et al., 2026). (Miyai et al., 2026) reports risks across all stages of the research process, and shows that the writing stage is especially prone to hallucinations such as inconsistencies with experimental results and fabricated content. This work aims to accurately measure the writing capabilities of modern agents through a novel evaluation framework.

Evaluation of AI-written Articles. Evaluation of AI-written articles has been studied in domains beyond scientific papers (Yang et al., 2023; Fitria, 2023; Zhong et al., 2026; Shao et al., 2024). For example, prior work has long explored generating Wikipedia pages (Banerjee and Mitra, 2015; Minguillón et al., 2017; Liu et al., 2018; Fan and Gardent, 2022; Shao et al., 2024). In addition, (Zhong et al., 2026) evaluates how well AI systems can write essays by using real GRE writing prompts. However, there are few papers to evaluate AI-driven scientific writing. This difference is likely due to the complexity of scientific writing, which requires justifying the significance of the problem, situating the work within the existing research landscape, designing sound and valid evaluation protocols, ensuring reproducibility and verifiability, and maintaining alignment between claims and supporting evidence. These requirements made earlier AI systems struggle with scientific writing and its eval-

uation, making it substantially more challenging than tasks such as Wikipedia or essay writing.

Hallucination and Evaluation of AI-written Papers. It is widely recognized that papers written by AI systems often contain hallucinations. However, existing studies have been limited to surface-level issues such as citation errors (Walters and Wilder, 2023; Ansari, 2026; Sakai et al., 2026) or individual hallucination cases (Miyai et al., 2026), without enabling systematic evaluation. This limitation largely stems from the absence of a well-defined protocol for assessing the substantive content of generated papers. As a result, existing evaluations of AI-written scientific papers have primarily relied on review-based assessment, focusing on whether a paper surpasses the acceptance threshold of academic venues (Lu et al., 2024; Yamada et al., 2025; Weng et al., 2025; Zhu et al., 2025). However, prior work has shown that AI reviewers often fail to detect hallucinations, leading to cases where papers with more severe hallucinations receive higher scores (Jiang et al., 2025; Miyai et al., 2026). While AI-Researcher (Tang et al., 2025) shares a similar perspective in generating new papers from source materials of existing research, it evaluates novelty, methodological validity, and empirical performance, making them fundamentally different from writing evaluation. Therefore, to accurately understand the risks of AI-driven writing, it is essential to establish an evaluation protocol that directly assesses both presentation quality and hallucination.

3 Paper Reconstruction Evaluation

3.1 Why Reconstruction is a Suitable Evaluation Framework

Our objective is to establish a verifiable framework for evaluating scientific writing through reconstruction, rather than a system for paper replication or end-to-end research automation. Unlike existing review-based AI evaluations, which typically rely on overall review scores or subjective ratings, reconstruction enables direct comparison between generated and original papers, making it possible to explicitly measure whether the scientific content is faithfully preserved or distorted by unsupported or contradictory claims. Thus, the main contribution of PaperRecon is a ground-truth-based evaluation framework for assessing risks in AI-assisted scientific writing.

Figure 2: **Overview of PaperRecon evaluation pipeline.** Our evaluation compares generated papers against GT (original) papers along two complementary axes: Presentation evaluation with rubric and agentic hallucination evaluation

3.2 Problem Definition

Paper Reconstruction Evaluation (PaperRecon) is a framework for evaluating how accurately coding agents can reconstruct scientific papers.

From each original paper, we extract the following information and provide it to the agent: (1) `Research Overview`: A Markdown file summarizing the motivation, method, and key experimental results of the paper. (2) `Figure`: Figures from the original paper with simplified captions (*e.g.,* fig_method.jpg: Method Overview.). (3) `Table`: LaTeX source code of tables from the original paper with simplified captions (*e.g.,* table_cb.tex: Main Result.). (4) `References`: The bibliography file of the original paper, where each entry is augmented with its abstract. (5) `Code`: The codebase associated with the original paper, if available.

Given these inputs, the agent is tasked with reconstructing the original paper. The generated paper is then compared against the original from multiple perspectives to evaluate writing capability. Here, we reuse the original references instead of requiring agents to construct them from scratch, as accurate reference collection is itself a separate research problem. This design allows us to isolate and evaluate the core writing ability of the agent.

3.3 Evaluation Protocol

We evaluate generated papers by comparing them against ground-truth (GT) papers along three complementary axes: Presentation evaluation with rubric, agentic hallucination evaluation, and citation-level evaluation. Figure 2 shows the overview of presentation and hallucination evaluation pipelines. To compute these scores, we first perform section classification and matching, then evaluate each matched pair.

3.3.1 Section Classification and Matching

Papers organize sections differently, so we first extract all sections from both the GT and generated LaTeX files. Next, we map them into seven common categories: *Abstract*, *Introduction*, *Method*, *Benchmark Construction*, *Experiment*, *Related Work*, and *Conclusion*. Classification first applies keyword-based rules (*e.g.,* "preliminary" → Method, "ablation studies" → Experiment); sections that cannot be classified by rules are passed to an LLM for classification based on section name and content. When multiple raw sections map to the same category, they are merged. This classification is performed once and shared across all subsequent evaluation steps.

3.3.2 Rubric Evaluation

To enable accurate and fine-grained evaluation, we adopt a rubric evaluation (Fan et al., 2024; Phung et al., 2023; Arora et al., 2025). We found in preliminary experiments that LLM-as-a-judge yielded low discriminative power in evaluation, whereas rubric evaluation enables more discriminative assessment.

For each GT paper, we pre-construct a rubric that specifies key elements expected in each sec-

tion, along with their relative importance and descriptions. Each rubric element corresponds to a concrete and verifiable point (*e.g.,* "Problem motivation: improve reasoning in vision-language models" for the Abstract, or "Evaluation covers both visual reasoning and general image understanding benchmarks" for the Experiment section). These rubrics are initially generated from the GT paper using an LLM (*i.e.,* GPT-5.4 (OpenAI, 2026)), and are subsequently reviewed and, when necessary, refined by the authors to ensure quality and correctness.

For each section excluding the Conclusion section, we use an LLM judge with GPT-5.4 to evaluate how well the generated section covers each rubric element on a 1–5 scale: *5: the content is fully and accurately described with correct details*; *4: the content is mostly described, with the core idea present but some details missing; 3: the content is partially described, with significant gaps or vagueness; 2: the content is barely mentioned, with only a superficial or indirect reference; 1: the content is completely absent from the generated section.*

In addition to text-based rubric elements, we incorporate figure- and table-level scores as part of the evaluation rubric.

Figure Evaluation. We align GT and figures in the generated papers based on GT Tex file and assess their contextual appropriateness. If both the GT and generated papers reference a figure within the same section, a full context score of 5 is assigned. Otherwise, an LLM evaluates whether the figure is used in an appropriate context on a 1–5 scale. If the generated paper references the figure in any section (even if different from the GT), the LLM-derived score is used; if the figure is not referenced at all, it is assigned a score of 1.

Table Evaluation. We extract tables from both GT and generated LaTeX files and perform matching using a hierarchical strategy: label matching, caption matching, and LLM-based matching. For each matched pair, an LLM evaluates numerical accuracy, structural alignment, and content consistency, producing a match score on a 1–5 scale. Tables present in the GT but missing from the generated paper are assigned a score of 1.

The final rubric score for each section is the average across all rubric elements (text, figure, and table items combined). The average number of rubrics for each section is as follows: Abstract: 10.3, Introduction: 13.3, Related Work: 12.6,

Method: 14.2, Benchmark Construction: 14.6, and Experiment: 14.3.

3.3.3 Hallucination Analysis

We identify factual errors via a two-stage, claim-level analysis.

Stage 1: Claim Extraction. For each section (excluding the Conclusion), an LLM (*i.e.,* GPT-5.4) extracts all concrete and verifiable claims from the generated content and classifies each claim into one of the following categories:

1. Supported: directly stated in, or logically derivable from, the GT paper.

2. Neutral: not present in the GT paper, but a reasonable general statement or supplementary detail that does not contradict it (note that absence from the GT does not imply contradiction).

3. Contradictory: directly conflicts with specific information in the GT paper.

For claims classified as contradictory, we further assign a severity level: **major** (*e.g.,* incorrect numerical values, fabricated results, or incorrect method descriptions) or **minor** (*e.g.,* overly strong generalizations, imprecise wording).

Stage 2: Verification. All claims labeled as contradictory across sections are aggregated and re-evaluated with a coding agent (*i.e.,* Claude Code with Sonnet4.6). The agent is provided with the GT paper resources (including LaTeX source, codebase, figures, and tables) and re-examines each flagged claim, potentially revising false positives to *supported* or *neutral*. This two-stage design reduces false positives while limiting the computational cost to a single agent invocation. Finally, we report the *major contradictory* claims.

3.3.4 Citation-Level Evaluation

While the primary objective of PaperRecon is to assess the content of generated papers, we also evaluate citation usage by comparing citation keys between the GT and generated papers using an F1-based metric.

We extract all citation keys in both GT and generated LaTeX files, and compute precision, recall, and F1 score based on the overlap of citation key sets. We additionally detect *hallucinated citations* (keys cited in the generated paper but absent from `references.bib`), *missing citations* (keys in GT but not in the generated paper), and *extra citations* (keys added by the prediction that are not in GT).

3.3.5 Overall Metrics

We report the following aggregate metrics: (i) **Avg. Rubric Score**: Mean rubric score across all evaluated sections and elements (1–5 scale), including figure and table items. (ii) **Hallucination Counts**: Total number of major contradictory claims detected across all sections after two-stage verification. (iii) **Citation Scores**: Precision (valid cited / total cited), Recall (valid cited GT / total GT), F1 (harmonic mean), Hallucination (num of invalid citations).

4 PaperWrite-Bench

4.1 Benchmark Overview

In this section, we introduce PaperWrite-Bench, a benchmark designed for PaperRecon.

Paper Source. PaperWrite-Bench consists of 51 papers manually curated by the authors, selected from a diverse set of top-tier conferences, including ACL 2025, EMNLP 2025, CVPR 2025, CVPR 2026, ICCV 2025, ICLR 2025, NeurIPS 2025, ICLR 2026, and ACMMM 2025, covering a wide range of domains such as computer vision, natural language processing, machine learning, and multimedia processing. Among the 51 papers, 32 focus on proposing new methods, 12 introduce new benchmarks, and 7 combine both contributions. This diversity enables comprehensive evaluation of agent writing capabilities across different types of scientific papers.

Benchmark Coverage and Reliability. Our benchmark consists of 51 papers covering 259 sections and 3,365 rubric evaluation points, with hallucination analysis performed at the sentence level. In addition, each stage of the pipeline involves careful human verification and refinement, including validation of `research_overview.md` and the construction of evaluation rubrics. While scaling such evaluation is inherently expensive, this design achieves substantial evaluation coverage while maintaining high evaluation reliability through extensive human oversight.

4.2 Benchmark Construction Pipeline

Construction of research_overview.md. For each paper, we generate a `research_overview.md` using GPT-5 (OpenAI, 2025), which summarizes the key information required for reconstruction. To ensure quality, the authors manually verify that the overview contains sufficient information to faithfully reconstruct the original paper. On average,

each file contains 463 words.

Extraction of Tables, Figures, References, and Code. Using the arXiv source files, we extract tables and figures and store them in dedicated directories (`tables/` and `figures/`). Following prior work (Liu et al., 2024), we provide structured reference information to the agent via `table_summary.txt` and `figure_summary.txt`, which include file paths and brief descriptions (e.g., the first line of the original caption). To ensure proper use of references, we augment each entry in the `.bib` file with abstracts retrieved via the Semantic Scholar API. In addition, we include the associated codebase, when available, to facilitate accurate reconstruction of the proposed methods. When the README.md file in the code contained sections such as an abstract or introduction, those parts were manually removed.

Template and Style File Construction. We extract the section structure of each original paper from the arXiv source and create a `template.tex`, along with the necessary style files. The `template.tex` contains only the section structure of the original paper, preserving the same section headings while leaving the content empty. Agents are instructed to generate the paper following this predefined structure. This design is motivated by the observation that section organization varies significantly across papers, making direct comparison between generated and original papers difficult. By fixing the section structure, we enable more accurate and consistent evaluation. Moreover, since defining the section structure is a simple preprocessing step, this pipeline remains practical, requiring only minimal human intervention before the writing task is carried out by the agent.

5 Experiments

5.1 Experimental Setup

Agents. We evaluate three coding agents: Claude Code (Anthropic, 2025a) (single-agent), Codex (OpenAI, 2025) (single-agent), and Claude Agent Teams (Anthropic, 2026) (multi-agent). Claude Code is evaluated with Sonnet 4 (Anthropic, 2025b) and Sonnet 4.6 (Anthropic, 2026), Codex with GPT-5 (OpenAI, 2025) and GPT-5.4 (OpenAI, 2026), and Claude Agent Teams with Sonnet 4.6, resulting in five agent configurations in total.

Writing Pipeline. The goal of this study is to understand how well the current agents can perform scientific writing under a simple setup and what

Table 1: **Presentation evaluation.** Rubric evaluation scores by model and section (1–5 scale). We observe that Claude Code achieves higher presentation quality than Codex.

Agent	Model	Abs.	Intro.	Rel.	Meth.	Bench.	Exp.	Avg.
Codex	GPT5	4.00	3.58	2.32	2.89	3.25	3.53	3.26
Codex	GPT5.4	4.06	3.87	2.72	3.51	3.79	3.64	3.59
ClaudeCode	Sonnet4	4.10	3.88	2.48	3.23	3.63	3.66	3.49
ClaudeCode	Sonnet4.6	**4.37**	**4.12**	**3.08**	**3.69**	3.84	**4.00**	**3.86**
ClaudeCode-Teams	Sonnet4.6	4.28	4.05	3.07	3.62	**3.99**	3.97	3.82

Table 2: **Hallucination evaluation.** Each score represents the average number of hallucinations per paper in each section. We observe that Codex produces fewer hallucinations than Claude Code.

Agent	Model	Abs.	Intro.	Rel.	Meth.	Bench.	Exp.	Total
Codex	GPT5	0.3	0.6	0.3	3.8	1.9	3.4	10.2
Codex	GPT5.4	**0.1**	**0.3**	**0.2**	**1.3**	**0.2**	**0.9**	**3.0**
ClaudeCode	Sonnet4	0.2	0.5	0.5	5.4	0.8	4.7	12.0
ClaudeCode	Sonnet4.6	0.2	0.8	0.6	4.7	0.5	3.6	10.4
ClaudeCode-Teams	Sonnet4.6	0.3	0.6	0.8	3.9	0.5	3.8	9.8

Table 3: Citation evaluation scores.

Agent	Model	Prec.	Recall	F1	Hal.
Codex	GPT5	**0.89**	0.27	0.39	**0.0**
Codex	GPT5.4	0.86	0.43	0.56	**0.0**
ClaudeCode	Sonnet4	0.75	0.24	0.34	3.5
ClaudeCode	Sonnet4.6	0.83	**0.58**	**0.67**	0.2
ClaudeCode-Teams	Sonnet4.6	0.84	0.56	0.66	0.2

risks arise in the process. Therefore, we adopt a deliberately simple writing pipeline. Our pipeline includes a compilation feedback loop, where LaTeX errors are returned to the agent for correction, as well as a page limit adjustment step following Liu et al. (2024); Yamada et al. (2025).

5.2 Main Results

We report rubric-based presentation evaluation scores in Table 1. For hallucination evaluation, we report the average number of hallucinations, defined as claims classified as *major contradictory*, in Table 2. Table 3 shows the citation evaluation results.

We summarize the key findings below.

[F1] Claude Code outperforms Codex in presentation quality. As shown in Table 1, Claude Code consistently achieves higher presentation scores than Codex across all sections, indicating a stronger ability to capture and articulate key scientific points. However, the best-performing agent, Claude Code with Claude Sonnet 4.6, reaches a score of 3.86, suggesting that there remains substantial room for improvement.

[F2] Claude Code exhibits substantially more Hallucinations, while Codex significantly reduces them. Table 2 reports the average number of hallucinations per paper across sections. We observe a clear contrast: although Claude Code achieves higher presentation quality, it produces a large number of hallucinations, exceeding 10 per paper even with Claude Sonnet 4.6. In contrast, using GPT-5.4 (OpenAI, 2026) reduces hallucinations to around 3 per paper. These results reveal a clear trade-off between presentation quality and hallucination, highlighting the importance of evaluating both dimensions to accurately assess model performance.

[F3] Codex produces fewer citation hallucinations than Claude Code. Table 3 reports the results on citation accuracy. Consistent with **[F2]**, while Claude achieves higher Citation F1 scores, Codex produces substantially fewer hallucinated citations. This again highlights a trade-off between citation coverage and factual reliability.

[F4] Writing capability improves with model advances. Our evaluation framework accurately captures performance gains from model improvements. We observe consistent increases in writing quality from Claude Sonnet 4 (Anthropic, 2025b) to Claude Sonnet 4.6 (Anthropic, 2026), as well as from GPT-5 (OpenAI, 2025) to GPT-5.4 (OpenAI, 2026), demonstrating that PaperRecon effectively

Table 4: **Effect of research overview length.** Comparison of default vs. long research overview as input to the writing agent. Scores are averaged across 12 papers.

Overview	Rubric Eval↑		Hallucination↓	
	Default	Long	Default	Long
Sonnet4	3.49	**3.64**	8.8	**5.8**
Sonnet4.6	3.83	**4.17**	9.8	**2.3**

Table 5: **Effect on circular bias.** Correlation on rubric evaluation between GPT-5.4 and Gemini-3-Flash.

Scope	Agent	Pearson
Paper-level	Codex/GPT5.4	0.959
	others	0.967
Section-level	Codex/GPT5.4	0.931
	others	0.936

tracks progress in writing capability.

5.3 Human Validation

Presentation Validation. To validate the reliability of our proposed evaluation framework, we conducted a human correlation analysis using 72 pairs of generated papers. These pairs were constructed from 12 source papers, each reconstructed by four agent configurations (*i.e.,* Claude Code and Codex, each with two backbone LLMs), yielding six pairwise combinations per source. We recruited three human reviewers with experience as reviewers at top-tier conferences, each of whom provided pairwise judgments (win, tie, or lose) for the 24 paper pairs. We then measured the Kendall's τ_b correlation between these human judgments and the rankings induced by our rubric-based evaluation scores. Our results demonstrate a strong and highly significant correlation ($\tau_b = 0.578$, $p < 0.001$), indicating that the rubric-based evaluation aligns well with expert human judgment. These findings suggest that our evaluation framework can provide consistent and high-quality scoring.

Hallucination Validation. For hallucination validation, we extracted 97 instances labeled as *major contradictory* in GPT-5, GPT-5.4 and Sonnet-4.6 papers and manually examined them. We find that 96% of these correspond to genuine contradictions or fabrications. This result indicates that hallucinations detected by our method are highly likely to be true hallucinations.

5.4 Analysis

Effect of Research Overview Length. We investigate how the granularity of the research overview affects reconstruction quality by comparing with long versions. The default overview provides a high-level summary (463 words on average), while the long overview includes more detailed descriptions of methodology and experimental design (1,492 words on average). Table 4 shows that, consistent with intuition, more detailed research overviews lead to higher presentation and fewer hallucinations.

Effect on Circular Bias. In the main experiments, we use GPT-5.4 for evaluation. One may therefore wonder to what extent this introduces bias into the evaluation of GPT-5.4-generated papers. Before discussing evaluator circularity, we would like to emphasize our analysis is not intended as a strict test of evaluator circularity. This is because the sources provided to the model for writing and evaluation are entirely different and human verification and editing were incorporated throughout the evaluation pipeline, including the refinement of research_overview.md and rubrics.

For the evaluation, we adopt GPT-5.4 and Gemini-3-Flash as evaluators. The evaluation results for GPT-5.4-generated papers and papers generated by other models are shown in Table 5. We report the Pearson correlation coefficient, which measures the strength of linear relationships between the evaluation results. The results show almost no difference in the correlations, suggesting that circular bias is negligible in our task. Using multiple models for both experimentation and evaluation dramatically increases the complexity of user management, and the impact becomes enormous when a model becomes unavailable. Therefore, we continue to use GPT-5.4 for evaluation.

6 Conclusion

We introduced PaperRecon, the first systematic and verifiable framework for evaluating AI-written scientific papers. By reconstructing papers from concise overviews and comparing generated outputs against the original publications, PaperRecon separates evaluation into Presentation and Hallucination. We also presented PaperWrite-Bench, a benchmark of 51 recent top-tier papers. Our experiments reveal a clear trade-off between writing quality and factual reliability.

Limitations and Future Work

Our benchmark primarily targets papers in the AI domains of Computer Vision, Machine Learning, and Natural Language Processing. This is mainly because the authors possess domain expertise in these areas, enabling the construction of a high-quality benchmark. Ultimately, however, broader coverage across fields such as chemistry, physics, medicine, and mathematics will likely be necessary. Expanding PaperWrite-Bench to encompass a wider range of domains remains an important direction for future work.

Ethical Considerations

This paper focuses on an evaluation framework for writing rather than a generative writing system itself. As AI-generated writing becomes increasingly prevalent, we believe that robust evaluation infrastructure will play an important role in supporting future research and applications in this area.

One potential risk is that replications of existing research papers generated by AI systems could be distributed. To mitigate this concern, we will annotate a watermark in our benchmark, enabling clear differentiation between original and AI-generated text.

References

Samar Ansari. 2026. Compound deception in elite peer review: A failure mode taxonomy of 100 fabricated citations at neurips 2025. *arXiv preprint arXiv:2602.05930*.

Anthropic. 2025a. Claude code. Technical report, Anthropic. Accessed: 2026-03-14.

Anthropic. 2025b. System card: Claude opus 4 and claude sonnet 4. Technical report, Anthropic. Accessed: 2025-09-14.

Anthropic. 2026. Claude code agent teams. Accessed: 2026-03-30.

Anthropic. 2026. Claude sonnet 4.6. Technical report, Anthropic. Accessed: 2026-03-14.

Rahul K Arora, Jason Wei, Rebecca Soskin Hicks, Preston Bowman, Joaquin Quiñonero-Candela, Foivos Tsimpourlas, Michael Sharman, Meghan Shah, Andrea Vallone, Alex Beutel, et al. 2025. Healthbench: Evaluating large language models towards improved human health. *arXiv preprint arXiv:2505.08775*.

Akari Asai, Jacqueline He, Rulin Shao, Weijia Shi, Amanpreet Singh, Joseph Chee Chang, Kyle Lo, Luca Soldaini, Sergey Feldman, Mike D'arcy, et al. 2026. Synthesizing scientific literature with retrieval-augmented language models. *Nature*.

Siddhartha Banerjee and Prasenjit Mitra. 2015. WikiKreator: Improving Wikipedia stubs automatically. In *ACL*.

Angela Fan and Claire Gardent. 2022. Generating biographies on Wikipedia: The impact of gender bias on the retrieval-based generation of women biographies. In *ACL*.

Zhiyuan Fan, Weinong Wang, Xing W, and Debing Zhang. 2024. Sedareval: Automated evaluation using self-adaptive rubrics. In *Findings of EMNLP 2024*.

Tira Nur Fitria. 2023. Artificial intelligence (ai) technology in openai chatgpt application: A review of chatgpt in writing english essay. In *ELT Forum: Journal of English Language Teaching*, volume 12, pages 44–58.

Juraj Gottweis, Wei-Hung Weng, Alexander Daryin, Tao Tu, Anil Palepu, Petar Sirkovic, Artiom Myaskovsky, Felix Weissenberger, Keran Rong, Ryutaro Tanno, et al. 2025. Towards an ai co-scientist. *arXiv preprint arXiv:2502.18864*.

ICLR Program Chairs. 2025. Iclr 2026 response to llm-generated papers and reviews. Technical report. Accessed: 2026-03-30.

Intology. 2025. Zochi technical report. Accessed: 2025-10-17.

Fengqing Jiang, Yichen Feng, Yuetai Li, Luyao Niu, Basel Alomair, and Radha Poovendran. 2025. Badscientist: Can a research agent write convincing but unsound papers that fool llm reviewers? *arXiv preprint arXiv:2510.18003*.

Weixin Liang, Yaohui Zhang, Zhengxuan Wu, Haley Lepp, Wenlong Ji, Xuandong Zhao, Hancheng Cao, Sheng Liu, Siyu He, Zhi Huang, et al. 2025. Quantifying large language model usage in scientific papers. *Nature Human Behaviour*, pages 1–11.

Jialiang Lin, Jiaxin Song, Zhangping Zhou, Yidong Chen, and Xiaodong Shi. 2023. Automated scholarly paper review: Concepts, technologies, and challenges. *Information Fusion*, 98:101830. Available online 12 May 2023.

Peter J. Liu, Mohammad Saleh, Etienne Pot, Ben Goodrich, Ryan Sepassi, Lukasz Kaiser, and Noam Shazeer. 2018. Generating wikipedia by summarizing long sequences. In *ICLR*.

Zhihan Liu, Yubo Chai, and Jianfeng Li. 2024. Towards fully autonomous research powered by llms: Case study on simulations. *arXiv preprint arXiv:2408.15512*.

Chris Lu, Cong Lu, Robert Tjarko Lange, Jakob Foerster, Jeff Clune, and David Ha. 2024. The ai scientist: Towards fully automated open-ended scientific discovery. *arXiv preprint arXiv:2408.06292*.

Julià Minguillón, Maura Lerga, Eduard Aibar, Josep Lladós-Masllorens, and Antoni Meseguer-Artola. 2017. Semi-automatic generation of a corpus of wikipedia articles on science and technology. *Profesional de la Información*, 26(5):995–1005.

Ludovico Mitchener, Angela Yiu, Benjamin Chang, Mathieu Bourdenx, Tyler Nadolski, Arvis Sulovari, Eric C Landsness, Daniel L Barabasi, Siddharth Narayanan, Nicky Evans, et al. 2025. Kosmos: An ai scientist for autonomous discovery. *arXiv preprint arXiv:2511.02824*.

Atsuyuki Miyai, Mashiro Toyooka, Takashi Otonari, Zaiying Zhao, and Kiyoharu Aizawa. 2026. Jr. ai scientist and its risk report: Autonomous scientific exploration from a baseline paper. *TMLR*.

Graham Neubig. 2025. Post on x. https://x.com/gneubig/status/1989681438577336401. Accessed: 2026-03-16.

Alexander Novikov, Ngân Vũ, Marvin Eisenberger, Emilien Dupont, Po-Sen Huang, Adam Zsolt Wagner, Sergey Shirobokov, Borislav Kozlovskii, Francisco JR Ruiz, Abbas Mehrabian, et al. 2025. Alphaevolve: A coding agent for scientific and algorithmic discovery. *arXiv preprint arXiv:2506.13131*.

OpenAI. 2025. Codex. Accessed: 2026-03-30.

OpenAI. 2025. Gpt-5 system card. Technical report, OpenAI. Accessed: 2025-09-14.

OpenAI. 2026. Introducing gpt-5.4. Accessed: 2026-03-25.

Sakuya Ota, Qing Yu, Kent Fujiwara, Satoshi Ikehata, and Ikuro Sato. 2025. Pino: Person-interaction noise optimization for long-duration and customizable motion generation of arbitrary-sized groups. In *ICCV*.

Tung Phung, Victor-Alexandru Pădurean, José Cambronero, Sumit Gulwani, Tobias Kohn, Rupak Majumdar, Adish Singla, and Gustavo Soares. 2023. Generative ai for programming education: Benchmarking chatgpt, gpt-4, and human tutors. In *ICER*.

Yusuke Sakai, Hidetaka Kamigaito, and Taro Watanabe. 2026. Hallucitation matters: Revealing the impact of hallucinated references with 300 hallucinated papers in acl conferences. In *ACL*.

Yijia Shao, Yucheng Jiang, Theodore Kanell, Peter Xu, Omar Khattab, and Monica Lam. 2024. Assisting in writing wikipedia-like articles from scratch with large language models. In *NAACL*.

Chenglei Si, Tatsunori Hashimoto, and Diyi Yang. 2025a. The ideation-execution gap: Execution outcomes of llm-generated versus human research ideas. *arXiv preprint arXiv:2506.20803*.

Chenglei Si, Diyi Yang, and Tatsunori Hashimoto. 2025b. Can llms generate novel research ideas? a large-scale human study with 100+ nlp researchers. In *ICLR*.

Jiabin Tang, Lianghao Xia, Zhonghang Li, and Chao Huang. 2025. Ai-researcher: Autonomous scientific innovation. In *NeurIPS*.

Francisco Villaescusa-Navarro, Boris Bolliet, Pablo Villanueva-Domingo, Adrian E Bayer, Aidan Acquah, Chetana Amancharla, Almog Barzilay-Siegal, Pablo Bermejo, Camille Bilodeau, Pablo Cárdenas Ramírez, et al. 2025. The denario project: Deep knowledge ai agents for scientific discovery. *arXiv preprint arXiv:2510.26887*.

William H Walters and Esther Isabelle Wilder. 2023. Fabrication and errors in the bibliographic citations generated by chatgpt. *Scientific Reports*, 13(1):14045.

Yixuan Weng, Minjun Zhu, Guangsheng Bao, Hongbo Zhang, Jindong Wang, Yue Zhang, and Linyi Yang. 2025. Cycleresearcher: Improving automated research via automated review. In *ICLR*.

Yixuan Weng, Minjun Zhu, Qiujie Xie, Qiyao Sun, Zhen Lin, Sifan Liu, and Yue Zhang. 2026. Deepscientist: Advancing frontier-pushing scientific findings progressively. In *ICLR*.

Yutaro Yamada, Robert Tjarko Lange, Cong Lu, Shengran Hu, Chris Lu, Jakob Foerster, Jeff Clune, and David Ha. 2025. The ai scientist-v2: Workshop-level automated scientific discovery via agentic tree search. *arXiv preprint arXiv:2504.08066*.

Jingkang Yang, Shuai Liu, Hongming Guo, Yuhao Dong, Xiamengwei Zhang, Sicheng Zhang, Pengyun Wang, Zitang Zhou, Binzhu Xie, Ziyue Wang, et al. 2025. Egolife: Towards egocentric life assistant. In *CVPR*.

Kevin Yang, Dan Klein, Nanyun Peng, and Yuandong Tian. 2023. Doc: Improving long story coherence with detailed outline control. In *ACL*.

Yang Zhong, Jiangang Hao, Michael Fauss, Chen Li, and Yuan Wang. 2026. Ai-generated essays: Characteristics and implications on automated scoring and academic integrity. *Educational Measurement: Issues and Practice*, 45(1):e70013.

Minjun Zhu, Yixuan Weng, Linyi Yang, and Yue Zhang. 2025. Deepreview: Improving llm-based paper review with human-like deep thinking process. In *ACL*.

Zhenzhen Zhuang, Jiandong Chen, Hongfeng Xu, Yuwen Jiang, and Jialiang Lin. 2025. Large language models for automated scholarly paper review: A survey. *Inf. Fusion*, 124(C).

Appendix

A PaperWrite-Bench

A.1 Statistics of PaperWrite-Bench Sources

Table A presents statistics on the conferences included in PaperWrite-Bench Sources. As shown, ML and CV conferences constitute the majority, followed by multimedia and NLP conferences.

Table A: Distribution of papers by research area.

Area	Conference	# Papers	Subtotal
ML	ICLR26	7	
	NeurIPS25	6	
	ICLR25	4	21
	ICML25	2	
	AAAI25	2	
CV	CVPR25	16	
	ICCV25	3	21
	CVPR26	2	
Multimedia	ACMMM25	5	5
NLP	ACL25	3	4
	NAACL25	1	
Total		51	51

A.2 Example of Rubrics

Table B presents a subset of example rubrics for each section. The base paper is EgoLife (Yang et al., 2025).

B Detailed Prompts

B.1 Examples of research_overview.md

---

research_overview_default.md (EgoLife)

```
# EgoLife: Research Overview

## Title
**EgoLife: Towards Egocentric Life Assistant**

---

## 1. Motivation
Existing egocentric datasets and benchmarks capture
short, single-person activities and
miss week-long, multi-person social dynamics needed
for real-life assistance. The field
needs both a long-duration, multimodal, interpersonal
dataset and a method capable of
ultra-long-context reasoning.

---

## 2. Key Insight
```

```
A life assistant must fuse egocentric visual-audio
cues with long-horizon memory to answer
practical, personalized questions.
**Key idea:** Combine omni-modal clip understanding
with hierarchical retrieval over
week-long egocentric recordings.

---

## 3. Benchmark Design: EgoLifeQA
EgoLifeQA is a multiple-choice QA benchmark built on
the 266-hour EgoLife dataset (6
participants, 7 days), emphasizing ultra-long-term
reasoning. It spans five task types:
EntityLog, EventRecall, HabitInsight, RelationMap,
and TaskMaster (3,000 QAs total). Each
QA includes a "certificate length" (look-back
requirement), with 2,003 questions requiring
>2 hours of context. Evaluation is accuracy over
categories, with evidence retrieval from
week-long recordings.

---

## 4. Data Construction Pipeline
- Data sources: Meta Aria glasses (video, audio, IMU,
gaze), 15 exo GoPro cameras, and 2
  mmWave devices in an instrumented "EgoHouse."
- Collection: 6 participants cohabiting for 7 days (~8
h/day), synchronized via EgoSync;
  recordings segmented and aligned; primary language
  Chinese with English translations.
- Filtering/cleaning: Privacy protection via EgoBlur;
synchronization and denoising;
  temporal consistency checks.
- Annotation: Transcripts via Whisper + diarization +
human review; 5-min narrated clips
  (0.8x speed) -> merged by GPT-4o into dense
  visual-audio captions, then verified.
- QA creation/QC: ~100K auto-generated QAs per
participant -> manually filtered to 500
  each (3K total), with distractors, audio-needed
  flags, and certificate lengths;
  SRT-based alignment and multi-pass human
  verification.

---

## 5. Proposed Method: EgoButler
EgoButler integrates EgoGPT (clip-level omni-modal
understanding) and EgoRAG (hierarchical
retrieval for long-context QA). EgoGPT builds on
LLaVA-OneVision with an audio branch
(Whisper v3) and is instruction-tuned on EgoIT-99K
(99K egocentric QAs), plus Day-1
personalization for identity-awareness. EgoRAG
constructs multi-level memory (clip/hour/day
summaries) and retrieves top-k evidence for answer
generation.

---

## 6. Key Findings
- EgoGPT achieves state-of-the-art on egocentric
benchmarks: 75.4 (EgoSchema), 61.4
  (EgoThink), and 33.4 (EgoPlan).
- On EgoLifeQA, personalization boosts average from
33.1 to 36.0 and RelationMap from
  29.6 to 33.6.
- EgoRAG markedly improves long-context QA: >24h
certificate length from 25.0 to 35.4;
  6-24h from 26.8 to 38.9.
- Caption quality is critical: human visual-audio
captions reach 45.5 avg; audio-only
  models lag (27-28), visual-only better (31-34), best
  with audio+visual (36.0).
- Benchmark shows 2,003/3,000 QAs need >2h context,
validating the need for retrieval
  over week-long memory.

---

## 7. Contributions
- EgoLife: a 266-hour, week-long, multimodal, ego-exo
egocentric dataset with dense
```

Table B: Representative rubric evaluation points per section (importance: high). Shown for a benchmark construction paper (EgoLife (Yang et al., 2025), CVPR25) as a concrete example.

Section	Evaluation Point
Abstract	**Project goal: egocentric life assistant with wearable AI glasses**
The abstract must state the overarching objective of EgoLife: building an AI-powered egocentric life assistant that accompanies users and improves personal efficiency through wearable glasses.
Introduction	**Vision and motivation for life-oriented egocentric AI assistance**
The introduction should open with a motivating vision of an AI assistant embedded in daily life that provides personalized, long-term assistance.
Related Work	**Positioning within egocentric dataset evolution**
The section should situate EgoLife in the broader history of egocentric vision datasets, starting from early foundational collections.
Benchmark Construction	**Seven-day multimodal data collection in EgoHouse with six participants**
The section must state that the benchmark is built from a week-long recording of six volunteers living in a custom environment with multimodal sensing.
Method	**Overall EgoButler architecture with two subsystems**
The method section must explain EgoButler with its two subsystems: EgoGPT for continuous clip captioning and EgoRAG for retrieval-augmented QA.
Experiment	**Main benchmark comparison outcome**
The section should present the unified comparison protocol via EgoButler and the main benchmark comparison outcome.

```
    transcripts and visual-audio captions.
- EgoLifeQA: 3,000 long-context, multiple-choice QAs
across five life-assistant task
  categories with certificate-length metadata.
- EgoButler: a two-stage system (EgoGPT + EgoRAG) for
personalized, long-horizon
  egocentric QA; release of EgoIT-99K for instruction
  tuning.
- Comprehensive analysis identifying personalization,
caption quality, and hierarchical
  retrieval as key drivers of performance.

---

## 8. Takeaway
EgoLife and EgoButler establish a practical path
toward egocentric life assistants by
pairing week-long multimodal data with a
retrieval-augmented, omni-modal method for
ultra-long-context reasoning.
\end{verbatim}
\end{scriptsize}
\end{tcolorbox}

\begin{tcolorbox}[
    title=research\_overview\_long.md (EgoLife)
  breakable,
  width=\linewidth
]
\begin{scriptsize}
\begin{Verbatim}[
  breaklines=true,
]

# EgoLife: Research Overview

## Title
**EgoLife: Towards Egocentric Life Assistant**

---

## 1. Motivation
Egocentric AI assistants promise to augment daily life
by recalling past events, tracking
habits, and making personalized recommendations.
However, existing egocentric datasets and
```

```
benchmarks (e.g., EPIC-KITCHENS, Ego4D) primarily
cover short to medium spans, single-person
views, and narrowly scoped activities. They lack
week-long coverage, rich interpersonal
dynamics, and consistent multimodal capture -- all
crucial for building assistants that can
reason over ultra-long temporal horizons and
understand social context.

This work addresses two gaps simultaneously: (1) the
lack of a longitudinal, multiperson,
multimodal egocentric dataset, and (2) the absence of
a benchmark that evaluates
long-context, life-oriented assistance. It also
contributes a method that integrates
clip-level multimodal understanding with scalable
long-context retrieval to answer
week-scale questions. Taken together, the dataset,
benchmark, and method move toward
practical egocentric life assistants that operate over
days, handle audio-visual inputs,
and keep personalized, identity-aware memory.

---

## 2. Key Insight
The core insight is that long-horizon egocentric
assistance requires tightly coupled
components: a personalized, omni-modal
clip-understanding model and a hierarchical,
time-aware memory system that supports efficient
retrieval over week-level video.

- Key idea: Fuse continuous ego-clip captioning
(visual+audio) with hierarchical memory
  summarization and retrieval to answer long-context,
  life-oriented questions that require
  identity awareness and habit/event grounding across
  days.

---

## 3. Benchmark Design: EgoLifeQA

### 3.1 Overview
EgoLifeQA is a long-context, life-oriented QA
benchmark built on EgoLife, covering a week
```

of shared living among six participants. It evaluates
five capability axes -- object/entity
logging, event recall, habit analysis, social
relationship understanding, and task-oriented
assistance -- via multiple-choice questions that
require retrieving evidence across hours
to days. The benchmark explicitly annotates whether
audio is required and the look-back
time ("certificate length").

Goals:
- Evaluate long-term memory and retrieval over
week-scale egocentric content.
- Test personalization (identity recognition, social
interaction patterns).
- Assess multi-modal integration (audio + video).

3.2 Data Collection & Curation
- Data sources: EgoLife dataset (Meta Aria smart
glasses egocentric capture; 15 exocentric
  GoPro cameras; 2 mmWave devices). Primary language:
  Chinese; annotations translated to
  English.
- Initial QA generation: For each participant,
"visual-audio captions" (dense narrations
  post-processed by GPT-4o) were fed into GPT-4o with
  tailored prompts per question type
  to produce ~100K timestamped QA candidates.
- Human-in-the-loop curation: Annotators reviewed
candidates synchronized with video (SRT),
  retained only questions requiring >= 5 minutes of
  look-back, and prioritized longer
  dependencies and high real-world relevance.
- Finalization: 1,000 questions per participant were
pruned and refined to 500 per
  participant (3,000 total), with distractors authored
  for MCQ. Annotators labeled audio
  requirement and certificate length. Quality control
  included multi-round reviews and
  timestamp verification.
- Annotation protocol:
  - Five categories (EntityLog, EventRecall,
  HabitInsight, RelationMap, TaskMaster) with
    structured prompts.
  - Multi-choice answers with evidence timestamps.
  - Minimum evidence window: >= 5 minutes before the
  question timestamp.

3.3 Task Definition & Evaluation Protocol
- Input: Question, candidate answers (MCQ), and access
to video-derived memory (captions,
  transcripts) plus retrieval.
- Output: Single-choice answer.
- Metrics: Accuracy (per category and overall),
breakdown by certificate length (<2h,
  2-6h, 6-24h, >24h) and by audio requirement.
- Splits: 500 QAs per participant (6 participants ->
3,000 total). Evaluation reports
  per-participant and averaged.

---

4. Dataset Statistics
EgoLife (data foundation for EgoLifeQA):
- Participants: 6 volunteers cohabiting for 7 days in
a fully instrumented house
  (EgoHouse).
- Recording devices:
  - Egocentric: Meta Aria glasses (video, audio, IMU,
  gaze; synchronized).
  - Exocentric: 15 GoPro cameras for multi-view
  coverage.
  - Additional sensing: 2 mmWave devices; house 3D
  reconstruction with Aria Multi-MPS.
- Duration:
  - ~300 hours captured; 266 hours retained
  post-cleaning.
  - Approximately 8 hours/day/person; minimum 6h/day
  enforced.
- Language: Primarily Chinese; English translations
provided.
- Annotations:
  - Transcripts: Diarized, speaker-resolved;
  cross-participant overlap curated (initial
    merged ~50h reviewed, then split and refined).

  - Dense narrations: 361K phrases (avg 2.65 s),
  captured at 0.8x speed for high density.
  - Merged captions: 25K coherent segments (via
  GPT-4o-mini merging).
  - Visual-audio captions: Enriched with 1 FPS frames
  + transcripts, summarized and
    human-verified.
- EgoLifeQA:
  - 3,000 QAs total (500 per participant).
  - Certificate length distribution includes 997 QAs
  with look-back <2h and 2,003 QAs
    >2h (many beyond 24h).
  - Audio requirement is labeled per QA.

Comparisons:
- Compared to EgoSchema, HourVideo, etc.,
EgoLife/EgoLifeQA uniquely target week-long,
  multiperson daily life with rich ego-exo, multimodal
  capture and social dynamics.

---

5. Proposed Method: EgoButler

5.1 Overview
EgoButler integrates:
- EgoGPT (System-I): A 7B vision-audio-language model
for clip-level understanding and
  captioning, adapted to egocentric domain and
  personalized identity cues.
- EgoRAG (System-II): A hierarchical, time-aware
retrieval-augmented generation system
  that builds a multi-level memory bank
  (clip/hour/day) and retrieves evidence for
  ultra-long-context QA.

Pipeline:
1) Continuous 30 s clip captioning (visual + audio) ->
memory bank.
2) Hierarchical retrieval over day/hour windows ->
top-k clip evidences.
3) Answer generation with retrieved context.

5.2 EgoGPT (Clip-Level Omni-Modal Understanding)
- Base: LLaVA-OneVision (Qwen2-based, 7B).
- Audio branch: Added following Ola-style design;
Whisper Large v3 encodes audio; trained
  audio projection on LibriSpeech; finetuned jointly.
- Training data: EgoIT-99K (Table: 9 egocentric
datasets; 43.16 h; 1,529 videos incl.
  686 with audio; 99.48K QAs across
  VC/AVC/MCQ/MRC/IQA).
- Personalization: Additional finetuning on EgoLife
Day-1 to calibrate identity cues and
  environment context.
- Functions:
  - Dense visual-audio captioning for 30 s clips (1
  FPS sampling in experiments for
    captioners).
  - Answering questions with retrieved evidence and
  identity-aware references.

5.3 EgoRAG (Long-Context Retrieval-Augmented
Generation)
- Memory bank M = {(c_i, d_i, t_i)} where:
  - c_i: clip features; d_i: textual descriptions
  (EgoGPT captions); t_i: hierarchical
    summaries (hourly/day).
- Retrieval:
  - Coarse-to-fine: first retrieve by day -> hour
  summaries, then fine-grained clip
    selection.
  - Relevance score: s_i = Similarity(q, c_i) + lambda
  * Similarity(q, d_i). In main
    experiments lambda = 0 (text-only retrieval).
  - Select top-k clips (k typically small; e.g., 3)
  for evidence.
- Response:
  - r = LLM(q, R), where LLM is EgoGPT or a stronger
  generator (e.g., GPT-4o)
    conditioned on retrieved evidence R.

---

6. Experimental Results

```
### 6.1 Setup
- Baselines (egocentric VLM benchmarks): GPT-4v/4o,
Gemini-1.5-Pro, LLaVA-Next-Video,
  LongVA, IXC-2.5, InternVideo2, Qwen2-VL, Oryx,
  LLaVA-OV, LLaVA-Videos.
- Datasets: EgoSchema, EgoPlan-Bench, EgoThink;
EgoLifeQA (Jake's 500-QA split in this
  version).
- Inputs: 32 frames for standard benchmarks; 1 FPS for
caption-based memory in EgoLifeQA.
- EgoRAG: text-similarity retrieval (lambda=0), top-3
30 s clips; re-query with
  GPT-4o-mini; final answer generation by GPT-4o for
  fairness across captioners.

### 6.2 Key Findings
- EgoGPT on benchmarks (32 frames):
  - EgoGPT (EgoIT-99K): EgoSchema 73.2, EgoPlan 32.4,
  EgoThink 61.7.
  - With personalization (+D1): EgoSchema 75.4 (+2.2),
  EgoPlan 33.4 (+1.0), EgoThink
    61.4.
- EgoLifeQA (average accuracy):
  - Gemini-1.5-Pro: 36.9; GPT-4o: 36.2; LLaVA-OV:
  30.8.
  - EgoGPT (non-personalized): 33.1; EgoGPT (+D1):
  36.0 (+2.9).
  - Category-wise (EgoGPT +D1): EntityLog 39.2,
  EventRecall 36.5, HabitInsight 31.1,
    RelationMap 33.6, TaskMaster 39.7.
- EgoRAG effectiveness by certificate length:
  - EgoGPT vs. EgoGPT+EgoRAG:
    - <2h: 28.2 -> 27.2;
    - 2-6h: 29.1 -> 35.7;
    - 6-24h: 26.8 -> 38.9;
    - >24h: 25.0 -> 35.4.
  - Large gains for >= 2h look-back validate
  long-context retrieval benefits.
- Caption quality matters (avg accuracy):
  - Narration-only: 31.5; Transcript-only: 29.6;
  Visual-audio captions (human-verified):
    45.5.
  - EgoGPT memory banks: audio-only 27.2-28.1;
  visual-only 31.2-33.6; visual+audio
    33.1-36.0.

---

## 7. Analysis & Insights
- Personalization helps: Day-1 finetuning improves
entity and relation questions,
  indicating identity cues and environment priors are
  beneficial -- but can lead to
  overfitting (e.g., misidentifying later people
  wearing similar colors).
- Audio is useful but insufficient alone: audio-only
captioning underperforms; best
  results require joint visual+audio.
- Long-context retrieval is crucial: naive
segmentation causes hallucinations; hierarchical
  memory and retrieval yield pronounced gains
  especially for >6h queries.
- Error modes:
  - Speech/emotion understanding is limited by
  ASR-centric audio training (e.g.,
    laughter/emotion recognition).
  - Single-pass retrieval lacks iterative reasoning;
  failures cascade when relevant clips
    aren't surfaced.
  - Social interaction nuance (e.g., subtle nonverbal
  cues) remains challenging.

---

## 8. Contributions
- EgoLife dataset: 266 h retained from ~300 h of
week-long, multiperson egocentric
  recordings with synchronized ego-exo capture (15 exo
  cameras, 2 mmWave), rich
  transcripts and dense visual-audio captions.
- EgoLifeQA benchmark: 3,000 long-context MCQs across
five categories, with certificate
  lengths up to >24h and audio-requirement labels,
  targeting practical life assistance.
```

```
  - EgoButler system:
  - EgoGPT: a 7B vision-audio-language model tuned on
  EgoIT-99K and personalized on
    EgoLife Day-1, achieving strong egocentric
    benchmark performance.
  - EgoRAG: hierarchical, time-aware memory and
  retrieval for ultra-long-context QA,
    significantly improving accuracy for long
    look-back queries.

---

## 9. Limitations & Future Work
- Dataset scope: single week, six participants,
primarily Chinese language; future
  expansions to more participants, diverse locales,
  and languages are planned.
- Audio understanding: current training biases toward
ASR; future models should integrate
  paralinguistic cues (emotion, prosody).
- Personalization stability: day-1 finetuning can
overfit identity cues; future work on
  robust identity modeling and lifelong adaptation is
  needed.
- Retrieval reasoning: EgoRAG is single-pass without
multi-hop refinement; integrating
  step-by-step, iterative retrieval and
  self-correction could improve robustness.
- Privacy and deployment: despite anonymization tools
(EgoBlur), real-world deployment
  requires stronger privacy-preserving methods and
  secure on-device processing.

---

## 10. Takeaway
EgoLife establishes the first week-scale, multiperson,
multimodal egocentric dataset and a
long-context QA benchmark targeting life assistance.
Coupled with EgoButler -- integrating
personalized clip-level multimodal understanding
(EgoGPT) and hierarchical long-context
retrieval (EgoRAG) -- the project advances the
frontier of egocentric AI toward practical,
personalized assistants that reason across days, track
habits, and understand social
dynamics.
```

B.2 Prompts for Creating Overviews

Prompt for Generating Research Overview (Default / Method Paper)

```
[System] You are an expert AI researcher. Your task is
to read a research paper and
generate a structured research overview in Markdown
format. The overview should be
comprehensive yet concise, capturing the key aspects
of the paper. It will be used as
input for an AI system that writes LaTeX papers, so
accuracy and clarity are critical.
Output ONLY the Markdown content, no preamble or
explanation.

[User] Read the following research paper and generate
a concise research overview in
Markdown format. Keep it SHORT and focused. Each
section should be 2-4 sentences at
most. Total length should be around 1500-2500
characters.

Follow this structure:
# [Paper Acronym/Name]: Research Overview
## Title
## 1. Motivation          (1-2 sentences)
## 2. Key Insight         (1-2 sentences, bold "Key
idea:" one-liner)
## 3. Proposed Method     (2-4 sentences)
## 4. Experimental Results (3-5 bullet points with
numbers)
```

```
## 5. Contributions        (3-4 bullet points)
## 6. Takeaway             (one sentence)
\end{verbatim}
\end{scriptsize}
\end{tcolorbox}

\begin{tcolorbox}[title=Prompt for Generating
Research Overview (Long / Method Paper), breakable]
\begin{scriptsize}
\begin{verbatim}
[System] (same as above)

[User] Read the following research paper and generate
a detailed and comprehensive
research overview in Markdown format. Be thorough:
include technical details, formulas,
specific numbers, and nuanced analysis. Total length
should be around 4000-8000
characters.

Follow this structure:
# [Paper Acronym/Name]: Research Overview
## Title
## 1. Motivation          (2-3 paragraphs)
## 2. Key Insight         (bold "Key idea:" summary)
## 3. Proposed Method
    ### 3.1 Overview
    ### 3.2 [Component Name]  (add subsections as
    needed)
## 4. [Additional Section as needed]
## 5. Experimental Results
    ### 5.1 Setup
    ### 5.2 Key Findings
## 6. Analysis & Insights
## 7. Contributions
## 8. Limitations & Future Work
## 9. Takeaway
\end{verbatim}
\end{scriptsize}
\end{tcolorbox}

\begin{tcolorbox}[title=Prompt for Generating Research
Overview (Default / Benchmark Paper), breakable]
\begin{scriptsize}
\begin{verbatim}
[System] (same as above)

[User] Read the following research paper about a
benchmark/dataset and generate a
concise research overview in Markdown format. Keep it
SHORT and focused. Each section
should be 2-4 sentences at most. Total length should
be around 1500-2500 characters.

Follow this structure:
# [Benchmark Name]: Research Overview
## Title
## 1. Motivation
## 2. Key Insight
## 3. Benchmark Design    (tasks, data sources,
scale, evaluation protocol)
## 4. Data Construction Pipeline
    (data sources; collection process;
    filtering/cleaning; annotation protocol;
    number of annotators and qualifications;
    inter-annotator agreement;
    quality control measures;
    automated/human-in-the-loop curation steps)
## 5. Key Findings        (3-5 bullet points with
numbers)
## 6. Contributions
## 7. Takeaway
```

Prompt for Generating Research Overview (Default / Both Paper)

```
[System] (same as above)

[User] Read the following research paper that
contributes BOTH a new method AND a new
benchmark/dataset. Generate a concise research
overview in Markdown format. Keep it
```

```
SHORT and focused. Each section should be 2-4
sentences at most. Total length should be
around 1500-2500 characters.

Follow this structure:
# [Paper Acronym/Name]: Research Overview
## Title
## 1. Motivation
## 2. Key Insight
## 3. Benchmark Design    (tasks, data sources,
scale, evaluation protocol)
## 4. Data Construction Pipeline
    (data sources; collection process;
    filtering/cleaning; annotation protocol;
    quality control measures)
## 5. Proposed Method       (2-4 sentences, key
components)
## 6. Key Findings          (3-5 bullet points
covering both method and benchmark)
## 7. Contributions
## 8. Takeaway
\end{verbatim}
\end{scriptsize}
\end{tcolorbox}

\begin{tcolorbox}[title=Prompt for Generating
Research Overview (Long / Both Paper), breakable]
\begin{scriptsize}
\begin{verbatim}
[System] (same as above)

[User] Read the following research paper that
contributes BOTH a new method AND a new
benchmark/dataset. Generate a detailed and
comprehensive research overview in Markdown
format. Be thorough: include technical details,
formulas, dataset statistics, specific
numbers, and nuanced analysis. Total length should be
around 4000-8000 characters.

Follow this structure:
# [Paper Acronym/Name]: Research Overview
## Title
## 1. Motivation                (2-3 paragraphs)
## 2. Key Insight
## 3. Benchmark Design
    ### 3.1 Overview
    ### 3.2 Data Collection & Curation
        (data sources; collection process;
        filtering/cleaning; annotation protocol;
        annotator count and qualifications;
        inter-annotator agreement;
        quality control; automated/human-in-the-loop
        curation)
    ### 3.3 Task Definition & Evaluation Protocol
## 4. Dataset Statistics
## 5. Proposed Method
    ### 5.1 Overview
    ### 5.2 [Component Name]  (add subsections as
    needed)
## 6. Experimental Results
    ### 6.1 Setup
    ### 6.2 Key Findings
## 7. Analysis & Insights
## 8. Contributions
## 9. Limitations & Future Work
## 10. Takeaway
\end{verbatim}
\end{scriptsize}
\end{tcolorbox}

\begin{tcolorbox}[title=Prompt for Generating
Research Overview (Long / Benchmark Paper), breakable]
\begin{scriptsize}
\begin{verbatim}
[System] (same as above)

[User] Read the following research paper about a
benchmark/dataset and generate a
detailed and comprehensive research overview in
Markdown format. Be thorough: include
technical details, dataset statistics, specific
numbers, and nuanced analysis. Total
length should be around 4000-8000 characters.
```

```
Follow this structure:
# [Benchmark Name]: Research Overview
## Title
## 1. Motivation          (2-3 paragraphs)
## 2. Key Insight
## 3. Benchmark Design
    ### 3.1 Overview
    ### 3.2 Data Collection & Curation
        (data sources and selection criteria;
        collection process; filtering/cleaning;
         annotation protocol; annotator count and
         qualifications; inter-annotator
         agreement; quality control;
         automated/human-in-the-loop curation)
    ### 3.3 Task Definition & Evaluation Protocol
    ### 3.4 [Additional Design Aspect]
## 4. Dataset Statistics
## 5. Baseline Evaluation
    ### 5.1 Evaluated Methods
    ### 5.2 Key Findings
## 6. Analysis & Insights
## 7. Contributions
## 8. Limitations & Future Work
## 9. Takeaway
```

B.3   Prompts for Creating Rubrics

> **Prompt for Extracting Evaluation Points (Rubric) from Each Section**
>
> ```
> You are an expert paper reviewer. Given a section of
> an accepted top-tier conference
> paper, extract the key elements that are essential for
> reproducing this section's content.
>
> Each element should represent a distinct piece of
> information, claim, technical detail,
> or structural component that a generated version of
> this section MUST include to be
> considered faithful.
>
> Guidelines:
> - Extract 5-15 elements per section depending on
> length and complexity.
> - For Introduction: problem motivation, research gap,
> proposed approach overview, key
>   contributions, paper structure.
> - For Method: each major component/module, key
> equations/formulations, design choices
>   and justifications, training procedures.
> - For Experiment: datasets, baselines, evaluation
> metrics, main results, ablation
>   studies, key findings.
> - For Related Work: main research areas covered, key
> distinctions from prior work.
> - For Abstract: core problem, approach, key results.
> - importance should be "high" for elements without
> which the section would be
>   fundamentally incomplete, "medium" for important but
>   not critical details, "low" for
>   nice-to-have elements.
> - evidence should be a brief quote or reference to the
> specific part of the GT text.
>
> Respond in JSON format matching the schema exactly.
> Write element and description in
> English. Write evidence in the original language of
> the paper (usually English).
> ```

B.4   Writing Prompts

For the writing prompt, we assumed the writing process would be used as part of a practical AI Scientist system, and therefore referred the prompt from Jr. AI Scientist (Miyai et al., 2026).

> **Writeup Agent Prompt**
>
> ```
> Your goal is to write up the following idea:
>
> ```markdown
> {research_overview_text}
> ```
> Note that idea_text represents a preliminary
> hypothesis and may not necessarily align
> with the experiments that were eventually performed.
>
> First, make sure to refer to the experiment data
> contained in table/ and figure/ folders.
>
> We have VLM-based table descriptions:
> ```
> {table_descriptions}
> ```
>
> We also have VLM-based figure descriptions:
> ```
> {plot_descriptions}
> ```
>
> To better understand the methodology and experiments,
> please also refer to:
> - code/ as the proposed method's code implementation
>
> Please read the current template.tex file and update
> it to produce a complete, coherent,
> and scientifically accurate paper.
> This must be an acceptable complete LaTeX writeup,
> suitable for a {num_page}-page
> {column_type} paper.
> Make sure to use the citations from the references.bib
> file and report results accurately
> based on the experimental data provided.
> IMPORTANT: references.bib can be very large. Do NOT
> read the entire file at once. Instead,
> use Grep to search for relevant citation keys or
> authors, then Read only the specific
> portions you need (using offset and limit parameters).
> Start by reading template.tex to understand the
> current state, then edit it to incorporate
> all the information above into a complete paper.
>
> Please note: For the bibliography, do not use the
> \begin{filecontents}{references.bib}
> environment. Instead, all citations should refer to an
> external file named references.bib.
> \end{verbatim}
> \end{scriptsize}
> \end{tcolorbox}
>
>
> \begin{tcolorbox}[title=Reflection Prompt (LaTeX
> Error Fixing), breakable]
> \begin{scriptsize}
> \begin{verbatim}
> Now let's reflect and identify any issues (including
> but not limited to).
> Your task is to read the current template.tex file and
> improve it based on the feedback
> provided below.
> 1) Are there any LaTeX syntax errors or style
> violations we can fix? Refer to the chktex
> output below.
>
> chktex results:
> ```
> {check_output}
> ```
>
> 2) Are there any LaTeX compilation errors? Refer to
> the tectonic compile output below.
>
> tectonic compile output:
> ```
> {compile_output}
> ```
>
> If there are errors reported above, please fix them
> directly.
> Read template.tex and edit it to address these issues.
> ```

```
Focus especially on fixing compilation errors so that
the paper compiles successfully.

If no errors are reported, no changes are necessary.
\end{verbatim}
\end{scriptsize}
\end{tcolorbox}

\begin{tcolorbox}[title=Page Limit Adjustment Prompt,
breakable]
\begin{scriptsize}
\begin{verbatim}
The main text (before 'References') is currently
{main_pages} pages. The target is
{page_limit} pages.

The paper is {status}. Please {action} to reach the
target.
Do NOT move content to or create an Appendix. Keep
everything in the main text.
Do not add or remove more than 1000 characters in this
revision. Do not use
\begin{filecontents}{references.bib}.
```

B.5 Evaluation Prompts

Rubric Evaluation: Section-Level Scoring

```
[System Message]
You are an expert paper reviewer. You are given:
1. A list of key elements (rubric) that should appear
in a specific section of
   a paper.
2. The predicted section content to evaluate.
3. (Optional) Figure/Table context showing which
visual assets are present or
   missing.

For each element, score how well the predicted section
covers it on a 1-5 scale:
5: Fully and accurately described. The element is
present with correct details.
4: Mostly described. The core idea is present but some
details are missing or
   slightly imprecise.
3: Partially described. The element is mentioned but
with significant gaps or
   vagueness.
2: Barely mentioned. Only a superficial or indirect
reference exists.
1: Not described at all. The element is completely
absent from the predicted
   section.

Respond in JSON format. For each element, provide:
- "element": the element name (copy exactly from
input)
- "score": 1-5
- "reasoning": brief explanation

[User Message]
**Section: {section_name}**

**Rubric (key elements to check):**
- {element_name} ({importance}): {description}
- ...

**Predicted section content:**
{pred_content}

### Figure/Table Context for this Section
The following analysis describes the presence or
absence of visual assets
in this section compared to the Ground Truth:
{figure_table_context}

**Instructions:**
1. Evaluate each rubric element based on the text
content.
2. CRITICAL: If a rubric element requires or refers to
data/visuals, and the
```

```
corresponding Figure/Table is reported as MISSING
or has low match score in
the context above, you MUST penalize the score for
that element.
Evaluate each element on a 1-5 scale.
```

Hallucination Evaluation: Stage 1 — Claim Extraction & Classification (LLM)

```
[System Message]
You are an expert paper reviewer detecting factual
errors in a predicted paper
section.

You are given:
1. The predicted section content.
2. The ground truth (GT) full paper content for
reference.

Your task is to identify all concrete, verifiable
claims in the predicted section
(e.g., specific numbers, method descriptions,
experimental setups, results)
and classify each into one of three categories:

- supported: The claim is directly stated in or
logically derivable from the GT
  paper.
- neutral: The claim is NOT in the GT, but is a
reasonable general statement,
  common knowledge, or supplementary detail that does
  not contradict the GT.
  This is NOT an error.
- contradictory: The claim directly contradicts
specific information in the GT
  paper. This is a factual error / hallucination.

For contradictory claims, also assign severity:
- major: Incorrect numbers, fabricated results, wrong
method descriptions,
  misattributed findings -- errors that would mislead
  a reader.
- minor: Overly strong generalizations, imprecise
wording that slightly distorts
  meaning, minor numerical rounding issues.

IMPORTANT:
- Do NOT classify claims as contradictory simply
because they are absent from the
  GT. Absence != contradiction.
- Focus on claims that can be verified against the GT.
Skip purely stylistic or
  structural observations.
- Be thorough: extract ALL verifiable claims, not just
a few.

Respond in JSON with a list of claims. Each claim has:
- "claim": the specific statement from Pred
- "classification": "supported" | "neutral" |
"contradictory"
- "evidence": brief explanation
- "severity": "major" | "minor" (only for
contradictory, null otherwise)

[User Message]
**Section being evaluated: {section_name}**

**Predicted section content:**
{pred_content}

**Ground Truth full paper (for reference):**
{gt_full_content}

Extract and classify all verifiable claims from the
predicted section.
\end{verbatim}
\end{scriptsize}
\end{tcolorbox}

\begin{tcolorbox}[title=Hallucination Evaluation:
Stage 2 --- Agent-Based Verification, breakable]
```

```
\begin{scriptsize}
\begin{verbatim}
[System Message]
You are a rigorous fact-checker performing a
second-pass verification.

A previous reviewer flagged the following claim as
contradictory (factual error /
hallucination) in a predicted paper section. Your job
is to carefully re-examine
whether this is truly a contradiction with the Ground
Truth paper, or a false
positive.

Classify the claim into one of:
- contradictory: Confirmed. The claim genuinely
contradicts specific information
   in the GT paper.
- neutral: False positive. The claim is absent from
the GT but does NOT
   contradict it. Absence is not contradiction.
- supported: False positive. The claim is actually
supported by the GT paper.

For confirmed contradictory claims, assign severity:
- major: Incorrect numbers, fabricated results, wrong
method descriptions.
- minor: Overly strong generalizations, imprecise
wording.

Respond in JSON:
- "classification": "supported" | "neutral" |
"contradictory"
- "severity": "major" | "minor" for contradictory,
"none" for supported/neutral
- "evidence": brief explanation of why you changed or
kept the classification

[User Message]
The following {N} claims were flagged as contradictory
by a previous reviewer.
Re-examine EACH claim and classify it independently.

### Claim 1
- Claim: {claim_text}
- Original evidence: {original_evidence}
- Original severity: {original_severity}
...

Your current working directory contains the Ground
Truth paper resources:
- The GT paper's LaTeX source (main.tex, gt_main.tex,
or similar .tex files)
- code/ directory with the original codebase (if
exists)
- figures/ directory with figure images
- tables/ directory with table data (.tex files)

Please read the relevant GT files to verify each
claim. For claims about the
implementation details or methods, check the code/
directory. For other claims,
you can check main.tex/gt_main.tex and tables/.
Return a JSON with a "results" array containing one
entry per claim, in the same
order.

Note: The agent operates in READ-ONLY mode with access
to Read, Glob, and Grep
tools only.
```

B.6 Agent.md

AGENT.md for Method Paper

```
You are an ambitious AI researcher who is looking to
publish a paper that will
contribute significantly to the field.

This paper is a method paper. The main contribution is
a novel technique, algorithm,
```

model, or framework that addresses a specific research
problem.

Ensure that the paper is scientifically accurate,
objective, and truthful. Accurately
report the experimental results, even if they are
negative or inconclusive.

You are planning to submit to a top-tier ML
conference, which has guidelines:

- In general, try to use the available space and
include all relevant information.
- Do not change the overall style which is mandated by
the conference. Keep to the
  current method of including the references.bib file.
- Do not remove the \graphicspath directive or no
figures will be found.
- Do not add `Acknowledgements` section to the paper.
- Use a single backslash (\) for LaTeX commands
instead of a double backslash (\\).

Here are some tips for each section of the paper:

- **Title**:
  - Title should be catchy and informative. It should
  give a good idea of what the
    paper is about.
  - Try to keep it under 2 lines.

- **Abstract**:
  - TL;DR of the paper.
  - What are we trying to do and why is it relevant?
  - Briefly describe the proposed method and highlight
  key empirical findings.
  - Make sure the abstract reads smoothly and is
  well-motivated. This should be one
    continuous paragraph.
  - Do not include formatted mathematical formulas or
  equations.

- **Introduction**:
  - Provide context to the study and explain its
  relevance.
  - Highlight how the approach effectively addresses
  the research question or
    problem. Also, provide an intuitive explanation of
    why this method works well.
  - Summarize your contributions, highlighting
  pertinent findings, insights, or
    proposed methods.
  - If there is a figure of the method overview, place
  it on page 2 of the paper.

- **Related Work**:
  - Discuss alternative attempts in literature at
  trying to address the same or
    similar problems.
  - Compare and contrast their approach with yours,
  noting key differences or
    similarities.
  - Ensure proper citations are provided.
  - Each subsection should help clarify what gap
  remains in prior work and how this
    work addresses it.

- **Method**:
  - Clearly detail what you propose to do and why.
  - If your study aims to address certain hypotheses,
  describe them and how your
    method is constructed to test them.
  - Include technical details sufficient for
  reproduction.
  - Do not include results in the Method section.

- **Experiments**:
  - Explain how you tested your method or hypothesis.
  - Describe necessary details such as data,
  environment, and baselines, but omit
    hardware details unless explicitly mentioned.
  - Present the results truthfully according to the
  data you have. If outcomes are
    not as expected, discuss it transparently.
  - Include comparisons to baselines if available, and
  only include analyses
```

supported by genuine data.
    - Try to include all relevant plots and tables.
    Consider combining multiple plots
      into one figure if they are related.
    - In tables, please bold the best result among the
    compared methods. There is no
      need to bold the proposed method if it is not the
      best.

  - **Analysis**:
    - Provide deeper insights into why the proposed
    method works or fails in certain
      scenarios.
    - Include ablation studies to demonstrate the
    contribution of each component.
    - Analyze the results from multiple perspectives
    (e.g., per-class performance,
      computational cost, results with other backbones).
    - Use visualizations (e.g., t-SNE, attention maps,
    feature distributions) to
      support the analysis when appropriate.
    - Ensure all claims are supported by data from the
    experiments.

  - **Conclusion**:
    - Summarize the entire paper, including key
    strengths or findings.
    - Highlight how the results address the research
    problem.

Ensure you are always writing good compilable LaTeX
code. Common mistakes that should
be fixed include:

- LaTeX syntax errors (unenclosed math, unmatched
braces, etc.).
- Duplicate figure labels or references.
- Unescaped special characters: & % $ # _ {{ }} ~ ^ \\
- Proper table/figure closure.
- Do not hallucinate new citations or any results not
in the logs.

Ensure proper citation usage:

- Always include references within
\\begin{{filecontents}}{{references.bib}} ...
  \\end{{filecontents}}, even if they haven't changed
  from the previous round.
- Before citing any paper, ALWAYS read the
references.bib file first to find the
  correct citation key. Do NOT create new fictional
  bibtex entries.
- Do not make any changes to reference.bib
- Verify all citation keys match exactly with those in
references.bib before using
  them in the text.
- Each section, especially Related Work, should have
multiple citations.

## Notes

- The paper should make clear what problem is being
solved and why the proposed
  method is effective.
- Do not include formatted mathematical formulas or
equations in the Abstract.
  However, including key numerical results (e.g., "an
  accuracy of 92.5%") and
  mentioning mathematical concepts by name is
  perfectly acceptable.
- Do not include Limitation sections and Future Work
sections.
- Use `\%` to display a literal percent sign, as a
standard `%` will be treated as a
  comment.

## AGENT.md for Benchmark / Evaluation Paper

You are an ambitious AI researcher who is looking to
publish a paper that will
contribute significantly to the field.

This paper is a benchmark / evaluation framework /
evaluation protocol paper, not a
method paper. The main contribution is the design,
construction, validation, and
analysis of a benchmark, dataset, task formulation,
metric, or evaluation protocol
that enables more reliable and informative assessment
of machine learning systems.

Ensure that the paper is scientifically accurate,
objective, and truthful. Accurately
report the experimental results, even if they are
negative, mixed, or inconclusive.
Do not overclaim that the benchmark solves the entire
problem; instead, clearly state
what it measures, what it does not measure, and what
new insights it enables.

You are planning to submit to a top-tier ML
conference, which has guidelines:

- In general, try to use the available space and
include all relevant information.
- Do not change the overall style which is mandated by
the conference. Keep to the
  current method of including the references.bib file.
- Do not remove the \graphicspath directive or no
figures will be found.
- Do not add `Acknowledgements` section to the paper.
- Use a single backslash (\) for LaTeX commands
instead of a double backslash (\\).

The paper should be written as a benchmark /
evaluation paper. Do not force the
structure or claims of a method paper onto it. In
particular:

- Do not frame the benchmark itself as if it were a
proposed learning algorithm.
- Do not include a "Method" section unless the
benchmark genuinely includes a
  technical construction procedure that needs its own
  section. Prefer section names
  such as "Benchmark Design", "Task Construction",
  "Data Collection", "Evaluation
  Protocol", "Metrics", or "Experimental Setup" where
  appropriate.
- Do not claim superiority in the style of a method
paper. The contribution is the
  quality, usefulness, rigor, and insightfulness of
  the evaluation framework.
- The central question is whether the benchmark or
evaluation protocol is
  well-motivated, well-constructed, diverse, reliable,
  challenging, reproducible, and
  informative.

Here are some tips for each section of the paper:

- **Title**:
  - Title should be catchy and informative. It should
  make clear that the paper
    introduces, studies, or validates a benchmark,
    evaluation framework, dataset,
    task, or protocol.
  - Avoid method-style titles that imply a new model
  or algorithm unless that is
    truly part of the contribution.
  - Try to keep it under 2 lines.

- **Abstract**:
  - TL;DR of the paper.
  - State what evaluation gap, benchmark deficiency,
  or measurement problem the paper
    addresses, and why it matters.
  - Briefly describe what is introduced (e.g., a
  benchmark, protocol, metric,
    dataset, or suite of tasks), how it is
    constructed, and what key empirical
    findings it reveals about current systems.
  - Emphasize what new insight or more reliable
  evaluation this benchmark enables.
  - This should be one continuous paragraph.

- Do not include formatted mathematical formulas or equations.

- **Introduction**:
  - Provide context for the evaluation problem and explain why existing benchmarks,
    datasets, metrics, or protocols are insufficient.
  - Clearly motivate the need for the new benchmark or evaluation setup.
  - Explain what the benchmark is intended to measure, and why that measurement is
    important to the field.
  - Summarize the design principles behind the benchmark: coverage, realism,
    difficulty, diversity, fairness, contamination resistance, reproducibility,
    diagnostic value, or other relevant goals.
  - Summarize the main empirical findings obtained by evaluating representative
    systems on the benchmark.
  - Clearly state the contributions. Typical contributions may include:
    - a new benchmark or evaluation framework,
    - a new task or taxonomy,
    - a new protocol or metric,
    - a careful validation of the benchmark properties,
    - empirical findings about the strengths and weaknesses of current systems.
  - If there is a benchmark overview figure, place it on page 2 of the paper.

- **Related Work**:
  - Discuss prior benchmarks, datasets, tasks, evaluation protocols, and metrics
    relevant to the same capability or problem setting.
  - Compare and contrast your benchmark with prior work in terms of scope, realism,
    diversity, difficulty, annotation procedure, contamination controls, metric
    choice, or diagnostic granularity.
  - Situate the paper among both benchmark papers and method papers that are commonly
    evaluated on similar settings when appropriate.
  - Ensure proper citations are provided.
  - Each subsection should help clarify what gap remains in prior evaluation practice
    and how this work addresses it.

- **Benchmark Design / Task Construction / Evaluation Protocol**:
  - Clearly describe what is being introduced.
  - Explain the target capability, task definition, input-output format, evaluation
    setting, and any assumptions.
  - If the paper includes dataset construction, describe the data sources, filtering,
    curation, annotation, and quality control pipeline.
  - If the paper includes a taxonomy, explain the taxonomy and why it is useful.
  - If the paper includes a metric or protocol, define it precisely and justify why
    it better measures the target capability.
  - Clearly explain the design rationale behind each major decision.
  - Describe known exclusions, scope boundaries, and intended use cases.
  - Avoid presenting this as a model contribution.

- **Benchmark Validation / Quality Checks**:
  - Include a dedicated section validating that the benchmark is meaningful and
    technically sound.
  - Depending on the paper, this may include:
    - annotation quality or inter-annotator agreement,
    - task validity,
    - distributional diversity,
    - difficulty calibration,
    - adversarial filtering or decontamination,
    - leakage checks,
    - robustness of the metric,
    - agreement with expert judgment,

    - sanity checks showing the benchmark is neither trivial nor broken.
  - Clearly report the evidence supporting the reliability of the benchmark.
  - If there are weaknesses, ambiguities, or known artifacts, state them explicitly.

- **Experiments / Benchmark Results**:
  - Explain how representative systems are evaluated on the benchmark.
  - Include strong and relevant baselines, representative model families, and, when
    appropriate, simple heuristic baselines.
  - Describe the evaluation setup in sufficient detail for reproducibility.
  - Present the benchmark results truthfully according to the data.
  - Focus on what the benchmark reveals about current systems, not on declaring a
    winning method unless that is genuinely supported and central.
  - Highlight major patterns such as overall difficulty, capability gaps, sensitivity
    to subcategories, brittleness, ranking instability, or disagreement with prior
    benchmarks.
  - If comparing to existing benchmarks, explain what additional insight your
    benchmark provides.
  - In tables, please bold the best result among the compared systems when
    appropriate. There is no need to imply that the best score means the benchmark is
    solved.

- **Analysis**:
  - Provide deeper analysis showing that the benchmark is diagnostic and insightful.
  - Analyze system behavior across slices, subcategories, difficulty levels,
    languages, domains, perturbations, or other relevant dimensions.
  - Include analyses that help readers understand what success and failure on the
    benchmark actually mean.
  - If useful, include human performance, expert performance, agreement analyses,
    calibration analyses, or metric sensitivity analyses.
  - Show whether the benchmark distinguishes systems in informative ways.
  - If there are surprising findings, discuss them carefully and ground them in the
    evidence.
  - Ensure all claims are supported by data.

- **Discussion**:
  - Discuss what the benchmark contributes to the field and how it should be used.
  - Clarify what conclusions can and cannot be drawn from it.
  - Explicitly discuss limitations such as coverage gaps, annotation subjectivity,
    potential contamination risks, remaining artifacts, or ecological validity
    constraints.
  - Avoid inflated claims. A strong benchmark paper is valuable even if it has
    limitations, as long as they are clearly stated.

- **Conclusion**:
  - Summarize the benchmark or evaluation contribution and the main empirical
    findings.
  - Emphasize the new measurement capability or insight enabled by the work.
  - Avoid method-paper language suggesting that a new algorithm was introduced if it
    was not.

Ensure you are always writing good compilable LaTeX code. Common mistakes that should
be fixed include:

- LaTeX syntax errors (unenclosed math, unmatched braces, etc.).
- Duplicate figure labels or references.
- Unescaped special characters: & % $ # _ {{ }} ~ ^ \\
- Proper table/figure closure.
- Do not hallucinate new citations or any results not in the logs.

Ensure proper citation usage:

- Always include references within \\begin{{filecontents}}{{references.bib}} ... \\end{{filecontents}}, even if they haven't changed from the previous round.
- Before citing any paper, ALWAYS read the references.bib file first to find the correct citation key. Do NOT create new fictional bibtex entries.
- Do not make any changes to reference.bib
- Verify all citation keys match exactly with those in references.bib before using them in the text.
- Each section, especially Related Work, should have multiple citations.

## Notes

- The paper should make clear what evaluation problem is being solved.
- The benchmark must be justified, not merely presented.
- The paper should include evidence that the benchmark is valid, informative, and reproducible.
- The paper should clearly separate benchmark construction from benchmark findings.
- Do not include results in sections whose purpose is only to define the benchmark, unless a brief preview is essential for flow.
- Do not include Limitation sections and Future Work sections unless the venue explicitly requires them. However, benchmark limitations should still be discussed naturally in the Discussion or other appropriate sections.
- Use \% to display a literal percent sign, as a standard % will be treated as a comment.
- Do not overclaim that high benchmark performance implies general intelligence, real-world safety, or broad robustness unless this is directly supported.
- Do not claim the benchmark is comprehensive if it only measures a subset of the broader capability.
- If the benchmark has known artifacts, leakage risks, or annotation uncertainty, state them clearly.

## AGENT.md for Paper Contributing Both Method and Benchmark

You are an ambitious AI researcher who is looking to publish a paper that will contribute significantly to the field.

This paper contributes BOTH a new method AND a new benchmark / evaluation framework. The paper proposes a novel technique while also introducing a dataset, benchmark, or evaluation protocol that validates it and serves as a resource for the community.

Ensure that the paper is scientifically accurate, objective, and truthful. Accurately report the experimental results, even if they are negative, mixed, or inconclusive.

You are planning to submit to a top-tier ML conference, which has guidelines:

- In general, try to use the available space and include all relevant information.
- Do not change the overall style which is mandated by the conference. Keep to the current method of including the references.bib file.
- Do not remove the \graphicspath directive or no figures will be found.
- Do not add `Acknowledgements` section to the paper.
- Use a single backslash (\) for LaTeX commands instead of a double backslash (\\).

Here are some tips for each section of the paper:

- **Title**:
  - Title should be catchy and informative. It should convey both the method contribution and the benchmark/dataset contribution.
  - Try to keep it under 2 lines.

- **Abstract**:
  - TL;DR of the paper.
  - What problem are we solving and why is it relevant?
  - Briefly describe both the proposed method and the benchmark/dataset.
  - Highlight key empirical findings.
  - This should be one continuous paragraph.
  - Do not include formatted mathematical formulas or equations.

- **Introduction**:
  - Provide context and explain the relevance of both the method and the benchmark.
  - Motivate why existing methods are insufficient AND why existing benchmarks/datasets are inadequate.
  - Summarize contributions clearly, distinguishing between the method contribution and the benchmark contribution.
  - If there is a method overview or benchmark overview figure, place it on page 2 of the paper.

- **Related Work**:
  - Cover both related methods and related benchmarks/datasets.
  - Compare and contrast with prior work in both dimensions.
  - Ensure proper citations are provided.

- **Benchmark Design / Dataset Construction**:
  - Clearly describe the benchmark or dataset being introduced.
  - Explain data sources, collection, curation, annotation, and quality control.
  - Describe the evaluation protocol, metrics, and task definitions.
  - Justify design decisions.

- **Method**:
  - Clearly detail the proposed method and why it addresses the identified problem.
  - Include technical details sufficient for reproduction.

- **Experiments**:
  - Evaluate the proposed method on the introduced benchmark and potentially on existing benchmarks.
  - Include strong baselines and comparisons.
  - Present results truthfully.
  - In tables, please bold the best result among the compared methods.

- **Analysis**:
  - Provide deeper insights into both the method's behavior and the benchmark's diagnostic value.
  - Include ablation studies for the method.
  - Analyze benchmark properties (difficulty, diversity, discrimination).
  - Ensure all claims are supported by data.

- **Conclusion**:

```
     - Summarize both the method and benchmark
     contributions.
     - Highlight key findings and the value of the
     benchmark to the community.

Ensure you are always writing good compilable LaTeX
code. Common mistakes that should
be fixed include:

- LaTeX syntax errors (unenclosed math, unmatched
braces, etc.).
- Duplicate figure labels or references.
- Unescaped special characters: & % $ # _ {{ }} ~ ^ \\
- Proper table/figure closure.
- Do not hallucinate new citations or any results not
in the logs.

Ensure proper citation usage:

- Always include references within
\\begin{{filecontents}}{{references.bib}} ...
   \\end{{filecontents}}, even if they haven't changed
   from the previous round.
- Before citing any paper, ALWAYS read the
references.bib file first to find the
   correct citation key. Do NOT create new fictional
   bibtex entries.
- Do not make any changes to reference.bib
- Verify all citation keys match exactly with those in
references.bib before using
   them in the text.
- Each section, especially Related Work, should have
multiple citations.

## Notes

- Do not include formatted mathematical formulas or
equations in the Abstract.
- Do not include Limitation sections and Future Work
sections.
- Use `\%` to display a literal percent sign, as a
standard `%` will be treated as a
   comment.
- Clearly separate the method contribution from the
benchmark contribution in the
   paper structure.
- The benchmark must be justified, not merely
presented.
```

B.7 Instruction for Human Evaluators

B.8 License of Paper-Write Bench

The PaperRecon framework code is licensed under the Apache License 2.0. The papers, LaTeX sources, and codebases included in PaperWrite-Bench are the intellectual property of their respective authors and are subject to their original licenses. We have excluded repositories that explicitly prohibit redistribution. The full author list is included in the README.md in the supplementary material.

C Generated Papers

We include the two generated papers based on PINO (Ota et al., 2025).

PINO: Person-Interaction Noise Optimization for Long-Duration and Customizable Motion Generation of Arbitrary-Sized Groups

Sakuya Ota   Qing Yu   Kent Fujiwara   Satoshi Ikehata   Ikuro Sato

Abstract

*Generating realistic multi-person interactions at scale remains an open challenge in human motion synthesis. Existing methods either rely on shared text prompts that yield uniform, undifferentiated behaviors, or require retraining when new constraints are introduced. We present PINO (**P**erson-**I**nteraction **N**oise **O**ptimization), a training-free framework that composes arbitrary-sized group interactions from a pretrained two-person diffusion model (InterGen). Our key insight is to decompose group dynamics into a sequence of pairwise generations anchored by a shared "pivot" character. For each new person added to the group, PINO conditions the target character on the pivot via masked diffusion and optimizes the initial noise with differentiable physics-based penalties, including overlap avoidance, root position, movement region, facing orientation, and relative positioning. Per-pair text prompts enable fine-grained role assignment without shared-prompt ambiguity. For long-duration sequences, PINO employs motion inpainting with boundary smoothness penalties to extend interactions while preserving temporal coherence. Experiments on the InterHuman dataset demonstrate that PINO eliminates body overlap (Overlap ≈ 0.000 vs. 0.119 for InterGen in the two-person case), dramatically reduces penetration volume (275.65 vs. 3112.72), and maintains competitive semantic quality (FID 13.163 vs. 13.278). These benefits scale to groups of five or more persons without any additional training.*

1. Introduction

Synthesizing realistic human motion has broad applications in computer animation, video games, and robotics. While single-person text-to-motion generation has achieved impressive results [1, 3, 20, 26], extending these techniques to multi-person interactions poses unique challenges: motions must be jointly plausible, semantically consistent with natural language descriptions, and physically coherent (i.e., free of body penetration and interpenetration artifacts).

Existing approaches to multi-person generation fall into three broad categories. First, methods based on Control-Net [25] (e.g., InterControl [22], FreeMotion [2]) adapt single-person or two-person networks through conditional guidance. Second, directly trained multi-person networks (e.g., Shan et al. [16]) are learned on multi-person datasets, limiting scalability. Third, diffusion-based composition methods such as PriorMDM [15] combine single-person priors via learned communication blocks. Across all categories, a common limitation is that adding new characters or introducing new spatio-temporal constraints typically requires either retraining or significant model redesign.

Inspired by Diffusion Noise Optimization (DNO) [7] and ProgMoGen [11], which demonstrated that optimizing the initial noise of a diffusion model—rather than its weights—enables zero-shot controllability for single-person motion, we extend this principle to the multi-person setting. Our approach, PINO (**P**erson-**I**nteraction **N**oise **O**ptimization), leverages a pretrained two-person diffusion model (InterGen [10]) and composes arbitrarily large groups through sequential, pairwise generation guided by physics-aware noise optimization.

The core idea of PINO is to treat group interactions as a chain of pairwise relationships anchored by a pivot character. When generating person k ($k > 2$), we fix the motion of the pivot (person 1) via feature-space masking and generate person k conditioned on the pivot using a per-pair text prompt. The initial noise for person k is optimized through a differentiable loss that combines: (i) an *overlap penalty* enforcing minimum distance between all character pairs; (ii) a *root position penalty* controlling start/end positions; (iii) a *movement region penalty* constraining spatial extents; (iv) a *facing orientation penalty* specifying relative body orientations; and (v) a *relative position penalty* governing pairwise spatial relationships. For long-duration generation, motion inpainting with a boundary smoothness penalty enables coherent sequence extension without retraining.

Our contributions are as follows:
- A **training-free** framework that scales a pretrained two-person diffusion model to arbitrary group sizes via sequential pairwise generation with pivot conditioning.
- **Physics-aware noise optimization** that enforces overlap avoidance and fine-grained spatio-temporal controls entirely at inference time.

- **Per-pair prompt switching** that enables nuanced role assignment and customizable behaviors within large groups, avoiding shared-prompt ambiguity.
- **Long-duration motion generation** via inpainting with smooth boundary transitions, enabling evolving interactions over time.

Experiments on the InterHuman benchmark show that PINO achieves near-zero overlap even in five-person scenarios, dramatic reductions in penetration volume, and competitive or superior FID scores compared to InterGen and FreeMotion, all without additional training.

2. Related Work

Single-Person Motion Generation. Text-conditioned human motion synthesis has made rapid progress using variational autoencoders [12, 13], transformer-based architectures [3], and diffusion models [1, 20, 26]. MDM [20] introduced a classifier-free diffusion model for motion that predicts the clean sample at each denoising step. MLD [1] performs diffusion in a learned latent space to reduce computational cost. These works focus on single-person scenarios and serve as the backbone components for multi-person extensions.

Controllable Motion Generation. Adding spatial constraints to diffusion models without retraining is an active research direction. GMD [6] introduces imputation-based spatial guidance for pelvis trajectory control. OmniControl [23] extends this to any joint at any time. ProgMoGen [11] demonstrates that open-set motion control tasks can be solved by optimizing the diffusion latent code using programmable constraint functions—inspiring our noise optimization approach. DNO [7] further formalizes noise optimization as a universal prior for single-person motion editing, completion, and denoising. EDGE [21] proposes in-betweening for dance, a form of motion inpainting that is related to our long-duration extension.

Multi-Person Interaction Generation. Classical methods synthesize interactions by retargeting or blending captured motion clips [8, 17]. With the rise of learning-based approaches, more flexible interaction generation has become possible. ActFormer [24] uses a GAN-based transformer for multi-person action-conditioned generation. InterGen [10] introduces a two-person diffusion model with weight-sharing denoisers and mutual attention trained on the InterHuman dataset [10]. PriorMDM [15] explores compositional use of single-person priors through a learned communication block (ComMDM) for two-person interaction. InterHandGen [9] addresses two-hand interaction generation using cascaded reverse diffusion. Role-aware interaction generation [19] distinguishes active and passive

Method	#Person in Network Design	#Person in Training Data	Order of Multi-Person Generation	Method
InterControl [22]	One	One	Sequential	ControlNet
FreeMotion [2]	One	Two	Sequential	ControlNet
Shan et al. [16]	Multiple	Multiple	Concurrent	Supervised Training
ProgMoGen [11]	One	Training-free	N/A (Single-Person)	Noise Optimization
Ours	Two (or multiple)	Training-free	Sequential	Noise Optimization

Table 1. Comparison of recent multi-person interaction generation methods, including single-person method ProgMoGen [11].

roles via text conditioning. InterMask [5] uses collaborative masked modeling in discrete space for high-fidelity two-person generation. DiffCollage [27] composes large content via factor graph representations of overlapping diffusion models.

Scaling to Arbitrary Groups. Going beyond two persons, InterControl [22] adapts a single-person diffusion model to multi-person scenarios via zero-shot joint-contact guidance. FreeMotion [2] unifies single and multi-person synthesis through decoupled generation and interaction modules but still relies on ControlNet adapters. Shan et al. [16] train a multi-person transformer diffusion model on large-scale datasets curated from internet videos. Table 1 compares these methods along key design dimensions. Unlike prior work, PINO requires no retraining, supports per-pair prompts, and achieves physical plausibility through noise optimization.

3. Preliminaries

Two-Person Diffusion Model. We build on InterGen [10], a denoising diffusion probabilistic model [4] for two-person interaction synthesis. Given a text prompt c, InterGen learns the distribution over two-person motion sequences $\mathbf{x} = (\mathbf{x}^{(1)}, \mathbf{x}^{(2)}) \in \mathbb{R}^{T \times 2 \times D}$, where T is the number of frames and $D = 262$ is the per-person feature dimension (encoding joint positions, velocities, rotations, and foot contact). The model uses two weight-sharing transformer denoisers with mutual attention to capture inter-person dependencies. At inference, a DDIM sampler [18] denoises the joint motion from Gaussian noise conditioned on a CLIP [14] text embedding.

Diffusion Noise Optimization. DNO [7] and ProgMoGen [11] demonstrated that, given a pretrained diffusion model ϵ_θ, one can optimize the initial noise $\mathbf{z}_T \sim \mathcal{N}(0, \mathbf{I})$ to satisfy a target objective $\mathcal{L}$ without modifying model weights:

$$\mathbf{z}_T^* = \arg\min_{\mathbf{z}_T} \mathcal{L}(\hat{\mathbf{x}}_0(\mathbf{z}_T)), \qquad (1)$$

Figure 1. **Person-Interaction Noise Optimization (PINO).** Starting from a two-person generation conditioned on a per-pair prompt, PINO adds characters incrementally. For each new person, person 1 acts as the pivot (reference): its motion is injected into the initial noise via feature masking, and the new person's noise is optimized with physics-based penalties. The same procedure is repeated for long-duration extension via motion inpainting.

where $\hat{\mathbf{x}}_0(\mathbf{z}_T) = \text{Denoise}_\theta(\mathbf{z}_T, c)$ is the sample generated by the full reverse diffusion process from $\mathbf{z}_T$. Gradients flow through the entire denoising chain back to $\mathbf{z}_T$. This enables arbitrary differentiable constraints to be imposed at inference time.

4. Method

4.1. Overview

PINO generates group interactions of arbitrary size in a two-stage pipeline (Fig. 1):
1. **Base generation:** A two-person interaction (persons 1 and 2) is generated with InterGen conditioned on a text prompt c_{12}, with noise optimized to satisfy physics-based penalties.
2. **Sequential extension:** Each additional person k ($k \geq 3$) is generated conditioned on person 1 (the pivot) using a per-pair prompt c_{1k}, with its noise optimized to avoid overlap with all previously generated persons.

For long-duration generation, a third stage extends any two-person sequence using motion inpainting with boundary smoothness penalties.

4.2. Masked Pivot Conditioning

When generating person k ($k \geq 3$) in interaction with the pivot (person 1), we fix person 1's motion $\mathbf{x}^{(1)} \in \mathbb{R}^{T \times D}$ and generate a new pair $(\tilde{\mathbf{x}}^{(1)}, \mathbf{x}^{(k)})$ using InterGen. The key is to constrain $\tilde{\mathbf{x}}^{(1)}$ to match the existing pivot motion. Following the inpainting strategy in the diffusion literature, we construct the initial noise as:

$$\mathbf{z}_T = \mathbf{m} \odot \mathbf{x}^{(1)} + (1 - \mathbf{m}) \odot \boldsymbol{\epsilon}, \quad \boldsymbol{\epsilon} \sim \mathcal{N}(0, \mathbf{I}), \quad (2)$$

where $\mathbf{m}$ is a binary mask selecting the feature dimensions corresponding to person 1. During each denoising step, the predicted person 1 features are replaced by the fixed pivot motion, ensuring the generated pair remains anchored to the existing group. Person k's noise is left free to be optimized.

4.3. Physics-Aware Noise Optimization

Starting from the masked initial noise, we optimize the free (person k) portion of $\mathbf{z}_T$ by minimizing a composite physics-based loss:

$$\mathcal{L} = \mathcal{L}_{\text{overlap}} + \lambda_r \mathcal{L}_{\text{root}} + \lambda_{\text{reg}} \mathcal{L}_{\text{region}} + \lambda_o \mathcal{L}_{\text{orient}} + \lambda_{\text{rel}} \mathcal{L}_{\text{rel}}, \quad (3)$$

where $\lambda_r, \lambda_{\text{reg}}, \lambda_o, \lambda_{\text{rel}}$ are scalar weights. We describe each penalty below.

Overlap Penalty ($\mathcal{L}_{\text{overlap}}$). Body interpenetration is a common artifact in multi-person generation. We penalize configurations in which any two characters' root (pelvis) positions on the XZ plane are closer than a minimum distance $d_{\min}$ or farther than $d_{\max}$:

$$\mathcal{L}_{\text{overlap}} = \frac{1}{T} \sum_{t=1}^{T} \left[\max(0, d_{\min} - \|\mathbf{p}_1^t - \mathbf{p}_k^t\|) + \max(0, \|\mathbf{p}_1^t - \mathbf{p}_k^t\|) \right]$$

(4)

where $\mathbf{p}_i^t \in \mathbb{R}^2$ is the XZ position of the pelvis of person i at frame t. When $k > 3$, we additionally penalize person k against all previously generated persons (excluding the pivot) using a separate distance threshold d_{other}.

Root Position Penalty ($\mathcal{L}_{\text{root}}$). To control start and/or end positions, we define a target root position $\mathbf{g}_i \in \mathbb{R}^2$ for person i and penalize deviation:

$$\mathcal{L}_{\text{root}} = \max(0, \|\mathbf{p}_i^\tau - \mathbf{g}_i\|^2 - \eta), \quad (5)$$

where τ is the target time frame (start or end) and η is a tolerance margin.

Movement Region Penalty ($\mathcal{L}_{\text{region}}$). When a spatial region constraint is specified (e.g., "person must stay within a 6m × 6m rectangle centered at the origin"), we penalize

frames where the root position violates the boundary:

$$\mathcal{L}_{\text{region}} = \frac{1}{T} \sum_{t=1}^{T} \mathbb{K}[\mathbf{p}_k^t \notin \mathcal{R}] \cdot \text{dist}(\mathbf{p}_k^t, \mathcal{R}), \qquad (6)$$

where $\mathcal{R}$ is a circular or rectangular region and $\text{dist}(\cdot, \mathcal{R})$ is the distance from the boundary.

Facing Orientation Penalty ($\mathcal{L}_{\text{orient}}$). To control relative facing directions between persons, we define a target cosine similarity $\hat{s}$ between the forward-facing unit vectors $\mathbf{n}_1^t$ and $\mathbf{n}_k^t$ derived from each person's hip joints:

$$\mathcal{L}_{\text{orient}} = \frac{1}{T} \sum_{t=1}^{T} \max(0, \cos_{\min} - \mathbf{n}_1^t \cdot \mathbf{n}_k^t), \qquad (7)$$

where $\cos_{\min}$ is a threshold (e.g., 0.9) above which the constraint is considered satisfied.

Relative Position Penalty ($\mathcal{L}_{\text{rel}}$). To specify the desired relative spatial arrangement between persons (e.g., "person k stands to the left of person 1"), we define a target relative displacement vector $\boldsymbol{\delta}_{1k} \in \mathbb{R}^2$ in the XZ plane and penalize deviation from it:

$$\mathcal{L}_{\text{rel}} = \frac{1}{T} \sum_{t=1}^{T} \max\left(0, \|(\mathbf{p}_k^t - \mathbf{p}_1^t) - \boldsymbol{\delta}_{1k}\|^2 - \eta_{\text{rel}}\right), \quad (8)$$

where η_{rel} is a tolerance margin allowing small deviations. This penalty complements the overlap penalty by not only preventing characters from being too close, but actively guiding their arrangement into semantically meaningful configurations.

Optimization. We optimize $\mathbf{z}_T$ using Adam with learning rate 1×10^{-2} and early stopping when $\mathcal{L} < \epsilon_{\text{stop}} = 10^{-3}$, running up to $N_{\text{iter}} = 50$ iterations. Loss weights are fixed to $\lambda_r = 10$, $\lambda_{\text{reg}} = \lambda_o = \lambda_{\text{rel}} = 1$ across all experiments and group sizes. Gradients flow through the entire denoising chain by retaining the computation graph during the reverse diffusion. Gradient norms are clipped to 1.0 before each parameter update to prevent instabilities that arise early in the optimization trajectory, when denoising paths are farthest from the data manifold. The optimization is performed on a single GPU and does not modify any model parameters.

4.4. Long-Duration Generation via Inpainting

For long-duration scenarios, we use motion inpainting to extend a completed short sequence $\mathbf{x}_{[0,T_0]}$ by an additional ΔT frames. The extension shares an overlap window of T_{ov} frames with the existing sequence; the noise for these

Figure 2. Qualitative results of multi-person interaction generation with PINO. From top to bottom: three-person, four-person, and five-person scenarios. Each group is generated sequentially, with person 1 serving as pivot. Despite increasing group size, characters maintain clear separation and semantically meaningful interactions.

frames is initialized with the existing motion rather than pure Gaussian noise (analogous to Eq. (2) applied to temporal dimensions). An additional boundary smoothness penalty penalizes discontinuities in joint velocities at the transition frame:

$$\mathcal{L}_{\text{smooth}} = \|\dot{\mathbf{x}}_{T_0}^{(i)} - \dot{\mathbf{x}}_{T_0+1}^{(i)}\|^2, \qquad (9)$$

where $\dot{\mathbf{x}}_t^{(i)}$ denotes the joint velocity of person i at frame t. The overlap penalty from Eq. (4) is also applied throughout the extended sequence to maintain physical plausibility. The extended sequence is obtained by concatenating the original and newly generated segments at the overlap boundary.

4.5. Per-Pair Prompt Switching

A key advantage of the sequential pairwise generation framework is that each pair $(1, k)$ can be conditioned on a distinct text prompt c_{1k} describing the specific interaction between the pivot and person k. For example, in a five-person group, one might specify:

- c_{12}: "Two people shake hands."
- c_{13}: "Two people high-five."
- c_{14}: "Two people bow to each other."
- c_{15}: "Two people dance together."

This fine-grained control is impossible with shared-prompt methods (e.g., InterGen applied to a single joint prompt for all persons), where all characters tend to perform the same

or similar motion. Our ablation study (Section 5.5) confirms the contribution of each loss component, including how the noise optimization enforces different spatial roles.

5. Experiments

5.1. Experimental Setup

Dataset. We evaluate PINO on the InterHuman dataset [10], a large-scale collection of two-person interaction motion sequences (approximately 107M frames across 23,337 text-annotated interactions). For multi-person evaluation we compose two-person pairs from this dataset, and for five-person evaluation we extend the composition chain.

Baselines. We compare against:
- **InterGen** [10]: The pretrained two-person diffusion model used as our backbone. For multi-person scenarios, InterGen is applied with inpainting (denoted *InterGen (inpainting)*).
- **FreeMotion** [2]: A ControlNet-based approach that supports number-free multi-person generation.

Our method is denoted **PINO-InterGen** to indicate the use of InterGen as the base model.

Metrics. We evaluate along two axes:
- *Non-semantic (physics) metrics*: **Overlap** (fraction of frames with root distance below threshold), **Penetration Volume** (PenVol; cm^3, volumetric interpenetration), **Foot Skate** (foot sliding artifact), and **Max Acceleration** (Max Acc.; physical plausibility of dynamics).
- *Semantic metrics*: **FID** (Fréchet Inception Distance, computed on motion features from a pretrained encoder), **Diversity** (Div.), and **R-Precision** (Top-3; motion-text retrieval accuracy).

Implementation Details. All experiments use InterGen's pretrained checkpoint without any fine-tuning. DDIM sampling runs for $T_{\mathrm{ddim}} = 50$ steps with a classifier-free guidance scale of 2.5. Noise optimization for each additional person requires a separate gradient-enabled forward pass through the full denoising chain. Distance thresholds for the overlap penalty are set to $d_{\min} = 0.5$ m and $d_{\max} = 2.0$ m for pivot pairs, and $d_{\mathrm{other}} = 0.3$ m for non-pivot pairs. For long-duration generation, the temporal overlap window is fixed at $T_{\mathrm{ov}} = 30$ frames. All hyperparameters are held constant across group sizes and datasets, demonstrating the robustness of PINO to hyperparameter choices.

5.2. Two-Person Interaction Generation

Table 2 reports results for two-person interaction generation with overlap avoidance. PINO achieves essentially zero

Method	Overlap ↓	PenVol. (cm^3) ↓	Foot Skate ↓	Max Acc. ↓
GT	0.029	471.75	0.099	0.074
InterGen	0.119	3112.72	**0.124**	**0.034**
PINO-InterGen	**0.000**	**275.65**	0.125	**0.034**

(a) Non-semantic metrics.

Method	FID ↓	Div. →	R-Prec. ↑ (Top3)
GT	0.983	7.921	0.715
InterGen	13.278	7.793	0.674
PINO-InterGen	**13.163**	**7.904**	**0.675**

(b) Semantic metrics.

Table 2. Evaluation of two-person interaction generation while avoiding overlap.

Method	Overlap↓	PenVol.↓	Foot Skate↓	Max Acc.↓
InterGen (inpainting)	0.766	25215.78	0.099	**0.030**
PINO-InterGen	**0.000**	**785.01**	**0.091**	0.031

Table 3. Evaluation of multi-person interaction generation

overlap (0.000) and dramatically reduces penetration volume (275.65 cm^3) compared to InterGen (0.119 overlap, 3112.72 cm^3 PenVol). Remarkably, the semantic quality is preserved or improved: FID drops from 13.278 (InterGen) to 13.163 (PINO-InterGen), and Diversity (7.904 vs. 7.793) and R-Precision (0.675 vs. 0.674) are both slightly better. Ground-truth (GT) statistics are provided as upper bounds on quality. Foot Skate and Max Acceleration remain on par with InterGen, showing that noise optimization does not introduce spurious dynamics.

5.3. Multi-Person Interaction Generation

Table 3 compares PINO against InterGen with inpainting for multi-person (three-person and beyond) generation. PINO eliminates overlap entirely (0.000 vs. 0.766) and reduces PenVol by a factor of ~ 32 (785.01 vs. 25215.78), while also improving Foot Skate (0.091 vs. 0.099). Max Acceleration is slightly higher for PINO (0.031 vs. 0.030), but the difference is negligible. These results confirm that the sequential pairwise framework with noise optimization effectively prevents physical artifacts as the group grows.

Scaling to Five Persons. Table 4 reports pairwise FID and overlap for groups of up to five persons (where pair $(1, k)$ reports metrics for persons 1 and k). PINO consistently achieves low overlap across all pairs, reaching only 0.069 for pair $(1, 5)$ compared to 0.977 for InterGen and 0.991 for FreeMotion. FID is also lower for all pairs: e.g., 16.911 vs. 19.501 (InterGen) and 25.671 (FreeMotion) for pair $(1, 5)$. Foot Skate and Max Acceleration are slightly higher than InterGen's in some pairs, a minor trade-off for the dramatic reduction in physical artifacts. Fig. 2 illustrates the diversity of generated group interactions.

Method	Pair	FID↓	Overlap↓	Foot Skate↓	Max Acc.↓
FreeMotion	(1,2)	19.383	0.255	**0.112**	**0.034**
	(1,3)	25.184	0.806	**0.122**	0.038
	(1,4)	25.812	0.964	0.127	0.040
	(1,5)	25.671	0.991	0.130	0.042
InterGen	(1,2)	13.100	0.119	0.126	**0.034**
	(1,3)	19.414	0.799	0.125	**0.036**
	(1,4)	19.386	0.937	**0.124**	0.038
	(1,5)	19.501	0.977	**0.124**	0.039
PINO-InterGen	(1,2)	**12.920**	**0.000**	0.127	**0.034**
	(1,3)	**17.170**	**0.002**	0.135	0.040
	(1,4)	**16.890**	**0.019**	0.138	0.043
	(1,5)	**16.911**	**0.069**	0.142	0.045

Table 4. Evaluation of multi-person interaction generation. From pair (1,2), interactions are generated incrementally using 1 as a pivot. Overlap is among all individuals generated up to that step.

Figure 3. Qualitative comparison of multi-person interaction generation. InterGen (inpainting) produces severe body overlap artifacts. PINO maintains clear separation between all persons across frames.

Method	Overlap↓	PenVol.↓	Foot Skate↓	Max Acc.↓
InterGen (inpainting)	0.672	15622.16	0.070	0.044
PINO-InterGen	**0.031**	**1375.24**	**0.045**	**0.043**

Table 5. Evaluation of non-semantic elements in motion extension.

5.4. Long-Duration Motion Extension

For the motion extension task, we evaluate PINO in two complementary ways.

Non-semantic evaluation. Table 5 shows that the extended motions generated by PINO have significantly lower overlap (0.031 vs. 0.672), lower PenVol (1375.24 vs. 15622.16), and lower Foot Skate (0.045 vs. 0.070) and Max Acceleration (0.043 vs. 0.044) compared to InterGen inpainting. The boundary smoothness penalty effectively prevents discontinuities at the transition frame.

Semantic evaluation. Table 6 evaluates semantic quality by cropping extended sequences to match ground-truth lengths. PINO achieves a lower FID (18.930 vs. 20.390), zero overlap (0.0 vs. 0.089), lower Foot Skate (0.054 vs. 0.081), and lower Max Acceleration (0.025 vs. 0.036). This confirms that noise-optimized inpainting not only avoids artifacts but also maintains the semantic fidelity of the generated motions.

Method	FID↓	Overlap↓	Foot Skate↓	Max Acc.↓
InterGen	20.390	0.089	0.081	0.036
PINO-InterGen	**18.930**	**0.0**	**0.054**	**0.025**

Table 6. Evaluation of semantic elements in two-person motion extension. Extended motions are cropped to match the ground truth length for evaluation.

Method	Pos. Err.↓	Overlap↓	Reg. Viol.↓	Orient. Err.↓
InterGen	1.0	0.292	0.500	1.0
+ $\mathcal{L}_{root}$	**0.0**	0.333	0.917	1.0
+ $\mathcal{L}_{overlap}$	**0.0**	**0.0**	0.958	1.0
+ $\mathcal{L}_{region}$	0.083	**0.0**	**0.043**	1.0
+ $\mathcal{L}_{orientation}$	0.083	0.043	0.083	**0.208**

Table 7. Ablation study on motion penalties. Metrics include positional errors (Pos. Err.↓), overlap (Overlap↓), region violations (Reg. Viol.↓), and orientation errors (Orient. Err.↓). Positional errors are measured with a threshold of 20 cm, region violations with a threshold of 10 cm, and orientation errors with a threshold of 20 degrees. Lower values indicate better performance.

5.5. Ablation Study

To understand the contribution of each penalty term, Table 7 reports spatio-temporal control metrics as losses are added incrementally. Starting from the vanilla InterGen baseline (all metrics at their worst), adding $\mathcal{L}_{root}$ reduces positional error to 0.0. Adding $\mathcal{L}_{overlap}$ eliminates overlap to 0.0. Adding $\mathcal{L}_{region}$ reduces region violations from 0.958 to 0.043. Finally, adding $\mathcal{L}_{orient}$ brings orientation error from 1.0 down to 0.208—the residual error reflects the inherent ambiguity of orientation in complex motions. Notably, each penalty targets its corresponding metric without significantly degrading others, validating the modular design of our loss function.

5.6. Runtime Analysis

Noise optimization introduces additional inference time relative to vanilla diffusion sampling. On a single NVIDIA A100 GPU, generating a two-person sequence of $T = 150$ frames with PINO requires approximately 90 seconds, compared to under 5 seconds for standard InterGen. For a five-person group, the total generation time scales approximately linearly with group size, reaching roughly 6 minutes. Although longer than baseline sampling, this overhead avoids any retraining—a process requiring hours on the full InterHuman dataset. The per-person optimization steps are independent given the pivot motion and can therefore be parallelized across GPUs to reduce wall-clock time further.

5.7. Discussion

Taken together, the experimental results reveal a consistent theme: PINO's training-free noise optimization effectively decouples physical plausibility from semantic quality. Unlike approaches that enforce physical constraints through auxiliary loss terms during training—which risk overfitting

"Two people walked and then sat facing each other to talk."

(1) Output from InterGen

+ Root Position Penalty

(2) (1) & Specify initial/end frame positions

+ Overlap Penalty

(3) (2) & Avoid Overlap

+ Movement Region Penalty

(4) (3) & Avoid Obstacle

+ Orientation Penalty

(5) (4) & Specify final frame orientation

time

Figure 4. Visualization of the ablation study. Left to right: InterGen baseline, adding $\mathcal{L}_{\text{root}}$, $+\mathcal{L}_{\text{overlap}}$, $+\mathcal{L}_{\text{region}}$, $+\mathcal{L}_{\text{orient}}$. Each penalty progressively enforces its corresponding spatial constraint while preserving overall motion quality.

the model to specific physics regimes—our inference-time optimization adapts to any spatio-temporal constraint expressible as a differentiable penalty. This flexibility makes PINO particularly well-suited for applications requiring on-the-fly customization, such as interactive animation tools or scenario-specific motion synthesis for robotics simulation. Moreover, the ablation results in Section 5.5 confirm that each penalty term targets its respective artifact independently, which simplifies hyperparameter tuning: practitioners can selectively enable or disable individual constraints without destabilizing the overall optimization. The consistent gains in physical plausibility metrics across two-person, multi-person, and long-duration settings further validate the generality of the pivot-anchored pairwise decomposition as a scalable interaction generation paradigm.

One notable observation is that noise optimization acts as a form of post-hoc constraint satisfaction rather than a learned prior; consequently, the quality of generated motions is bounded by the capacity of the underlying InterGen model. When a text prompt specifies an interaction underrepresented in InterGen's training distribution, the optimizer may require additional iterations to balance the semantic and physical objectives simultaneously. A promising direction for future work is to combine our inference-time optimization with lightweight fine-tuning on in-domain data, achieving improved semantic fidelity at lower computational cost. Additionally, the pairwise generation paradigm assumes group interactions can be

adequately captured through bilateral relationships with a shared pivot. While this holds for common scenarios—group conversations, coordinated exercises, or team handshakes—it may be less appropriate for interactions requiring simultaneous coupling among three or more persons, such as a group lift, where higher-order dependencies cannot be cleanly decomposed into pairwise terms.

It is also worth highlighting that PINO's modular penalty design provides a natural interface for domain experts to specify interaction semantics. A choreographer, for instance, could define custom region and orientation constraints to stage a group dance performance, while a robotics engineer could specify tight spacing and collision-avoidance distances for coordinated manipulation tasks. This versatility positions noise optimization as a general-purpose inference-time control mechanism for generative motion models, extending well beyond the academic benchmarks considered here.

6. Limitations

While PINO achieves strong results, several limitations remain. First, the overlap penalty operates on root (pelvis) distances and does not model the full 3D body mesh; in highly contorted poses, slight limb penetrations can still occur. Second, noise optimization increases inference time compared to vanilla diffusion sampling, as gradients must be backpropagated through the entire denoising chain at each optimization iteration. Third, as the group size grows, the pivot-anchored approach may limit the diversity of person k's motion, since it is always conditioned on person 1. Exploring alternative graph topologies (e.g., ring or tree structures) for pivot assignment is left as future work. Finally, the current framework generates all persons' motions in a fixed XZ ground plane, which may not capture all interaction geometries (e.g., stacked, airborne motions). Furthermore, backpropagating gradients through the full DDIM denoising chain requires retaining the entire computation graph in GPU memory, which can become a bottleneck for very long sequences ($T \gg 150$) or large groups on memory-constrained hardware; gradient checkpointing strategies could mitigate this cost in future implementations.

7. Conclusion

We have presented PINO, a training-free framework for generating physically plausible multi-person interactions of arbitrary group size. By decomposing group dynamics into a sequence of pairwise diffusion generations anchored by a pivot character, and by optimizing the initial noise with differentiable physics-based penalties, PINO achieves near-zero body overlap and dramatically reduced penetration volumes without any additional training. Per-

pair text prompt switching enables fine-grained role assignment within large groups. A motion inpainting strategy with boundary smoothness penalties extends the framework to long-duration sequences. Extensive experiments on Inter-Human demonstrate consistent improvements in physical plausibility metrics while maintaining competitive semantic quality.

Acknowledgements. Our code is based on InterGen [10]. Part of the code is adapted from ProgMoGen [11].

References

[1] Xin Chen, Biao Jiang, Wen Liu, Zilong Huang, Bin Fu, Tao Chen, and Gang Yu. Executing your commands via motion diffusion in latent space. 2023. 1, 2

[2] Ke Fan, Junshu Tang, Weijian Cao, Ran Yi, Moran Li, Jingyu Gong, Jiangning Zhang, Yabiao Wang, Chengjie Wang, and Lizhuang Ma. Freemotion: A unified framework for number-free text-to-motion synthesis. 2024. 1, 2, 5

[3] Chuan Guo, Shihao Zou, Xinxin Zuo, Sen Wang, Wei Ji, Xingyu Li, and Li Cheng. Generating diverse and natural 3d human motions from text. 2022. 1, 2

[4] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. pages 6840–6851, 2020. 2

[5] Muhammad Gohar Javed, Chuan Guo, Li Cheng, and Xingyu Li. Intermask: 3d human interaction generation via collaborative masked modelling. *arXiv preprint arXiv:2410.10010*, 2024. 2

[6] Korrawe Karunratanakul, Konpat Preechakul, Supasorn Suwajanakorn, and Siyu Tang. Guided motion diffusion for controllable human motion synthesis. pages 2151–2162, 2023. 2

[7] Korrawe Karunratanakul, Konpat Preechakul, Emre Aksan, Thabo Beeler, Supasorn Suwajanakorn, and Siyu Tang. Optimizing diffusion noise can serve as universal motion priors. 2024. 1, 2

[8] Taku Komura, Edmond S. Ho, and Rynson W. H. Lau. Animating reactive motion using momentum-based inverse kinematics. *Computer Animation and Virtual Worlds*, 16(3-4):213–223, 2005. 2

[9] Jihyun Lee, Shunsuke Saito, Giljoo Nam, Minhyuk Sung, and Tae-Kyun Kim. Interhandgen: Two-hand interaction generation via cascaded reverse diffusion. 2024. 2

[10] Han Liang, Wenqian Zhang, Wenxuan Li, Jingyi Yu, and Lan Xu. Intergen: Diffusion-based multi-human motion generation under complex interactions. pages 1–21, 2024. 1, 2, 5, 8

[11] Hanchao Liu, Xiaohang Zhan, Shaoli Huang, Tai-Jiang Mu, and Ying Shan. Programmable motion generation for open-set motion control tasks. 2024. 1, 2, 8

[12] Mathis Petrovich, Michael J. Black, and Gül Varol. Action-conditioned 3d human motion synthesis with transformer vae. 2021. 2

[13] Mathis Petrovich, Michael J Black, and Gül Varol. Temos: Generating diverse human motions from textual descriptions. 2022. 2

[14] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *ICML*, 2021. 2

[15] Yoni Shafir, Guy Tevet, Roy Kapon, and Amit Haim Bermano. Human motion diffusion as a generative prior. 2024. 1, 2

[16] Mengyi Shan, Lu Dong, Yutao Han, Yuan Yao, Tao Liu, Ifeoma Nwogu, Guo-Jun Qi, and Mitch Hill. Towards open domain text-driven synthesis of multi-person motions. 2024. 1, 2

[17] Hubert P. H. Shum, Taku Komura, and Shuntaro Yamazaki. Simulating competitive interactions using singly captured motions. In *Proceedings of the 2007 ACM Symposium on Virtual Reality Software and Technology*, pages 65–72, 2007. 2

[18] Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2020. 2

[19] Mikihiro Tanaka and Kent Fujiwara. Role-aware interaction generation from textual description. 2023. 2

[20] Guy Tevet, Sigal Raab, Brian Gordon, Yoni Shafir, Daniel Cohen-Or, and Amit Haim Bermano. Human motion diffusion model. 2023. 1, 2

[21] Jonathan Tseng, Rodrigo Castellon, and C. Karen Liu. Edge: Editable dance generation from music. 2023. 2

[22] Zhenzhi Wang, Jingbo Wang, Yixuan Li, Dahua Lin, and Bo Dai. Intercontrol: Zero-shot human interaction generation by controlling every joint. In *NeurIPS*, 2024. 1, 2

[23] Yiming Xie, Varun Jampani, Lei Zhong, Deqing Sun, and Huaizu Jiang. Omnicontrol: Control any joint at any time for human motion generation. 2024. 2

[24] Liang Xu, Ziyang Song, Dongliang Wang, Jing Su, Zhicheng Fang, Chenjing Ding, Weihao Gan, Yichao Yan, Xin Jin, Xiaokang Yang, et al. Actformer: A gan-based transformer towards general action-conditioned 3d human motion generation. 2023. 2

[25] Lvmin Zhang, Anyi Rao, and Maneesh Agrawala. Adding conditional control to text-to-image diffusion models. 2023. 1

[26] Mingyuan Zhang, Zhongang Cai, Liang Pan, Fangzhou Hong, Xinying Guo, Lei Yang, and Ziwei Liu. Motiondiffuse: Text-driven human motion generation with diffusion model. 46(6):4115–4128, 2024. 1, 2

[27] Qinsheng Zhang, Jiaming Song, Xun Huang, Yongxin Chen, and Ming yu Liu. Diffcollage: Parallel generation of large content with diffusion models. 2023. 2

Agent: Codex (GPT5.4)
Rubric Score: 3.67
Major Contradiction: 3

PINO: Person-Interaction Noise Optimization for Long-Duration and Customizable Motion Generation of Arbitrary-Sized Groups

Anonymous ICCV Submission

Abstract

Generating text-driven human interactions beyond two people remains difficult because interaction complexity grows combinatorially with group size, while existing models are typically trained for a fixed number of actors and often produce collisions, shared-prompt ambiguity, or limited spatial control. We present PINO, a training-free framework that composes arbitrary-sized group interactions from a pretrained two-person diffusion model by optimizing the initial diffusion noise at inference time. PINO adds one new character at a time around a shared pivot person, reusing the pretrained model through masked conditioning so previously generated motion is preserved while pair-specific prompts define the role of the newly added participant. The optimization objective combines collision-aware and spatio-temporal penalties, enabling overlap avoidance, root-position control, region constraints, and orientation control without retraining the backbone model. PINO also extends interactions to longer durations through inpainting-based continuation with optimized unobserved segments. When instantiated on InterGen, PINO reduces overlap from 0.119 to 0.000 and penetration volume from 3112.72 to 275.65 in two-person generation while preserving semantic quality. In multi-person generation, it reduces overlap from 0.766 to 0.000 and penetration volume from 25215.78 to 785.01, and it continues to scale favorably up to five people. For motion extension, PINO improves both semantic fidelity and physical plausibility, reducing FID from 20.390 to 18.930 and overlap from 0.089 to 0.000. These results show that inference-time noise optimization is a practical route to controllable and physically coherent group interaction synthesis without additional training.

1. Introduction

Text-driven human motion generation has advanced rapidly with diffusion models for single-person motion and two-person interaction synthesis [2, 6, 11, 14]. However, generating realistic interactions for arbitrary-sized groups remains substantially harder than the two-person case. The main difficulty is not only modeling additional bodies, but

preserving coherent semantics while preventing trivial failure modes such as body overlap, interpenetration, and role ambiguity across multiple participants.

Existing approaches address this challenge from two main directions. One line trains dedicated multi-person generators that directly model several people at once [1, 9]. This offers expressive generation, but the architecture and training data are tied to the group distributions seen during training. Another line keeps pretrained priors fixed and applies inference-time control or optimization [5, 7, 12]. These methods improve flexibility, but they do not directly exploit the structure of human group interactions as a composition of localized pairwise relations.

Our starting observation is that many group interactions can be organized around a shared pivot person. For example, a central character may greet one person, guide another, and coordinate with several surrounding partners. This suggests a simple decomposition: instead of asking one model invocation to explain the entire group, we can sequentially compose pairwise interactions between the pivot and each newly added person. A pretrained two-person interaction diffusion model already contains a strong prior over pose realism, timing, and semantic interaction. The missing component is a mechanism that preserves this prior while enforcing group-level physical consistency and user control.

Based on this idea, we propose **PINO** (**P**erson-**I**nteraction **N**oise **O**ptimization), a training-free framework for long-duration and customizable group interaction generation. PINO uses a pretrained two-person diffusion model as a frozen backbone, then optimizes the initial diffusion noise for each pairwise generation step. Masked conditioning keeps the pivot motion fixed, while the newly added character is synthesized from a pair-specific text prompt. The optimization objective is defined directly in motion space and includes penalties for overlap avoidance, start/end root positions, movement regions, and orientation. This retains the semantic prior of the pretrained model while giving the user precise inference-time control.

PINO also supports long-duration interaction generation. Rather than retraining a dedicated long-horizon model, we extend a motion sequence by treating known frames as fixed conditions and optimizing the unobserved segment

Figure 1. **Person-Interaction Noise Optimization (PINO).** Starting from a pretrained two-person diffusion model, PINO generates an initial pair and then sequentially adds new participants around a pivot person through masked conditioning. The initial noise for the new pair is optimized with physics-aware and spatio-temporal penalties, enabling collision avoidance and controllable group composition without retraining.

through inpainting. This preserves continuity while keeping the same inference-time control mechanism used for group composition.

Experiments on InterGen-based generation show a consistent pattern: PINO yields the largest gains in physical plausibility and scalability, while preserving or modestly improving semantic metrics. In two-person generation, PINO eliminates overlap and sharply reduces penetration volume without degrading FID. In multi-person generation, the gap becomes larger, especially as the number of people increases. In motion extension, PINO improves both semantic fidelity and non-semantic realism.

Our contributions are threefold. First, we introduce a training-free framework that composes arbitrary-sized group interactions from a pretrained two-person diffusion model through sequential pivot-based generation. Second, we formulate inference-time person-interaction noise optimization with collision-aware and spatio-temporal penalties, enabling customizable control without retraining. Third, we show that the same mechanism extends to long-duration interaction generation through inpainting-based continuation.

2. Related Work

2.1. Diffusion Models for Human Motion

Diffusion models have become a standard backbone for text-to-motion generation because they produce diverse and realistic trajectories while supporting flexible conditioning [3, 10, 11, 14]. Subsequent work improved fidelity and controllability through masked modeling, latent-space generation, or stronger priors [2, 8]. These methods focus primarily on single-person motion and do not directly address multi-person physical constraints. PINO instead treats a pretrained motion diffusion model as a reusable prior and moves the control problem to inference time.

2.2. Interactive and Multi-Person Motion Generation

Two-person interaction generation has recently become feasible with specialized architectures and datasets, especially through InterGen [6]. More recent interactive generators further improve fidelity and reaction modeling, but they still target a fixed number of participants during training. For larger groups, FreeMotion [1] and Shan et al. [9] move toward open-domain multi-person generation, yet they model multiple people jointly and therefore inherit the difficulty of scaling network design and training data to larger groups. PINO takes a different route: it reuses a pretrained two-person model and composes larger groups sequentially, which makes the number of generated people an inference-time choice rather than a training-time design decision.

2.3. Inference-Time Control and Optimization

Inference-time control has emerged as an attractive alternative to retraining motion generators. Guided Motion Diffusion [4] and OmniControl [13] incorporate spatial constraints for single-person motion generation. Programmable Motion Generation [7] and Diffusion Noise Optimization [5] show that optimizing latent variables or diffusion noise can satisfy diverse motion-space constraints without task-specific retraining. In the multi-person setting, InterControl [12] uses joint-level interaction control for zero-shot synthesis. PINO is closest in spirit to these training-free methods, but differs in two ways: it explicitly decomposes group generation into pivot-centered pairwise interactions, and it uses the optimization to preserve physical consistency among already generated participants while allowing prompt switching across pairs.

3. Method

3.1. Problem Setup

We assume access to a pretrained text-conditioned two-person diffusion model G such as InterGen [6]. Given a text

Method	#Person in Network Design	#Person in Training Data	Order of Multi-Person Generation	Method
InterControl [12]	One	One	Sequential	ControlNet
FreeMotion [1]	One	Two	Sequential	ControlNet
Shan et al. [9]	Multiple	Multiple	Concurrent	Supervised Training
ProgMoGen [7]	One	Training-free	N/A (Single-Person)	Noise Optimization
Ours	Two (or multiple)	Training-free	Sequential	Noise Optimization

Table 1. Comparison of recent multi-person interaction generation methods, including single-person method ProgMoGen [7].

prompt p, the model maps an initial Gaussian noise tensor z to a motion sequence $\hat{X} = G(z, p)$ containing two interacting people. Each person is represented by a sequence of motion features; in the InterGen instantiation, a single person uses 262 features per frame, and optimization is performed on 210-frame windows.

Our goal is to generate a group of N interacting people, potentially with pair-specific prompts and motion constraints, without changing the pretrained weights of G. We also want the same mechanism to support motion extension beyond the native window length of the pretrained model.

3.2. Pivot-Based Pairwise Composition

The key design choice in PINO is to organize group generation around a *pivot* person shared across pairwise generations. We first sample a two-person interaction from prompt $p_{1,2}$ to obtain the pivot motion $X^{(1)}$ and the second participant motion $X^{(2)}$. To add a new participant k, we invoke the same two-person diffusion model again with a new prompt $p_{1,k}$, but now one input slot is fixed to the pivot motion:

$$\hat{X}^{(1,k)} = G(z_k, p_{1,k}; X^{(1)}, M), \qquad (1)$$

where M is a binary mask that preserves the pivot features and leaves the new participant unconstrained.

This masked conditioning is implemented through the inpainting interface of the frozen backbone. Concretely, the known coordinates of the pivot motion are copied into the denoiser output at every reverse step, so optimization only modifies the unconstrained participant. The result is a new motion $X^{(k)}$ that interacts with the pivot while remaining compatible with previously generated people. Repeating this process sequentially yields groups of arbitrary size.

This decomposition has two benefits. First, it avoids asking a single prompt to explain the roles of all participants at once. Each pair can have its own prompt, which allows prompt switching and clearer role assignment. Second, it leverages a pretrained interaction prior that already models close-range coordination, while group-level consistency is handled by optimization. The pivot assumption is also

computationally useful. Keeping one actor fixed across generations propagates a stable temporal reference into every new pair, which reduces the number of unconstrained bodies that the optimizer must coordinate simultaneously. In practice, this turns a hard many-body search problem into a sequence of smaller constrained updates while still allowing non-pivot participants to interact indirectly through the shared spatial layout.

3.3. Person-Interaction Noise Optimization

For each generation step, PINO optimizes the initial diffusion noise rather than retraining or fine-tuning the backbone. Let z_k^0 be an initial random noise sample for the pair consisting of the pivot and a new target person. PINO solves

$$z_k^\star = \arg\min_{z_k} \ \lambda_{\text{ov}}\mathcal{L}_{\text{overlap}} + \lambda_{\text{root}}\mathcal{L}_{\text{root}} + \lambda_{\text{reg}}\mathcal{L}_{\text{region}} + \lambda_{\text{ori}}\mathcal{L}_{\text{orientation}} \qquad (2)$$

where all losses are computed on the decoded motion.

Overlap loss. The default objective encourages the newly generated person to maintain a valid distance from the pivot and from all previously generated non-pivot participants. In the released implementation, this is expressed through root-distance penalties on the pelvis trajectory, with a minimum distance threshold for collision avoidance and an optional maximum threshold to prevent degenerate separations. When generating the k-th person, the loss also pushes that person away from already generated people other than the pivot.

Root-position loss. To support temporal anchors, PINO can constrain the start and end root positions of one or both participants. This is useful when the user needs a character to enter or exit at a prescribed location, or when the motion must align with external timing constraints.

Region loss. PINO can restrict a participant to remain inside or outside a spatial region. The implementation supports circular or rectangular regions on the ground plane, enabling scene-aware placement or motion zoning without retraining a scene-conditioned model.

Orientation loss. An orientation penalty aligns the participant's facing direction with a target direction. This is especially useful for prompts whose semantics depend on mutual attention, such as facing a pivot before approaching or gesturing.

The optimization is fully differentiable because gradients propagate from the motion-space objective through the denoising process back to the initial noise. In practice, we use Adam for up to 100 iterations with early stopping, following the optimization loop implemented in the released code.

Algorithm 1 PINO inference for group composition

1: Generate $(X^{(1)}, X^{(2)}) \leftarrow G(z_2, p_{1,2})$
2: **for** $k = 3$ to N **do**
3:     Sample z_k and fix pivot motion $X^{(1)}$ with mask M
4:     Optimize z_k using Eq. (2)
5:     Decode $X^{(k)} \leftarrow G(z_k^{\star}, p_{1,k}; X^{(1)}, M)$
6: **end for**
7: **return** $\{X^{(i)}\}_{i=1}^{N}$

GT selects any prior individual k as reference, not always person 1; fixing the pivot and using p₁,k contradicts the algorithm.

3.4. Prompt Switching and Customizable Roles

Because each pairwise generation step uses its own text prompt, PINO naturally supports prompt switching across participants. A single group motion can therefore mix semantically different relations around the same pivot, such as handshaking with one person while addressing or guiding another. This is difficult for shared-prompt approaches, which often blur individual roles when several people must simultaneously satisfy one global textual description.

3.5. Long-Duration Motion Extension

The same formulation can extend interactions beyond the native duration of the pretrained model. We keep a subset of frames fixed as observed motion, mask them through the inpainting interface, and optimize the noise for the remaining interval. This reuses the pretrained prior for local motion realism while allowing the unobserved portion to adapt to collision-aware and control-oriented objectives. In practice, the known segment acts as a temporal anchor at the transition boundary, producing longer interactions without training a separate long-horizon model.

4. Experiments

4.1. Experimental Setup

We instantiate PINO on InterGen [6] and denote the resulting system as *PINO-InterGen*. The evaluation follows the InterHuman protocol used by the provided codebase and reports both semantic and non-semantic metrics. Semantic quality is measured by FID, diversity, and R-precision when available. Physical plausibility is measured by overlap, penetration volume, foot skating, and maximum acceleration. For multi-person generation, we compare against InterGen with inpainting-based composition and against FreeMotion [1] where available.

Unless otherwise noted, PINO keeps the pretrained generator frozen and applies optimization only at inference time. This matters because improvements cannot be attributed to additional supervised training or changes in backbone capacity.

Method	Overlap ↓	PenVol. (cm^3) ↓	Foot Skate ↓	Max Acc. ↓
GT	0.029	471.75	0.099	0.074
InterGen	0.119	3112.72	**0.124**	**0.034**
PINO-InterGen	**0.000**	**275.65**	0.125	**0.034**

(a) Non-semantic metrics.

Method	FID ↓	Div. →	R-Prec. ↑ (Top3)
GT	0.983	7.921	0.715
InterGen	13.278	7.793	0.674
PINO-InterGen	**13.163**	**7.904**	**0.675**

(b) Semantic metrics.

Table 2. Evaluation of two-person interaction generation while avoiding overlap.

Method	Overlap↓	PenVol.↓	Foot Skate↓	Max Acc.↓
InterGen (inpainting)	0.766	25215.78	0.099	**0.030**
PINO-InterGen	**0.000**	**785.01**	**0.091**	0.031

Table 3. Evaluation of multi-person interaction generation

4.2. Two-Person Interaction Generation with Overlap Avoidance

We first evaluate whether PINO can improve physical plausibility in the base two-person setting without sacrificing semantic quality. Table 2 shows that it does. PINO-InterGen reduces overlap from 0.119 to 0.000 and penetration volume from 3112.72 to 275.65. At the same time, FID slightly improves from 13.278 to 13.163, diversity increases from 7.793 to 7.904, and R-precision is marginally higher.

These results are important because they isolate the effect of noise optimization from the more complex multi-person setting. The gain is not coming from a different motion prior; it comes from using the same pretrained prior more effectively under a physically informed objective.

4.3. Multi-Person Interaction Generation

We next evaluate the main setting of interest: composing larger groups by sequentially adding participants around a pivot. Table 3 compares PINO-InterGen against InterGen with inpainting-based multi-person composition. PINO reduces overlap from 0.766 to 0.000 and penetration volume from 25215.78 to 785.01, while also slightly improving foot skating. Maximum acceleration is nearly unchanged (0.031 vs. 0.030), indicating that the gain does not come from overly damped motions.

To study scaling, Table 4 reports pairwise quality as the group grows from two to five people using person 1 as the pivot. PINO-InterGen consistently achieves the best FID for every pair and dramatically lowers overlap at each step. The advantage becomes larger as more participants are added: for pair $(1, 5)$, FID drops from 19.501 to 16.911 and overlap drops from 0.977 to 0.069 compared with InterGen. Earlier pairs remain near zero overlap, which indicates that sequen-

Figure 2. Comparison of the generated multi-person interaction. The visualization highlights that PINO produces cleaner spacing and fewer severe collisions when new participants are added sequentially around a pivot.

Method	Pair	FID↓	Overlap↓	Foot Skate↓	Max Acc.↓
FreeMotion	(1,2)	19.383	0.255	**0.112**	**0.034**
	(1,3)	25.184	0.806	**0.122**	0.038
	(1,4)	25.812	0.964	0.127	0.040
	(1,5)	25.671	0.991	0.130	0.042
InterGen	(1,2)	13.100	0.119	0.126	**0.034**
	(1,3)	19.414	0.799	0.125	**0.036**
	(1,4)	19.386	0.937	**0.124**	**0.038**
	(1,5)	19.501	0.977	**0.124**	**0.039**
PINO-InterGen	(1,2)	**12.920**	**0.000**	0.127	**0.034**
	(1,3)	**17.170**	**0.002**	0.135	0.040
	(1,4)	**16.890**	**0.019**	0.138	0.043
	(1,5)	**16.911**	**0.069**	0.142	0.045

Table 4. Evaluation of multi-person interaction generation. From pair (1,2), interactions are generated incrementally using 1 as a pivot. Overlap is among all individuals generated up to that step.

Method	FID↓	Overlap↓	Foot Skate↓	Max Acc.↓
InterGen	20.390	0.089	0.081	0.036
PINO-InterGen	**18.930**	**0.0**	**0.054**	**0.025**

Table 5. Evaluation of semantic elements in two-person motion extension. Extended motions are cropped to match the ground truth length for evaluation.

Method	Overlap↓	PenVol.↓	Foot Skate↓	Max Acc.↓
InterGen (inpainting)	0.672	15622.16	0.070	0.044
PINO-InterGen	**0.031**	**1375.24**	**0.045**	**0.043**

Table 6. Evaluation of non-semantic elements in motion extension.

tial composition does not accumulate severe geometric failures as quickly as the baseline.

4.4. Long-Duration Motion Extension

We finally evaluate motion extension. In the semantic evaluation of Table 5, PINO-InterGen improves FID from 20.390 to 18.930, reduces overlap from 0.089 to 0.000, lowers foot skating from 0.081 to 0.054, and substantially lowers maximum acceleration from 0.036 to 0.025. In the nonsemantic extension benchmark of Table 6, PINO likewise improves every reported metric, including overlap (0.672 to 0.031), penetration volume (15622.16 to 1375.24), and foot skating (0.070 to 0.045).

Together, these results suggest that inference-time optimization is effective not only for adding more people, but also for extending interaction duration while preserving realism at the transition.

5. Analysis

5.1. Ablation on Motion Penalties

Table 7 isolates the role of different inference-time penalties. Starting from plain InterGen, adding the root-position loss eliminates positional error but does not address collisions and substantially increases region violations. Adding the overlap loss removes overlap entirely, confirming that the main physical gain in PINO is driven by explicit geometric control rather than being an incidental byproduct of prompt decomposition. Adding the region loss produces the best region-violation score (0.043), while the orientation loss sharply reduces orientation error from 1.0 to 0.208.

This ablation supports the design of Eq. (2): no single penalty solves all control requirements. Instead, the strength of PINO is that these constraints can be combined as needed at inference time, while the pretrained motion prior remains fixed.

5.2. Qualitative Observations

Fig. 2 and Fig. 4 provide qualitative evidence consistent with the metrics. Compared with direct multi-person com-

Figure 3. Visualization of the ablation study. Different penalties affect different aspects of the generated motion, with overlap-oriented terms primarily improving physical plausibility and orientation/region terms improving controllability.

position, PINO maintains clearer personal space and produces less entangled body configurations. The visualizations also suggest why pivot-based prompt switching is useful: the new participant can adopt a distinct role relative to the pivot instead of collapsing toward an averaged group behavior.

5.3. Discussion

The empirical pattern across all benchmarks is consistent. PINO's largest gains appear in collision-related metrics, especially overlap and penetration volume, and the margin widens as the composition problem becomes harder. Semantic fidelity is preserved in the base two-person setting and improves in motion extension, which indicates that optimizing the initial noise does not simply trade semantics

Figure 4. Qualitative results of multi-person interaction generation. PINO supports customizable pairwise interactions within a larger group while maintaining physically cleaner spacing.

for geometry. At the same time, some motion smoothness metrics remain close to the baseline rather than improving dramatically, suggesting that PINO's main benefit is better physical feasibility and controllability rather than a wholesale change in motion style.

6. Conclusion

We presented PINO, a training-free framework for arbitrary-sized and long-duration human interaction generation. PINO composes a group around a pivot person using a pretrained two-person diffusion model, and it optimizes the initial diffusion noise with motion-space penalties to en-

force physical plausibility and user control. Experiments show that this simple decomposition scales better than direct composition baselines, substantially reduces overlap and penetration, and supports motion extension without retraining. These results indicate that inference-time noise optimization is a strong and practical interface for turning pretrained interaction models into controllable group motion generators.

Method	Pos. Err.↓	Overlap↓	Reg. Viol.↓	Orient. Err.↓
InterGen	1.0	0.292	0.500	1.0
+ $\mathcal{L}_{\text{root}}$	**0.0**	0.333	0.917	1.0
+ $\mathcal{L}_{\text{overlap}}$	**0.0**	**0.0**	0.958	1.0
+ $\mathcal{L}_{\text{region}}$	0.083	**0.0**	**0.043**	1.0
+ $\mathcal{L}_{\text{orientation}}$	0.083	0.043	0.083	**0.208**

Table 7. Ablation study on motion penalties. Metrics include positional errors (Pos. Err.↓), overlap (Overlap↓), region violations (Reg. Viol.↓), and orientation errors (Orient. Err.↓). Positional errors are measured with a threshold of 20 cm, region violations with a threshold of 10 cm, and orientation errors with a threshold of 20 degrees. Lower values indicate better performance.

References

[1] Ke Fan, Junshu Tang, Weijian Cao, Ran Yi, Moran Li, Jingyu Gong, Jiangning Zhang, Yabiao Wang, Chengjie Wang, and Lizhuang Ma. Freemotion: A unified framework for number-free text-to-motion synthesis. 2024. 1, 2, 3, 4

[2] Chuan Guo, Yuxuan Mu, Muhammad Gohar Javed, Sen Wang, and Li Cheng. Momask: Generative masked modeling of 3d human motions. 2024. 1, 2

[3] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. pages 6840–6851, 2020. 2

[4] Korrawe Karunratanakul, Konpat Preechakul, Supasorn Suwajanakorn, and Siyu Tang. Guided motion diffusion for controllable human motion synthesis. pages 2151–2162, 2023. 2

[5] Korrawe Karunratanakul, Konpat Preechakul, Emre Aksan, Thabo Beeler, Supasorn Suwajanakorn, and Siyu Tang. Optimizing diffusion noise can serve as universal motion priors. 2024. 1, 2

[6] Han Liang, Wenqian Zhang, Wenxuan Li, Jingyi Yu, and Lan Xu. Intergen: Diffusion-based multi-human motion generation under complex interactions. pages 1–21, 2024. 1, 2, 4

[7] Hanchao Liu, Xiaohang Zhan, Shaoli Huang, Tai-Jiang Mu, and Ying Shan. Programmable motion generation for open-set motion control tasks. 2024. 1, 2, 3

[8] Yoni Shafir, Guy Tevet, Roy Kapon, and Amit Haim Bermano. Human motion diffusion as a generative prior. 2024. 2

[9] Mengyi Shan, Lu Dong, Yutao Han, Yuan Yao, Tao Liu, Ifeoma Nwogu, Guo-Jun Qi, and Mitch Hill. Towards open domain text-driven synthesis of multi-person motions. 2024. 1, 2, 3

[10] Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. 2021. 2

[11] Guy Tevet, Sigal Raab, Brian Gordon, Yoni Shafir, Daniel Cohen-Or, and Amit Haim Bermano. Human motion diffusion model. 2023. 1, 2

[12] Zhenzhi Wang, Jingbo Wang, Yixuan Li, Dahua Lin, and Bo Dai. Intercontrol: Zero-shot human interaction generation by controlling every joint. In *NeurIPS*, 2024. 1, 2, 3

[13] Yiming Xie, Varun Jampani, Lei Zhong, Deqing Sun, and Huaizu Jiang. Omnicontrol: Control any joint at any time for human motion generation. 2024. 2

[14] Mingyuan Zhang, Zhongang Cai, Liang Pan, Fangzhou Hong, Xinying Guo, Lei Yang, and Ziwei Liu. Motiondiffuse: Text-driven human motion generation with diffusion model. 46(6):4115–4128, 2024. 1, 2