Are Vision Transformers Always More Robust Than Convolutional Neural Networks?

Abstract

Since Transformer architectures have been popularised in Computer Vision, several papers started analysing their properties in terms of calibration, out-of-distribution detection and data-shift robustness. Most of these papers conclude that Transformers, due to some intrinsic properties (presumably the lack of restrictive inductive biases and the computationally intensive self-attention mechanism), outperform Convolutional Neural Networks (CNNs). In this paper we question this conclusion: in some relevant cases, CNNs, with a pre-training and fine-tuning procedure similar to the one used for transformers, exhibit competitive robustness. To fully understand this behaviour, our evidence suggests that researchers should focus on the interaction between pre-training, fine-tuning and the considered architectures rather than on intrinsic properties of Transformers. For this reason, we present some preliminary analyses that shed some light on the impact of pre-training and fine-tuning on out-of-distribution detection and data-shift.

1 Introduction

Transformers revolutionised natural language processing [Vaswani et al., 2017], and a standard procedure has become to pre-train transformers on large scale corpora to then fine-tune them on smaller datasets [Kalyan et al., 2021]. Since Transformers were introduced in Computer Vision [Dosovitskiy et al., 2020], several transformer variants have been introduced [Yuan et al., Touvron et al., 2020, Liu et al., 2021]. The literature points out that since transformers do not rely on the restrictive inductive bias of convolutions, they can capture long-range correlations in the input from the first layers through the self-attention mechanism and hence can leverage the massive amounts of data used to train them to learn better input embeddings. Several papers analysing the robustness of Transformer-based classifiers, indeed, claim Transformers achieve superior robustness with respect to convolutional classifiers.

In this paper we: (1) empirically show that some of the figures indicating a remarkable superiority of Transformers under data-shift and for out-of-distribution detection over convolutional alternatives are wrong or misleading, and in such cases the latter perform competitively; (2) argue that the parameter count should not be used as a proxy of the expressiveness of models (capacity) to pick pairs of models for comparisons, given such a strategy only measures efficiency (i.e. ability to provide better performance with less parameters); (3) propose a fine-tuning scheme that is more efficient than BiT [Kolesnikov et al., 2019] while producing state-of-the-art results for both Transformers and CNNs; (4) suggest the interaction between pre-training, fine-tuning and network architecture should be analysed in depth to deeply understand why in very similar settings (e.g. fine-tuning on CIFAR-10 or CIFAR-100) CNNs can both exhibit comparable performance to Transformers, and be outperformed by them. We also provide a preliminary analysis of the impact of fine-tuning.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

2 Assessing the robustness of a classifier to data-shift and out-of-distribution detection

Neural classifiers typically consist in a feature extractor $h = \phi(x)$ (where $x \in \mathbb{R}^d$ is the input, $h \in \mathbb{R}^h$ is the network embedding) followed by a linear logistic regression layer implemented through a linear layer followed by a softmax layer. The output of the softmax layer represent a distribution over the labels, and is used to both select a predicted label (the fraction of correct results is measured via the accuracy metric) and to extract uncertainty scores about such prediction. However, in most application domains of interest, no ground-truth uncertainty is available to evaluate the quality of the uncertainty scores produced.

For this reason, several downstream tasks have been devised to assess the usefulness of the uncertainty scores that can be extracted from a classifier's output. In this paper, besides measuring the accuracy, we also consider the following two important evaluation settings to measure the reliability of a classifier: calibration and out-of-distribution detection. For calibration, we report the ECE [Naeini et al., 2015] and AdaECE [Mukhoti et al., 2020]. We consider the accuracy and calibration performance both when the test set is i.i.d. with respect to the training set (i.e. IND test distribution), or when the test set undergoes a very specific form of data-shift: covariate shift (i.e. the set of labels is the same of the IND distribution, but the inputs come from a different region of the input space). For OOD detection we report the AUROC and AUPR [Hendrycks and Gimpel, 2016]. Refer to Appendix A for a more extensive discussion of these metrics.

3 Discussion of existing literature

Transformers are often regarded as more robust than Convolutional classifiers In the literature analysing the robustness of Transformers, it is common to point out their superior performance with respect to convolutional classifiers and to attribute it to the lack of strong inductive biases, and the ability of the self-attention mechanism to learn better representations. As we will show, some of the figures leading to this conclusion are wrong or unreliable. For a discussion of the most common baselines, refer to Appendix B. In this paper we consider ViT [Dosovitskiy et al., 2020] and BiT [Kolesnikov et al., 2019] variants as Transformers and CNN models, respectively.

The authors of [Zhang et al., 2021] define a taxonomy for some of the most popular data-shift datasets available for ImageNet and report the superior performance of DeiT[1] with respect to BiT under data-shift. However, they only consider the BiT-R50x1 architecture (the lowest capacity BiT variant) against several Transformer variants. The authors of [Fort et al., 2021] only considers BiT-R50x1 and BiT-R103x3 against ViT-B/16 to conclude that Transformers achieve better out-of-distribution detection performance when fine-tuned on smaller datasets (CIFAR-10 and CIFAR-100 [Krizhevsky et al.]). We will show BiT classifiers can indeed achieve comparable OOD detection performance. The authors of [Paul and Chen, 2021] report results for OOD detection on ImageNet-O and data-shift robustness on ImageNet-A and ImageNet-R, claiming transformers produce better performance. We will show in the case of ImageNet-O and -A, these findings are associated to mistakes or arbitrary choices in the evaluation procedure. We will also provide alternative performance figures on ImageNet-R. The authors of [Minderer et al., 2021], instead, perform a more extensive analysis that considers most of the relevant BiT/ViT variants. Their conclusion is that transformers are better calibrated than convolutional models, both on IND test sets and under data-shift. Our findings agree with their analysis.

The impact of pre-training Literature evidencing the usefulness of pre-training in order to improve out-of-distribution detection and data-shift generalization exists [Hendrycks et al., 2019a]. The authors of [Steiner et al., 2021] suggest some empirical methods to select the best pre-trained model for a downstream task (finding that high accuracy on pre-training dataset is a good predictor of fine-tuned accuracy). However, a proper understanding of how pre-training impacts on downstream task and how fine-tuning affects the performance is lacking. We provide some preliminary analyses about this topic in Appendix C.

---

[1]DeiT [Touvron et al., 2020] is a variant of ViT that can be trained directly on ImageNet-1K via distillation.

Methods	Params	Clean Data ImageNet-1K (Test)			Domain-Shift ImageNet-A			ImageNet-R		
		Accuracy (↑)	ECE (↓)	AdaECE (↓)	Accuracy (↑)	ECE (↓)	AdaECE (↓)	Accuracy (↑)	ECE (↓)	AdaECE (↓)
R50x1	25M	73.98	3.54	3.52	39.75	15.55	15.55	10.97	42.91	42.91
R50x3	217M	77.95	6.55	6.50	46.38	14.69	14.69	24.01	34.50	34.50
R101x1	44M	75.87	5.10	5.10	41.74	12.23	12.23	16.52	36.52	36.52
R101x3	387M	78.14	7.67	7.67	47.02	15.77	15.77	27.24	32.86	32.85
R152x2	232M	77.86	6.59	6.54	48.01	15.41	15.41	27.25	31.95	31.95
152x4	936M	78.24	9.28	9.26	47.62	15.29	15.29	31.16	29.52	29.52
ViTB-16	86M	78.09	1.59	1.57	24.12	23.12	23.12	43.22	5.09	5.09
ViTL-16	304M	84.40	1.92	1.86	47.50	11.6	11.6	61.57	3.02	3.02

Table 1: ImageNet-1K scale classifications and calibration experiments on clean data and under data-shift.

4 Experiments

Our experiments show that CNNs can achieve comparable reliability to Transformers for classification both at ImageNet-1K scale and on small-scale classification (CIFAR-10/CIFAR-100) when it is performed by fine-tuning a model that was pre-trained on ImageNet-1K. We do not compare models based on the number of parameters, as we believe a comparison based on this metric to be misleading. Refer to Appendix D for further discussion of the topic.

4.1 Imagenet-1K scale experiments

Accuracy and calibration on clean data and under data-shift   In Table 1 we report the accuracy and calibration results for Imagenet-1K. The results seem consistent with those reported [Minderer et al., 2021] (i.e. transformers are better calibrated).

As for the ImageNet-A results, we observe the dataset only contains examples belonging to 200 classes. For this reason, the authors of the dataset [Hendrycks et al., 2019b] only consider the logits associated with such 200 classes[2]; on the other hand the Paul et al. [Paul and Chen, 2021] use the logits associated with all the classes. While their evaluation methodology shows the superiority of transformers, applying the Hendryck's evaluation procedure allows us to conclude that: (1) in terms of accuracy and calibration, all the CNNs outperform ViT-B/16, (2) the high-capacity CNNs achieve competitive or better accuracy than ViT-L/16, but have worse calibration. Similarly to ImageNet-A, Paul et al. follow a different evaluation procedure from Hendrycks et al. also for ImageNet-R. Following Hendrycks et al., we observe transformers are significantly more robust than convolutional networks for this kind of distribution shift both in terms of accuracy and calibration.

Out-of-distribution detection performance   We point out several methodological errors that yield to the erroneous belief that ImageNet-O is a particularly hard dataset to discriminate from ImageNet-1K. In particular, [Hendrycks et al., 2019b, Paul and Chen, 2021] report extremely low values of the AUPR metric. We observe that ImageNet-O contains only 2000 samples belonging to 200 classes, while the subset of ImageNet-1K taken as IND test set contains 10000 samples [3]. The AUPR is a metric that is extremely sensitive to: (1) class imbalance (the OOD dataset is 5x smaller than the IND dataset), (2) choice of the positive class. In particular, [Hendrycks et al., 2019b] arbitrarily choose to indicate OOD points as positive class. In Table 2 we observe that flipping the positive class yields dramatic changes in the AUPR. We also perform experiments rebalancing the proportion of OOD and IND samples by resampling each OOD sample 4 more times (so that both IND and OOD datasets have 10000 samples each)[4]. The application of this strategy yields to much less relevant changes when the choice of the positive class is flipped. Across all the considered settings, the AUROC does not vary, and hence should be the privileged metric to describe OOD detection performance. These results allow us to conclude that ImageNet-O is evidently not as hard to distinguish from ImageNet as it is believed to be: the mentioned papers report solely results from the third column from the

---

[2]See code-base: `https://github.com/hendrycks/natural-adv-examples`; we report the accuracy in absolute value (i.e. not the accuracy gap with respect to the accuracy on the same classes with respect to ImageNet-1K)

[3]Refer to their code-base:`https://github.com/hendrycks/natural-adv-examples`

[4]We could rebalance them by randomly sampling 2000 out of the 10000 IND points, but this induces randomness in the metrics; we also observed that the average of this strategy coincides with the other balancing strategy we propose.

| | IND=1,OOD=0 | | | | IND=0,OOD=1 | | | |
| Methods | Imbalanced | | Balanced | | Imbalanced | | Balanced | |
	AUROC (↑)	AUPR (↑)	AUROC (↑)	AUPR (↑)	AUROC (↑)	AUPR (↑)	AUROC (↑)	AUPR (↑)
R50x1	65.17	90.15	65.17	65.81	65.17	23.30	65.17	60.13
R50x3	74.56	92.30	74.56	71.28	74.56	36.26	74.56	72.49
R101x1	70.34	91.35	70.34	68.75	70.34	28.53	70.34	66.11
R101x3	77.32	93.40	77.32	74.84	77.32	38.74	77.32	74.66
R152x2	77.46	93.51	77.46	75.23	77.46	38.24	77.46	74.43
R152x4	80.07	94.39	80.07	78.10	80.07	44.25	80.07	78.17
ViTB-16	79.89	95.26	79.89	82.30	79.89	36.77	79.89	73.77
ViTL-16	90.60	97.85	90.60	91.27	90.60	64.58	90.60	88.90

Table 2: ImageNet-O: Out-of-distribution experiments

right of Table 2). We also observe that the performance gap between R101x1, R101x3, R152x2 and R152x4 with respect to ViT-B/16 to be not dramatic and perhaps caused by random chance. On the other hand, the AUROC of ViT-L/16 is significantly better.

4.2 CIFAR scale experiments (results in Appendix E)

How we change the BiT fine-tuning recipe   Differently from the BiT [Kolesnikov et al., 2019] fine-tuning recipe, we only train for 60 epochs (against approximately 103 epochs of BiT), with learning rate 0.001 or 0.0001 and multiplying it by 0.1 at epochs 20 and 40. We report the best performing learning rate configuration, and observe that the downstream performance can significantly vary based on such hyperparameter (shuffling the ranking among methods). We also don't use Mixup, and directly upscale the 32x32 CIFAR-10/100 images to the resolution of 224x224. We apply random flipping for augmentation. No weight decay is used.

Accuracy and calibration on clean data and data-shifted inputs   In Tables 4 and 5 we report the accuracy and calibration results for CIFAR-10 and CIFAR-100 respectively. For CIFAR-10, the CNNs can be competitive with respect to transformers in accuracy and calibration. For instance, R101x3 is competitive with ViT-B/16. Pre-training on ImageNet-21K does not significantly improve the performance of transformers, but it does for Convolutional models, allowing lower capacity models to be more competitive. Yet, observe how the performance of R101x3 pretrained on ImageNet-21K is inferior to when pretrained on ImageNet-1K. Similar observations hold under data-shift (we consider the CIFAR-10-C and CIFAR-100-C datasets [Hendrycks and Dietterich, 2019]), except that the gap between Transformers and CNNs is morere markable and the Transformers are generally better calibrated.

Out-of-distribution detection performance   In Tables 4 and 5 we report the results for out-of-distribution detection performance using CIFAR-10/100 and SVHN as out-of-distribution datasets. On far-OOD detection (CIFAR vs SVHN) some convolutional models achieve competitive performance. On near-OOD detection (CIFAR-10 vs CIFAR-100 or vice versa), although slightly inferior, in CIFAR-10 vs CIFAR-100 CNNs are competitive, while the gap increases for CIFAR-100 vs CIFAR-10.

5   Discussion and Conclusion

In several relevant settings, CNNs pre-trained on ImageNet-1K can be competitive with Transformers pre-trained on ImageNet-21K and fine-tuned on ImageNet-1K. This suggests the discrepancy in performance in other cases in which Transformers exhibit superior performance might not be fully explained just by intrinsic properties of transformers, and might lie in the interplay between pre-training, fine-tuning and architecture. We leave further experiments using DeiT [Touvron et al., 2020] (which is solely pre-trained on ImageNet-1K) or for CNNs pre-trained on ImageNet-21K and fine-tuned on ImageNet-1K to future research. We will also consider other forms of data-shift (e.g. ImageNet-C [Hendrycks and Dietterich, 2019], ImageNet-9 [Xiao et al., 2020]). We will also leave to future research the analysis of the variance of all the metrics considered using multiple seeds and other BiT variants. Indeed, the small discrepancies might be just due to the inherent randomness of the fine-tuning. In Appendix C we report a preliminary analysis of the impact of fine-tuning.

References

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009. doi: 10.1109/CVPR.2009.5206848.

Yukun Ding, Jinglan Liu, Jinjun Xiong, and Yiyu Shi. Revisiting the evaluation of uncertainty estimation and its application to explore model Complexity-Uncertainty Trade-Off. March 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. October 2020.

Stanislav Fort, Jie Ren, and Balaji Lakshminarayanan. Exploring the limits of Out-of-Distribution detection. June 2021.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016. doi: 10.1109/CVPR.2016.90.

D Hendrycks, K Lee, and M Mazeika. Using pre-training can improve model robustness and uncertainty. *Conference on Machine . . .* , 2019a.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *Proceedings of the International Conference on Learning Representations*, 2019.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and Out-of-Distribution examples in neural networks. October 2016.

Dan Hendrycks, Kevin Zhao, Steven Basart, Jacob Steinhardt, and Dawn Song. Natural adversarial examples. July 2019b.

Katikapalli Subramanyam Kalyan, Ajit Rajasekharan, and Sivanesan Sangeetha. AMMUS : A survey of transformer-based pretrained models in natural language processing. August 2021.

Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (BiT): General visual representation learning. December 2019.

Alex Krizhevsky, Vinod Nair, and Geoffrey Hinton. Cifar-10 (canadian institute for advanced research). URL http://www.cs.toronto.edu/~kriz/cifar.html.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. March 2021.

Michael McCloskey and Neal J. Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. volume 24 of *Psychology of Learning and Motivation*, pages 109–165. Academic Press, 1989. doi: https://doi.org/10.1016/S0079-7421(08)60536-8. URL https://www.sciencedirect.com/science/article/pii/S0079742108605368.

Matthias Minderer, Josip Djolonga, Rob Romijnders, Frances Hubis, Xiaohua Zhai, Neil Houlsby, Dustin Tran, and Mario Lucic. Revisiting the calibration of modern neural networks. June 2021.

Jishnu Mukhoti, Viveka Kulharia, Amartya Sanyal, Stuart Golodetz, Philip HS Torr, and Puneet K Dokania. Calibrating deep neural networks using focal loss. In *NeurIPS*, 2020.

Mahdi Pakdaman Naeini, Gregory F Cooper, and Milos Hauskrecht. Obtaining well calibrated probabilities using bayesian binning. *Proc. Conf. AAAI Artif. Intell.*, 2015:2901–2907, January 2015.

Jeremy Nixon, Mike Dusenberry, Ghassen Jerfel, Linchuan Zhang, and Dustin Tran. Measuring calibration in deep learning. September 2019.

Sayak Paul and Pin-Yu Chen. Vision transformers are robust learners. May 2021.

205 Tal Ridnik, Emanuel Ben-Baruch, Asaf Noy, and Lihi Zelnik-Manor. Imagenet-21k pretraining for
206   the masses, 2021.

207 Rebecca Roelofs, Nicholas Cain, Jonathon Shlens, and Michael Curtis Mozer. Mitigating bias in
208   calibration error estimation. September 2020.

209 Andreas Steiner, Alexander Kolesnikov, Xiaohua Zhai, Ross Wightman, Jakob Uszkoreit, and Lucas
210   Beyer. How to train your ViT? data, augmentation, and regularization in vision transformers. June
211   2021.

212 Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé
213   Jégou. Training data-efficient image transformers & distillation through attention. December 2020.

214 Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł Ukasz
215   Kaiser, and Illia Polosukhin. Attention is all you need. In I Guyon, U V Luxburg, S Bengio,
216   H Wallach, R Fergus, S Vishwanathan, and R Garnett, editors, *Advances in Neural Information
217   Processing Systems*, volume 30. Curran Associates, Inc., 2017.

218 Kai Xiao, Logan Engstrom, Andrew Ilyas, and Aleksander Madry. Noise or signal: The role of image
219   backgrounds in object recognition. *ArXiv preprint arXiv:2006.09994*, 2020.

220 Li Yuan, Yunpeng Chen, Tao Wang, Weihao Yu, Yujun Shi, Zihang Jiang, Francis E H Tay, Jiashi
221   Feng, and Shuicheng Yan. Tokens-to-Token ViT: Training vision transformers from scratch on
222   ImageNet.

223 Chongzhi Zhang, Mingyuan Zhang, Shanghang Zhang, Daisheng Jin, Qiang Zhou, Zhongang Cai,
224   Haiyu Zhao, Shuai Yi, Xianglong Liu, and Ziwei Liu. Delving deep into the generalization of
225   vision transformers under distribution shifts. June 2021.

A   Evaluation Metrics Details

Calibration metrics   Calibration is often defined via the Expected Calibration Error: $\mathbb{E}_{\hat{p}}[|P(\hat{y} = y|\hat{p} = p) - p|]$, i.e. the mismatch between probability that the model's predicted label $\hat{y}$ is actually y given that the model's confidence $\hat{p}$ (i.e. maximum probability of the softmax layer) takes the value of p and p itself. Informally, it's the expectation of the absolute difference between the model's accuracy and confidence. For instance, a classifier is calibrated if, whenever its prediction's confidence is 90%, it is correct 90% of the times. The theoretical Expected Calibration Error is often estimated by splitting the confidence range into M equally spaced bins and taking the weighted average of the bins' accuracy/confidence mismatch (i.e. $ECE \approx \sum_{m=1}^{M} |B_m||A(B_m) - C(B_m)|/n$, where n is the number of samples, $A(B_m)$ and $C(B_m)$ are the accuracy and the average confidence of the points in the bin B_m respectively [Naeini et al., 2015]. To alleviate the bias of this estimator [Ding et al., 2019], adaptive binning techniques that induce the same number of samples in each bin (reducing the impact of varying density of confidences on the estimator) have been proposed [Roelofs et al., 2020, Nixon et al., 2019, Mukhoti et al., 2020]. For this reason, we will also estimate this quantity via the Adaptive ECE (AdaECE) [Mukhoti et al., 2020].

Out-of-distribution detection metrics   Defined as the ability of the classifier to correctly detect samples whose class is not among the set of classes it has been trained on [Hendrycks and Gimpel, 2016]. The evaluation procedure takes the test set corresponding to the training set (considered as the in-didstribution (IND) set) and the test set of another dataset (the out-of-distribution (OOD) set) with no label overlapping with the in-domain test set. Both sets are fed to the classifier, for each point an uncertainty score is computed on top of the softmax output, and a binary thresholding classifier is used to distinguish between the IND and OOD set. Since the choice of the threshold depends on the risk exposure desired for a certain application, a general evaluation procedure considers all the risk thresholds by measuring the Area Under Receiver Operating Characteristic curve (AUROC) or the Area Under Precision-Recall curve (AUPR), which respectively plot the true positive and false positive rates or the precision and recall as the decision threshold is varied.

B   Further literature discussion

Transformers and Convolutional Classifiers   In this paper we consider a popular transformer architecture, whose robustness has been extensively analysed in the literature: ViT [Dosovitskiy et al., 2020]. ViT [Dosovitskiy et al., 2020] represents the first adaptation of the original Transformer architecture [Vaswani et al., 2017] to the task of Image Classification; to achieve ImageNet-1K [Deng et al., 2009] classification performance comparable with state-of-the-art convolutional classifiers, the model needs to be pre-trained on large-scale datasets first (for what we are concerned, ImageNet-21K [Ridnik et al., 2021]).

The most common convolutional baseline used in Transformer papers is BiT [Kolesnikov et al., 2019], a ResNet [He et al., 2016] variant that has been shown to achieve state-of-the-art accuracy on ImageNet classification and that, with an appropriate fine-tuning procedure, transfers well to many other datasets.

Several variants of both ViT and BiT exist. We will consider the following transformer variants ViT-B/16 and ViT-L/16[5], where B and L indicate the capacity (B = Base, L = Large), while 16 or 32 indicates the token patch size. The most popular BiT variants are R50x1, R50x3, R101x1, R101x3 and R152x2, R152x4 (where R50/101/152 indicates the ResNet variant, and the multiplicative factor scales the number of channels). For our experiments we use the checkpoints available in the timm library: `https://fastai.github.io/timmdocs/`

C   A preliminary analysis of fine-tuning

Fine-tuning might incur in catastrophic forgetting   Let us consider R101x3 and ViT-L/16 fine-tuned on CIFAR-10 as described before. We take snapshots before starting the fine-tuning (Epoch 0) and for the first 2 epochs of fine-tuning. We aim to understand how the features of ImageNet-1K and CIFAR-10 change over the fine-tuning. For a fair comparison, we discard all examples in ImageNet-1K whose class does not map to a class contained in CIFAR-10 in the ImageNet hierarchy. We also discard the class "deer" in CIFAR-10, which is not present in ImageNet. We also consider the effect of the corruption induced by upscaling CIFAR-10 from 32x32 to 224x224, by simulating a similar form of corruption by downscaling ImageNet-1K images to 32x32 and then back to 224x224 (we call this evaluation setting ImageNet-1K ↓ 32 ↑ 224). For Epoch 0, we feed the three datasets to the pre-trained networks, and map the 1000-dimensional output to the CIFAR-10 labels set to measure Accuracy and Calibration. For Epochs 1 and 2, the head of the pre-trained networks has been replaced by a 10-dimensional output. We measure the Accuracy and Calibration on this output. As it can be seen from Table 3, both Transformers and CNNs start with a similarly high accuracy on ImageNet1K (97.90 and 96.81 respectively, making Transformers better), but CNNs exhibit better calibration. On ImageNet-1K ↓ 32 ↑ 224 the accuracy drops and the calibration gets worse for both, with Transformers having better accuracy, and CNNs having better calibration. On CIFAR-10, both models have comparable accuracy to the one they have ImageNet1K↓ 32 ↑ 224, showing the performance drop on CIFAR-10 with respect to ImageNet-1K is explained by the corruption induced by the resolution upscaling. Also in this case transformers have better accuracy and worse calibration. After the first epoch of fine-tuning, the ImageNet1K and ImageNet1K ↓ 32 ↑ 224 accuracies drop dramatically (with transformers having better accuracy, and for ImageNet1K also better calibration) while the CIFAR-10 accuracy and calibration improve dramatically. Given the similarity in performance at Epoch 0 on ImageNet1K ↓ 32 ↑ 224 and CIFAR-10, we infer the network is forgetting important features that were needed to maintain a good accuracy on ImageNet1K ↓ 32 ↑ 224, despite the datasets being so similar that the Epoch 0 accuracy and calibration are similar. This phenomenon seems to be somehow related to catastrophic forgetting [McCloskey and Cohen, 1989]. We leave to future research a more extensive investigation of the phenomenon at a finer resolution, using different architectures and fine-tuning strategies.

Where OOD inputs are mapped while fine-tuning?   In this paragraph we describe some insights we derived by measuring the distance of the embeddings of CIFAR-10, CIFAR-100 and SVHN datasets from 0. We consider pre-trained checkpoints of ViT-L/16 fine-tuned on ImageNet-1K and then fine-tuned on CIFAR-10 for 1 epoch. Consider Figure 1. At Epoch 0 (left-most) all three

---

[5]We omit ViT-B/32 ViT-L/32 since they always underperform with respect to ViT-B/16 and ViT-L/16 [Paul and Chen, 2021]

Epochs		ImageNet1K			ImageNet1K ↓ 32 ↑ 224			CIFAR10		
		0	1	2	0	1	2	0	1	2
ResNetv2-101x3	Acc	96.81	23.82	23.15	87.30	26.24	21.6	86.87	97.99	98.54
	ECE	9.56	41.59	41.71	19.07	42.56	49.31	19.81	0.53	0.64
	AdaECE	9.85	41.59	51.71	19.14	42.56	49.31	19.79	0.42	0.60
ViT-L/16	Acc	97.90	31.59	31.42	89.29	29.09	29.27	91.93	98.32	99.00
	ECE	10.89	40.15	39.51	28.99	45.02	44.10	35.80	0.63	0.43
	AdaECE	10.89	40.15	39.51	28.99	45.02	44.10	35.80	0.60	0.36

Table 3: Fine-tuning accuracy and calibration over the first two epochs of training for ImageNet1K and ImageNet1K ↓ 32 ↑ 224 (both restricted to classes that can be mapped to CIFAR-10) and CIFAR-10

Figure 1: **First row: Epoch 0. Second row: Epoch 1**. From left to right, in the first column we report the histogram of the distances of the embeddings of CIFAR-10,CIFAR-100 and SVHN from the 0 of the embedding space. In the second column we report a t-SNE projection containing all three datasets. In the third column, we report the t-SNE projection reported in the second column, but removing the dots associated with CIFAR-100 and SVHN, and assigning to each CIFAR-10 class a different colour.

datasets are projected very close to 0 and the datasets are not distinguishable from the t-SNE plot. The CIFAR-10 classes are not distinguisheable from the t-SNE, given the high accuracy in Table 3 we can conjecture the class separation is disturbed by the presence of the other datasets somehow, but is visible to the classifier. At Epoch 1 (middle) all three datasets are now projected much further away from the 0, and the t-SNE plot shows the SVHN dataset is clearly distinguishable form the other two, while some overlapping exists between CIFAR10 and CIFAR100. In CIFAR100, class clusters are not visible, while they are in CIFAR10.

The fact CIFAR-10 embeddings lie much closer to 0 at Epoch 0 and the classification accuracy on it is still 91.93, suggests that the scale of the regions of the embedding space where IND/OOD points are mapped for a ViT checkpoint pre-trained on ImageNet is much smaller than the one for a fine-tuned checkpoint. This phenomenon requires further investigation also in the case of CIFAR-100 and CNNs, as this increased scale is a clear sign that the embedding space is undergoing a drastic change that yields just a small improvement in accuracy on CIFAR10 (about 10% or less) but significantly damages the accuracy on corresponding classes in ImageNet1K (refer to Table 3).

D   Should the number of parameters of a model be considered when picking pairs of models to compare?

We would like to point out that, although assuming the number of parameters of a model to be a proxy of its capacity is a crude but often convenient approximation, it can be misleading. For this reason, the choice of performing a comparison between Transformer and Convolutional architectures (as done in [Paul and Chen, 2021]) solely based on the parameter count should be discouraged, as

Methods	Clean Data			Domain-Shift			Out-of-Distribution			
	CIFAR10 (Test)			CIFAR10-C			CIFAR100		SVHN	
	Accuracy ($\uparrow$)	ECE ($\downarrow$)	AdaECE ($\downarrow$)($\uparrow$)	Accuracy ($\uparrow$)	ECE ($\downarrow$)	AdaECE ($\downarrow$)($\uparrow$)	AUROC ($\uparrow$)	AUPR ($\uparrow$)	AUROC ($\uparrow$)	AUPR ($\uparrow$)
R50x1-1K-0.001	97.62	1.73	1.69	85.75	10.17	10.16	95.90	95.69	97.42	98.79
R50x3-1K-0.001	98.62	1.00	0.97	89.22	8.09	8.08	97.07	97.14	98.55	99.31
R101x1-1K-0.001	98.14	1.44	1.43	88.41	8.41	8.38	96.88	97.04	97.29	98.77
R101x3-1K-0.001	98.37	0.96	0.96	91.28	6.38	6.36	97.87	97.99	98.94	99.52
ViT-B/16-1K-0.001	98.91	0.77	0.75	92.48	5.23	5.21	97.92	97.90	99.35	99.71
ViT-L/16-1K-0.0001	99.14	0.50	0.50	94.64	2.93	2.90	98.84	98.88	99.80	99.91
R50x3-21k-0.001	98.59	1.04	1.01	87.86	8.70	8.68	97.44	97.51	99.19	99.64
R101x1-21k-0.001	98.45	1.16	1.13	88.97	7.74	7.72	97.22	97.32	98.90	99.51
R101x3-21k-0.001	97.91	1.51	1.45	84.55	10.86	10.84	96.19	95.94	98.41	99.27
R152x2-21k-0.001	98.74	0.91	0.91	90.90	5.88	5.86	97.97	98.03	99.03	99.52
ViT-B/16-21k-0.001	98.82	0.90	0.89	92.37	5.39	5.37	97.87	97.88	99.31	99.68
ViT-L/16-21k-0.001	99.24	0.51	0.51	95.07	3.31	3.29	98.73	98.87	99.76	99.90

Table 4: CIFAR-10 Experiments. To each method name we append whether the fine-tuned checkpoint starts from a ImageNet-1K (1K) or ImageNet-21K (21K). Implicitly, all ViTs fine-tuned on ImageNet-1K were pre-trained on ImageNet-21K, so it might be not fair excluding from the comparison BiTs fine-tuned on ImageNet-21K. After we append the best learning rate. We observe that the other considered learning rate has often dramatically different performance. We will also consider more BiT variants in future research.

Methods	Clean Data			Domain-Shift			Out-of-Distribution			
	CIFAR10 (Test)			CIFAR10-C			CIFAR100		SVHN	
	Accuracy ($\uparrow$)	ECE ($\downarrow$)	AdaECE ($\downarrow$)($\uparrow$)	Accuracy ($\uparrow$)	ECE ($\downarrow$)	AdaECE ($\downarrow$)($\uparrow$)	AUROC ($\uparrow$)	AUPR ($\uparrow$)	AUROC ($\uparrow$)	AUPR ($\uparrow$)
R50x1-1K-0.0001	86.22	6.28	6.13	62.23 ± 0.00	18.70 ± 0.00	18.68 ± 0.00	85.30	85.45	86.38	93.87
R50x3-1K-0.001	90.89	6.05	6.02	69.83 ± 0.00	18.82 ± 0.00	18.81 ± 0.00	90.90	90.80	91.33	95.88
R101x1-1K-0.001	90.43	6.09	6.09	68.86 ± 0.00	19.14 ± 0.00	19.13 ± 0.00	89.77	89.63	88.51	94.69
R101x3-1K-0.001	92.25	5.04	5.02	73.74 ± 0.00	16.01 ± 0.00	16.00 ± 0.00	92.60	92.69	90.63	95.64
ViT-B/16-1K-0.0001	93.32	4.17	4.17	78.32 ± 0.00	13.19 ± 0.00	13.17 ± 0.00	94.78	94.79	94.02	97.29
ViT-L/16-1K-0.001	93.98	4.00	3.94	83.38 ± 0.00	10.62 ± 0.00	10.61 ± 0.00	96.63	96.81	94.80	97.77
R50x3-21k-0.0001	90.15	5.22	5.17	67.50 ± 0.00	15.64 ± 0.00	15.63 ± 0.00	90.43	90.63	94.79	97.86
R101x1-21k-0.001	90.95	5.74	5.74	68.80 ± 0.00	18.47 ± 0.00	18.46 ± 0.00	90.61	90.48	85.86	93.06
R101x3-21k-0.001	91.41	4.49	4.45	70.58 ± 0.00	14.75 ± 0.00	14.73 ± 0.00	92.56	92.95	94.67	97.80
R152x2-21k-0.001	92.92	4.49	4.48	75.55 ± 0.00	14.20 ± 0.00	14.19 ± 0.00	93.34	93.43	94.22	97.44
ViT-B/16-21k-0.001	93.17	4.45	4.41	78.27 ± 0.00	13.26 ± 0.00	13.24 ± 0.00	94.16	94.09	94.48	97.56
ViT-L/16-21k-0.001	93.44	4.14	4.13	82.58 ± 0.00	11.25 ± 0.00	11.24 ± 0.00	95.66	95.90	91.39	96.07

Table 5: CIFAR-100 Experiments. To each method name we append whether the fine-tuned checkpoint starts from a ImageNet-1K (1K) or ImageNet-21K (21K). Implicitly, all ViTs fine-tuned on ImageNet-1K were pre-trained on ImageNet-21K, so it might be not fair excluding from the comparison BiTs fine-tuned on ImageNet-21K. After we append the best learning rate. We observe that the other considered learning rate has often dramatically different performance. We will also consider more BiT variants in future research.

this comparison would only capture the efficiency of the model (i.e. providing better performance with less parameters)[6]. An obvious example of why we do not pick paris of models for comparison based on the parameter count can be given by comparing ViT-B/16 and ViT-L/16 to their respective ViT-B/32 and ViT-L/32 variants. The latter both contain almost 2 million parameters more than the former ones, yet they always dramatically underperform with respect to the former in all cases considered in [Paul and Chen, 2021]. The parameter count does not fully represent the expressiveness of the model and how easily the optimisation procedure can find good solutions for its parameters. For this reason, we do not perform a comparison between CNNs and Transformers based on the number of their parameters.

E   Additional results

For space reasons, here we report Tables 4 and 5.

---

[6]It is evident that Transformers often are more efficient than CNNs.