Beyond Code Pairs: Dialogue-Based Data Generation for LLM Code Translation

Abstract

Large language models (LLMs) have shown remarkable capabilities in code translation, yet their performance deteriorates in low-resource programming domains such as Fortran and emerging frameworks like CUDA, where high-quality parallel data are scarce. We present an automated dataset generation pipeline featuring a dual-LLM Questioner–Solver design that incorporates external knowledge from compilers and runtime feedback. Beyond traditional source–target code pair datasets, our approach additionally generates (1) verified translations with unit tests for assessing functional consistency, and (2) multi-turn dialogues that capture the reasoning process behind translation refinement. Applied to Fortran→C++ and C++→CUDA, the pipeline yields 3.64k and 3.93k dialogues, respectively. Fine-tuning on this data yields dramatic improvements in functional correctness, boosting unit test success rates by over 56% on the challenging C++-to-CUDA task. We show this data enables a 7B open-weight model to significantly outperform larger proprietary systems on key metrics like compilation success.

1 Introduction

Automated code translation has long been a goal in programming languages and systems research, enabling developers to migrate software across languages, frameworks, and hardware platforms (Ahmad et al., 2021; Feng et al., 2020; Lachaux et al., 2020). In high-performance computing (HPC) and scientific computing, this problem is particularly pressing since legacy codes need to interoperate with modern ecosystems while new frameworks such as CUDA and OpenMP continue to emerge to exploit specialized hardware (Czarnul et al., 2020; Dhruv and Dubey, 2025). Large language models (LLMs) have recently demonstrated impressive capabilities in code understanding and generation, motivating their application to code translation. Yet their effectiveness is uneven, with good results in popular languages such as Python and Java, but substantially weaker performance in low-resource domains and specialized frameworks where training data is scarce and structural complexity is high. For example, LLMs often produce translations that compile but fail unit tests or generate code that is syntactically invalid without guidance from external tools (Chen et al., 2024).

Agent-based approaches have been widely adopted to address the limitations of LLMs in code translation. Most existing systems follow a source-to-target workflow (Dearing et al., 2024; Bitan et al., 2025; Chen et al., 2025), where multiple agents iteratively perform translation, verification, and refinement until a syntactically valid target program is produced (Figure 1, up). The resulting outputs are typically source–target code pairs, which are well suited for traditional supervised learning pipelines (Chen et al., 2021). Although these approaches can produce correct translations, they discard valuable intermediate information that could further enhance the performance of LLMs. These information, such as compiler feedback, runtime diagnostics, and interactions with external tools or scripts, has been shown to be crucial for enabling deeper reasoning about program semantics and functional behavior (Ding et al., 2024).

To address this gap, we introduce a dual-LLM Questioner–Solver design within each LLM agent, which automatically collects and generates reasoning process data during the agent-based translation workflow (Figure 1, bottom). Instead of producing only final code pairs, our framework automatically generates question-solution data covering intermediate queries, responses, and tool interactions that occur during translation. The Questioner analyzes the current state, formulates targeted questions, and incorporates external signals such as compiler errors or runtime outputs, while the Solver executes translations, generates unit tests, and pro-

Figure 1: High-level architecture of the Questioner–Solver module in our design to replace the single LLM core in regular LLM agent frameworks. The Questioner analyzes state and formulates queries using dialogue memory and external tools (e.g., compilers, runtime environments, scripts), while the Solver generates translations, unit tests, and repairs. Their iterative interaction enables reasoning separation, external knowledge integration, and progressive refinement of translations.

poses fixes. This interaction yields multi-turn dialogues that not only capture verified source–target programs but also encode the decision-making and error-correction steps behind them. By embedding this structured reasoning into the dataset, our approach enables fine-tuned LLMs to learn both the end results of translation and the process by which correctness is achieved.

Our contributions are as follows:

- A automated pipeline for code translation dataset generation: we introduce a multi-turn dialogue generation framework driven by a dual-LLM Questioner–Solver module that integrates external knowledge into structured reasoning traces.
- Two new translation benchmarks: we instantiate this pipeline on Fortran→C++ and C++→CUDA, producing large-scale datasets of 3.6k and 3.9k dialogues with verified translations and unit tests. These are further decomposed into over **14.1k** (Fortran→C++) and **12.7k** (C++→CUDA) Question-Solution pairs and are released alongside three disjoint test

suites for rigorous evaluation.
- We introduce and validate strategies for structuring our dialogue data, demonstrating that different formats are optimal for different tasks. We show that decomposing dialogues into fine-grained `QS-Pairs` is highly effective for mastering syntactic complexity, while using the full `Dialogue` trace is superior for preserving semantic correctness, with both formats demonstrating significant improvements over traditional code pairs

To demonstrate the generality of our approach, we apply it to two downstream tasks: `Fortran→C++` and `C++→CUDA`. Fine-tuning mid-size open-weight models on our data yields substantial gains across Compilation, Execution, and Unit-Test success (e.g., CodeLlama-13B on C++→CUDA improves Unit-Test success rate from 12.5% to 68.8%; Fortran→C++ from 42.3% to 74.1%), consistent Code-BLEU improvements, and stronger debug-round gains. A dialogue-tuned Qwen2.5-7B outperforms larger proprietary baselines (Gemini 2.5 Flash, LLaMA 4 Scout 17B) on compilation and execution success, highlighting the cost-efficiency of dialogue-centered supervision. More broadly, our results establish dialogue-driven dataset generation as a general paradigm for advancing LLM-based code translation across low-resource and domain-specific settings.

2 Background

2.1 Code Translation in Software Modernization

Automated code translation plays a central role in software engineering and high-performance computing (Yang et al., 2024). Legacy applications written in languages such as Fortran and C need to increasingly interoperate with modern ecosystems, while frameworks such as CUDA, OpenMP, and SYCL have emerged to exploit heterogeneous hardware (Nichols et al., 2024a). Traditional approaches to translation have relied on expert-driven rules, glue code, or intermediate representations, but these methods are costly to maintain and often lack generality across diverse language paradigms (Kadosh et al., 2024). The rise of large language models has introduced a new direction to use data-driven methods to directly generate target-language code from source-language inputs.

2.2 Challenges for LLMs in Translation

Despite progress, LLMs face notable challenges when applied to translation tasks beyond mainstream languages such as Python and Java. First, data scarcity limits generalization in low-resource languages (e.g., Fortran) and in specialized frameworks (e.g., CUDA). Parallel corpora that align source and target languages are rare, particularly when functional equivalence and performance portability must be guaranteed. Second, static source–target pairs only capture the final translation output, omitting the iterative workflows that developers follow when diagnosing compiler errors, validating runtime behavior, and refining translations (Nichols et al., 2024b; Ding et al., 2024). As a result, fine-tuned models often fail to recover from errors or generate functionally correct code.

2.3 LLM Agent Systems

LLM agent frameworks provide a promising way to address these limitations (Mohammadi et al., 2025). By combining reasoning, planning, memory, and tool integration, agents enable multi-step problem solving that goes beyond single-turn inference. Recent work has demonstrated the value of integrating compilers, execution environments, and feedback loops into translation pipelines, producing data that reflects not only correct outputs but also the reasoning traces behind them (Dearing et al., 2024; Chen et al., 2025; Ding et al., 2024). However, current agent-based code translation approaches are not able to leverage the intermediate information effectively and automatically.

3 Approach

3.1 Problem and Notion Formulation

We formulate code translation as a supervised or semi-supervised learning problem. In standard settings, the training or fine-tuning dataset consists of paired examples $\{(x_s, x_t)\}$, where x_s is a program in the **source language** and x_t is its semantically equivalent implementation in the **target language**. A translation model f_θ parameterized by θ then learns to map

$$x_t = f_\theta(x_s).$$

As noted earlier, this formulation faces two main challenges. First, reliable parallel corpora $\{(x_s, x_t)\}$ are scarce for low-resource languages and specialized frameworks. Second, conventional datasets capture only the final source–target mapping, omitting the intermediate reasoning required to handle compiler errors, validate runtime behavior, and refine translations. As a result, LLMs trained on static pairs tend to overfit to patterns and struggle to recover from errors.

To overcome these limitations, we extend the notion of a dataset to include not only the **Code Pair** (x_s, x_t) but also the **Dialogue** that produces it. A dialogue d is a multi-turn sequence of interactions between the Questioner and the Solver,

$$d = \{(q_1, s_1), (q_2, s_2), \ldots, (q_T, s_T)\},$$

where q_i is a query and s_i the corresponding response. We refer to each pair $\langle q_i, s_i \rangle$ as a **Question–Solution Pair**.

This formulation captures not only the final verified source–target pair (x_s, x_t) but also the reasoning trajectory that leads to it. The specific roles of the Questioner and Solver will be detailed in the following subsection.

Table 1: Roles of the Questioner and Solver in dialogue-based translation.

Role	Main Responsibilities
Questioner	Uses memory of previous turns; incorporates compiler and runtime feedback; specifies context, tags, and constraints; checks source–target consistency.
Solver	Generates target-language code; refines or fixes code when errors occur; returns verification results such as tests and error reports.

3.2 The Questioner–Solver Module

At the core of our approach is the *Questioner–Solver* module, which extends translation beyond static source–target pairs by modeling an interactive dialogue. As illustrated in Figure 1, the module integrates state tracking, external tools, and iterative refinement into the translation process.

The roles of the two parts are summarized in Table 1. The **Questioner** analyzes the current state and formulates questions by leveraging dialogue memory, which stores past translation attempts, errors, and fixes, and by incorporating feedback from compilers, runtime environments, and scripts. The **Solver**, in turn, generates target-language translations, produces unit tests, and applies repairs based on the Questioner's prompts and verification results.

This separation of responsibilities enables explicit modeling and automatic construction of the reasoning process: the Questioner focuses on analysis and guidance, while the Solver specializes in

code generation and correction. Their iterative exchange supports progressive refinement of translations and facilitates the integration of external knowledge sources, ultimately leading to more robust and generalizable models.

3.3 Multi-Turn Dialogue Dataset Generation Pipeline

Figure 2 illustrates our multi-turn dialogue dataset generation pipeline. The pipeline integrates the dual-LLM Questioner–Solver module throughout all stages, ensuring that both source–target code pairs and reasoning-rich information are systematically captured and automatically constructed into dialogue data. Unlike prior works that stop at producing verified code pairs, our design explicitly embeds compiler and runtime feedback into structured multi-turn exchanges, capturing the reasoning traces behind successful translations.

1. Preprocessing. The pipeline begins with the preprocessing of the source programming language (SPL) code. This stage removes comments, filters out dependency-heavy snippets, and enforces a token-length constraint to fit within the LLM context window. Only self-contained, executable inputs are retained, ensuring that subsequent testing, translation, and refinement are feasible.

2.1 SPL Unit Test Generation. After preprocessing, the Questioner requests unit tests in a main function, and the Solver generates them for the source language code. These unit tests are embedded directly in the program (e.g., using assert in C++ or conditional checks in Fortran) rather than relying on external frameworks, ensuring that the tests can be executed uniformly across different environments.

2.2 SPL with Unit Test Verification and Refinement. The generated unit tests are compiled and executed. The Questioner analyzes the results and, in any failure, prompts the Solver to repair the tests or refine the code. This feedback loop continues until the tests pass. If iterations reach the predefined threshold of seven, the process terminates and discards the sample. By recording these exchanges, the pipeline captures valuable reasoning traces related to test generation and repair.

3.1 Initial Translation. Once unit tests are validated, the Questioner requests an initial target-language translation, and the Solver produces the corresponding code. This translation, together with the source code and tests, forms the basis for the iterative refinement stage.

3.2 Translation with Unit Test Verification and Refinement. The translated code is compiled and executed against the generated unit tests. The Questioner evaluates the results, and if errors are detected, it instructs the Solver to refine the translation. This loop continues until the program passes compilation and test execution or is rejected after repeated failures. By capturing intermediate errors and fixes, this stage enriches the dialogue dataset with problem-solving trajectories.

3.3 Duo-Test Verification. In this final stage, the Questioner requests a verification step to ensure functional equivalence between the source and translated programs. Both codes are compiled and executed, and results are compared. If outputs match, the translation and its dialogue history are stored as verified data. If mismatches persist, the dialogue is still recorded, including error messages and unsuccessful fixes, making it valuable for training error recovery.

3.4 Dataset Output

The complete process results in dialogues $d = \{(q_1, s_1), \ldots, (q_T, s_T)\}$, where each query q_i is generated by the Questioner and each response s_i is returned by the Solver. These dialogues capture not only the final verified source–target program pair (x_s, x_t) but also the reasoning trajectory leading to it. This design enables the dataset to serve both as a repository of verified code pairs and as a source of structured supervision for reasoning-centered fine-tuning.

3.5 Dataset Construction

Compared with code-pair data, a major advantage of dialogue data lies in its flexibility for constructing downstream tasks. By default, we adopt Dialogue-Level Splitting for fine-tuning, though the data can also be divided at the Question–Solution Pair level to avoid overfitting.

Dialogue-Level Splitting: Our dataset consists of multi-turn dialogues generated by the dual-agent Questioner–Solver system, where each dialogue captures a full translation workflow—initial translation, unit test generation, error diagnosis, iterative correction, and final verification. To preserve the natural flow of interactions, we split the data at the dialogue level. Each dialogue is assigned entirely to the training, validation, or test set, ensuring that no portion of a conversation appears in multiple splits. This prevents context leakage and allows evaluation on truly unseen translation scenarios.

Figure 2: Multi-Turn Dialogue Dataset Generation Pipeline.

Question–Solution Pair Splitting: Each multi-turn dialogue can be further decomposed into cumulative Question–Solution pairs for model fine-tuning. This splitting strategy emphasizes individual interactions and applies random sampling across pairs. It preserves the iterative refinement and error-correction context essential for model learning while mitigating potential overfitting. We posit that such finer-grained and randomized splitting enhances generalization by exposing the model to a broader and more diverse set of interaction patterns—a hypothesis that we further analyze in the discussion section.

4 Experiments

This section validates our proposed dialogue-based data generation pipeline through a series of experiments on two critical, low-resource code translation tasks. The first, **Fortran-to-C++ (Fortran2CPP)**, addresses the challenge of updating legacy scientific code. The second, **C++-to-CUDA (CPP2CUDA)**, focuses on modernizing code for heterogeneous parallelization and GPU kernel synthesis. Our analysis is structured to answer three core research questions that systematically evaluate our method's performance, advantages, and competitiveness.

4.1 Datasets

The datasets for these two tasks were generated via our pipeline, which queried the LLaMA-3.3-70B-Instruct (AI@Meta, 2024b) and LLaMA-4-Scout-17B-16E-Instruct (AI@Meta, 2024a) models through the Google Vertex AI API (Google, 2024). To ensure a rigorous evaluation, we split all generated data by source file index ranges into distinct training and testing partitions, guaranteeing no overlap.

4.1.1 Fine-tuning Datasets

Fortran2CPP Translation. We sampled Fortran programs from the CodeParrot GitHub-Code dataset (Tunstall et al., 2021), a collection of over 142,000 files from open-source scientific repositories. Our pipeline processed a contiguous block of 40,000 samples (indices 70,000–110,000) and produced 3,652 validated Fortran-to-C++ pairs, each confirmed to compile and execute successfully. The first 3,000 of these pairs formed the training set.

CPP2CUDA Translation. We built upon the CodeRosetta corpus (Tehrani et al., 2024), a large synthetic collection for unsupervised parallel programming translation. From its 6,033 C++–CUDA pairs, we retained only the C++ sources and retranslated them, yielding 3,394 verified translations. The first 3,000 pairs were used for training. Each training entry includes the source C++ function, the generated CUDA kernel with a runnable test unit, and multi-round dialogue logs that record compiler errors and solver fixes.

Data Formats. To analyze the impact of supervision structure, we prepared three dataset variants: **Code Pair**, containing direct source-target translations; **Dialogue**, comprising full multi-turn reasoning traces with compiler and runtime feedback; and **Question-Solution (QS) Pair**, consisting of atomic QS exchanges extracted from dialogues, which yielded 14,182 pairs for Fortran2CPP and 12,770 for CPP2CUDA.

4.1.2 Evaluation Benchmarks

Fortran2CPP Evaluation Sets. We used the remaining 652 pairs from our generated Fortran-to-C++ corpus as the `Fortran2CPP Code Pair Test` set. To assess broader generalization, we also adopted the HPC-Fortran-Cpp dataset (Lei et al., 2023), which contains 315 manually curated OpenMP Fortran/C++ pairs. After filtering for sources under 4,000 tokens, 301 pairs were retained for evaluation. As only 116 Fortran codes in the datasets are executable, the Unit Test Success rate is consistently low for this dataset.

Table 2: Results on **Fortran2CPP** translation benchmarks. Each cell shows *count (rate)*. The best value in each column is highlighted in **bold**.

Setting	CodeLlama-13B-Instruct-hf			DeepSeek-Coder-6.7B-Instruct			Qwen2.5-Coder-7B-Instruct		
	Unit Test Success	Compilation Success	Execution Success	Unit Test Success	Compilation Success	Execution Success	Unit Test Success	Compilation Success	Execution Success
Fortran2CPP Code Pair Test (652 tests)									
Original	276 (42.30%)	385 (59.05%)	373 (57.21%)	480 (73.60%)	599 (91.87%)	576 (88.34%)	444 (68.10%)	530 (81.29%)	517 (79.29%)
Code Pair	449 (68.90%)	**597 (91.56%)**	570 (87.42%)	478 (73.30%)	**619 (94.94%)**	**602 (92.33%)**	411 (63.00%)	**604 (92.64%)**	**573 (87.88%)**
Dialogue	**483 (74.10%)**	574 (88.04%)	564 (86.50%)	**516 (79.10%)**	590 (90.49%)	582 (89.26%)	**491 (75.30%)**	570 (87.42%)	561 (86.04%)
QS-Pair	442 (67.80%)	592 (90.80%)	**576 (88.34%)**	471 (72.20%)	593 (90.95%)	576 (88.34%)	374 (57.40%)	556 (85.28%)	523 (80.21%)
HPC-Fortran-Cpp (301 tests)									
Original	37 (12.29%)	115 (38.21%)	100 (33.22%)	**78 (25.91%)**	168 (55.81%)	153 (50.83%)	70 (23.26%)	158 (52.49%)	155 (51.50%)
Code Pair	**81 (26.91%)**	**253 (84.05%)**	**238 (79.07%)**	74 (24.58%)	**254 (84.39%)**	**237 (78.74%)**	**72 (23.92%)**	**248 (82.39%)**	**234 (77.74%)**
Dialogue	72 (23.92%)	204 (67.77%)	193 (64.12%)	70 (23.26%)	229 (76.08%)	209 (69.44%)	69 (22.92%)	225 (74.75%)	221 (73.42%)

CPP2CUDA Evaluation Sets. Two complementary test sets were derived from the CodeRosetta source corpus, disjoint from the training indices. The first is the CPP2CUDA Code Pair Test with Checksum, containing the last 394 pairs evaluated under strict verification that enforces bit-exact checksum consistency between CPU and GPU outputs. The second is the CPP2CUDA Code Pair Test, an additional 528 pairs drawn from the remaining 800 samples that preceded the test subset. Both test sets were generated using the same pipeline configuration.

4.2 Experiment Setup

Models. For our fine-tuning experiments, we selected a range of strong, publicly available code-oriented language models (details in Table 6 in Appendix). These include CodeLlama-13B-Instruct-hf (Roziere et al., 2023), DeepSeek-Coder-6.7B-Instruct (Guo et al., 2024), and Qwen2.5-Coder-7B-Instruct (Team, 2024), which represent different architectures and training data sizes. To benchmark the performance of our fine-tuned models, we compare them against two state-of-the-art proprietary models: Gemini 2.5 Flash (Gemini Team, 2024) and LLaMA 4 Scout 17B (AI@Meta, 2024a).

Evaluation Metrics. We assess the quality of the translated code using four complementary metrics that evaluate syntactic, runtime, functional, and structural correctness:

- **Compilation Success Rate:** This metric measures the syntactic validity of the generated code. A translation is considered successful if it compiles without any errors using standard compilers (e.g., GCC for C++, NVCC for CUDA).
- **Execution Success Rate:** For code that compiles successfully, this metric assesses its runtime stability. A translation passes if the compiled executable runs to completion without encountering any runtime errors, such as segmentation faults.
- **Unit Test Success Rate:** This is our primary and most stringent metric for functional correctness. It evaluates whether the translated code produces the correct output, as verified by a set of unit tests.
- **CodeBLEU Score:** This metric evaluates the quality of translated code by measuring its similarity to a reference solution. It extends the standard BLEU score by incorporating code-specific features like n-gram, abstract syntax tree (AST), and dataflow matching.

Implementation Details: All experiments were conducted on an NVIDIA H200 GPU (140 GB) using LLaMA Factory (Zheng et al., 2024) for model training. We fine-tuned each model with LoRA (Hu et al., 2021) under the supervised fine-tuning (SFT) stage on two datasets: one split at the conversation level and one at the prompt-response pair level, each containing 3,000 samples. The Dialogue-Model was trained with a context length of 8,192, while the Pair-Model used 4,096. LoRA was applied to all target modules with rank = 8, $\alpha = 16$. Training used a per-device batch size = 1, gradient accumulation = 8, learning rate = 1×10^{-4}, a cosine learning-rate scheduler with warm-up ratio = 0.1, and ran for 3 epochs with fp16 precision enabled.

For inference, we merged the LoRA adapters with the base model weights and evaluated the test split with a temperature of 0.2 on vllm (Kwon et al., 2023). This setup provides a comprehensive evaluation of LLM performance for Fortran-to-C++ translation across our datasets and metrics.

4.3 Results and Analysis

RQ1: Can the proposed pipeline effectively generate high-quality data that supports large language models (LLMs) in code translation tasks? Fine-tuning on datasets generated by our

Figure 3: Impact of Fine-tuning and Debug Rounds on Fortran to C++ Translation Success (Qwen2.5-Coder-7B).

Table 3: Results on **CPP2CUDA** translation benchmarks. Each cell shows *count (rate)*. The best value in each column is highlighted in **bold**.

Setting	CodeLlama-13B-Instruct-hf			DeepSeek-Coder-6.7B-Instruct			Qwen2.5-Coder-7B-Instruct		
	Unit Test Success	Compilation Success	Execution Success	Unit Test Success	Compilation Success	Execution Success	Unit Test Success	Compilation Success	Execution Success
CPP2CUDA Code Pair Test (528 tests)									
Original	66 (12.50%)	318 (60.23%)	243 (46.02%)	306 (58.00%)	418 (79.17%)	395 (74.81%)	260 (49.20%)	349 (66.10%)	316 (59.85%)
Code Pair	351 (66.50%)	423 (80.11%)	414 (78.41%)	368 (69.70%)	440 (83.33%)	428 (81.06%)	342 (64.80%)	417 (78.98%)	406 (76.89%)
Dialogue	339 (64.20%)	423 (80.11%)	404 (76.52%)	354 (67.00%)	435 (82.39%)	423 (80.11%)	339 (64.20%)	436 (82.58%)	421 (79.73%)
QS-Pair	**363 (68.80%)**	**451 (85.42%)**	**433 (82.01%)**	**377 (71.40%)**	**453 (85.80%)**	**443 (83.90%)**	**358 (67.80%)**	**458 (86.74%)**	**444 (84.09%)**
CPP2CUDA Code Pair Test with Checksum (394 tests)									
Original	26 (6.60%)	143 (36.29%)	136 (34.52%)	230 (58.40%)	267 (67.77%)	260 (65.99%)	184 (46.70%)	227 (57.61%)	222 (56.35%)
Code Pair	**299 (75.90%)**	**332 (84.26%)**	**328 (83.25%)**	**305 (77.40%)**	**335 (85.03%)**	**329 (83.50%)**	281 (71.30%)	332 (84.26%)	328 (83.25%)
Dialogue	275 (69.80%)	304 (77.16%)	300 (76.14%)	286 (72.60%)	320 (81.22%)	315 (79.95%)	273 (69.30%)	316 (80.20%)	313 (79.44%)
QS-Pair	288 (73.10%)	329 (83.50%)	323 (81.98%)	289 (73.40%)	326 (82.74%)	321 (81.47%)	277 (70.30%)	331 (84.01%)	327 (82.99%)

pipeline leads to substantial and consistent performance gains across all metrics—compilation, execution, and unit-test success. compared to the original models. As shown in Table 3, the baseline CodeLlama-13B model achieves a Unit Test Success Rate of just 12.50% on the main CPP2CUDA test set; after fine-tuning with our QS-Pair data, its success rate soars to 68.80% (+56.3%). This trend holds for the Fortran2CPP task (Table 2), where CodeLlama-13B improves from 42.3% to 74.1%, DeepSeek-6.7B from 73.6% to 79.1%, and Qwen2.5-7B from 68.1% to 75.3%. The consistent upward trends also align with CodeBLEU gains (Table 5), confirming that the generated datasets enhance both syntactic validity and functional correctness. This unequivocally demonstrates that our pipeline can produce large-scale, high-quality translation supervision that reliably benefits multiple model families.

RQ2: Compared with conventional Code Pair datasets, does incorporating compiler and runtime feedback as well as reasoning traces within multi-round dialogues improve translation accuracy and robustness? Dialogue-centric formats (Dialogue and QS-Pair) are highly competitive and often superior to conventional Code Pair fine-tuning. On the relatively easier **Fortran2CPP** task, full *Dialogue* achieves the best functional correctness (e.g., 74.10% Unit Test Success for CodeLlama-13B; Table 2), indicating that when syntactic correctness is already high, the rich reasoning context in dialogues helps models master the algorithmic details needed for correct outputs. Conversely, the **CPP2CUDA** task is substantially more challenging; here, *QS-Pair* performs best across models (Table 3). By decomposing 3k dialogues into >12k shuffled question–solution turns, QS-Pair provides many more effective optimization steps within the same three epochs, accelerating convergence to stable compilation/execution patterns, whereas full dialogues may require more epochs to fully realize their benefit.

To better illustrate the benefits of dialogue supervision, we introduce a *debug round* mechanism: if a generated program fails to compile, the system returns the code *along with the compiler error message* to the model for regeneration. Figure 3 shows that under this protocol, Code-Pair fine-tuning achieves the highest *compilation* success in every round, yet its *unit-test* success remains consistently below that of Dialogue. In contrast, the Dialogue-tuned model improves across all metrics with each debug round, and by D-Round 3 it achieves the highest Compilation, Execution, and Unit-Test success rates, surpassing both Code-Pair and QS-Pair settings. This demonstrates that feedback-rich dialogues enable models to learn

Figure 4: Impact of Fine-tuning and Debug Rounds on C++ to CUDA Translation Success (CodeLlama-13B).

Table 4: Comparison of model performance on **CPP2CUDA** and **Fortran2CPP** code pair tests. The results show compilation, execution, and overall unit test success rates across different fine-tuned models.

Model	CPP2CUDA Code Pair Test			Fortran2CPP Code Pair Test		
	Compilation	Execution	Unit Test	Compilation	Execution	Unit Test
Gemini 2.5 Flash	79.17%	73.86%	63.30%	91.87%	90.64%	**87.30**%
LLaMA 4 Scout 17B	78.98%	75.57%	64.80%	91.10%	89.88%	85.60%
Qwen2.5 Coder 7B (Dialogue, D-round=3)	**93.18%**	**92.05%**	**72.70%**	**96.32%**	**94.94%**	82.20%

Table 5: CodeBLEU scores on Fortran2CPP and CPP2CUDA tasks across different fine-tuning settings.

Task	CodeLlama-13B				DeepSeek-Coder-6.7B				Qwen2.5-Coder-7B				Large Baselines	
	Original	Code Pair	Dialogue	QS-Pair	Original	Code Pair	Dialogue	QS-Pair	Original	Code Pair	Dialogue	QS-Pair	Gemini	LLaMA4
Fortran2CPP	0.5647	**0.5964**	0.5937	0.5914	0.5422	**0.5969**	0.5917	0.5926	0.5562	0.5805	**0.5852**	0.5709	0.5934	0.5927
CPP2CUDA	0.5593	0.6282	0.6232	**0.6289**	0.5744	0.6262	0.6256	**0.6293**	0.5809	**0.6185**	0.6179	0.6161	0.6291	0.6295

how to correct and refine their translations rather than merely generate compilable templates. Figure 4 further confirms that on the more difficult task, all training methods benefit from additional debug rounds, with Dialogue exhibiting the steepest and most consistent improvements across all metrics, highlighting the universal value of iterative feedback.

Overall, dialogue-based supervision not only boosts headline success rates but also markedly reduces compilation failures and improves recoverability. By structuring the same conversations as full *Dialogue* or fine-grained *QS-Pair*, we can match the supervision granularity to task difficulty, enabling models to generate code that is both syntactically sound and functionally correct.

RQ3: Can small open-weight models fine-tuned on dialogue-centric data achieve competitiveness with state-of-the-art proprietary systems? Yes. Our fine-tuned, mid-size open-weight models demonstrate the ability to match or even surpass the performance of larger, proprietary systems. As detailed in Table 4, our Dialogue fine-tuned Qwen2.5-7B models with Debug rounds 3 significantly outperform both Gemini 2.5 Flash and LLaMA 4 Scout 17B in Compilation, Execution, and Unit Test Success rates. A similar trend is ob-

served on the Fortran2CPP task, where our model's Execution Success Rate of 94.94% exceeds that of the larger baselines. This parameter-efficient competitiveness is further supported by the CodeBLEU scores in Table 5, where our best models are on par with or exceed the large baselines. These findings highlight that our data generation method is a cost-effective pathway to achieving state-of-the-art performance.

5   Conclusion

This paper addresses the significant challenges inherent in Fortran-to-C++ translation by introducing an innovative LLM-based approach featuring a novel Questioner-Solver module. This approach not only generates a valuable multi-turn dialogue dataset to enhance LLMs' domain knowledge but also demonstrates substantial improvements across multiple metrics, affirming its effectiveness in increasing syntactic accuracy and functional reliability. The results highlight the potential of dialogue-based LLM training to revolutionize legacy code modernization, proposing a new paradigm for automated code translation technologies. Future efforts will focus on expanding dataset diversity and enhancing model capabilities to advance HPC translation tasks.

Limitations

Our framework, though effective, relies on simplified test environments and currently targets only Fortran→C++ and C++→CUDA. Dialogue quality depends on base model reasoning, and evaluation focuses mainly on compilability and correctness rather than performance. Future work will broaden language coverage, include performance checks, and improve efficiency.

References

Wasi Uddin Ahmad, Saikat Chakraborty, Baishakhi Ray, and Kai-Wei Chang. 2021. Unified pre-training for program understanding and generation. *arXiv preprint arXiv:2103.06333*.

AI@Meta. 2024a. Llama 4 Scout Model Card (Placeholder). Citation is illustrative for the specified model variant.

AI@Meta. 2024b. The Llama 3 Herd of Models. *arXiv preprint arXiv:2404.11051*.

Tomer Bitan, Tal Kadosh, Erel Kaplan, Shira Meiri, Le Chen, Peter Morales, Niranjan Hasabnis, and Gal Oren. 2025. Unipar: A unified llm-based framework for parallel and accelerated code translation in hpc. *arXiv preprint arXiv:2509.12136*.

Le Chen, Nesreen Ahmed, Mihai Capotă, Ted Willke, Niranjan Hasabnis, and Ali Jannesari. 2025. Pcebench: A multi-dimensional benchmark for evaluating large language models in parallel code generation. In *2025 IEEE International Parallel and Distributed Processing Symposium (IPDPS)*, pages 546–557. IEEE.

Le Chen, Nesreen K Ahmed, Akash Dutta, Arijit Bhattacharjee, Sixing Yu, Quazi Ishtiaque Mahmud, Waqwoya Abebe, Hung Phan, Aishwarya Sarkar, Branden Butler, and 1 others. 2024. The landscape and challenges of hpc research and llms. *arXiv preprint arXiv:2402.02018*.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, and 1 others. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Paweł Czarnul, Jerzy Proficz, and Krzysztof Drypczewski. 2020. Survey of methodologies, approaches, and challenges in parallel programming using high-performance computing systems. *Scientific Programming*, 2020:1–19.

Matthew T Dearing, Yiheng Tao, Xingfu Wu, Zhiling Lan, and Valerie Taylor. 2024. Lassi: An llm-based automated self-correcting pipeline for translating parallel scientific codes. In *2024 IEEE International Conference on Cluster Computing Workshops (CLUSTER Workshops)*, pages 136–143. IEEE.

Akash Dhruv and Anshu Dubey. 2025. Leveraging large language models for code translation and software development in scientific computing. In *Proceedings of the Platform for Advanced Scientific Computing Conference*, pages 1–9.

Yangruibo Ding, Jinjun Peng, Marcus Min, Gail Kaiser, Junfeng Yang, and Baishakhi Ray. 2024. Semcoder: Training code language models with comprehensive semantics reasoning. *Advances in Neural Information Processing Systems*, 37:60275–60308.

Zhangyin Feng, Daya Guo, Duyu Tang, Nan Duan, Xiaocheng Feng, Ming Gong, Linjun Shou, Bing Qin, Ting Liu, Daxin Jiang, and 1 others. 2020. Codebert: A pre-trained model for programming and natural languages. *arXiv preprint arXiv:2002.08155*.

Google Gemini Team. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. Technical report, Google.

Google. 2024. Vertex AI. https://cloud.google.com/vertex-ai. Accessed: 2025-10-07.

Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, Kai Dong, Wentao Zhang, Guanting Chen, Xiao Bi, Yu Wu, YK Li, and 1 others. 2024. Deepseekcoder: When the large language model meets programming-the rise of code intelligence. *arXiv preprint arXiv:2401.14196*.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. *Preprint*, arXiv:2106.09685.

Tal Kadosh, Niranjan Hasabnis, Vy A Vo, Nadav Schneider, Neva Krien, Mihai Capotă, Abdul Wasay, Guy Tamir, Ted Willke, Nesreen Ahmed, and 1 others. 2024. Monocoder: Domain-specific code language model for hpc codes and tasks. In *2024 IEEE High Performance Extreme Computing Conference (HPEC)*, pages 1–7. IEEE.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*.

Marie-Anne Lachaux, Baptiste Roziere, Lowik Chanussot, and Guillaume Lample. 2020. Unsupervised translation of programming languages. *arXiv preprint arXiv:2006.03511*.

Bin Lei, Caiwen Ding, Le Chen, Pei-Hung Lin, and Chunhua Liao. 2023. Creating a dataset for high-performance computing code translation using llms: A bridge between openmp fortran and c++. In *2023 IEEE High Performance Extreme Computing Conference (HPEC)*, pages 1–7. IEEE.

Mahmoud Mohammadi, Yipeng Li, Jane Lo, and Wendy Yip. 2025. Evaluation and benchmarking of llm agents: A survey. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2*, pages 6129–6139.

Daniel Nichols, Joshua H. Davis, Zhaojun Xie, Arjun Rajaram, and Abhinav Bhatele. 2024a. Can large language models write parallel code? In *Proceedings of the 33rd International Symposium on High-Performance Parallel and Distributed Computing*, HPDC '24, page 281–294. ACM.

Daniel Nichols, Aniruddha Marathe, Harshitha Menon, Todd Gamblin, and Abhinav Bhatele. 2024b. Hpc-coder: Modeling parallel programs using large language models. In *ISC High Performance 2024 Research Paper Proceedings (39th International Conference)*, pages 1–12. Prometeus GmbH.

Baptiste Roziere, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Tal Remez, Jérémy Rapin, and 1 others. 2023. Code llama: Open foundation models for code. *arXiv preprint arXiv:2308.12950*.

Qwen Team. 2024. Qwen2: The New Generation of Open-Source Language Models. *arXiv preprint arXiv:2406.04707*.

Ali Tehrani, Arijit Bhattacharjee, Le Chen, Nesreen K Ahmed, Amir Yazdanbakhsh, and Ali Jannesari. 2024. Coderosetta: Pushing the boundaries of unsupervised code translation for parallel programming. *Advances in Neural Information Processing Systems*, 37:100965–100999.

Lewis Tunstall, Leandro von Werra, and Thomas Wolf. 2021. CodeParrot GitHub-Code Dataset. https://huggingface.co/datasets/codeparrot/github-code. Accessed: 2025-10-07.

Zhen Yang, Fang Liu, Zhongxing Yu, Jacky Wai Keung, Jia Li, Shuo Liu, Yifan Hong, Xiaoxue Ma, Zhi Jin, and Ge Li. 2024. Exploring and unleashing the power of large language models in automated code translation. *Proceedings of the ACM on Software Engineering*, 1(FSE):1585–1608.

Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, Zheyan Luo, Zhangchi Feng, and Yongqiang Ma. 2024. Llamafactory: Unified efficient fine-tuning of 100+ language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, Bangkok, Thailand. Association for Computational Linguistics.

A LLM Selection

Table 6 listed the details of the LLMs we use in the work.

B Discussion: Toward Fine-Grained Dialogue Utilization

Beyond the demonstrated benefits of dialogue-based supervision, we further explore how to more effectively exploit the internal structure of these dialogues to construct richer training signals. In our current datasets, each full dialogue can be decomposed into multiple *Question–Solution (QS)* pairs, resulting in a substantially enlarged fine-tuning corpus (12,770 pairs for CPP2CUDA and 14,182 for Fortran2CPP; see Section 4.1).

Empirically, QS-Pair supervision achieves the best overall performance on the CPP2CUDA task (Table 3), confirming that fine-grained "question–answer" signals help models learn robust compiler- and runtime-aware translation patterns. Fortran2CPP, on the other hand, benefits more from complete dialogue reasoning traces, suggesting that full-context reasoning captures algorithmic and semantic consistency.

These findings motivate several directions for future refinement:

- **Round-aware curriculum.** Sample dialogue turns progressively by round depth or error type to form a structured learning schedule.

- **Feedback-tagged prompts.** Explicitly label compiler errors (syntax, linkage, parallel primitives, memory) to guide targeted repair learning.

- **Dual-view mixing.** Combine Dialogue and QS-Pair views within each epoch, balancing high-level reasoning with dense supervision.

Overall, these results suggest that multi-round dialogue data not only enhance current fine-tuning but also provide a foundation for more systematic curriculum and retrieval-augmented training strategies in code translation.

C Prompts

Below we include the prompt strings used in our pipeline. For different translation tasks, we will attach corresponding examples in prompts.

System Instruction for Questioner: Dual-Agent Translation Pipeline

```
You orchestrate a two-phase pipeline for code
    translation and verification.
PHASE A (C++ BENCH FIRST):
```

Table 6: Selected Code-Oriented Language Models for Evaluation

Specification	DeepSeek-Coder	CodeLlama	Qwen2.5-Coder	Gemini 2.5 Flash	LLaMA 4 Scout
Parameters	6.7B	13B	7B	Unknown	17B
Training Data	2T tokens	500B tokens	3T tokens	Unknown	Unknown
Context Window	16K	100K	128K	2M	Unknown
Open Weights	Yes	Yes	Yes	No	No
Developer	DeepSeek AI	Meta	Alibaba Cloud	Google	Meta

```
1) Ask for a SINGLE-FILE **C++** program that
   contains:
   - the provided **C++ implementation** (you
   may refactor into functions),
   - a 'main' that constructs deterministic
   inputs (fixed sizes/seed),
   - **self-checking** that proves correctness,
   - **NO external libs** (NO GoogleTest/Catch2/
   etc.). OpenMP optional.
2) It must compile with 'g++ -fopenmp' (OpenMP
   optional) and run to completion.
3) It must print exactly one final summary line:
   RESULT_OK checksum=<integer>

PHASE B (TRANSLATE TO CUDA WITH IDENTICAL TEST):
1) After C++ passes locally, ask for a SINGLE-
   FILE **CUDA** program that:
   - implements the same logic with CUDA kernels,

   - **reproduces the same test scenario** (same
   inputs, seed, sizes),
   - prints the **EXACT SAME** final summary
   line:
   RESULT_OK checksum=<integer>
2) If outputs mismatch or any error occurs, you
   will be given the logs.
   You MUST return a full single-file program in
   a fenced block that fixes the issue.
```

Prompt for Generating Deterministic C++ Benchmark

```
Please produce a SINGLE-FILE C++ program that
   both defines the **reference implementation
   **
AND contains a 'main' that builds deterministic
   inputs and validates outputs.
Requirements:
- No external dependencies or test frameworks.
- If you use OpenMP, allow serial fallback if
   OpenMP is unavailable.
- End by printing exactly ONE line:
   RESULT_OK checksum=<integer>
Return the entire program in a '''cpp fenced
   block. Nothing else.
```

Prompt for Translating C++ to CUDA under Identical Test Conditions

```
Translate the validated C++ program into a
   SINGLE-FILE **CUDA** program with identical
   logic and the **same test scenario**.
Requirements:
```

```
- Keep the same input sizes and data/seed.
- Validate results on host with the same
   criteria/tolerance.
- Print EXACTLY the same final summary line:
   RESULT_OK checksum=<integer>
Return the entire program in a '''cuda fenced
   block. Nothing else.
```

Concise Question Prompt for Code Translation Queries

```
I now need to ask you some questions about C++
   to CUDA code translation, You need to keep
   every answer concise.
The first question is: {CPP_Code}
```

Prompt for Unit Test Execution and Constraints

```
{Unit_Test_Request}
I will execute part of the unit test code you
   gave.
But please note that I cannot download external
   libraries, so please do not add any external
   libraries (such as google test) when
   writing unit testing code.
```

Prompt for Removing Comments from Source Code

```
Help me to delete the comments of the following
   C++ code:
C++ Code:
{CPP_Code}
C++ Code without comments:
```

Prompt for Checking Code Self-Containment

```
Decide if this C++ snippet is selfcontained for
   immediate test-bench generation.

Selfcontained means:
1. All referenced functions \/ classes are fully
   defined here **or** are from the standard
   library.
2. Adding a minimal 'main()' and standard
   headers lets it compile & link without
   unresolved symbols.
3. No external files, network, or special
   hardware APIs needed.
```

Return ONLY ''YES" or ''NO".

{CPP_Code}

Prompt for Initializing Solver with Unit Test Code

C++ Unit test code:
```cpp
{cpp_code}
```

CUDA Unit test code:
```cuda
{cuda_code}
```

Prompt Template for Repair Intent and Full Program Output

First line = JSON array of 'repair intent tags';
    then ONE fenced code block with the FULL
    single-file program. No other text.

Prompt for Validating and Aligning C++ and CUDA Test Scenarios

You are given a validated **C++** program and
    the current **CUDA** program.
First, internally decide whether the CUDA **TEST
    ** (input construction, shapes/sizes,
    constants, seeds, tolerance,
and the final summary print) is IDENTICAL to the
    C++ TEST.
- If NOT identical: Modify **ONLY THE TEST
    SCAFFOLD** of the CUDA program so that it
    exactly matches the C++ test.
  Do not change kernel math yet. Keep the same
    final summary line format.
- If identical: Do not change the test; modify
    ONLY THE COMPUTATION (kernels and
    related glue)
  so that the CUDA output produces exactly this
    final line: {target_line}.
Strict output format: first line = JSON array of
    repair intent tags; then ONE ```cuda code
    block with the full corrected program. No
    other text.
C++ reference program:
```cpp
{cpp_code}
```
Current CUDA program:
```cuda
{cuda_code}
```

Prompt Related to CUDA Translation or Validation

The CUDA program's test already matches the C++
    test. Do NOT change any test scaffolding (
    input sizes, seed, I/O, validation).
Modify ONLY the kernels/computation so that the
    CUDA output produces exactly this final line
    : {target_line}.
Strict output format: first line = JSON array of
    repair intent tags; then ONE ```cuda code
    block with the full corrected program. No
    other text.
C++ reference program:
```cpp
{cpp_code}
```
Current CUDA program:
```cuda
{cuda_code}
```

General Prompt Template

(Code variable: ft_ct_further_check*)*

Answer only 'Yes' or 'No': Do the CUDA and C++
    programs produce IDENTICAL final summary
    lines?
C++: {cpp_compile_result}
CUDA: {cuda_compile_result}

General Prompt Template

Provide the FINAL pair of programs **known to
    compile and run successfully** and that
    print identical final summary lines.
Return both in two separate fenced blocks: first
    ```cpp, then ```cuda. No extra commentary.

General Prompt Template

modify the unit test code based on the outputs
    and give me the complete modified unit test
    code to make sure I can compile and run it
    directly
C++ code result: {cpp_compile_result}
cuda code outputs: {cuda_compile_result}

General Prompt Template

Here is my C++ code: {cpp_code}. Now you need to
    provide a complete question (including code
) to the answerer and ask him to translate
    this C++ code to CUDA code and give you the
    CUDA code. Don't translate this C++ code by
    yourself. Ask the answerer to follow the
    template to start CUDA code with '''cuda and
    end with '''.

Prompt for Unit Test Generation or Execution

Here is the answer from the solver: {ser_answer}, you now need to ask the answerer to provide the executable unit-test code for both the original C++ code and the translated CUDA code seperately.

Please write the main function for both code and add the unit tests. Add them to C++ code and CUDA code seperately.

In the C++ code, you should use 'assert' for the unit-test checking. One example:
assert(your_cpp_function(arg1, arg2) == expected_result);

In the CUDA code, perform the unit-test checking on the host (CPU) after the results have been copied back from the device. Use a pattern similar to:
// Assuming 'h_result' is an array on the host that holds the results
// copied back from the GPU, and 'expected_value' is the expected outcome
// for a specific test case.
if (h_result[i] != expected_value) {{
    printf("Test case failed: assertion failed at index %d!\n", i);
    return 1; // or exit(1)
}}

Important:
* Keep the C++ and CUDA tests completely separateeach must compile and run on its own.
* Provide one same unit-test for both C++ and CUDA code.
* The C++ code should start with ```cpp and end with ```.
* The CUDA code should start with ```cuda and end with ```.
* Each program should exit with status 0 (or print a success message) when all tests pass.

General Prompt Template

Help me continue to modify the C++ and cuda codes to ensure that they have the same functions and provide the complete unit test code to make sure I can compile and run it directly (Not only the main code).

General Prompt Template

Your answer was neither 'yes' nor 'no'. Please provide a clear answer.

Prompt Related to CUDA Translation or Validation

Help me to translate the following CUDA code to C++ code, don't give any words:
CUDA Code:
```
__global__ void addKernel(int *c, const int *a, const int *b) {{
    int i = threadIdx.x;
    c[i] = a[i] + b[i];
}}
```
Translated C++ Code:
```
void add(int *c, const int *a, const int *b, int size) {{
    for (int i = 0; i < size; ++i) {{
        c[i] = a[i] + b[i];
    }}
}}
```

Help me to translate the following CUDA code to C++ code, don't give any words:
CUDA Code:
```
__global__ void saxpy(int n, float a, float *x, float *y) {{
    int i = blockIdx.x * blockDim.x + threadIdx.x;
    if (i < n) {{
        y[i] = a * x[i] + y[i];
    }}
}}
```
Translated C++ Code:
```
void saxpy(int n, float a, float *x, float *y) {{
    for (int i = 0; i < n; ++i) {{
        y[i] = a * x[i] + y[i];
    }}
}}
```

Help me to translate the following CUDA code to C++ code, don't give any words:
CUDA Code:
{CPP_Code}
Translated C++ Code:

General Prompt Template

Help me to translate the following CUDA code to C++ code by using the following format:
The function of the source CUDA Code is: ...
Translated c++ code is: ...
Explanation: ...

Example:
CUDA Code needs to be translated:
```
__global__ void addKernel(int *c, const int *a, const int *b) {{
    int i = threadIdx.x;
    c[i] = a[i] + b[i];
}}
```
Translated C++ Code:
```
void add(int *c, const int *a, const int *b, int size) {{
    for (int i = 0; i < size; ++i) {{
        c[i] = a[i] + b[i];
    }}
}}
```

The function of the source CUDA Code is:

The CUDA kernel `addKernel` performs element-wise addition of two integer arrays and stores the result in a third array. Each GPU thread handles one element, enabling parallel execution.

Translated c++ code is:
```cpp
#include <cstddef>
void add(int *c, const int *a, const int *b, std::size_t size) {{
    for (std::size_t i = 0; i < size; ++i) {{
        c[i] = a[i] + b[i];
    }}
}}
```

Explanation:
1. **Parallel vs. serial** the CUDA kernel runs thousands of threads in parallel; the C++ translation uses a simple `for` loop that executes serially on the CPU.
2. **Thread index** the GPU index `threadIdx.x` is replaced by the loop variable `i`.
3. **Kernel qualifiers** `__global__` is removed in C++ because it is specific to GPU kernels; the function becomes an ordinary CPU routine.
4. **Array bounds** the original kernel relies on the grid configuration to limit `i`; the C++ loop explicitly iterates from `0` to `size-1`.
5. **Headers / types** C++ version includes `<cstddef>` to get `std::size_t` for portable size handling.

Real Code:
CUDA Code needs to be translated:
{CPP_Code}

General Prompt Template

I will provide you a paragraph of CUDA code and a paragraph of translated C++ code.
Tell me whether the CUDA code has been **correctly translated** into C++:

* If it **is** correct, answer **"Yes"**.
* If **not**, answer **"No"** and give a short reason.

CUDA code:
```cpp
__global__ void addKernel(int *c, const int *a, const int *b) {{
    int i = threadIdx.x;
    c[i] = a[i] + b[i];
}}
```
Translated C++ Code:
```cpp
void add(int *c, const int *a, const int *b, int size) {{
    for (int i = 0; i < size; ++i) {{
        c[i] = a[i] + b[i];
    }}
}}
```

Answer: Yes

CUDA code:

```cpp
__global__ void saxpy(int n, float a, float *x, float *y) {{
    int i = blockIdx.x * blockDim.x + threadIdx.x;
    if (i < n) {{
        y[i] = a * x[i] + y[i];
    }}
}}
```
Translated C++ Code:
```cpp
void saxpy(int n, float a, float *x) {{
    for (int i = 0; i < n; ++i) {{
        x[i] = a * x[i];  // wrong: y is missing
        and operation differs
    }}
}}
```

Answer: No
1. Missing parameter **y** in the C++ function.
2. C++ version overwrites **x** instead of computing **y = ax + y**.

CUDA code:
{CPP_Code}
Translated C++ Code:
{Cpp_Code}
Answer:

General Prompt Template

(Code variable: Own_model_Modify_code)

The following code translation is not perfect, you need to modify the translated C++ Code based on the reasons.
Original CUDA code:
{CPP_Code}
Translated C++ Code:
{Cpp_Code}
Reasons:
{Reasons}
Modified C++ Code:

General Prompt Template

Help me to assess if the translated C++ is correct.
        Source cuda code: {CUDA_code}
        Translated C++ Code: {Cpp_code}

        Answer:

Prompt Related to CUDA Translation or Validation

Help me to modify the translated C++ code based on the reason above, just provide the modified C++ code, don't give any words:
C++ Code:
```cpp
#include <stdio.h>
int a[100][100];
int main(){{
    int i, j;
    #pragma omp parallel for collapse(2)
    for (i = 0; i < 100; ++i){{
        for (j = 0; j < 100; ++j){{
```

```
        a[i][j] = a[i][j] + 1;
    }}
}}
    return 0;
}}

Help me to modify the translated C++ code based
    on the reason above, just provide the
    modified C++ code, don't give any words:
C++ Code:
#include <stdio.h>
#if (_OPENMP < 201511)
#error "An OpenMP 4.5 compiler is needed to
    compile this test."
#endif

int a[100][100];
int main(){{
    int i, j;
    #pragma omp parallel
    {{
        #pragma omp single
        {{
            #pragma omp taskloop collapse(2)
            for (i = 0; i < 100; ++i){{
                for (j = 0; j < 100; ++j){{
                    a[i][j] += 1;
                }}
            }}
        }}
    }}
    printf("a[50][50] = %d\n", a[50][50]);
    return 0;
}}

Help me to modify the translated C++ code based
    on the reason above, just provide the
    modified C++ code, don't give any words:
C++ Code:
```

General Prompt Template

I am trying to translate a paragraph of CUDA
    code to C++ code, but the translated C++
    code cannot pass the compiler.
Please modify the C++ code so that it compiles
    successfully.
**Return only the modified C++ codeno
    explanations.**

```
Source CUDA Code:
__global__ void addKernel(int *c, const int *a,
    const int *b) {{
    int i = threadIdx.x;
    c[i] = a[i] + b[i];
}}

Translated C++ Code:
void add(int *c, const int *a, const int *b) {{
    // BUG: missing loop and index declaration
    c[i] = a[i] + b[i];
}}

Modified C++ Code:
void add(int *c, const int *a, const int *b, int
    size) {{
    for (int i = 0; i < size; ++i) {{
```

```
        c[i] = a[i] + b[i];
    }}
}}

Source CUDA Code:
{CPP_Code}
Translated C++ Code:
{Cpp_Code}
Modified C++ Code:
```

General Prompt Template

I am trying to translate a paragraph of CUDA
    code to C++ code, but the translated C++
    code cannot pass the compiler.
Please modify the C++ so it **compiles
    successfully**.
Return **only** the modified C++ codeno
    explanations.

```
Source CUDA Code:
__global__ void addKernel(int *c, const int *a,
    const int *b) {{
    int i = threadIdx.x;
    c[i] = a[i] + b[i];
}}

Translated C++ Code:
void add(int *c, const int *a, const int *b) {{
    // BUG: missing loop and index
    c[i] = a[i] + b[i];
}}

Source CUDA Code:
{CPP_Code}
Translated C++ Code:
{Cpp_Code}
```

General Prompt Template

The compiler is throwing errors. The error
    report is: {reason}. Please help me to
    continue modifying the C++ code. Just write
    out the modified C++ code based on the error
    report, DO NOT write other words! New C++
    Code:

Prompt for Unit Test Generation or Execution

I want you to help me choose suitable code for a
    unit test. I will provide
two snippets: one in CUDA and one in C++.

```
Tasks
-----
1. Check whether the two snippets have the same
    valuebased input and output parameters.
2. If they do not, reply "False".
3. If they do, output a GoogleTest skeleton of
    the form

TEST(MyLib, MyKernel_test) {{
    // ---- prepare identical inputs ----
```

```
       /* ... */

       // ---------- C++ reference ----------
       cpp_function_name(/* host args */);

       // ---------- CUDA kernel launch ----------
       /* allocate device memory, copy inputs,
        launch, copy outputs back */

       EXPECT_EQ(/* C++ result */, /* CUDA result
       */);
}}

Notes
-----
* Wrap literal braces in your output as double
   braces {{ }} so they are not interpreted as
   format placeholders.
* When calling the CUDA kernel, wrap it in a
   simple host function or launch it directly
   with <<<grid, block>>>.
* Use EXPECT_EQ, EXPECT_FLOAT_EQ, or EXPECT_NEAR
    as appropriate.

Examples
========

Example 1 -> False
------------------
CUDA code:
__global__ void badIndex(float* a) {{
    int idx = 1.5f;  // illegal float index
    a[idx] = 0.0f;
}}

C++ code:
int main() {{
    float a[10];
    a[1] = 0.0f;
    return 0;
}}

Answer:
False

Example 2 -> Unittest skeleton
------------------------------
CUDA code:
__global__ void saxpy(int n, float a,
                      const float* x, float* y)
    {{
    int i = blockIdx.x * blockDim.x + threadIdx.
    x;
    if (i < n) {{
        y[i] = a * x[i] + y[i];
    }}
}}

C++ code:
void saxpy_cpu(int n, float a,
               const float* x, float* y) {{
    for (int i = 0; i < n; ++i) {{
        y[i] = a * x[i] + y[i];
    }}
}}

Answer:
TEST(SaxpyLib, Saxpy_test) {{
    const int N = 1024;
    const float A = 2.0f;
```

```
    float hx[N], hy_cpp[N], hy_cuda[N];

    for (int i = 0; i < N; ++i) {{
        hx[i]     = static_cast<float>(i);
        hy_cpp[i] = static_cast<float>(i * 0.5f
    );
        hy_cuda[i] = hy_cpp[i];
    }}

    saxpy_cpu(N, A, hx, hy_cpp);  // C++
     reference

    float* dx;
    float* dy;
    cudaMalloc(&dx, N * sizeof(float));
    cudaMalloc(&dy, N * sizeof(float));
    cudaMemcpy(dx, hx,      N * sizeof(float),
     cudaMemcpyHostToDevice);
    cudaMemcpy(dy, hy_cuda, N * sizeof(float),
     cudaMemcpyHostToDevice);

    dim3 block(256);
    dim3 grid((N + block.x - 1) / block.x);
    saxpy<<<grid, block>>>(N, A, dx, dy);
    cudaMemcpy(hy_cuda, dy, N * sizeof(float),
     cudaMemcpyDeviceToHost);

    for (int i = 0; i < N; ++i) {{
        EXPECT_FLOAT_EQ(hy_cpp[i], hy_cuda[i]);
    }}

    cudaFree(dx);
    cudaFree(dy);
}}
Example 3 -> no code provided
----------------------------
CUDA code:

C++ code:

Answer:

Real code
---------
CUDA code:
{cpp_code}

C++ code:
{cpp_code}

Answer:
```

General Prompt Template

```
Please modify the code and give the modified
    complete code, make sure all the functions
    are within a file and I will re-run the code
    .
1. You can add debugging statements if needed.
2. If there is a need for external library
    installations, please let me know the
    appropriate pip command by enclosing them in
    ```sh ```
```

General Prompt Template

Please judge whether the test code you just gave is correct based on the output of the code execution. Just Answer: 'Yes' or 'No'.

General Prompt Template

Give me the correct modified function code (without the test code) based on your last unit test code.

General Prompt Template

Please go ahead and modify the code to make sure it can run correctly.
You should make sure all the functions are within a file and I will re-run the code.

General Prompt Template

Could you help verify whether your code can run correctly?
1. If needed, You could create some mock data or files to assist with this. But note that whether you create new data or create a new file and write the data to it, these operations need to be done in same python file.
2. I will help you to install the related packages, you just need to tell me how install the package you need by using ```sh ... ```.
3. Our goal is to verify that the function works correctly. So you need to make sure you provide me with a complete python code rather than providing some simplified version of it.

General Prompt Template

To confirm the code functions properly, we should execute it and check its performance.
Let's test the code to make sure it operates as expected.
To verify that the code is functioning correctly, let's run a test.
Let's execute the code to validate its proper functioning.
To make certain our code is running right, we should perform a test.
Let's initiate a run to confirm that the code works as intended.
To ascertain the code's effectiveness, we must test it.
We need to run the code to ensure it meets our standards.
Let's check the code's functionality by running it.
To guarantee the code's accuracy, testing is essential.

We should execute the code to verify its accuracy.
Let's run the code to make sure everything is functioning properly.
To ensure flawless operation, we need to test the code.
Let's operate the code to check its effectiveness.
We should validate the code's performance by running it.
Let's put the code through a run-test to ensure it works correctly.
To be certain of the code's operation, we need to run it.
Running the code will help us verify its proper function.
Let's test run the code to check for any issues.
To confirm code reliability, let's execute it now.
We should run a trial to test the code's functionality.
Let's activate the code to ensure it's working as it should.
Running the code will confirm its efficiency and correctness.
We need to execute the code to confirm that it performs correctly.
To make sure the code is error-free, let's run a verification test.
Let's run the code to determine if it functions correctly.
We should check the code by running it to ensure its efficacy.
Let's perform a test run to validate the code's functionality.
To ascertain code performance, executing it is necessary.
We must run the code to ensure it operates efficiently.
To verify the code's success, let's give it a run.
Running the code will allow us to confirm its functionality.
We need to execute the code to see if it's working properly.
Let's initiate a test run to ensure the code is effective.
To confirm the code's operational success, testing it is crucial.
Let's deploy the code to check its working condition.
Running the code is essential to verify its proper execution.
We should operate the code to confirm its capabilities.
Let's activate a test run to ensure the code functions well.
To make sure the code performs its intended functions, we need to run it.
Running the code will help us ensure it meets functional requirements.
We should test the code to confirm that it executes properly.
Let's perform a functional test to ensure the code is running correctly.
To check the code's precision, let's run it.
We must initiate a test to verify the code's functionality.
To determine if the code is error-free, we should run it now.

Running the code is the best way to ensure its accuracy.

Let's conduct a run to verify that the code operates as it should.

We need to run the code to check its functionality and reliability.

Let's execute the code to test its overall performance.

General Prompt Template

Can you check if your code runs as expected?

Could you test your code to see if it functions properly?

Would you mind confirming that your code operates correctly?

Can you please verify the functionality of your code?

Could you ensure that your code is executing correctly?

Would you verify whether your code is functioning properly?

Can you determine if your code performs well?

Could you assist in checking if your code runs smoothly?

Can you help confirm your code's correctness?

Would you be able to test if your code is working right?

Can you examine your code to ensure it operates as intended?

Could you validate that your code works properly?

Would you mind running a test on your code to verify its performance?

Can you see if there are any issues with how your code runs?

Could you take a look to confirm your code functions correctly?

Would you mind ensuring your code's accuracy?

Can you help determine if your code is error-free?

Could you check for any flaws in your code's operation?

Would you be able to confirm the operational functionality of your code?

Can you make sure that your code is free of errors?

Could you perform a quick check to see if your code runs correctly?

Would you test your code to ensure it's executing properly?

Can you verify that your code meets the expected standards?

Could you assist by verifying your code's performance?

Would you mind checking if your code executes without issues?

Can you confirm the reliability of your code?

Could you please ensure that your code works as it should?

Would you assess whether your code runs effectively?

Can you help verify your code's operational correctness?

Could you double-check the functioning of your code?

Would you mind verifying that your code operates without problems?

Can you look into whether your code functions as planned?

Could you help confirm that your code performs as needed?

Would you be willing to check your code for proper operation?

Can you ensure that your code executes as expected?

Could you run a diagnostic to see if your code is working correctly?

Would you mind testing your code for functionality?

Can you verify the accuracy of your code's execution?

Could you provide assurance that your code is running properly?

Would you verify if your code is up to performance standards?

Can you check your code for any operational errors?

Could you run a trial on your code to confirm it functions correctly?

Would you conduct a check to ensure your code is accurate?

Can you help make sure your code is functioning correctly?

Could you assess if your code is performing as expected?

Would you mind giving your code a run-through to check its correctness?

Can you verify if your code is functioning up to standards?

Could you please test your code for correct operation?

Would you be willing to help ensure that your code is running smoothly?

Can you confirm if your code meets all functional requirements?

Make sure the code runs as intended.
Ensure that the code functions properly.
Verify the correct operation of the code.
Confirm that the code performs as expected.
Double-check the execution of the code.
Test the code to see that it works correctly.
Ascertain that the code behaves as it should.
Check that the code operates correctly.
Ensure the code executes without errors.
Validate the functionality of the code.
Review the code's performance to ensure accuracy.

Monitor the execution to confirm it's functioning properly.
Examine the code to make sure it runs smoothly.
Assess whether the code meets the expected outcomes.
Certify that the code is executing as planned.
Scrutinize the code for proper execution.
Check off that the code works as designed.
Inspect the code for correct operation.
Reconfirm that the code operates as intended.
Authenticate the correct running of the code.
Proof the code to ensure it's working correctly.
Cross-verify the execution of the code.
Make certain the code is functioning correctly.
Confirm the proper execution of your code.
Ensure your code executes as planned.
Verify that your code runs correctly.
Double-check that your code is functioning properly.
Make sure your code performs as expected.

Check that your code operates smoothly.
Validate that your code meets the operational criteria.
Ensure the code does what it's supposed to do.
Test to ensure the code's functionality.
Confirm that the code is error-free upon execution.
Ensure that the code delivers the expected results.
Double-check the code's results for accuracy.
Confirm that the code's output is as anticipated.

Make sure the code completes without issues.
Ensure that the code's performance is up to standard.
Confirm the reliability of the code during execution.
Make sure the code's logic performs correctly.
Verify the outcome of the code's execution.
Check for any discrepancies in the code's operation.
Ensure the code executes as it is supposed to.
Confirm the stability of the code upon execution.

Test the code thoroughly before finalizing.
Make certain the code executes without any hiccups.
Validate the precision of the code's operation.
Check that the code complies with the requirements.
Recheck the code's functionality for assurance.
Ensure that the code achieves the intended functionality.
Monitor the code to ensure it executes flawlessly.
Evaluate the code's execution to confirm correctness.
Ascertain that the code meets performance standards.
Review the code to ensure it fulfills its purpose.
Confirm that the code executes according to the plan.
Make sure the code is free from execution errors.

Ensure that the code's execution aligns with expectations.
Cross-check to confirm the code's proper functionality.
Validate that the code operates as it should.
Confirm that the code's process is correct.
Make certain the code's results are accurate.
Ensure that the code runs efficiently.
Verify that the code's performance is satisfactory.
Check that the code is functioning as it should.
Test the code's execution for any potential issues.
Make sure the code functions as intended under all conditions.
Confirm the integrity of the code's operations.
Ensure that the code performs effectively.
Review the code execution for any anomalies.
Validate the effectiveness of the code's execution.
Double-check the code for flawless performance.
Ensure that the code meets all operational expectations.
Confirm that the code handles all scenarios correctly.

Verify the code's effectiveness in real conditions.
Check the code's consistency in execution.
Make certain that the code adheres to the expected behavior.
Ensure the code's compliance with the specifications.
Confirm the code's capability to perform as necessary.
Monitor the code's performance for stability.
Ascertain that the code is ready for deployment.
Make sure the code satisfies all functional requirements.
Ensure that the code executes without deviations.

Confirm the code's readiness for operational use.

Test the code for dependability during execution.

Verify the code's robustness in various environments.
Check that the code performs efficiently.
Confirm that the code is up to professional standards.
Ensure the code's operations are in full effect.
Reaffirm the code's readiness for live environments.
Make sure the code is optimized for performance.
Confirm the code's suitability for the intended tasks.
Double-check the code for operational accuracy.
Ensure the code meets the quality standards.
Verify the code's readiness for full-scale use.
Confirm that the code maintains consistency.
Make certain the code delivers on its promises.
Ensure the code's functionality before release.
Confirm that the code functions optimally.
Double-check to ensure the code's successful execution.
Make sure the code's behavior matches the documentation.

General Prompt Template

Our code has passed all the tests successfully, here's the code:
The code has successfully cleared all the tests, here it is:
We've successfully passed all tests with our code, here's the code:
All tests have been successfully passed by our code, here is what we wrote:
Our program succeeded in all the tests, here's the code:
Our code has cleared all its tests successfully, here's the code:
We've completed all tests successfully, here's our code:
Our coding tests were all passed successfully, here's our code:
Every test has been successfully passed by our code, see it here:
Our code achieved success in all the tests, here it is:
Successfully, our code has passed all tests, here's what we developed:
Our code met all the test criteria successfully, here is the code:

Our code excelled in all the tests, here's the code:
All the tests have been cleared by our code, here it is:
Our software has successfully passed all the testing, here's the code:
Every test was a success for our code, here's the code:
We've passed all the required tests with our code, here it is:
Our code was successful in all the tests, here is our work:
The tests were all successfully passed by our code, here it is:
Our code sailed through all the tests, here's the code:
Our code has surpassed all testing successfully, here it is:
We've successfully navigated all tests with our code, here's the result:
All required tests were successfully passed by our code, see it here:
Our code has triumphed in all the tests, here's our code:
Every test has been successfully conquered by our code, here it is:
Our application passed all tests successfully, here is the code:
The code has proven successful in all tests, here it is:
Our code has come through all the tests with success, here's the code:
Our programming successfully passed all examinations, here's our code:
We've mastered all the tests with our code, here it is:
Our system has successfully passed all tests, here is the code:
The code has been successful in all tests, here is our work:
Every testing hurdle was successfully cleared by our code, here it is:
We've cleared all tests with our code successfully, here's the code:
Our code has been vetted and succeeded in all tests, here it is:
All tests have been met with success by our code, here's the code:
Our project successfully passed all the test phases, here is our code:
Successfully, our code has conquered all the tests, here's the output:
Our code managed to pass all tests successfully, here's the code:
The code has fulfilled all test conditions successfully, here it is:
Our code was tested and passed all assessments successfully, here's the code:
Every test was smoothly passed by our code, here's what we coded:
Our code nailed all the tests successfully, here's our work:
We have successfully completed all tests with our code, here it is:
Every test criteria was met successfully by our code, here's the code:
Our script passed all tests without fail, here is the code:
Our code stood up to all tests and passed, here's the code:

All testing barriers were successfully broken by our code, here it is:
Our code has flawlessly passed all the tests, here's our script:
Our code has been validated through all tests successfully, here's the code: