CONTRASTIVE LEARNING WITH 3D SHAPES

ABSTRACT

In fields such as Computer Vision or NLP, there is a large amount of data available which, however, cannot be labeled, as it would be very expensive. A possible solution to this problem is Contrastive Learning, a Self-Supervised technique. This work aims to implement a contrastive learning regime for a non-Euclidean data type, more precisely 3D Point Cloud Shape.

1 INTRODUCTION

Contrastive Learning is a machine learning technique used to learn the general characteristics of an unlabeled dataset by teaching the model which data points are similar or different by incorporating versions of the same sample next to each other while attempting to push away the embeds from different samples (as explained in "Understanding Contrastive Learning (Tiu, 2021)."). This technique is very useful because manually annotating unlabeled datasets is a very time and money-consuming task, especially in fields such as *Computer Vision* or *Natural Language Processing*, where there is an increasing amount of data that is not labeled. The Contrastive Learning pipeline can be divided into three main sections:

- **Augmentation**: for each sample in our dataset, two combinations of augmentation are performed, in such a way as to use the original image as an anchor, its augmented version as a positive sample, and the rest of the images in the batch (or in the training data) as negative samples.

- **Encoding**: we feed our augmented data into our deep learning model, to create vector representations for each sample. The goal is to train the model to produce similar representations for similar samples.

- **Training**: we try to maximize the similarity of the two vector representations by minimizing a *Contrastive Loss* function.

2 METHOD

Model   There are several possible approaches to managing the 3D point cloud, such as *Voxelization*, which is not very efficient, or *Multi-View*, which is more powerful than the first, but we don't use 3D information. However, there are Deep Learning models that can operate directly on it, thanks to the fact that they are invariant to permutations and therefore to the ordering of points. Examples of these models are: *PPFNet* (Birdal et al., 2018), *PointNet/Pointnet++* (Guibas et al., 2007), *EdgeConv/DynamicEdgeConv* (Bronstein et al., 2020).

For the network architecture, I took inspiration from the SimCLR (for more information see "A Simple Framework for Contrastive Learning of Visual Representations (Chen et al., 2020a)."), where an **End-to-End** architecture is used (Figure 1), i.e. for each sample x, we have two augmented versions ($\tilde{x}_i$ and $\tilde{x}_j$), which we will pass to the encoder $f(\cdot)$ (consisting of two **DynamicEdgeConv** layers), to obtain a representation vector. Then we pass this to the Projection Head, a fully connected network. The projection head $g(\cdot)$ maps the representation h into a smaller space where we apply the loss function.

The reason why it is necessary to apply the Projection Head is that most similarity measures that are used in contrastive losses suffer from the *curse of dimensionality*. Therefore, when we calculate the loss on smaller vectors, we will get better results (as we can see in "*A Simple Framework for Contrastive Learning of Visual Representations* Chen et al. (2020b).").

Figure 1: Contrasting Learning model architecture (Chen et al., 2020a).

Loss Function As Loss function I used **NTXentLoss**, which compare the similarity of $z_i = g(h_i)$ and $z_j = g(h_j)$ to the similarity of z_i to any other representation in the batch z_k, by performing a *soft-max* over the similarity values. The loss can be formally written as:

$$\mathcal{L}_{i,j} = -\log \frac{\exp(\text{sim}(z_i, z_j)/\tau)}{\sum_{k=1}^{2N} \mathbb{1}_{[k \neq i]} \exp(\text{sim}(z_i, z_k)/\tau)} \tag{1}$$

where τ is the *temperature*, $\mathbb{1}_{[k \neq i]}$ is an indicator function (1 if $k \neq i$, 0 otherwise), and $sim()$ is the application of Cosine Similarity. The code of this work is available at the following web address: `https://bit.ly/contrastive-learning-3D-shapes`.

3 EXPERIMENTAL RESULTS

For testing, I used a **Down-Stream** approach (as SimCLR) to see how the model performs with small data. I used logistic regression to see if the model generalizes well, and we'll pass the 3D elements that have already been processed by our $f(\cdot)$ function, i.e. encoded in their feature vector, to associate the representations with a class prediction. I achieved 51% accuracy in 100 epochs, as can be seen from Figure 2.

Figure 2: Result of the Down-Stream Task.

4 DISCUSSION AND CONCLUSION

One of the main problems is the use of the End-to-End architecture, which, as explained in *A survey on contrastive self-supervised learning* Banerjee et al. (2020), works well only in the presence of a large number of negative samples and, therefore, a large batch size. In fact, due to hardware limitations, I was only able to use batches of 64 elements. A future improvement could be to use a different architecture that has no problems related to the use of the GPU memory, for example, the Memory Bank or the Momentum Encoder.

URM STATEMENT

The key author of this work meets the URM criteria of the ICLR 2023 Tiny Papers Track.

REFERENCES

Debapriya Banerjee, Fillia Makedon, Ashish Jaiswal, Ashwin Ramesh Babu, and Mohammad Zaki Zadeh. A survey on contrastive self-supervised learning. *Technologies 2021*, 2020.

Tolga Birdal, Haowen Deng, and Slobodan Ilic. Ppfnet: Global context aware local features for robust 3d point matching. *CVPR 2018*, 2018.

Michael M. Bronstein, Ziwei Liu, Sanjay E. Sarma, Justin M. Solomon, Yongbin Ssun, and Yue Wang. Dynamic graph cnn for learning on point clouds. *Technologies 2021*, 2020.

Ting Chen, Geoffrey Hinton, Simon Kornblith, and Mohammad Norouzi. A simple framework for contrastive learning of visual representations. *PMLR*, 2020a.

Ting Chen, Geoffrey Hinton, Simon Kornblith, Mohammad Norouzi, and Kevin Swersky. Big self-supervised models are strong semi-supervised learners. *Advances in Neural Information Processing Systems 2020*, 2020b.

Leonidas J. Guibas, Charles R. Qi, Hao Su, and Li Yi. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *NIPS'17*, 2007.

Ekin Tiu. Understanding contrastive learning. `https://towardsdatascience.com/understanding-contrastive-learning-d5b19fd96607`, 2021.