Infrastructure for AI Agents

Abstract

Increasingly many AI systems can plan and execute interactions in open-ended environments, such as making phone calls or buying online goods. As developers grow the space of tasks that such **AI agents** can accomplish, we will need tools both to unlock their benefits and manage their risks. Current tools are largely insufficient because they are not designed to shape how agents interact with existing institutions (e.g., legal and economic systems) or actors (e.g., digital service providers, humans, other AI agents). For example, alignment techniques by nature do not assure counterparties that some human will be held accountable when a user instructs an agent to perform an illegal action. To fill this gap, we propose the concept of **agent infrastructure**: technical systems and shared protocols external to agents that are designed to mediate and influence their interactions with and impacts on their environments. Agent infrastructure could consist both of new tools and reconfigurations or extensions of existing tools. For example, to facilitate accountability, protocols that tie users to agents could build upon existing systems for user authentication, such as OpenID. Just as the Internet relies on infrastructure like HTTPS, we argue that agent infrastructure will be similarly indispensable to ecosystems of agents. We identify three functions for agent infrastructure: 1) attributing actions, properties, and other information to specific agents, their users, or other actors; 2) shaping agents' interactions; and 3) detecting and remedying harmful actions from agents. We provide an incomplete catalog of research directions that could help achieve each function, explaining use cases, adoption, limitations, and open questions. Making progress on agent infrastructure can prepare society for the adoption of more advanced agents.

1 Introduction

A fundamental goal of the AI research community is to build **AI agents**: AI systems that can plan and execute interactions in open-ended environments,[1] such as making phone calls or buying online goods (Maes, 1994; 1995; Lieberman, 1997; Jennings et al., 1998; Johnson, 2011; Sutton & Barto, 2018; Russell & Norvig, 2021; Chan et al., 2023; Shavit et al., 2023; Wu et al., 2023; OpenAI, 2018; Gabriel et al., 2024; Kolt, 2024; Lazar, 2024). Agents differ from other computational systems in two significant ways. First, in comparison to foundation models used as chatbots, agents directly interact with the world (e.g., a flight booking website) rather than only with users. Second, in comparison to traditional software (e.g., an implementation of a sorting algorithm), agents can adapt to under-specified task instructions. Although the AI community has been developing agents for decades, these agents typically performed only a narrow set of tasks (Wooldridge, 2009; Mnih et al., 2013; Silver et al., 2018; Badia et al., 2020). In contrast, recent agents built upon language models can attempt—with varying degrees of reliability (Kapoor et al., 2024; Liu et al., 2023; Mialon et al., 2023; Lu et al., 2024; Zhang et al., 2024)—a much wider array of tasks, such as software engineering (Jimenez et al., 2024; Wu, 2024; Chowdhury et al., 2024) or office support (Gur et al., 2024; MultiOn, 2024).

As developers expand the space of tasks that AI agents can accomplish, we will need tools both to unlock their benefits and manage their risks. As an example of a potential benefit, personalized agents could help individuals make a wide variety of difficult decisions, such as what insurance to buy or which school to attend

---

[1]Gabriel et al. (2024) heavily inspire this definition. See (Maes, 1994; Sutton & Barto, 2018; Chan et al., 2023; Shavit et al., 2023; Kolt, 2024; Lazar, 2024) for other definitions.

Figure 1: **Agent infrastructure** consists of technical systems and shared protocols external to agents that are designed to mediate and influence their interactions with and impacts on their environments, including interactions with existing institutions (e.g., legal and economic systems) and actors (e.g., digital service providers, humans, other AI agents).

(Van Loo, 2019; Sunstein, 2024; Lazar et al., 2024). Yet, blockers such as a lack of reliability, an inability to maintain effective oversight, or the absence of recourse mechanisms could hinder adoption. Compared to the adoption of chatbots, these blockers could be more significant in the context of agents because the latter could directly cause negative consequences in the world (e.g., a mistaken financial transaction). Tools that address these blockers could enable positive uses of agents that would otherwise not materialize. On the other hand, if AI agents are adopted despite such blockers, we will need tools to prevent and respond to resulting problems. One such problem is disruptions to digital services that can result from the ability to carry out certain tasks at speed and scale, analogous to DDoS attacks. For example, an individual fradulently obtained more than 10 million dollars in royalties from Spotify by automating music creation and streaming (U.S. Attorney's Office, 2024).

The predominant focus of AI safety research is on **system-level** interventions, which intervene on the AI system itself to shape its behaviour. Major areas of work include goal specification and following (Hadfield-Menell et al., 2016; Christiano et al., 2017; Leike et al., 2018; Bai et al., 2022; Hua et al., 2024; Wang et al., 2024a;b; Kirk et al., 2024; Huang et al., 2024; OpenAI, 2024), adversarial robustness (Greshake et al., 2023; Tamirisa et al., 2024; Zou et al., 2024; Anil et al., 2024; Wallace et al., 2024), and cooperation (Lerer & Peysakhovich, 2019; Hu et al., 2020; Leibo et al., 2021; Dafoe et al., 2021). System-level interventions can help to improve the reliability of agents when they work and are adopted (Askell et al., 2019), but they are inapplicable to many of the problems we discuss above. For example, they by nature do not provide accountability or recourse when harm occurs. Addressing such problems will instead require structuring how agents interact with existing institutions (e.g., legal and economic systems) and actors (e.g., web service providers, humans, other AI agents).

To answer this challenge, we propose the concept of **agent infrastructure**: technical systems and shared protocols external to agents[2] that are designed to mediate and influence their interactions with and impacts on their environments[3] These systems and protocols could be novel, or could be reconfigurations or extensions of existing systems and protocols. Examples of agent infrastructure include inter-agent communication protocols (Marro et al., 2024), IDs for agents (Chan et al., 2024b), systems for certifying an agent's properties or behaviour, and methods for rolling back an agent's actions (Patil et al., 2024). We include more examples in Table 1. Our notion of agent infrastructure is *not* about the technical systems that enable basic operation of agents (e.g., memory systems, cloud compute), although it will in practice often build upon or modify such systems. Furthermore, while our discussion will be grounded in language-model-based agents, the core

---

[2]I.e., they are not system-level interventions.

[3]See Section 7 for a comparison of agent infrastructure with adaptation interventions (Bernardi et al., 2024), which roughly include any intervention that is not a system-level intervention.

Function	Research directions
Attribution (Section 3): Attributing actions, properties, and other information to agents or users	• **Identity binding** (Section 3.1): Associates an agent or its actions with a legal identity, such as a human or corporation.

• **Certification** (Section 3.2): Makes, verifies, and revokes claims about an agent (instance), such as what data the agent is collecting, which tools it can access, and the level of autonomy it has been authorized to exercise.

• **Agent IDs** (Section 3.3): Identifies instances of agents and links to useful attributes, such as the credentials above. |
| **Interaction** (Section 4): Shaping how agents interact with counterparties. | • **Agent channels** (Section 4.1): Isolates agent traffic from all other digital traffic in interactions with an existing digital service (e.g., Airbnb).

• **Oversight layers** (Section 4.2): Enables actors (e.g., a user) to intervene upon an agent's actions.

• **Inter-agent communication** (Section 4.3): Helps facilitate joint activities amongst groups of agents.

• **Commitment devices** (Section 4.4): Enforce commitments between agents. |
| **Response** (Section 5): Addressing problems that occur during interaction with an agent. | • **Incident reporting** (Section 5.1): Enables actors (e.g., humans, agents interacting with other agents) to report incidents.

• **Rollbacks** (Section 5.2): Helps void or undo an agent's actions. |

Table 1: This table summarizes all of the types of agent infrastructure that we discuss in this work.

ideas of agent infrastructure are largely architecture-agnostic and extend existing work across computational science, economics, and social science (Wooldridge, 2009; Perrier, 2025).

To further understand the distinctions between agent infrastructure and system-level interventions, consider traffic safety as an analogy. If we treat human drivers as analogous to AI agents, system-level interventions includes driver training programs. Infrastructure could include traffic lights, roundabouts, emergency lanes, and camera-enforced speed limits. We provide more comparisons in Table 2.

Just as the Internet relies on infrastructure like TCP (Eddy, 2022), HTTPS (Fielding et al., 2022), and BGP (Rekhter et al., 2006), we argue that agent infrastructure will likely be crucial for unlocking the benefits and managing the risks of agents. As an example of unlocking benefits, protocols that tie an agent's actions to a user could facilitate accountability and thereby reduce blockers to agent adoption. Analogously, the ability to perform secure financial transactions over HTTPS enables an e-commerce market in the trillions of dollars (Statista, 2024). As an example of managing risks, agent infrastructure can support system-level interventions. For instance, a certification system for agents could warn actors (e.g., other agents) not to interact with agents that lack certain safeguards, just as browsers flag non-HTTPS websites. In this way, agent infrastructure can use agents' interactions as a leverage point to improve safety: restricting an agent's interactions correspondingly restricts the agent's potential negative impacts.

Domain	System-level	Infrastructure
AI agent safety	Fine-tuning, prompting, unlearning, filtering training data	Protocol to forget confidential information from an interaction, technologies to enable agent certification, distinct interaction interfaces for agents
Traffic safety	Driver training programs	Traffic lights, roundabouts, emergency lanes, camera-enforced speed limits
Health	Medication, exercise	Hospitals, emergency response systems, parks for exercise

Table 2: We compare analogues to system-level interventions and agent infrastructure across different domains. These categories of interventions are often complementary.

This work identifies three functions that agent infrastructure could serve: 1) attributing actions, properties, and other information to specific agents or other actors; 2) shaping agents' interactions; and 3) detecting and remedying harmful actions from agents. We propose infrastructure that could help achieve each function, including analysis of use cases, adoption, limitations, and open questions. Our suggestions are primarily aimed at researchers and developers who may want to build agent infrastructure. These suggestions could also be useful to governments or funding bodies who may want to support its construction.

2 Agent Infrastructure

2.1 Categories of Agent Infrastructure

We focus on agents that interact with digital environments. Roughly speaking, we consider an agent to consist of the underlying machine-learning model and any primitives that provide basic functionality (e.g., memory, scaffolding). Language-model agents commonly act by issuing commands to tools, such as APIs that return the output of a separate software service (e.g., the weather).[4] Environments consist of such tools and any counterparties that interact with an agent (e.g., other agents, humans).

Some of agent infrastructure applies to instances of agents. An **agent instance** is an instantiation of the underlying machine-learning model and any primitives for a particular user. Specifically, an instance would correspond to an interaction history, a set of available tools, memory, etc, much like process IDs in operating systems correspond to running instances of programs.[5] Agent instances are a useful concept because different instances of the same underlying model and primitives can have different users or behave differently, and therefore potentially justify different treatment.

We identify three functions of agent infrastructure. **Attribution** is about attributing actions, properties, and other information to (instances of) agents, users, or other actors. **Interaction** is about shaping agents' interactions with the world. Finally, **response** is about detecting and remedying harmful actions from agents. To maintain a manageable scope, we do not discuss how infrastructure could help to manage more diffuse potential impacts, such as widespread unemployment. We summarize all the infrastructure we discuss in Table 1.

2.2 Example

To illustrate how agent infrastructure could help unlock the benefits and manage the risks of agents, consider the task of running a company. In this hypothetical company, agents would perform or assist with the work that human employees would usually perform, such as operations, R&D, and legal tasks. Agent infrastructure could enable the following functions for this agent-run company.

---

[4]See Wooldridge (2009); Perrier & Lazar (2025) for further discussion of ontologies of agents.

[5]An instance is an abstraction and may not correspond to a hardware separation. For example, inference calls for different instances could be batched together on the same piece of hardware.

- Human review: Human managers can make use of oversight layers (Section 4.2) to ensure that their agent employees are not malfunctioning.

- Coordination: A communication protocol (Section 4.3) and commitment devices (Section 4.4) can facilitate coordination between agents both within a company and from different companies. For example, agents could make commitments to carry out certain tasks, much as companies create contracts.

- Recourse: A lack of recourse mechanisms could discourage interaction with the company's agents. One way to address this issue is by ensuring that each agent has at least one human that can answer for the agent's actions (Section 3.1), and making this information available to those that interact with the company's agents or a third-party mediator.

- Undoing mistakes: Rollback mechanisms (Section 5.2) enable certain decisions, such as updates to compensation or internal data management processes, to be easily undone if an agent makes a mistake.[6]

3 Attribution

Attribution infrastructure attributes actions, properties, and other information to (instances of) agents, users, or other actors. **Identity binding** links an agent or its actions to an existing legal identity. **Certification** would provide assurance about behaviour and properties of an agent instance. An **agent ID** would be a container of information about an agent instance, such as associated certifications. In Figure 2, we depict how these pieces of infrastructure fit together.

Figure 2: **Identity binding** links an agent or its actions to an existing legal identity, **certification** would provide assurance about behaviour and properties of an agent instance, and an **agent IDs** would be a container of information about an agent instance. We illustrate **identity binding** for a user, but an agent could also be bound to other actors, such as those involved in overseeing it

3.1 Identity Binding

Description: AI agents are not legal entities[7]. The ability (but not necessarily the requirement) to associate an agent's actions with a legal entity, such as a human or a corporation, could help existing institutions accommodate agents. For example, users could be held accountable for illegal activity (e.g., fraud (Fang et al., 2024)) that they instruct their agents to carry out. Analogously, cars are associated to drivers through license plates and registries. Such binding could be helpful even when the relevant legal entity is not fully responsible for all of the agents' actions. For example, in addition to the employee using an agent, managers reviewing the agent's actions and the corporation hiring the employee could potentially

---

[6]The conditions under which a decision should be undone is a separate question. Rollback mechanisms merely provide flexibility.

[7]Some argue that sufficiently capable future agents should have legal rights (Salib & Goldstein, 2024).

bear some responsibility. With this motivation, we define **identity binding** to be a process that consists of (1) authentication of an identity and (2) linking that identity to an (instance of an) agent or its actions. Crucially, linking an identity to an agent does not mean making the identity visible publicly. For example, identity information could be accessible only to authorized parties, such as if needed for legal action, or only reveal limited information, such as the fact that a real person is responsible for the agent (Adler et al., 2024). Further below, we discuss how existing infrastructure could help accomplish (1) and (2), along with modifications that may be needed.

Potential functions:

- Accountability: Malicious uses of agents could be harder to address if all agents acted anonymously. For example, anonymity enables Sybil attacks, wherein someone creates multiple fake identities to undermine a network (e.g., an online voting system).

- Trust: Counterparties could be more willing to engage in productive interactions with agents that are bound to legal entities because it could be easier to obtain recourse in case of harm. Analogously, identity verification of drivers reassures users that would otherwise be dissuaded from ridesharing by personal safety considerations.

- Application of laws: Identity binding could allow the broader application of existing laws to interactions between agents. For example, at least as a starting point, identity binding could provide evidence that an agent did indeed enter into a contract on behalf of a particular principal (Benthall & Shekman, 2023; Aguirre et al., 2020).

Existing alternatives: Existing technologies can provide some functionality for authentication and identity linking, but have limitations. User authentication is already required for many digital services, such as banking (through know-your-customer regulations) or services requiring an account (through logging in with OAuth). The actions of agents interacting with such services would by default be attributable to the user. However, some services only provide attribution to a pseudonymous internet user, rather than a specific legal entity. In addition, there is currently no comparable authentication system for agent-agent interactions or actors other than users. The former may be important for agents that are significant economic actors, whereas the latter could include actors that assume responsibility for some of the agent's actions (e.g., an insurance company) or other overseers of the agent.

Identity information could be linked to an agent in a variety of ways. Drawing from work on content provenance (e.g., (C2PA, 2023)), identity information can be included as metadata or as a watermark. However, metadata can be stripped from content and watermarks can potentially be removed (Zhang et al., 2023). Furthermore, privacy considerations could weigh against revealing identity information in this way. If so, a potential alternative could be to establish a trusted intermediary that would hold this identity information (Kling et al., 1999). Counterparties could request that this intermediary reveal the information or use it appropriately in the event it is needed. As an analogy, ISPs can share information about their users in response to a criminal investigation. It remains to be seen how such a function could be provided for agents.

Adoption: Firstly, users might be more likely to engage with platforms that include or require identity binding. Some evidence suggests that contractors use AI systems on platforms like Upwork (Veselovsky et al., 2023). Dharmesh (2024) is also creating a service where AI agents play the role of crowdworkers and are matched to tasks. In both of these cases, customers are likely to engage more fully if they know there is a person ultimately responsible for the service, similar to identity verification for gig economy services (Uber, 2025; DoorDash, 2025). Secondly, platforms might require identity binding to avoid Sybil-like attacks. For example, an individual recently defrauded Spotify of millions of dollars by synthetically generating music and creating multiple fake accounts to stream it (U.S. Attorney's Office, 2024).

Limitations: Identity binding entails at least some collection and use of user information, even if that information is only shared with authorized actors when needed. Security vulnerabilities analogous to those in existing authentication systems could compromise user information (Batra et al., 2024; Microsoft Threat Intelligence, 2023). More broadly, reduced anonymity (or the threat of reduced anonymity) could threaten personal safety (e.g., doxxing), hinder whistleblowing, and reduce expression of novel ideas (Kling et al.,

1999; Zittrain, 2006; Choi, 2012; Kang et al., 2013). Such concerns imply that identity binding may not be appropriate in every application of agents, and proportionate confidentiality provisions will be necessary when it is used. Analogously, although it can be abused, legislatures and courts have recognized the importance of identification of internet users under certain conditions (Ekstrand, 2003; Choi, 2012; noa, 2018).

Research questions:

- What key applications of agents could identity binding enable?

- How can identity binding build upon existing digital identity solutions, such as (national) digital wallets?

- How could an authentication system be designed for agent-agent interactions and authentication of actors other than human users (e.g., for companies with digital identities (GLEIF, 2024))?

- How can identity information be linked to an agent or its actions?

- If intermediaries hold identity information, who should be able to request access to or use of the information, such as for obtaining recourse? Under what conditions should such access or use be granted?

3.2 Certification

Description: Before interacting with an agent (instance), counterparties might want assurances about its operation, behaviour, or properties. For example, agents whose actions are regularly reviewed could be more trustworthy than agents who do not undergo such review. Claims about operation, behavior, or properties could come from a user, an agent deployer, or other actors (e.g., third-party auditors). Actors making such claims could include them in certificates, which could be associated with the relevant agent and made visible to counterparties interacting with it. Analogously, SSL certificates make claims to website users about domain ownership. **Certification infrastructure** consists of tools for making, verifying, and revoking certificates for agents. Verification includes how those viewing a certificate can verify both its claims and that it corresponds to the agent with which they are interacting.

Example claims: We provide potential example claims of an agent's operation, behavior, or properties that could be included in a certificate.

- The tools the agent can access: Certain tools, such as commitment devices (Sun et al., 2023), could make agents more reliable or useful.

- Capabilities, accounting for post-training modifications: Weaker agents could be more susceptible to prompt injections from stronger agents (e.g., stronger agents could be more capable at detecting such attempts). If so, a user might want their agent only to interact with agents that are at most as strong as their agent. Accounting for post-training modifications would likely involve analysis of an agent's behaviour log. Doing so in a privacy-preserving way is an open problem (Trask et al., 2023; 2024).

- The level of autonomy with which the agent is authorized to act: Agents that act with more regular human oversight could be, but are not necessarily (Parasuraman & Riley, 1997; Skitka et al., 1999; Green, 2022), more trustworthy.

- How an agent handles sensitive information: For example, an agent could follow a protocol to delete sensitive information from context and memory after use (Rahaman et al., 2024).

Potential functions:

- Trust: Certificates for safety-relevant properties can build trust in agent interactions. For such trust not to be misplaced, a certificate should at minimum only contain claims about what can feasibly be known about the agent, given the state of the science. For example, it may be difficult to provide useful bounds on whether an agent will ever violate a safety constraint.

- Races to the top: If counterparties can selectively interact with agents that have certificates for pro-social properties (e.g., that use cooperation mechanisms (Sun et al., 2023)), developers and users could be incentivized to respectively develop and use agents with those properties.

- Supporting recourse: Certain forms of recourse (e.g., undoing an action; see Section 5.2) could rely on an auditor to certify that, for example, an agent was prompt injected.

Existing alternatives: Auditing of companies involved in the development or use of agents, such as developers or cloud compute providers, can be a component of certification of agents. For example, an auditor could verify that a cloud compute provider has policies for only running agents that have passed certain safety standards. Yet, certifying such companies could be ineffective if large numbers of users modify and deploy their own agents.

In the absence of any additional certification infrastructure, developers, deployers, and users could make their own claims about their agents. However, counterparties may be unable to assess the veracity of such claims. Evaluating AI systems is not straightforward and empirical experiments can be subtly misleading (Leech et al., 2024). Even so, entities may still be able to assess the quality of an agent's actions and reject them if necessary. For example, a counterparty may not know in general how reliable a software engineering agent is, but could run software to verify the correctness of the agent's code.

Adoption: Demand for certification is likely to vary across domains and contexts. For instance, protocols for forgetting sensitive information can enable agreements that would otherwise not be possible (Rahaman et al., 2024). Certifying that an agent can follow such protocol seems more important for high-stakes negotiations. Feasibility and economic cost could also affect demand. For example, properties that require access to interaction logs (e.g., whether a prompt injection is present) could raise privacy concerns, in the absence of privacy-preserving certification methods (Trask et al., 2023; 2024).

Finally, as discussed above, developers and deployers could support certification as a way to credibly signal the trustworthiness of their agents.

Limitations: It could be impossible or extremely difficult to verify certain properties. Providing meaningful guarantees about the behavior of a system in general is an active area of research (Dalrymple et al., 2024). If meaningful guarantees are not technically possible, certifications could provide a false sense of security. Other properties could be feasible, but potentially impractical or invasive, to certify. A potential example could be whether an agent has interacted with a particular, other agent.

Furthermore, actors creating certificates for agents could be incompetent, captured, or fail to perform any useful certification. A notable case is TrustARC (formerly TRUSTe), who provided privacy certification for websites. Although TrustARC claimed to verify website privacy policies, it often did not conduct any such checks whatsoever (Connolly et al., 2014). Surprisingly, as an example of adverse selection, Edelman (2009) provides evidence that websites that obtained TrustARC certification were significantly less trustworthy than websites without it. potential Ways to address this problem include oversight over actors performing certification of agents and transparency requirements about their processes.

Research questions:

- For the example claims we list above, who should be making the claims? How could the claims be verified?

- What other claims about an agent would be useful to make?

- How can actors verify that a certificate corresponds to the agent instance with which they are interacting?

- Under what conditions should a certificate be revoked? For example, claims about an agent's future behavior could become outdated the longer the agent operates.

- How would certification of agents interact with existing auditing practices and regimes (Raji et al., 2020; 2022)?

- How could existing infrastructure (e.g., verifiable credentials (Sporny et al., 2024)) support certification of agents?

- What existing certification methods in information systems and cybersecurity could provide useful inspiration (Oberkampf & Roy, 2010; Perrier, 2025; Perrier & Lazar, 2025)?

- What oversight or transparency requirements should exist for actors providing certificates for agents?

- What recourse should be available if certificates contain mistakes or are otherwise compromised in some way?

3.3   Agent IDs

Description: An **agent ID** would at minimum consist of a unique identifier[8] for an agent instance, and potentially include other information relevant to the instance, such as a system card or certifications (Chan et al., 2024b). ID-like systems exist across many domains to facilitate risk and incident management, such as serial numbers on consumer products, tail numbers on aircraft, and registration numbers for businesses. Although any AI system could have an ID, IDs could be significantly more useful for agents because they take actions in the world (see below).

Potential functions: Many of these uses draw from Chan et al. (2024b).

- Supporting certification: An ID could present an agent's certifications (Section 3.2) and bound identities (Section 3.1) to entities that seek to engage with it.

- Incident response: IDs could provide information that is useful for incident response. For example, an agent could create sub-agents to split up a harmful task into multiple sub-tasks (Jones et al., 2024). An ID could link the activities of these sub-agents to the original agent. An ID could also be useful for detecting cross-platform incidents, where an agent harms multiple counterparties.

- Enabling targeted action against particular agents: Much like how process IDs in operating systems enable monitoring and resource restriction, an ID could enable interventions on the agents that are causing harm.

Existing alternatives: For agents that interact with digital services, OAuth tokens or (read-only) API keys could aid incident attribution. However, such tools do not apply to interactions between agents. These tools are also service-specific. For example, an OAuth token cannot link the activity of an agent across different counterparties, nor can it link the activities of sub-agents to the agent that created them.

IP addresses could also help incident attribution, but may not reliably identify an agent instance. Indeed, they may not be static and can also be shared amongst different internet users.

Adoption: Identifiers could be a part of existing obligations to inform humans when they are interacting with AI systems (noa, 2024, Art. 50(1)). As agents are assigned increasingly complex roles, counterparties could demand more information from IDs so as to ensure reliable interactions (e.g., through certification) and facilitate incident attribution.

Counterparties that expect only to interact with agents (or which only interact with agents through specific channels [Section 4.1]) could require IDs before an interaction. Other counterparties which also interact with systems other than agents may have more difficulty doing so. For example, suppose a counterparty engages with both agents and traditional software programs. Extending a verifiable ID system from agents to all software programs would likely be infeasible, since traditional software programs do not have IDs.

Limitations: IDs could allow attackers to target particular agents and their users. If activity associated with an ID is logged, leaks of such information could allow attackers to identify high-value targets. Knowing an agent's frequently used services could also facilitate exploits like prompt injections (e.g., attackers could infect particular websites). When interacting with a particular agent, attackers could exfiltrate information or jailbreak the agent to act on the attacker's behalf, such as by performing financial transfers.

IDs could also be stolen or otherwise compromised. For example, IDs that depend on certificate authorities are vulnerable to existing security vulnerabilities (Berkowsky & Hayajneh, 2017).

Research questions:

- How could IDs complement existing tools for incident investigation?

- Where should IDs be required, and what information should an ID include?

---

[8]A cryptographic scheme is necessary to prevent spoofing of the identifier. See Chan et al. (2024b) for more details.

Figure 3: **Agent channels** separate agent traffic from other digital traffic. **Oversight layers** enable actors to intervene on an agent's behaviour. **Inter-agent communication** help to facilitate joint activities amongst groups of agents. **Commitment devices** enforce commitments between agents. See Section 4 for discussion.

- How can counterparties incentivize or enforce ID usage (e.g., by making sure that agents use unique channels (Section 4.1))?

- When should IDs link to information identifying the user?

- What should entities be allowed to do with an identifier? For example, should an entity with an identifier be allowed to contact the associated agent, or otherwise interact with it?

- What other systems need to be in place to make IDs more useful? E.g., should there be a registry of certain agent IDs or a reviewing system?

- How can the design of IDs avoid known problems with existing Internet infrastructure (e.g., certificate authorities) (Berkowsky & Hayajneh, 2017; Dumitrescu & Pouwelse, 2024)?

- How can the design of IDs limit abuse (e.g., attackers use IDs to target particular agents and their users)?

4 Interaction

Interaction infrastructure consists of protocols and affordances to shape how agents interact with their environments. **Agent channels** would isolate agent traffic from other traffic. **Oversight layers** would enable actors to intervene on an agent's behaviour. **Inter-agent communication** protocols would help to facilitate joint activities amongst groups of agents. **Commitment devices** are mechanisms that enforce commitments between agents. We depict these pieces of infrastructure in Figure 3.

4.1 Agent Channels

Description: For interactions with a digital service (e.g., payment services), an **agent channel** would separate agent traffic (or AI traffic in general) from other digital traffic. An agent channel could, for example, facilitate incident management by temporarily suspending access if a language-model worm spreads (Cohen et al., 2024; Gu et al., 2024). Traffic separation is common across many applications. For example, digital payments companies isolate systems that handle cardholder data (Council, 2016). Some hospitals separate networks for storing and using different kinds of medical data, so as to safeguard privacy in case one network is compromised (Digital, 2023). Wi-Fi routers provide guest networks that restrict the activity of unfamiliar devices.

There are two axes of design considerations for agent channels. First, agent channels could be different software interfaces or protocols for agents, or could take the form of more dedicated internet infrastructure. As examples of the former, there are efforts to build agent-specific web browsers (Turow, 2024) and interaction protocols (Kaliski, 2024; Anthropic, 2024b). As examples of the latter, agents could have a dedicated block of IP addresses (which could perhaps function as IDs Section 3.3), or separate routing systems could handle agent traffic.

The second axis is how to operationalize traffic separation. Rate limits on human channels and the relative absence or weakening of such limits on agent channels could incentivize the use of the latter. However, it may in practice be difficult to separate agent or AI traffic from software traffic in general. For example, agents could write software that interacts with counterparties.[9]

Potential functions:

- Monitoring: Separate transaction data for agents, for example, can help to understand the potential macroeconomic effects of high volumes of agent activity (Van Loo, 2019).

- Managing incidents: Isolation of traffic could help to manage incidents. For example, providers of services could shut down agent channels, but not human channels, to restrict spread of a text or image worm (Cohen et al., 2024; Gu et al., 2024).

- Enforcing agent-specific rules: Agent channels could implement rules to support reliable agent use, such as around rolling back unintended actions (Section 5.2) or how to handle sensitive data.

- Reduced attack surface: Human graphical interfaces have a large attack surface. For example, imperceptible changes to a website page could hide a prompt injection. APIs designed for agents could reduce this attack surface, although text-based prompt injections would still be possible.

- Supporting IDs: As discussed in Section 3.3, agent channels could make it more feasible to require IDs from agents.

Existing alternatives: Agents currently use existing software interfaces when interacting with web services (Significant-Gravitas, 2024). In the absence of dedicated channels, behavioural tests could try to identify and isolate agent behaviour. CAPTCHAs tend to be unreliable (Hossen et al., 2020; Hossen & Hei, 2021; Searles et al., 2023). Another potential test is whether an entity interacts with an interface at faster-than-average human speeds. If so, the entity could undergo more intensive monitoring or have more limited access to functions, under the suspicion that it might not be human. This differential treatment would effectively constitute an agent channel, without building specific interfaces or other dedicated internet infrastructure.

Adoption: Agents currently have difficulty interacting with human interfaces (Furuta et al., 2024; Tao et al., 2023; Gur et al., 2024; Xie et al., 2024). If agent channels are optimized to help agents function more efficiently and reliably (Song et al., 2024), such as by simplifying interfaces (e.g., website navigation instructions) or imposing fewer limitations (e.g., higher rate limits, reduced latency) compared to human interfaces, there could be much demand for them. Yet, agents could soon become capable of interacting with with human interfaces. Encouraging the use of agent channels could therefore be time-sensitive.

---

[9]If agents come to mediate large fractions of digital interactions, there may be very little software that is not related to an agent in some way.

Limitations: Agent channels could fail to cover enough agents or could cover entities besides agents. On the first point, agent channels would likely be less effective if only a small number of agents use them. Monitoring of agent channels may miss incidents, and interventions on agent channels may not catch all agent activity. On the second point, although it seems difficult to prevent other entities from using agent channels, this limitation may not be significant. For example, any rules applied to agent channels (e.g., slowing the spread of a language-model worm by restricting activities) would simply also apply to those entities.

Research questions:

- How should agent channels be designed and implemented? Can their creation be automated (e.g., automatic API creation)?

- What could encourage the adoption of agent channels?

- Is it possible (or desirable) to isolate agent traffic for functionalities already provided by traditional software interfaces (e.g., email (Significant-Gravitas, 2024), weather retrieval (OpenAI, 2024))?

- What policies should govern the use of agent channels to influence or constrain agents?

4.2 Oversight Layers

Description: The potential for unreliable agent behaviour motivates review of the agent's actions. An **oversight layer** would consist of (1) a monitoring system to detect when external intervention is required during an agent's operation and (2) an interface for an actor to intervene. Examples of external intervention include the provision of additional information (e.g., about the task or what the agent is not authorized to do) or rejection of the agent's action. The actor in (2) could be a human user, but not necessarily. For example, a trusted, automated system could take the place of a user (Greenblatt et al., 2024; Dalrymple et al., 2024), especially if the oversight layer flags many actions. An oversight layer could also be useful for *any* actor that engages with an agent, not just a user. For example, a manager in a company could use an oversight layer to review actions from agents used by individual employees.

Potential functions:

- Rejecting unsafe actions: Agents could take consequential actions that are unbeknownst to, or unintended by, their users. For example, a malicious actor could prompt-inject an agent to drain a user's bank account. Similar to credit card fraud detection, methods for detecting when actions may be unintended could protect users.

- Improving functionality: As Hewett (2024) discusses, an oversight layer could ask a human for help whenever an agent is incapable of completing a particular action (e.g., misinterprets the task or is stuck in a loop), without the human having to restart the agent from scratch.

- Accountability: An oversight layer could make it easier to assess responsibility for an agent's actions, such as by recording the explicit approval of a user for an action that harmed another party.

- Generating useful information: Oversight layers could generate useful information about which agents tend to take actions that overseers reject more often. This information could enable, for example, insurance to be designed around the expected reliability of an agent.

Existing alternatives: Some technical frameworks already include some kind of oversight layer (Chase, 2022; Wu et al., 2023). See below for additional research questions to extend upon this work.

Adoption: There could be strong incentives to develop and implement oversight layers because they make agents more usable. However, it is unclear if the market will provide them to a socially optimal degree (or what a socially optimal degree would be). Analogously, although more granular social feed controls (e.g., reducing the degree of sensationalist content) would make social media more usable, major social media companies have not provided such options. Indeed, some controls may be against the financial interests of such companies. For example, removing sensationalist content could reduce engagement and ad revenue. Analogously, AI companies could hesitate about providing users with the ability to limit how agents engage

with activities that could be profitable for the company, such as making financial transactions or viewing advertisements.

Limitations: Oversight layers are only useful to the extent that actors use them to intervene as needed. Automation bias could reduce the ability of human actors to do so (Parasuraman & Riley, 1997; Skitka et al., 1999; Goddard et al., 2012). Weaker agents could also have difficulty in detecting problematic actions from stronger agents (Greenblatt et al., 2024).

Research questions:

- How can oversight layers maintain security or confidentiality (e.g., for approval of financial transaction or sending of sensitive information)?

- Can a monitoring system accurately flag actions that are likely to be unintended? E.g., the system could draw upon past user or agent behavior.

- Can a monitoring system accurately flag when an agent requires external intervention (e.g., additional information)?

- How can an oversight layer gracefully interrupt an agent when it requires external intervention and integrate additional information or actions from another actor?

- How can we design interfaces that allow users (or other actors) to set the degree of oversight (e.g., how often the user is notified of a flagged action)?

- How can we build trusted, automated systems (Greenblatt et al., 2024; Dalrymple et al., 2024) to intervene so as to minimize the degree of human intervention required?

- Will the market sufficiently provide for oversight layers? If not, what government action can best help incentivize their development and implementation?

4.3 Inter-Agent Communication

Description: Agents will likely interact not only with existing digital services, but also with other agents. For example, agents from different users could collaborate on shared projects. **Inter-agent communication infrastructure** includes (1) rules for how agents communicate and (2) the underlying technical systems to enable such communication. On (1), in addition to point-to-point communications, infrastructure may also need to facilitate broadcast-like communications (e.g., for important announcements). On (2), technical systems include an addressing system and the underlying messaging protocol. Agent channels (Section 4.1) are similar to inter-agent communication infrastructure, but focuses on interaction with existing digital services rather than interactions between agents.

Potential functions:

- Notification: Communications can convey important information. For example, an agent could warn other agents about the discovery of a security vulnerability.

- Cooperation: Communications could be useful for coordinating the activities of different agents, whether for completing shared projects or helping to resolve collective action problems.

- Negotiation: Agents could use communications to negotiate on rules for an interaction (Marro et al., 2024), such as how to handle confidential information (Rahaman et al., 2024).

Existing alternatives: Existing communication infrastructure may be difficult for agents to use because they require human involvement. For example, signing up for a Gmail account requires access to a phone number. It may also be difficult to add agent-specific functionality onto existing communication infrastructure. For instance, Facebook Messenger does not currently support broadcasting functions.

Adoption: The difficulties of using the existing alternatives above could spur adoption of more specialized inter-agent communication infrastructure.

Limitations: As with existing internet communication infrastructure, inter-agent communication infrastructure could be abused. For example, broadcast functionalities could be frequent sources of spam. Scammers Could use an addressing system to target agents they believe to be especially vulnerable (e.g., more easily hijacked through a prompt injection). The extent of abuse will likely depend upon the specifics of implementation (e.g., the effectiveness of any blocking functionalities).

Research questions:

- What security measures should inter-agent communication infrastructure incorporate? For example, what could be analogues to HTTPS?

- What are use cases for broadcasting?

- How should broadcasting be designed? For example, one way of implementing broadcasting is to rely on other agents to pass messages, rather than having a centralized system.

- What functionalities should inter-agent communication infrastructure include? For example, a communication protocol could include a way to signal or carry out commitments (Section 4.4).

- How can inter-agent communication infrastructure integrate with other types of agent infrastructure, such as oversight layers (Section 4.2), agent IDs (Section 3.3), and identity binding (Section 3.1)?

4.4 Commitment Devices

Description: An inability to credibly commit to particular actions is a key reason why rational actors sometimes do not obtain cooperative outcomes (Fearon, 1995; Powell, 2006; Clifton et al., 2022). Commitment devices—mechanisms that can enforce commitments—aim to address this issue. Examples of commitment devices include escrow payments, assurance contracts, and legal contracts. As agents become increasingly important economic and social actors, commitment devices designed for agents can help to achieve positive societal outcomes. Such commitment devices could simply be interfaces connecting agents to existing human commitment devices, or could be specially designed for agents.

Potential functions:

- Funding productive activities: The funding of productive activities can suffer from collective action problems (e.g., underprovisioning of public goods). Commitment devices could help agents with economic resources, whether used independently or on behalf of a user, cooperate to fund such activities. For example, future agents could initiate a vast array of projects or companies. Analogues to Kickstarter (i.e., assurance contracts (Bagnoli & Lipman, 1989; Tabarrok, 1998)) could facilitate funding of such projects or companies.

- Helping to avoid the tragedy of the commons: Commitment device could allow agents to agree not to carry out risky activities as long as others do the same, even if such activities advance the interests of the individual agent or user. For example, competitive pressures in AI development likely lead to underinvestment in safety (Askell et al., 2019). Future agents that are able to perform such development (Wijk et al., 2024) or run AI companies could commit, for example, not to build systems that surpass certain capability thresholds without sufficient safety guardrails, so long as others do the same.

Existing alternatives: Commitment devices that depend upon (threats of) action in the physical world or human social norms, such as legal contracts or making announcements to friends, are likely to be ineffective for agents that we are currently building. Connecting agents to existing software-based commitment devices, such as smart contracts, is likely to be more fruitful in the short term.

Adoption: Commitment devices are low-cost for actors who seek to make conditional commitments. If the conditions of the commitment do not hold (e.g., a quorum is reached), the actors take no action. Some types of commitment devices, such as dominant assurance contracts (Tabarrok, 1998), may even positively incentivize participation in the device.

Limitations: A commitment device is only useful in so far as it is employed. Depending on how a commitment device is implemented, users could be able to circumvent them. For example, if a commitment device

Figure 4: **Incident reporting** systems would collect information about and respond to events that could result in harm, while **Rollbacks** are tools that would void or undo an agent's actions. See Section 5 for further discussion.

depends upon modifying an agent's weights so that it takes an action, the user could simply shut the agent down.

Commitments could also lead to negative outcomes. For example, an agent that misunderstands a user's preferences could mistakenly commit funds to a project that the user does not support. More broadly, improved cooperation between agents could come at the expense of actors not included within the cooperative coalition (Dafoe et al., 2021; Fish et al., 2024), such as humans who are less capable of using cooperative technologies.

Research questions:

- What commitment devices could help agents from different users better cooperate on productive projects (e.g., software development)?

- How could commitment devices integrate with inter-agent communication channels (Section 4.3)?

- When should commitments between agents be legally enforceable?

- Will private actors sufficiently provide for commitment devices?

- If future agents are responsive to legal incentives,[10] would new types of commitment devices still be necessary?

5 Response

Response infrastructure consists of tools for detecting and remediating harmful actions from agents. **Incident reporting** systems would collect information about and respond to events that could result in harm. **Rollbacks** are tools that would void or undo an agent's actions.

5.1 Incident Reporting

Description: As agents become more involved in economic and social activities, they could both cause or witness events that could result in harm. Responding to and learning from such events, which we call **incidents** (Wei & Heim, 2024), will require information gathering. Many compute providers and AI deployers already monitor their AI systems (Cloud, 2023; ChrisHMSFT et al., 2023; OpenAI, 2023b; AWS, 2023; OpenAI, 2023c; DeepMind, 2024; Anthropic, 2024c), but the downstream impacts of agents could be invisible to such actors. For example, a deployer of agent A would not observe the impact of any infectious code or prompts given to agent B. On the other hand, if agents become involved in many interactions, they

---

[10]One possibility is to directly train agents that follow the law.

could become a valuable source of information about incidents involving other agents. **Incident reporting** infrastructure consists of (1) tools and processes for agents and other actors to collect information about incidents and file incident reports, (2) ways to filter for informationally valuable reports and prevent inundations of spurious reports (Schneier & Sanders, 2024), and (3) scalable methods for analyzing and responding to reports. Such infrastructure could help prevent future incidents by informing improvements to agent systems and safeguards.

Others have also proposed incident reporting systems, but without the focus on agents as a source of information (Costanza-Chock et al., 2022; Wei & Heim, 2024). More broadly, analogous systems include financial whistleblower programs for financial institutions (Securities and Exchange Commission, 2024), public reporting systems for vehicle offenses (Government of the United Kingdom, 2024), and cybersecurity incident reporting (Government of the United Kingdom, 2022). Another related idea is using weaker AI systems to supervise stronger AI systems (Greenblatt et al., 2024).

Potential functions:

- Improving safety practices: Incident reports could surface novel harms or impacts that upstream actors, such as regulators or developers, had not considered. These actors can incorporate such insights into safety practices, such as by improving their monitoring systems or development processes.

- Monitoring locally run agents: No intermediaries can monitor the activities of agents that are locally run. Incident reports from counterparties that interact with these agents could help to fill this gap.

Existing alternatives: Existing incident reporting systems for AI are limited. Some AI companies run bug bounty programs (Anthropic, 2024a; OpenAI, 2023a). OpenAI allows users to flag whether a GPT is illegal or fails to function (OpenAI, 2024). Although some civil society organizations run reporting systems that accept broader types of incidents (AI Risk and Vulnerability Alliance, 2024; AIAAIC, 2024; Responsible AI Collaborative, 2024), no mechanisms yet commit government or industry to respond to those incidents. Furthermore, existing programs are designed to collect information only from humans, not AI agents.

A potential challenge for existing incident report systems in other countries is scaling up resources to detect and block spurious reports, as agents become more capable of crafting compelling reports (Schneier & Sanders, 2024). Identity binding (Section 3.1) could potentially alleviate the risk of spurious reports.

Adoption: Incident reports could help companies improve product functionality. Yet, incident reports could also result in reputational damage, such as being associated with building unsafe AI agents. Confidential reporting systems, such as in aviation, could reduce this hesitation so as to improve safety learning across an industry. On the other hand, ensuring accountability for incidents will likely require some government intervention.

Limitations: For interactions with anonymous agents, it is unclear if a counterparty would have information that could facilitate further investigation. To that extent, counterparties could prefer interacting with agents that have an ID (Section 3.3) or for which identity binding (Section 3.1) is possible. Attackers could also abuse incident reporting systems, for example to distract regulators from real incidents (Schneier & Sanders, 2024).

Research questions:

- If an agent causes an incident, what information could feasibly be included in an incident report? For example, an agent ID (Section 3.3) could be included if it is available.

- How can existing, domain-specific incident reporting systems make filing reports more accessible to agents? How can operators of incident reporting systems manage influxes of spurious reports? For example, could incident reporting systems require personhood credentials (Adler et al., 2024)?

- Which organizations should respond to incidents involving agents run on local compute?

- How can agents help with managing and responding to incident reports?

5.2 Rollbacks

Description: Voiding or undoing an agent's actions could be useful in certain circumstances. For example, if agents often malfunction and make incorrect financial transactions, reversal of such actions could reduce harms to users. **Rollback infrastructure** would enable voiding or undoing an agent's actions. It includes both mechanisms to implement such a voiding or undoing action, as well as interfaces for actors to perform or request it. As an example of the former, Patil et al. (2024) build a LM runtime that allows reversal to a previously saved state.

Potential functions:

- Undoing unintended actions: Agents that malfunction or are hijacked (Greshake et al., 2023) could act contrary to user interests, such as by exfiltrating sensitive information. Standardized processes for undoing these actions could protect users.

- Minimizing contagion: Rollbacks could reduce the negative impacts of agents on third parties. For example, an agent could use inter-agent communication channels (Section 4.3) to spread text or image worms, which could hijack other agents and propagate themselves (Cohen et al., 2024; Gu et al., 2024). To help prevent further infection, administrators of these communication channels could unsend or take down the worm.

- Enabling productive interactions: Parties could make contracts or trade on the basis of rollbacks. For example, two users could allow their agents to engage in a financial transaction with the proviso that the transaction be reversed if an independent, objective third-party (such as an automatic monitoring system) deems one of the agents to have jailbroken the other.

Existing alternatives: Rollback infrastructure already exists in certain domains. For example, banks can void fraudulent transactions and social media companies can take down content. As agents come to carry out more tasks, potential challenges include making the infrastructure more accessible and responsive to users, scaling it to the potentially increased demand for rollbacks (e.g., if hijacking of agents becomes common), and building rollback infrastructure in domains where it does not already exist.

Adoption: Although rollbacks are likely to be useful, those responsible for undoing an action may be resistant to implementing them. This resistance may stem from the additional business uncertainty of a transaction that could be undone. For example, online merchants may have difficulty predicting demand if orders are undone at highly variable rates. If the advantages of rollbacks outweigh such disadvantages, governments could intervene to encourage their implementation. Analogously, US federal legislation allows consumers to dispute fraudulent credit card transactions (noa, 2023). Furthermore, monitoring and approval of rollback requests could be resource intensive in terms of human or AI labour.

Limitations: Some actions may be practically difficult to undo. For example, there is no way to undo physical harm caused by an agent operating a robotic system. Preventing such actions altogether or remedying them in another way (e.g., compensation) may be more appropriate.

Research questions:

- How could a rollback mechanism for agents connect to existing methods for undoing actions (e.g., a credit card company undoing financial transactions)?

- Could the availability of a rollback option to the user be made conditional upon some measure of the agent's reliability?

- How does implementation of rollbacks for agents affect business economics? Are the effects significantly different than those from existing rollback mechanisms (e.g., refund policies)?

- When is government intervention necessary to support implementation of rollbacks?

- How could rollbacks be abused?

6 Common Challenges

We discuss challenges common not only to all types of agent infrastructure, but also infrastructure (e.g., for the Internet) more broadly.

6.1 Lack of Interoperability

Actors could adopt mutually incompatible forms of agent infrastructure. For example, different groups of developers and providers of digital services could implement ID systems that do not recognize IDs from competitor systems. An agent with a valid certification under one ID system may not be able to interact with entities that recognize another ID system. Although this lack of interoperability would make IDs less useful, it could benefit dominant players by shutting out potential competitors and creating a walled garden around users. Similar problems beset digital platforms (e.g., Facebook Messenger, WhatsApp, iMessage). Legislation such as the EU's Digital Markets Act has encouraged more interoperability in these cases, but it remains to be seen whether and how similar rules could apply to the implementation of agent infrastructure.

6.2 Difficulty of Use

Users will likely not opt for infrastructure that is unintuitive to use or requires substantial setup. For example, users could simply ignore oversight layers that flag too many actions.

6.3 Lock-In

Widespread adoption of harmful or ineffective infrastructure could be difficult to reverse. Consider the network effects of interaction protocols. Moving away from a common protocol could mean losing important traffic. As an additional barrier, the benefits of moving away from the protocol could be realized only once a sufficient number of entities do so. Adoption of the Border Gateway Protocol (BGP) (Rekhter et al., 2006) ran into similar problems. Routing information on BGP is not verifiable: any entity can claim to have a route to another entity. In 2008, in an attempt to block YouTube domestically, a Pakistani ISP accidentally sent routing information that brought down YouTube worldwide (Mathew, 2014). Despite the potential for such problems, adoption of a verifiable version of BGP has been slow (Testart et al., 2024). For agents, it will be important to adopt procedures for effectively updating infrastructure.

7 Related Work

Some recent literature has grown around how to govern foundation-model-based agents. Chan et al. (2023); Lazar (2024); Gabriel et al. (2024); Kolt (2024) study the ethical and societal implications of agents. Shavit et al. (2023) propose practices for governing agents, some of which are related to types of agent infrastructure we discuss. Chan et al. (2024a;b) propose agent infrastructure that can help certain actors obtain visibility into how agents are used, whereas we take a broader view of the functions of agent infrastructure. Finally, Perrier (2025); Perrier & Lazar (2025) study the ontology of agents and review historical examples of agent infrastructure.

We consider agent infrastructure to be a subset of **adaptation interventions** (Bernardi et al., 2024), which intervene on features other than the capabilities of an AI system. Our definition of agent infrastructure rules out adaptation interventions like laws, regulatory action, civic initiatives or activities, and applications of AI systems for a specific purpose (e.g., a company using an agent to find cybersecurity loopholes). At the same time, we expect agent infrastructure to help with the implementation of such adaptation interventions. For example, identity binding (Section 3.1) can aid the application of laws to AI agents.

8 Conclusion

We identified three functions for agent infrastructure: 1) tools for attributing actions, properties, and other information to specific agents, humans, or other actors; 2) methods for influencing agents' interactions

with the world; and 3) systems for detecting and remedying harmful actions from agents. We proposed infrastructure that could help achieve each function and outlined use cases, adoption, limitations, and open questions. Our presentation is likely not exhaustive, and additional types of agent infrastructure may become relevant as agent capabilities improve.

Agent infrastructure is not itself a complete solution, but is rather a platform for policies and norms. For example, tools for identity binding by themselves do not resolve how to allocate liability for the actions of agents (Kolt, 2024; Wills, 2024). Our presentation of infrastructure has also neglected other challenges. For instance, if the deployment of agents causes significant unemployment (Korinek & Juelfs, 2022; Korinek & Suh, 2024), more comprehensive economic and political responses will be needed. Future work should study the regulatory and legal reforms needed to adapt to these and other challenges.

There are many opportunities for moving forward with agent infrastructure. Researchers could investigate open questions around the use and implementation of agent infrastructure. Agent developers, service providers, and other companies could begin to build and experiment with infrastructure. Building infrastructure that is interoperable, easy to use, and updatable will likely require engagement between governments, industry, and civil society. Analogous to the Internet Engineering Task Force for maintaining Internet infrastructure, specialized institutions could support agent infrastructure. As increasingly capable agents enter the world, agent infrastructure could enable their use in a way that promotes prosperity and safeguards society.

References

Rogers Communications Inc. v. Voltage Pictures, September 2018. URL https://canlii.ca/t/hv2zb.

15 U.S. Code § 1666 - Correction of billing errors, 2023.

Regulation (EU) 2024/1689 of the European Parliament and of the Council of 13 June 2024 laying down harmonised rules on artificial intelligence and amending Regulations (EC) No 300/2008, (EU) No 167/2013, (EU) No 168/2013, (EU) 2018/858, (EU) 2018/1139 and (EU) 2019/2144 and Directives 2014/90/EU, (EU) 2016/797 and (EU) 2020/1828 (Artificial Intelligence Act), July 2024. URL http://data.europa.eu/eli/reg/2024/1689/oj. Volume: L tex.shorthand: EU AI Act.

Steven Adler, Zoë Hitzig, Shrey Jain, Catherine Brewer, Wayne Chang, Renée DiResta, Eddy Lazzarin, Sean McGregor, Wendy Seltzer, Divya Siddarth, Nouran Soliman, Tobin South, Connor Spelliscy, Manu Sporny, Varya Srivastava, John Bailey, Brian Christian, Andrew Critch, Ronnie Falcon, Heather Flanagan, Kim Hamilton Duffy, Eric Ho, Claire R. Leibowicz, Srikanth Nadhamuni, Alan Z. Rozenshtein, David Schnurr, Evan Shapiro, Lacey Strahm, Andrew Trask, Zoe Weinberg, Cedric Whitney, and Tom Zick. Personhood credentials: Artificial intelligence and the value of privacy-preserving tools to distinguish who is real online, August 2024. URL http://arxiv.org/abs/2408.07892. arXiv:2408.07892 [cs].

Anthony Aguirre, Gaia Dempsey, Harry Surden, and Peter B. Reiner. AI loyalty: A New Paradigm for Aligning Stakeholder Interests, March 2020. URL http://arxiv.org/abs/2003.11157. arXiv:2003.11157 [cs].

AI Risk and Vulnerability Alliance. AI Vulnerability Database, 2024. URL https://avidml.org/.

AIAAIC. AI, algorithmic, and automation incidents, 2024. URL https://www.aiaaic.org/aiaaic-repository/ai-algorithmic-and-automation-incidents.

Cem Anil, Esin Durmus, Nina Rimsky, Mrinank Sharma, Joe Benton, Sandipan Kundu, Joshua Batson, Meg Tong, Jesse Mu, Daniel J Ford, Francesco Mosconi, Rajashree Agrawal, Rylan Schaeffer, Naomi Bashkansky, Samuel Svenningsen, Mike Lambert, Ansh Radhakrishnan, Carson Denison, Evan J Hubinger, Yuntao Bai, Trenton Bricken, Timothy Maxwell, Nicholas Schiefer, James Sully, Alex Tamkin, Tamera Lanham, Karina Nguyen, Tomasz Korbak, Jared Kaplan, Deep Ganguli, Samuel R. Bowman, Ethan Perez, Roger Baker Grosse, and David Duvenaud. Many-shot jailbreaking. In *The thirty-eighth annual conference on neural information processing systems*, 2024. URL https://openreview.net/forum?id=cw5mgd71jW.

Anthropic. Expanding our model safety bug bounty program, August 2024a. URL https://www.anthropic.com/news/model-safety-bug-bounty.

Anthropic. Model Context Protocol, 2024b. URL https://modelcontextprotocol.io/introduction.

Anthropic. Responsible Scaling Policy. Technical report, October 2024c.

Amanda Askell, Miles Brundage, and Gillian Hadfield. The Role of Cooperation in Responsible AI Development. July 2019. URL https://arxiv.org/abs/1907.04534v1.

AWS. AI Safety Summit - Enhancing Frontier AI Safety, 2023. URL https://aws.amazon.com/uki/cloud-services/uk-gov-ai-safety-summit/.

Adrià Puigdomènech Badia, Bilal Piot, Steven Kapturowski, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, and Charles Blundell. Agent57: Outperforming the Atari Human Benchmark, March 2020. URL http://arxiv.org/abs/2003.13350. arXiv:2003.13350 [cs, stat].

Mark Bagnoli and Barton L. Lipman. Provision of Public Goods: Fully Implementing the Core through Private Contributions. *The Review of Economic Studies*, 56(4):583–601, October 1989. ISSN 0034-6527. doi: 10.2307/2297502. URL https://doi.org/10.2307/2297502.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, Carol Chen, Catherine Olsson, Christopher Olah, Danny Hernandez, Dawn Drain, Deep Ganguli, Dustin Li, Eli Tran-Johnson, Ethan Perez, Jamie Kerr, Jared Mueller, Jeffrey Ladish, Joshua Landau, Kamal Ndousse, Kamile Lukosuite, Liane Lovitt, Michael Sellitto, Nelson Elhage, Nicholas Schiefer, Noemi Mercado, Nova DasSarma, Robert Lasenby, Robin Larson, Sam Ringer, Scott Johnston, Shauna Kravec, Sheer El Showk, Stanislav Fort, Tamera Lanham, Timothy Telleen-Lawton, Tom Conerly, Tom Henighan, Tristan Hume, Samuel R. Bowman, Zac Hatfield-Dodds, Ben Mann, Dario Amodei, Nicholas Joseph, Sam McCandlish, Tom Brown, and Jared Kaplan. Constitutional AI: Harmlessness from AI Feedback, December 2022. URL http://arxiv.org/abs/2212.08073. arXiv:2212.08073 [cs].

Anirudh Batra, Sparsh Kulshrestha, and Abhishek Mathew. Compromising Google Accounts: Malwares Exploiting Undocumented OAuth2 Functionality for session hijacking, 2024. URL https://cloudsek.com/blog/compromising-google-accounts-malwares-exploiting-undocumented-oauth2-functionality-for-session-hijack

Sebastian Benthall and David Shekman. Designing Fiduciary Artificial Intelligence, July 2023. URL http://arxiv.org/abs/2308.02435. arXiv:2308.02435 [cs].

Jake A. Berkowsky and Thaier Hayajneh. Security issues with certificate authorities. In *2017 IEEE 8th Annual Ubiquitous Computing, Electronics and Mobile Communication Conference (UEMCON)*, pp. 449–455, October 2017. doi: 10.1109/UEMCON.2017.8249081. URL https://ieeexplore.ieee.org/document/8249081.

Jamie Bernardi, Gabriel Mukobi, Hilary Greaves, Lennart Heim, and Markus Anderljung. Societal Adaptation to Advanced AI, May 2024. URL http://arxiv.org/abs/2405.10295. arXiv:2405.10295 [cs].

C2PA. C2PA Technical Specification, 2023. URL https://c2pa.org/specifications/specifications/1.3/specs/C2PA_Specification.html#_introduction.

Alan Chan, Rebecca Salganik, Alva Markelius, Chris Pang, Nitarshan Rajkumar, Dmitrii Krasheninnikov, Lauro Langosco, Zhonghao He, Yawen Duan, Micah Carroll, Michelle Lin, Alex Mayhew, Katherine Collins, Maryam Molamohammadi, John Burden, Wanru Zhao, Shalaleh Rismani, Konstantinos Voudouris, Umang Bhatt, Adrian Weller, David Krueger, and Tegan Maharaj. Harms from Increasingly Agentic Algorithmic Systems. In *Proceedings of the 2023 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '23, pp. 651–666, New York, NY, USA, June 2023. Association for Computing Machinery. ISBN 9798400701924. doi: 10.1145/3593013.3594033. URL https://dl.acm.org/doi/10.1145/3593013.3594033.

Alan Chan, Carson Ezell, Max Kaufmann, Kevin Wei, Lewis Hammond, Herbie Bradley, Emma Bluemke, Nitarshan Rajkumar, David Krueger, Noam Kolt, Lennart Heim, and Markus Anderljung. Visibility into AI Agents. In *Proceedings of the 2024 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '24, pp. 958–973, New York, NY, USA, June 2024a. Association for Computing Machinery. ISBN 9798400704505. doi: 10.1145/3630106.3658948. URL https://dl.acm.org/doi/10.1145/3630106.3658948.

Alan Chan, Noam Kolt, Peter Wills, Usman Anwar, Christian Schroeder de Witt, Nitarshan Rajkumar, Lewis Hammond, David Krueger, Lennart Heim, and Markus Anderljung. IDs for AI Systems, June 2024b. URL http://arxiv.org/abs/2406.12137. arXiv:2406.12137 [cs].

Harrison Chase. LangChain 0.0.77 Docs, 2022. URL https://langchain.readthedocs.io/en/latest/modules/agents/getting_started.html.

Bryan H. Choi. The Anonymous Internet. *Maryland Law Review*, 72:501, 2012. URL https://heinonline.org/HOL/Page?handle=hein.journals/mllr72&id=513&div=&collection=.

Neil Chowdhury, James Aung, Chan Jun Shern, Oliver Jaffe, Dane Sherburn, Giulio Starace, Evan Mays, Rachel Dias, Marwan Aljubeh, Mia Glaese, Carlos E. Jimenez, John Yang, Kevin Liu, and Aleksander Madry. Introducing SWE-bench verified, 2024. URL https://openai.com/index/introducing-swe-bench-verified/?utm_source=substack&utm_medium=email.

ChrisHMSFT, PatrickFarley, mrbullwinkle, eric urban, and aahill. Data, privacy, and security for Azure OpenAI Service - Azure AI services, June 2023. URL https://learn.microsoft.com/en-us/legal/cognitive-services/openai/data-privacy.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep Reinforcement Learning from Human Preferences. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper_files/paper/2017/hash/d5e2c0adad503c91f91df240d0cd4e49-Abstract.html.

Jesse Clifton, Samuel Martin, and Anthony DiGiovanni. When would AGIs engage in conflict?, October 2022. URL https://longtermrisk.org/will-agis-avoid-conflict-by-default/.

Google Cloud. Generative AI, Privacy, and Google Cloud. Technical report, 2023. URL https://services.google.com/fh/files/misc/genai_privacy_google_cloud_202308.pdf.

Stav Cohen, Ron Bitton, and Ben Nassi. Here Comes The AI Worm: Unleashing Zero-click Worms that Target GenAI-Powered Applications, March 2024. URL http://arxiv.org/abs/2403.02817. arXiv:2403.02817 [cs].

Chris Connolly, Graham Greenleaf, and Nigel Waters. Privacy Self-Regulation in Crisis? – TRUSTe's 'Deceptive' Practices, December 2014. URL https://papers.ssrn.com/abstract=2567090.

Sasha Costanza-Chock, Inioluwa Deborah Raji, and Joy Buolamwini. Who Audits the Auditors? Recommendations from a field scan of the algorithmic auditing ecosystem. In *Proceedings of the 2022 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '22, pp. 1571–1583, New York, NY, USA, June 2022. Association for Computing Machinery. ISBN 978-1-4503-9352-2. doi: 10.1145/3531146.3533213. URL https://doi.org/10.1145/3531146.3533213.

PCI Security Standards Council. Information Supplement: Guidance for PCI DSS Scoping and Network Segmentation. Technical report, December 2016.

Allan Dafoe, Yoram Bachrach, Gillian Hadfield, Eric Horvitz, Kate Larson, and Thore Graepel. Cooperative AI: machines must learn to find common ground. *Nature*, 593(7857):33–36, 2021. Publisher: Nature Publishing Group UK London.

David "davidad" Dalrymple, Joar Skalse, Yoshua Bengio, Stuart Russell, Max Tegmark, Sanjit Seshia, Steve Omohundro, Christian Szegedy, Ben Goldhaber, Nora Ammann, Alessandro Abate, Joe Halpern, Clark Barrett, Ding Zhao, Tan Zhi-Xuan, Jeannette Wing, and Joshua Tenenbaum. Towards Guaranteed Safe AI: A Framework for Ensuring Robust and Reliable AI Systems, May 2024. URL http://arxiv.org/abs/2405.06624. arXiv:2405.06624 [cs].

DeepMind. Frontier Safety Framework. Technical report, May 2024.

Dharmesh. agent.ai | The Professional Network for AI Agents, 2024. URL https://agent.ai.

NHS England Digital. Network segmentation - An introduction for health and care organisations, November 2023. URL https://digital.nhs.uk/cyber-and-data-security/guidance-and-assurance/network-segmentation/introduction.

DoorDash. Dasher Identity Verification FAQ, 2025. URL https://help.doordash.com/dashers/s/article/Dasher-Identification-Verification-FAQ?language=en_US.

Adrian-Tudor Dumitrescu and Johan Pouwelse. Failures of public key infrastructure: 53 year survey, January 2024. URL http://arxiv.org/abs/2401.05239. arXiv:2401.05239 [cs].

W Eddy. RFC 9293: Transmission control protocol (tcp), 2022.

Benjamin Edelman. Adverse selection in online "trust" certifications. In *Proceedings of the 11th International Conference on Electronic Commerce*, ICEC '09, pp. 205–212, New York, NY, USA, August 2009. Association for Computing Machinery. ISBN 978-1-60558-586-4. doi: 10.1145/1593254.1593286. URL https://doi.org/10.1145/1593254.1593286.

Victoria Smith Ekstrand. Unmasking Jane and John Doe: Online Anonymity and the First Amendment. *Communication Law and Policy*, 8(4):405–427, October 2003. ISSN 1081-1680. doi: 10.1207/S15326926CLP0804_02. URL https://doi.org/10.1207/S15326926CLP0804_02. Publisher: Routledge _eprint: https://doi.org/10.1207/S15326926CLP0804_02.

Richard Fang, Dylan Bowman, and Daniel Kang. Voice-Enabled AI Agents can Perform Common Scams, October 2024. URL http://arxiv.org/abs/2410.15650. arXiv:2410.15650 [cs].

James D. Fearon. Rationalist Explanations for War. *International Organization*, 49(3):379–414, 1995. ISSN 0020-8183. URL https://www.jstor.org/stable/2706903. Publisher: [The MIT Press, Cambridge University Press, International Organization Foundation].

R Fielding, M Nottingham, and J Reschke. RFC 9110: HTTP semantics, 2022.

Sara Fish, Yannai A. Gonczarowski, and Ran I. Shorrer. Algorithmic Collusion by Large Language Models, March 2024. URL http://arxiv.org/abs/2404.00806. arXiv:2404.00806 [cs, econ, q-fin].

Hiroki Furuta, Yutaka Matsuo, Aleksandra Faust, and Izzeddin Gur. Exposing Limitations of Language Model Agents in Sequential-Task Compositions on the Web, February 2024. URL http://arxiv.org/abs/2311.18751. arXiv:2311.18751 [cs].

Iason Gabriel, Arianna Manzini, Geoff Keeling, Lisa Anne Hendricks, Verena Rieser, Hasan Iqbal, Nenad Tomašev, Ira Ktena, Zachary Kenton, Mikel Rodriguez, Seliem El-Sayed, Sasha Brown, Canfer Akbulut, Andrew Trask, Edward Hughes, A. Stevie Bergman, Renee Shelby, Nahema Marchal, Conor Griffin, Juan Mateos-Garcia, Laura Weidinger, Winnie Street, Benjamin Lange, Alex Ingerman, Alison Lentz, Reed Enger, Andrew Barakat, Victoria Krakovna, John Oliver Siy, Zeb Kurth-Nelson, Amanda McCroskery, Vijay Bolina, Harry Law, Murray Shanahan, Lize Alberts, Borja Balle, Sarah de Haas, Yetunde Ibitoye, Allan Dafoe, Beth Goldberg, Sébastien Krier, Alexander Reese, Sims Witherspoon, Will Hawkins, Maribeth Rauh, Don Wallace, Matija Franklin, Josh A. Goldstein, Joel Lehman, Michael Klenk, Shannon Vallor, Courtney Biles, Meredith Ringel Morris, Helen King, Blaise Agüera y Arcas, William Isaac, and James Manyika. The Ethics of Advanced AI Assistants, April 2024. URL http://arxiv.org/abs/2404.16244. arXiv:2404.16244 [cs].

GLEIF. Introducing the verifiable LEI (vLEI) - vLEI – GLEIF, 2024. URL https://www.gleif.org/en/vlei/introducing-the-verifiable-lei-vlei.

Kate Goddard, Abdul Roudsari, and Jeremy C Wyatt. Automation bias: a systematic review of frequency, effect mediators, and mitigators. *Journal of the American Medical Informatics Association*, 19(1):121–127, January 2012. ISSN 1067-5027. doi: 10.1136/amiajnl-2011-000089. URL https://doi.org/10.1136/amiajnl-2011-000089.

Government of the United Kingdom. Where to Report a Cyber Incident, May 2022. URL https://www.gov.uk/guidance/where-to-report-a-cyber-incident.

Government of the United Kingdom. Reporting vehicle and driving offences, 2024. URL https://www.gov.uk/browse/driving/driving-enforcing-the-law.

Ben Green. The flaws of policies requiring human oversight of government algorithms. *Computer Law & Security Review*, 45:105681, July 2022. ISSN 0267-3649. doi: 10.1016/j.clsr.2022.105681. URL https://www.sciencedirect.com/science/article/pii/S0267364922000292.

Ryan Greenblatt, Buck Shlegeris, Kshitij Sachan, and Fabien Roger. AI Control: Improving Safety Despite Intentional Subversion, January 2024. URL http://arxiv.org/abs/2312.06942. arXiv:2312.06942 [cs].

Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection, May 2023. URL http://arxiv.org/abs/2302.12173. arXiv:2302.12173 [cs].

Xiangming Gu, Xiaosen Zheng, Tianyu Pang, Chao Du, Qian Liu, Ye Wang, Jing Jiang, and Min Lin. Agent smith: A single image can jailbreak one million multimodal llm agents exponentially fast. *arXiv preprint arXiv:2402.08567*, 2024.

Izzeddin Gur, Hiroki Furuta, Austin Huang, Mustafa Safdari, Yutaka Matsuo, Douglas Eck, and Aleksandra Faust. A Real-World WebAgent with Planning, Long Context Understanding, and Program Synthesis, February 2024. URL http://arxiv.org/abs/2307.12856. arXiv:2307.12856 [cs].

Dylan Hadfield-Menell, Stuart J Russell, Pieter Abbeel, and Anca Dragan. Cooperative Inverse Reinforcement Learning. In *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper_files/paper/2016/hash/c3395dd46c34fa7fd8d729d8cf88b7a8-Abstract.html.

Joe Hewett. Technologies for an agent-based world, 2024. URL https://www.species.gg/blog/technologies-for-an-agent-based-world.

Md Imran Hossen and Xiali Hei. A Low-Cost Attack against the hCaptcha System. In *2021 IEEE Security and Privacy Workshops (SPW)*, pp. 422–431, May 2021. doi: 10.1109/SPW53761.2021.00061. URL http://arxiv.org/abs/2104.04683. arXiv:2104.04683 [cs].

Md Imran Hossen, Yazhou Tu, Md Fazle Rabby, Md Nazmul Islam, Hui Cao, and Xiali Hei. An Object Detection based Solver for {Google's} Image {reCAPTCHA} v2. pp. 269–284, 2020. ISBN 978-1-939133-18-2. URL https://www.usenix.org/conference/raid2020/presentation/hossen.

Hengyuan Hu, Adam Lerer, Alex Peysakhovich, and Jakob Foerster. "Other-Play " for zero-shot coordination. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *ICML'20*, pp. 4399–4410. JMLR.org, July 2020.

Wenyue Hua, Xianjun Yang, Mingyu Jin, Wei Cheng, Ruixiang Tang, and Yongfeng Zhang. TrustAgent: Towards Safe and Trustworthy LLM-based Agents through Agent Constitution, August 2024. URL http://arxiv.org/abs/2402.01586. arXiv:2402.01586 [cs].

Saffron Huang, Divya Siddarth, Liane Lovitt, Thomas I. Liao, Esin Durmus, Alex Tamkin, and Deep Ganguli. Collective Constitutional AI: Aligning a Language Model with Public Input. In *Proceedings of the 2024 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '24, pp. 1395–1417, New York, NY, USA, June 2024. Association for Computing Machinery. ISBN 9798400704505. doi: 10.1145/3630106. 3658979. URL https://doi.org/10.1145/3630106.3658979.

Nicholas R Jennings, Katia Sycara, and Michael Wooldridge. A roadmap of agent research and development. *Autonomous agents and multi-agent systems*, 1:7–38, 1998. Publisher: Springer.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can Language Models Resolve Real-World GitHub Issues?, April 2024. URL http://arxiv.org/abs/2310.06770. arXiv:2310.06770 [cs].

Deborah G. Johnson. Software Agents, Anticipatory Ethics, and Accountability. In Gary E. Marchant, Braden R. Allenby, and Joseph R. Herkert (eds.), *The Growing Gap Between Emerging Technologies and Legal-Ethical Oversight: The Pacing Problem*, pp. 61–76. Springer Netherlands, Dordrecht, 2011. ISBN 978-94-007-1356-7. doi: 10.1007/978-94-007-1356-7_5. URL https://doi.org/10.1007/978-94-007-1356-7_5.

Erik Jones, Anca Dragan, and Jacob Steinhardt. Adversaries Can Misuse Combinations of Safe Models, June 2024. URL http://arxiv.org/abs/2406.14595. arXiv:2406.14595 [cs].

Steve Kaliski. Adding payments to your LLM agentic workflows, November 2024. URL https://stripe.dev/blog/adding-payments-to-your-agentic-workflows.

Ruogu Kang, Stephanie Brown, and Sara Kiesler. Why do people seek anonymity on the internet? informing policy and design. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '13, pp. 2657–2666, New York, NY, USA, April 2013. Association for Computing Machinery. ISBN 978-1-4503-1899-0. doi: 10.1145/2470654.2481368. URL https://doi.org/10.1145/2470654.2481368.

Sayash Kapoor, Benedikt Stroebl, Zachary S. Siegel, Nitya Nadgir, and Arvind Narayanan. AI Agents That Matter, July 2024. URL http://arxiv.org/abs/2407.01502. arXiv:2407.01502 [cs].

Hannah Rose Kirk, Alexander Whitefield, Paul Röttger, Andrew Bean, Katerina Margatina, Juan Ciro, Rafael Mosquera, Max Bartolo, Adina Williams, He He, Bertie Vidgen, and Scott A. Hale. The PRISM Alignment Project: What Participatory, Representative and Individualised Human Feedback Reveals About the Subjective and Multicultural Alignment of Large Language Models, April 2024. URL http://arxiv.org/abs/2404.16019. arXiv:2404.16019 [cs].

Rob Kling, Ya-ching Lee, Al Teich, and Mark S Frankel. Assessing anonymous communication on the internet: Policy deliberations. *The Information Society*, 15(2):79–90, 1999. Publisher: Taylor & Francis.

Noam Kolt. Governing AI Agents, April 2024. URL https://papers.ssrn.com/abstract=4772956.

Anton Korinek and Megan Juelfs. Preparing for the (Non-Existent?) Future of Work, June 2022. URL https://www.nber.org/papers/w30172.

Anton Korinek and Donghyun Suh. Scenarios for the Transition to AGI, March 2024. URL https://www.nber.org/papers/w32255.

Seth Lazar. Frontier AI Ethics: Anticipating and Evaluating the Societal Impacts of Generative Agents, April 2024. URL http://arxiv.org/abs/2404.06750. arXiv:2404.06750 [cs].

Seth Lazar, Luke Thorburn, Tian Jin, and Luca Belli. The Moral Case for Using Language Model Agents for Recommendation, October 2024. URL http://arxiv.org/abs/2410.12123. arXiv:2410.12123 [cs].

Gavin Leech, Juan J. Vazquez, Misha Yagudin, Niclas Kupper, and Laurence Aitchison. Questionable practices in machine learning, July 2024. URL http://arxiv.org/abs/2407.12220. arXiv:2407.12220 [cs].

Joel Z. Leibo, Edgar Duéñez-Guzmán, Alexander Sasha Vezhnevets, John P. Agapiou, Peter Sunehag, Raphael Koster, Jayd Matyas, Charles Beattie, Igor Mordatch, and Thore Graepel. Scalable Evaluation of Multi-Agent Reinforcement Learning with Melting Pot, July 2021. URL http://arxiv.org/abs/2107.06857. arXiv:2107.06857 [cs].

Jan Leike, David Krueger, Tom Everitt, Miljan Martic, Vishal Maini, and Shane Legg. Scalable agent alignment via reward modeling: a research direction, November 2018. URL http://arxiv.org/abs/1811.07871. arXiv:1811.07871 [cs, stat].

Adam Lerer and Alexander Peysakhovich. Learning Existing Social Conventions via Observationally Augmented Self-Play. In *Proceedings of the 2019 AAAI/ACM Conference on AI, Ethics, and Society*, AIES '19, pp. 107–114, New York, NY, USA, January 2019. Association for Computing Machinery. ISBN 978-1-4503-6324-2. doi: 10.1145/3306618.3314268. URL https://doi.org/10.1145/3306618.3314268.

Henry Lieberman. Autonomous interface agents. In *Proceedings of the ACM SIGCHI Conference on Human factors in computing systems*, CHI '97, pp. 67–74, New York, NY, USA, March 1997. Association for Computing Machinery. ISBN 978-0-89791-802-2. doi: 10.1145/258549.258592. URL https://dl.acm.org/doi/10.1145/258549.258592.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, Minlie Huang, Yuxiao Dong, and Jie Tang. AgentBench: Evaluating LLMs as Agents, October 2023. URL http://arxiv.org/abs/2308.03688. arXiv:2308.03688 [cs].

Jiarui Lu, Thomas Holleis, Yizhe Zhang, Bernhard Aumayer, Feng Nan, Felix Bai, Shuang Ma, Shen Ma, Mengyu Li, Guoli Yin, Zirui Wang, and Ruoming Pang. ToolSandbox: A Stateful, Conversational, Interactive Evaluation Benchmark for LLM Tool Use Capabilities, August 2024. URL http://arxiv.org/abs/2408.04682. arXiv:2408.04682 [cs].

Pattie Maes. Agents that reduce work and information overload. *Communications of the ACM*, 37(7):30–40, July 1994. ISSN 0001-0782. doi: 10.1145/176789.176792. URL https://dl.acm.org/doi/10.1145/176789.176792.

Pattie Maes. Artificial life meets entertainment: lifelike autonomous agents. *Communications of the ACM*, 38(11):108–114, November 1995. ISSN 0001-0782. doi: 10.1145/219717.219808. URL https://dl.acm.org/doi/10.1145/219717.219808.

Samuele Marro, Emanuele La Malfa, Jesse Wright, Guohao Li, Nigel Shadbolt, Michael Wooldridge, and Philip Torr. A Scalable Communication Protocol for Networks of Large Language Models, October 2024. URL http://arxiv.org/abs/2410.11905. arXiv:2410.11905 [cs].

Ashwin Jacob Mathew. *Where in the world is the internet? Locating political power in internet infrastructure.* PhD thesis, University of California, Berkeley, 2014.

Grégoire Mialon, Clémentine Fourrier, Craig Swift, Thomas Wolf, Yann LeCun, and Thomas Scialom. GAIA: a benchmark for General AI Assistants, November 2023. URL https://arxiv.org/abs/2311.12983v1.

Microsoft Threat Intelligence. Threat actors misuse OAuth applications to automate financially driven attacks, December 2023. URL https://www.microsoft.com/en-us/security/blog/2023/12/12/threat-actors-misuse-oauth-applications-to-automate-financially-driven-attacks/.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing Atari with Deep Reinforcement Learning, December 2013. URL http://arxiv.org/abs/1312.5602. arXiv:1312.5602.

MultiOn. MultiOn AI, 2024. URL https://www.multion.ai/about.

William L Oberkampf and Christopher J Roy. *Verification and validation in scientific computing.* Cambridge university press, 2010.

OpenAI. OpenAI Charter, 2018. URL https://openai.com/charter/.

OpenAI. Coordinated vulnerability disclosure policy, July 2023a. URL https://openai.com/policies/coordinated-vulnerability-disclosure-policy/.

OpenAI. OpenAI Evals, September 2023b. URL https://github.com/openai/evals. original-date: 2023-01-23T20:51:04Z.

OpenAI. Preparedness Framework (Beta). Technical report, December 2023c.

OpenAI. GPT Actions, 2024. URL https://platform.openai.com/docs/actions/introduction.

OpenAI. How should I report a GPT?, 2024. URL https://help.openai.com/en/articles/8554982-how-should-i-report-a-gpt.

OpenAI. Model Spec, May 2024. URL https://cdn.openai.com/spec/model-spec-2024-05-08.html.

Raja Parasuraman and Victor Riley. Humans and Automation: Use, Misuse, Disuse, Abuse. *Human Factors*, 39(2):230–253, June 1997. ISSN 0018-7208. doi: 10.1518/001872097778543886. URL https://doi.org/10.1518/001872097778543886. Publisher: SAGE Publications Inc.

Shishir G. Patil, Tianjun Zhang, Vivian Fang, Noppapon C., Roy Huang, Aaron Hao, Martin Casado, Joseph E. Gonzalez, Raluca Ada Popa, and Ion Stoica. GoEX: Perspectives and Designs Towards a Runtime for Autonomous LLM Applications, April 2024. URL http://arxiv.org/abs/2404.06921. arXiv:2404.06921 [cs].

Elija Perrier. Classical and Language Model Multi-Agent Infrastructure: A Comparative Review. *Forthcoming*, 2025.

Elija Perrier and Seth Lazar. Language Model Agent Ontologies. *Forthcoming*, 2025.

Robert Powell. War as a Commitment Problem. *International Organization*, 60(1):169–203, 2006. ISSN 0020-8183. URL https://www.jstor.org/stable/3877871. Publisher: [MIT Press, University of Wisconsin Press, Cambridge University Press, International Organization Foundation].

Nasim Rahaman, Martin Weiss, Manuel Wüthrich, Yoshua Bengio, Li Erran Li, Chris Pal, and Bernhard Schölkopf. Language Models Can Reduce Asymmetry in Information Markets, March 2024. URL http://arxiv.org/abs/2403.14443. arXiv:2403.14443 [cs].

Inioluwa Deborah Raji, Andrew Smart, Rebecca N. White, Margaret Mitchell, Timnit Gebru, Ben Hutchinson, Jamila Smith-Loud, Daniel Theron, and Parker Barnes. Closing the AI accountability gap: defining an end-to-end framework for internal algorithmic auditing. In *Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, FAT* '20, pp. 33–44, New York, NY, USA, January 2020. Association for Computing Machinery. ISBN 978-1-4503-6936-7. doi: 10.1145/3351095.3372873. URL https://dl.acm.org/doi/10.1145/3351095.3372873.

Inioluwa Deborah Raji, Peggy Xu, Colleen Honigsberg, and Daniel Ho. Outsider Oversight: Designing a Third Party Audit Ecosystem for AI Governance. In *Proceedings of the 2022 AAAI/ACM Conference on AI, Ethics, and Society*, AIES '22, pp. 557–571, New York, NY, USA, July 2022. Association for Computing Machinery. ISBN 978-1-4503-9247-1. doi: 10.1145/3514094.3534181. URL https://dl.acm.org/doi/10.1145/3514094.3534181.

Yakov Rekhter, Tony Li, and Susan Hares. RFC 4271: A border gateway protocol 4 (BGP-4), 2006.

Responsible AI Collaborative. Artificial Intelligence Incident Database, 2024. URL https://incidentdatabase.ai/.

Stuart J. Russell and Peter Norvig. *Artificial Intelligence: A Modern Approach*. 4 edition, 2021.

Peter Salib and Simon Goldstein. AI Rights for Human Safety, 2024. URL https://papers.ssrn.com/sol3/papers.cfm?abstract_id=4913167.

Bruce Schneier and Nathan Sanders. The SEC Whistleblower Program Is Dominating Regulatory Enforcement, October 2024. URL https://prospect.org/api/content/9a02d5ca-8cc7-11ef-9343-12163087a831/.

Andrew Searles, Yoshimichi Nakatsuka, Ercan Ozturk, Andrew Paverd, Gene Tsudik, and Ai Enkoji. An Empirical Study & Evaluation of Modern CAPTCHAs, July 2023. URL http://arxiv.org/abs/2307.12108. arXiv:2307.12108 [cs].

Securities and Exchange Commission. Whistleblower Program, August 2024. URL https://www.sec.gov/enforcement-litigation/whistleblower-program.

Yonadav Shavit, Sandhini Agarwal, Miles Brundage, Steven Adler, Cullen O'Keefe, Rosie Campbell, Teddy Lee, Pamela Mishkin, Tyna Eloundou, Alan Hickey, Katarina Slama, Lama Ahmad, Paul McMillan, Alex Beutel, Alexandre Passos, and David G. Robinson. Practices for Governing Agentic AI Systems, 2023.

Significant-Gravitas. Auto-GPT-Plugins, 2024. URL https://github.com/Significant-Gravitas/Auto-GPT-Plugins.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, Timothy Lillicrap, Karen Simonyan, and Demis Hassabis. A general reinforcement learning algorithm that masters chess, shogi, and Go through self-play. *Science*, 362(6419):1140–1144, December 2018. doi: 10.1126/science.aar6404. URL https://www.science.org/doi/10.1126/science.aar6404. Publisher: American Association for the Advancement of Science.

LINDA J. Skitka, KATHLEEN L. Mosier, and MARK Burdick. Does automation bias decision-making? *International Journal of Human-Computer Studies*, 51(5):991–1006, November 1999. ISSN 1071-5819. doi: 10.1006/ijhc.1999.0252. URL https://www.sciencedirect.com/science/article/pii/S1071581999902525.

Yueqi Song, Frank Xu, Shuyan Zhou, and Graham Neubig. Beyond Browsing: API-Based Web Agents, October 2024. URL http://arxiv.org/abs/2410.16464. arXiv:2410.16464 [cs].

Manu Sporny, Dave Longley, David Chadwick, and Orie Steele. Verifiable Credentials Data Model v2.0. Technical report, W3C, May 2024.

Statista. eCommerce - Worldwide, 2024. URL https://www.statista.com/outlook/emo/ecommerce/worldwide.

Xinyuan Sun, Davide Crapis, Matt Stephenson, Barnabé Monnot, Thomas Thiery, and Jonathan Passerat-Palmbach. Cooperative AI via Decentralized Commitment Devices, November 2023. URL http://arxiv.org/abs/2311.07815. arXiv:2311.07815 [cs].

Cass R. Sunstein. Brave New World? Human Welfare and Paternalistic AI, 2024. URL https://papers.ssrn.com/sol3/papers.cfm?abstract_id=4908836.

Richard S. Sutton and Andrew G. Barto. *Reinforcement learning: An introduction.* Adaptive computation and machine learning series. The MIT Press, Cambridge, Massachusetts, second edition edition, 2018. ISBN 978-0-262-03924-6. tex.lccn: Q325.6 .R45 2018.

Alexander Tabarrok. The Private Provision of Public Goods via Dominant Assurance Contracts. *Public Choice*, 96(3/4):345–362, 1998. ISSN 0048-5829. URL https://www.jstor.org/stable/30024397. Publisher: Springer.

Rishub Tamirisa, Bhrugu Bharathi, Long Phan, Andy Zhou, Alice Gatti, Tarun Suresh, Maxwell Lin, Justin Wang, Rowan Wang, Ron Arel, Andy Zou, Dawn Song, Bo Li, Dan Hendrycks, and Mantas Mazeika. Tamper-Resistant Safeguards for Open-Weight LLMs, August 2024. URL http://arxiv.org/abs/2408.00761. arXiv:2408.00761 [cs].

Heyi Tao, Sethuraman T V, Michal Shlapentokh-Rothman, and Derek Hoiem. WebWISE: Web Interface Control and Sequential Exploration with Large Language Models, October 2023. URL http://arxiv.org/abs/2310.16042. arXiv:2310.16042 [cs].

Cecilia Testart, Josephine Wolff, Deepak Gouda, and Romain Fontugne. Identifying Current Barriers in RPKI Adoption, September 2024. URL https://papers.ssrn.com/abstract=4948317.

Andrew Trask, Akshay Sukumar, Antti Kalliokoski, Bennett Farkas, Callis Ezenwaka, Carmen Popa, Curtis Mitchell, Dylan Hrebenach, George-Cristian Muraru, Ionesio Junior, Irina Bejan, Ishan Mishra, Ivoline Ngong, Jack Bandy, Jess Stahl, Julian Cardonnet, Kellye Trask, Khoa Nguyen, Kien Dang, Koen van der Veen, Kyoko Eng, Lacey Strahm, Laura Ayre, Madhava Jay, Oleksandr Lytvyn, Osam Kyemenu-Sarsah, Peter Chung, Peter Smith, Rasswanth S, Ronnie Falcon, Shubham Gupta, Stephen Gabriel, Teo Milea, Theresa Thoraldson, Thiago Porto, Tudor Cebere, Yash Gorana, and Zarreen Reza. How to audit an AI model owned by someone else (part 1), July 2023. URL https://blog.openmined.org/ai-audit-part-1/.

Andrew Trask, Emma Bluemke, Teddy Collins, Ben Garfinkel Eric Drexler, Claudia Ghezzou Cuervas-Mons, Iason Gabriel, Allan Dafoe, and William Isaac. Beyond Privacy Trade-offs with Structured Transparency, March 2024. URL http://arxiv.org/abs/2012.08347. arXiv:2012.08347 [cs].

Jon Turow. The Rise of AI Agent Infrastructure, June 2024. URL https://www.madrona.com/the-rise-of-ai-agent-infrastructure/.

Uber. Identity Verification Checks, 2025. URL https://help.uber.com/driving-and-delivering/article/identity-verification-checks?nodeId=75fb55dc-da08-41bb-b1cb-3229f2839956.

Southern District of New York U.S. Attorney's Office. North Carolina Musician Charged With Music Streaming Fraud Aided By Artificial Intelligence, September 2024. URL https://www.justice.gov/usao-sdny/pr/north-carolina-musician-charged-music-streaming-fraud-aided-artificial-intelligence.

Rory Van Loo. Digital Market Perfection. *Michigan Law Review*, 117(5):815–884, January 2019. ISSN 0026-2234. doi: https://doi.org/10.36644/mlr.117.5.digital. URL https://repository.law.umich.edu/mlr/vol117/iss5/2.

Veniamin Veselovsky, Manoel Horta Ribeiro, and Robert West. Artificial Artificial Artificial Intelligence: Crowd Workers Widely Use Large Language Models for Text Production Tasks, June 2023. URL http://arxiv.org/abs/2306.07899. arXiv:2306.07899.

Eric Wallace, Kai Xiao, Reimar Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. The instruction hierarchy: Training llms to prioritize privileged instructions. *arXiv preprint arXiv:2404.13208*, 2024.

Han Wang, Archiki Prasad, Elias Stengel-Eskin, and Mohit Bansal. Soft Self-Consistency Improves Language Models Agents. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 287–301, Bangkok, Thailand, August 2024a. Association for Computational Linguistics. URL https://aclanthology.org/2024.acl-short.28.

Renxi Wang, Haonan Li, Xudong Han, Yixuan Zhang, and Timothy Baldwin. Learning From Failure: Integrating Negative Examples when Fine-tuning Large Language Models as Agents, April 2024b. URL http://arxiv.org/abs/2402.11651. arXiv:2402.11651 [cs].

Kevin Wei and Lennart Heim. Designing Incident Reporting Systems for Harms from AI. May 2024.

Hjalmar Wijk, Tao Lin, Joel Becker, Sami Jawhar, Neev Parikh, Thomas Broadley, Lawrence Chan, Michael Chen, Josh Clymer, Jai Dhyani, Elena Ericheva, Katharyn Garcia, Brian Goodrich, Nikola Jurkovic, Megan Kinniment, Aron Lajko, Seraphina Nix, Lucas Sato, William Saunders, Maksym Taran, Ben West, and Elizabeth Barnes. RE-Bench: Evaluating frontier AI R&D capabilities of language model agents against human experts, November 2024. URL http://arxiv.org/abs/2411.15114. arXiv:2411.15114.

Peter Wills. Care for Chatbots, May 2024. URL https://papers.ssrn.com/abstract=4814272.

Michael Wooldridge. *An introduction to multiagent systems*. John wiley & sons, 2009.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, Ahmed Hassan Awadallah, Ryen W. White, Doug Burger, and Chi Wang. AutoGen: Enabling Next-Gen LLM Applications via Multi-Agent Conversation Framework. 2023. _eprint: 2308.08155.

Scott Wu. Introducing Devin, the first AI software engineer, March 2024. URL https://www.cognition-labs.com/blog.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. OSWorld: Benchmarking Multimodal Agents for Open-Ended Tasks in Real Computer Environments, April 2024. URL http://arxiv.org/abs/2404.07972. arXiv:2404.07972 [cs].

Andy K. Zhang, Neil Perry, Riya Dulepet, Eliot Jones, Justin W. Lin, Joey Ji, Celeste Menders, Gashon Hussein, Samantha Liu, Donovan Jasper, Pura Peetathawatchai, Ari Glenn, Vikram Sivashankar, Daniel Zamoshchin, Leo Glikbarg, Derek Askaryar, Mike Yang, Teddy Zhang, Rishi Alluri, Nathan Tran, Rinnara Sangpisit, Polycarpos Yiorkadjis, Kenny Osele, Gautham Raghupathi, Dan Boneh, Daniel E. Ho, and Percy Liang. Cybench: A Framework for Evaluating Cybersecurity Capabilities and Risk of Language Models, August 2024. URL http://arxiv.org/abs/2408.08926. arXiv:2408.08926 [cs].

Hanlin Zhang, Benjamin L. Edelman, Danilo Francati, Daniele Venturi, Giuseppe Ateniese, and Boaz Barak. Watermarks in the Sand: Impossibility of Strong Watermarking for Generative Models, November 2023. URL http://arxiv.org/abs/2311.04378. arXiv:2311.04378 [cs].

Jonathan L. Zittrain. The Generative Internet. *Harvard Law Review*, 119(7):1974–2040, 2006. ISSN 0017-811X. URL https://www.jstor.org/stable/4093608. Publisher: The Harvard Law Review Association.

Andy Zou, Long Phan, Justin Wang, Derek Duenas, Maxwell Lin, Maksym Andriushchenko, Rowan Wang, Zico Kolter, Matt Fredrikson, and Dan Hendrycks. Improving Alignment and Robustness with Circuit Breakers, July 2024. URL http://arxiv.org/abs/2406.04313. arXiv:2406.04313 [cs].