Few-Shot In-Context Imitation Learning
via Implicit Graph Alignment

Abstract: Consider the following problem: given a few demonstrations of a task across a few different objects, how can a robot learn to perform that same task on new, previously unseen objects? This is challenging because the large variety of objects within a class makes it difficult to infer the task-relevant relationship between the new objects and the objects in the demonstrations. We address this by formulating imitation learning as a conditional alignment problem between graph representations of objects. Consequently, we show that this conditioning allows for in-context learning, where a robot can perform a task on a set of new objects immediately after the demonstrations, without any prior knowledge about the object class or any further training. In our experiments, we explore and validate our design choices, and we show that our method is highly effective for few-shot learning of several real-world, everyday tasks, whilst outperforming baselines. Videos and supplementary material are available on our anonymous webpage at https://sites.google.com/view/implicit-graph-alignment.

Keywords: Few-Shot Imitation Learning, Graph Neural Networks

Figure 1: Given a few (e.g. three) demonstrations of a new task across multiple object instances (left), a robot can perform this same task with previously unseen objects (right), based on a graph alignment energy model trained on a diverse dataset of task-agnostic object alignments (middle).

1 Introduction

For a robot to perform a manipulation task involving two objects, it must infer task-relevant parts of these objects and align them throughout the trajectory in a task-specific way. For example, the spout of a teapot should be aligned with the opening of a mug when pouring tea. However, objects within a class typically have slightly different shapes, so inferring the parts which should be aligned for a given task is challenging due to the diversity of object shapes. This becomes even more challenging in an imitation learning setting, where this task-specific alignment should be inferred only from demonstrations, and ideally, without requiring any prior knowledge about the objects or their class.

We approach this challenge as a few-shot in-context imitation learning problem, and learn a conditional distribution of alignments that can produce task-relevant alignments of novel objects from just

a few context examples, i.e. demonstrations. We propose to learn this distribution from point cloud observations using a novel heterogeneous graph-based energy model, whose graph structure with transformer-based attention is capable of representing intricate relations between different parts of the objects, and whose implicit energy-based learning is effective at capturing complex and multi-modal distributions. These design choices allow us to perform few-shot imitation learning on any arbitrary objects and over any arbitrary number of demonstrations, using just a single trained model.

But where can we obtain a large-scale dataset of task-relevant alignments between objects needed to train such a model? Our insight here is that simply by deforming pairs of arbitrary ShapeNet [1] objects in simulation, using an object augmentation function trained for a single object category of chairs [2], we can create sensible new instances of objects of an arbitrary category and align them consistently, providing us with the data required to train the aforementioned model. By training on objects from diverse categories and multiple alignments between them, we are able to predict task-relevant alignments for novel object pairs, all from the same trained model.

We evaluated our method both with simulation and real-world experiments and analysed its ability to align novel objects in a few-shot imitation learning setting, where each demonstration consists of one or more waypoints in a trajectory. Our real-world results show that for everyday tasks, such as pouring from a teapot into a mug, sweeping with a brush, and hanging a cap onto a peg, we achieve 80% task success rate under the following conditions: (1) only four demonstrations are provided, (2) the test objects are novel and unseen during the demonstrations, and (3) we assume no prior knowledge about the objects or class of objects. These results, when compared to the baselines, validate our method as an effective few-shot imitation in-context learning framework, capable of efficiently learning everyday robotic tasks from just a few demonstrations.

2 Related Work

The field of imitation learning has seen various approaches that aim to solve robotic tasks based on a single demonstration [3, 4, 5]. However, these methods are typically limited to scenarios where the objects used in the demonstrations and during deployment are either the same or sufficiently similar. This lack of flexibility prevents them from being applied to category-level manipulation tasks. Other methods tackle this limitation by leveraging category-level keypoints, which can be annotated [6, 7], predicted [8], or obtained through self-supervised correspondence methods [9, 10, 11]. However, selecting such keypoints in a task-agnostic manner is challenging, thereby restricting the applicability of these approaches. Transporter Nets [12], utilises learned feature maps and template matching to identify pick-and-place poses, but is restricted to pick-and-place tasks and struggles to predict arbitrary 6DoF poses. We also train a function to predict the quality of an object alignment, but we do so in an unrestricted $\mathbb{SE}(3)$ space, enabling us to handle much more complex and arbitrary tasks defined by the demonstrations. Graph neural networks [13, 14, 15, 16] and implicit learning of functions [17, 18, 19, 20] have recently gained significant attention for robot manipulation, and we study a novel formulation of these ideas for few-shot imitation learning.

The most closely related work to ours comes from Relational Neural Descriptor Fields (R-NDF) [21, 22] and TAX-Pose [23], both of which can generalise to novel instances within the same object category. [21] achieves object alignment by matching descriptors extracted from a pre-trained occupancy network. However, it requires per-object category training and the annotation of task-relevant object parts. Furthermore, [21] averages descriptors from multiple demonstrations, which can pose challenges when dealing with significantly different objects or multimodal demonstrations. [23] employs cross-object attention for estimating dense cross-object correspondences. However, it requires separate network training for each new alignment between the objects, limiting its applicability. In contrast to previously described methods, our approach learns a general conditional distribution of alignments using an energy-based model, which can be applied to objects of unseen categories and arbitrary alignments without the need for additional training beyond the initial demonstrations.

3 Method

3.1 Problem Formulation & Overview

Problem Setting. We consider an imitation learning setting involving two objects, namely a *grasped object* (or a robot gripper) and a *target object*, between which the interaction should occur. We do

not assume any prior knowledge about these objects, and denote their observations as O_A, and O_B. The alignment, or relative spatial configuration between these objects, is denoted as a general representation $\mathcal{A}(O_A, O_B)$, which should be independent of the global configurations of the objects, and focusses only on their relative alignment. As we will explain later, we use segmented point clouds as observations O_A and O_B and devise a heterogeneous graph to represent $\mathcal{A}(O_A, O_B)$.

Objective. Given an arbitrary task involving any two objects O_A and O_B, our goal is to infer a trajectory of alignments between them that would complete the task. We denote this trajectory as a sequence of alignments $\mathcal{A}_{test}^{1:T}(O_A, O_B)$, where T is the number of time steps in a trajectory. In general, to accomplish this, we would require knowledge of the task-conditional distribution $p(\mathcal{A}_{test}^{1:T}|task)$, but defining this analytically is infeasible all possible task and object combinations and from partial point cloud observations. Instead, we propose to approximate it using a few samples from this distribution $\{\mathcal{A}_{demo}^{1:T}(O_A^i, O_B^i)\}_i^N$, by learning a conditional distribution $p_\theta(\mathcal{A}_{test}^{1:T}|\{\mathcal{A}_{demo}^{1:T}\}_i^N)$, parameterised by θ. Here, N denotes the number of demonstrations.

Deployment. When presented with novel objects O_A and O_B, our objective is to perform a task by sampling from the learned conditional distribution, eliminating the need for task-specific training or fine-tuning. We sample from $p_\theta(\mathcal{A}_{test}(\mathcal{T}^t \times O_A, O_B)|\{\mathcal{A}_{demo}^t\}_i^N))$ by finding a sequence of transformations $\mathcal{T}^{1:T}$ which when applied to object A, yield alignments within the distribution. Assuming rigid grasps, we can directly apply this sequence of transformations to the robot's end-effector, causing it to move the grasped object along the task-relevant trajectory. In this work, we treat individual time steps in a trajectory independently, hence, going forward, we will drop the superscript t, and refer to a set of N demonstrations as $\mathcal{A}_{demo}$ for conciseness.

Single demonstration, same objects
Unique Alignment

Single demonstration, different objects
Many possible alignments

Multiple demonstrations, different objects
Task-Relevant alignment

Demo   Test   Demo   Test   Demos   Test

Figure 2: Illustration motivating the need for multiple demonstrations across different sets of objects, in order to generalise to unseen objects when inferring task-relevant alignments.

Multiple Demonstrations Requirement. When the objects during test time are the same as during the demonstrations, sampling from the learned distribution would yield alignments identical to the demonstrations (see Figure 2 left). However, if they differ from those in the demonstrations, the task-relevant parts should be aligned consistently. Inferring relevant object parts for an arbitrary task is infeasible from a single demonstration when objects used are different (see Figure 2 middle). Therefore, we use multiple demonstrations with different objects from the same categories and make an assumption that across the demonstrations, the relative alignment of the task-relevant parts remains consistent and can be inferred (see Figure 2 right). With an increasing number of demonstrations and a broader range of object shapes, the conditional distribution should converge towards a Dirac delta function $\delta(\cdot)$. In cases where the demonstrations are multimodal or inconsistent, the distribution becomes multimodal, representing different possible ways of completing the task.

3.2 Generalisation Through Shape Augmentation

To learn a conditional distribution $p_\theta(\mathcal{A}_{test}|\mathcal{A}_{demo})$ which generalises to arbitrary alignments between different instances of objects from the same category, we need a diverse dataset containing multiple objects with different geometries aligned in a semantically consistent way. Obtaining such a dataset would require a huge effort in annotation or solving the underlying semantic object alignment problem in the first place. Instead, we propose to utilise correspondence-preserving shape augmentation and treat each deformation of the object as a new instance. The ability to generate new instances of a specific category of objects and having privileged information regarding the ground truth correspondences allows us to create an arbitrary number of alignments between the objects with specific parts consistently aligned (see Figure 3). Although these deformations might not

120 represent realistic objects one might encounter in the real world, we hope that we can encapsulate
121 the true underlying distribution of objects within the convex hull of the produced deformations.

Figure 3: Two arbitrary objects and their deformed variations aligned based on specific parts. Colour maps indicate dense correspondences, green and blue spheres highlight the parts used for alignment.

122 In practice, we create a diverse dataset of alignments, as follows. 1) *Random Object Selection*: We
123 randomly select two objects from the ShapeNet dataset — representing O_A and O_B, and apply ran-
124 dom $\mathbb{SE}(3)$ transformations to them, creating an arbitrary alignment between them. 2) *Deformation*
125 *Generation*: To create variations of objects, we employ a correspondence-preserving implicit gener-
126 ative model called DIF-Net [2]. By deforming the objects, we obtain different instances of the same
127 category, each with its own unique shape characteristics. 3) *Alignment Based on Correspondences*:
128 For each original object, we randomly sample a point on its surface. Using the known correspon-
129 dences between the original and deformed objects, we align the deformed objects based on the local
130 neighbourhood of points around the sampled point. This alignment ensures that certain parts of the
131 objects maintain the same relative pose consistently. 4) *Rendering Point Clouds*: Finally, we ren-
132 der the point clouds of the aligned objects using simulated depth cameras, resulting in a sample of
133 consistently aligned object pairs. The resulting dataset $\mathcal{D} = \{\{\mathcal{P}_A^i, \mathcal{P}_B^i\}_i^N\}_j^M$ contains M samples,
134 where each sample consists of N aligned object pairs. We utilise these samples by using $N-1$
135 alignments as context and the left-out alignment as the target alignment for those object.

136 ## 3.3 Alignment Representation

Figure 4: (Left) High-level structure of the model used to learn the alignment distribution. (Right) The learnt energy landscape in 2D, and the graph alignment during different optimisation steps.

137 As hinted previously, we use point clouds $\mathcal{P}_A^i$ and $\mathcal{P}_B^i$ as the initial representation of the objects.
138 To learn the proposed distribution $p_\theta(\mathcal{A}_{test}|\mathcal{A}_{demo})$, we need to reason about the geometries of
139 different parts of the objects and their relative alignments. Directly using dense point clouds would
140 make this problem extremely computationally expensive. Therefore, we design a representation for
141 $\mathcal{A}(O_A, O_B)$, that encodes different parts of the objects and the relative poses between them.

142 First, we sample K points from each point cloud using Furthest Point Sampling Algorithm and
143 encode local geometry around them using the Set Abstraction (SA) layer [24], to obtain a set of
144 feature vectors $\mathcal{F}$ and their positions p describing the whole object $\{\mathcal{F}^i, p^i\}_i^K$ (see Figure 4). We

utilise Vector Neurons [25] which, together with the local nature of the SA layer, provide us with $\mathbb{SE}(3)$-Equivariant embeddings $\mathcal{F}$. To ensure that these embeddings describe the local geometry around the sampled point, we pre-train this network as an implicit occupancy network [26], reconstructing the encoded object. Note that each local embedding is used to reconstruct only a part of the object, reducing the complexity of the problem and allowing it to generalise more easily. We provide a full description of the occupancy network used in the Supplementary Material. To encode the relative alignment between the two objects based on the sets of feature and position pairs, we then construct a heterogeneous graph representation. This graph captures the relationships between different parts of the objects and fully describes their geometry. Each edge e_{ij} is assigned a feature vector representing the relative position between the nodes. To model high-frequency changes in the relative position between the nodes, we utilise positional encoding [27] to express edge features.

3.4 Learning the Conditional Alignment Distribution

We use our devised alignment representation $\mathcal{A}$ and learn the proposed conditional distribution $p_\theta(\mathcal{A}_{test}|\mathcal{A}_{demo})$ by employing a novel heterogeneous graph-based transformer energy model denoted as $E_\theta(\mathcal{A}_{test}, \mathcal{A}_{demo})$. Intuitively, the energy-based model should compare $\mathcal{A}_{test}$ with $\mathcal{A}_{demo}$, and predict if alignments are consistent (low energy) or not (high energy). Then, by minimising the predicted energy with respect to $\mathcal{A}_{test}$, we can find a desired alignment of test objects.

Firstly, we combine the graphs describing $\mathcal{A}_{test}$ and $\mathcal{A}_{demo}$ by connecting nodes from demonstrated and test alignments with directional edges, equipped with learnable embeddings (see Figure 4). These connections effectively propagate information about the relative alignment of the objects during the demonstrations to the test observation. This enables the graph to capture the alignment patterns observed in the context and makes it suitable for making predictions about whether the test observation is consistent with the demonstrations. To propagate the information through the graph in a structured manner, we utilise graph transformer convolutions [28], which, for a heterogenous graph, can be viewed as a collection of cross-attention modules. We then learn $p_\theta(\mathcal{A}_{test}|\mathcal{A}_{demo})$ by employing an InfoNCE-style [29] loss function, and minimise the negative log-likelihood of:

$$\hat{p}_\theta\left(\mathcal{A}_{test}|\mathcal{A}_{demo}, \{\hat{\mathcal{A}}_{test}^j\}_j^{N_{neg}}\right) = \frac{\exp(-E_\theta(\mathcal{A}_{test}, \mathcal{A}_{demo}))}{\exp(-E_\theta(\mathcal{A}_{test}, \mathcal{A}_{demo})) + \sum_j^{N_{neg}} \exp(-E_\theta(\hat{\mathcal{A}}_{test}^j, \mathcal{A}_{demo}))} \tag{1}$$

Here N_{neg} is a number of counter-examples, used to approximate the, otherwise intractable, normalisation constant. We create these counter-examples by applying $\mathbb{SE}(3)$ transformations to nodes in the graph describing O_A, transforming both their position p_A and feature vectors $\mathcal{F}_A$. Note that we are able to do this due to the $\mathbb{SE}(3)$-equivariant property of our point cloud encodings. We obtain the transformations using a combination of random and Langevin Dynamics [30, 31] sampling. At inference, we sample from the learnt distribution by minimising the energy using gradient-based optimisation [32, 30] to find an $\mathbb{SE}(3)$ transformation $\mathcal{T}$ which, when applied to O_A, would result in an alignment between the objects which is consistent with the demonstrations (see Figure 4 right).

$$\mathcal{T} = \underset{\mathcal{T} \in SE(3)}{\arg\min} E_\theta(\mathcal{A}_{test}(\mathcal{T} \times O_A, O_B), \mathcal{A}_{demo}) \tag{2}$$

Equation 2 can be understood as follows: Adjust the pose of the object A iteratively until the energy is minimised, indicating that the alignment between the objects A and B becomes consistent with the demonstrated alignments. In practice, we use separate networks for finding orientation and translation alignments, optimising them sequentially. In the Supplementary material, we provide full details regarding training of the proposed energy model, and optimisation on the $\mathbb{SE}(3)$ manifold. Using a graph neural network with transformer-based attention allows us to capture complex relational information between different parts of two objects, and dynamically handle an increasing number of demonstrations during inference. The energy-based approach allows us to learn complex and multi-modal distributions. It can capture the inherent variability and uncertainty in the alignment process, allowing for different ways of aligning objects. This flexibility is crucial when multiple valid alignments exist, e.g. when dealing with symmetrical objects or multi-modal demonstrations.

4 Experiments

To thoroughly assess the effectiveness of our method in learning a general alignment distribution and its practicality in real-world robotic tasks, we conducted experiments in two distinct settings: (1) a simulation setting, where we have access to ground truth information, and (2) a real-world setting, where we evaluate the performance of the complete robotic pipeline on everyday robotic tasks. A single model trained on $500K$ samples (5 consistent alignments each) is used for all the experiments evaluating it by providing new demonstrations as context.

4.1 Exploring Generalisation Modes

Our first set of simulated experiments aims to answer the following question: *Is our model capable of generalising and identifying task-relevant alignments when presented with both novel objects from familiar categories and entirely novel object categories?*

Experimental Procedure. We constructed five distinct evaluation datasets, each introducing an additional mode of generalisation requirement. The generation procedure follows the methodology outlined in Section 3.2, and only includes objects from non-symmetric categories in order to evaluate the orientation accuracy of found alignments. The five evaluation datasets encompass the following samples: 1) *Seen Alignments*: This dataset comprises objects and their alignments that were seen during training. 2) *Unseen Alignments*: In this dataset, objects that were seen during training are aligned in novel ways, introducing unfamiliar alignment configurations. 3) *Unseen Object Instances*: This dataset contains unseen instances of object categories that were encountered during training. 4) *Unseen Object Categorie*s: Here, objects are from categories that were unseen during training. 5) *Multi-Modal Demonstrations*: This dataset focuses on multimodal demonstrations of objects from unseen categories. This means that the demonstrations exhibit multiple modes, indicating different possible object alignments. *Unseen*, here refers to objects, alignments or categories, that have not been used during training. Every described dataset contains 1000 unique samples, each sample with 5 consistent object alignments, 4 of which are used as the context, and 1 as a ground truth label.

Evaluation Metrics. Having access to the ground truth alignment of the objects, we report the translation and rotation errors of the predicted alignment, when starting point clouds are initialised in random $\mathbb{SE}(3)$ poses. In the case of multi-modal demonstrations, we report the error to the closest ground truth alignment. To put the later presented error metrics in perspective, object sizes in the previously described datasets range from 8 cm to 35 cm.

Baselines. In our evaluation, we compare our method of *Implicit Graph Alignment (IGA)* against several baselines and its own variants to demonstrate its effectiveness. 1) *ICP*, where the target and grasped object point clouds are aligned to the closest match amongst the available demonstrations. It serves to validate the need to learn the alignment distribution. 2) *TAX-Pose-DC*, is a variant of TAX-Pose-GC [23], where instead of one-hot encoding, we use an average embedding of the demonstrations as a conditional variable. For a fair comparison, this is our attempt to extend a cross-object correspondence approach to be conditional on demonstrations (the original TAX-Pose-GC conditional on a one-hot encoding of a desired placement). 3) *R-NDF* is Relational Neural Descriptor Fields [21], which aims to validate our choice of using a heterogeneous graph representation for the alignment of objects, instead of matching local descriptors of two objects as in R-NDF. 4) *Ours(DirReg)*, is a variant of our method which, using our graph representation, directly regresses the transformation $\mathcal{T}$ instead of learning an energy function. 5) *Ours(DFM)* is another variant of our method, which predicts $\mathbb{SE}(3)$ distance to the ground truth alignment and learns a distance field instead of an energy function. For a fair comparison, our method and all baselines were trained on the same amount of data from a diverse range of object categories.

	(1) Seen Alignments		(2) Unseen Alignments		(3) Unseen Object Instances		(4) Unseen Object Categories		(5) Multi-Modal Demonstrations	
	Trans (cm)	Rot (deg)	Trans (cm)	Rot (deg)	Trans (cm)	Rot (deg)	Trans (cm)	Rot (deg)	Trans (cm)	Rot (deg)
ICP	15.8 ± 7.7	77.9 ± 27.1	15.3 ± 10.3	78.5 ± 28.1	14.9 ± 8.7	69.4 ± 29.0	16.5 ± 8.9	99.7 ± 34.9	15.0 ± 10.1	83.3 ± 26.4
R-NDF	8.5 ± 3.2	43.1 ± 32.3	8.1 ± 1.7	37.9 ± 21.8	9.2 ± 6.3	46.5 ± 23.1	9.8 ± 5.4	52.1 ± 29.2	13.6 ± 7.6	96.4 ± 45.5
Tax-Pose-DC	21.8 ± 9.9	105.6 ± 39.2	19.6 ± 10.4	117.2 ± 36.8	24.3 ± 9.8	105.4 ± 36.7	21.3 ± 8.9	126.3 ± 38.1	23.9 ± 9.4	123.3 ± 36.7
Ours (DirReg)	4.1 ± 2.4	27.7 ± 6.4	4.9 ± 3.6	27.5 ± 9.6	5.2 ± 3.5	31.6 ± 11.2	6.7 ± 5.0	31.1 ± 10.7	13.1 ± 6.3	76.8 ± 26.4
Ours (DFM)	3.2 ± 1.2	89.6 ± 42.8	3.7 ± 1.6	106.1 ± 57.1	3.7 ± 1.5	103.4 ± 56.8	4.4 ± 2.0	115.3 ± 61.8	10.4 ± 5.1	114.9 ± 58.7
Ours (IGA)	**2.1 ± 1.3**	**9.7 ± 6.4**	**2.3 ± 1.5**	**12.1 ± 5.6**	**2.3 ± 1.4**	**11.7 ± 6.1**	**3.0 ± 1.6**	**14.7 ± 5.3**	**3.9 ± 2.3**	**11.2 ± 6.7**

Table 1: Translation and rotation errors (means and standard deviations) of alignments for different modes of generalisation. Values of the best-performing method are presented in bold.

Results. Results shown in Table 1 reveal that using non-learning-based methods, such as *ICP*, and extending the cross-object correspondence approach to be conditional, yield unsatisfactory performance. The sub-optimal performance of *R-NDF* can be attributed to the high diversity within object categories and instances, as well as the arbitrary alignments between them (as it primarily focuses on finding alignments between objects in close proximity). Other variants of our approach show promising results in terms of translation, but struggle to accurately determine the orientation. Our proposed method, using an implicit energy-based model, excels in both translation and orientation, and across different modes of generalisation.

4.2 Exploring Demonstration Diversity

Our second set of simulated experiments aims to answer the following question: *Which is more important: the number of demonstrations, or the diversity of demonstrations?*

Experimental Procedure. We explore this question by varying both the diversity and the number of demonstrations provided as context. We create 3 different evaluation datasets of demonstrations, each with increasing diversity of objects. We vary the diversity of the objects by increasing the random scaling range, as well as the scale of the latent vector α, which controls the amount of deformations applied by the DIF-Net model [2]. For visualisation of the diversity of objects in the created evaluation datasets see the Supplementary Material.

Figure 5: Translation error based on the number of demonstrations for 3 different sets of diversities.

Results. Translation errors are shown in Figure 5 (orientation errors follow a similar trend and can be seen in the Supplementary Material). Note that a single model is used for all the evaluations. Analysis of Figure 5 reveals that the performance of our method does not improve when the number of demonstrations increases, unless the diversity among those demonstrations also increases. However, an increase in diversity can substantially enhance the performance. Notably, the performance of our method remains relatively unchanged when provided with either 10 or 15 demonstrations, suggesting that the remaining errors are not attributable to insufficient information in the demonstrations. Instead, they likely stem from inherent errors of the learnt model or ambiguities present in the generated datasets.

4.3 Real-World Experiments

Through our real-world experiments, we aim to answer the following question: *Can a robot learn real-world everyday tasks from just a small number of human demonstrations?*

Real-World Setup. Our experiments are performed using the Franka Emika robot, along with three realsense D415 depth cameras. To obtain point clouds of the objects, the cameras first capture the point cloud of the target object with the robot not obstructing their view. Then, the robot moves its gripper to a position where the grasped object is visible to both cameras, after which the cameras capture a point cloud of the grasped object.

Tasks. We evaluate our approach on six different tasks, which can be seen in Figure 6. 1) *Grasping*. The goal is to grasp different pans by the handle. 2) *Stacking*. The goal is to stack two bowls. 3) *Sweeping*. The goal is to sweep marbles into a dustpan with a brush. 4) *Hanging*. The goal is to hang a cap onto a deformable stand. 5) *Inserting*. The goal is to insert a bottle into a shoe. 6) *Pouring*. The goal is to pour a marble into a mug. We provide success criteria in the Supplementary Material.

Experimental Procedure. Trajectories for *Grasping* and *Stacking* tasks are defined by a single waypoint at the grasping or placing locations and executed with a scripted controller, consistent with *R-NDF* [21] and *TAX-Pose* [23]. For these tasks, we provide 3 demonstrations. Trajectories for other tasks are defined by 3 waypoints, which need to be reached sequentially. For these tasks, we provide 4 demonstrations each. Each demonstration is a unique combination of different grasped

Figure 6: Real-world tasks used to evaluate our method, and the corresponding objects used for providing demonstrations and testing.

and target objects. Notably, the *Hanging* task involves a deformable stand and deformable cap, both of which are randomly deformed before each demonstration and test. We evaluate each task on 5 different combinations / deformations of grasped and target test objects, repeating the evaluation 3 times by starting the objects in different configurations, totalling 15 evaluations per task per method. No objects used to provide the demonstrations are used during the evaluation.

Results. As we can see from Table 2, *ICP* and *R-NDF* baselines can be successfully used to complete *Grasping* or *Stacking* tasks but struggle with more challenging ones, e.g. Hanging or Pouring. This can be attributed to the relatively high task tolerances and limited variation in the object geome-

	Grasping	Stacking	Sweeping	Hanging	Inserting	Pouring
ICP	9 / 15	14 / 15	8 / 15	0 / 15	7 / 15	2 / 15
R-NDF	7 / 15	14 / 15	4 / 15	0 / 15	4 / 15	3 / 15
Ours (IGA)	14/ 15	15 / 15	8 / 15	12 / 15	11 / 15	12 / 15

Table 2: Success rates of our method and two best performing baselines in a real-world setting.

tries between demonstrations and inference for these tasks. Our method, on the other hand, can consistently complete all the evaluated tasks from just a few demonstrations, with the notable exception of a Sweeping task. We hypothesise that this is due to major geometry differences between demonstration and test objects, that were not covered by the shape augmentation model.

5 Discussion

Limitations. We now share the main limitations of our method, in order of importance. 1) As with many similar works, we assume that segmented point clouds are available of sufficient observability to capture task-relevant object parts, and thus we require three depth cameras. However, our experiments showed that with real-world hardware and noisy observations, our method is still highly effective for everyday tasks. 2) Our current implementation of gradient-based sampling is not yet suitable for reactive closed-loop control on today's computing hardware, as inference can be time-consuming (up to 15 seconds). 3) We model trajectories as sparse waypoints, which may not be suitable for tasks requiring more complex dynamics. However, in future work, our method could be extended to track a much denser trajectory, including velocities. 4) We assume that objects remain rigidly grasped during a trajectory. Therefore, whilst we have shown that our method works with deformable objects (the *Hanging* task), we have not yet extended this framework for objects which may deform during a task. 5) Our current formulation models a task as the interaction of 2 objects, which might not always be the case. However, we could extend our method to an arbitrary number of objects, if O_B is used to represent an observation of the entire environment. 6) Training of our model relies on data generated using a heuristic method, which may introduce inaccuracies in the training samples and limit the model's precision.

Conclusions. We have proposed a method for few-shot imitation learning, which is able to perform real-world everyday tasks on previously unseen objects, from three or four demonstrations of that task on similar objects. We achieved this by designing a novel graph alignment strategy based on an energy-based model and in-context learning, which was empirically shown to outperform alternative methods. Our experiments and videos highlight that this is also a practical method which enables a robot to perform a task immediately after the demonstrations, without requiring any further data collection or any prior knowledge about the object or class, using just a single trained network.

References

[1] A. X. Chang, T. Funkhouser, L. Guibas, P. Hanrahan, Q. Huang, Z. Li, S. Savarese, M. Savva, S. Song, H. Su, et al. Shapenet: An information-rich 3d model repository. *arXiv preprint arXiv:1512.03012*, 2015.

[2] Y. Deng, J. Yang, and X. Tong. Deformed implicit field: Modeling 3d shapes with learned dense correspondence. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10286–10296, 2021.

[3] Z. Mandi, F. Liu, K. Lee, and P. Abbeel. Towards more generalizable one-shot visual imitation learning. In *2022 International Conference on Robotics and Automation (ICRA)*, pages 2434–2444. IEEE, 2022.

[4] E. Johns. Coarse-to-fine imitation learning: Robot manipulation from a single demonstration. In *2021 IEEE international conference on robotics and automation (ICRA)*, pages 4613–4619. IEEE, 2021.

[5] E. Valassakis, G. Papagiannis, N. Di Palo, and E. Johns. Demonstrate once, imitate immediately (dome): Learning visual servoing for one-shot imitation learning. In *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 8614–8621. IEEE, 2022.

[6] L. Manuelli, W. Gao, P. Florence, and R. Tedrake. kpam: Keypoint affordances for category-level robotic manipulation. In *Robotics Research: The 19th International Symposium ISRR*, pages 132–157. Springer, 2022.

[7] W. Gao and R. Tedrake. kpam 2.0: Feedback control for category-level robotic manipulation. *IEEE Robotics and Automation Letters*, 6(2):2962–2969, 2021.

[8] Z. Qin, K. Fang, Y. Zhu, L. Fei-Fei, and S. Savarese. Keto: Learning keypoint representations for tool manipulation. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7278–7285. IEEE, 2020.

[9] P. R. Florence, L. Manuelli, and R. Tedrake. Dense object nets: Learning dense visual object descriptors by and for robotic manipulation. *arXiv preprint arXiv:1806.08756*, 2018.

[10] L. Manuelli, Y. Li, P. Florence, and R. Tedrake. Keypoints into the future: Self-supervised correspondence in model-based reinforcement learning. *arXiv preprint arXiv:2009.05085*, 2020.

[11] P. Florence, L. Manuelli, and R. Tedrake. Self-supervised correspondence in visuomotor policy learning. *IEEE Robotics and Automation Letters*, 5(2):492–499, 2019.

[12] A. Zeng, P. Florence, J. Tompson, S. Welker, J. Chien, M. Attarian, T. Armstrong, I. Krasin, D. Duong, V. Sindhwani, et al. Transporter networks: Rearranging the visual world for robotic manipulation. In *Conference on Robot Learning*, pages 726–747. PMLR, 2021.

[13] V. Vosylius and E. Johns. Where to start? transferring simple skills to complex environments. In *Conference on Robot Learning*, pages 471–481. PMLR, 2023.

[14] M. Sieb, Z. Xian, A. Huang, O. Kroemer, and K. Fragkiadaki. Graph-structured visual imitation. In *Conference on Robot Learning*, pages 979–989. PMLR, 2020.

[15] I. Kapelyukh and E. Johns. My house, my rules: Learning tidying preferences with graph neural networks. In *Conference on Robot Learning*, pages 740–749. PMLR, 2022.

[16] C. Wang, Y. Zhang, X. Zhang, Z. Wu, X. Zhu, S. Jin, T. Tang, and M. Tomizuka. Offline-online learning of deformation model for cable manipulation with graph neural networks. *IEEE Robotics and Automation Letters*, 7(2):5544–5551, 2022.

[17] D. Driess, J.-S. Ha, M. Toussaint, and R. Tedrake. Learning models as functionals of signed-distance fields for manipulation planning. In *Conference on Robot Learning*, pages 245–255. PMLR, 2022.

[18] J.-S. Ha, D. Driess, and M. Toussaint. Learning neural implicit functions as object representations for robotic manipulation. *arXiv preprint arXiv:2112.04812*, 2021.

[19] J. Urain, N. Funk, G. Chalvatzaki, and J. Peters. Se (3)-diffusionfields: Learning cost functions for joint grasp and motion optimization through diffusion. *arXiv preprint arXiv:2209.03855*, 2022.

[20] I. Huang, Y. Narang, R. Bajcsy, F. Ramos, T. Hermans, and D. Fox. Defgraspnets: Grasp planning on 3d fields with graph neural nets. *arXiv preprint arXiv:2303.16138*, 2023.

[21] A. Simeonov, Y. Du, Y.-C. Lin, A. R. Garcia, L. P. Kaelbling, T. Lozano-Pérez, and P. Agrawal. Se (3)-equivariant relational rearrangement with neural descriptor fields. In *Conference on Robot Learning*, pages 835–846. PMLR, 2023.

[22] A. Simeonov, Y. Du, A. Tagliasacchi, J. B. Tenenbaum, A. Rodriguez, P. Agrawal, and V. Sitzmann. Neural descriptor fields: Se (3)-equivariant object representations for manipulation. In *2022 International Conference on Robotics and Automation (ICRA)*, pages 6394–6400. IEEE, 2022.

[23] C. Pan, B. Okorn, H. Zhang, B. Eisner, and D. Held. Tax-pose: Task-specific cross-pose estimation for robot manipulation. In *Conference on Robot Learning*, pages 1783–1792. PMLR, 2023.

[24] C. R. Qi, L. Yi, H. Su, and L. J. Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *Advances in neural information processing systems*, 30, 2017.

[25] C. Deng, O. Litany, Y. Duan, A. Poulenard, A. Tagliasacchi, and L. J. Guibas. Vector neurons: A general framework for so (3)-equivariant networks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 12200–12209, 2021.

[26] L. Mescheder, M. Oechsle, M. Niemeyer, S. Nowozin, and A. Geiger. Occupancy networks: Learning 3d reconstruction in function space. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4460–4470, 2019.

[27] B. Mildenhall, P. P. Srinivasan, M. Tancik, J. T. Barron, R. Ramamoorthi, and R. Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. *Communications of the ACM*, 65(1):99–106, 2021.

[28] Y. Shi, Z. Huang, S. Feng, H. Zhong, W. Wang, and Y. Sun. Masked label prediction: Unified message passing model for semi-supervised classification. *arXiv preprint arXiv:2009.03509*, 2020.

[29] A. v. d. Oord, Y. Li, and O. Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[30] Y. Du and I. Mordatch. Implicit generation and modeling with energy based models. *Advances in Neural Information Processing Systems*, 32, 2019.

[31] P. Florence, C. Lynch, A. Zeng, O. A. Ramirez, A. Wahid, L. Downs, A. Wong, J. Lee, I. Mordatch, and J. Tompson. Implicit behavioral cloning. In *Conference on Robot Learning*, pages 158–168. PMLR, 2022.

[32] M. Welling and Y. W. Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pages 681–688, 2011.