# EXPLAINABLE GNN-BASED MODELS OVER KNOWLEDGE GRAPHS

## ABSTRACT

Graph Neural Networks (GNNs) are often used to learn transformations of graph data. While effective in practice, GNNs make predictions via numeric manipulations in an embedding space, so their output cannot be easily explained symbolically. We propose a new family of GNN-based transformations of graph data that can be trained effectively, but where all predictions can be explained symbolically as logical inferences in Datalog—a well-known rule-based formalism. We show how to encode an input knowledge graph into a graph with numeric feature vectors, process this graph using a GNN, and decode the result into an output knowledge graph. We use a new class of *monotonic* GNNs (MGNNs) to ensure that this process is equivalent to a round of application of a set of Datalog rules. We also show that, given an arbitrary MGNN, we can extract automatically a set of rules that completely characterises the transformation. We evaluate our approach by applying it to classification tasks in knowledge graph completion.

## 1 INTRODUCTION

*Knowledge graphs* (KGs) (Hogan et al., 2021) are graph-structured knowledge bases describing an application domain as a collection of entities and their relationships. They can be captured in formats such as the Resource Description Framework (RDF), and are used in applications such as Web search, recommendation, fraud detection, and data integration. Many of these applications involve realising a graph transformation. For example, in a recommender system we can represent user-item interactions as a graph (Aggarwal, 2016) and extend it with external KGs to improve accuracy, diversity, and interpretability of recommendations (Zhang et al., 2016; Wang et al., 2018; 2019a); the system then realises a transformation of the input graph into another graph containing recommended user-item interactions. Moreover, a KG completion system (Rossi et al., 2021; Bordes et al., 2013; Teru et al., 2020) transforms an input graph into another graph containing relationships missing in the input. Usually, the transformation is not given explicitly, but is learned from examples.

*Graph Neural Networks (GNNs)* (Scarselli et al., 2009; Liu & Zhou, 2020) are one of the most popular ML models for graph data. They are usually applied to KGs in three stages (Hamilton et al., 2017). First, the input KG is *encoded* into an *embedding space* as another graph whose vertices are labelled with numeric feature vectors. Second, this graph is processed by a GNN with several layers; for each layer, the GNN updates the feature vectors based on the learned model parameters and the vectors of the previous layer. Finally, the vectors of the output layer are *decoded* to the output KG.

While such approaches are effective in practice, GNNs compute predictions through numeric calculations in the embedding space, so the transformation can be difficult to understand. For example, it would be useful to know that a system recommended novel *The Idiot* because the user liked *Crime and Punishment* and both novels were written by Dostoevsky. There is growing interest in explaining GNN predictions, and many methods have focused on identifying relevant subgraphs in the embedding space (Ying et al., 2019; Luo et al., 2020; Lin et al., 2021). Such methods, however, do not explain predictions *symbolically*—that is, by showing how each prediction can be derived from the input KG using rules of inference in a knowledge representation formalism. Datalog (Abiteboul et al., 1995; Ceri et al., 1989) is a prominent formalism based on 'if–then' rules. When applied to facts, the rules derive new facts. For example, we can represent knowledge about literature using facts $Author(Dostoevsky, Crime\_and\_Punishment)$ and $Author(Dostoevsky, The\_Idiot)$, and past interactions using fact $Likes(Crime\_and\_Punishment)$.

Then, the application of rule $Author(x, y_1) \land Author(x, y_2) \land Likes(y_1) \rightarrow Recommend(y_2)$ to these facts derives the target fact $Recommend(\textit{The\_Idiot})$. State-of-the-art Datalog engines (Motik et al., 2014) provide powerful methods for generating human-readable proofs explaining why a target fact follows from the input rules and the data. Such proofs can help fostering trust in system predictions, ensuring compliance with norms, and enabling verification of fairness standards.

The main contribution of this paper is a new family of GNN-based transformations of KGs that can be trained from examples as usual, but whose predictions can be explained symbolically using Datalog rules. Our transformation consists of the three steps mentioned earlier: encoding an input KG, applying a GNN, and decoding the result back into an output KG. These steps, however, were carefully crafted to ensure that the transformation can always be described symbolically. We use a novel class of *monotonic GNNs* (MGNNs), which we designed to ensure an important property: when values in input feature vectors increase, no value of an output feature vector decreases. To capture this intuition formally, we show that our transformation is *monotonic under homomorphisms*—a well-known property that captures key aspects of Datalog rule application.

In contrast to the related approaches (Teru et al., 2020; Hamaguchi et al., 2017; Schlichtkrull et al., 2018; Wang et al., 2019b), all predictions of our transformation can be explained using Datalog rules. Specifically, for an arbitrary MGNN, we can produce an *equivalent* set of rules so that, on any KG, the rules and the MGNN-based transformation produce the same facts. This opens the door to new ways of using MGNNs: when developing Datalog rules manually is difficult, we can train an MGNN model in a supervised manner and use it to provide further predictions, but all such predictions can be explained using rules. For example, we could train an MGNN on a graph containing examples of credit applications and then use it to support decision-making on new applications by applying the model to a different graph; this is analogous to how deep learning is already used in practice. However, unlike the existing approaches, we can explicate the rules that are implicitly captured by the model and use them to *fully* explain each credit recommendation. Thus, we integrate ML and symbolic AI in a single framework, allowing applications to use the best of both worlds.

We demonstrate the effectiveness of our approach by applying it to classification tasks in KG completion. Using well-known benchmarks, we compare our system's performance with that of DRUM (Sadeghian et al., 2019) and AnyBURL (Meilicke et al., 2019), both state-of-the-art KG completion systems able to also generate rules. We show that, in addition to providing an exact correspondence between the model and the extracted rules, our technique also offers competitive performance.

Proofs are given in the appendix, and the source code is available as supplementary material.

## 2 AN MGNN-BASED TRANSFORMATION OF KNOWLEDGE GRAPHS

We now describe our GNN-based transformation of knowledge graphs. In this paper, we see a KG as a *dataset*, which is a finite set of facts of the form $A(a)$ or $R(a_1, a_2)$, where $A$ is a *unary predicate*, $R$ is a *binary predicate*, and $a, a_1, a_2$ are *constants*. Constants represent entities from an application domain, unary predicates typically represent entity types, and binary predicates represent relationships between entities. For example, the statements that a user likes *Crime and Punishment* and it is a novel written by Fyodor Dostoevsky are represented as facts $Likes(\textit{Crime\_and\_Punishment})$ and $Author(\textit{Dostoevsky}, \textit{Crime\_and\_Punishment})$. KGs in formats such as RDF can be transformed into such a dataset in the obvious way. For $D$ a dataset, $\mathsf{cn}(D)$ is the set of constants occurring in $D$.

Our transformation is realised by an operator $T_{\mathcal{M}}$ on datasets, which is parameterised by a GNN $\mathcal{M}$. A dataset $D$ is first encoded into a graph $G_D$ in the embedding space, where vertices are labelled with numeric feature vectors; then, $G_D$ is processed by $\mathcal{M}$; finally the result is decoded to the output dataset $T_{\mathcal{M}}(D)$. In Section 3, we show that, by restricting $\mathcal{M}$ to be a GNN of a special form, called *monotonic*, we can ensure that $T_{\mathcal{M}}$ is equivalent to a round of Datalog rule application; this, in turn, allows us to automatically extract an equivalent set of rules from $T_{\mathcal{M}}$. The embedding space consists of *coloured graphs*, which extend the standard notion of undirected graphs in two ways. First, each vertex is labelled by a numeric feature vector of some fixed dimension; this is necessary in order to allow the coloured graph to be processed by $\mathcal{M}$. Second, each edge in the graph is assigned a colour, which allows us to distinguish different types of connections in the graph.

Figure 1 illustrates the encoding of the dataset $D$ in the introduction. First, we introduce vertices $v_{Ds}$, $v_{CP}$, and $v_I$ in $G_D$ to represent constants *Dostoevsky*, *The\_Idiot*, and *Crime\_and\_Punishment*. The

Figure 1: Graphical representation of dataset $D = \{Author(Dostoevsky, Crime\_and\_Punishment),$
$Author(Dostoevsky, The\_Idiot), Likes(Crime\_and\_Punishment)\}$ and its encoding $G_D$ for predicates
*Likes, Recommended, Author* (first two unary, last binary); constants in the encoding are abbreviated

feature vector of each vertex $v_a$ represents all unary and binary facts of the form $X(a)$ and $Y(a, a)$;
for example, $v_{CP}$ has 1 as the first element of its vector representing *Likes(Crime\_and\_Punishment)*.
Second, we introduce vertices $v_{Ds,CP}$, $v_{CP,Ds}$, $v_{Ds,I}$, and $v_{I,Ds}$, whose vectors represent all binary facts
over the corresponding constants; for example, $v_{Ds,CP}$ has 1 as the third vector element, representing
*Author(Dostoevsky, Crime\_and\_Punishment)*. Since *The\_Idiot* and *Crime\_and\_Punishment* do not
occur together in a fact in $D$, the encoding of $D$ contains neither $v_{CP,I}$ nor $v_{I,CP}$. Here, we rely
on an order of predicates to determine the corresponding vector positions; this order is arbitrary,
but fixed in advance. Third, we connect all vertices of $G_D$ referring to common constants with
coloured edges, which allows us to distinguish different types of joins between facts. For example,
$v_{Ds}$ and $v_{Ds,CP}$ refer to *Dostoevsky*, so we connect them with an edge of colour $c_1$, thus indicating that
*Dostoevsky* occurs first in the constant pair of $v_{Ds,CP}$. Analogously, we connect $v_{Ds,CP}$ and $v_{CP}$ with
an edge of colour $c_2$. The constant pair of $v_{CP,Ds}$ is the inverse of $v_{Ds,CP}$'s, so we connect them
with an edge of colour $c_3$. Finally, we use edges of colour $c_4$ to connect vertices of $G_D$ representing
constants occurring together in a fact, such as $v_{CP}$ and $v_{Ds}$.

Formally, we fix a set of four *colours* $\mathsf{Col} = \{c_1, c_2, c_3, c_4\}$. We assume that datasets and derived
facts will use finitely many predicates, and fix a list $A_1, \ldots, A_\epsilon, R_{\epsilon+1}, \ldots, R_\delta$ of available unary
and binary predicates. We consider vectors and matrices over the reals $\mathbb{R}$ and its nonnegative subset
$\mathbb{R}^+$. For $\mathbf{v}$ a vector, $(\mathbf{v})_i$ is the $i$-th element of $\mathbf{v}$. We apply scalar functions to vectors and matrices
element-wise; for example, for $\mathbf{v}_1, \ldots, \mathbf{v}_n$ vectors of equal dimension, $\max\{\mathbf{v}_1, \ldots, \mathbf{v}_n\}$ is the vec-
tor whose $i$-th element is $\max\{(\mathbf{v}_1)_i, \ldots, (\mathbf{v}_n)_i\}$. Finally, a function $\sigma : \mathbb{R} \to \mathbb{R}$ is *monotonically
increasing* if $x < y$ implies $\sigma(x) \leq \sigma(y)$, and function $\sigma$ is *Boolean* if it ranges over $\{0, 1\}$. The
following definition describes the structure of our embedding space.

**Definition 1.** *A* $(\mathsf{Col}, \delta)$-*graph is a tuple* $\langle V, \{E_c\}_{c \in \mathsf{Col}}, \lambda \rangle$, *where* $V$ *is a finite set of vertices; for
each* $c \in \mathsf{Col}$, $E_c$ *is a set of* $c$-*coloured undirected edges (possibly including self-loops) over* $V$; *and
labelling* $\lambda$ *assigns to each* $v \in V$ *a vector* $\lambda(v)$ *of dimension* $\delta$. *If* $\lambda$ *is implicitly understood,* $\lambda(v)$
*is written as* $\mathbf{v}$. *For* $c \in \mathsf{Col}$ *and* $v \in V$, $N_c(v)$ *is the set of vertices connected to* $v$ *by an edge in* $E_c$.

We are now ready to define our encoding of an arbitrary dataset $D$ into a $(\mathsf{Col}, \delta)$-graph $G_D$.

**Definition 2.** *The* encoding *of a dataset* $D$ *is the* $(\mathsf{Col}, \delta)$-*graph* $G_D$ *that contains a vertex* $v_a$ *for
each constant* $a \in \mathsf{cn}(D)$, *and vertices* $v_{a,b}$ *and* $v_{b,a}$ *for all (not necessarily distinct) constants* $a$ *and
$b$ that occur together in a binary fact in* $D$. *For each vertex* $v_{a,b}$, $G_D$ *contains an edge of colour* $c_1$
*connecting* $v_{a,b}$ *and* $v_a$, *an edge of colour* $c_2$ *connecting* $v_{a,b}$ *and* $v_b$, *an edge of colour* $c_3$ *connecting*
$v_{a,b}$ *and* $v_{b,a}$, *and an edge of colour* $c_4$ *connecting* $v_a$ *and* $v_b$. *For each* $v_a$, *labelling* $(\mathbf{v}_a)_i$ *is 1 if*
$A_i(a) \in D$ *and 0 otherwise. For each* $v_{a,b}$, *labelling* $(\mathbf{v}_{a,b})_i$ *is 1 if* $R_i(a, b) \in D$ *and 0 otherwise.*

We process $G_D$ by a GNN. As we explain in more detail Section 3, if we are to ensure that our
transformation 'mimics' Datalog rule application, we cannot use an arbitrary GNN. Instead, we
introduce *Monotonic Graph Neural Networks (MGNNs)*, which restrict GNNs in a way that allows
us to attain our objective. Definition 3 also specifies how to apply an MGNN to a coloured graph.

**Definition 3.** *A* $(\mathsf{Col}, \delta)$-monotonic graph neural network *(MGNN)* $\mathcal{M}$ *with* $L \geq 1$ *layers is a tuple*
$\langle \{\mathbf{A}^\ell\}_{1 \leq \ell \leq L}, \{\mathbf{B}_c^\ell\}_{c \in \mathsf{Col}, 1 \leq \ell \leq L}, \{\mathbf{b}^\ell\}_{1 \leq \ell \leq L}, \sigma, \mathsf{cls} \rangle$. *For each* $\ell \in \{1, \ldots, L\}$ *and each* $c \in \mathsf{Col}$, $\mathbf{A}^\ell$
*and* $\mathbf{B}_c^\ell$ *are matrices over* $\mathbb{R}^+$ *of dimension* $m^\ell \times n^\ell$, *and* $\mathbf{b}^\ell$ *is a vector over* $\mathbb{R}$ *of dimension* $n^\ell$
*such that* $n^1 = m^L = \delta$, *and* $m^{\ell-1} = n^\ell$ *for each* $\ell \in \{2, \ldots, L\}$. *Moreover,* $\sigma : \mathbb{R} \to \mathbb{R}^+$ *is a
monotonically increasing* activation *function, and* $\mathsf{cls} : \mathbb{R}^+ \to \{0, 1\}$ *is a monotonically increasing*
classification *function. The* dimension *of* $\mathcal{M}$ *is* $\max\{n^1, \ldots, n^L\}$.

*Applying $\mathcal{M}$ to a $(\mathsf{Col}, \delta)$-graph $G = \langle V, \{E_c\}_{c \in \mathsf{Col}}, \lambda \rangle$ induces the sequence $\lambda^0, \ldots, \lambda^L$ of vertex labellings where $\lambda^0 = \lambda$, and for each $\ell \in \{1, \ldots, L\}$ and $v \in V$, the value of $\lambda^\ell(v)$ is given by*

$$\mathbf{v}^\ell = \sigma\big(\mathbf{A}^\ell \mathbf{v}^{\ell-1} + \sum_{c \in \mathsf{Col}} \mathbf{B}_c^\ell \max\{\mathbf{w}^{\ell-1} \mid w \in N_c(v)\} + \mathbf{b}^\ell\big). \tag{1}$$

*The result $\mathcal{M}(G)$ of applying $\mathcal{M}$ to $G$ is the $(\mathsf{Col}, \delta)$-graph with the same vertices and edges as $G$, but where each vertex $v \in V$ is labelled by $\mathsf{cls}(\lambda^L(v))$.*

Intuitively, an MGNN consists of $L$ layers, where each layer $\ell \in \{1, \ldots, L\}$ is defined by a matrix $\mathbf{A}^\ell$, a matrix $\mathbf{B}_c^\ell$ for each colour $c$, and a bias vector $\mathbf{b}^\ell$; these constitute the learnable parameters of the model. In addition, an MGNN also uses functions $\sigma$ and $\mathsf{cls}$ which are fixed and given explicitly. An MGNN transforms an arbitrary $(\mathsf{Col}, \delta)$-graph $G$ into another $(\mathsf{Col}, \delta)$-graph $\mathcal{M}(G)$ as follows. Each vertex $v$ in $G$ and each $\ell \in \{0, \ldots, L\}$ is associated with a labelling $\mathbf{v}^\ell$. Labelling $\mathbf{v}^0$ is the labelling $\mathbf{v}$ of $v$ in $G$, and, for each layer $\ell$, vertex $v$ is labelled by a feature vector $\mathbf{v}^\ell$ computed as specified in equation (1). The feature vector of $v$ in the resulting graph is computed by applying the classification function $\mathsf{cls}$ to the final labelling $\mathbf{v}^L$. Thus, MGNNs instantiate the GNN framework by (i) taking the maximum of the features of a vertex' neighbours (instead of the more commonly used sum or average), (ii) using nonnegative weights in matrices $\mathbf{A}^\ell$ and $\mathbf{B}_c^\ell$ (but the elements of bias vectors $\mathbf{b}^\ell$ can be negative), and (iii) requiring the activation and classification functions to be monotonically increasing. We discuss the reasons for these restrictions in Section 3.

The result $\mathcal{M}(G_D)$ of applying an MGNN to the encoding $G_D$ of a dataset $D$ can be decoded into the output dataset of the transformation by essentially inverting the encoder (see Figure 1 for an example). Thus, for each MGNN $\mathcal{M}$, we obtain a distinct operator $T_\mathcal{M}$ that is specified as follows.

**Definition 4.** *For $\mathcal{M}$ a $(\mathsf{Col}, \delta)$-MGNN and $D$ a dataset, $T_\mathcal{M}(D)$ is the dataset containing the fact $A_i(a)$ for each $i \in \{1, \ldots, \epsilon\}$ and each vertex $v_a$ such that $(\mathbf{v}_a)_i = 1$ in $\mathcal{M}(G_D)$, and the fact $R_i(a, b)$ for each $i \in \{\epsilon + 1, \ldots, \delta\}$ and each vertex $v_{a,b}$ such that $(\mathbf{v}_{a,b})_i = 1$ in $\mathcal{M}(G_D)$.*

Note that the dimensions of the matrices in $\mathcal{M}$ do not predetermine the kind of dataset to which $T_\mathcal{M}$ can be applied; in fact, $\mathcal{M}$ can be trained on some dataset and then applied to a different dataset over the same predicates. This makes our transformation ideally suited for *inductive settings* in applications such as KG completion and recommendation (Teru et al., 2020; Hamaguchi et al., 2017; van den Berg et al., 2017), where the datasets to which a trained model is applied may use constants (i.e., *entities*) not mentioned in the datasets on which the model was trained.

## 3 EXTRACTING AN EQUIVALENT SET OF DATALOG RULES

We now show that, for each MGNN $\mathcal{M}$, we can automatically generate a set of Datalog rules $\mathcal{P}_\mathcal{M}$ such that $T_\mathcal{M}$ and $\mathcal{P}_\mathcal{M}$ derive the same facts on any dataset $D$. To this end, we first recapitulate the basic definitions of Datalog and identify a property that characterises Datalog reasoning.

A (Datalog) *atom* is of the form $A(t_1)$ or $R(t_1, t_2)$, where $A$ and $R$ are unary and binary predicates, respectively, and each $t_i$ is a constant or *variable*. A (Datalog) *rule* is an implication of the form (2), where $H$ is the atom called the rule's *head*, all $B_i$ are atoms that together form the rule's *body*, and each variable in $H$ occurs in some $B_i$.

$$H \leftarrow B_1 \wedge \cdots \wedge B_m \tag{2}$$

A (Datalog) *program* is a finite set of rules. A *substitution* $\nu$ is a mapping of finitely many variables to constants; for $\alpha$ an atom, $\alpha\nu$ is the result of replacing in $\alpha$ each variable $x$ on which $\nu$ is defined with $\nu(x)$. Each rule $r$ of form (2) defines the *immediate consequence* operator $T_r$ on datasets: for $D$ a dataset, $T_r(D)$ contains fact $H\nu$ for each substitution $\nu$ satisfying $\{B_1\nu, \ldots, B_m\nu\} \subseteq D$. For $\mathcal{P}$ a program, operator $T_\mathcal{P}$ on datasets is defined by $T_\mathcal{P}(D) = \bigcup_{r \in \mathcal{P}} T_r(D)$.

Our objective is to show that, for each MGNN $\mathcal{M}$, operator $T_\mathcal{M}$ 'behaves analogously' to Datalog rule application. Definition 5 specifies formally what this means in our setting.

**Definition 5.** *A homomorphism from a dataset $D$ to a dataset $D'$ is a mapping $h$ of constants to constants that is defined at least on $\mathsf{cn}(D)$ and that satisfies $h(D) \subseteq D'$, where $h(D)$ is the dataset obtained by replacing each constant $a$ in $D$ with $h(a)$ and removing all duplicate facts. An operator $T$ from datasets to datasets is* monotonic under homomorphisms *if, for all datasets $D$ and $D'$, each homomorphism from $D$ to $D'$ is also a homomorphism from $T(D)$ to $T(D')$.*

For any constant-free program $\mathcal{P}$, operator $T_{\mathcal{P}}$ is monotonic under homomorphisms. For example, let $D = \{A(a), R(a,b)\}$ and $\mathcal{P} = \{S(x,y) \leftarrow A(x) \wedge R(x,y)\}$, so $T_{\mathcal{P}}(D) = \{S(a,b)\}$. First, operator $T_{\mathcal{P}}$ is *monotonic*: adding facts to $D$ cannot invalidate any consequence of $T_{\mathcal{P}}$, since the body of $r$ still matches and the rule derives $S(a,b)$. Second, operator $T_{\mathcal{P}}$ is resilient to replacement of constants. For example, let $D' = \{A(c), R(c,c)\}$ be obtained from $D$ by replacing $a$ and $b$ with $c$. Rule $r$ 'cannot tell' that the constants have been replaced, deriving $T_{\mathcal{P}}(D') = \{S(c,c)\}$, which is obtained from $T_{\mathcal{P}}(D)$ by the same replacement. Monotonicity under homomorphisms combines both properties. We next show that rules can be extracted from any operator satisfying this property.

**Definition 6.** *An operator $T$ on datasets* captures *a rule or program $\alpha$ if $T_{\alpha}(D) \subseteq T(D)$ for each dataset $D$.*

**Proposition 7.** *Let $T$ be an operator on datasets, let $r$ be a constant-free rule of form* (2)*, let $\mu$ be a substitution that maps each variable of $r$ to a distinct constant, and let $D_r = \{B_1\mu, \ldots, B_m\mu\}$. If $T$ is monotonic under homomorphisms and $H\mu \in T(D_r)$, then $T$ captures $r$.*

Intuitively, if some operator $T$ captures a rule $r$, then $T_r$ provides us with a *lower bound* for the consequences of $T$ on an arbitrary dataset—on any dataset, $T$ derives at least as many facts as $r$ (but $T$ can derive more facts). Moreover, if $T$ is monotonic under homomorphisms, Proposition 7 provides us with an effective way of checking whether $T$ captures $r$: replace each variable in $r$ with a distinct constant, collect the resulting body atoms in a dataset $D_r$, apply $T$ to $D_r$, and finally check whether the result contains the replaced head atom of $r$. Clearly, $T$ captures a constant-free program $\mathcal{P}$ if $T$ captures each rule $r \in \mathcal{P}$, so we can just apply this check to each $r \in \mathcal{P}$ to verify whether $T$ captures $\mathcal{P}$. This provides us with the necessary machinery for rule extraction.

We next show that operator $T_{\mathcal{M}}$ is monotonic under homomorphisms. This shows that $T_{\mathcal{M}}$ indeed 'behaves like' Datalog reasoning, and it will allow us to use Proposition 7 for rule extraction.

**Theorem 8.** *For each $(\mathsf{Col}, \delta)$-MGNN $\mathcal{M}$, mapping $T_{\mathcal{M}}$ is monotonic under homomorphisms.*

Theorem 8 is a consequence of the restrictions on MGNNs mentioned after Definition 3. For monotonicity, note that adding facts to a dataset $D$ has the effect of possibly adding new vertices and edges and then flipping from $0$ to $1$ some vector positions labelling the vertices of $G_D$; moreover, the elements of $\mathbf{A}^{\ell}$ and $\mathbf{B}_c^{\ell}$ are nonnegative so the arguments of $\sigma$ in equation (1) can only increase; finally, functions $\sigma$ and $\mathsf{cls}$ are monotonically increasing so the elements of the feature vectors in $\mathcal{M}(G_D)$ can only flip from $0$ to $1$, which is equivalent to deriving more facts in $T_{\mathcal{M}}(D)$. For the resilience of constant merging, replacing, say, constant $b$ with constant $a$ in $D$ is tantamount to merging vertices $v_b$ into $v_a$ in $G_D$; this will cause vertex $v_a$ to have fewer neighbours, but since we aggregate neighbours' feature vectors by taking the maximum, this cannot change the result of equation (1). Note that, if we aggregated neighbours using a sum (as is common in the literature), then elements of the feature vectors in $\mathcal{M}(G_D)$ could decrease due to merging, which would invalidate Theorem 8.

Theorem 8 tells us that we can check whether $T_{\mathcal{M}}$ captures a rule $r$ effectively using Proposition 7. This is a key step of our rule extraction algorithm. In particular, we next show that it is sufficient to consider only rules of a certain structure, and that the number of such rules is bounded and determined by the dimension of $\mathcal{M}$, the number of layers of $\mathcal{M}$, and the number of predicates $\delta$. Thus, to obtain a program $\mathcal{P}_{\mathcal{M}}$ deriving the same consequences as $T_{\mathcal{M}}$, we can, in principle, enumerate all such rules, apply Proposition 7 to each rule, and keep only the rules that pass this check. To realise such procedure in practice, several optimisations are possible. For example, the relevant space of rules can be significantly reduced by exploiting the fact that rules can be subsumed (i.e., logically implied) by other rules; for instance, if we have determined that a rule $B(x) \leftarrow A(x)$ has been captured, then rules of the form $B(x) \leftarrow A(x) \wedge C$, with $C$ any conjunction, do not need to be considered since such rules are logically implied by the previous one and are hence redundant.

Definition 9 describes the syntactic structure of the rules that can fully characterise $T_{\mathcal{M}}$. To this end, we use the well-known notion of a *primal graph* of a conjunction $C$ of atoms, which is the undirected graph (possibly with self-loops) whose vertices are the variables of $C$, and where an edge connects each pair of (not necessarily distinct) variables $x$ and $y$ such that $R(x,y)$ is in $C$ for some $R$. Note that the primal graph of an empty conjunction is also empty. A primal graph is a (possibly empty) *tree* if it is connected and acyclic (and, in particular, without self-loops).

**Definition 9.** *Let $c$ and $d$ be nonnegative integers. A constant-free conjunction $C$ is $(c,d)$-tree-like for a variable $x$ if the primal graph of $C$ is a tree that is either empty or can be rooted at $x$*

*(i.e., $x$ occurs in $C$) and, for each vertex $v$ in the tree, the distance $i$ of $v$ from $x$ is at most $d$ and moreover $v$ has at most $c(d-i)$ children. A $(c,d)$-tree-like rule is a rule of form $A(x) \leftarrow C_x$ or $R(x,y) \leftarrow C_x \wedge B_{x,y} \wedge C_y$, where $C_x$ and $C_y$ are $(c,d)$-tree-like conjunctions for $x$ and $y$, respectively, with no variables in common, and $B_{x,y}$ is a nonempty constant-free conjunction of binary atoms of the form $S(x,y)$ or $S(y,x)$.[1]*

*For $\mathcal{M}$ a $(\mathsf{Col}, \delta)$-MGNN with $L$ layers and dimension $k$ (see Definition 3), let $\mathcal{P}_{\mathcal{M}}$ be the program that contains, up to variable renaming, each $(3k, L)$-tree-like rule that is captured by $T_{\mathcal{M}}$.*

The primal graph of rule $A(x) \wedge R(x,y) \wedge S(x,z)$ is a tree with root $x$ and children $y$ and $z$; thus, it is $(2,1)$-tree like, but not $(1,1)$-tree-like (since $x$ is at distance 0 from itself it can have at most one child). Second, the primal graph of $A(x) \wedge R(x,y) \wedge S(x,z) \wedge T(y,z)$ is a triangle with nodes $x$, $y$, and $z$, so it is not $(c,d)$-tree-like for any $c$ and $d$.

**Theorem 10.** *For each $(\mathsf{Col}, \delta)$-MGNN $\mathcal{M}$ and each dataset $D$, we have $T_{\mathcal{M}}(D) = T_{\mathcal{P}_{\mathcal{M}}}(D)$.*

Theorem 10 also describes the expressiveness (i.e., the kind of possible predictions) of $T_{\mathcal{M}}$. For example, no MGNN can capture rules such as $r = R(x,z) \leftarrow R(x,y) \wedge R(y,z)$. To see this, let $D = \{R(a,b), R(b,c)\}$. For an arbitrary MGNN $\mathcal{M}$, Theorem 10 ensures that all predictions of $T_{\mathcal{M}}$ involving binary facts are made by rules of the form $R(x,y) \leftarrow C_x \wedge B_{x,y} \wedge C_y$; however, no such rule can derive $R(a,c)$ on $D$, so we necessarily have $R(a,c) \notin T_{\mathcal{M}}(D)$ as well.

## 4 EVALUATION

We have evaluated our approach on KG completion tasks, which involve extending a KG seen as a dataset $D$ to its complete version $D'$ by adding missing facts. When seen as a classification problem, the aim is to learn a Boolean function $f(\cdot, \cdot)$ that takes a dataset $D$ and a fact $\alpha$ over a fixed set of unary and binary predicates such that $f(D, \alpha)$ returns *true* if and only if $\alpha \in D'$. We consider the more general *inductive* variant of this task, where the testing dataset may contain constants not occurring in the training or validation datasets (but all predicates in the testing dataset are known before training). Inductive KG completion is more general and challenging than the *transductive* variant (Bordes et al., 2013), where all constants in the testing data also occur in the training data.

**Baselines.** We compared our approach with DRUM (Sadeghian et al., 2019) and AnyBURL (Meilicke et al., 2019), two state-of-the-art approaches for knowledge graph completion.

DRUM learns an end-to-end differentiable model that, given a dataset $D$ and a fact $\alpha$, returns a score representing the likelihood of $\alpha$ belonging to the completion of $D$; predictions are then computed by applying a threshold to the score. The system also produces a set of *chain* Datalog rules of the form $H(x_1, x_n) \leftarrow B_1(x_1, x_2) \wedge B_2(x_2, x_3) \wedge \cdots \wedge B_{n-1}(x_{n-1}, x_n)$, each associated with a confidence score. These extracted rules approximate the model's predictions, but, unlike in our work, the exact relationship between the predictions and the result of applying the rules is unspecified.

AnyBURL uses path sampling techniques to generate chain rules of a slightly more general form (variables can be replaced by constants). Each rule is associated with a score. Given dataset $D$ and fact $\alpha$, AnyBURL makes its prediction by applying a threshold to a score computed by first applying the rules on $D$ once and then combining the probabilities associated to all rules deriving $\alpha$.

**Benchmarks and performance metrics.** We used the 12 KG completion benchmarks by Teru et al. (2020), which are based on FB15K-237 (Bordes et al., 2013), NELL-995 (Xiong et al., 2017), and WN18RR (Dettmers et al., 2018). Each benchmark provides disjoint datasets $\mathcal{T}$, $\mathcal{V}$, and $\mathcal{S}$ for training, validation, and testing, respectively; statistics are shown in Table 1.

We evaluated performance of our systems as follows. Each benchmark provides a method for randomly splitting its testing dataset $\mathcal{S}$ into disjoint subsets $\mathcal{S}_I$ and $\mathcal{S}_C$; intuitively, $\mathcal{S}_I$ is the incomplete dataset to be completed with dataset $\mathcal{S}_C$. Thus, we took $(\mathcal{S}_I, \alpha)$ for each fact $\alpha \in \mathcal{S}_C$ as a positive example for testing. Moreover, we randomly sampled $|\mathcal{S}_C|$ facts $\beta_1, \ldots, \beta_n$ over the predicates of $S_I$ satisfying $\beta_i \notin \mathcal{S}_C$, and we took each $(\mathcal{S}_I, \beta_i)$ as a negative example for testing. Sampling was necessary because the set of possible facts not contained in $\mathcal{S}_C$ is very large; moreover, random

---

[1]Note that $C_x$ cannot be empty in a rule of form $A(x) \leftarrow C_x$ since $x$ is required to occur in the body.

|  | FB15K-237 | | | | NELL-995 | | | | WN18RR | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  | v1 | v2 | v3 | v4 | v1 | v2 | v3 | v4 | v1 | v2 | v3 | v4 |
| Train. | 4,245 | 9,739 | 17,986 | 27,203 | 4,687 | 8,219 | 16,393 | 7,546 | 5,410 | 15,262 | 25,901 | 7,940 |
| Valid. | 489 | 1,166 | 2,194 | 3,352 | 414 | 922 | 1,851 | 876 | 630 | 1,838 | 3,097 | 934 |
| Test. | 2,198 | 4,623 | 8,271 | 13,138 | 933 | 5,062 | 8,857 | 7,804 | 1,806 | 4,452 | 6,932 | 13,763 |

Table 1: Number of facts for each benchmark and phase (Training, Validation, and Testing)

|  |  | Precision | | | Recall | | | Accuracy | | | F1 Score | | | AUC | | | Training (s) | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  |  | A | D | M | A | D | M | A | D | M | A | D | M | A | D | M | D | M |
| FB15K-237 | v1 | **100.0** | 82.2 | 98.5 | 25.6 | **40.5** | 32.7 | 62.9 | 65.9 | **66.1** | 41.1 | **54.2** | 49.1 | 62.0 | **68.6** | 65.7 | 15,540 | 9,192 |
|  | v2 | **100.0** | 85.3 | 99.5 | 47.9 | **48.5** | 41.2 | **74.0** | 70.0 | 70.5 | **64.5** | 61.9 | 58.3 | 73.8 | **76.0** | 70.4 | 19,080 | 23,523 |
|  | v3 | **100.0** | 85.6 | 99.0 | 43.6 | **45.2** | 34.6 | **71.2** | 68.8 | 67.1 | **60.7** | 59.2 | 51.2 | 71.7 | **73.3** | 67.4 | 37,776 | 45,104 |
|  | v4 | **100.0** | 88.8 | 99.4 | **46.0** | 41.6 | 35.1 | **73.0** | 68.2 | 67.5 | **63.0** | 56.7 | 52.0 | 73.0 | **73.7** | 67.3 | 87,000 | 42,540 |
| NELL-995 | v1 | **97.5** | 94.7 | 96.4 | 77.0 | 18.0 | **80.0** | 87.5 | 58.5 | **88.5** | 86.0 | 30.3 | **87.4** | 85.7 | 52.6 | **89.6** | 402 | 662 |
|  | v2 | **100.0** | 80.7 | **100.0** | **53.1** | 41.2 | 48.3 | **76.6** | 65.7 | 74.2 | **69.4** | 54.5 | 65.2 | **76.3** | 74.6 | 74.2 | 6,354 | 3,575 |
|  | v3 | **100.0** | 85.8 | **100.0** | 47.3 | 45.6 | **55.3** | 73.7 | 69.0 | **77.6** | 64.2 | 59.6 | **71.2** | 69.3 | 75.3 | **77.6** | 36,090 | 13,456 |
|  | v4 | **100.0** | 80.3 | 99.5 | 44.3 | 26.8 | **57.2** | 72.2 | 60.1 | **78.5** | 61.4 | 40.2 | **72.6** | 71.6 | 67.1 | **78.5** | 3,990 | 16,839 |
| WN18RR | v1 | 99.1 | 97.9 | **100.0** | 58.5 | **73.4** | 62.8 | 79.0 | **85.9** | 81.4 | 73.6 | **83.4** | 77.1 | 78.8 | **92.5** | 80.1 | 312 | 292 |
|  | v2 | **100.0** | 96.3 | **100.0** | **75.7** | 69.8 | 60.8 | **87.9** | 83.6 | 80.4 | **86.2** | 80.9 | 75.6 | 59.8 | **87.4** | 80.3 | 2,856 | 856 |
|  | v3 | 99.7 | 91.3 | **100.0** | 48.4 | **59.7** | 28.3 | 74.1 | **77.0** | 64.1 | 65.2 | **72.2** | 44.1 | 60.6 | **85.2** | 64.0 | 9,984 | 2,423 |
|  | v4 | 99.9 | 98.3 | **100.0** | **71.6** | 65.6 | 58.0 | **85.8** | 82.2 | 79.0 | **83.4** | 78.7 | 73.4 | 59.0 | **93.9** | 79.0 | 1,638 | 409 |

Table 2: Results for AnyBURL (A), DRUM (D), and our MGNN-based system (M), in percentages

sampling does not favour a specific way of constructing negative examples during training. The number of positive and negative examples was the same to ensure that metrics are balanced. For each system, we classified the positive and negative testing examples and computed the precision, recall, accuracy, and F1 score in the usual way, as well as the area under the precision-recall curve (AUC) by considering different classification thresholds between 0.01 and 0.99.

**Training.** Our system is trained as a denoising autoencoder (Vincent et al., 2010). The training dataset $\mathcal{T}$ is first split with a 9:1 ratio into an incomplete dataset $\mathcal{T}_I$ and a set $\mathcal{T}_C$ of facts that should hold in the completion of $\mathcal{T}_I$. To train our model, we used $(\mathcal{T}_I, \alpha)$ for each fact $\alpha \in \mathcal{T}_C$ as a positive example, and we obtained negative examples $(\mathcal{T}_I, \beta)$ by sampling $\beta$ analogously to how this was done for testing. We consider MGNNs with 2 layers and ReLU as activation function. We used cross-entropy loss with a logistic sigmoid on $\lambda^L(v)$ as the output probability, and we trained using Adam optimisation with the standard learning rate (0.01) and weight decay ($5 \times 10^{-4}$), and a maximum of $50,000$ epochs. We implemented the procedure in Pytorch Geometric v1.5.0, and ran it on a laptop running macOS 10.15.7 with 8 GB of RAM and an Intel Core i5 2.30 GHz CPU.

We trained the baseline systems using their (publicly available) code with their default configurations. For each system and benchmark, we computed the accuracy on the validation dataset for a range of thresholds, and we used in our tests the threshold that maximises accuracy.

**Evaluation results.** Table 2 shows the results of our evaluation. As one can see, our system was overall very competitive, and it outperformed both baselines on most benchmarks based on NELL-995. Table 2 also shows the training times for DRUM and our system, which are are comparable; no times can be shown for AnyBURL because this system does not train a model.

Similarly to AnyBURL, our system attained extremely high precision scores; however, recall values were significantly lower, especially for the benchmarks based on FB15K. This can be explained by the fact that, after randomly splitting the testing dataset $\mathcal{S}$ into subsets $\mathcal{S}_I$ and $\mathcal{S}_C$, numerous facts of the form $R(a, b)$ in $\mathcal{S}_C$ use pairs of constants $a$ and $b$ that do not occur together in any fact in $\mathcal{S}_I$. By Theorem 10 from Section 3, our transformation can never produce such facts in the output. To confirm our hypothesis that this is the main reason for low recall scores, we additionally split the testing dataset $\mathcal{S}$ so that a fact $R(a, b)$ is placed into $\mathcal{S}_C$ only if $\mathcal{S}_I$ contains a fact of the form $S(a, b)$ or $S(b, a)$ for some predicate $S$. The results for our system obtained in this way are shown in Table 3. As one can see, precision scores remain high, whereas recall values increase significantly; thus, accuracy, F1 score, and AUC values improve accordingly. Our system significantly outperformed all

| Benchmark | | Precision | Recall | Accuracy | F1 Score | AUC |
|---|---|---|---|---|---|---|
| FB15K-237 | v1 | 95.5 | 74.0 | 85.3 | 83.4 | 89.5 |
| | v2 | 90.3 | 70.0 | 79.9 | 76.9 | 85.8 |
| | v3 | 88.8 | 72.6 | 81.7 | 79.9 | 86.9 |
| | v4 | 90.5 | 79.7 | 85.6 | 84.7 | 91.7 |
| NELL-995 | v1 | 92.3 | 98.8 | 95.2 | 95.5 | 93.3 |
| | v2 | 83.5 | 57.3 | 73.0 | 68.0 | 79.4 |
| | v3 | 82.3 | 71.1 | 77.9 | 76.3 | 89.0 |
| | v4 | 78.5 | 62.4 | 72.7 | 69.5 | 75.8 |
| WN18RR | v1 | 82.1 | 100.0 | 89.1 | 90.2 | 95.1 |
| | v2 | 91.7 | 98.0 | 94.6 | 94.7 | 98.7 |
| | v3 | 88.2 | 98.9 | 92.9 | 93.3 | 89.0 |
| | v4 | 83.8 | 99.0 | 89.9 | 90.8 | 97.7 |

Table 3: Evaluation of the MGNN transformation with alternative splitting of the testing dataset

| Benchmark | | # Rules captured containing... | |
|---|---|---|---|
| | | 1 body atom | 2 body atoms |
| FB15K-237 | v1 | 2,102 | 41,341 |
| | v2 | 3,370 | 27,900 |
| | v3 | 3,199 | 42,590 |
| | v4 | 8,464 | 82,003 |
| NELL-995 | v1 | 149 | 215 |
| | v2 | 1,784 | 3,087 |
| | v3 | 2,308 | 5,085 |
| | v4 | 1,308 | 4,348 |
| WN18RR | v1 | 19 | 3 |
| | v2 | 22 | 35 |
| | v3 | 23 | 19 |
| | v4 | 20 | 54 |

Table 4: Rules captured by $T_{\mathcal{M}}$

| Benchmark | | Total AnyBURL | Tree-like AnyBURL | Captured by $T_{\mathcal{M}}$ | Captured on $\mathcal{S}_I$ |
|---|---|---|---|---|---|
| FB15K-237 | v1 | 2812 | 252 | 72 | 1371 |
| | v2 | 2823 | 404 | 102 | 1048 |
| | v3 | 4805 | 490 | 118 | 1749 |
| | v4 | 3574 | 584 | 134 | 1046 |
| NELL-995 | v1 | 891 | 51 | 49 | 707 |
| | v2 | 1123 | 181 | 112 | 650 |
| | v3 | 1104 | 277 | 181 | 603 |
| | v4 | 841 | 187 | 108 | 606 |
| WN18RR | v1 | 397 | 15 | 11 | 30 |
| | v2 | 522 | 21 | 14 | 35 |
| | v3 | 424 | 21 | 21 | 48 |
| | v4 | 511 | 16 | 12 | 23 |

Table 5: Comparison of rule extraction with AnyBURL

baselines in this setting; however, this way of splitting the data gives our system an unfair advantage in a comparison, and hence we did not present the results for the baselines in Table 3.

**Rule Extraction.** For each benchmark, we used the algorithm in Appendix D to extract the set $\mathcal{P}$ of all non-redundant rules in program $\mathcal{P}_{\mathcal{M}}$ (c.f. Definition 9) with at most two body atoms. Table 4 shows the numbers of such rules learned on each benchmark. Since all rules of $\mathcal{P}$ are captured by $T_{\mathcal{M}}$, operator $T_{\mathcal{P}}$ approximates $T_{\mathcal{M}}$; in particular, $T_{\mathcal{P}}(D) \subseteq T_{\mathcal{M}}(D)$ for any dataset $D$. To measure the quality of the approximation, we applied $T_{\mathcal{P}}$ to the test dataset of each benchmark. We observed that precision remained unchanged, while recall decreased only slightly (1.6% in average). This shows that the generated "short" rules account for almost all predictions on the benchmarks.

By analysing the rules in $\mathcal{P}$, we noted that our transformation learned many rules describing sound inferences such as symmetry (e.g., $sibling(x, y) \leftarrow sibling(y, x)$ on FB15K-237), inverse relations (e.g., $capitalOfArea(x, y) \leftarrow areaHasCapital(y, x)$ on FB15K-237), and relationship subsumption (e.g., $athletePlayedForTeam(x, y) \leftarrow athleteLedSportsTeam(x, y)$ on NELL-995).

In addition, we generated rules using AnyBURL on each benchmark and checked how many of those are captured by our transformation;[2] Table 5 summarises our results. The first column provides the total number of rules generated by AnyBURL on each benchmark. The second column indicates how many of those rules were tree-like as per Definition 9. The third column shows how many rules from the second column are captured by our transformation per Definition 6. Finally, the fourth column shows the number of AnyBURL rules $r$ that are captured by $T_{\mathcal{M}}$ *on the specific dataset*—that is, such that $T_r(\mathcal{S}_I) \subseteq T_{\mathcal{M}}(\mathcal{S}_I)$. As one can see, a significant proportion of tree-like rules generated by AnyBURL are captured by $T_{\mathcal{M}}$. Additionally, a significant proportion of (not necessarily tree-shaped) rules generated by AnyBURL are captured by $T_{\mathcal{M}}$ on the specific dataset, which partially explains why many of the predictions by AnyBURL are also obtained by $T_{\mathcal{M}}$.

---

[2]We could not do this for DRUM since the version of the system available online cannot produce the rules.

## 5 RELATED WORK

*GNN-based approaches to KG completion* (Hamaguchi et al., 2017; Schlichtkrull et al., 2018; Xu et al., 2020; Teru et al., 2020; Zhang et al., 2020) are becoming increasingly popular as they are more generally applicable than earlier solutions based on graph embeddings (Rossi et al., 2021). Typically, the predictions made by these techniques cannot be explained symbolically.

*Rule mining* techniques for KGs can categorised in two groups. Systems in the first category learn a model on training data and provide ways to extract rules from it: DRUM and similar approaches (Yang et al., 2017; Sadeghian et al., 2019; Wang et al., 2020) use RNNs, while others use reinforcement learning (Xiong et al., 2017; Das et al., 2018), dynamic neural module networks (Rocktäschel & Riedel, 2017; Campero et al., 2018), or graph embeddings (Omran et al., 2018; Zhang et al., 2019). However, the formal relationship between the model and the rules extracted from it is unspecified in these approaches; hence, model predictions can differ from the result of applying the rules. Systems in the second category, such as AnyBURL, use training data to identify patterns of paths in the graph that are represented as rules (Galárraga et al., 2015; Meilicke et al., 2019; Ahmadi et al., 2020; Gu et al., 2020); hence, they do not involve training an ML model.

*Inductive Logic Programming (ILP)* generates rules given a dataset and examples of positive and negative inferences so that rule application yields all positive and no negative examples (Muggleton, 1991). ILP techniques cannot typically handle noisy examples (Muggleton, 1991; Cropper & Muggleton, 2014; Si et al., 2019; Raghothaman et al., 2020). Other recent ILP systems, such as $\partial$ILP (Evans & Grefenstette, 2018), achieve robustness to noise by interpreting the ILP task as a binary classification problem and providing a differentiable implementation of deduction. These approaches are similar to rule mining techniques, and they compare to our work analogously. Furthermore, they focus on learning rules from small datasets and struggle with large-scale KGs.

*Neuro-symbolic computation* focuses on integrating Logic with neural networks (d'Avila Garcez et al., 2002). Rule extraction methods have focused on identifying classes of rules for which the immediate consequence operator can be simulated by recurrent (Hölldobler et al., 1999), fibring (Bader et al., 2005), or feed-forward networks (Bader et al., 2007). Their embedding methods are, however, different from ours, as they encode groups of facts as numeric vector components and they can only extract variable-free rules from trained networks. Recently, Dong et al. (2019) presented a network architecture that simulates application of arbitrary function-free first-order rules to a dataset. This work, however, does not provide an algorithm extracting rules from a trained model.

Existing methods for *explaining the predictions of a GNN* focus on identifying parts of the graph in the embedding space that are most relevant to a given prediction (Ying et al., 2019; Luo et al., 2020; Lin et al., 2021). These techniques are largely independent from the specifics of the model used. In contrast, we focus on a specific type of GNN and provide a logical proof for each prediction.

GNNs were shown capable of expressing graph property tests such as isomorphism, existence of cliques, bipartiteness, and planarity (Xu et al., 2019; Morris et al., 2019; Garg et al., 2020). Moreover, first-order logic queries expressible by GNNs correspond to the description logic $\mathcal{ALCQ}$ (Barceló et al., 2020). Our work follows this line of research by relating GNNs and Datalog.

There has been work on neural learning of functions that are monotonic for the ordering on the real numbers You et al. (2017); Gupta et al. (2016); Wehenkel & Louppe (2019), and which rely on the use of non-negative matrices and monotonic activation functions. Our work, however concerns GNNs and the learning of monotonic functions for the ordering induced by the existence of homomorphisms between datasets, which is the notion of monotonicity in Logic and Data Management.

## 6 CONCLUSION AND FUTURE WORK

We presented a GNN-based transformation of datasets that mimics a round of application of Datalog rules. The predictions made by our transformation can be explained symbolically, and we have shown our approach to be practically feasible. We see many avenues for future work. On the theoretical side, we shall develop extensions that capture more complex rules (e.g., transitivity), as well as nonmonotonic extensions such as negation or aggregation. On the practical side, we shall establish links with the existing approaches to rule mining and ILP, thus allowing us to compare the performance of all of these heterogeneous approaches in a unified way.

# REFERENCES

Serge Abiteboul, Richard Hull, and Victor Vianu. *Foundations of Databases*. Addison-Wesley, Reading, MA, 1995.

Charu C. Aggarwal. *Recommender Systems - The Textbook*. Springer, 2016.

Naser Ahmadi, Viet-Phi Huynh, Venkata Vamsikrishna Meduri, Stefano Ortona, and Paolo Papotti. Mining expressive rules in knowledge graphs. *ACM J. Data Inf. Qual.*, 12(2):8:1–8:27, 2020.

Sebastian Bader, Artur S. d'Avila Garcez, and Pascal Hitzler. Computing First-Order Logic Programs by Fibring Artificial Neural Networks. In *FLAIRS*, pp. 314–319, 2005.

Sebastian Bader, Pascal Hitzler, Steffen Hölldobler, and Andreas Witzel. A Fully Connectionist Model Generator for Covered First-Order Logic Programs. In *IJCAI*, pp. 666–671, 2007.

Pablo Barceló, Egor V. Kostylev, Mikaël Monet, Jorge Pérez, Juan L. Reutter, and Juan Pablo Silva. The Logical Expressiveness of Graph Neural Networks. In *ICLR*. OpenReview.net, 2020.

Antoine Bordes, Nicolas Usunier, Alberto García-Durán, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. In Christopher J. C. Burges, Léon Bottou, Zoubin Ghahramani, and Kilian Q. Weinberger (eds.), *NeurIPS*, pp. 2787–2795, 2013.

Andres Campero, Aldo Pareja, Tim Klinger, Josh Tenenbaum, and Sebastian Riedel. Logical Rule Induction and Theory Learning Using Neural Theorem Proving. *CoRR*, abs/1809.02193, 2018.

Stefano Ceri, Georg Gottlob, and Letizia Tanca. What you always wanted to know about datalog (and never dared to ask). *IEEE Trans. Knowl. Data Eng.*, 1(1):146–166, 1989.

Andrew Cropper and Stephen H. Muggleton. Logical minimisation of meta-rules within meta-interpretive learning. In *ILP*, volume 9046 of *LNCS*, pp. 62–75. Springer, 2014.

Rajarshi Das, Shehzaad Dhuliawala, Manzil Zaheer, Luke Vilnis, Ishan Durugkar, Akshay Krishnamurthy, Alex Smola, and Andew McCallum. Go for a Walk and Arrive at the Answer: Reasoning Over Paths in Knowledge Bases using Reinforcement Learning. In *ICLR*. OpenReview.net, 2018.

Artur S. d'Avila Garcez, Krysia Broda, and Dov M. Gabbay. *Neural-symbolic Learning Systems— Foundations and Applications*. Springer-Verlag, London, 2002.

Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. Convolutional 2D knowledge graph embeddings. In Sheila A. McIlraith and Kilian Q. Weinberger (eds.), *AAAI*, pp. 1811–1818. AAAI Press, 2018.

Honghua Dong, Jiayuan Mao, Tian Lin, Chong Wang, Lihong Li, and Denny Zhou. Neural logic machines. In *ICLR*. OpenReview.net, 2019.

Richard Evans and Edward Grefenstette. Learning Explanatory Rules from Noisy Data. *JAIR*, 61: 1–64, 2018.

Luis Galárraga, Christina Teflioudi, Katja Hose, and Fabian M. Suchanek. Fast Rule Mining in Ontological Knowledge Bases with AMIE+. *VLDB J.*, 24(6):707–730, 2015.

V. K. Garg, S. Jegelka, and T. S. Jaakkola. Generalization and Representational Limits of Graph Neural Networks. In *ICML*, pp. 3419–3430, 2020.

Yulong Gu, Yu Guan, and Paolo Missier. Efficient Rule Learning with Template Saturation for Knowledge Graph Completion. *CoRR*, abs/2003.06071, 2020.

Maya R. Gupta, Andrew Cotter, Jan Pfeifer, Konstantin Voevodski, Kevin Robert Canini, Alexander Mangylov, Wojtek Moczydlowski, and Alexander Van Esbroeck. Monotonic calibrated interpolated look-up tables. *J. Mach. Learn. Res.*, 17:109:1–109:47, 2016.

Takuo Hamaguchi, Hidekazu Oiwa, Masashi Shimbo, and Yuji Matsumoto. Knowledge transfer for out-of-knowledge-base entities : A graph neural network approach. In *IJCAI*, pp. 1802–1808. AAAI Press, 2017.

William L. Hamilton, Rex Ying, and Jure Leskovec. Representation learning on graphs: Methods and applications. *IEEE Data Eng. Bull.*, 40(3):52–74, 2017.

Aidan Hogan, Eva Blomqvist, Michael Cochez, Claudia d'Amato, Gerard de Melo, Claudio Gutiérrez, Sabrina Kirrane, José Emilio Labra Gayo, Roberto Navigli, Sebastian Neumaier, Axel-Cyrille Ngonga Ngomo, Axel Polleres, Sabbir M. Rashid, Anisa Rula, Lukas Schmelzeisen, Juan F. Sequeda, Steffen Staab, and Antoine Zimmermann. Knowledge graphs. *ACM Comput. Surv.*, 54(4):71:1–71:37, 2021.

Steffen Hölldobler, Yvonne Kalinke, and Hans-Peter Störr. Approximating the Semantics of Logic Programs by Recurrent Neural Networks. *Appl. Intell.*, 11(1):45–58, 1999.

Wanyu Lin, Hao Lan, and Baochun Li. Generative causal explanations for graph neural networks. In *ICML*, volume 139, pp. 6666–6679, 2021.

Zhiyuan Liu and Jie Zhou. *Introduction to Graph Neural Networks*. Morgan and Claypool Publishers, 2020.

Dongsheng Luo, Wei Cheng, Dongkuan Xu, Wenchao Yu, Bo Zong, Haifeng Chen, and Xiang Zhang. Parameterized explainer for graph neural network. In *NeurIPS*, 2020.

Christian Meilicke, Melisachew Wudage Chekol, Daniel Ruffinelli, and Heiner Stuckenschmidt. Anytime bottom-up rule learning for knowledge graph completion. In Sarit Kraus (ed.), *IJCAI*, pp. 3137–3143, 2019.

C. Morris, M. Ritzert, M. Fey, W/ L. Hamilton, J. E. Lenssen, G. Rattan, and M. Grohe. Weisfeiler and Leman Go Neural: Higher-Order Graph Neural Networks. In *AAAI*, pp. 4602–4609, 2019.

Boris Motik, Yavor Nenov, Robert Piro, Ian Horrocks, and Dan Olteanu. Parallel materialisation of datalog programs in centralised, main-memory RDF systems. In *Proceedings of the Twenty-Eighth AAAI Conference on Artificial Intelligence*, pp. 129–137. AAAI Press, 2014.

Stephen Muggleton. Inductive Logic Programming. *New Gener. Comput.*, 8(4):295–318, 1991.

Pouya G. Omran, Kewen Wang, and Zhe Wang. Scalable Rule Learning via Learning Representation. In *IJCAI*, pp. 2149–2155, 2018.

Mukund Raghothaman, Jonathan Mendelson, David Zhao, Mayur Naik, and Bernhard Scholz. Provenance-guided synthesis of datalog programs. *Proc. ACM Program. Lang.*, 4(62):1–27, 2020.

Tim Rocktäschel and Sebastian Riedel. End-to-end differentiable proving. In *NeurIPS*, pp. 3788–3800, 2017.

Andrea Rossi, Denilson Barbosa, Donatella Firmani, Antonio Matinata, and Paolo Merialdo. Knowledge graph embedding for link prediction: A comparative analysis. *ACM Trans. Knowl. Discov. Data*, 15(2):14:1–14:49, 2021.

Ali Sadeghian, Mohammadreza Armandpour, Patrick Ding, and Daisy Zhe Wang. DRUM: End-To-End differentiable rule mining on knowledge graphs. In *NeurIPS*, pp. 15321–15331, 2019.

Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The Graph Neural Network Model. *IEEE TNNLS*, 20(1):61–80, 2009.

Michael Schlichtkrull, Thomas N. Kipf, Peter Bloem, Rianne Van Den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In *ESWC*, pp. 593–607, 2018.

Xujie Si, Mukund Raghothaman, Kihong Heo, and Mayur Naik. Synthesizing datalog programs using numerical relaxation. In *IJCAI*, pp. 6117–6124. ijcai.org, 2019.

Komal K. Teru, Etienne Denis, and Will Hamilton. Inductive relation prediction by subgraph reasoning. In *ICML*, volume 119 of *Proceedings of Machine Learning Research*, pp. 9448–9457. PMLR, 2020.

Rianne van den Berg, Thomas N. Kipf, and Max Welling. Graph convolutional matrix completion, 2017.

Pascal Vincent, Hugo Larochelle, Isabelle Lajoie, Yoshua Bengio, Pierre-Antoine Manzagol, and Léon Bottou. Stacked denoising autoencoders: Learning useful representations in a deep network with a local denoising criterion. *J. of Machine Learning Res.*, 11(12), 2010.

Hongwei Wang, Fuzheng Zhang, Jialin Wang, Miao Zhao, Wenjie Li, Xing Xie, and Minyi Guo. Ripplenet: Propagating user preferences on the knowledge graph for recommender systems. In *CIKM*, pp. 417–426, 2018.

Hongwei Wang, Miao Zhao, Xing Xie, Wenjie Li, and Minyi Guo. Knowledge graph convolutional networks for recommender systems. In *WWW*, pp. 3307–3313, 2019a.

Peifeng Wang, Jialong Han, Chenliang Li, and Rong Pan. Logic attention based neighborhood aggregation for inductive knowledge graph embedding. In *AAAI*, pp. 7152–7159, 2019b.

Po-Wei Wang, Daria Stepanova, Csaba Domokos, and J. Zico Kolter. Differentiable learning of numerical rules in knowledge graphs. In *ICLR*. OpenReview.net, 2020.

Antoine Wehenkel and Gilles Louppe. Unconstrained monotonic neural networks. *CoRR*, abs/1908.05164, 2019. URL http://arxiv.org/abs/1908.05164.

Wenhan Xiong, Thien Hoang, and William Yang Wang. Deeppath: A reinforcement learning method for knowledge graph reasoning. In *EMNLP*, pp. 564–573. Association for Computational Linguistics, 2017.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How Powerful are Graph Neural Networks? In *ICLR*, 2019.

Xiaoran Xu, Wei Feng, Yunsheng Jiang, Xiaohui Xie, Zhiqing Sun, and Zhi-Hong Deng. Dynamically Pruned Message Passing Networks for Large-scale Knowledge Graph Reasoning. In *ICLR*. OpenReview.net, 2020.

Fan Yang, Zhilin Yang, and William W. Cohen. Differentiable Learning of Logical Rules for Knowledge Base Reasoning. In *NeurIPS*, pp. 2319–2328, 2017.

Zhitao Ying, Dylan Bourgeois, Jiaxuan You, Marinka Zitnik, and Jure Leskovec. GNNExplainer: Generating explanations for graph neural networks. In *NeurIPS*, pp. 9240–9251, 2019.

Seungil You, David Ding, Kevin Robert Canini, Jan Pfeifer, and Maya R. Gupta. Deep lattice networks and partial monotonic functions. In *NeurIPS*, pp. 2981–2989, 2017.

Fuzheng Zhang, Nicholas Jing Yuan, Defu Lian, Xing Xie, and Wei-Ying Ma. Collaborative knowledge base embedding for recommender systems. In *SIGKDD*, pp. 353–362, 2016.

Wen Zhang, Bibek Paudel, Liang Wang, Jiaoyan Chen, Hai Zhu, Wei Zhang, Abraham Bernstein, and Huajun Chen. Iteratively Learning Embeddings and Rules for Knowledge Graph Reasoning. In *WWW*, pp. 2366–2377, 2019.

Yuyu Zhang, Xinshi Chen, Yuan Yang, Arun Ramamurthy, Bo Li, Yuan Qi, and Le Song. Efficient probabilistic logic reasoning with graph neural networks. In *ICLR*. OpenReview.net, 2020.

## A    PROOF OF PROPOSITION 7

**Proposition 7.** *Let $T$ be an operator on datasets, let $r$ be a constant-free rule of form* (2)*, let $\mu$ be a substitution that maps each variable of $r$ to a distinct constant, and let $D_r = \{B_1\mu, \dots, B_m\mu\}$. If $T$ is monotonic under homomorphisms and $H\mu \in T(D_r)$, then $T$ captures $r$.*

*Proof.* Consider $T$, $r$, $D_r$, and $\mu$ that satisfy the prerequisites of the proposition. Moreover, consider an arbitrary dataset $D$ and an arbitrary fact $\alpha \in T_r(D)$; we show that $\alpha \in T(D)$. By the definition of operator $T_r$, there exists a substitution $\nu$ such that $\{B_1\nu, \dots, B_m\nu\} \subseteq D$ and $H\nu = \alpha$. Now let $h$ be the mapping of constants to constants such that $h(x\mu) = x\nu$ for each variable $x$ in occurring in $r$. This definition of $h$ is correct since $\mu$ maps each variable in $r$ to a distinct constant. Also, rule $r$ is constant-free, so $h(D_r) = h(\{B_1\mu, \dots, B_m\mu\}) = \{B_1\nu, \dots, B_m\nu\} \subseteq D$ holds; moreover, each constant in $D_r$ is obtained by instantiating a variable of $r$, so $h$ is defined on all of $\mathsf{cn}(D_r)$. In other words, $h$ is a homomorphism from $D_r$ to $D$. Since $T$ is monotonic under homomorphisms by the assumption of the proposition, $h$ is also a homomorphism from $T(D_r)$ to $T(D)$. Moreover, $H\mu \in T(D_r)$ holds by our assumption, so the definition of homomorphisms ensures $h(H\mu) \in T(D)$. Finally, atom $H$ is constant-free, which together with the definition of $h$ ensures $h(H\mu) = H\nu$. Thus, we have $H\nu \in T(D)$, as required.                                                 $\square$

## B    PROOF OF THEOREM 8

We prove Theorem 8 in two steps. First, we first introduce in Definition B1 a notion of homomorphisms on $(\mathsf{Col}, \delta)$-graphs that is analogous to the notion of homomorphisms on datasets. Then, in Lemma B2 we show that the transformation of $(\mathsf{Col}, \delta)$-graphs by an MGNN preserves such homomorphisms. Theorem 8 finally combines this result with our encoding and decoding steps. To formalise these results, we extend the order $\leq$ on real numbers to a partial order on vectors so that $\mathbf{a}_1 \leq \mathbf{a}_2$ holds whenever $(\mathbf{a}_1)_i \leq (\mathbf{a}_2)_i$ holds for each position $i$.

**Definition B1.** *A* label-respecting homomorphism *from a $(\mathsf{Col}, \delta)$-graph $\langle V, \{E_c\}_{c \in \mathsf{Col}}, \lambda \rangle$ to a $(\mathsf{Col}, \delta)$-graph $\langle V', \{E'_c\}_{c \in \mathsf{Col}}, \lambda' \rangle$ is a mapping $h : V \to V'$ such that $\lambda(v) \leq \lambda'(h(v))$ for each vertex $v \in V$, and, for each colour $c \in \mathsf{Col}$ and each edge in $E_c$ between vertices $v$ and $w$, vertices $h(v)$ and $h(w)$ are connected by an edge in $E'_c$.*

**Lemma B2.** *For each $(\mathsf{Col}, \delta)$-MGNN $\mathcal{M}$ and all $(\mathsf{Col}, \delta)$-graphs $G$ and $G'$, each label-respecting homomorphism $h$ from $G$ to $G'$ is also a label-respecting homomorphism from $\mathcal{M}(G)$ to $\mathcal{M}(G')$.*

*Proof.* Consider a $(\mathsf{Col}, \delta)$-MGNN $\mathcal{M}$ with components as specified in Definition 3, $(\mathsf{Col}, \delta)$-graphs $G = \langle V, \{E_c\}_{c \in \mathsf{Col}}, \lambda \rangle$ and $G' = \langle V', \{E'_c\}_{c \in \mathsf{Col}}, \lambda' \rangle$, and a label-respecting homomorphism $h$ from $G$ to $G'$. Since $\mathcal{M}(G)$ and $\mathcal{M}(G')$ have the same edges as $G$ and $G'$, respectively, $h$ satisfies the first condition of a label-preserving homomorphism from $\mathcal{M}(G)$ to $\mathcal{M}(G')$. We show that $h$ also satisfies the second condition. To this end, let $\lambda^0, \dots, \lambda^L$ and $\lambda'^0, \dots, \lambda'^L$ be the sequences of vertex labelling functions used in the computation of $\mathcal{M}(G)$ and $\mathcal{M}(G')$, respectively. We next show by induction on $0 \leq \ell \leq L$ that $\lambda^\ell(v) \leq \lambda'^\ell(h(v))$ holds for each vertex $v \in V_1$; since classification function $\mathsf{cls}$ is monotonically increasing, this will imply that $\mathsf{cls}(\lambda^L(v)) \leq \mathsf{cls}(\lambda'^L(h(v)))$ holds for each vertex $v \in V_1$ as well, which proves our claim.

The base case for $\ell = 0$ holds immediately since $\lambda^0 = \lambda$ and $\lambda'^0 = \lambda'$. For the inductive step, we assume that, for some $\ell - 1$, we have $\lambda^{\ell-1}(v) \leq \lambda'^{\ell-1}(h(v))$ for each $v \in V_1$, and we show that $\lambda^\ell(v) \leq \lambda'^\ell(h(v))$ also holds for each $v \in V_1$. To this end, consider arbitrary $i$ between 1 and the dimension of $\mathbf{b}^\ell$. By Definition 3, the $i$-th components of $\lambda^\ell(v)$ and $\lambda'^\ell(h(v))$ are equal to $\sigma(x_1)$ and $\sigma(x_2)$, where $x_1$ and $x_2$ are as in (3) and (4) for $(\mathbf{A}^\ell)_i$ and $(\mathbf{B}^\ell_c)_i$ the $i$-th rows of $\mathbf{A}^\ell$ and $\mathbf{B}^\ell_c$, respectively:

$$x_1 = (\mathbf{A}^\ell)_i\, \lambda^{\ell-1}(v) \quad + \sum_{c \in \mathsf{Col}} (\mathbf{B}^\ell_c)_i \max\{\lambda^{\ell-1}(w) \mid w \in N_c(v)\} \quad + (\mathbf{b}^\ell)_i, \tag{3}$$

$$x_2 = (\mathbf{A}^\ell)_i\, \lambda'^{\ell-1}(h(v)) + \sum_{c \in \mathsf{Col}} (\mathbf{B}^\ell_c)_i \max\{\lambda'^{\ell-1}(u) \mid u \in N_c(h(v))\} + (\mathbf{b}^\ell)_i. \tag{4}$$

By the inductive hypothesis, we have $\lambda^{\ell-1}(v) \leq \lambda'^{\ell-1}(h(v))$; moreover, all numbers in $\mathbf{A}^\ell$ are nonnegative, so we clearly have $(\mathbf{A}^\ell)_i\lambda^{\ell-1}(v) \leq (\mathbf{A}^\ell)_i\lambda'^{\ell-1}(h(v))$. In addition, mapping $h$

satisfies the first property of label-preserving homomorphisms so, for each colour $c \in \mathsf{Col}$ and each $w \in N_c(v)$, we have $h(w) \in N_c(h(v))$; moreover, by the inductive hypothesis, we have $\lambda^{\ell-1}(w) \leq \lambda'^{\ell-1}(h(w))$. By combining these two observations, we have

$$\max\{\lambda^{\ell-1}(w) \mid w \in N_c(v)\} \leq \max\{\lambda'^{\ell-1}(u) \mid u \in N_c(h(v))\},$$

which, together with the fact that all numbers in $(\mathbf{B}_c^\ell)_i$ are nonnegative, implies

$$(\mathbf{B}_c^\ell)_i \max\{\lambda^{\ell-1}(w) \mid w \in N_c(v)\} \leq (\mathbf{B}_c^\ell)_i \max\{\lambda'^{\ell-1}(u) \mid u \in N_c(h(v))\}.$$

Consequently, we have $x_1 \leq x_2$. Finally, activation function $\sigma$ is monotonically increasing, so $\sigma(x_1) \leq \sigma(x_2)$ holds, which completes our proof of the inductive step. $\qquad\square$

**Theorem 8.** *For each* $(\mathsf{Col}, \delta)$*-MGNN* $\mathcal{M}$*, mapping* $T_\mathcal{M}$ *is monotonic under homomorphisms.*

*Proof.* Consider an arbitrary $(\mathsf{Col}, \delta)$-MGNN $\mathcal{M}$, arbitrary datasets $D$ and $D'$, and an arbitrary homomorphism $h$ from $D$ to $D'$; thus, $h(D) \subseteq D'$ holds. Now let $G_D$ and $G_{D'}$ be $(\mathsf{Col}, \delta)$-graphs obtained by transforming $D$ and $D'$ as in Definition 2. Moreover, let $g$ be the mapping from the vertices of $G_1$ to the vertices of $G_2$ defined as follows:

- $g(v_a) = v_{h(a)}$ for each vertex $v_a$ of $G_1$; and
- $g(v_{a,b}) = v_{h(a),h(b)}$ for each vertex $v_{a,b}$ of $G_1$.

It is straightforward to see that $g$ is a label-respecting homomorphism from $G_D$ to $G_{D'}$. By Lemma B2, mapping $g$ is also a label-respecting homomorphism from $\mathcal{M}(G_D)$ to $\mathcal{M}(G_{D'})$. Thus, however, implies that $h$ is also a homomorphism from $T(D)$ to $T(D')$, as required. $\qquad\square$

## C  PROOF OF THEOREM 10

**Theorem 10.** *For each* $(\mathsf{Col}, \delta)$*-MGNN* $\mathcal{M}$ *and each dataset* $D$*, we have* $T_\mathcal{M}(D) = T_{\mathcal{P}_\mathcal{M}}(D)$*.*

*Proof.* Consider arbitrary $\mathcal{M}$, $\mathcal{P}_\mathcal{M}$, and $D$ as stated in the claim. Let $L$ be the number of layers of $\mathcal{M}$, and let $k$ be the dimension of $\mathcal{M}$. Since operator $T_{\mathcal{P}_\mathcal{M}}$ captures each rule in $\mathcal{P}_\mathcal{M}$ by definition, we clearly have $T_{\mathcal{P}_\mathcal{M}}(D) \subseteq T_\mathcal{M}(D)$. For the converse, consider an arbitrary fact $\alpha \in T_\mathcal{M}(D)$. We next construct a rule $r$ for which we prove $r \in \mathcal{P}_\mathcal{M}$ and $\alpha \in T_r(D)$.

Let $G_D$ be the $(\mathsf{Col}, \delta)$-graph obtained from $D$ by the transformation in Definition 2, and let $V_D$ be the set of vertices of $G_D$. For each $\ell \in \{0, \ldots, L\}$, let $\mathbf{v}^\ell$ be the vector labelling each $v \in V_D$ in the computation of $\mathcal{M}(G_D)$. Moreover, let $\mu$ be a substitution that maps each variable to a distinct constant. We next construct an atom $H$, a conjunction $C$, a substitution $\nu$ from the variables in $C$ to $\mathsf{cn}(D)$, a set $U$ of fresh vertices (i.e., vertices not occurring in $G_D$) of the form $u_d$ and $u_{d,e}$ for $d$ and $e$ constants from the image of $\mu$, and mappings $\xi : U \to V_D$ and $M_c : U \to 2^{V_D}$ for each $c \in \mathsf{Col}$. We also assign each vertex in $U$ to a level between $0$ and $L$, and we identify a single vertex from $U$ as the *root* vertex. In the rest of this proof, we use letters $a$ and $b$ for the constants in $D$, letters $d$ and $e$ for the constants in the image of $\mu$, possibly indexed letters $v$, $w$, and $s$ for the vertices in $V_D$, and possibly indexed letters $u$ and $t$ for the vertices in $U$. Our construction is by induction from level $L$ down to level $1$, and we prove in parallel the following properties:

- P1. for each vertex of the form $u_d \in U$, for $x$ the variable such that $\mu(x) = d$, and for $a = \nu(x)$, we have $\xi(u_d) = v_a$;

- P2. for each vertex of the form $u_{d,e} \in U$, for $x$ and $y$ variables such that $\mu(x) = d$ and $\mu(y) = e$, and for $a = \nu(x)$ and $b = \nu(y)$, we have $\xi(u_{d,e}) = v_{a,b}$;

- P3. conjunction $C$ satisfies $\nu(C) \subseteq D$; and

- P4. if $H$ is of the form $A(x)$, conjunction $C$ is $(3k, L)$-tree-like for $x$; otherwise it is of the form $C_x \wedge B_{x,y} \wedge C_y$, where $C_x$ and $C_y$ are $(3k, L)$-tree-like conjunctions for $x$ and $y$, respectively, and $B_{x,y}$ is a nonempty conjunction of atoms of the form $S(x, y)$ or $S(y, x)$.

We initialise $C$ as the empty conjunction, and we set $\nu$, $\xi$, and each $M_c$ for $c \in \mathsf{Col}$ as the empty mappings. For the induction base, we consider the form of the atom $\alpha \in T_\mathcal{M}(D)$ and proceed as follows; the base case also identifies the root vertex. Properties P1–P4 clearly hold after these steps.

- If $\alpha$ is of the form $A(a)$, then $V_D$ contains vertex $v_a$. We introduce a fresh variable $x$, and we let $d$ be the constant such that $d = \mu(x)$. We define $\nu(x) = a$; we define $H = A(x)$; we introduce vertex $u_d$ of level $L$; we define $\xi(u_d) = v_a$; and we make $u_d$ the root vertex. Finally, we extend $C$ with atom $B(x)$ for each $B(a) \in D$. Note that $C$ can be empty if $D$ does not contain a fact such as $B(a)$. However, $v_a \in V_D$ implies that constant $a$ must occur in $D$ in a fact of the form $S(a, b)$ or $S(b, a)$. Thus, $N_c(v_a) \neq \emptyset$ for $c \in \{c_1, c_2, c_4\}$. Since $L \geq 1$, vertex $u_d$ is processed in the inductive step below, which will extend $C$ with an atom that contains variable $x$.

- If $\alpha$ is of the form $R(a, b)$, then $V_D$ contains vertices $v_{a,b}$ and $v_{b,a}$; due to the latter, $D$ contains at least one fact of the form $S(a, b)$ or $S(b, a)$, and so $V_D$ contains vertices $v_a$ and $v_b$. We introduce fresh variables $x$ and $y$, and we let $d$ and $e$ be constants such that $d = \mu(x)$ and $e = \mu(y)$. We define $\nu(x) = a$ and $\nu(y) = b$; we define $H = R(x, y)$; we introduce vertices $u_d$, $u_e$, $u_{d,e}$, and $u_{e,d}$ of level $L$; we define $\xi(u_d) = v_a$, $\xi(u_e) = v_b$, $\xi(u_{d,e}) = v_{a,b}$, and $\xi(u_{e,d}) = v_{b,a}$; and we make $u_{d,e}$ the root vertex. Moreover, we extend $C$ with an atom $S(x, y)$ for each $S(a, b) \in D$, an atom $S(y, x)$ for each $S(b, a) \in D$, an atom $B(x)$ for each $B(a) \in D$, and an atom $B(y)$ for each $B(b) \in D$; note that, $C$ cannot empty after this step. Finally, we define $M_c(u) = N_c(\xi(u))$ for each $u \in \{u_{d,e}, u_{e,d}\}$ and colour $c \in \mathsf{Col}$; note that $M_{c_1}(u)$, $M_{c_2}(u)$, and $M_{c_3}(u)$ are all singletons, and $M_{c_4}(u) = \emptyset$.

Next, we consider each level $\ell$ with $1 \leq \ell \leq L$ that has already been processed, and we consider each vertex of the form $u_d$ of level $\ell$. Let $x$ be the variable such that $\mu(x) = d$, and let $a = \nu(x)$; property P1 ensures $\xi(u_d) = v_a$. For each colour $c \in \{c_1, c_2, c_4\}$, we choose a smallest set $M_c(u_d) \subseteq N_c(v_a)$ such that, for each $\ell' \in \{0, \ldots, \ell - 1\}$ and each $i \in \{1, \ldots, k\}$, there exists a vertex $w \in M_c(u_d)$ satisfying

$$(\mathbf{w}^{\ell'})_i = \max\{(\mathbf{s}^{\ell'})_i \mid s \in N_c(v_a)\}. \tag{5}$$

Note that set $M_c(u_d)$ may not be unique, but any set satisfying (5) can be selected. There are at most $k$ distinct values of $(\mathbf{w}^{\ell'})_i$ for each $\ell'$, so set $M_c(u_d)$ contains at most $k\ell$ elements. We also define $M_{c_3}(u_d) = \emptyset$. We now consider each vertex $v \in M_{c_1}(u_d) \cup M_{c_2}(u_d) \cup M_{c_4}(u_d)$. By Definition 2, such $v$ is of the form $v_{a,b}$, $v_{b,a}$, or $v_b$ for $b \in \mathsf{cn}(D)$, depending on the set from which $v$ is drawn. Set $V_D$ clearly also contains vertices $v_{b,a}$ and $v_b$ if $v \in M_{c_1}(u_d)$, and vertices $v_{a,b}$ and $v_b$ if $v \in M_{c_2}(u_d)$. Moreover, if $v \in M_{c_4}(u_d)$, then $V_D$ clearly contains $v_b$, and $M_{c_4}(u_d) \subseteq N_{c_4}(v_a)$ ensures that $D$ contains a fact of the form $S(a, b)$ or $S(b, a)$; thus, $V_D$ also contains $v_{a,b}$ and $v_{b,a}$. We introduce a fresh variable $y$, and we let $e$ be the constant such that $e = \mu(y)$. We define $\nu(y) = b$; we introduce vertices $u_e$, $u_{d,e}$, and $u_{e,d}$ of level $\ell - 1$; and we define $\xi(u_e) = v_b$, $\xi(u_{d,e}) = v_{a,b}$, and $\xi(u_{e,d}) = v_{b,a}$. Moreover, we extend $C$ with an atom $S(x, y)$ for each $S(a, b) \in D$, an atom $S(y, x)$ for each $S(b, a) \in D$, and an atom $B(y)$ for each $B(b) \in D$. Finally, we define $M_c(u) = N_c(\xi(u))$ for each $u \in \{u_{d,e}, u_{e,d}\}$ and colour $c \in \mathsf{Col}$; note that $M_{c_1}(u)$, $M_{c_2}(u)$, and $M_{c_3}(u)$ are all singletons, and $M_{c_4}(u) = \emptyset$. Since each $M_c(u_d)$ with $c \in \{c_1, c_2, c_4\}$ contains at most $k\ell$ vertices and we consider three colours, this step introduces at most $3k\ell$ fresh variables. Moreover, note that each fresh variable $y$ occurs in $C$ in an atom of the form $S(x, y)$ or $S(y, x)$. Finally, it should be clear that P1–P4 hold after level $\ell$ is processed.

This completes our inductive construction. At this point, either $H = A(x)$ and $C$ is a nonempty $(3k, L)$-tree-like conjunction for $x$, or $H = R(x, y)$ and $C = C_x \wedge B_{x,y} \wedge C_y$ where $C_x$ and $C_y$ are $(3k, L)$-tree-like conjunctions for $x$ and $y$, respectively, and $B_{x,y}$ is a nonempty conjunction of atoms of the form $S(x, y)$ or $S(y, x)$. Thus, rule $H \leftarrow C$ is of the form $A(x) \leftarrow C_x$ or $R(x, y) \leftarrow C_x \wedge B_{x,y} \wedge C_y$. To complete the proof, we next show this rule is captured by $T_\mathcal{M}$. Then, Definition 9 ensures ensures $H \leftarrow C \in \mathcal{P}_\mathcal{M}$; together with $H\nu = \alpha$ and $\nu(C) \subseteq D$, we have $\alpha \in T_{\mathcal{P}_\mathcal{M}}(D)$, which proves our claim.

We use Proposition 7 to show that $H \leftarrow C$ is captured by $T_\mathcal{M}$. To this end, let $D_C = \{\alpha\mu \mid \alpha \in C\}$, and let $G_{D_C}$ be the $(\mathsf{Col}, \delta)$-graph constructed using vertices in $U$ obtained by applying the encoding from Definition 2 to dataset $D_C$. Finally, let $\mathbf{u}^\ell$ be the labelling associated with each vertex $u \in U$ in the computation of $\mathcal{M}(G_{D_C})$. The construction of $C$ clearly ensures the following two properties for each colour $c \in \mathsf{Col}$ and each vertex $u \in U$:

R1. for each vertex $v \in M_c(u)$, there exists a vertex $t \in N_c(u)$ such that $\xi(t) = v$; and

R2. for each vertex $t \in N_c(u)$ in graph $G_{D_C}$, we have $\xi(t) \in N_c(\xi(u))$.

We now show by the induction on $\ell$ that, for each $0 \leq \ell \leq L$ and each vertex $u \in U$ whose level is at least $\ell$, we have $\mathbf{u}^\ell = \mathbf{v}^\ell$ for $v = \xi(u)$. For the base case $\ell = 0$, we have the following possibilities.

- Assume $u$ is of the form $u_d$. Let $x$ be the variable such that $d = \mu(x)$, and let $a = \nu(x)$. Property P1 ensures $\xi(u_d) = v_a$, and the construction of $C$ ensures $B(x) \in C$ if and only if $B(a) \in D$; thus, $\mathbf{u}_d^0 = \mathbf{v}_a^0$ holds.
- Assume $u$ is of the form $u_{d,e}$. Let $x$ and $y$ be variables such that $\mu(x) = d$ and $\mu(y) = e$, and let $a = \nu(x)$ and $b = \nu(y)$. Property P2 ensures $\xi(u_{d,e}) = v_{a,b}$, and the construction of $C$ ensures $S(x,y) \in C$ if and only if $S(a,b) \in D$; thus, $\mathbf{u}_{d,e}^0 = \mathbf{v}_{a,b}^0$ holds.

For the induction step, assume that the property holds for some $\ell - 1$, and consider an arbitrary vertex $u \in U$ whose level is at least $\ell$. Let $v = \xi(u)$. The induction assumption ensures $\mathbf{u}^{\ell-1} = \mathbf{v}^{\ell-1}$. Also, for each colour $c \in \mathsf{Col}$, our construction ensures that each vertex $t \in N_c(u)$ is of level at least $\ell - 1$, so the induction assumption ensures $\mathbf{t}^{\ell-1} = \mathbf{w}^{\ell-1}$ for $w = \xi(t)$. Finally, property R2 ensures that each $\mathbf{t}^{\ell-1}$ used to compute $\mathbf{u}^\ell$ is considered when computing $\mathbf{v}^\ell$, and property R1 ensures that the maximal values of $\mathbf{t}^{\ell-1}$ are also present in the computation of $\mathbf{u}^\ell$. Thus, $\mathbf{u}^\ell = \mathbf{v}^\ell$ holds.

To complete the proof, let $u$ be the root vertex, and let $v = \xi(u)$. The above property ensures $\mathbf{u}^L = \mathbf{v}^L$, and so $\mathsf{cls}(\mathbf{u}^L) = \mathsf{cls}(\mathbf{v}^L)$ as well. Thus, we have $\mu(H) \in T_{\mathcal{M}}(D_C)$, so Proposition 7 allows us to conclude that rule $H \leftarrow C$ is captured by $T_{\mathcal{M}}$. $\qquad\square$

Please note that given a $(\mathsf{Col}, \delta)$-MGNN $\mathcal{M}$, a dataset $D$, and a fact $\alpha \in T_{\mathcal{M}}(D)$, the proof of Theorem 10 shows how to identify a rule $r \in \mathcal{P}_{\mathcal{M}}$ such that $\alpha \in T_r(D)$. A user interested in understanding why $T_{\mathcal{M}}$ derived $\alpha$ from $D$ can apply this procedure to extract a rule $r$ that explains why $\alpha$ was derived. Furthermore, a user can then search for shorter explanations by considering rules that subsume $r$ and checking whether they are still captured by $T_{\mathcal{M}}$ (using Proposition 7), and whether they still derive $\alpha$ from $D$.

## D  OPTIMISED RULE EXTRACTION ALGORITHM

In this section we describe the rule extraction algorithm that we have implemented and used to obtain the results in in Table 4 from Section 4. The pseudocode for the algorithm is shown in Algorithm 1.

Our algorithm takes as input a trained model $\mathcal{M}$ and a number $m$ and generates as output a list of $(3k, L)$-tree-like rules captured by $T_{\mathcal{M}}$ with at most $m$ atoms in the body, with $k$ and $L$ the dimension and number of layers of $\mathcal{M}$ respectively. The algorithm relies on rule subsumption checks to ensure that redundant rules (i.e., logically implied by another rule) are not included in the output.

The algorithm starts by initialising an empty mapping $head\_to\_bodies$ in Line 1. This mapping will store pairs of the form $(S(x,y), \{C_1, C_2, \ldots, C_n\})$, where each $S(x,y) \leftarrow C_i$ is a $(3k, L)$-tree-like rule captured by $T_{\mathcal{M}}$ with no more than $m$ body atoms. In each iteration $i$ of the loop in Lines 2–15, the algorithm will generate rules with exactly $i$ atoms in the body. To this end, the algorithm iterates over all ordered combinations of predicates with repetition of length $i$, which are generated by the auxiliary function COMBINATIONS($i$). Then, in Line 4, given the list of predicates $pred\_list$, the algorithm iterates over all conjunctions (up to variable renaming) that can be obtained by transforming each predicate in $pred\_list$ into an atom, using a number of variables no greater than the size of $pred\_list$. For example, if $pred\_list$ is $[A, R]$, where $A$ is unary and $R$ is binary, then BODIES($pred\_list$) is

$$\big(A(x) \wedge R(x,x),\ A(x) \wedge R(x,y),\ A(x) \wedge R(y,x),\ A(x) \wedge R(y,y)\big)$$

Lines 5 and 6 discard each conjunction that is not $(3k, L)$-tree-like, to avoid testing rules that do not have such form. Lines 7-9 ground the conjunction $body$, apply $T_{\mathcal{M}}$ to the result, and lift the resulting dataset back into a set of non-ground atoms. In particular, ENCODE($body$) grounds $body$ by mapping each variable to a different constant, and then encodes the result into a $(\mathsf{Col}, \delta)$-labelled-graph as described in Section 2. Function DECODE($output\_graph$) performs the reverse operation,

---

**Algorithm 1** Rule extraction algorithm

**Input:**  $m$ : natural number (max. num. of atoms desired in the body of an extracted rule)
$\mathcal{M}$ : MGNN model (from where we extract rules)

1: $head\_to\_bodies := \emptyset$
2: **for** $i \leq m$ **do**
3:     **for** $pred\_list$ in COMBINATIONS($i$) **do**
4:         **for** $body$ in BODIES($pred\_list$) **do**
5:             **if not** TREELIKE($body$) **then**
6:                 **next**;
7:             $input\_graph \leftarrow$ ENCODE($body$)
8:             $output\_graph \leftarrow \mathcal{M}(input\_graph)$
9:             $heads \leftarrow$ DECODE($output\_graph$)
10:             **for** $head$ in $heads$ **do**
11:                 $new\_head, new\_body \leftarrow$ NORMALISE($head, body$)
12:                 **for** $prev\_body$ in $head\_to\_bodies(new\_head)$ **do**
13:                     **if** SUBSUMES($prev\_body, new\_body$) **then**
14:                         **break**;
15:                 $head\_to\_bodies(new\_head)$.add($new\_body$)
16: $extracted\_rules := [\,]$
17: **for** $(head, bodies)$ in $head\_to\_bodies$ **do**
18:     **for** $body$ in $bodies$ **do**
19:         $extracted\_rules$.append($head \leftarrow body$)
    **return** $extracted\_rules$

---

and the result is a set $heads$ of non-ground atoms, where each set element $head$ is such that $T_{\mathcal{M}}$ captures $head \leftarrow body$.

In Line 10, the algorithm iterates over each $head$ in $heads$. Line 11 rewrites the candidate rule $head \leftarrow body$ to ensure that heads of extracted rules always use variables $x$ and $y$ in this order, and it makes the corresponding substitutions in the body of the candidate rule. The result is rule $new\_head \leftarrow new\_body$. Lines 12 and 14 check whether $new\_head \leftarrow new\_body$ is subsumed by any rule previously stored in $head\_to\_bodies$. If it is not, then Line 15 adds rule $new\_head \leftarrow new\_body$ to $head\_to\_bodies$. Specifically, conjunction $new\_body$ is added to the set $head\_to\_bodies(new\_head)$. Finally, Lines 16 to 19 process the mapping $head\_to\_bodies$ and output all rules encoded in it.

Algorithm 1 satisfies the following property, which ensures its correctness.

**Proposition D1.** *Let* EXTRACT($\mathcal{M}, m$) *be the set of rules generated by Algorithm 1 for a* $(\mathsf{Col}, \delta)$-*MGNN* $\mathcal{M}$, *of dimension* $k$ *and* $L$ *layers, and a number* $m \in \mathbb{N}$. *Then:*

1. *For every* $r \in$ EXTRACT($\mathcal{M}, m$), $r$ *is a* $(3k, L)$-*tree-like rule* $r$ *captured by* $T_{\mathcal{M}}$ *with no more than* $m$ *atoms in the body.*

2. *For every* $(3k, L)$-*tree-like rule* $r$ *captured by* $T_{\mathcal{M}}$ *with no more than* $m$ *atoms in the body, there exists a rule in* EXTRACT($\mathcal{M}, m$) *that subsumes* $r$ *(up to variable renaming).*

*Proof.* Item 1 is a direct consequence of Proposition 7 and the fact that Algorithm 1 only evaluates $(3k, L)$-tree-like rules with at most $m$ atoms in the body. To see that Item 2 holds, one can straightforwardly verify that if $r$ is a $(3k, L)$-tree-like rule with at most $m$ atoms in the body, then Lines 2-9 of Algorithm 1 check whether this rule is captured by $T_{\mathcal{M}}$; if so, Lines 10-15 ensure that $r$ is either in the output of the algorithm, or the output contains a rule that subsumes it. □

| Benchmark | | Precision | Recall | Accuracy | F1 Score |
|---|---|---|---|---|---|
| FB15K-237 | v1 | 98.5 | 32.7 | 66.1 | 49.1 |
| | v2 | 100.0 | 38.3 | 69.1 | 55.4 |
| | v3 | 100.0 | 33.1 | 66.5 | 49.7 |
| | v4 | 99.6 | 32.7 | 66.3 | 49.3 |
| NELL-995 | v1 | 96.4 | 80.0 | 88.5 | 87.4 |
| | v2 | 100.0 | 45.2 | 72.6 | 62.2 |
| | v3 | 100.0 | 51.1 | 75.5 | 67.6 |
| | v4 | 99.7 | 53.9 | 76.9 | 70.0 |
| WN18RR | v1 | 100.0 | 61.7 | 80.9 | 76.3 |
| | v2 | 100.0 | 60.3 | 80.2 | 75.2 |
| | v3 | 100.0 | 27.9 | 64.0 | 43.7 |
| | v4 | 100.0 | 57.6 | 78.8 | 73.1 |

Table 6: Evaluation of the programs extracted using Algorithm 1 with $m = 2$.

In Section 4, we used Algorithm 1 with $m = 2$ to extract, for each benchmark, all the rules from the corresponding $\mathcal{P}_{\mathcal{M}}$ that have at most two atoms in the body and are not subsumed by another rule in the program. Table 6 shows the classification metrics obtained by using the extracted program to classify the positive and negative examples in the testing dataset of each benchmark.