CoMNet: Cortical Modules Are Powerful

Abstract

Existing CNN architectures may achieve efficiency in either one or two dimensions: FLOPs, depth, accuracy, representation power, latency but not in all. In this work, we present a pragmatically designed novel CNN architecture "CoMNet" which offers multi-dimensional efficiency at once such as: simple yet accurate, lower latency and FLOPs, high representation power in limited parameters, low memory consumption, negligible branching, smaller depths, and only a few design hyperparameters. The key to achieve the multi-dimensional efficiency is our use of biological underpinnings into CoMNet which is primarily the organization of cortical modules in the visual cortex. To realize CoMNet, a few concepts from well understood CNN designs are directly inherited such as residual learning. Our solid experimental evaluations demonstrate superiority of CoMNet over many state-of-the-art industry and academia dominant architectures such as ResNet, RepVGG etc. For instance, CoMNet supersedes ResNet-50 on ImageNet while being 50% shallower, 22% lesser parameters, 25% lower FLOPs and latency, and in 16% lesser training epochs. Code will be opensourced post the reviews.

1 Introduction

To date, a wide variety of CNN architectures exists: branchless (12; 28), single branch (6), multi-branch and variable filter topology (29; 30), feature resue (10), mobile series (8; 23; 35; 31). Despite their architectural diversity, they all have one characteristic in common; their primary design objective dimensions are limited. For instance, (28; 29; 6; 30; 10) seek to achieve higher accuracy regardless of network size and runtime, while (8; 23; 35; 19) aim for fewer FLOPs at the cost of reduced representation power. Some neural architecture search based designs (36; 31) focus on both higher accuracy and lower FLOPs but are heavily branched and runs slower on GPU devices. More recently, (4) focus on accelerating (28) during inference phase while leaving training-phase unaddressed.

In contrast, there are many other dimensions which also need to be addressed in order to cater the demands of CNNs in real-time applications, such as autonomous driving, autonomous robotics etc. Foremost is latency or per-sample runtime which still remains ignored in CNN designs in favour of FLOPs or throughput. Optimizing latency is crucial because real-time applications tend to process as few as one frame at a time but not large batches, and also, fewer FLOPs does not mean lower latency (4). Second, many algorithms are now being replaced by their neural network counterparts, posing a challenge to run multiple networks on a single device (15), bringing in resource efficiency constraints. Third, rising complexity of the tasks (15; 14) demands large networks to achieve satisfactory results, because mobile series networks are insufficient due to their smaller representation power (Sec 2).

In the existing designs, the primary objective dimensions such as higher accuracy (6; 30), smaller FLOPs (8; 23; 31), and inference time FLOPs (4) are explored only individually. However, considering the above discussion, addressing multi-dimensional efficiency is current need of the time. In this case, an ideal choice of CNN should exhibit efficiency in many dimensions while offering trade-offs in others such as: simple yet accurate, controlled parameter growth when scaling network, lower latency and FLOPs, high representation power in limited parameters, low memory consumption, minimum branching, smaller depths, and minimal design hyperparameters. To the best of our knowledge, achieving multi-dimensional efficiency has not been explored as it is a difficult task, mostly due to a high correlation among dimensions, which makes it possible to be better in one but worse in another.

Consequently, in this work, we aim to achieve multi-dimensional efficiency at once, while offering stronger trade-offs in some of them if efficiency in all dimensions is not feasible. To this end, we turn towards biological underpinnings of cortical modules (20) which predominantly exist in a visual cortex. We particularly refer to the structure of cortical modules in ventral stream (32) which is responsible for object recognition in mammalians. To realize our mere biological design inspirations, we inherit a few concepts from the well established CNN designs e.g. residual leaning (6).

Towards our objective, we propose a novel architecture "CoMNet", that can offer multi-dimensional benefits of lower architectural complexity, smaller depth, hardware-accelerators compatible, low memory consumption, low memory access costs on parallel computing hardware, per-sample runtime, parameter efficiency. CoMNet mostly outperforms many key CNN designs, and also offers trade-offs but minimally. Although CoMNet has its design inspired from biological studies, we neither investigate nor assert that CoMNet is functionally similar to the visual cortex.

In a brief, key take-aways of the paper are: *First*, the notion of artificial cortical modules (`ACM`) which helps achieving high representation in fewer parameters, controlled parameter growth, increased computational density, *second*, the concept of columnar organization (20) which helps to achieve smaller depths, lower latency and FLOPs, faster convergence, *Third*, long range connections similar to pyramidal neurons (20) which further improves the accuracy of CoMNet. We also provide a detailed ablation study, and a minimal design space of CoMNet which helps one choosing a suitable model as per the needs. By using GradCAM (26), we also show that CoMNet learns better data representations. Finally, we briefly discuss BrainScore (25) and future prospects of CoMNet.

In the next section, we talk about the most relevant works. In Sec. 2, we brief our biological insights and their translation into the CoMNet architecture. In Sec. 5, we present a rigorous experimental analysis. Finally, in Sec. 6, we provide conclusions about the paper.

2 RELATED WORK

Parameters and Representation Power: The earlier CNN designs (12; 28; 29; 6) poses high representation power. In these designs, the deeper layers consist of a large number of channels e.g. 512 (28) to compensate for the reduction in resolution, leading to exponential growth in the parameters, and synaptic connections of a kernel in these layers. It becomes a predominant cause of overfitting (28) which is alleviated via dropout (12), but at the cost of increased training time. ResNet (6) avoids that by reducing and expanding the number of channels via 1×1 conv layers and placing them before and after 3×3 convolutions. The mobile CNNs (8; 23; 35; 19) on the other hand employ depthwise convolutions (27) to control the parameter growth and reduce FLOPs. However representation power decreases quickly. Moreover, depthwise convs are devoid of cross channel context which is crucial for better performance (35). Therefore such a convolution is followed by a 1×1 conv to intertwine cross channel information.

Depth: In the above networks, the use of 1×1 layers increases network depth rapidly. For example, two 1×1 for each 3×3 in (6; 23; 35; 31), while one in (8). Despite being beneficial, these layers constitute a significant amount of depth e.g. 66% in (6). Moreover, due to their pointwise nature, 1×1 convs do not contribute in the receptive field, which in contrast is governed by 3×3 layers.

Branching: With time, the CNN architectures have grown from branchless (12; 28) to single branch (6) to multibranch (30; 24). Neural architecture search has resulted in even heavily branched designs (36; 31). Although branching helps in improving accuracy, it also raises memory access cost on parallel computing hardware (4) which directly impacts latency and memory consumption.

Latency: Both Depth and high branching increase latency despite having fewer FLOPs. In CNNs, each layer require certain computing time and many such layers are linked serially. Output of one layer can not be computed until all outputs of the preceding layers are available, despite enough computing power remains. This dramatically increases the latency despite fewer calculations per layer. For example, 100 layers each with 1ms time result in 100ms of latency while a shallow network of 15 layers with 3ms per layer runtime will result in 45ms of latency. The best illustration of this phenomenon is (31) which despite having fewer FLOPs, runs equivalent to a five times bigger network (6). More recently, (4) proposes structural reparameterization to accelerate (28) during inference phase, however, the training-phase network is still high in parameters, and branches even more than its predecessor (6), showing no improvement in training time (Table 4).

Convergence: Reduced representation power in (8; 23; 35; 19; 31) results in overly large training schedules on ImageNet, and reduced performance on other downstream tasks. For instance, (8) requires 200 epochs on ImageNet to perform similar to one variant of (28) which is trained only for 75 epochs, but performs poorly on object detection. A similar case (31) which requires $4\times$ training schedule(400 epochs), and larger input resolutions in contrast to the earlier ones (6; 28; 24) that are always trained for a smaller resolution 224×224 and in a range of $90 - 120$ epochs.

With the above multi-dimensional challenges, in this paper, we explore the possibility to achieve multi-dimensional efficiency at once, while offering trade-offs if efficiency everywhere is not possible.

Figure 1: (a) Illustration of cortical modules in IT, (b) `CM_Feeder`, and (c) realization of `ACM`, `CCM`.

3 BIOLOGICAL VISUAL CORTEX

A biological visual cortex is fairly complex but consists of several interesting properties. We highlight the most relevant ones below. For more details, kindly refer to the supplementary material.

Columnar Structure. Cortical modules are present all across a biological cortex (20). Modules in the shallower layers are referred as ocular dominance columns which respond to simple stimuli such as edges, lines of different orientations (11). Whereas modules in the deeper layers are a collection of neurons which respond to a complex stimuli such as face, monkey, human etc, by encoding stimuli information from different viewpoints (32). These modules are mainly present in inferotemporal cortex (IT) which is responsible for object detection, and recognition tasks (Figure 1a).

Shared Input or Input Replication. Two cortical modules having different stimuli response can have a common input i.e. the input is replicated to feed the modules. This is crucial because at a given location in the visual field, there can be a monkey or a car etc. Hence, a module with highest similarity with the stimuli fires strongly, and signals to other parts of the cortex (11).

Limited Synaptic Connections. Typically, a cortical column contains a small number of neurons $(70-100)$ (20) which results in smaller number of synaptic connections per column. It is advantageous as this collection of neurons can learn a simple stimuli.

Massive Parallelization. Regardless of layers being shallower or deeper, a cortical module processes only a small region of retina. Multiples of such modules having similar stimuli response are replicated to span the whole retinal field. This organization facilitates massive parallelization.

Lateral Connection Inhibition. Cortical modules do not communicate with each other except at the output (32), which is achieved via fewer pyramidal neurons having large number of long range connections. Such neurons fuse cross module information (32).

4 COMNET DESIGN

While designing CoMNet, we closely pay attention to the five most crucial objectives: latency, depth, branching, FLOPs, and parameters, which are sufficient to achieve multi-dimensional efficiencies of controlled parameter growth, high representation power in fewer parameters, increased computational density, minimal branching, as other objectives such as memory consumption, memory access cost depend on these. Next, we discuss our proposed biologically inspired designs, their advantage in the context of the above objectives, and their translation into CNN realm. At the end of this section, we intertwine all the individual designs to develop the fundamental computational unit of CoMNet which is used to build different instances of CoMNet.

4.1 ARTIFICIAL CORTICAL MODULES

Our first contribution is to develop IT like structure in CNNs. We achieve that by developing artificial cortical modules `ACM`s, and a mechanism to feed them similar to input replication in the visual cortex. We realize input replication by defining an operator, called `CM_Feeder`. This operator transforms a tensor $\in \mathbb{R}^{C \times H \times W}$ into another tensor $\in \mathbb{R}^{(M \times C) \times H \times W}$, where M denotes the desired number of cortical modules. This operator consumes a tensor and outputs its M identical replicas (Figure 1b).

Since a cortical module is essentially a group of neurons, we realize its artificial counterpart (`ACM`) via a $k \times k$ convolution layer, $k = 3$, having N neurons, Figure 1c. Following, the limited synaptic connection property, N is kept small. To serve as M cortical modules, M such convolutions are employed in parallel, each processing one of the replicas obtained from the `CM_Feeder`. We refer the collection of M `ACM`s as a Collective Cortical Module (`CCM`). The above proposed concept of `ACM` helps achieving controlled parameter growth, high representation power in fewer parameters, and improved computational density as discussed below.

Controlled Parameter Growth. In the earlier designs, number of parameters is controlled by either increasing network width or depth which offers only a little control, and leads to exponential growth in parameters, especially in the deeper layers (Sec. 2). On the other hand, ACMs provide an absolute control over number of synaptic connections which precisely reflects the parameters count. This flexibility is crucial while scaling a CNN as per the needs.

High Representation Power We build a hypothesis that multiple neurons with lesser synaptic connections are better than a single neuron with large connections. For any stimuli, it requires certain amount of representation power or neurons to be learnt. In the existing CNNs, a kernel operates on a large number of channels, thus having large number of synaptic connections. During learning phase, it gets penalized for all the visual stimuli even if it is uncorrelated with them. This is also visible by weight pruning which suggests that post training, eliminating many channels/connections does not impact accuracy, indicating a wastage of synaptic connections.

CoMNet addresses the issue by prioritizing smaller neurons over larger ones by limiting the number of synaptic connection. In other words, we can synthesize more number of neurons out of a larger one. As a result, CoMNet exhibits higher accuracy in lesser parameters without prolonging the training duration, in contrast to (23; 31). It shows that CoMNet learns better data representation in fewer parameters. See Table 1 for quantitative evaluation, and Figure 3 for qualitative representations.

Increased Parallelization and Computational density. Naively, each of the ACM in a CCM is executed independently, however as all of the ACMs are operating parally, they can be computed in parallel by using NVIDIA's highly efficient `Batched-Matrix-Multiply` routines. To achieve that, we combine all the ACMs of a CCM layer into a single convolution layer having M groups. This strategy packs computations of all ACMs into a single convolution, which leads to increased computational density, increased GPU utilization, and reduced memory access cost (4).

Although concept of groups is widely explored (35), (19) etc, however there is a key difference. These approaches divide the input channels into groups i.e. a slicing operation. Whereas in CoMNet, input from previous stages in replicated i.e. replication operation, which is fed to multiple ACMs at once. This is the key difference between CoMNet and CNNs employing group convolutions.

4.2 COLUMNAR STRUCTURE

Our second contribution is to translate the idea of columnar organization into ACM. In a cortical column, several neurons are connected both parally and serially (20). The parallel connections get realized implicitly via N neurons in a module. However, to realize the serial connection, we stack several ACMs one after the another, forming a column, as shown in Figure 2a. Since, ACMs are housed in CCMs, stacking essentially is performed over CCMs. Moreover to respect lateral connection inhibition, an ACM of a CCM can communicate with exactly one ACM of another CCM. For example, an ACM at k^{th} location in a CCM can only feed the ACM at k^{th} location in the subsequent CCM (Figure 2a).

We also follow the concept of pyramidal neurons which fuses the outputs of several cortical modules. We achieve that by placing a 1×1 conv (P_c) layer after the final CCM in the columnar organization. This conv layer fuses the information of multiple modules or ACMs by operating at each $(h, w) \in \mathbb{R}^{(M \times N) \times H \times W}$. Each neuron in the P_c consists of a large number of connections arising due to combining the output of $M * N$ channels. It greatly mimics the property of pyramidal neurons. The proposed artificial columnar organization facilitates eliminating 1×1 layers which results in reduced depth, reduced FLOPs, latency, and faster convergence of CoMNet, as discussed below.

Reduced Depth, FLOPs, and Latency As mentioned in Sec. 2, 1×1 layers are the major constituent of depth in state-of-art networks because they are based on unit/blocks which is a stack of 1×1, 3×3, and 1×1 layers. Several such units are connected serially to form a stage. For instance, in a stage with three units, six 1×1 layers are present for three 3×3 layers. Since, receptive field is mainly governed by $k \times k$ conv layers with $k > 1$ (18), the columnar organization facilitates elimination of 1×1 layers by stacking 3×3 CCM layers, achieving equivalent receptive in just three layers. In other words, columnar organization reduces the three units into one. Notice that, It is true for any number of units. Interestingly, for this reason, a CoMNet unit acts as a stage in contrast to earlier networks where a unit serves as a block, and multiple of such blocks forms stage which are sequentially connected to build a network. The elimination of 1×1 results in decreased depth which results in reduced FLOPs and latency because of the reason mentioned in Sec 2. As an example, CoMNet performs better than ResNet-50 at 50% fewer layers, while having lower parameters, FLOPs and latency, indicating a huge achievement.

Figure 2: (a) Columnar organization, (b) long range connections (LRC), and (c) CoMNet unit / stage.

Faster Convergence   In just half epochs i.e. 60, CoMNet can achieve 99.17% (76.16%) of its accuracy obtained at 120 epochs (76.76%), as compared to ResNet-50 which achieves only 97% (74.15% vs 76.32%). Primary reason behind these improvements is our belief that the 3×3 layers are more important than 1×1 because they are solely responsible for extracting contextual information, thereby governing the receptive fields. Hence, we can obtain equivalent receptive field without 1×1 by keeping the number of 3×3 layers same. However, using 3×3 suffers with overly large parameters for which 1×1 convolutions were introduced in (6). CoMNet tackles this issue by employing ACMs.

4.3 ARTIFICAL LONG RANGE CONNECTIONS

Our third contribution is to develop artificial long range connections. In visual cortex, these are frequently utilized via pyramidal neurons which apart from communicating with the modules, also projects their input to many layers (20). This helps in taking advantage of multi-layer information.

We achieve the same by employing 1×1 conv (L_c) layer which is fed by pooling the input of the CoMNet unit (discussed next). L_c projects this input directly toward the output of the unit while fusing it with the output of P_c. This simulates the behavior of combining the cortical module information and multi-layer information. There are many CCM layers between the input and output of a CoMNet unit, however, L_c bypasses all of them, and directly connect input and output, thereby realizing the effect of long range connections. Although they improve accuracy significantly, they can be traded for parameters, FLOPs at the cost of reduced accuracy.

The long range connections find their structural similarity with projections in (6), however there are notable differences. First, projections in (6) are used only in the first block of a stage, while projection between stages does not exist. Second, projection conv operates with a stride of 2 in (6), whereas in our case, L_c is preceded by a pooling operation. Pooling serves two objectives: First, it helps gathering spatial context because L_c is a pointwise convolution, and aligns the spatial size of the input with output of the final CCM.

4.4 THE COMNET UNIT.

The above proposed CoMNet design ideas are combined to realize the fundamental computational unit of CoMNet. Such a unit is shown in Figure 2. In a CoMNet unit, the input tensor T_i is first passed through a 1×1 conv (S) which squeezes the number of channels by a factor $\mathcal{R}$. Its output T_s is then passed to CM_Feeder, which is followed by a stack of CCM layers. Each CCM layer is connected with the previous via residual connections. The output of final CMM layer is fed to the P_c layer which fuses information from all of the ACMs of the final CMM. Now, T_i is fed to L_c after pooling (p), which projects the information from previous stage i.e. T_i to the P_c layer. The output of P_c and L_c are summed elementwise to produce output tensor T_o. Mathematically, the whole computational unit can be written as follows:

$$T_s = S(T_i), \quad T_{cm} = \texttt{CM\_Feeder}(T_s), \quad T_{ccm} = \texttt{CCM}(.) \tag{1}$$

$$T_c = \texttt{CCM}_l \odot ... \texttt{CCM}_1 \odot \texttt{CCM}_0(T_{cm}) \implies \bigodot_{s=0...l} \texttt{CCM}_s(X_s), X_0 = T_{cm}, X_{s>0} = T_{ccm_{s-1}} \tag{2}$$

$$T_o = P_c(T_c) + L_c(p(T_i)) \tag{3}$$

The most crucial the design objectives are addressed by the three proposed designs which are housed altogether in the CoMNet unit. In addition to those, it can be seen that CoMNet has similar branching as ResNet at the train time which can be eliminated using structural reparameterization (4) during inference. Fewer branching reduce the memory consumption and memory access cost regardless of training or testing. As the CoMNet units are mostly 3×3 convs, CoMNet is fully compatible with hardware accelerators because they have dedicated support for them 3×3. With that saying, we have shed light on all of the objectives which we envisaged to achieve. Next we present a thorough experimental study and test CoMNet in the wild.

Table 1: Effect of ACM, Varying M, N, l. Values of M, N, l are for each of the four CoMNet stages.

Row	N				l				M				#Depth	LRC	Residual CCM	#Params	#FLOPs	Top-1 (%)
R0	16	32	64	128	3	4	6	3	1	1	1	1	26	✓	✓	8.80M	1.25B	74.45
R1	16	32	64	128	3	4	6	3	4	4	4	4	26	✓	✓	12.1M	1.77B	75.65
R2	16	32	64	128	3	4	6	3	5	5	5	5	26	✓	✓	13.2M	1.95B	76.01
R3	32	64	128	256	3	4	6	3	1	1	1	1	26	✓	✓	11.3M	1.65B	75.37
R4	32	64	128	256	3	4	6	3	4	4	4	4	26	✓	✓	19.8M	3.05B	76.76
R5	32	64	128	256	3	4	6	3	5	5	5	5	26	✓	✓	22.6M	3.51B	77.01
R6	32	64	128	256	3	4	6	3	1	1	1	1	26	✓	✗	11.3M	1.65B	75.28
R7	32	64	128	256	3	4	6	3	1	1	1	1	26	✓	✓	11.3M	1.65B	75.37
R8	32	64	128	256	4	5	20	3	1	1	1	1	44	✓	✗	13.4M	2.12B	75.18
R9	32	64	128	256	4	5	20	3	1	1	1	1	44	✓	✓	13.4M	2.12B	75.88

4.5 COMNET INSTANTIATION

A CoMNet variant can be instantiated by connecting many CoMNet units serially which also serve as stages. Without complicating, we follow earlier models (6; 28) to keep the tradition of five stages among which first is a plain 3×3 convolution with stride 2, while remaining are the CoMNet units. Following (6), the channel dimension of S starts with 64 which gets multiplied by 2 at each stage, while channel dimension of P_c and L_c always equals to $\mathcal{R}$ times of the channels in S. We set $\mathcal{R} = 4$, following (6). To further simplify the instantiation process, the number of CCM layers i.e. l in k^{th} CoMNet unit is set equal to the number of blocks in the k^{th} stage of ResNet-50 (6). A CoMNet unit mainly has three hyperparameters: M, N, l In this work, we do not explore every permutation and combination of them, instead, the presented CoMNet models in this paper, are derived such that, they can outperform most useful and deployed state-of-the-art models.

5 EXPERIMENTS

We present in-silico testing of CoMNet on ImageNet (3) which is de-facto standard to benchmark novel architectures. We begin with ablations where we specifically study the significance of ACMs, variation in M, N, l, effect of long range connection, and residual connections in CCM. We train each CoMNet variant for 120 epochs using SGD, Nesterov momentum, base_lr=0.1 with cosine-annealing (17). We also study 200 epochs regime to demonstrate efficacy of CoMNet against state-of-the-art CNNs which are evaluated for 200 epcohs. For 120 epochs, we use RandomResized crop (21), random flip only, while for 200 epochs, MixUp (34), AutoAugment(2), LabelSmoothing (30) are also employed. We also show faster convergence by training CoMNet for 60 epochs.

5.1 ABLATION STUDY

Variation in M, N Table 1 demonstrate the effect of varying N and M (R0-R5). We first fix the values of N and vary M (R0-R5), and then vary M while fixing N (R0 ↔ R3, R1 ↔ R4, R2 ↔ R5). It can be seen that for fixed N, accuracy improves by increasing M, and the same effect is seen by fixing M and varying N. The purpose of this ablation is to show how accuracy, parameters and FLOPs changes with these hyper-parameters. It can be noticed that parameters, FLOPs can be precisely controlled by changing the M (R1 ↔ R2, R4 ↔ R5) which directly reflects accuracy.

Effect of ACM To analyze the significance of ACM, we compare instances having different N, M, but have similar parameters and FLOPs budget, for instance, R1 ↔ R2, R1 ↔ R3, Table 1. It is noticeable that, $R2$ with 5 ACM is better by 0.36% in accuracy, only at 1.1M more parameters relative to R1. Similarly, $R1$ is better by 0.28% in accuracy, only at 0.8M more parameters relative to R3. It shows that multiple ACMs facilitates improved accuracy in just a fraction of parameters, and FLOPs. Moreover, if comparing R9 (a deeper model) with R2, we see that R2 with multiple cortical modules achieves 0.60% more accuracy in 1.4M fewer parameters, and 0.23B fewer FLOPs. It shows the advantage of having multiple cortical modules while being shallower.

Varying "l" The impact of varying l is shown in R9, Table 1. It can be seen that accuracy definitely improves relative to shallower, but depth increases simultaneously. The increased depth causes increased latency, therefore, we stick to $20 - 40$ layers of depth.

Residuals in CCM R6-R9, Table 1 shows this analysis for a shallower and a deeper variant. For shallower model, residual connection shows only minor improvement (0.09%) however for deeper model the effect of residual connections is significant (0.7%).

Table 2: Effect of long range connections `LRC` module.

Row	N				l				M				#Depth	LRC	Residual CCM	#Params	#FLOPs	Top-1 (%)
R0	32	64	128	256	3	4	6	3	1	1	1	1	26	✗	✓	8.5M	1.29B	73.61
R1	32	64	128	256	3	4	6	3	1	1	1	1	26	w/o. Pool	✓	9.8M	1.44B	74.15
R2	32	64	128	256	3	4	6	3	1	1	1	1	26	w. Pool	✓	9.8M	1.44B	75.37

Table 3: Minimal design space of CoMNet.

Model	P_c				l				l				M				#Depth	#Params	#FLOPs	Latency	#Epochs	Top-1 (%)
CoMNet-A0	256	512	1024	2048	16	32	64	128	3	4	6	3	1	1	1	1	26	8.8M	1.25B	4ms	120	74.45
CoMNet-A1	256	512	1024	2048	16	32	64	128	3	4	6	3	4	4	4	4	26	12.1M	1.77B	5ms	120	75.65
CoMNet-A2	256	512	1024	2048	16	32	64	128	3	4	6	3	5	5	5	5	26	13.2M	1.95B	7ms	120	76.01
CoMNet-B0	256	512	1024	2048	32	64	128	256	3	4	6	3	1	1	1	1	26	11.3M	1.65B	4ms	120	75.37
CoMNet-B1	256	512	1024	2048	32	64	128	256	3	4	6	3	4	4	4	4	26	19.8M	3.05B	6ms	120	76.76
CoMNet-B2	256	512	1024	2048	32	64	128	256	3	4	12	3	4	4	4	4	32	23.3M	3.74B	8ms	120	77.15
CoMNet-B3	256	512	1024	2048	32	64	128	256	3	4	6	3	5	5	5	5	26	22.6M	3.51B	6ms	120	77.01
CoMNet-C0	256	512	1024	2048	48	80	144	272	3	4	6	3	4	4	4	4	26	21.6M	3.73B	6ms	120	76.93
CoMNet-C1	256	512	1024	2048	48	80	144	272	4	4	6	4	4	4	4	4	28	24.4M	4.12B	7ms	120	77.34
CoMNet-C1	256	512	1024	2048	48	80	144	272	4	4	6	4	4	4	4	4	28	24.4M	4.12B	7ms	200	78.54
CoMNet-C2	256	512	1024	2048	48	80	144	272	3	4	6	3	6	6	16	6	26	38.9M	7.09B	9ms	120	78.05
CoMNet-C2	256	512	1024	2048	48	80	144	272	3	4	6	3	6	6	16	6	26	38.9M	7.09B	9ms	200	79.25
CoMNet-D0	256	512	1024	2048	64	96	160	288	3	4	6	3	4	4	4	4	26	23.6M	4.52B	8ms	120	77.25
CoMNet-D1	256	512	1024	2048	64	96	160	288	4	5	12	5	4	4	12	4	36	57.0M	10.8B	11ms	200	80.53
CoMNet-E0	256	512	1024	2048	64	128	256	512	3	4	6	3	1	1	1	1	26	18.2M	2.81B	6ms	120	76.51

Effect of Long Range Connections (`LRC`)   As mentioned previously, `LRC` module can be traded for parameters and FLOPs at the cost of reduced accuracy. However, it is important to analyze its significance. We achieve that by training a CoMNet instance in three ways: First, remove `LRC` entirely, second, use `LRC` without pool, and third, use `LRC` with pool. Table 2 shows the corresponding analysis. It can be noticed that without `LRC` (R0), the model suffers with heavy accuracy loss of $\sim 0.54\%$ relative to when `LRC` is used without pool (R1). Moreover, when using `LRC` with pool, accuracy improves significantly i.e. 1.22% and 1.76% relative to R1, and R0 respectively. It happens because pooling operation can provide more spatial context to the 1×1 L_c layer by summarizing the neighborhood.

5.1.1 COMNET DESIGN SPACE

In the presence of many design hyperparameters, it becomes difficult to train many instances to analyze every hyper-parameter, since it is a very time consuming process which requires a lot of computing resources and months of duration. For this reason, despite having only three hyperparameters, we train only a few CoMNet models that shows superiority over the existing models. Even the earlier (6; 28; 30; 10) and newer ones (4) follow this strategy without exploring the whole design space. ResNet being more than half a decade old, its relevant design space is only recently explored (24).

Although the same applies to us, we have tried our best to train a number of CoMNet instances having diversity in representation power, depth, FLOPs, and accuracy, which can easily outperform the most useful state-of-the-art deployable baselines, and can be used by the community as pretrained models.

As mentioned previously and visible in (24) that exploring the whole network design space is challenging, we show a minimal design space of CoMNet in Table 3. All the CoMNet instances are diverse, and have their five most crucial attributes reported i.e. parameters, FLOPs, Latency, epochs and accuracy. Definitely there are always better ways to train i.e. longer training (300 epochs), more complex augmentation (33), (9) which can be used to further improve the accuracy of these instances.

5.1.2 IMAGENET CLASSIFICATION

Next we put CoMNet in the context of existing and popular models which are quite dominant in the academia, industry and real-time applications. We shed light on the multi-dimensional efficiencies achieved by CoMNet. If efficiency is not possible in all dimensions, CoMNet offers stronger trade-offs relative the rival network. We show that CoMNet is simple during both training and inference while can also take advantage of recent structural reparameterization (4) during inference phase. When comparing CoMNet with existing CNNs, if efficiency in every dimension is not feasible, we prioritize a few dimensions over the others by defining a dimension precedence: `Latency = Depth > Branching > FLOPs > Parameters`. Although parameters efficiency is important, it can be sacrificed if CoMNet is better in other dimensions, while latency is kept at the highest.

Table 4: CoMNet in the wild.

Row	Architecture	#Depth	#Epochs	#Params	#SR_Params	#FLOPs	#SR_FLOPs	Latency	SR_Latency	Top-1 (%)
R0	ResNet-18 (6)	18	120	11.6M	–	1.83B	–	4ms	–	71.16
	RepVGG-A0 (4)	22	120	9.10M	8.30M	1.51B	1.46B	8ms	4ms	72.41
	ResNet-34 (6)	34	120	21.7M	–	3.68B	–	8ms	–	74.17
	CoMNet-A0	26	120	8.8M	1.25M	1.25B	1.25B	7ms	5ms	74.45
R1	RepVGG-A1 (4)	22	120	14.0M	12.7M	2.63B	2.36B	7ms	5ms	74.46
	EfficientNet-B0 (4)	49	120	5.26M	–	0.40B	–	8ms	–	75.11
	RepVGG-B0 (4)	28	120	15.8M	14.3M	3.06B	3.40B	7ms	5ms	75.14
	CoMNet-A1	26	120	12.1M	12.1M	1.77B	1.77B	7ms	5ms	75.65
R2	ResNet-50 (21)	50	120	25.5M	–	4.12B	–	11ms	–	76.30
	RepVGG-A2 (4)	22	120	28.1M	25.5M	5.69B	5.12B	9ms	7ms	76.48
	CoMNet-B1	26	120	19.8M	19.8M	3.05B	3.05B	7ms	6ms	76.76
R3	ResNet-101 (6)	101	120	44.5M	–	7.85B	–	15ms	–	77.21
	CoMNet-C1	28	120	24.4M	24.4M	4.12B	4.12B	7ms	6ms	77.34
R4	ResNet-152 (6)	152	120	60.1M	–	11.5B	–	15ms	–	77.78
	CoMNet-C2	26	120	38.9M	38.9M	7.09B	7.09B	11ms	9ms	78.05
R5	RepVGG-B3 (4)	28	200	123.0M	110.9M	29.1B	26.2B	22ms	17ms	80.52
	RegNetX-12GF (6)	57	200	46.0M	–	12.1B	–	13ms	–	80.55
	CoMNet-D1	36	200	57.0M	57.0M	10.8B	10.8B	12ms	11ms	80.53
R6	ResNet-50 (21)	50	60	25.5M	–	4.12B	–	10ms	–	74.15
	CoMNet-B1	26	60	19.8M	19.8M	3.05B	3.05B	7ms	6ms	76.16

Table 4 shows the comparison of CoMNet with existing models over multi-dimensional metrics. Latency is reported for RTX-2070 GPU which may vary on a different GPU device, therefore the numbers are only for reference. Below we discuss the observations in a structured manner.

R0. CoMNet is 3.29% accurate, has 25% fewer parameters, 31% fewer FLOPs than ResNet-18 while offers similar runtime speed. Although it has 6 more layers, CoMNet offers higher representation power in fewer parameters at equivalent latency. Similarly, in comparison to ResNet-34, it is accurate by 0.28%, has 59% fewer parameters, 66% fewer FLOPs, 23% less deeper while runs faster by 37%. In terms of state-of-the-art RepVGG (4) models, CoMNet is more accurate by 2.04% while having marginally fewer FLOPs, parameters and equivalent speed.

R1. CoMNet is a strong competitor to RepVGG i.e. $\sim 13\%$ fewer parameters, 32% fewer FLOPs while offering similar speeds but higher accuracy by 1.19% for RepVGG-A1. Although we do not target mobile regime in this paper, we still show that having fewer parameters and FLOPs do not guarantee faster speeds. EfficientNet-B0 has 50% fewer parameters and 77% fewer FLOPs, but is 50% more deeper, and runs 37% slower. We believe that by exploring the design space of CoMNet for mobile regime, CoMNet can offer trade-offs to EfficientNet, which we leave for future work.

R2. ResNet-50 is the most successful and widely employed backbone for many applications such as (22; 7; 1), and to establish new benchmarks (34; 5) due to its affordability in terms of representation power, FLOPs, depth and accuracy. CoMNet easily surpasses ResNet-50 while being 50% shallower, 22% fewer parameters, 25% fewer FLOPs and 40% faster. CoMNet also outperforms RepVGG-A2.

R3-R4. The corresponding experiments shows that CoMNet is better than two larger variants of ResNet which despite being older, still serves as backbones for many cutting-edge works (1; 16). Our CoMNet outperforms these two baselines in every aspect while surprisingly being 72% and 82% less deeper relative to ResNet-101 and ResNet-152 respectively. CoMNet also runs significantly faster by almost 50% in roughly 50% fewer parameters and FLOPs. This is quite promising in short training epochs while being shallower.

R5. CoMNet models achieve beyond 80% of accuracy in just 36 layers while offering strong trade-offs to the state of the art. For example, CoMNet is as accurate as RegNetX-12GF (24) at 10% fewer FLOPs, 36% less depth, and runs faster by 15% while offering tradeoffs in the parameters dimension. For such a shallow model, achieving this much of accuracy in multi-dimensional efficiency setting has not been seen previously. Even RepVGG is dramatically less efficient i.e. 53% fewer parameters, 62% fewer FLOPs while running significantly faster. This shows promising nature of CoMNet in large network regime. However, our target in this paper is the real-time domain only.

R6. This experiment shows the faster convergence of CoMNet in half of the original training epochs i.e. 60. It can be seen that CoMNet attains 99.17% (76.16%) of its accuracy obtained at 120 epochs (76.76%), as compared to ResNet-50 which achieves only 97% (74.15% vs 76.32%).

Figure 3: GradCAM visualizations

Figure 4: Multi-dimensional efficiency plots.

Structural Reparameterization (4). RepVGG uses structural reparameterization (SR) during inference phase which converts it into a plain VGG (28) like structure. CoMNet is also fully compatible with reparameterization and can achieve lower latency but marginally. Interestingly, RepVGG offers lower architectural complexity only during inference phase, but training-phase complexity is still very high i.e. very larger parameters, three branches at each layer (4) which leads to increased training time (Table 4). Whereas CoMNet offers extremely lower complexity at both training and testing phase because CoMNet only have single residual connections in CCM layers which can be eliminated via SR. This leads to reduction in FLOPs of element-wise summation layers which is only marginal, however, memory access cost gets reduced due to the branch elimination (4).

Multi-dimensional Efficiency Figure 4 shows different plots for accuracy vs an objective dimension. It can noticed that CoMNet is always better regardless of the objective except in depth relative to RepVGG, which is only a difference of $3 - 4$ layers. Despite that, CoMNet is accurate, has lower latency, lower FLOPs while has low architectural complexity, justifying the objective of this paper.

5.2 ADDITIONAL QUALITATIVE EVALUATIONS

GradCAM: Gradient based Class Activation Map (26) To comprehend why CoMNet performs better in multi-dimension, we investigate the class activation maps on ImageNet (3) validation images. We use GradCAM (26) for this purpose, which is provided with a class label for which it calculates activation maps indicating the attended regions by the network. We show GradCAM visualizations of ResNet-50 and CoMNet-B1 (based on R2, Table 4 in Figure 3). It can be seen that CoMNet significantly improves the attended regions of the target objects relative to the baseline. It indirectly indicates high generalizability of CoMNet by emphasizing on class specific parts in the image.

BrainScore (25) Although CoMNet follows the structure of biological visual cortex, we neither claim on CoMNet's functional similarity with brain nor do we aim to build models that are more brain-like (13). However, as the structure of IT cortex is our major inspiration, we ran BrainScore test on CoMNet-B1 out of curiosity. The BrainScore (25) provides a degree to which the intermediate layers of a network behave similar to the layers of a visual cortex. For more details, please refer to (25). The BrainScore performance largely depends on the training method. However, in our test, we found that CoMNet ranks 39 (in more than 350 entries) in the IT score without any specialized training. The models ResNet-101 and ResNet-152 are ranked 119 and 143 respectively in the IT score. Notice that our BrainScore analysis merely provides a new perspective on CoMNet, not to assert the functional similarity of CoMNet with visual cortex.

5.3 FUTURE DIRECTIONS

Achieving multi-dimensional efficiency is crucial for real-time applications. CoMNet is the first effort in this direction by incorporating biological underpinnings. Despite the significant achievements, there still remain a room of improvement in CoMNet. *First*, a comprehensive design space of CoMNet can be explored, similar to (24). *Second*, mobile regime of CoMNet is yet to be explored. *Third*, BrainScore can serve as an additional efficiency dimension to improve CoMNet's brain-like behavior.

6 CONCLUSION

In this work, we present a novel deployable CNN architecture "CoMNet" which inherits certain properties of biological visual cortex such as cortical modules, columnar organization to achieve multi-dimensional efficiency in parameters, FLOPs, accuracy, latency, lesser training epochs while having very low architectural complexity. We provide a minimal design space of CoMNet instead of training only a few models. CoMNet outperforms many state-of-the-art and popular networks such as RepVGG, ResNet, while being shallower, running significantly faster, and also offering stronger trade-offs when multi-dimensional efficiency is not possible.

REFERENCES

[1] Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision*, pp. 213–229. Springer, 2020.

[2] Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le. Autoaugment: Learning augmentation strategies from data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 113–123, 2019.

[3] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

[4] Xiaohan Ding, Xiangyu Zhang, Ningning Ma, Jungong Han, Guiguang Ding, and Jian Sun. Repvgg: Making vgg-style convnets great again. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13733–13742, 2021.

[5] Priya Goyal, Piotr Dollár, Ross Girshick, Pieter Noordhuis, Lukasz Wesolowski, Aapo Kyrola, Andrew Tulloch, Yangqing Jia, and Kaiming He. Accurate, large minibatch sgd: Training imagenet in 1 hour. *arXiv preprint arXiv:1706.02677*, 2017.

[6] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

[7] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pp. 2961–2969, 2017.

[8] Andrew G Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.

[9] Gao Huang, Yu Sun, Zhuang Liu, Daniel Sedra, and Kilian Q Weinberger. Deep networks with stochastic depth. In *European conference on computer vision*, pp. 646–661. Springer, 2016.

[10] Gao Huang, Zhuang Liu, Kilian Q Weinberger, and Laurens van der Maaten. Densely connected convolutional networks. *CVPR*, 2017.

[11] David H Hubel and TN Wiesel. Shape and arrangement of columns in cat's striate cortex. *The Journal of physiology*, 165(3):559–568, 1963.

[12] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

[13] Jonas Kubilius, Martin Schrimpf, Kohitij Kar, Rishi Rajalingham, Ha Hong, Najib Majaj, Elias Issa, Pouya Bashivan, Jonathan Prescott-Roy, Kailyn Schmidt, et al. Brain-like object recognition with high-performing shallow recurrent anns. *Advances in neural information processing systems*, 32, 2019.

[14] Ashish Kumar and Laxmidhar Behera. Semi supervised deep quick instance detection and segmentation. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 8325–8331. IEEE, 2019.

[15] Ashish Kumar, Mohit Vohra, Ravi Prakash, and Laxmidhar Behera. Towards deep learning assisted autonomous uavs for manipulation tasks in gps-denied environments. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 1613–1620. IEEE, 2020.

[16] Feng Li, Hao Zhang, Shilong Liu, Jian Guo, Lionel M Ni, and Lei Zhang. Dn-detr: Accelerate detr training by introducing query denoising. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13619–13627, 2022.

[17] Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

[18] Wenjie Luo, Yujia Li, Raquel Urtasun, and Richard Zemel. Understanding the effective receptive field in deep convolutional neural networks. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, pp. 4905–4913, 2016.

[19] Ningning Ma, Xiangyu Zhang, Hai-Tao Zheng, and Jian Sun. Shufflenet v2: Practical guidelines for efficient cnn architecture design. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 116–131, 2018.

[20] Vernon B Mountcastle. The columnar organization of the neocortex. *Brain: a journal of neurology*, 120(4):701–722, 1997.

[21] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

[22] Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. *Advances in neural information processing systems*, 28:91–99, 2015.

[23] Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4510–4520, 2018.

[24] Nick Schneider, Florian Piewak, Christoph Stiller, and Uwe Franke. Regnet: Multimodal sensor registration using deep neural networks. In *2017 IEEE intelligent vehicles symposium (IV)*, pp. 1803–1810. IEEE, 2017.

[25] Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J Majaj, Rishi Rajalingham, Elias B Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Franziska Geiger, et al. Brain-score: Which artificial neural network for object recognition is most brain-like? *BioRxiv*, pp. 407007, 2020.

[26] Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

[27] L Sifre and S Mallat. Rigid-motion scattering for image classification. arxiv 2014. *arXiv preprint arXiv:1403.1687*.

[28] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *CoRR*, abs/1409.1556, 2014.

[29] Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1–9, 2015.

[30] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2818–2826, 2016.

[31] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, pp. 6105–6114. PMLR, 2019.

[32] Keiji Tanaka. Inferotemporal cortex and object vision. *Annual review of neuroscience*, 19(1): 109–139, 1996.

[33] Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 6023–6032, 2019.

[34] Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *arXiv preprint arXiv:1710.09412*, 2017.

[35] Xiangyu Zhang, Xinyu Zhou, Mengxiao Lin, and Jian Sun. Shufflenet: An extremely efficient convolutional neural network for mobile devices. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6848–6856, 2018.

[36] Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V Le. Learning transferable architectures for scalable image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 8697–8710, 2018.