VISUAL RECOGNITION WITH DEEP NEAREST CENTROIDS

ABSTRACT

We devise deep nearest centroids (DNC), a conceptually elegant yet surprisingly effective network for large-scale visual recognition, by revisiting Nearest Centroids, one of the most classic and simple classifiers. Current deep models learn the classifier in a *fully parametric* manner, ignoring the latent data structure and lacking explainability. DNC instead conducts nonparametric, case-based reasoning; it utilizes sub-centroids of training samples to describe class distributions and clearly explains the classification as the proximity of test data and the class sub-centroids in the feature space. Due to the distance-based nature, the network output dimensionality is flexible, and all the learnable parameters are *only* for data embedding. That means all the knowledge learnt for ImageNet classification can be *completely* transferred for pixel recognition learning, under the "pre-training and fine-tuning" paradigm. Apart from its nested simplicity and intuitive decision-making mechanism, DNC can even possess *ad-hoc* explainability when the sub-centroids are selected as actual training images that humans can view and inspect. Compared with parametric counterparts, DNC performs better on image classification (CIFAR-10, CIFAR-100, ImageNet) and greatly boots pixel recognition (ADE20K, Cityscapes) with improved transparency, using various backbone network architectures (ResNet, Swin) and segmentation models (FCN, DeepLab$_{V3}$, Swin). Our code will be released.

1 INTRODUCTION

Deep learning models, from convolutional networks (*e.g.*, VGG [1], ResNet [2]) to Transformer-based architectures (*e.g.*, Swin [3]), push forward the state-of-the-art on visual recognition. With these advancements, parametric softmax classifiers, which learn a set of parameters, *i.e.*, weight vector, and bias term, for each class, have become the *de facto* regime in the area (Fig. 1(b)). However, due to the parameterization nature, they suffer from several limitations: **First**, they lack simplicity and explainability. The parameters in the classification layer are abstract and detached from the physical nature of the problem being modelled [4]. Thus these classifiers are hard to naturally lend to an explanation that humans are able to process [5]. **Second**, the networks are trained purely to optimize the accuracy of predictions, neglecting the latent structure that data may possess. For each class, only one single weight vector is learned in a fully parametric manner. Thus they essentially assume *unimodality* for each class [6, 7], bearing no intra-class variation. **Third**, as each class has its own set of parameters, deep parametric classifiers require the output space with a fixed dimensionality (equal to the number of classes) [8]. As a result, their transferability is limited; when using ImageNet [9] trained image classifiers initialize segmentation networks (*i.e.*, pixel classifiers), the last classification layer, whose parameters are valuable knowledge learnt from the image classification task, has to be thrown away.

In light of the foregoing discussions, we are motivated to present deep nearest centroids (DNC), a powerful, nonparametric classification network (Fig. 1(d)). Nearest Centroids, which has historical roots dating back to the dawn of artificial intelligence [10–15], is arguably the simplest classifier. Nearest Centroids operates on an intuitive principle: given a data sample, it is directly classified to the class of training examples whose mean (centroid) is closest to it. Apart from its internal transparency, Nearest Centroids is a classical form of exemplar-based reasoning [5, 12], which is fundamental to our most effective strategies for tactical decision-making [16] (Fig. 1(c)). Numerous past studies [17–19] have shown that humans learn to solve new problems by using past solutions of similar problems. Despite its conceptual simplicity, empirical evidence in cognitive science, and ever popularity [20–23], Nearest Centroids, and particularly its utility in large datasets with high-dimensional input spaces, are widely unknown or ignored by current community. Inheriting the intuitive power of Nearest Centroids, our

Figure 1: (b) Prevalent visual recognition models 🔲, built upon parametric softmax classifiers, have a few limitations, such as their non-transparent decision-making process. (c) Humans 👤 can use past cases as models when solving new problems [17, 19] (*e.g.*, comparing 🐱 with a few familiar/exemplar animals for categorization). (d) DNC 🔲 makes classification based on the similarity of 🐱 to class sub-centroids (representative training examples) in the feature space. The class sub-centroids are vital for capturing underlying data structure, enhancing interpretability, and boosting recognition.

DNC is able to serve as a *strong yet interpretable backbone* for large-scale visual recognition; it is fully aware of the limitations of parametric counterparts while shows even better performance.

Specifically, DNC summarizes each class into a set of sub-centroids (sub-cluster centers) by clustering of training data inside the same class, and assigns each test sample to the class with the nearest sub-centroid. DNC is essentially an *experience-/distance-*based classifier – it merely relies on the proximity of test query to local means of training data ("quintessential" past observations) in the deep feature space. As such, DNC learns visual recognition by directly optimizing the representation, instead of deep parametric models needing an extra softmax classification layer after feature extraction. For training, DNC alternates between two steps: **i)** *class-wise clustering* for automatically discovering class sub-centroids, and **ii)** *classification prediction* for supervised representation learning, through retrieving the nearest sub-centroids. However, since the feature space evolves continually during training, computing the sub-centroids is expensive – it requires a pass over the full training dataset after each batch update and limits DNC's scalability. To solve this, we use a Sinkhorn Iteration [24] based clustering algorithm [25] for fast cluster assignment. We further adopt momentum update with an external memory for online estimating the sub-centroids (whose amount is more than 1K on ImageNet [9]) with small-batch size (*e.g.*, 256). Consequently, DNC can be efficiently trained by simultaneously conducting clustering and stochastic optimization on large datasets with small batches, only slowing the training speed slightly (*e.g.*, ∼5% on ImageNet).

DNC enjoys a few attractive qualities: **First**, improved *simplicity* and *transparency*. The intuitive working mechanism and statistical meaning of class sub-centroids make DNC elegant and easy to understand. **Second**, automated discovery of ***underlying data structure***. By within-class deterministic clustering, the latent distribution of each class is automatically mined and fully captured as a set of representative local means. In contrast, parametric classifiers learn one single weight vector per class, intolerant of rich intra-class variations. **Third**, direct supervision of *representation learning*. DNC achieves classification by comparing data samples and class sub-centroids on the feature space. With such distance-based nature, DNC blends unsupervised sub-pattern mining (class-wise clustering) and supervised representation learning (nonparametric classification) in a synergy: local significant patterns are automatically mined to facilitate classification decision-making; the supervisory signal from classification directly optimizes the representation, which in turn boosts meaningful clustering. **Forth**, better *transferability*. DNC learns by *only* optimizing the feature representation, thus the output dimensionality no longer needs to be as many as the classes. With this algorithmic merit, all the useful knowledge (parameters) learnt from a source task (*e.g.*, ImageNet [9] classification) are stored in the representation space, and can be completely transferred to target tasks (*e.g.*, Cityscapes [26] segmentation). **Fifth**, *ad-hoc explainability*. If further restricting the class sub-centroids to be samples (images) of the training set, DNC can explain its prediction based on *IF···Then* rules and allow users to intuitively view the class representatives, and appreciate the similarity of test data to the representative images (detailed in §3&4.3). Such *ad-hoc* explainability [27] is valuable in safety-sensitive scenarios, and differs DNC from most existing network interpretation techniques [28–30] that only investigate *post-hoc* explains and thus fail to elucidate precisely how a model works [31, 32].

DNC is an intuitive yet general classification framework; it is compatible with different visual recognition network architectures and tasks. We experimentally show: **In §4.1**, with ResNet [2] and Swin [3] network architectures, DNC outperforms parametric counterparts on image classification, *i.e.*, **0.23-0.24**% top-1 accuracy on CIFAR-10 [33] and **0.24-0.32**% on ImageNet [9], by *training from scratch*.

In §4.2, when using our ImageNet-pretrained, nonparametric versions of ResNet and Swin as backbones, our pixel-wise DNC classifier greatly improves the segmentation performance of FCN [34], DeepLab$_{V3}$[35], and UperNet [36], on ADE20K [37] (**1.6-2.5**% mIoU) and Cityscapes [26] (**1.1-1.9**% mIoU). These results verify DNC's strong transferability and high versatility. **In §4.3**, after constraining class sub-centroids as training images of ImageNet, DNC becomes more interpretable, with only **0.12**% sacrifice in top-1 accuracy (but is still **0.17**% better than the parametric counterpart).

These results are particularly impressive, considering the nonparametric and transparent nature of DNC. We feel this work brings fundamental insights into related fields. Our code will be released.

2 RELATED WORK

Distance-/Prototype-based Classifiers. Among the numerous classification algorithms (*e.g.*, logistic regression [38], Naïve Bayes [39], random forest [40], support vector machines [41], and deep neural networks (DNNs) [42]), distance-based methods are particularly remarkable, due to their intuitive working mechanism. Distance-based classifiers are nonparametric and exemplar-driven, relying on similarities between samples and internally stored exemplars/prototypes. Thus they conduct case-based reasoning that humans use naturally in problem-solving, making them appealing and interpretable [17, 43]. k-Nearest Neighbors (k-NN) [10, 11] is a form of distance-based classifiers; it uses *all* training data as exemplars [44, 45]. Towards network implementation of k-NN [46–48], Wu *et al.* [49] made notable progress; their k-NN network outperforms parametric softmax based ResNet [2] and the learnt representation works well in few-shot settings. However, k-NN classifiers (including the deep learning analogues) cost huge storage space and pose heavy computation burden (*e.g.*, persistently retaining the training dataset and making full-dataset retrieval for each query) [50, 51], and the nearest neighbors may not be good class representatives [43]. Nearest Centroids [12–15] is another famous distance-based classifier yet has neither of the deficiencies of k-NN [21, 43]. Nearest Centroids selects representative class centers, instead of all the training data, as exemplars. Guerriero *et al.* [52] also investigate the idea of bringing Nearest Centroids into DNNs. However, they simply abstract each class into one single class mean, failing to capture complex class-wise distributions and showing weak results even in small datasets [33].

The idea of distance-based classification also stimulates the emergence of *prototypical networks*, which mainly focus on few-shot [53, 54] and zero-shot [55, 56] learning. However, they often associate to each class only one representation (prototype) [57] and their prototypes are usually flexible parameters [51, 53, 56] or defined prior to training [8, 55]. In DNC, a prototype (sub-centroid) is either a generalization of a number of observations or intuitively a typical training visual example. Via clustering based sub-class mining, DNC addresses two key properties of prototypical exemplars: *sparsity* and *expressivity* [58, 59]. In this way, the representation can be learnt to capture the underlying class structure, hence facilitating large-scale visual recognition while preserving transparency.

Neural Network Interpretability. As the *black-box* nature limits the adoption of DNNs in decision-critical tasks, there has been a recent surge of interest in DNNs' interpretability. However, most interpretation techniques only produce posteriori explanations for already-trained DNNs, typically by analysis of reverse-engineer importance values [28–30, 60–65] and sensitivities of inputs [66–69]. As many literature outlined, *post-hoc* explanations are problematic and misleading [32, 43, 70, 71]; they cannot explain what *actually* makes a DNN arrive at its decisions [72]. To pursue *ad-hoc* explainability, some attempts have been initiated to develop explainable DNNs, by deploying more interpretable machineries into black-box DNNs [73–75] or regularizing representation with certain properties (*e.g.*, sparsity [76], decomposability [77], monotonicity [78]) that can enhance interpretability.

DNC intrinsically relies on class sub-centroid retrieving. The theoretical simplicity makes it easy to understand; when anchoring the sub-centroids to available observations, DNC can derive intuitive explanations based on the similarities of test samples to representative observations. It simultaneously conducts representation learning and case-based reasoning, making it self-explainable without post-hoc analysis [27]. DNC relates to *concept*-based explainable networks [4, 5, 72–74, 79, 80] that refer to human-friendly concepts/prototypes during decision making. These methods, however, necessitate nontrivial architectural modification and usually resort to pre-trained models, not to mention serving as backbone networks. In sharp contrast, DNC only brings minimal architecture change to parametric classifier based DNNs and yields remarkable performance on ImageNet [9] with training from scratch and ad-hoc explainability. It provides solid empirical evidence, for the first time as far as we know, for the power of case-based reasoning in large-scale visual recognition.

Figure 2: With a distance-/case-based classification scheme, DNC combines unsupervised sub-pattern discovery and supervised representation learning in a synergy.

3 DEEP NEAREST CENTROIDS (DNC)

Problem Statement. Consider the standard visual recognition setting. Let $\mathcal{X}$ be the visual space (*e.g.*, image space for recognition, pixel space for segmentation), and $\mathcal{Y} = \{1, \cdots, C\}$ the set of semantic classes. Given a training dataset $\{(x_n, y_n) \in \mathcal{X} \times \mathcal{Y}\}_{n=1}^N$, the goal is to use the N training examples to fit a *model* (or hypothesis) $h : \mathcal{X} \mapsto \mathcal{Y}$ that accurately predicts the semantic classes for new visual samples.

Parametric Softmax Classifier. Current common practice is to implement h as DNNs and decompose it as $h = l \circ f$. Here $f : \mathcal{X} \mapsto \mathcal{F}$ is a *feature extractor* (*e.g.*, convolution based or Transformer-like networks) that maps an input sample $x \in \mathcal{X}$ into a d-dimensional representation space $\mathcal{F} \in \mathbb{R}^d$, *i.e.*, $\boldsymbol{x} = f(x) \in \mathcal{F}$; and $l : \mathcal{F} \mapsto \mathcal{Y}$ is a *parametric classifier* (*e.g.*, the last fully-connected layer in recognition or last 1×1 convolution layer in segmentation) that takes $\boldsymbol{x}$ as input and produces class prediction $\hat{y} = l(\boldsymbol{x}) \in \mathcal{Y}$. Concretely, l assigns a query $x \in \mathcal{X}$ to the class $\hat{y} \in \mathcal{Y}$ according to:

$$\hat{y} = \arg\max_{c \in \mathcal{Y}} s^c, \qquad s^c = (\boldsymbol{w}^c)^\top \boldsymbol{x} + b^c, \tag{1}$$

where $s^c \in \mathbb{R}$ indicates the unnormalized prediction score (*i.e.*, *logit*) for class c, $\boldsymbol{w}^c \in \mathbb{R}^d$ and $b^c \in \mathbb{R}$ are learnable parameters – class weight and bias term for c. Parameters of l and f are learnt by minimizing the softmax cross-entropy loss:

$$\mathcal{L} = \frac{1}{N} \sum_{n=1}^N -\log p(y_n | x_n), \quad p(y|x) = \mathrm{softmax}_y(l \circ f(x)) = \frac{\exp(s^y)}{\sum_{c \in \mathcal{Y}} \exp(s^c)}. \tag{2}$$

Though highly successful, the use of the parametric classifier l has drawbacks as well: **i)** The weight matrix $\boldsymbol{W} = (\boldsymbol{w}^1, \cdots, \boldsymbol{w}^C) \in \mathbb{R}^{d \times C}$ and bias vector $\boldsymbol{b} = (b^1, \cdots, b^C) \in \mathbb{R}^d$ in l are learnable parameters, cannot providing any information about what makes the model h reach its decisions. **ii)** l makes the loss $\mathcal{L}$ only depend on the relative relation among logits, *i.e.*, $\{s^c\}_{c=1}^C$, and cannot directly supervise on the representation $\boldsymbol{x}$ [81, 82]. **iii)** $\boldsymbol{W}$ and $\boldsymbol{b}$ are learnt without considering any underlying data distribution. **iv)** The final output dimensionality is constrained as many as the classes, *i.e.*, C. During transfer learning, as different visual recognition tasks typically have distinct semantic label spaces (with different number of classes), the classifier from a pretrained model has to be abandoned, even though the learnt parameters $\boldsymbol{W}$ and $\boldsymbol{b}$ contain valuable knowledge from the source task.

The question naturally arises: might there be a simple way to address the limitations of current *de facto*, parametric classifier based visual recognition regime? Here we show that this is indeed possible, even coming with better performance.

DNC Classifier. Our DNC (Fig. 2) is built upon the intuitive idea of Nearest Centroids, *i.e.*, assign a sample x to the class $\hat{y} \in \mathcal{Y}$ with the closest class center:

$$\hat{y} = \arg\min_{c \in \mathcal{Y}} \langle \boldsymbol{x}, \bar{\boldsymbol{x}}^c \rangle, \quad \bar{\boldsymbol{x}}^c = \frac{1}{N^c} \sum_{x_n^c : y_n^c = c} \boldsymbol{x}_n^c, \tag{3}$$

where $\langle \cdot, \cdot \rangle$ is a distance measure, used as the negative cosine similarity: $\langle \boldsymbol{u}, \boldsymbol{v} \rangle = -\boldsymbol{u}^\top \boldsymbol{v} / \|\boldsymbol{u}\| \|\boldsymbol{v}\|$. Here $\bar{\boldsymbol{x}}^c$ is the mean vector of class c, x_n^c is a training sample of c, *i.e.*, $y_n^c = c$, and N^c is the number of training samples in c. As such, the feature-to-class mapping $\mathcal{F} \mapsto \mathcal{Y}$ is achieved in a *nonparametric* manner and *understandable* from user's view, in contrast to the parametric classifier l that learns "non-transparent" parameters for each class. It makes more sense if using multiple sub-centroids (local means) per class instead of just one, which is in particular true for challenging visual recognition where complex intra-class variations cannot be simply described by the simple assumption of unimodality of data of each class. When representing each class c as K sub-centroids, denoted by $\{\boldsymbol{p}_k^c \in \mathbb{R}^d\}_{k=1}^K$, the C-way classification for sample x takes place as a *winner-takes-all* rule:

$$\hat{y} = c^*, \quad (c^*, k^*) = \arg\min_{c \in \mathcal{Y}, k \in \{1, \cdots, K\}} \langle \boldsymbol{x}, \boldsymbol{p}_k^c \rangle. \tag{4}$$

Clearly, estimating class sub-centroids needs clustering of training samples within each class. As class sub-centroids are sub-cluster centers in the latent feature space $\mathcal{F}$, they are locally significant visual patterns and can comprehensively represent class-level characteristics. DNC can be intuitively understood as selecting and storing prototypical exemplars for each class, and finding classification evidence for a previously unseen sample by retrieving the most similar exemplar. This also aligns with the *prototype theory* in psychology [18, 83, 84]: prototypes are a typical form of cognitive organisation of real world objects. DNC thus emulates the case-based reasoning process that we humans are accustomed to [27]. For instance, when ornithologists classify a bird, they will compare it with those typical exemplars from known bird species to decide which species the bird belongs to [43].

Sub-centroid Estimation. To find informative sub-centroids that best represent classes, we perform deterministic clustering within each class on the representation space $\mathcal{F}$. More specifically, for each class c, we cluster all the representations $\{\boldsymbol{x}_n^c \in \mathbb{R}^d\}_{n=1}^{N^c}$ into K clusters whose centers are used as the sub-centroids of c, *i.e.*, $\{\boldsymbol{p}_k^c \in \mathbb{R}^d\}_{k=1}^K$. Let $\boldsymbol{X}^c = [\boldsymbol{x}_1^c, \cdots, \boldsymbol{x}_{N^c}^c] \in \mathbb{R}^{d \times N^c}$ and $\boldsymbol{P}^c = [\boldsymbol{p}_1^c, \cdots, \boldsymbol{p}_K^c] \in \mathbb{R}^{d \times K}$ denote the feature and sub-centroid matrixes, respectively. The deterministic clustering, *i.e.*, the mapping from $\boldsymbol{X}^c$ to $\boldsymbol{P}^c$, can be denoted as $\boldsymbol{Q}^c = [\boldsymbol{q}_1^c, \cdots, \boldsymbol{q}_{N^c}^c] \in \{0, 1\}^{K \times N^c}$, where n-*th* column $\boldsymbol{q}_n^c \in \{0, 1\}^K$ is an one-hot assignment vector of n-*th* sample x_n^c *w.r.t* the K clusters. $\boldsymbol{Q}^c$ is desired to maximize the similarity between $\boldsymbol{X}^c$ and $\boldsymbol{P}^c$, leading to the following binary integer program (BIP):

$$\max_{\boldsymbol{Q}^c \in \mathcal{Q}^c} \mathrm{Tr}\big((\boldsymbol{Q}^c)^\top (\boldsymbol{P}^c)^\top \boldsymbol{X}^c\big), \ \ \mathcal{Q}^c = \{\boldsymbol{Q}^c \in \{0, 1\}^{K \times N^c} | (\boldsymbol{Q}^c)^\top \mathbf{1}_K = \mathbf{1}_{N^c}\}, \tag{5}$$

where $\mathbf{1}_K$ is a K-dimensional all-ones vector. As in [25], we relax $\mathcal{Q}^c$ to be a *transportation polytope* [24]: $\mathcal{Q}'^c = \{\boldsymbol{Q}^c \in \mathbb{R}_+^{K \times N^c} | (\boldsymbol{Q}^c)^\top \mathbf{1}_K = \mathbf{1}_{N^c}, \boldsymbol{Q}^c \mathbf{1}_{N^c} = \frac{N^c}{K} \mathbf{1}_K\}$, casting BIP (5) into an *optimal transport* problem. In $\mathcal{Q}'^c$, besides the *one-hot assignment* constraint (*i.e.*, $(\boldsymbol{Q}^c)^\top \mathbf{1}_K = \mathbf{1}_{N^c}$), an *equipartition* constraint (*i.e.*, $\boldsymbol{Q}^c \mathbf{1}_{N^c} = \frac{N^c}{K} \mathbf{1}_K$) is added to inspire N^c samples to be evenly assigned to K clusters. This can efficiently avoid degeneracy, *i.e.*, mapping all the data to the same cluster. Then the solution can be given by a fast version [24] of Sinkhorn-Knopp algorithm [85], in a form of a normalized exponential matrix:

$$\boldsymbol{Q}^{c*} = \mathrm{diag}(\boldsymbol{\alpha}) \exp\big(\frac{(\boldsymbol{P}^c)^\top \boldsymbol{X}^c}{\varepsilon}\big) \mathrm{diag}(\boldsymbol{\beta}), \tag{6}$$

where the exponentiation is performed element-wise, $\boldsymbol{\alpha} \in \mathbb{R}^K$ and $\boldsymbol{\beta} \in \mathbb{R}^{N^c}$ are two renormalization vectors, which can be computed using a small number of matrix multiplications via Sinkhorn-Knopp Iteration [24], and $\varepsilon = 0.05$ trades off convergence speed with closeness to the original transport problem. In short, by mapping data samples into a few clusters under the constraints $\mathcal{Q}'^c$, we pursue *sparsity* and *expressivity* [58, 59], making class sub-centroids representative of the dataset.

Training of DNC = Supervised Representation Learning + Automatic Sub-class Pattern Mining. Ideally, according to class-wise cluster assignments $\{\boldsymbol{Q}^c\}_{c=1}^C$, we can get totally CK sub-centroids $\{\boldsymbol{p}_k^c\}_{c,k=1}^{C,K}$, *i.e.*, mean feature vectors of the training data in the CK clusters. Then the training target becomes as:

$$\mathcal{L} = \frac{1}{N} \sum_{n=1}^N - \log p(y_n | x_n), \ \ p(y|x) = \frac{\exp\big(-\min(\{\langle \boldsymbol{x}, \boldsymbol{p}_k^y\rangle\}_{k=1}^K)\big)}{\sum_{c \in \mathcal{Y}} \exp\big(-\min(\{\langle \boldsymbol{x}, \boldsymbol{p}_k^c\rangle\}_{k=1}^K)\big)}. \tag{7}$$

Comparing (2) and (7), as the class sub-centroids $\{\boldsymbol{p}_k^c\}_{c,k}$ are derived solely from data representations, DNC learns visual recognition by directly optimizing the representation f, instead of the parametric classifier l. Moreover, with such a nonparametric, distance-based scheme, DNC builds a closer link to metric learning [86–89]; DNC can even be viewed as learning a metric function f to compare data samples $\{x_n\}_n$, under the guidance of the corresponding semantic labels $\{y_n\}_n$.

During training, DNC alternates two steps iteratively: **i)** class-wise clustering (5) for automatic sub-centroid discovery, and **ii)** sub-centroid based classification for supervised representation learning (7). Through clustering, DNC probes underlying data distribution of each class, and produces informative sub-centroids by aggregating statistics from data clusters. With the semantic label, DNC directly optimizes the representation by adjusting the arrangement between sub-centroids and data samples. The enhanced representation in turn helps to find more informative sub-centroids, benefiting classification eventually. As such, DNC conducts *unsupervised sub-class pattern discovery* during *supervised representation learning*, distinguishing it from most (if not all) of current visual recognition models.

Since the latent representation f evolves continually during training, class sub-centroids should be synchronized, which requires performing class-wise clustering over all training data after each batch update. This is highly expensive on large datasets, even though Sinkhorn-Knopp iteration [24] based

clustering (6) is highly efficient. To circumvent the expensive, offline sub-centroid estimation, we adopt *momentum update* and *online* clustering. Specifically, at each training iteration, we conduct class-wise clustering on the current batch and update each sub-centroid as:

$$\boldsymbol{p}_k^c \leftarrow \mu \boldsymbol{p}_k^c + (1 - \mu) \bar{\boldsymbol{x}}_k^c, \tag{8}$$

where $\mu \in [0, 1]$ is a momentum coefficient, and $\bar{\boldsymbol{x}}_k^c \in \mathbb{R}^d$ is the mean feature vector of data assigned to (c, k)-cluster in current batch. As such, the sub-centroids can be up-to-date with the change of parameters. Though effective enough in most cases, batch-wise clustering could not extend to a large number of classes, *e.g.*, when training on ImageNet [9] with 1K classes using batch size 256, not all the classes/clusters are present in a batch. To solve this, we store features from several prior batches in a memory, and do clustering on both the memory and current batch. DNC can be trained by gradient backpropagation in small-batch setting, with negligible lagging ($\sim$5% training delay on ImageNet).

Versatility. DNC is a general framework; it can be effortless integrated into any parametric classifier based DNNs, coming with minimal architecture change, *i.e.*, removing the parametric softmax layer. However, DNC changes the classification decision-making mode, reforms the training regime, and makes the reasoning process more transparent, without slowing the inference speed. DNC can be applied to various visual recognition tasks, including image classification (§4.1) and segmentation (§4.2).

Transferability. As a nonparametric scheme, DNC can handle an arbitrary number of classes with fixed output dimensionality (d); all the knowledge learnt on a source task (*e.g.*, ImageNet classification with 1K classes) are stored as a constant amount of parameters in f, and thus can be *completely* transferred for a new task (*e.g.*, Cityscapes [26] segmentation with 19 classes), under the "pre-training and fine-tuning" paradigm. In a similar setting, the parametric counterpart has to discard 2M parameters during transfer learning ($d=2048$ when using ResNet101 [2]). See §4.2 for related experiments.

Ad-hoc Explainability. DNC is a transparent classifier that has a built-in case-based reasoning process, as the sub-centroids are summarized from real observations and actually used during classification. So far we only discussed the case where the sub-centroids are considered as average mean feature vectors of a few training samples with similar patterns. When restricting the sub-centroids to be elements of the training set (*i.e.*, representative training images), DNC naturally comes with human-understandable explanations for each prediction, and the explanations are loyal to the internal decision mode and not created post-hoc. Studies regarding ad-hoc explainability are given in §4.3.

4 EXPERIMENT

4.1 EXPERIMENTS ON IMAGE CLASSIFICATION

Dataset. The evaluation for image classification is carried out on CIFAR-10 [33] and ImageNet [9].

Network Architecture. For completeness, we craft DNC on popular CNN-based ResNet50/100 [2] and recent Transformer-based Swin-Small/-Base [3]. Note that, we only remove the last linear classification layer, and the final output dimensionality of DNC is as many as the last layer feature of the parametric counterpart, *i.e.*, 2,048 for ResNet50/100, 768 for Swin-Small, and 1,024 for Swin-Base.

Training. We use mmclassification[1] as codebase and follow the *default* training settings. For CIFAR-10, we train ResNet for 200 epochs, with batch size 128. The memory size for DNC models is set as 100 batches. For ImageNet, we train 100 and 300 epochs with batch size 16 for ResNet and Swin, respectively. The initial learning rates of ResNet and Swin are set as 0.1 and 0.0005, scheduled by a step policy and polynomial annealing policy, respectively. Limited by our GPU capacity, the memory sizes are set as 1,000 and 500 batches for DNC versions of ResNet and Swin, respectively. Other hyperparameters are empirically set as: $K=4$ and $\mu=0.999$. Models are trained *from scratch* on eight V100 GPUs.

Results on CIFAR-10. Table 1 compares DNC with the parametric counterpart, based on the most representative CNN network architecture, *i.e.*, ResNet. As seen, DNC obtains better performance: DNC is **0.23**% higher on ResNet50, and **0.24**% higher on ResNet101, using fewer learnable parameters. With the exact same backbone architectures and training settings, one can safely attribute the performance gain to DNC.

Table 1: **Classification `top-1` accuracy** on CIFAR-10[33]`test`. #Params: the number of learnable parameters (same for other tables).

Method	Backbone	#Params	top-1
ResNet [2]	ResNet50	23.52M	95.55%
DNC-ResNet		23.50M	**95.78**%
ResNet [2]	ResNet101	42.51M	95.58%
DNC-ResNet		42.49M	**95.82**%

---

[1]https://github.com/open-mmlab/mmclassification

Results on ImageNet. Table 2 illustrates again our compelling results over different vision network architectures. In terms of `top-1` acc., our DNC exceeds the parametric classifier by **0.29**% and **0.28**% on ResNet50 and ResNet101, respectively. DNC also obtains promising results with Transformer architecture: **83.26**% *vs* 83.02% on Swin-S, **83.68**% *vs* 83.36% on Swin-B. These results are impressive, considering the transparent, case-based reasoning nature of DNC. One may notice another nonparametric, k-NN classi-

Table 2: **Classification `top-1` and `top-5` accuracy** on ImageNet [9] `val`.

Method	Backbone	#Params	top-1	top-5
ResNet [2]	ResNet50	25.56M	76.20%	93.01%
DNC-ResNet		23.51M	**76.49**%	**93.08**%
ResNet [2]	ResNet101	44.55M	77.52%	93.06%
DNC-ResNet		42.50M	**77.80**%	**93.85**%
Swin [3]	Swin-S	49.61M	83.02%	96.29%
DNC-Swin		48.84M	**83.26**%	**96.40**%
Swin [3]	Swin-B	87.77M	83.36%	96.44%
DNC-Swin		86.75M	**83.68**%	**97.02**%

fier [49] reports 76.57% `top-1` acc., based on ResNet50. However, [49] is trained with 130 epochs; in this setting, DNC gains 76.64%. Moreover, as mentioned in §2, [49] poses huge storage demand, *i.e.*, retaining the whole ImageNet training set (*i.e.*, 1.2M images) to perform the k-NN decision rule, and suffers from very low efficiency, caused by extensive comparisons between each test image and all the training images. These limitations prevent the adoption of [49] in real application scenarios. In contrast, DNC only relies on a small set of class representatives (*i.e.*, four sub-centroids per class) for classification decision-making and causes no extra computation budget during network deployment.

4.2 EXPERIMENTS ON SEMANTIC SEGMENTATION

Dataset. The evaluation for semantic segmentation is carried out on ADE20K [37] and Cityscapes [26].

Segmentation Network Architecture. For comprehensive evaluation, we approach DNC on three famous segmentation models (*i.e.*, FCN [34], DeepLab$_{V3}$ [35], UperNet [36]), using two backbone architectures (*i.e.*, ResNet101 [2] and Swin-B [3]). For the segmentation models, the only architectural modification is the removal of the "segmentation head" (*i.e.*, 1×1 conv based, pixel-wise classification layer). For the backbone networks, we respectively adopt parametric classifier based and our nonparametric, DNC based versions, which are both trained on ImageNet [9] and reported in Table 2, for initialization. Thus for each segmentation model, we derive four variants from the different combinations of parametric and DNC versions of the backbone and segmentation network architectures.

Training. We adopt `mmsegmentation`[2] as the codebase, and follow the *default* training settings. We train FCN and DeepLab$_{V3}$ with ResNet101 using SGD optimizer with an initial learning rate 0.1, and UperNet with Swin-B using AdamW with an initial learning rate 6e-5. For all the models, the learning rate is scheduled following a polynomial annealing policy. As common practices [90, 91], we train the models on ADE20K `train` with crop size 512×512 and batch size 16; on Cityscapes `train` with crop size 769×769 and batch size 8. All the models are trained for 160K iterations on both datasets. Standard data augmentation techniques are used, including scale and color jittering, flipping, and cropping. The hyper-parameters of DNC are by default set as: $K = 10$ and $\mu = 0.999$.

Performance on Segmentation. As summarized in Table 3, our DNC segmentation models, no matter whether using DNC based backbones, obtain better performance over parametric competitors, *i.e.*, FCN + ResNet101, DeepLab$_{V3}$ + ResNet101, UperNet + Swin-B, across different segmentation and backbone network architectures. Taking as an example the famous FCN, the original version gains 39.91% and 75.6% `mIoU` on ADE20K and Cityscapes, respectively. By comparison, with the same backbone – ResNet101, DNC-FCN boosts the scores to 41.1%

Table 3: **Segmentation mIoU score** on ADE20K [37] `val` and Cityscapes [26] `val` (`top-1` acc. on ImageNet [9] `val` of backbones are also reported for reference).

Method	Backbone	ImageNet top-1 acc.	#Params	ADE20K mIoU	Cityscapes mIoU
FCN [34]	ResNet101 [2]	77.52%	68.6M	39.9%	75.6%
	DNC-ResNet101	77.80%	68.6M	40.4%↑0.5	76.3%↑0.7
DNC-FCN	ResNet101 [2]	77.52%	68.5M	41.1%↑1.2	76.7%↑1.1
	DNC-ResNet101	77.80%	68.5M	**42.3**%↑2.4	**77.5**%↑1.9
DeepLab$_{V3}$ [35]	ResNet101 [2]	77.52%	62.7M	44.1%	78.1%
	DNC-ResNet101	77.80%	62.7M	44.6%↑0.5	78.7%↑0.6
DNC-DeepLab$_{V3}$	ResNet101 [2]	77.52%	62.6M	45.0%↑0.9	79.1%↑1.0
	DNC-ResNet101	77.80%	62.6M	**45.7**%↑1.6	**79.8**%↑1.7
UperNet [36]	Swin-B [3]	83.36%	90.6M	48.0%	79.8%
	DNC-Swin-B	83.68%	90.6M	48.4%↑0.4	80.1%↑0.3
DNC-UperNet	Swin-B [3]	83.36%	90.5M	48.6%↑0.6	80.5%↑0.7
	DNC-Swin-B	83.68%	90.5M	**50.5**%↑2.5	**80.9**%↑1.1

and 76.7%. When turning to DNC pre-trained backbone – DNC-ResNet101, our DNC-FCN outperforms again its parametric counterpart – FCN, *i.e.*, 42.3% *vs* 40.4% on ADE20K, 77.5% *vs* 76.3% on Cityscapes. Similar trends can be also observed for DeepLab$_{V3}$ and UperNet.

---

[2]https://github.com/open-mmlab/mmsegmentation

Analysis on Transferability. One appealing feature of DNC is its strong transferability, as DNC learns classification by directly comparing data samples in the feature space. The results in Table 3 also evidence this point. For example, DeepLab$_{V3}$ – even a parametric classifier based segmentation model – can achieve large performance gains, *i.e.*, 44.6% *vs* 44.1% on ADE20K, 78.7% *vs* 78.1% on Cityscapes, after using DNC-ResNet101 for fine-tuning. When it comes to DNC-DeepLab$_{V3}$, better performance can be achieved, after replacing ResNet101 with DNC-ResNet101, *i.e.*, 45.7% *vs* 45.0% on ADE20K, 79.8% *vs* 79.1% on Cityscapes. We speculate this is because, when the segmentation and backbone networks are both built upon DNC, the model only needs to adapt the original representation space to the target task, without learning any extra new parameters. Also, these impressive results reflect the innovative opportunity of applying our DNC for more downstream visual recognition tasks, either as a new classification network architecture or a strong and transferable backbone.

4.3 STUDY OF AD-HOC EXPLAINABILITY

So far, we have empirically showed that, by inheriting the intuitive power of Nearest Centroids and the strong representation learning ability of DNNs, DNC can serve as a transparent yet powerful tool for visual recognition tasks with improved transferability. When anchoring the class sub-centroids to real observations (*i.e.*, actual images from the training dataset), instead of selecting them as cluster centers (*i.e.*, mean features of a set of training images), one may expect DNC can gain stronger, ad-hoc explainability. Next we will show this is indeed possible, only at negligible performance cost.

Experimental Setup. We still train DNC version of ResNet50 on ImageNet `train` for 100 epochs. In the first 90 epochs, the model is trained in a standard manner, *i.e.*, computing the class sub-centroids as cluster centers. Then we anchor each sub-centroid to its closest training image, based on the cosine similarity of features. In the final 10 epochs, the sub-centroids are only updated as the features of their anchored training images. Besides this, all the other training settings are as normal. In this way, we can get a more interpretable DNC-ResNet50.

Interpretable Class Sub-centroids. The top of Fig. 3 plots our discovered sub-centroid images for four

Figure 3: *Top:* sub-centroid images. *Bottom:* rule created for "goose".

ImageNet classes. These representative images are diverse in appearance, viewpoints, illuminations, scales, *etc.*, characterizing their corresponding classes and allowing humans to view and understand.

Performance with Improved Interpretability. We then report the score of our DNC-ResNet50 based on the interpretable class representatives on ImageNet `val`. As shown in Table 4, enforcing the class sub-centroids as real training images only brings marginal performance degradation (*e.g.*, 76.49%→ 76.37% `top-1` acc.), while coming with better interpretability. More impressively, ***our explainable DNC-ResNet50 even outperforms the vanilla black-box ResNet50***, *e.g.*, 76.37% *vs* 76.20%.

Table 4: **Classification `top-1` and `top-5` accuracy** on ImageNet [9] `val`, using cluster center *vs* resembling real observation as class sub-centroids, based on DNC-ResNet50 architecture.

Sub-centroid	Architecture	top-1	top-5
cluster center	**DNC**-ResNet50	76.49%	93.08%
real observation		76.37%	93.04%
-	ResNet50[2]	76.20%	93.01%

Explain Inner Decision-Making Mode based on *IF* ⋯ *Then* Rules. With the simple Nearest Centroids mechanism, we can use the representative images to form a set of *IF* ⋯ *Then* rules [4], so as to intuitively interpret the inner decision-making mode of DNC for human users. In particular, let $\hat{I}$ denote a sub-centroid image for class c, $\check{I}_{1:T}$ representative images for all the other classes, and I a query image. One linguistic logical *IF* ⋯ *Then* rule can be generated for $\hat{I}$:

$$\text{IF } \left([I, \hat{I}] > [I, \check{I}_1] \text{ AND } [I, \hat{I}] > [I, \check{I}_2] \text{ AND} \cdots \text{AND } [I, \hat{I}] > [I, \check{I}_T]\right) \text{ THEN (class } c\text{),} \quad (9)$$

where $[\cdot, \cdot]$ stands for similarity, given by DNC. The final rule for class c is created by combining all the rules of K sub-centroid images $\hat{I}_{1:K}$ of class c (see Fig. 3 bottom):

$$\begin{aligned}
&\text{IF } \left([I, \hat{I}_1] > [I, \check{I}_1] \text{ AND} \cdots \text{AND } [I, \hat{I}_1] > [I, \check{I}_T]\right) \\
&\text{OR } \left([I, \hat{I}_2] > [I, \check{I}_1] \text{ AND} \cdots \text{AND } [I, \hat{I}_2] > [I, \check{I}_T]\right) \\
&\text{OR } \cdots \text{OR } \left([I, \hat{I}_K] > [I, \check{I}_1] \text{ AND} \cdots \text{AND } [I, \hat{I}_K] > [I, \check{I}_T]\right) \text{ THEN (class } c\text{).}
\end{aligned} \quad (10)$$

Figure 4: DNC can provide (dis)similarity-based interpretation. For the two test samples, we only plot the normalized similarities for their corresponding closest sub-centroids from top-4 scoring classes.

Table 5: A set of ablative experiments on ImageNet [9] `val` and ADE20K [37] `val`.

K	ImageNet top-1	ImageNet top-5	K	ADE20K mIoU
1	77.31%	93.01%	1	43.2%
2	77.54%	93.32%	5	44.0%
3	77.68%	93.63%	**10**	**44.3%**
4	**77.80%**	**93.85%**	20	44.0%

(a) Number of sub-centroids (K) for each class

Memory (#*batch*)	ImageNet top-1	ImageNet top-5
0	77.49%	93.09%
700	77.58%	93.16%
800	77.64%	93.35%
900	77.75%	93.67%
1000	**77.80%**	**93.85%**

(b) Memory size

μ	ImageNet top-1	ImageNet top-5	ADE20K mIoU
0	73.82%	93.02%	42.7%
0.9	76.41%	93.07%	43.6%
0.99	77.33%	93.51%	44.0%
0.999	**77.80%**	**93.85%**	**44.3%**
0.9999	77.31%	93.48%	44.2%

(c) Momentum coefficient (μ)

Interpret Prediction Based on (Dis)similarity to Sub-centroid Images. Based on the interpretable class representatives, DNC can explain its predictions by letting users view and verify its computed (dis)similarity between query and class sub-centroid images. As shown in Fig. 4(a), an observation is correctly classified, as DNC thinks it looks (more) like a particular exemplar of "*toucan*". However, in Fig. 4(b), DNC struggles to assign the observation to two exemplars from "*white wolf*" and "*kuvasz*" respectively, and makes a wrong decision finally. Though users are unclear how DNC maps an image to feature, they can easily understand the decision-making mode [43] (*e.g.*, why is one class predicted over another), and verify the calculated (dis)similarity – the evidence for classification decision.

4.4 DIAGNOSTIC EXPERIMENT

To perform extensive ablation experiments, we train ResNet101 classification and DeepLab$_{V3}$ segmentation models for 100 epochs and 80K iterations, on ImageNet and ADE20K, respectively.

Class Sub-centroids. Table 5a studies the impact of the number of class sub-centroids (K) for each class. When $K = 1$, each class is represented by its centroid – the average feature vector of all the training samples of the class (Eq. 3), without clustering. The corresponding baseline obtains 77.31% `top-1` acc. and 43.2% `mIoU` for classification and segmentation, respectively. For classification, increasing K from 1 to 4 leads to better performance (*i.e.*, 77.31% → 77.80%). This supports our hypothesis that one single class weight/center is far enough to capture the underlying data distribution and proves the efficacy of our clustering based sub-class pattern mining. We stop using $K > 4$ as the required memory exceeds the computational limit of our hardware. We find similar trends on segmentation; using more sub-centroids ($K: 1 \to 10$) brings noticeable performance boost: 43.2% → 44.3%. However, increasing K above 10 provides marginal or even negative gain. This may be because over-clustering finds some insignificant patterns, which are trivial or harmful for decision-making.

External Memory. We next study the influence of the external memory, only used in image classification. As shown in Table 5b, DNC gradually improves the performance as the increase of the memory size. It reaches 77.80% `top-1` acc. at size 1000. However, the results are still not reaching the performance saturating point, but rather the upper limit of our hardware's computational budget.

Momentum Update. Last, we ablate the effect of the momentum coefficient μ (Eq. 8) that controls the speed of sub-centroid online updating. From Table 5c we find the behaviors of μ are consistent in both tasks. In particular, DNC performs well with larger coefficients (*i.e.*, $\mu \in [0.999, 0.9999]$), signifying the importance of slow updating. The performance degrades when $\mu \in [0.9, 0.99]$, and encounters a large drop when $\mu = 0$ (*i.e.*, only using batch sub-centroids as approximations).

5 CONCLUSION

We present deep nearest centroids (DNC), building upon the classic idea of classifying data samples according to nonparametric class representatives. Compared to classic parametric models, DNC has merits in: **i)** systemic simpli- city by bringing the intuitive Nearest Centroids mechanism to DNNs; **ii)** automated discovery of latent data structure using within-class clustering; **iii)** direct supervision of representation learning, boosted by unsupervised sub-pattern mining; **iv)** improved transferability that lossless transfers learnable knowledge across tasks; and **v)** ad-hoc explainability by anchoring class exemplars with real observations. Experiments confirm the efficacy and enhanced interpretability.

REFERENCES

[1] Simonyan, K., Zisserman, A.: Very deep convolutional networks for large-scale image recognition. In: ICLR (2015) 1

[2] He, K., Zhang, X., Ren, S., Sun, J.: Deep residual learning for image recognition. In: CVPR (2016) 1, 2, 3, 6, 7, 8, 14, 16, 17, 18, 19

[3] Liu, Z., Lin, Y., Cao, Y., Hu, H., Wei, Y., Zhang, Z., Lin, S., Guo, B.: Swin transformer: Hierarchical vision transformer using shifted windows. In: ICCV (2021) 1, 2, 6, 7, 14, 16, 17, 22, 23

[4] Angelov, P., Soares, E.: Towards explainable deep neural networks (xdnn). Neural Networks **130**, 185–194 (2020) 1, 3, 8

[5] Li, O., Liu, H., Chen, C., Rudin, C.: Deep learning for case-based reasoning through prototypes: A neural network that explains its predictions. In: AAAI (2018) 1, 3

[6] Hayashi, H., Uchida, S.: A discriminative gaussian mixture model with sparsity. In: ICLR (2021) 1

[7] Zhou, T., Wang, W., Konukoglu, E., Van Gool, L.: Rethinking semantic segmentation: A prototype view. In: CVPR (2022) 1

[8] Mettes, P., van der Pol, E., Snoek, C.: Hyperspherical prototype networks. In: NeurIPS (2019) 1, 3

[9] Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., Huang, Z., Karpathy, A., Khosla, A., Bernstein, M.S., Berg, A.C., Li, F.: Imagenet large scale visual recognition challenge. IJCV **115**(3), 211–252 (2015) 1, 2, 3, 6, 7, 8, 9, 16, 17, 18, 19, 20

[10] Fix, E., Hodges Jr, J.L.: Discriminatory analysis - nonparametric discrimination: Small sample performance. Tech. rep., California Univ Berkeley (1952) 1, 3

[11] Cover, T., Hart, P.: Nearest neighbor pattern classification. IEEE TIT **13**(1), 21–27 (1967) 3

[12] Kolodner, J.L.: An introduction to case-based reasoning. Artificial Intelligence Review **6**(1), 3–34 (1992) 1, 3

[13] Kohonen, T.: Learning vector quantization. In: Self-Organizing Maps, pp. 175–189 (1995)

[14] Chaudhuri, B.: A new definition of neighborhood of a point in multi-dimensional space. Pattern Recognition Letters **17**(1), 11–17 (1996)

[15] Webb, A.R.: Statistical pattern recognition. John Wiley & Sons (2003) 1, 3

[16] Kim, B., Rudin, C., Shah, J.A.: The bayesian case model: A generative approach for case-based reasoning and prototype classification. In: NeurIPS (2014) 1

[17] Newell, A., Simon, H.A., et al.: Human problem solving, vol. 104 (1972) 1, 2, 3

[18] Rosch, E.H.: Natural categories. Cognitive Psychology **4**(3), 328–350 (1973) 5

[19] Aamodt, A., Plaza, E.: Case-based reasoning: Foundational issues, methodological variations, and system approaches. AI Communications **7**(1), 39–59 (1994) 1, 2

[20] Slade, S.: Case-based reasoning: A research paradigm. AI magazine **12**(1), 42–42 (1991) 1

[21] Sánchez, J.S., Pla, F., Ferri, F.J.: On the use of neighbourhood-based non-parametric classifiers. Pattern Recognition Letters **18**(11-13), 1179–1186 (1997) 3

[22] Gou, J., Yi, Z., Du, L., Xiong, T.: A local mean-based k-nearest centroid neighbor classifier. The Computer Journal **55**(9), 1058–1071 (2012)

[23] Mensink, T., Verbeek, J., Perronnin, F., Csurka, G.: Distance-based image classification: Generalizing to new classes at near-zero cost. IEEE TPAMI **35**(11), 2624–2637 (2013) 1

[24] Cuturi, M.: Sinkhorn distances: Lightspeed computation of optimal transport. In: NeurIPS (2013) 2, 5

[25] Asano, Y.M., Rupprecht, C., Vedaldi, A.: Self-labelling via simultaneous clustering and representation learning. In: ICLR (2020) 2, 5

[26] Cordts, M., Omran, M., Ramos, S., Rehfeld, T., Enzweiler, M., Benenson, R., Franke, U., Roth, S., Schiele, B.: The cityscapes dataset for semantic urban scene understanding. In: CVPR (2016) 2, 3, 6, 7, 17, 22, 23

[27] Biehl, M., Hammer, B., Villmann, T.: Prototype-based models in machine learning. Wiley Interdisciplinary Reviews: Cognitive Science **7**(2), 92–111 (2016) 2, 3, 5

[28] Simonyan, K., Vedaldi, A., Zisserman, A.: Deep inside convolutional networks: Visualising image classification models and saliency maps. arXiv preprint arXiv:1312.6034 (2013) 2, 3

[29] Zeiler, M.D., Fergus, R.: Visualizing and understanding convolutional networks. In: ECCV (2014)

[30] Zhou, B., Khosla, A., Lapedriza, A., Oliva, A., Torralba, A.: Learning deep features for discriminative localization. In: CVPR (2016) 2, 3

[31] Lipton, Z.C.: The mythos of model interpretability: In machine learning, the concept of interpretability is both important and slippery. Queue **16**(3), 31–57 (2018) 2

[32] Rudin, C.: Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. Nature Machine Intelligence **1**(5), 206–215 (2019) 2, 3

[33] Krizhevsky, A., Hinton, G.: Learning multiple layers of features from tiny images. Technical report, University of Toronto (2009) 2, 3, 6, 14, 17, 18

[34] Long, J., Shelhamer, E., Darrell, T.: Fully convolutional networks for semantic segmentation. In: CVPR (2015) 3, 7, 16, 17

[35] Chen, L.C., Papandreou, G., Schroff, F., Adam, H.: Rethinking atrous convolution for semantic image segmentation. arXiv preprint arXiv:1706.05587 (2017) 3, 7, 16, 17

[36] Xiao, T., Liu, Y., Zhou, B., Jiang, Y., Sun, J.: Unified perceptual parsing for scene understanding. In: ECCV (2018) 3, 7, 16, 17, 22, 23

[37] Zhou, B., Zhao, H., Puig, X., Fidler, S., Barriuso, A., Torralba, A.: Scene parsing through ade20k dataset. In: CVPR (2017) 3, 7, 9, 17, 22, 23

[38] Friedman, J.H.: The elements of statistical learning: Data mining, inference, and prediction. Springer (2009) 3

[39] Hand, D.J., Yu, K.: Idiot's bayes—not so stupid after all? International Statistical Review **69**(3), 385–398 (2001) 3

[40] Breiman, L.: Random forests. Machine Learning **45**(1), 5–32 (2001) 3

[41] Cortes, C., Vapnik, V.: Support-vector networks. Machine Learning **20**(3), 273–297 (1995) 3

[42] LeCun, Y., Bengio, Y., Hinton, G.: Deep learning. nature **521**(7553), 436–444 (2015) 3

[43] Rudin, C., Chen, C., Chen, Z., Huang, H., Semenova, L., Zhong, C.: Interpretable machine learning: Fundamental principles and 10 grand challenges. Statistics Surveys **16**, 1–85 (2022) 3, 5, 9

[44] Boiman, O., Shechtman, E., Irani, M.: In defense of nearest-neighbor based image classification. In: CVPR (2008) 3

[45] Guillaumin, M., Mensink, T., Verbeek, J., Schmid, C.: Tagprop: Discriminative metric learning in nearest neighbor models for image auto-annotation. In: ICCV (2009) 3

[46] Lippmann, R.P.: Pattern classification using neural networks. IEEE Communications Magazine **27**(11), 47–50 (1989) 3

[47] Salakhutdinov, R., Hinton, G.: Learning a nonlinear embedding by preserving class neighbourhood structure. In: Artificial Intelligence and Statistics. pp. 412–419 (2007)

[48] Papernot, N., McDaniel, P.: Deep k-nearest neighbors: Towards confident, interpretable and robust deep learning. arXiv preprint arXiv:1803.04765 (2018) 3

[49] Wu, Z., Efros, A.A., Yu, S.X.: Improving generalization via scalable neighborhood component analysis. In: ECCV (2018) 3, 7

[50] Garcia, S., Derrac, J., Cano, J., Herrera, F.: Prototype selection for nearest neighbor classification: Taxonomy and empirical study. IEEE TPAMI **34**(3), 417–435 (2012) 3

[51] Yang, H.M., Zhang, X.Y., Yin, F., Liu, C.L.: Robust classification with convolutional prototype learning. In: CVPR (2018) 3

[52] Guerriero, S., Caputo, B., Mensink, T.: Deepncm: Deep nearest class mean classifiers. In: ICLR workshop (2018) 3

[53] Snell, J., Swersky, K., Zemel, R.S.: Prototypical networks for few-shot learning. In: NeurIPS (2017) 3

[54] Dong, N., Xing, E.P.: Few-shot semantic segmentation with prototype learning. In: BMVC (2018) 3

[55] Jetley, S., Romera-Paredes, B., Jayasumana, S., Torr, P.: Prototypical priors: From improving classification to zero-shot learning. arXiv preprint arXiv:1512.01192 (2015) 3

[56] Xu, W., Xian, Y., Wang, J., Schiele, B., Akata, Z.: Attribute prototype network for zero-shot learning. In: NeurIPS (2020) 3

[57] Rebuffi, S.A., Kolesnikov, A., Sperl, G., Lampert, C.H.: icarl: Incremental classifier and representation learning. In: CVPR (2017) 3

[58] Quattoni, A., Collins, M., Darrell, T.: Transfer learning for image classification with sparse prototype representations. In: CVPR (2008) 3, 5

[59] Biehl, M., Hammer, B., Schneider, P., Villmann, T.: Metric learning for prototype-based classification. In: Innovations in Neural Information Paradigms and Applications, pp. 183–199 (2009) 3, 5

[60] Erhan, D., Bengio, Y., Courville, A., Vincent, P.: Visualizing higher-layer features of a deep network. University of Montreal **1341**(3), 1 (2009) 3

[61] Mahendran, A., Vedaldi, A.: Understanding deep image representations by inverting them. In: CVPR (2015)

[62] Yosinski, J., Clune, J., Nguyen, A., Fuchs, T., Lipson, H.: Understanding neural networks through deep visualization. arXiv preprint arXiv:1506.06579 (2015)

[63] Bach, S., Binder, A., Montavon, G., Klauschen, F., Müller, K.R., Samek, W.: On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. PloS one **10**(7), e0130140 (2015)

[64] Shrikumar, A., Greenside, P., Kundaje, A.: Learning important features through propagating activation differences. In: ICML (2017)

[65] Selvaraju, R.R., Cogswell, M., Das, A., Vedantam, R., Parikh, D., Batra, D.: Grad-cam: Visual explanations from deep networks via gradient-based localization. In: ICCV (2017) 3

[66] Ribeiro, M.T., Singh, S., Guestrin, C.: "why should i trust you?" explaining the predictions of any classifier. In: KDD (2016) 3

[67] Zintgraf, L.M., Cohen, T.S., Adel, T., Welling, M.: Visualizing deep neural network decisions: Prediction difference analysis. In: ICLR (2017)

[68] Koh, P.W., Liang, P.: Understanding black-box predictions via influence functions. In: ICML (2017)

[69] Lundberg, S.M., Lee, S.I.: A unified approach to interpreting model predictions. In: NeurIPS (2017) 3

[70] Laugel, T., Lesot, M.J., Marsala, C., Renard, X., Detyniecki, M.: The dangers of post-hoc interpretability: Unjustified counterfactual explanations. In: IJCAI (2019) 3

[71] Arrieta, A.B., Díaz-Rodríguez, N., Del Ser, J., Bennetot, A., Tabik, S., Barbado, A., García, S., Gil-López, S., Molina, D., Benjamins, R., et al.: Explainable artificial intelligence (xai): Concepts, taxonomies, opportunities and challenges toward responsible ai. Information Fusion **58**, 82–115 (2020) 3

[72] Chen, C., Li, O., Tao, D., Barnett, A., Rudin, C., Su, J.K.: This looks like that: deep learning for interpretable image recognition. In: NeurIPS (2019) 3

[73] Alvarez Melis, D., Jaakkola, T.: Towards robust interpretability with self-explaining neural networks. In: NeurIPS (2018) 3

[74] Kim, B., Wattenberg, M., Gilmer, J., Cai, C., Wexler, J., Viegas, F., et al.: Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In: ICML (2018) 3

[75] Wang, T.: Gaining free or low-cost interpretability with interpretable partial substitute (2019) 3

[76] Subramanian, A., Pruthi, D., Jhamtani, H., Berg-Kirkpatrick, T., Hovy, E.: Spine: Sparse interpretable neural embeddings. In: AAAI (2018) 3

[77] Chen, X., Duan, Y., Houthooft, R., Schulman, J., Sutskever, I., Abbeel, P.: Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In: NeurIPS (2016) 3

[78] You, S., Ding, D., Canini, K., Pfeifer, J., Gupta, M.: Deep lattice networks and partial monotonic functions. In: NeurIPS (2017) 3

[79] Ming, Y., Xu, P., Qu, H., Ren, L.: Interpretable and steerable sequence learning via prototypes. In: KDD (2019) 3

[80] Arık, S.O., Pfister, T.: Protoattend: Attention-based prototypical learning. Journal of Machine Learning Research **21**, 1–35 (2020) 3

[81] Pang, T., Xu, K., Dong, Y., Du, C., Chen, N., Zhu, J.: Rethinking softmax cross-entropy loss for adversarial robustness. In: ICLR (2020) 4

[82] Zhang, X., Zhao, R., Qiao, Y., Li, H.: Rbf-softmax: Learning deep representative prototypes with radial basis function softmax. In: ECCV (2020) 4

[83] Rosch, E.: Cognitive representations of semantic categories. Journal of Experimental Psychology: General **104**(3), 192 (1975) 5

[84] Knowlton, B.J., Squire, L.R.: The learning of categories: Parallel brain systems for item memory and category knowledge. Science **262**(5140), 1747–1749 (1993) 5

[85] Knight, P.A.: The sinkhorn–knopp algorithm: convergence and applications. SIAM Journal on Matrix Analysis and Applications **30**(1), 261–275 (2008) 5

[86] Hadsell, R., Chopra, S., LeCun, Y.: Dimensionality reduction by learning an invariant mapping. In: CVPR (2006) 5

[87] Sohn, K.: Improved deep metric learning with multi-class n-pair loss objective. In: NeurIPS (2016)

[88] Kaya, M., Bilge, H.Ş.: Deep metric learning: A survey. Symmetry **11**(9), 1066 (2019)

[89] Boudiaf, M., Rony, J., Ziko, I.M., Granger, E., Pedersoli, M., Piantanida, P., Ayed, I.B.: A unifying mutual information view of metric learning: cross-entropy vs. pairwise losses. In: ECCV (2020) 5

[90] Xie, E., Wang, W., Yu, Z., Anandkumar, A., Alvarez, J.M., Luo, P.: Segformer: Simple and efficient design for semantic segmentation with transformers. In: NeurIPS (2021) 7

[91] Cheng, B., Schwing, A.G., Kirillov, A.: Per-pixel classification is not all you need for semantic segmentation. In: NeurIPS (2021) 7

[92] Caesar, H., Uijlings, J., Ferrari, V.: Coco-stuff: Thing and stuff classes in context. In: CVPR. pp. 1209–1218 (2018) 14, 16

[93] Sandler, M., Howard, A., Zhu, M., Zhmoginov, A., Chen, L.C.: Mobilenetv2: Inverted residuals and linear bottlenecks. In: CVPR. pp. 4510–4520 (2018) 14, 16

[94] Huh, M., Agrawal, P., Efros, A.A.: What makes imagenet good for transfer learning? arXiv preprint arXiv:1608.08614 (2016) 18

SUMMARY OF THE APPENDIX

This appendix contains additional details for the ICLR 2023 submission, titled *Visual Recognition with Deep Nearest Centroids"*. The appendix is organized as follows:

- §A provides the pseudo code of DNC.
- §B introduces more quantitative results on image classification.
- §C provides additional semantic segmentation results on COCO-Stuff [92] dataset.
- §D presents the corresponding error bars on Tables 1, 2, and 3.
- §E investigates the potential of DNC in sub-categories discovery.
- §F reports additional diagnostic experiments for further investigations on K, update ratio of external memory, ImageNet capacity, and feature size.
- §G depicts more visual examples regarding the ad-hoc explainability of DNC.
- §H plots qualitative semantic segmentation results.
- §I discusses our limitations, societal impact, and directions of our future work.

A PSEUDO CODE OF DNC AND CODE RELEASE

The pseudo-code of DNC is given in Algorithm 1. To guarantee reproducibility, our full implementation shall be publicly released upon paper acceptance.

B MORE EXPERIMENTS ON IMAGE CLASSIFICATION

Additional Results on CIFAR-10 [33]. CIFAR-10 dataset contains 60K (50K/10K for `train`/ `test`) 32×32 colored images of 10 classes. Table 6 reports additional comparison results on CIFAR-10, based on ResNet-18 [2] network architecture. As seen, in terms of `top-1` accuracy, our DNC is **0.94**% higher than the parametric counterpart, under the same training setting.

Table 6: **Classification `top-1` accuracy** on CIFAR-10 [33] `test`. #Params: the number of learnable parameters (same for other tables). See §B for more details.

Method	Backbone	#Params	top-1
ResNet [2]	ResNet18	11.17M	93.55%
DNC-ResNet		11.16M	**94.49**%

Additional Results on CIFAR-100 [33]. Table 7 reports comparison results on CIFAR-100, based on ResNet50 and ResNet101 network architectures [2]. CIFAR-100 dataset has 100 classes with 500 training images and 100 testing images per class. We can find that, DNC obtains consistently better performance, compared to the classic parametric counterpart. Specifically, DNC is **0.10**% higher on ResNet50, and **0.16**% higher on ResNet101, in terms of `top-1` accuracy.

Table 7: **Classification `top-1` accuracy** on CIFAR-100 [33] `test`, using lightweight backbone network architectures : MobileNet-V2 [93], and Swin-T [3]. See §B for more details.

Method	Backbone	#Params	top-1
ResNet [2]	ResNet50	23.71M	79.81%
DNC-ResNet		23.50M	**79.91**%
ResNet [2]	ResNet101	42.70M	79.83%
DNC-ResNet		42.49M	**79.99**%

Algorithm 1 Pseudo-code of DNC in a PyTorch-like style.

```
# P: non-parametric sub-centroids (C x K x D)
# X: feature embeddings (N x D)

# C: number of classes
# K: number of sub-centroids for each class
# R: sinhorn-knopp iteration number
# mu: momentum coefficient (Eq.8)
# epsilon: hyper-parameter in the Sinkhorn-Knopp algorithm (Eq.6)

def DNC(X, label)
    #== Model Prediction and Training Loss (Eq.7) ==#

    # image-to-centroid assignment (N x K x C, Eq.5)
    L = torch.einsum('nd,ckd->nkc', X, P)
    output = torch.amax(L, dim=1)
    loss = CrossEntropyLoss(output, label)

    #======= Sub-centroid Estimation =======#
    for c in range(C)
        init_L = L[...,c]
        Q = online_clustering(init_L)

        # assignments and embeddings for images in class c
        m_c = L[label == c]
        x_c = X[label == c, ...]

        # find images that are assigned to each sub-centroid
        # and correctly classified
        m_c_tile = repeat(m_c, tile=K)
        m_q = Q * m_c_tile

        # find images with label c that are correctly classified
        x_c_tile = repeat(m_c, tile=x_c.shape[-1])
        x_c_q = x_c * x_c_tile
        f = torch.mm(m_q.transpose(), x_c_q)

        # num assignments for each sub-centroid of class c
        n = torch.sum(m_q, dim=0)

        # momentum update (Eq.8)
        if torch.sum(n) > 0:
            P_c = mu * P[c, n != 0, :] + (1-mu) * f[n != 0, :]
            P[c, n != 0, :] = P_c

    return loss

def online_clustering(L, iters=3, epsilon=0.05)
    Q = torch.exp(L / epsilon)
    Q /= torch.sum(Q)

    for _ in range(R):
        # row normalization
        Q /= torch.sum(Q, dim=1, keepdim=True)
        Q /= K

        # column normalization
        Q /= torch.sum(L, dim=0, keepdim=True)
        Q /= N

    # make sure the sum of each column to be 1
    Q *= N

    return one_hot(Q)
```

Additional Results on ImageNet [9] using Lightweight Backbone Network Architectures. Table 8 reports performance on ImageNet [9], using two lightweight backbone architectures: MobileNet-V2 [93], and Swin-T [3]. As can be seen, DNC, again, attributes decent performance. In particular, our DNC is **0.28**% and **0.30**% higher on MobileNet-V2 and Swin-Tiny, respectively. It is worth noticing that DNC can efficiently reduce the number of learnable parameters when the parametric classifier occupies a massive proportion in the original lightweight classification networks. Taking MobileNet-V2 as an example: our DNC reduces the number of learnable parameters from 3.50M to **2.22**M.

Table 8: **Classification `top-1` accuracy** on ImageNet [9] `val`. See §B for more details.

Method	Backbone	#Params	top-1
MobileNet [93]	MobileNet-V2	3.50M	71.76%
DNC-MobileNet		**2.22M**	**72.04**%
Swin [3]	Swin-T	28.29M	81.08%
DNC-Swin		**27.52M**	**81.38**%

C   MORE EXPERIMENTS ON SEMANTIC SEGMENTATION

For through evaluation, we conduct extra experiments on COCO-Stuff [92], a famous semantic segmentation dataset. COCO-Stuff contains 9K/1K images for `train/test` of 80 object classes and 91 stuff classes. Similar to §4.2, we approach DNC on FCN [34], DeepLab$_{V3}$ [35], and UperNet [36], using two backbone architectures, *i.e.*, ResNet101 [2] and Swin-B [3]. All models are obtained by following the standard training settings of COCO-Stuff `train`, *i.e.*, crop size 512×512, batch size 16, and 40K iterations. From Table 9 we can draw similar conclusions: in comparison with the parametric counterpart, DNC produces more precise segments and yields improved transferability.

Table 9: **Segmentation mIoU score** on COCO-Stuff [92]. See §C for more details.

Method	Backbone	COCO-Stuff `test` mIoU
FCN [34]	ResNet101 [2]	32.63%
	DNC-ResNet101	32.89%↑**0.26**
DNC-FCN	ResNet101 [2]	33.04%↑**0.41**
	DNC-ResNet101	**33.49**%↑**0.86**
DeepLab$_{V3}$ [35]	ResNet101 [2]	36.01%
	DNC-ResNet101	36.28%↑**0.27**
DNC-DeepLab$_{V3}$	ResNet101 [2]	36.51%↑**0.50**
	DNC-ResNet101	**36.79**%↑**0.78**
UperNet [36]	Swin-B [3]	42.77%
	DNC-Swin-B	42.84%↑**0.07**
DNC-UperNet	Swin-B [3]	43.13%↑**0.36**
	DNC-Swin-B	**43.29**%↑**0.52**

D   ERROR BARS

In this section, we report standard deviation error bars on Tables 10, 11, and 12 for our main experiments regarding image classification (§4.1) and semantic segmentation (§4.2).

E   EXPERIMENTS ON SUB-CATEGORIES DISCOVERY

Through unsupervised, within-class clustering, our DNC represents each class as a set of automatically discovered class sub-centroids (*i.e.*, cluster center). This allows DNC to better describe

Table 10: **Classification `top-1` accuracy** on CIFAR-10 [33] `test` with error bars.

Method	Backbone	#Params	top-1
ResNet [2]	ResNet50	23.52M	$95.55 \pm (0.14)$%
DNC-ResNet		23.50M	**95.78** $\pm$ **(0.12)**%
ResNet [2]	ResNet101	42.51M	$95.58 \pm (0.13)$%
DNC-ResNet		42.49M	**95.82** $\pm$ **(0.13)**%

Table 11: **Classification `top-1` and `top-5` accuracy** on ImageNet [9] `val` with error bars.

Method	Backbone	#Params	top-1	top-5
ResNet [2]	ResNet50	25.56M	$76.20 \pm (0.10)$%	93.01%
DNC-ResNet		23.51M	**76.49** $\pm$ **(0.09)**%	**93.08**%
ResNet [2]	ResNet101	44.55M	$77.52 \pm (0.11)$%	93.06%
DNC-ResNet		42.50M	**77.80** $\pm$ **(0.10)**%	**93.85**%
Swin [3]	Swin-S	49.61M	$83.02 \pm (0.14)$%	96.29%
DNC-Swin		48.84M	**83.26** $\pm$ **(0.13)**%	**96.40**%
Swin [3]	Swin-B	87.77M	$83.36 \pm (0.12)$%	96.44%
DNC-Swin		86.75M	**83.68** $\pm$ **(0.12)**%	**97.02**%

Table 12: **Segmentation mIoU score** on ADE20K [37] `val` and Cityscapes [26] `val` with error bars.

Method	Backbone	ImageNet top-1 acc.	#Params	ADE20K mIoU	Cityscapes mIoU
FCN [34]	ResNet101 [2]	77.52%	68.6M	$39.9 \pm (0.11)$%	$75.6 \pm (0.13)$%
	DNC-ResNet101	77.80%	68.6M	$40.4 \pm (0.11)$%	$76.3 \pm (0.12)$%
DNC-FCN	ResNet101 [2]	77.52%	68.5M	$41.1 \pm (0.10)$%	$76.7 \pm (0.11)$%
	DNC-ResNet101	77.80%	68.5M	**42.3** $\pm$ **(0.10)**%	**77.5** $\pm$ **(0.11)**%
DeepLab$_{V3}$ [35]	ResNet101 [2]	77.52%	62.7M	$44.1 \pm (0.13)$%	$78.1 \pm (0.12)$%
	DNC-ResNet101	77.80%	62.7M	$44.6 \pm (0.13)$%	$78.7 \pm (0.13)$%
DNC-DeepLab$_{V3}$	ResNet101 [2]	77.52%	62.6M	$45.0 \pm (0.10)$%	$79.1 \pm (0.13)$%
	DNC-ResNet101	77.80%	62.6M	**45.7** $\pm$ **(0.09)**%	**79.8** $\pm$ **(0.12)**%
UperNet [36]	Swin-B [3]	83.36%	90.6M	$48.0 \pm (0.11)$%	$79.8 \pm (0.13)$%
	DNC-Swin-B	83.68%	90.6M	$48.4 \pm (0.10)$ %	$80.1 \pm (0.12)$%
DNC-UperNet	Swin-B [3]	83.36%	90.5M	$48.6 \pm (0.09)$ %	$80.5 \pm (0.10)$%
	DNC-Swin-B	83.68%	90.5M	**50.5** $\pm$ **(0.09)**%	**80.9** $\pm$ **(0.10)**%

the underlying, multimodal data structure and robusty depict for rich intra-class variance. In other words, our DNC can effectively capture sub-class patterns, which is conducive to algorithmic performance. Such a capacity of sub-patter mining is also considered crucial for good transferable features – representations learnt on coarse classes are capable of fine-grained recognition [94].

In order to quantify the ability of DNC for automatic sub-category discovery, we follow the experimental setup posed by [94] – learning the feature embedding using coarse-grained object labels, and evaluating the learned feature using fine-grained object labels. This evaluation strategy allows us to assess the feature learning performance regarding how well the deep model can discover variations within each category. A conjecture is that deep networks that perform well on this test have an exceptional capacity to identify and mine sub-class patterns during training, which the proposed DNC seeks to rigorously establish.

In particular, the network is first trained on coarse-grained labels with the baseline parametric softmax and with our non-parametric DNC using the same network architecture. After training on coarse classes, we use the top-1 nearest neighbor accuracy in the final feature space to measure the accuracy of identifying fine-grained classes. The classification performance evaluated in such setting is referred as **induction accuracy** as in [94]. Next we provide our experimental results on CIFAR100 [33] and ImageNet [9], respectively.

Performance of Sub-category Discovery on CIFAR100. CIFAR100 includes both fine-grained annotations in 100 classes and coarse-grained annotations in 20 classes. We examine sub-category discovery by transferring representation learned from 20 classes to 100 classes. As shown in Table 13, DNC consistently outperforms the parametric counterpart: DNC increases 0.12%, in terms of the standard `top-1` accuracy, on both ResNet50 and ResNet101 architectures. Nevertheless, when transferred to CIFAR100 (*i.e.*, 100 classes) using k-NN, a significant loss occurs on the baseline: 53.22% and 54.31% `top-1` acc. on ResNet50 and ResNet101, respectively. Our features, on the other hand, provide 14.24% and 13.82% improvement over the baseline, achieving 67.46% and 68.13% `top-1` acc. on 100 classes on ResNet50 and ResNet101, respectively. In addition, in comparison the parametric model, our approach results in only a smaller drop in transfer performance, *i.e.*, **-18.87** *vs* -32.99 on ResNet50, and **-18.47** *vs* -32.17 on ResNet101.

Table 13: **Top-1 induction accuracy** on CIFAR-100 [33] test using CIFAR-20 pre-trained models. Numbers reported with k-nearest neighbor classifiers. See §E for more details.

Method	Backbone	20 classes	100 classes
ResNet [2]	ResNet50	86.21%	53.22%
DNC-ResNet		**86.33**%	**67.46**%
ResNet [2]	ResNet101	86.48%	54.31%
DNC-ResNet		**86.60**%	**68.13**%

Performance of Sub-category Discovery on ImageNet. Table 14 provides experimental results of sub-category discovery on ImageNet `val`. As in [94], 127 coarse ImageNet categories are obtained by top-down clustering of 1000 ImageNet categories on WordNet tree. Training on the 127 coarse classes, DNC improves the performance of baseline by 0.10% and 0.03%, achieving 84.39% and 85.91% on ResNet50 and ResNet101, respectively. When transferring to the 1000 ImageNet classes using k-NN, our features provide huge improvements, *i.e.*, 8.98% and 9.29%, over the baseline.

Table 14: **Top-1 induction accuracy** on ImageNet [9] val using ImageNet-127 pre-trained models. Numbers reported with k-nearest neighbor classifiers. See §E for more details.

Method	Backbone	127 classes	1000 classes
ResNet [2]	ResNet50	84.29%	43.23%
DNC-ResNet		84.39%	**52.21%**
ResNet [2]	ResNet101	85.88%	45.31%
DNC-ResNet		85.91%	**54.60%**

The promising transfer results on CIFAR100 and ImageNet serve as strong evidence to suggest that our DNC is capable of automatically discovering meaningful sub-class patterns – latent visual structures that are not explicitly presented in the supervisory signal, and hence handle intra-class variance and boost visual recognition.

F ADDITIONAL DIAGNOSTIC EXPERIMENT

Output Dimensionality. As stated in §4, the final output dimensionality of our DNC is set as many as the one of the last layer of the parametric counterpart, for the sake of fair comparison. However, owing to the distance-/similarity-based nature, DNC has the flexibility to handle any output dimensionality. In Table 15, we further study the influence of the output dimensionality of DNC. As seen, when setting the final output dimensionality as 1280, we can achieve **76.61%** top-1 acc., which is higher than the initial 2048 dimension configuration, *i.e.*, 76.49%. We attribute the reason for the better balance between memory capacity and feature dimensionality with the limitation of hardware computational budget – when reducing the final output dimensionality, the expressibility of the final feature is weakened but more image features can be stored in the external memory for more accurate sub-centroid estimation.

Table 15: **Ablative experiments regarding the final output dimensionality** on ImageNet [9] val. See §F for more details.

Output dimensionality	ImageNet	
	top-1	top-5
640	76.23%	92.83%
1024	76.28%	92.90%
1280	**76.61%**	**93.12%**
2048	76.49%	93.08%

G ADDITIONAL STUDY OF AD-HOC EXPLAINABILITY

Interpretable Class Sub-centroids. In Fig. 5, we show more examples of sub-centroid images for eight ImageNet classes. These representative images are automatically discovered by DNC, and can be intuitively viewed by users. As seen, the class sub-centroid images are able to capture diverse characteristics of their classes, in the aspects of appearance, viewpoints, scales, illuminations, *etc*.

Interpret Prediction Based on (Dis)similarity to Sub-centroid Images. Fig. 6 provides more results regarding the (dis)similarity-based interpretation of DNC prediction. As seen, based on the similarity of test images to the class sub-centroid images, users can clearly understand the decision making mode and make verification. DNC's compelling explainability enables it to establish trustworthiness with humans and empowers its potential in high stake applications.

Figure 5: Sub-centroid images for eight randomly chosen classes from ImageNet [9]. See §G for more details.

Figure 6: More examples on DNC interpreting its predictions based on its computed similarity to class sub-centroid images. For each test image, we plot the normalized similarities for the corresponding closest sub-centroids from the top-4 scoring classes. See §G for more details.

H   QUALITATIVE RESULTS ON SEMANTIC SEGMENTATION

Fig. 7 and Fig. 8 illustrate a few representative visual examples of semantic segmentation results on ADE20K [37] and Cityscapes [26], respectively. In comparison with the parametric counterpart, our approach produces more precise segments in different challenging scenes (for example, where objects with drastic photometric or geometric appearances). For instance, UperNet [36]-Swin-B [3] confuses on neighbouring objects with similar colors (*e.g.*, desk and chair) and leaves a large false-negative regions (see the first image of Fig. 7); it also has difficulties in segmenting small scale objects (*e.g.*, motorbike semantic parsing). Among these examples, DNC consistently demonstrates supreme performance. Essentially, we argue that the proposed DNC has a stronger ability to supervises the pixel embedding space via anchoring sub-centroids directly, leading to a better predictions on segmenting such hard cases.

I   LIMITATION AND FUTURE WORK

Limitation.   One limitation of our approach is that the Sinkhorn-Knopp algorithm runs in time $\widetilde{O}(\frac{n^2}{\epsilon^3})$ which would reduce the training efficiency. Though in practice, we find 3 sinkhorn loops per training iteration is sufficient enough for model representation, bringing a minor computational overhead (*i.e.*, $\sim$5% training delay on ImageNet). This also indicates possible directions for our future research.

Social Impact.   This work introduces DNC possessing the nature of nested simplicity, intuitive decision-making mechanism and even *ad-hoc* explainability. On positive side, the approach advances model accuracy and is valuable in safety-sensitive applications by showing the advanced robustness on sub-categories discovery, *e.g.*, quality analytics, autonomous driving, *etc.*. For potential negative social impact, our DNC struggles in handling out-of-distribution data, which is a common limitation of all the discriminative classifiers. Hence its utility in open-world scenarios should be further examined.

Future Work.   In the future, in addition to investigating more powerful, time-efficiency online clustering algorithms with further advantages on training speed and testing accuracy, we will explore the possibility of unifying close-set and open-world visual recognition within our framework. Moreover, considering the similarity-/distance-based nature, the incorporation of metric learning based training objectives is also another promising direction for further boosting the performance.

Figure 7: **Qualitative semantic segmentation results** of UperNet [36]-Swin-B [3] and DNC on ADE20K [37] val. Red and green bounding boxes represent the same zoom-in area on UperNet [36]-Swin-B [3] and DNC, respectively. See §H for more details.

Figure 8: **Qualitative semantic segmentation results** of UperNet [36]-Swin-B [3] and DNC on Cityscapes [26] val. Red and green bounding boxes represent the same zoom-in area on UperNet [36]-Swin-B [3] and DNC, respectively. See §H for more details.