Group Equivariant Subsampling

Abstract

Subsampling is used in convolutional neural networks (CNNs) in the form of pooling or strided convolutions, to reduce the spatial dimensions of feature maps and to allow the receptive fields to grow exponentially with depth. However, it is known that such subsampling operations are not translation equivariant, unlike convolutions that *are* translation equivariant. Here, we first introduce translation equivariant subsampling/upsampling layers that can be used to construct exact translation equivariant CNNs. We then generalise these layers beyond translations to general groups, thus proposing *group equivariant subsampling/upsampling*. We use these layers to construct group equivariant autoencoders (GAEs) that allow us to learn low-dimensional equivariant representations. We empirically verify on images that the representations are indeed equivariant to input translations and rotations, and thus generalise well to unseen positions and orientations. We further use GAEs in models that learn object-centric representations on multi-object datasets, and show improved data efficiency and decomposition compared to non-equivariant baselines.

1 Introduction

Convolutional Neural Networks (CNNs) are known to be more data efficient and show better generalisation on perceptual tasks than fully-connected networks, due to translation equivariance encoded in the convolutions: when the input image/feature map is translated, the output feature map also translates by the same amount. In typical CNNs, convolutions are used in conjunction with subsampling operations, in the form of pooling or strided convolutions, to reduce the spatial dimensions of feature maps and to allow receptive field to grow exponentially with depth. Subsampling/upsampling operations are especially necessary for convolutional autoencoders (ConvAEs) [30] because they allow efficient dimensionality reduction. However, it is known that subsampling operations implicit in strided convolutions or pooling layers are *not* translation equivariant [47], hence CNNs that use these components are also not translation invariant. Therefore such CNNs and ConvAEs are not guaranteed to generalise to arbitrarily translated inputs despite their convolutional layers being translation equivariant.

Previous work, such as [3, 47], has investigated how to enforce translation invariance on CNNs, but does not study equivariance with respect to symmetries beyond translations, such as rotations or reflections. In this work, we first describe subsampling/upsampling operations that preserve exact translation equivariance. The main idea is to sample feature maps on an input-dependent grid rather than a fixed one as in pooling or strided convolutions, and the grid is chosen according to a *sampling index* computed from the inputs (see Figure 1). Simply replacing the subsampling/upsampling in standard CNNs with such translation equivariant subsampling/upsampling operations leads to CNNs and transposed CNNs that can map between spatial inputs and low-dimensional representations in a translation equivariant manner.

We further generalise the proposed subsampling/upsampling operations from translations to arbitrary groups, proposing *group equivariant subsampling/upsampling*. In particular we identify subsampling

Figure 1: Equivariant subsampling on $1D$ feature maps with a scale factor $c = 2$. The input feature map has length 8, and initially we sample from odd positions determined by Equation (3) (top). When the original feature map is shifted to the right by 1 unit (bottom left), the sampling index becomes 1, so we instead sample from even positions. When the feature map is shifted to the right by 2 units (bottom right), we again sample from odd positions, but the outputs have been shifted to the right by 1 unit correspondingly.

as mapping features on groups G to features on subgroups K (vice versa for upsampling), and identify the sampling index as a coset in the quotient space G/K. See Appendix A for a primer on group theory that is needed to describe this generalisation. We note that group equivariant subsampling is different to *coset pooling* introduced in [5], which instead gives features on the quotient space G/K, and discuss differences in detail in Section 4. Similar to the translation equivariant subsampling/upsampling, group equivariant subsampling/upsampling can be used with group equivariant convolutions to produce group equivariant CNNs. Using such group equvariant CNNs we can construct group equivariant autoencoders (GAEs) that separate representations into an invariant part and an equivariant part.

While there is a growing body of literature on group equivariant CNNs (G-CNNs) [5, 8, 37, 40, 42–44], such equivariant convolutions usually preserve the spatial dimensions of the inputs (or lift them to even higher dimensions) until the final invariant pooling layer. There is a lack of exploration on how to reduce the spatial dimensions of such feature maps while preserving exact equivariance, to produce low-dimensional equivariant representations. This work attempts to fill in this gap. Such low-dimensional equivariant representations can be employed in representation learning methods, allowing various advantages such as interpretability, out-of-distribution generalisation, and better sample complexity. When using such learned representations in downstream tasks such as abstract reasoning, reinforcement learning, video modelling, scene understanding, it is especially important for representations to be equivariant rather than invariant in these tasks, because transformations and how they act on feature spaces are critical information, rather than nuisance as in image classification problems.

In summary, we make the following contributions: (i) We propose subsampling/upsampling operations that preserve translational equivariance. (ii) We generalise the proposed subsampling/upsampling operations to arbitrary symmetry groups. (iii) We use equivariant subsampling/upsampling operations to construct GAEs that gives low-dimensional equivariant representations. (iv) We empirically show that representations learned by GAEs enjoys many advantages such as interpretability, out-of-distribution generalisation, and better sample complexity.

2 Equivariant Subsampling and Upsampling

2.1 Translation Equivariant Subsampling for CNNs

In this section we describe the proposed translation equivariant subsampling scheme for feature maps in standard CNNs. Later in Section 2.2, we describe how this can be generalised to group equivariant subsampling for feature maps on arbitrary groups.

Standard subsampling Feature maps in CNNs can be seen as functions defined on the integer grid, e.g. $\mathbb{Z}$ for 1D feature maps, and $\mathbb{Z}^2$ for 2D. Hence we represent feature maps as $f : \mathbb{Z} \to R^d$, where d is the number of feature map channels. For simplicity, we start with 1D and move on to the 2D case. Typically, subsampling in CNNs is implemented as either strided convolution or (max)

pooling, and they can be decomposed as

$$\text{CONV}_k^c = \text{SUBSAMPLING}^c \circ \text{CONV}_k^1 \tag{1}$$

$$\text{MAXPOOL}_k^c = \text{SUBSAMPLING}^c \circ \text{MAXPOOL}_k^1 \tag{2}$$

where subscripts denote kernel sizes and superscripts indicate strides. $c \in \mathbb{N}$ is the scale factor for SUBSAMPLING, and this operation simply restricts the input domain of the feature map from $\mathbb{Z}$ to $c\mathbb{Z}$, without changing the corresponding function values.

Translation equivariant subsampling In our equivariant subsampling scheme, we instead restrict the input domain to $c\mathbb{Z} + i$, the integers $\equiv i \mod c$, where i is a sampling index determined by the input feature map. The key idea is to choose i such that it shifts by $t(\mathrm{mod} c)$ when the input is translated by t, to ensure that the same features are subsampled upon translation. Let i be given by the mapping $\Phi_c : \mathcal{I}_\mathbb{Z} \rightarrow \mathbb{Z}/c\mathbb{Z}$. $\mathcal{I}_\mathbb{Z}$ denotes the space of vector functions on $\mathbb{Z}$ and $\mathbb{Z}/c\mathbb{Z}$ is the space of remainders upon division by c.

$$i = \Phi_c(f) = \mathrm{mod}(\arg\max_{x \in \mathbb{Z}} \|f(x)\|_1, c) \tag{3}$$

where $\| \cdot \|_1$ denotes L^1-norm (other choices of norm are equally valid). Other choices for Φ_c are equally valid as long as they satisfy translation equivariance, ensuring that the same features are subsampled upon translation of the input:

$$\Phi_c(f(\cdot - t)) = \mathrm{mod}(\Phi_c(f) + t, c). \tag{4}$$

Note that this holds for Equation (3) provided the argmax is unique, which we assume for now (we later deal with the non-unique case). We can decompose the subsampled feature map defined on $c\mathbb{Z} + i$ into its values and the offset index i, expressing it as $[f_b, i] \in (\mathcal{I}_{c\mathbb{Z}}, \mathbb{Z}/c\mathbb{Z})$, where f_b is the translated output feature map such that $f_b(cx) = f(cx + i)$ for $x \in \mathbb{Z}$.

The subsampling operation described above, which maps from $\mathcal{I}_\mathbb{Z}$ to $(\mathcal{I}_{c\mathbb{Z}}, \mathbb{Z}/c\mathbb{Z})$ is translation equivariant: when the feature map f is translated to the right by $t \in \mathbb{Z}$, one can verify that f_b will be translated to the right by $c\lfloor \frac{i+t}{c} \rfloor$, and the sampling index for the translated inputs would become $\mathrm{mod}(i + t, c)$. We provide an illustration for $c = 2$ in Figure 1, and describe formal proofs later in Section 2.2.

Multi-layer case For the subsequent layers, the feature map f_b is fed into the next convolution, and the sampling index i is appended to a list of outputs. When the above translation equivariant subsampling scheme is interleaved with convolutions in this way, we obtain an exactly translation equivariant CNN, where each subsampling layer with scale factor c_k produces a sampling index $i_k \in \mathbb{Z}/c_k\mathbb{Z}$. Hence the equivariant representation output by the CNN with L subsampling layers is a final feature map f_L and a L-tuple of sampling indices $(i_1, \dots, i_L)$. This tuple can in fact be expressed equivalently as a single integer by treating the tuple as mixed radix notation and converting to decimal notation. We provide details of this multi-layer case in Appendix B.2, including a rigorous formulation and its equivariance properties.

Translation equivariant upsampling As a counterpart to subsampling, upsampling operations increase the spatial dimensions of feature maps. We propose an equivariant upsampling operation that takes in a feature map $f \in \mathcal{I}_{c\mathbb{Z}}$ and a sampling index $i \in \mathbb{Z}/c\mathbb{Z}$, and outputs a feature map $f_u \in \mathcal{I}_\mathbb{Z}$, where we set $f_u(cx + i) = f(cx)$ and $\mathbf{0}$ everywhere else. This works well enough in practice, although in conventional upsampling the output feature map is often a smooth interpolation of the input feature map. To achieve this with equivariant upsampling, we can additionally apply average pooling with stride 1 and kernel size > 1.

2D Translation equivariant subsampling When feature maps are $2D$, they can be represented as functions on $\mathbb{Z}^2$. The sampling index becomes a 2-element tuple given by:

$$(x^*, y^*) = \arg\max_{(x,y) \in \mathbb{Z}^2} \|f(x)\|_1 \tag{5}$$

$$(i, j) = (\mathrm{mod}(x^*, c), \mathrm{mod}(y^*, c)) \tag{6}$$

and we subsample feature maps by restricting the input domain to $c\mathbb{Z}^2 + (i, j)$. The multi-layer construction and upsampling is analogous to the 1D-case.

2.2 Group Equivariant Subsampling and Upsampling

In this section, we propose group equivariant subsampling by starting off with the 1D-translation case in Section 2.1, and provide intuition for how each component of this special case generalises to arbitrary discrete groups G. We then proceed to mathematically formulate group equivariant subsampling, and prove that it is indeed G-equivariant.

Feature maps on groups First recall that the feature maps for the 1D-translation case were defined as functions on $\mathbb{Z}$, or $f \in \mathcal{I}_{\mathbb{Z}}$ for short. To extend this to the general case, we consider feature maps f as functions on a group G, i.e. $f \in \mathcal{I}_G = \{f : G \to V\}$[1] where V is a vector space, as is done in e.g. group equivariant CNNs (G-CNNs) [5]. Note that translating feature maps f on $\mathbb{Z}$ by displacement u is effectively defining a new feature map $f'(\cdot) = f(\cdot - u)$. In the general case, we say that the group action on the feature space is given by

$$[\pi(u)f](g) = f(u^{-1}g) \tag{7}$$

where π is a group representation describing how $u \in G$ acts on the feature space.

Recap: translation equivariant subsampling Recall that standard subsampling that occurs in pooling or strided convolutions for 1D translations amounts to restricting the domain of the feature map from $\mathbb{Z}$ to $c\mathbb{Z}$, whereas equivariant subsampling also produces a sampling index $i \in \mathbb{Z}/c\mathbb{Z}$, an integer mod c, and that this is equivalent to restricting the input domain to $c\mathbb{Z} + i$. i is given by the translation equivariant mapping $\Phi_c : \mathcal{I}_{\mathbb{Z}} \to \mathbb{Z}/c\mathbb{Z}$. We can translate the input domain back to $c\mathbb{Z}$, and represent the output of subsampling as $[f_b, i] \in (\mathcal{I}_{c\mathbb{Z}}, \mathbb{Z}/c\mathbb{Z})$, where f_b is the translated output feature map and $f_b(cx) = f(cx + i)$ for $x \in \mathbb{Z}$.

Group equivariant subsampling Similarly in the general case, for a feature map $f \in \mathcal{I}_G$, standard subsampling can be seen as restricting the domain from the group G to a subgroup K, whereas equivariant subsampling additionally produces a sampling index $pK \in G/K$, where the quotient space $G/K = \{gK : g \in G\}$ is the set of (left) *cosets* of K in G. Note that we have rewritten i as p to distinguish between the 1D translation case and the general group case. This is equivalent to restricting the f to the coset pK. The choice of the coset pK is given by equivariant map $\Phi : \mathcal{I}_G \to G/K$ (the action of G on G/K is given by $u(gK) = (ug)K$ for $u, g \in G$), such that $pK = \Phi(f)$. This restriction of f to pK can also be thought of as having an output feature map f_b on K and choosing a coset representative element $\bar{p} \in pK$, such that $f_b(k) = f(\bar{p}k)$. This choice of coset representative is described by a function $s : G/K \to G$, such that $\bar{p} = s(pK)$. The function s is called a section and should satisfy $s(pK)K = pK$.

Now let us formulate subsampling and upsampling operations $S_b\downarrow_K^G$ and $S_u\uparrow_K^G$ mathematically and prove its G-equivariance. Let $\mathcal{I}_K = \{f : K \to V'\}$ be the space of feature map on K. $S_b\downarrow_K^G$ takes in a feature map $f \in \mathcal{I}_G$ and produces a feature map $f_b \in \mathcal{I}_K$ and a coset in G/K. In reverse, the upsampling operation $S_u\uparrow_K^G$ takes in a feature map in $\mathcal{I}_K$, a coset in G/K, and produces a feature map in $\mathcal{I}_G$. We use a section $s : G/K \to G$ to represent a coset with a representative element in G, and point out that equivariance holds for any choice of s.

Formally, given an equivariant map $\Phi : \mathcal{I}_G \to G/K$ (we will discuss how to construct such a map in Section 2.3), and a fixed section $s : G/K \to G$ such that $\bar{p} = s(pK)$, the subsampling operation $S_b\downarrow_K^G : \mathcal{I}_G \to \mathcal{I}_K \times G/K$ is defined as:

$$pK = \Phi(f), \quad f_b(k) = f(\bar{p}k) \text{ for } k \in K$$
$$[f_b, pK] = S_b\downarrow_K^G(f; \Phi), \tag{8}$$

while the upsampling operation $S_u\uparrow_K^G : \mathcal{I}_K \times G/K \to \mathcal{I}_G$ is defined as:

$$f_u(g) = f(\bar{p}^{-1}g) \text{ if } g \in K \text{ else } \mathbf{0}$$
$$f_u = S_u\uparrow_K^G(f, pK). \tag{9}$$

---

[1]This is not to be confused with the space of Mackey functions in, e.g., [7], and rather it is the space of unconstrained functions on G.

To make the output of the upsampling dense rather than sparse, one can apply arbitrary equivariant smoothing functions such as average pooling with stride 1 and kernel size > 1, to compensate for the fact that we extend with **0**s rather than values close to their neighbours. In practice, we observe that upsampling without any smoothing function works well enough.

The statement on the equivariance of $S_b\!\downarrow_K^G$ and $S_u\!\uparrow_K^G$ requires we specify the action of G on the space $\mathcal{I}_K \times G/K$, which we denote as π'. For any $u \in G$,

$$p'K = upK, \quad f_b' = \pi(\bar{p}'^{-1}u\bar{p})f_b$$
$$[f_b', \ p'K] = \pi'(u)[f_b, \ pK] \tag{10}$$

Lemma 2.1. π' defines a valid group action of G on the space $\mathcal{I}_K \times G/K$.

We can now state the following equivariance property:

Proposition 2.2. *If the action of group G on the space $\mathcal{I}_G$ and $\mathcal{I}_K \times G/K$ are specified by π, π' (as defined in Equations (7) and (10)), and $\Phi : \mathcal{I}_G \to G/K$ is an equivariant map, then the operations $S_b\!\downarrow_K^G$ and $S_u\!\uparrow_K^G$ as defined in Equations (8) and (9) are equivariant maps between $\mathcal{I}_G$ and $\mathcal{I}_K \times G/K$. (See Appendix D for a proof)*

2.3   Constructing Φ

We use the following simple construction of the equivariant mapping $\Phi : \mathcal{I}_G \to G/K$ for subsampling/upsampling operations, although any equivariant mapping would suffice. For an input feature map $f \in \mathcal{I}_G$, we define

$$pK = \Phi(f) := (\arg\max_{g \in G} \|f(g)\|_1)K \tag{11}$$

Provided that the argmax is unique, it is easy to show that $(up) \cdot K = \Phi(\pi(u)f)$, hence Φ is equivariant. In practice one can insert arbitrary equivariant layers to f before and after we take the norm $\|\cdot\|_1$ to avoid a non-unique argmax (see Appendix E).

In theory, there could exist cases where the argmax is always non-unique. We provide a more complex construction of Φ that deals with this case in Appendix B.1.

3   Application: Group Equivariant Autoencoders

Group equivariant autoencoders (GAEs) are composed of alternating G-convolutional layers and equivariant subsampling/upsampling operations for the encoder/decoder. One important property of GAEs is that the final subsampling layer of the encoder subsamples to a feature map defined on the trivial group $\{e\}$, outputting a vector (instead of a feature map) that is *invariant*. For the 1D-translation case, suppose the input to the final subsampling layer is a feature map f defined on $\mathbb{Z}$. Then the final layer produces an invariant vector $f_b(0) = f(i_L)$ where $i_L = \arg\max_{x \in \mathbb{Z}} \|f(x)\|_1$. Note that there is no scale factor c_L here. Intuitively we can think of this as setting the scale factor $c_L = \infty$. Hence the encoder of the GAE outputs a representation that is disentangled into an invariant part $z_{\text{inv}} = f_b(0)$ (the vector output by the final subsampling layer) and an equivariant part $z_{\text{eq}} = (i_1, ..., i_L)$.

For the general group case, instead of specifying scale factors as in Section 2.1, we specify a sequence of nested subgroups $G = G_0 \geq G_1 \geq \cdots \geq G_L = \{e\}$, where the feature map for layer l is defined on subgroup G_L. For example, for the $p4$ group $G = \mathbb{Z} \rtimes \mathsf{C}_4$, we can use the following sequence for subsampling: $\mathbb{Z} \rtimes \mathsf{C}_4 \geq 2\mathbb{Z} \rtimes \mathsf{C}_4 \geq 4\mathbb{Z} \rtimes \mathsf{C}_4 \geq 8\mathbb{Z} \rtimes \mathsf{C}_2 \geq \{e\}$. Note that for the final two layers of this example, we are subsampling translations and rotations jointly.

We lift the input defined on the homogeneous input space to $\mathcal{I}_G$ (see Appendix A.3 for details on homogeneous spaces and lifting), and treat $f_0 \in \mathcal{I}_G$ as inputs to the autoencoders. The group equivariant encoder ENC can be described as follows:

$$[f_l, \ \bar{p}_l] = S_b\!\downarrow_{G_l}^{G_{l-1}}(\text{G-CNN}_{l-1}^E(f_{l-1}); \Phi)$$
$$[z_{\text{inv}}, z_{\text{eq}}] = [f_L(e), \ (p_1G_1, p_2G_2, \ldots, p_LG_L)] \tag{12}$$

where $l = 1, \ldots, L$ and G-CNN$_l(\cdot)$ denotes G-convolutional layers before the lth subsampling layer.

The decoder DEC simply goes in the opposite direction, and can be written formally as:

$$f_L \text{ is defined on } G_L = \{e\} \text{ and } f_L(e) = z_{\text{inv}}$$

$$f_{l-1} = \text{G-CNN}_{l-1}^D(S_u \uparrow_{G_l}^{G_{l-1}}(f_l, \; p_l G_l)) \tag{13}$$

where $l = L, \ldots, 1$ and $\hat{f} = f_0$ gives the final reconstruction.

Recall from Section 2.1 that the tuple $(i_1, \ldots, i_L)$ can be expressed equivalently as a single integer. Similarly, the tuple $(p_1 G_1, p_2 G_2, \ldots, p_L G_L)$ can be expressed as a single group element in G. We show in Appendix B.2 that the action implicitly defined on the tuple via Equation (10) simplifies elegantly to the left-action on the single group element in G.

We now have the following properties for the learned representations (see Appendix D for a proof):

Proposition 3.1. *When* ENC *and* DEC *are given by Equations* (12) *and* (13)*, and the group actions are specified as in Equation* (7) *and Equation* (10)*, for any* $g \in G$ *and* $f \in \mathcal{I}_G$*, we have*

$$[z_{\text{inv}}, g \cdot z_{\text{eq}}] = \text{ENC}(\pi(g)f) \tag{14}$$

$$\pi(g)\hat{f} = \text{DEC}(z_{\text{inv}}, g \cdot z_{\text{eq}}) \tag{15}$$

4 Related Work

Group equivariant neural networks The equivariant subsampling/upsampling that we propose deals with feature maps (functions) defined on the space of the group G or its subgroups K, which transform under the *regular representation* with the group action. Hence our equivariant subsampling/upsampling is compatible with *lifting-based* group equivariant neural networks defined on discrete groups [5, 20, 33, 34] that define a mapping between feature maps on G. We also discuss the extension of group equivariant subsampling to be compatible with those defined on continuous/Lie groups [1, 6, 12, 14, 22] in Section 6. This is in contrast to group equivariant neural networks that do not use lifting and use *irreducible representations*, defining mappings between feature maps on the input space $\mathbf{X}$. [8, 13, 15, 27, 37, 40, 42–44].

Coset pooling In particular, [5] propose *coset pooling*, which is also a method for equivariant subsampling. Here a feature map f on G is mapped onto a feature map $\Phi(f)$ on G/K (as opposed to K, for our equivariant subsampling) as follows:

$$\Phi(f)(gK) = \text{POOL}_{k \in K} f(gk) \tag{16}$$

such that the feature values on the coset gK are pooled. For the 1D-translation case, where $G = \mathbb{Z}, K = c\mathbb{Z}$, this amounts to pooling over every cth pixel, which disrupts the locality of features as opposed to our equivariant subsampling that preserves locality, and hence is more suitable to use with convolutions for translation equivariance. See Figure 2 for a visual comparison. As such, the $p4$-CNNs in [5] use standard max pooling with stride=2 rather than coset pooling for $\mathbb{Z}^2$, and coset-pooling is only used in the final layer to pool over feature maps across 90-degree rotations, achieving exact rotation equivariance but imperfect translation equivariance. In our work, we use translation equivariant subsampling in the earlier layers and rotation equivariant subsampling in the final layers to achieve exact roto-translation equivariance.

Figure 2: Coset (max) pooling vs. equivariant subsampling.

Unsupervised disentangling and object discovery GAEs produce equivariant (z_{eq}) and invariant (z_{inv}) representations, effectively separating position and pose information with other semantic information. This relates to unsupervised disentangling [4, 19, 26, 48] where different factors of variation in the data are separated in different dimensions of a low-dimensional representation. However unlike equivariant subsampling, there is no guarantee of any equivariance in the low-dimensional representation, making the resulting disentangled representations less interpretable.

Works on unsupervised object discovery [2, 11, 17, 28] learn object-centric representations, and we showcase GAEs in MONet [2] where we replace their VAE with a V-GAE in order to separate position and pose information and learn more interpretable representations of objects in a data-efficient manner.

Shift-invariance in CNNs   As early as [36], it has been discussed that shift-invariance cannot hold for conventional subsampling. Although standard subsampling operations such as pooling or strided convolutions are not *exactly* shift invariant, they do not prevent strong performance on classification tasks [35]. Nonetheless, [47] integrates anti-aliasing to improve shift-invariance, showing that it leads to better performance and generalisation on classification tasks. [3] explore a similar strategy to our equivariant subsampling by partitioning feature maps into polyphase components and select the component with the highest norm. However, unlike the proposed group equivariant subsampling/upsampling which tackle general equivariance for arbitrary discrete groups, both works focus only on translation invariance.

5   Experiments

In this section, we compare the performance of GAEs with equivariant subsampling to their non-equivariant counterparts that use standard subsampling/upsampling in object-centric representation learning. We show that GAEs give rise to more interpretable representations that show better sample complexity and generalisation than their non-equivariant counterparts.

Models and Baselines   (G-)Convolutional autoencoders (G)ConvAE are composed of alternating (G-)convolutional layers and subsampling/upsampling operations with a final MLPs applied to the flattened feature maps. We categorize models by the types of equivariance preserved by the convolutional layers. We consider three different discrete symmetry groups: $p1$ (only translations), $p4$ (composition of translations and 90 degree rotations), $p4m$ (composition of translations, 90 degree rotations and mirror reflection). The baseline models are: ConvAE-$p1$ (standard convolutional autoencoders), GConvAE-$p4$, GConvAE-$p4m$, where the corresponding equivariance is preserved in the (G-)convolutional layers but not in the subsampling/upsampling operations. The equivariant counterparts of these baseline models are GAE-$p1$, GAE-$p4$, GAE-$p4m$, where the subsampling/upsampling operations are also equivariant. For baseline models, we use a scale factor of 2 for all subsampling/upsampling layers. For GAEs, we subsample first the translations, then rotations, followed by reflections, all with scale factor 2. e.g. for GAE-$p4m$, the feature maps at each layer are defined on the following chain of nested subgroups: $\mathbb{Z}^2 \rtimes (\mathsf{C}_4 \rtimes \mathsf{C}_2) \geq (2\mathbb{Z})^2 \rtimes (\mathsf{C}_4 \rtimes \mathsf{C}_2) \geq (4\mathbb{Z})^2 \rtimes (\mathsf{C}_4 \rtimes \mathsf{C}_2) \geq (8\mathbb{Z})^2 \rtimes (\mathsf{C}_4 \rtimes \mathsf{C}_2) \geq (16\mathbb{Z})^2 \rtimes (\mathsf{C}_2 \rtimes \mathsf{C}_2) \geq \{e\}$. As in [5], we rescale the number of channels such that the total number of parameters of these models roughly match each other.

Data   To demonstrate basic properties of GAEs and compare sample complexity under the single object scenario, we use Colored-dSprite [31] and a modification of FashionMNIST [45], where we first apply zero-padding to reach a size of 64×64, followed by random shifts, rotations and coloring. For multi-object datasets, we use Multi-dSprites [24] and CLEVR6 which is a variant of CLEVR [23] with up to 6 objects. All input images are resized to a resolution of 64×64.

Our implementation is built upon a wide range of open source projects [11, 18, 21, 32, 38, 41, 46]. See Appendix E for details on hyperparameters, architectures and data preprocessing.

5.1   Basic Properties: Equivariance, Disentanglement and Out-of-Distribution Generalization

Equivariance   The encoder-decoder pipeline in GAEs is exactly equivariant. In Figure 3, we train GAE-$p4m$ on 6400 examples from Colored-dSprites, and we show how to manipulate reconstructions by manipulating the equivariant representation z_{eq} (left). If an image x is encoded into $[z_{\text{inv}}, z_{\text{eq}}]$, then decoding $[z_{\text{inv}}, g \cdot z_{\text{eq}}]$ will give $g \cdot \hat{x}$ where $\hat{x}$ is the reconstruction of x.

Disentanglement   The learned representations in GAEs are disentangled into an invariant part z_{inv} and an equivariant part z_{eq}. In Figure 3 (left), we vary the equivariant part while the invariant part remains the same. In Figure 3 (right), we show the frames of a movie of a heart, and show its reconstruction after replacing z_{inv} representing a heart with that of an ellipse. Note that the ellipse shape undergoes the same sequence of transformations as the heart.

Figure 3: (Left) Manipulating reconstructions by modifying the equivariant part z_{eq}. The second column are the original reconstructions, which match the inputs well. The subsequent columns are reconstructions decoded from modified z_{eq}. We transform z_{eq} with a sequence of group elements, and show the resulting reconstructions. (Right) Manipulating reconstruction shape by modifying z_{inv}.

Figure 4: Generalisation to out-of-distribution object locations and poses. During training, we constrain shapes to be in the top-left quarter, and the orientation to be always less than 90 degrees. On the right, we compare the error of reconstructions of different models generalise on objects at unseen locations in the first row, and how they generalise to unseen orientations in the second row.

Out-of-distribution generalisation GAEs can generalise to data with unseen object locations and poses. We train an GAE-$p4$ on 6400 constrained training examples, where we only use examples with locations in the top-left quarter and orientations within $[0, 90]$ degrees, as shown in Figure 4. During test time, we evaluate mean squared error (MSE) of reconstructions on unfiltered test data to see how models generalise to unseen location and poses. Both ConvAE-$p1$ and GConvAE-$p4$ cannot generalise well to object poses out of their training distribution. In contrast, GAE-$p1$ generalise to any locations without performance degradation but not to unseen orientations, while GAE-$p4$, which encodes both translation and rotation equivariance, generalises well to all locations and orientations. We only use heart shapes for evaluation, because the square and ellipse have inherent symmetries.

5.2 Single Object

Since GAEs are fully equivariant and can generalize to unseen object poses, it is natural to conjecture that such models can significantly improve data efficiency when symmetry-transformed data points are also plausible samples from the data distribution. We test this hypothesis on Colored-dSprites and transformed FashionMNIST, and the results are shown in Figure 5. On both datasets, equivariant autoencoders significantly outperform their non-equivariant counterparts for all considered training set sizes. In fact, as shown in the figure, equivariant models trained with a smaller training set size is often comparable to baseline models trained on a larger training set. Furthermore, the results demonstrate that it is beneficial to consider symmetries beyond translations in these problems: for both non-equivariant and equivariant models, variants that encode rotation and reflection symmetries consistently show better performance compared to models that only consider translation symmetry.

Figure 5: Reconstruction error on single object datasets

Table 1: Reconstruction error MSE ($\times 10^{-3}$) (mean(stddev) across 5 seeds) on multi-object datasets

Dataset	Multi-dSprites			CLEVR6		
Training Set Size	3200	6400	12800	3200	6400	12800
MONet	2.661(0.382)	1.385(0.235)	0.326(0.076)	0.673(0.059)	0.562(0.057)	0.546(0.056)
MONet-GAE-$p1$	0.659(0.103)	0.359(0.025)	0.264(0.042)	0.473(0.064)	0.432(0.052)	0.388(0.016)
MONet-GAE-$p4$	0.563(0.195)	0.317(0.060)	0.231(0.067)	0.461(0.025)	0.414(0.022)	0.413(0.018)

Table 2: Foreground segmentation performance in terms of ARI (mean(stddev) across 5 seeds)

Dataset	Multi-dSprites			CLEVR6		
Training Set Size	3200	6400	12800	3200	6400	12800
MONet	0.597(0.022)	0.747(0.049)	0.891(0.009)	0.829(0.055)	0.878(0.023)	0.865(0.033)
MONet-GAE-$p1$	0.762(0.049)	0.823(0.042)	0.889(0.013)	0.921(0.015)	0.917(0.032)	0.920(0.025)
MONet-GAE-$p4$	0.753(0.089)	0.833(0.072)	0.902(0.025)	0.878(0.055)	0.914(0.012)	0.910(0.011)

5.3 Multiple Objects

In multi-object scenes, it is often more interesting to consider local symmetries associated with objects rather than the global symmetry for the whole image. To exploit object symmetries in image data, one needs to first discover objects and separate them from the background, which is a challenging problem on its own. Currently, GAEs do not have inherent capability to solve these problems. In order to investigate whether our models could improve data efficiency in multi-object settings, we rely on recent work on unsupervised object discovery and only use GAEs to model object components. More specifically, we explored replacing component VAEs in MONet [2] with V-GAEs (probabilistic version of our GAEs, where a standard Gaussian prior is put on z_{inv} and z_{eq} remains deterministic), and train models end-to-end. Again we study the low data regime to show results on data efficiency.

We train models on Multi-dSprites and CLEVR6 with training set sizes 3200, 6400 and 12800. We consider two evaluation metrics: mean squared error (MSE) to measure the overall reconstruction quality, and adjusted rand index (ARI), which is a clustering similarity measure ranging from 0 (random) to 1 (perfect) to measure object segmentation. As in [2], we only use foreground pixels to compute ARI. Component VAEs in MONet use spatial broadcast decoders [39] that broadcast the latent representation to a full scale feature map before feeding them into the decoders, and the decoders therefore do not need upsampling. It has the implicit effect of encouraging the smoothness of the decoder outputs. To encourage similar behaviour, we add average pooling layers with stride 1 and kernel size 3 to our equivariant decoders. As shown in Table 1, using GAEs to model object components significantly improves reconstruction quality, which is consistent with our findings in single-object scenario. As shown in Table 2, using GAEs to model object components also leads to better object discovery in the low data regimes, but this advantage seems to diminish as the dataset becomes sufficiently large.

6 Conclusions, Limitations and Future Work

Conclusions We have proposed subsampling/upsampling operations that *exactly* preserve translation equivariance, and generalised them to define *exact* group equivariant subsampling/upsampling for discrete groups. We have used these layers in GAEs that allow learning low-dimensional representations that can be used to reliably manipulate pose and position of objects, and further showed how GAEs can be used to improve data efficiency in multi-object representation learning models.

Limitations and Future work Although the equivariance properties of subsampling layers also hold for Lie groups, we have not discussed the practical complexities that arise with the continuous case, where feature maps are only defined on a finite subset of the group rather than the whole group. We leave this as important future work, as well as application of equivariant subsampling for tasks other than representation learning where equivariance/invariance is desirable e.g. object classification, localization. Another limitation is that our work focuses on global equivariance, like most other works in the literature. An important direction is to extend to the case of local equivariances e.g. object-specific symmetries for multi-object scenes.

References

[1] Erik J Bekkers. B-spline CNNs on Lie groups. In *ICLR*, 2020.

[2] Christopher P Burgess, Loic Matthey, Nicholas Watters, Rishabh Kabra, Irina Higgins, Matt Botvinick, and Alexander Lerchner. Monet: Unsupervised scene decomposition and representation. *arXiv preprint arXiv:1901.11390*, 2019.

[3] Anadi Chaman and Ivan Dokmanić. Truly shift-invariant convolutional neural networks. *arXiv preprint arXiv:2011.14214*, 2020.

[4] Tian Qi Chen, Xuechen Li, Roger Grosse, and David Duvenaud. Isolating sources of disentanglement in variational autoencoders. In *International Conference on Learning Representations*, 2018.

[5] Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pages 2990–2999, 2016.

[6] Taco S Cohen, Mario Geiger, Jonas Köhler, and Max Welling. Spherical CNNs. In *ICLR*, 2018.

[7] Taco S Cohen, Mario Geiger, and Maurice Weiler. A general theory of equivariant cnns on homogeneous spaces. *Advances in neural information processing systems*, 32:9145–9156, 2019.

[8] Taco S Cohen and Max Welling. Steerable cnns. In *International Conference on Learning Representations*, 2017.

[9] Sander Dieleman, Jeffrey De Fauw, and Koray Kavukcuoglu. Exploiting cyclic symmetry in convolutional neural networks. In *International Conference on Machine Learning*, pages 1889–1898, 2016.

[10] Sander Dieleman, Kyle W Willett, and Joni Dambre. Rotation-invariant convolutional neural networks for galaxy morphology prediction. *Monthly notices of the royal astronomical society*, 450(2):1441–1459, 2015.

[11] Martin Engelcke, Adam R. Kosiorek, Oiwi Parker Jones, and Ingmar Posner. GENESIS: Generative Scene Inference and Sampling of Object-Centric Latent Representations. *International Conference on Learning Representations (ICLR)*, 2020.

[12] Carlos Esteves, Christine Allen-Blanchette, Ameesh Makadia, and Kostas Daniilidis. Learning SO(3) equivariant representations with spherical CNNs. In *ECCV*, 2018.

[13] Carlos Esteves, Ameesh Makadia, and Kostas Daniilidis. Spin-weighted spherical CNNs. In *NeurIPS*, 2020.

[14] Marc Finzi, Samuel Stanton, Pavel Izmailov, and Andrew Gordon Wilson. Generalizing convolutional neural networks for equivariance to Lie groups on arbitrary continuous data. In *ICML*, 2020.

[15] Fabian B Fuchs, Daniel E Worrall, Volker Fischer, and Max Welling. SE(3)-Transformers: 3D roto-translation equivariant attention networks. In *NeurIPS*, 2020.

[16] Robert Gens and Pedro M Domingos. Deep symmetry networks. *Advances in neural information processing systems*, 27:2537–2545, 2014.

[17] Klaus Greff, Raphaël Lopez Kaufman, Rishabh Kabra, Nick Watters, Christopher Burgess, Daniel Zoran, Loic Matthey, Matthew Botvinick, and Alexander Lerchner. Multi-object representation learning with iterative variational inference. In *International Conference on Machine Learning*, pages 2424–2433. PMLR, 2019.

[18] Charles R. Harris, K. Jarrod Millman, Stéfan J. van der Walt, Ralf Gommers, Pauli Virtanen, David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel J. Smith, Robert Kern, Matti Picus, Stephan Hoyer, Marten H. van Kerkwijk, Matthew Brett, Allan Haldane, Jaime Fernández del Río, Mark Wiebe, Pearu Peterson, Pierre Gérard-Marchant, Kevin Sheppard, Tyler Reddy, Warren Weckesser, Hameer Abbasi, Christoph Gohlke, and Travis E. Oliphant. Array programming with NumPy. *Nature*, 585(7825):357–362, September 2020.

[19] Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-VAE: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, 2017.

[20] Emiel Hoogeboom, Jorn WT Peters, Taco S Cohen, and Max Welling. HexaConv. In *ICLR*, 2018.

[21] J. D. Hunter. Matplotlib: A 2d graphics environment. *Computing in Science & Engineering*, 9(3):90–95, 2007.

[22] Michael Hutchinson, Charline Le Lan, Sheheryar Zaidi, Emilien Dupont, Yee Whye Teh, and Hyunjik Kim. Lietransformer: Equivariant self-attention for lie groups. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, 2021.

[23] Justin Johnson, Bharath Hariharan, Laurens Van Der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2901–2910, 2017.

[24] Rishabh Kabra, Chris Burgess, Loic Matthey, Raphael Lopez Kaufman, Klaus Greff, Malcolm Reynolds, and Alexander Lerchner. Multi-object datasets. https://github.com/deepmind/multi-object-datasets/, 2019.

[25] Angjoo Kanazawa, Abhishek Sharma, and David Jacobs. Locally scale-invariant convolutional neural networks. *arXiv preprint arXiv:1412.5104*, 2014.

[26] Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *International Conference on Learning Representations*, 2018.

[27] Risi Kondor, Zhen Lin, and Shubhendu Trivedi. Clebsch–Gordan nets: a fully Fourier space spherical convolutional neural network. In *NeurIPS*, 2018.

[28] Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. *arXiv preprint arXiv:2006.15055*, 2020.

[29] Diego Marcos, Michele Volpi, and Devis Tuia. Learning rotation invariant convolutional filters for texture classification. In *2016 23rd International Conference on Pattern Recognition (ICPR)*, pages 2012–2017. IEEE, 2016.

[30] Jonathan Masci, Ueli Meier, D. Ciresan, and J. Schmidhuber. Stacked convolutional auto-encoders for hierarchical feature extraction. In *ICANN*, 2011.

[31] Loic Matthey, Irina Higgins, Demis Hassabis, and Alexander Lerchner. dsprites: Disentanglement testing sprites dataset. https://github.com/deepmind/dsprites-dataset/, 2017.

[32] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019.

[33] David W Romero, Erik J Bekkers, Jakub M Tomczak, and Mark Hoogendoorn. Attentive group equivariant convolutional networks. In *ICML*, 2020.

[34] David W Romero and Mark Hoogendoorn. Co-attentive equivariant neural networks: Focusing equivariance on transformations co-occurring in data. In *ICLR*, 2020.

[35] Dominik Scherer, Andreas Müller, and Sven Behnke. Evaluation of pooling operations in convolutional architectures for object recognition. In Konstantinos Diamantaras, Wlodek Duch, and Lazaros S. Iliadis, editors, *Artificial Neural Networks – ICANN 2010*, pages 92–101, Berlin, Heidelberg, 2010. Springer Berlin Heidelberg.

[36] E.P. Simoncelli, W.T. Freeman, E.H. Adelson, and D.J. Heeger. Shiftable multiscale transforms. *IEEE Transactions on Information Theory*, 38(2):587–607, 1992.

[37] Nathaniel Thomas, Tess Smidt, Steven Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, and Patrick Riley. Tensor field networks: Rotation-and translation-equivariant neural networks for 3d point clouds. *arXiv preprint arXiv:1802.08219*, 2018.

[38] Michael L. Waskom. seaborn: statistical data visualization. *Journal of Open Source Software*, 6(60):3021, 2021.

[39] Nicholas Watters, Loic Matthey, Christopher P Burgess, and Alexander Lerchner. Spatial broadcast decoder: A simple architecture for learning disentangled representations in vaes. *arXiv preprint arXiv:1901.07017*, 2019.

[40] Maurice Weiler and Gabriele Cesa. General e (2)-equivariant steerable cnns. In *Advances in Neural Information Processing Systems*, pages 14334–14345, 2019.

[41] Maurice Weiler and Gabriele Cesa. General E(2)-Equivariant Steerable CNNs. In *Conference on Neural Information Processing Systems (NeurIPS)*, 2019.

[42] Maurice Weiler, Mario Geiger, Max Welling, Wouter Boomsma, and Taco S Cohen. 3d steerable cnns: Learning rotationally equivariant features in volumetric data. In *Advances in Neural Information Processing Systems*, pages 10381–10392, 2018.

[43] Maurice Weiler, Fred A Hamprecht, and Martin Storath. Learning steerable filters for rotation equivariant cnns. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 849–858, 2018.

[44] Daniel E Worrall, Stephan J Garbin, Daniyar Turmukhambetov, and Gabriel J Brostow. Harmonic networks: Deep translation and rotation equivariance. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5028–5037, 2017.

[45] Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017.

[46] Omry Yadan. Hydra - a framework for elegantly configuring complex applications. Github, 2019.

[47] Richard Zhang. Making convolutional networks shift-invariant again. In *International Conference on Machine Learning*, pages 7324–7334, 2019.

[48] Shengjia Zhao, Jiaming Song, and Stefano Ermon. Infovae: Information maximizing variational autoencoders. *arXiv preprint arXiv:1706.02262*, 2017.