Towards Adversarial Robustness of Bayesian Neural Network through Hierarchical Variational Inference

Abstract

Recent works have applied Bayesian Neural Network (BNN) to adversarial training, and shown the improvement of adversarial robustness via the BNN's strength of stochastic gradient defense. However, we have found that in general, the BNN loses its stochasticity after its training with the posterior. As a result, the lack of the stochasticity leads to weak regularization effect to the BNN, which increases KL divergence in ELBO from variational inference. In this paper, we propose an enhanced Bayesian regularizer through hierarchical variational inference in order to boost adversarial robustness against gradient-based attack. Furthermore, we also prove that the proposed method allows the BNN's stochasticity to be elevated with the reduced KL divergence. Exhaustive experiment results demonstrate the effectiveness of the proposed method by showing the improvement of adversarial robustness, compared with adversarial training (Madry et al., 2018) and adversarial-BNN (Liu et al., 2019) under PGD attack and EOT-PGD attack to the L_∞ perturbation on CIFAR-10/100, STL-10, and Tiny-ImageNet.

1 Introduction

Deep neural networks have achieved impressive performance in a wide variety of machine learning tasks. Despite the breakthrough outcomes, deep neural networks are easily deceived from adversarial attack with the carefully crafted perturbations (Szegedy et al., 2014; Goodfellow et al., 2015; Chen et al., 2017; Carlini & Wagner, 2017; Papernot et al., 2017; Eykholt et al., 2018; Madry et al., 2018). Injecting these perturbations into clean inputs (i.e., adversarial examples), which are imperceptible to the human eyes, fools the estimators in the deep neural networks. Weak reliability due to the invisible perturbations has affected security problems in deep learning applications (Apruzzese et al., 2019; Wang et al., 2019b; Sagduyu et al., 2019; Rosenberg et al., 2020).

To defend such adversarial examples, many algorithms have been studied to improve adversarial robustness so far. *Adversarial training*, where deep neural networks are trained on adversarial examples, is one of the few defense strategies against strong adversarial attacks (Huang et al., 2015; Zantedeschi et al., 2017; Kurakin et al., 2017; Madry et al., 2018; Athalye et al., 2018a; Liu et al., 2018). Among them, Madry et al. (2018) has shown that adversarially trained networks can be robust to white-box attacks with the knowledge of the network parameters. Besides, most of the above studies have agreed with that adversarial training shows an effective adversarial robustness against several white-box attacks.

Meanwhile, adversarial training and BNN have been combined to improve adversarial robustness with stochastic approach through variational inference. In fact, the variational inference maximizes Evidence Lower Bound (ELBO) to find the true posterior for the machine learning tasks (Graves, 2011; Kingma & Welling, 2014; Blundell et al., 2015; Hernández-Lobato & Adams, 2015). Based on the variational inference, adversarial training with BNN has accomplished the achievement of adversarial robustness by implicitly using the true posterior against the adversarial perturbations (Mescheder et al., 2017; Ye & Zhu, 2018). They have focused on training the network parameters or spaces itself on the maximum ELBO without obtaining the true posterior directly.

Contrary to the above studies, Liu et al. (2019) presents an adversarial training with BNN, called "adversarial-BNN" to deal with the true posterior explicitly. Liu et al. learns Gaussian parameters

i

(e.g., mean and variance) of the posterior as follows: $w \sim \mathcal{N}(\mu, \sigma^2)$, instead of the weight parameters. Alternatively, the weight parameters are sampled by the posterior, such that $w = \mu + \sigma\epsilon$, where the stochastic sampler ϵ is gererated from $\epsilon \sim \mathcal{N}(0, 1)$. The stochastic sampler ϵ provides the change of the weight parameters with the learned Gaussian parameters. The variation of them creates stochastic gradient, helping the improvement of adversarial robustness (Carbone et al., 2020).

However, we find that in general, the posterior's variance converges to zero-like small value as follows: $w \sim \mathcal{N}(\mu, \sigma^2 \approx 0)$ after training the BNN with the posterior. Although the stochastic sampler helps the weight parameters to change, they become fixed-like parameters, such that $w = \mu + \sigma(\approx 0)\epsilon$. The lack of their stochasticity causes the BNN's stochasticity to be vanished so that the BNN cannot easily respond to slightly different inputs within the same class. In other words, the vanished stochasticity breaks the regularization effect in the BNN, which increases KL divergence in the ELBO. The broken BNN regularizer produces an ill-posed posterior, thus resulting in weak adversarial robustness. This is because the broken regularizer hinders the maximum ELBO from obtaining the true posterior against the adversarial perturbations. Therefore, an enhanced BNN regularizer is required to better find the true posterior for adversarial robustness.

In this paper, we present the enhanced Bayesian regularizer through hierarchical variational inference in order to boost adversarial robustness compared to the BNN regularizer from variational inference. Furthermore, we also prove that the proposed method significantly intensifies the BNN's stochasticity by introducing the conjugate prior. In the end, we validate the effectiveness of the proposed method by showing the improvement of adversarial robustness, compared with adversarial training (Madry et al., 2018) and adversarial-BNN (Liu et al., 2019) under PGD attack as well as EOT-PGD attack to the L_∞ perturbation on CIFAR-10/100, STL-10, and Tiny-ImageNet.

Our contributions of this paper can be summarized into two-fold as follows.

- We newly design an enhanced Bayesian regularizer through hierarchical variational inference built with the conjugate prior, and verify that the proposed method further strengthens the BNN's stochasticity compared to the BNN regularizer based on variational inference.
- We conduct exhaustive experiments to validate the effectiveness of the proposed method by adversarial robustness, and exhibit the outstanding performance compared with adversarial training and adversarial-BNN under both PGD attack and EOT-PGD attack on four benchmark datasets: CIFAR-10/100, STL-10, and Tiny-ImageNet.

2 PRELIMINARY

In this section, we specify the notations used in our paper at first and summarize the related works on adversarial attack/defense, and adversarial training with BNN.

Notations. Let x denote the clean image from a given dataset, and y denote the class label corresponding to the clean image. Let $\mathcal{D}$ and $\mathcal{D}^{adv}$ indicate each clean dataset and adversarial dataset, such that $(x, y) \sim \mathcal{D}$ and $(x^{adv}, y) \sim \mathcal{D}^{adv}$. A deep neural network f parameterized by weight parameters w is denoted by $f_w(x)$. Adversarial examples are represented by $x^{adv} = x + \delta$, where δ denotes the adversarial perturbations. In order to align the experiments in the previous works, we use the cross-entropy loss $J(f_w(x), y)$ for image classification. Moreover, we regard δ as the L_∞ norm perturbation within γ-ball, such that $\|\delta\|_\infty \leq \gamma$. Here, $\|\cdot\|_\infty$ describes the L_∞ norm.

2.1 ADVERSARIAL ATTACK/DEFENSE

Adversarial Attacks. The goal of adversarial attacks is generating the adversarial examples to deceive the prediction of the deep neural networks. Most of the adversarial attacks produce the adversarial examples by the gradient of the loss function over the input. Goodfellow et al. (2015) introduces a single-step attack called Fast Gradient Sign Method (FGSM). Kurakin et al. (2017) proposes iterative-FGSM with multiple-step attack. Further, Carlini & Wagner (2017) presents C&W attack to overcome defensive distillation (Papernot et al., 2016), encompassing a range of attacks cast from the same optimization framework. On the other hand, Athalye et al. (2018a) analyzes the effectiveness of Projected Gradient Descent (PGD) method (Madry et al., 2018) to perform adversarial attack to the L_∞ perturbation. PGD attack is an iterative algorithm by computing the gradient

of the loss in the direction of the highest loss and projecting it back to the L_∞ perturbation norm around the clean image. We use the PGD attack for the experiments of adversarial robustness, which can be written as:

$$x_{t+1}^{adv} = \prod_{x,\gamma} \left[x_t^{adv} + \eta \cdot \text{sign} \left(\nabla_x J \left(f_w(x), y \right) \big|_{x=x_t^{adv}} \right) \right], \tag{1}$$

where $\prod_{x,\gamma}$ is the function to project its argument to the surface of x's γ-neighbor ball $\left\{ x \middle| \left\| x^{adv} - x \right\|_\infty \le \gamma \right\}$, and η denotes step size. For the adversarial defense utilizing randomized classifiers, an adaptive attack such as Expectation over Transformation (EOT) is known to be effective because it allows an attacker to compute the actual gradient over the expected transformation to the stochastic classifiers (Athalye et al., 2018a;b). Inspired from the EOT attack, we can modify Eq. (1) and adjust more efficient PGD attack (Zimmermann, 2019).

$$x_{t+1}^{adv} = \prod_{x,\gamma} \left[x_t^{adv} + \eta \cdot \text{sign} \left(\mathbb{E}_w \left[\nabla_x J \left(f_w(x), y \right) \big|_{x=x_t^{adv}} \right] \right) \right], \tag{2}$$

Zimmermann (2019) applies the averaged-gradient over the multiple weight parameters to generate the adversarial examples, and shows that this efficient PGD attack degrades the BNN's adversarial robustness. This is because the averaged-gradient can attack all of the possibly sampled weight parameters in the BNN. In other words, the averaged-gradient attack weakens the BNN's advantage of stochastic gradient defense. In this paper, we call the efficient PGD attack, namely *EOT-PGD attack*, and take it to validate the effectiveness of the proposed method.

Adversarial Defense. The aim of adversarial defense is to secure deep learning networks against adversarial attacks. There are generally three main categories of defense strategies. (i) Gradient masking/obfuscation: a defender intentionally hides the gradient information of deep neural networks in order to confuse adversaries, because most attack algorithms are based on the classifier's gradient information (Papernot et al., 2016; Buckman et al., 2018; Guo et al., 2018; Dhillon et al., 2018). (ii) Adversarial detections: they focus on distinguishing whether the input is benign or adversarial (Metzen et al., 2017; Grosse et al., 2017; Xu et al., 2017). When they succeed to detect the adversarial attack in the input, the classifiers stop making a decision. (iii) Robust optimizations: main interest is improving the classifier's robustness by changing the training scheme with the adversarial examples (Cisse et al., 2017; Hein & Andriushchenko, 2017; Raghunathan et al., 2018; Wong & Kolter, 2018).

Adversarial training (Goodfellow et al., 2015; Kurakin et al., 2017; Madry et al., 2018) is one of the robust optimization methods, which allows the deep neural network to learn robust parameters against the adversarial examples. Especially, Madry et al.(2018) tries to find the optimal weight parameters against adversarial dataset $\mathcal{D}^{adv}$ to improve adversarial robustness under PGD attack to the L_∞ perturbation, by minimizing the pre-defined loss $\mathcal{L}$ for the machine learning tasks. The formulation can be written as:

$$w^* = \arg\min_w \mathbb{E}_{(x^{adv}, y) \sim \mathcal{D}^{adv}} \left[\mathcal{L} \left(f_w(x^{adv}), y \right) \right], \tag{3}$$

where x^{adv} is generated from the PGD attack as described in Eq. (1). The optimal weight parameters w^* get the capacity of adversarial defense to confront the adversarial perturbations.

2.2 ADVERSARIAL TRAINING WITH BNN

Many studies have been done to mingle with adversarial training and BNN through variational inference. Here, variational inference imposes the probabilistic approach on the network parameters or spaces to obtain the true posterior based on the maximum ELBO, thus leading to well-posed inference (Welling & Teh, 2011; Paisley et al., 2012; Hoffman et al., 2013; Salimans & Knowles, 2013; Kingma & Welling, 2014; Rezende et al., 2014).

Likewise, adversarial training with BNN also have to obtain the true adv-posterior: $p(w \mid \mathcal{D}^{adv})$, which conducts the well-posed inference for adversarial robustness. But, the true adv-posterior is intractable because of a high dimensional dependency of adversarial dataset $p(\mathcal{D}^{adv})$. Thus, variational inference for adversarial robustness introduces an approximate posterior in the form of

Figure 1: Diagrams that describe the methods of sampling the weight parameters for (a) with adversarial-BNN and (b) the proposed method. The weight parameters in (a) are sampled from the Gaussian distribution $q(w)$ through variational inference, and those in (b) are sampled from the Normal-Inverse Gamma distribution $q(\mu, \sigma^2)$ through hierarchical variational inference. Red circles denote the learning parameters in the BNN, black circles denote the random variables sampled from the described probability distributions, and the black arrows indicate the sampling order.

$q(w)$ as a practical estimator to approximate the true adv-posterior, where the formulation can be written as:

$$
\begin{aligned}
\log p(y \mid x^{adv}) = \mathcal{D}_{KL}(q(w) \mid\mid p(w \mid \mathcal{D}^{adv})) \\
+ \underbrace{\mathop{\mathbb{E}}_{w \sim q(w)} \left[\log p(y \mid x^{adv}, w) \right] - \mathcal{D}_{KL}(q(w) \mid\mid p(w))}_{\text{ELBO}}.
\end{aligned}
\tag{4}
$$

We should minimize KL divergence $\mathcal{D}_{KL}\left(q(w) \mid\mid p(w \mid \mathcal{D}^{adv})\right)$ to make the probability-distance close between the two probability distributions. But, this KL divergence is still intractable measurement, and we can alternatively maximize the ELBO in Eq. (4), which has the same effect to minimize this KL divergence. This is because the log-probability $\log p(y \mid x^{adv})$ in Eq. (4) is consistent with the change of the weight parameters w. The formulation of variational inference also can be represented to lower bound as: $\log p(y \mid x^{adv}) \geq$ **ELBO**.

Some of the studies (Mescheder et al., 2017; Ye & Zhu, 2018; Wang et al., 2019a; Carbone et al., 2020) to improve adversarial robustness by maximizing the ELBO. Others (Feinman et al., 2017; Smith & Gal, 2018; Wang et al., 2018) are to detect the adversarial examples by predicting Bayesian uncertainty (Gal & Ghahramani, 2016; Kendall & Gal, 2017; Pearce et al., 2020), also based on the maximum ELBO. The previous studies have implicitly examined the true adv-posterior to better learn the network parameters or spaces, instead of directly shaping it.

Unlike the previous studies, Liu et al. (2019) proposes "adversarial-BNN" which combines adversarial training and the BNN to improve adversarial robustness by dealing with the true adv-posterior explicitly. Liu et al. designs the posterior $q(w) = \mathcal{N}(\mu, \sigma^2)$ and considers Gaussian parameters (e.g., mean, variance) of it as learning parameters.

The first term in the ELBO represents the expected log-likelihood calculated from the cross-entropy as follows: $\frac{1}{N} \sum_{i=1}^{N} J\left(f_{w^{(i)}}(x^{adv}), y\right)$ by Monte-Carlo sampling, where N denotes the sampling number. As shown in Fig. 1(a), the weight parameter $w^{(i)}$ is sampled by the posterior's mean and variance μ, σ^2, such that $w^{(i)} = \mu + \sigma\epsilon^{(i)}$. Here, $\epsilon^{(i)}$ is the stochastic sampler, such that $\epsilon^{(i)} \sim \mathcal{N}(0, 1)$. The second term represents a regularization term for the Gaussian parameters in the BNN. This term can be computed from the KL divergence between the posterior and an prior $p(w)$ which is usually set to $\mathcal{N}(0, 1)$ for variational inference. If the Gaussian parameters of the posterior are not learned to follow those of the mean prior, the KL divergence increases.

The KL divergence at the second term has a role of a BNN regularizer in ELBO, and this regularizer is an important factor for adversarial robustness. This is because if the BNN regularizer is increased unexpectedly, the minimum ELBO produces an ill-posed posterior, creating weak adversarial robustness. In contrast, as the BNN regularizer is reduced, the maximum ELBO allows the well-posed inference by the true adv-posterior. In addition to the aspect of the ELBO, there are many studies showing that high regularization performance improves adversarial robustness (Saito et al., 2018; Yu et al., 2019; Zhang & Liang, 2019; Sun et al., 2019; Terjék, 2020; Zhang et al., 2020).

3 PROPOSED METHOD

Adversarial training with BNN has expanded generic probability to adversarial probability, and has shown the improvement of adversarial robustness. However, as mentioned in the Section 1, the vanished stochasticity declines adversarial defense functionality of the BNN. To investigate the BNN's stochasticity, we introduce the conjugate prior, and develop the ELBO with the conjugate prior. The conjugate prior can provide a key to how the Gaussian parameters of the (approximate) posterior $q(w)$ are trained during adversarial training. Based on our findings in the conjugate view, we will design an enhanced Bayesian regularizer that solves the stochasticity problem causing weak adversarial robustness. Before we explain the proposed method, we firstly introduce two parts: (i) the conjugate prior of the Gaussian posterior, (ii) hierarchical variational inference for building a new ELBO with the conjugate prior.

The (Gaussian) Conjugate Prior. The conjugate prior of the Gaussian posterior is called the Gaussian conjugate prior. It is the probability distribution for the Gaussian parameters of the posterior, called the Normal-Inverse Gamma distribution. In the conjugate view, the posterior $q(w)$ is no longer the posterior, but is the likelihood $q(w|\mu, \sigma^2)$ given the Gaussian parameters as random variables. The conjugate prior $q(\mu, \sigma^2)$ is employed to analyze the probability distribution for the Gaussian parameters. The formulation of the Gaussian conjugate prior can be written as:

$$q(\mu, \sigma^2) = \mathcal{N}\left(\mu \mid \mu_0, \sigma_0^2\right) \mathcal{IG}\left(\sigma^2 \mid \nu, \psi\right). \tag{5}$$

The conjugate prior can be factorized into the Normal distribution $q(\mu) = \mathcal{N}\left(\mu \mid \mu_0, \sigma_0^2\right)$ and the Inverse Gamma distribution $q(\sigma^2) = \mathcal{IG}\left(\sigma^2 \mid \nu, \psi\right)$ independently by mean-field approximation (Kingma & Welling, 2014). In the Normal distribution, μ_0 denotes the posterior's mean prior knowledge, and σ_0^2 denotes the variance of the posterior's mean. In addition, ν, in the Inverse Gamma distribution, denotes the degree of freedom on positive real set which determines the shape of this distribution, and ψ denotes the posterior's variance prior knowledge. Each of the Gaussian parameters is sampled independently from the conjugate prior, where the Normal distribution samples the posterior's mean, and the Inverse Gamma distribution samples the variance of that.

Importantly, the conjugate prior has more number of the tractable parameters μ_0, σ_0^2, ψ, and ψ than the posterior $q(w)$, which help representing the weight parameters. As illustrated in Fig. 1(b), the tractable parameters generate the mean μ and the variance σ^2 of the posterior, where $\mu = \mu_0 + \sigma_0\epsilon_\mu$, and $\sigma^2 = \psi\epsilon_{\sigma^2}$, such that $\epsilon_\mu \sim \mathcal{N}(0, 1)$, $\epsilon_{\sigma^2} \sim \mathcal{IG}(\nu, 1)$. In addition, the generated mean and the variance are both used to sample the weight parameters: $w = \mu_0 + \sigma_0\epsilon_\mu + (\psi\epsilon_{\sigma^2})^{1/2}\epsilon$. We call it Normal-Inverse Gamma sampling.

Hierarchical Variational Inference. The conjugate prior in the form of $q(\mu, \sigma^2)$ can be used to sample the weight parameters with more tractable parameters for complex representation. Next, we should find a (hierarchical) true adv-posterior $p(\mu, \sigma^2 \mid \mathcal{D}^{adv})$ for adversarial robustness. At this time, the conjugate prior can be also employed as an approximate hierarchical posterior. Thus, it is possible to design hierarchical variational inference to obtain the true adv-posterior. We modify the ELBO in Eq. (4) to build up a new ELBO with the conjugate prior, namely *hierarchical-ELBO*, which can be written as:

$$\mathbb{E}_{(\mu, \sigma^2) \sim q(\mu, \sigma^2)}\left[\log p(y \mid x^{adv}, \mu + \sigma\epsilon)\right] - \mathcal{D}_{KL}(q(\mu, \sigma^2) \mid\mid p(\mu, \sigma^2)). \tag{6}$$

The first term above stands for the classification performance taken from the cross-entropy. The second term represents the BNN regularizer in hierarchical-ELBO equivalent to that in the ELBO as depicted in Eq. (4). The second term can be computed by the KL divergence between the conjugate prior and a hierarchical prior $p(\mu, \sigma^2)$. Note that the hierarchical prior is factorized into the mean prior $p(\mu \mid \sigma^2)$ and the variance prior $p(\sigma^2)$. Then, the above KL divergence can be decomposed into two equations: (i) $\mathbb{E}_{\sigma^2 \sim q(\sigma^2)}\left[\mathcal{D}_{KL}(q(\mu) \mid\mid p(\mu \mid \sigma^2))\right]$ and (ii) $\mathcal{D}_{KL}(q(\sigma^2) \mid\mid p(\sigma^2))$ (see Appendix A). In order to make two equations tractable, both the mean prior and the variance prior should be set, similar to the setting of the prior $p(w)$ in the ELBO. We set the mean prior to $\mathcal{N}\left(0, \lambda^{-1}\sigma^2\right)$ for (i), where the posterior's mean prior knowledge is zero, and λ denotes inverse scale factor to the variance σ^2. In addition, the variance prior is set to $\mathcal{IG}(\nu, 1)$ for (ii), where the posterior's variance prior knowledge is one. Here, ν is set to the same parameters both in $q(\sigma^2)$ and $p(\sigma^2)$ to reduce computational complexity in calculating (ii).

On the above settings for the hierarchical prior $p(\mu, \sigma^2)$, the second term can be tractably expanded with the summation of the two equations (see Appendix B), which can be written as:

$$\mathcal{D}_{KL}(q(\mu, \sigma^2) \parallel p(\mu, \sigma^2)) = \frac{1}{M} \sum_{j=1}^{M} [\nu_j \frac{\lambda_j(\sigma_{0,j}^2 + \mu_{0,j}^2) + 2}{2\psi_j} + \log \frac{\psi_j^{\frac{2\nu_j+1}{2}}}{(\lambda_i \sigma_{0,j}^2)^{\frac{1}{2}}} - \frac{2\nu_j+1}{2} - \frac{1}{2}G(\nu_j)], \quad (7)$$

where M denotes the number of weight parameters in the deep neural networks, and j represents the j^{th} parameters for the j^{th} posterior. The function G has the formulation of Digamma function, such that $G(\nu_j) = \Gamma'(\nu_j)/\Gamma(\nu_j)$.

ELBO vs Hierarchical-ELBO. Until controlling the parameters λ, ν of the hierarchical prior $p(\mu, \sigma^2)$, the ELBO is essentially same to the hierarchical-ELBO. In above condition, the BNN regularizer in the ELBO is also identical to that in the hierarchical-ELBO. This is because it is nothing but we just have replaced the weight parameters in the ELBO with the Gaussian parameters for the extension, as described in Eq. (6). Different from the fixed prior $p(w) = \mathcal{N}(0, 1)$ in the ELBO, controllable parameters λ, ν of the hierarchical prior $p(\mu, \sigma^2)$ can allow the BNN regularizer in the hierarchical-ELBO to change adaptively. As a consequence, λ and ν can reduce the KL divergence, helping to find the well-posed posterior with the maximum hierarchical-ELBO. The formulation of the hierarchical-ELBO can be also represented to lower bound with the ELBO as follows: $\log p(y \mid x^{adv}) \geq$ **hierarchical-ELBO** $\geq$ **ELBO**, where the hierarchical-ELBO better approximates the true adv-posterior than the ELBO.

Enhanced Bayesian Regularizer. Now, we focus on the optimization of the BNN regularizer in the hierarchical-ELBO to reduce the KL divergence. By gradient results over the controllable parameters: $\frac{\partial}{\partial \lambda_j} \mathcal{D}_{KL} = 0$ and $\frac{\partial}{\partial \nu_j} \mathcal{D}_{KL} = 0$, we can easily obtain the optimal value $\lambda^* = \frac{\psi}{\nu(\sigma_0^2 + \mu_0^2)}$, but the optimal value ν^* is intractable to acquire, since the gradient result is intractable as follows: $\frac{1}{2}\frac{d}{d\nu}G(\nu) - \frac{1}{2\nu} = \frac{1}{\psi} + \log \psi - 1$. We should indirectly find the optimal value ν^* by applying the above gradient results to the KL divergence, which can be written as:

$$\mathcal{D}_{KL}(q(\mu, \sigma^2) \parallel p(\mu, \sigma^2)) = \frac{1}{M} \sum_{j=1}^{M} [\frac{1}{2} \log \left(1 + \frac{\mu_{0,j}^2}{\sigma_{0,j}^2}\right) + \underbrace{\frac{\nu_j}{2}\frac{d}{d\nu_j}G(\nu_j) - \frac{1}{2}G(\nu_j) + \frac{1}{2}\log \nu_j - \frac{1}{2}}_{H(\nu_j)}], \quad (8)$$

where the function $H(\nu_j)$ is decreasing and convergent function (see Appendix C). We examine this function is converged to zero, as ν_j gets large enough. With the optimal value ν^* infinite, the KL divergence in the hierarchical-ELBO can be definitely reduced.

Finally, we propose the enhanced Bayesian regularizer as follows: $\frac{1}{M} \sum_{j=1}^{M} [\frac{1}{2} \log \left(1 + \frac{\mu_{0,j}^2}{\sigma_{0,j}^2}\right)]$. The proposed method provides more tight lower bound than the ELBO, such that the formulation can be described as follows: $\log p(y \mid x^{adv}) \geq$ **hierarchical-ELBO** $>$ **ELBO**. Based on the tight lower bound, the enhanced Bayesian regularizer aids to the acquisition of the well-posed posterior to boost adversarial robustness. Consequently, we have verified that the proposed method considerably intensifies the BNN regularizer by designing the hierarchical-ELBO. In practical, depending on the learned conjugate prior in each iteration, we can compute the proposed method for each, such as Expectation-Maximization (EM) step. We describe the algorithm for the proposed method below.

Algorithm 1 Code for adversarial training in the BNN with the enhanced Bayesian regularizer

---

1: **Required:** α (learning rate), μ_0 and σ_0 (learning parameters)
2: **for** (x, y) in $\mathcal{D}$ **do** ▷ Training procedure per epoch
3:     $w \leftarrow \mu_0 + \sigma_0 \epsilon, \epsilon \sim \mathcal{N}(0, 1)$ ▷ Sample the weight parameters
4:     $x^{adv} \leftarrow \text{attack}(x, y, w)$ ▷ PGD Attack to generate adversarial examples
5:     $\hat{y} \leftarrow f_w(x^{adv})$ ▷ Predict the outputs given the adversarial examples
6:     $\mathcal{L}_1 \leftarrow J(\hat{y}, y)$ ▷ Calculate the cross-entropy loss
7:     $\mathcal{L}_2 \leftarrow \sum_{j=1}^{M} \frac{1}{2} \log(1 + \frac{\mu_{0,j}^2}{\sigma_{0,j}^2})$ ▷ Calculate the proposed method
8:     $\mathcal{L} \leftarrow \mathcal{L}_1 + \mathcal{L}_2$ ▷ Calculate the hierarchical-ELBO in Eq. (6)
9:     $(\mu_0, \sigma_0) \leftarrow (\mu_0 - \alpha \frac{\partial \mathcal{L}}{\partial \mu_0}, \sigma_0 - \alpha \frac{\partial \mathcal{L}}{\partial \sigma_0})$ ▷ Update the learning parameters
10: **end for**

Theoretical Analysis. On the above optimization, the Inverse Gamma distributions are converged to delta probability distribution, such that $\lim_{\nu^* \to \infty} q(\sigma^2) = \delta(\sigma^2)$, $\lim_{\nu^* \to \infty} p(\sigma^2) = \delta(\sigma^2)$. Hence, we can discover that the BNN from the ELBO generally loses its stochasticity after its training with the posterior $q(w)$ via the zero convergence variance. For the hierarchical-ELBO, the tractable parameter ψ is not required anymore during sampling the weight parameters in Fig. 1(b). Only the Normal distribution $q(\mu) = \mathcal{N}(\mu_0, \sigma_0^2)$ in the conjugate prior is involved in sampling the weight parameters as follows: $w = \mu_0 + \sigma_0 \epsilon$. Here, $q(\mu)$ is learned to follow the optimized mean prior, such that $\lim_{\lambda \to \lambda^*} p(\mu \mid \sigma^2) = \mathcal{N}(0, k(\mu_0^2 + \sigma_0^2))$, where k is statistically proven to be above one (see Appendix D). In other words, the variance σ_0^2 of $q(\mu)$ follows the variance $k(\mu_0^2 + \sigma_0^2)$ of the mean prior, which is definitely larger than the variance σ_0^2. Therefore, we verify that the proposed method allows for the enhancement of the BNN's stochasticity through hierarchical-ELBO.

4 EXPERIMENTS

In this section, we validate the robustness of our proposed method compared to strong baselines in various datasets. Since our method is inspired by adversarial training (Madry et al., 2018), BNN (Blundell et al., 2015), and adversarial training with BNN (Liu et al., 2019), these three models are natural baselines. We also include their performances without any defense (See Appendix F).

Implementation Details. Recent papers agree with that adversarial training methods have difficulty training with high dimensional data (Kurakin et al., 2017; Tramèr et al., 2018; Schmidt et al., 2018). To test the general robustness of our regularizer, we conduct experiments on not only a standard low dimensional dataset (CIFAR-10), but also more challenging datasets such as CIFAR-100, STL-10 (Coates et al., 2011), and Tiny-ImageNet (Le & Yang, 2015). STL-10 has 5,000 training images and 8,000 testing images with a size of 96×96 pixels. Tiny-ImageNet is a small subset of ImageNet dataset. It contains 100,000 training images, 10,000 validation images, and 10,000 testing images separated in 200 different classes. The spatial dimensions of the images are 64×64 pixels. For the implementation, we set the learning rate to 0.01, and initialize the learning parameters (mean and variance) to each 0 and 0.1 with Adam (Kingma & Ba, 2015) to fairly validate adversarial robustness.

Evaluation under white-box L_∞-PGD attack. First of all, we compare the accuracy of each model under the white-box L_∞-PGD attack (first row in the Fig.2). In this experiment, we apply the PGD attack on the test set as mentioned in Section 2.1 and adjust the maximum L_∞ norm of perturbation δ from 0 to 0.03. Two vanilla networks, VGG16 and Model A[1], are adopted as our baseline. Model A is trained for STL-10 while the other datasets are trained via VGG16. Each model is trained with 0.03 L_∞ norm of perturbation during the adversarial training stage. Adversarial training with our enhanced Bayesian regularizer with outperforms other baselines in all datasets. Considering the performance of each model without any defense(See Appendix F), our superior robustness is not just from a improvement of performance. Furthermore, there is no excessive computational burden to implement our regularizer. According to the Fig. 1 and previous theoretical analysis on the nonnecessity of ψ, we only need μ and σ^2 as learning parameters, which are the same number of parameters as the adversarial-BNN (Liu et al., 2019).

Tab. 1 shows statistical summaries of the weight parameters such as mean, variance and KL divergence in ELBO. The statistical results are in line with our earlier statement that the variance of the posterior $q(w)$ converges to small value. Contrary to the initial intention of adopting Bayesian neural networks, this phenomenon results in lacking its stochasticity and making the broken BNN regularizer(increased KL divergence in the ELBO). On the other hand, our enhanced regularizer shows comparatively lower KL divegernce in the ELBO and is expected to have a strong regularization effect. The discrepancy becomes greater in large datasets with more classes such as tiny-imagenet. Thus, the experiment results show an empirical evidence on the recall of vanished stochasticity via our enhanced Bayesian regularizer.

Evaluation under EOT-PGD attack. We also evaluate the accuracy of each model under the Expectation over Transformation(EOT)-PGD attack mentioned in Section 2.1 (second row in the Fig. 2). In general, a randomized network provides a stochastic tolerance obfuscating the gradient-based

---

[1]Publicly available at https://github.com/aaron-xichen/pytorch-playground/tree/master/stl10

Table 1: Comparison of the statistical summaries of weight parameters. We include mean, variance, and KL divergence. The statistical results of our enhanced Bayesian regularizer is marked in **bold**. Note that our proposed model has non-zero mean, higher variance, and lower KLD. We calculate KLD for all layers and use the sum of KLD.

	CIFAR-10			STL-10			CIFAR-100			Tiny-ImageNet		
	Mean	Variance	KLD	Mean	Variance	KLD	Mean	Variance	KLD	Mean	Variance	KLD
adv-Ours	0.003	**0.137**	**0.9**	0.001	**0.097**	**0.846**	0.003	**0.118**	**1.0**	0.015	**0.226**	**1.4**
adv-BNN	0	0.073	4.7	0	0.054	1.286	0	0.073	8.9	0	0.069	15.5

Figure 2: Accuracy under L_∞-normal PGD attack(first row) and EOT-PGD attack(second row) on different datasets: CIFAR-10, STL-10, CIFAR-100, and Tiny-ImageNet.

attack, which uses a single sample of the randomness. In other words, the BNN's stochasticity makes an attacker confused to incorrectly estimate the true gradient. However, EOT attack easily bypasses this stochasticity by taking the expectation over multiple weight parameters. Now that our enhanced Bayesian regularizer surpasses other baselines on all datasets against EOT-PGD attack, we can insist that our proposed regularizer is not just obfuscating the gradient, but helping neural network learn and optimize strong robustness. We also find that our regularizer shows a stronger robustness on the complex dataset with a large number of classes.

The robustness based on our re-birth of BNN's stochasticity against EOT-PGD attacks can be mathematically represented by Taylor series. Let $f(w) = \nabla J(x, w)$ where w denotes the weight parameters $w = \mu + \sigma\epsilon$, and J denotes the cross-entropy loss. If we take the expectation of $f(w)$ over weight parameters, it satisfies $\mathbb{E}_w[f(w)] = \mathbb{E}_\epsilon[f(\mu + \sigma\epsilon)]$, which can be written as $\mathbb{E}_\epsilon[f(\mu) + \sigma\epsilon f'(\mu) + \frac{(\sigma\epsilon)^2}{2!} f''(\mu) + \cdots]$. Here, the actual gradient of adversarial training is just the same as $\mathbb{E}_\epsilon[f(\mu)] = f(\mu)$ because σ is not used. Moreover, we find that the variance σ^2 of the weight parameters becomes infinitesimal and converges to zero value in adversarial training with BNN. Thus, Taylor series ends up with a first-order approximation $\mathbb{E}_\epsilon[f(\mu) + \sigma\epsilon f'(\mu)] = f(\mu)$, which yields the same stochasticity with the adversarial training. On the other hand, our enhanced Bayesian regularizer can maintain BNN's stochasticity with large enough variance. As a result, the remaining intractable terms of Taylor series still survive and cause an attacker to have difficulty estimating the actual gradient (see Appendix E).

5 CONCLUSION

As mentioned in *Theoretical Analysis* at the Section 3, we have found that the BNN generally loses its stochasticity after its training with the posterior via the zero convergence variance. To solve it, we newly design the enhanced Bayesian regularizer with improved stochasticity through the hierarchical-ELBO built with the conjugate prior. We believe the hierarchical-ELBO provides the true adv-posterior by the tight lower bound more than the ELBO, thus boosting the adversarial robustness. Further progress can be made by investigating the hierarchical-ELBO to explore generative models like VAE and GAN for scalable machine learning tasks.

REFERENCES

G. Apruzzese, M. Colajanni, L. Ferretti, and M. Marchetti. Addressing adversarial attacks against security systems based on machine learning. In *2019 11th International Conference on Cyber Conflict (CyCon)*, volume 900, pp. 1–18, 2019.

Anish Athalye, Nicholas Carlini, and David A. Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *ICML*, pp. 274–283, 2018a. URL http://proceedings.mlr.press/v80/athalye18a.html.

Anish Athalye, Logan Engstrom, Andrew Ilyas, and Kevin Kwok. Synthesizing robust adversarial examples. volume 80 of *Proceedings of Machine Learning Research*, pp. 284–293, Stockholmsmässan, Stockholm Sweden, 10–15 Jul 2018b. PMLR. URL http://proceedings.mlr.press/v80/athalye18b.html.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural networks. In *Proceedings of the 32nd International Conference on International Conference on Machine Learning - Volume 37*, ICML'15, pp. 1613–1622. JMLR.org, 2015.

Jacob Buckman, Aurko Roy, Colin Raffel, and Ian Goodfellow. Thermometer encoding: One hot way to resist adversarial examples. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=S18Su--CW.

Ginevra Carbone, Matthew Wicker, Luca Laurenti, Andrea Patane, Luca Bortolussi, and Guido Sanguinetti. Robustness of Bayesian Neural Networks to Gradient-Based Attacks. *arXiv e-prints*, art. arXiv:2002.04359, February 2020.

N. Carlini and D. Wagner. Towards evaluating the robustness of neural networks. In *2017 IEEE Symposium on Security and Privacy (SP)*, pp. 39–57, 2017.

Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, AISec '17, pp. 3–14, New York, NY, USA, 2017. Association for Computing Machinery. ISBN 9781450352024. doi: 10.1145/3128572.3140444. URL https://doi.org/10.1145/3128572.3140444.

Pin-Yu Chen, Huan Zhang, Yash Sharma, Jinfeng Yi, and Cho-Jui Hsieh. Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models. *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, 2017.

Moustapha Cisse, Piotr Bojanowski, Edouard Grave, Yann Dauphin, and Nicolas Usunier. Parseval networks: Improving robustness to adversarial examples. *arXiv preprint arXiv:1704.08847*, 2017.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 215–223, 2011.

Guneet S. Dhillon, Kamyar Azizzadenesheli, Jeremy D. Bernstein, Jean Kossaifi, Aran Khanna, Zachary C. Lipton, and Animashree Anandkumar. Stochastic activation pruning for robust adversarial defense. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=H1uR4GZRZ.

K. Eykholt, I. Evtimov, E. Fernandes, B. Li, A. Rahmati, C. Xiao, A. Prakash, T. Kohno, and D. Song. Robust physical-world attacks on deep learning visual classification. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1625–1634, 2018.

Reuben Feinman, Ryan R. Curtin, Saurabh Shintre, and Andrew B. Gardner. Detecting adversarial samples from artifacts. *ArXiv*, abs/1703.00410, 2017.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *Proceedings of the 33rd International Conference on International Conference on Machine Learning - Volume 48*, ICML'16, pp. 1050–1059. JMLR.org, 2016.

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2015. URL http://arxiv.org/abs/1412.6572.

Alex Graves. Practical variational inference for neural networks. In J. Shawe-Taylor, R. S. Zemel, P. L. Bartlett, F. Pereira, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 24*, pp. 2348–2356. Curran Associates, Inc., 2011. URL http://papers.nips.cc/paper/4329-practical-variational-inference-for-neural-networks.pdf.

Kathrin Grosse, Praveen Manoharan, Nicolas Papernot, Michael Backes, and Patrick McDaniel. On the (statistical) detection of adversarial examples. *arXiv preprint arXiv:1702.06280*, 2017.

Chuan Guo, Mayank Rana, Moustapha Cisse, and Laurens van der Maaten. Countering adversarial images using input transformations. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=SyJ7ClWCb.

Matthias Hein and Maksym Andriushchenko. Formal guarantees on the robustness of a classifier against adversarial manipulation. In *Advances in Neural Information Processing Systems*, pp. 2266–2276, 2017.

José Miguel Hernández-Lobato and R. Adams. Probabilistic backpropagation for scalable learning of bayesian neural networks. In *ICML*, 2015.

Matthew D. Hoffman, David M. Blei, Chong Wang, and John Paisley. Stochastic variational inference. *Journal of Machine Learning Research*, 14(4):1303–1347, 2013. URL http://jmlr.org/papers/v14/hoffman13a.html.

Ruitong Huang, Bing Xu, Dale Schuurmans, and Csaba Szepesvári. Learning with a strong adversary. *http://arxiv.org/abs/1511.03034*, 11 2015.

Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 5574–5584. Curran Associates, Inc., 2017. URL http://papers.nips.cc/paper/7141-what-uncertainties-do-we-need-in-bayesian-deep-learning-for-computer-vision.pdf.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations*, 2014. URL https://openreview.net/forum?id=33X9fd2-9FyZd.

Alexey Kurakin, Ian J. Goodfellow, and Samy Bengio. Adversarial machine learning at scale. 2017. URL https://arxiv.org/abs/1611.01236.

Ya Le and Xuan Yang. Tiny imagenet visual recognition challenge. *CS 231N*, 7, 2015.

Xuanqing Liu, Minhao Cheng, Huan Zhang, and Cho-Jui Hsieh. Towards robust neural networks via random self-ensemble. In Vittorio Ferrari, Martial Hebert, Cristian Sminchisescu, and Yair Weiss (eds.), *Computer Vision – ECCV 2018*, pp. 381–397, Cham, 2018. Springer International Publishing. ISBN 978-3-030-01234-2.

Xuanqing Liu, Yao Li, Chongruo Wu, and Cho-Jui Hsieh. Adv-BNN: Improved adversarial defense through robust bayesian neural network. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=rk4Qso0cKm.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=rJzIBfZAb.

Lars Mescheder, Sebastian Nowozin, and Andreas Geiger. Adversarial variational bayes: Unifying variational autoencoders and generative adversarial networks. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, pp. 2391–2400. JMLR.org, 2017.

Jan Hendrik Metzen, Tim Genewein, Volker Fischer, and Bastian Bischoff. On detecting adversarial perturbations. *arXiv preprint arXiv:1702.04267*, 2017.

John Paisley, David M. Blei, and Michael I. Jordan. Variational bayesian inference with stochastic search. In *Proceedings of the 29th International Coference on International Conference on Machine Learning*, ICML'12, pp. 1363–1370, Madison, WI, USA, 2012. Omnipress. ISBN 9781450312851.

Nicolas Papernot, Patrick D. McDaniel, Xi Wu, Somesh Jha, and Ananthram Swami. Distillation as a defense to adversarial perturbations against deep neural networks. *2016 IEEE Symposium on Security and Privacy (SP)*, pp. 582–597, 2016.

Nicolas Papernot, P. McDaniel, Ian J. Goodfellow, S. Jha, Z. Y. Celik, and A. Swami. Practical black-box attacks against machine learning. *Proceedings of the 2017 ACM on Asia Conference on Computer and Communications Security*, 2017.

Tim Pearce, Felix Leibfried, and Alexandra Brintrup. Uncertainty in neural networks: Approximately bayesian ensembling. volume 108 of *Proceedings of Machine Learning Research*, pp. 234–244, Online, 26–28 Aug 2020. PMLR. URL `http://proceedings.mlr.press/v108/pearce20a.html`.

Aditi Raghunathan, Jacob Steinhardt, and Percy Liang. Certified defenses against adversarial examples. *arXiv preprint arXiv:1801.09344*, 2018.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. volume 32 of *Proceedings of Machine Learning Research*, pp. 1278–1286, Bejing, China, 22–24 Jun 2014. PMLR. URL `http://proceedings.mlr.press/v32/rezende14.html`.

Ihai Rosenberg, Asaf Shabtai, Yuval Elovici, and Lior Rokach. Adversarial Learning in the Cyber Security Domain. *arXiv e-prints*, art. arXiv:2007.02407, July 2020.

Y. E. Sagduyu, Y. Shi, and T. Erpek. Iot network security from the perspective of adversarial deep learning. In *2019 16th Annual IEEE International Conference on Sensing, Communication, and Networking (SECON)*, pp. 1–9, 2019.

Kuniaki Saito, Yoshitaka Ushiku, Tatsuya Harada, and Kate Saenko. Adversarial dropout regularization. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=HJIoJWZCZ`.

Tim Salimans and David A. Knowles. Fixed-form variational posterior approximation through stochastic linear regression. *Bayesian Anal.*, 8(4):837–882, 12 2013. doi: 10.1214/13-BA858. URL `https://doi.org/10.1214/13-BA858`.

Ludwig Schmidt, Shibani Santurkar, Dimitris Tsipras, Kunal Talwar, and Aleksander Madry. Adversarially robust generalization requires more data. In *Advances in Neural Information Processing Systems*, pp. 5014–5026, 2018.

Lewis Smith and Yarin Gal. Understanding measures of uncertainty for adversarial example detection. In Amir Globerson and Ricardo Silva (eds.), *Proceedings of the Thirty-Fourth Conference on Uncertainty in Artificial Intelligence, UAI 2018, Monterey, California, USA, August 6-10, 2018*, pp. 560–569. AUAI Press, 2018. URL `http://auai.org/uai2018/proceedings/papers/207.pdf`.

S. Sun, P. Guo, L. Xie, and M. Hwang. Adversarial regularization for attention based end-to-end robust speech recognition. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 27(11):1826–1838, 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *International Conference on Learning Representations*, 2014. URL `http://arxiv.org/abs/1312.6199`.

Dávid Terjék. Adversarial lipschitz regularization. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=Bke_DertPB`.

Florian Tramèr, Alexey Kurakin, Nicolas Papernot, Ian Goodfellow, Dan Boneh, and Patrick McDaniel. Ensemble adversarial training: Attacks and defenses. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=rkZvSe-RZ`.

Kang Wang, Rui Zhao, Hui Su, and Qiang Ji. Generalizing eye tracking with bayesian adversarial learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019a.

Kuan-Chieh Wang, Paul Vicol, James Lucas, Li Gu, Roger B. Grosse, and Richard S. Zemel. Adversarial distillation of bayesian neural network posteriors. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 5177–5186. PMLR, 2018. URL `http://proceedings.mlr.press/v80/wang18i.html`.

Xianmin Wang, Jing Li, Xiaohui Kuang, Yu an Tan, and Jin Li. The security of machine learning in an adversarial setting: A survey. *Journal of Parallel and Distributed Computing*, 130:12 – 23, 2019b. ISSN 0743-7315. doi: https://doi.org/10.1016/j.jpdc.2019.03.003. URL `http://www.sciencedirect.com/science/article/pii/S0743731518309183`.

Max Welling and Yee Whye Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, ICML'11, pp. 681–688, Madison, WI, USA, 2011. Omnipress. ISBN 9781450306195.

Eric Wong and Zico Kolter. Provable defenses against adversarial examples via the convex outer adversarial polytope. In *International Conference on Machine Learning*, pp. 5286–5295. PMLR, 2018.

Weilin Xu, David Evans, and Yanjun Qi. Feature squeezing: Detecting adversarial examples in deep neural networks. *arXiv preprint arXiv:1704.01155*, 2017.

Nanyang Ye and Zhanxing Zhu. Bayesian adversarial learning. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 6892–6901. Curran Associates, Inc., 2018. URL `http://papers.nips.cc/paper/7921-bayesian-adversarial-learning.pdf`.

Bing Yu, Jingfeng Wu, Jinwen Ma, and Zhanxing Zhu. Tangent-normal adversarial regularization for semi-supervised learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Valentina Zantedeschi, Maria-Irina Nicolae, and Ambrish Rawat. Efficient defenses against adversarial attacks. *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, 2017.

Han Zhang, Zizhao Zhang, Augustus Odena, and Honglak Lee. Consistency regularization for generative adversarial networks. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=S1lxKlSKPH`.

Yuchen Zhang and Percy Liang. Defending against whitebox adversarial attacks via randomized discretization. In *AISTATS*, 2019.

Roland S. Zimmermann. Comment on "Adv-BNN: Improved Adversarial Defense through Robust Bayesian Neural Network". *arXiv e-prints*, art. arXiv:1907.00895, July 2019.

A   DECOMPOSITION OF KL DIVERGENCE IN HIERARCHICAL-ELBO

The conjugate prior $q(\mu, \sigma^2)$ can be independently factorized into the Normal distribution $q(\mu)$ and the Inverse Gamma distribution $q(\sigma^2)$ by the mean-field approximation. The hierarchical prior $p(\mu, \sigma^2)$ is factorized into the mean prior $p(\mu \mid \sigma^2)$ and the variance prior $p(\sigma^2)$. The KL divergence in the hierarchical-ELBO can be decomposed as follows:

$$\mathcal{D}_{KL}(q(\mu, \sigma^2) \| p(\mu, \sigma^2))$$

$$= \iint q(\mu, \sigma^2) \log \frac{q(\mu, \sigma^2)}{p(\mu, \sigma^2)} d\mu d\sigma^2$$

$$= \iint q(\mu)q(\sigma^2) \log \frac{q(\mu)q(\sigma^2)}{p(\mu^2 \mid \sigma^2)p(\sigma^2)} d\mu d\sigma^2$$

$$= \iint q(\mu)q(\sigma^2) \log \frac{q(\mu)}{p(\mu \mid \sigma^2)} d\mu d\sigma^2 + \iint q(\mu)q(\sigma^2) \log \frac{q(\sigma^2)}{p(\sigma^2)} d\mu d\sigma^2 \qquad (9)$$

$$= \int q(\sigma^2) \left[\int q(\mu) \log \frac{q(\mu)}{p(\mu \mid \sigma^2)} d\mu \right] d\sigma^2 + \int q(\sigma^2) \log \frac{q(\sigma^2)}{p(\sigma^2)} d\sigma^2$$

$$= E_{\sigma^2 \sim q(\sigma^2)} \left[\mathcal{D}_{KL}(q(\mu) \| p(\mu \mid \sigma^2)) \right] + \mathcal{D}_{KL}(q(\sigma^2) \| p(\sigma^2)).$$

B   FULL EXPANSION OF KL DIVERGENCE IN HIERARCHICAL-ELBO

The first term in the KL divergence at the hierarchical-ELBO can be written as:

$$E_{\sigma^2 \sim q(\sigma^2)} \left[\mathcal{D}_{KL}(q(\mu) \| p(\mu \mid \sigma^2)) \right]$$

$$= \sum_{j=1}^{M} E_{\sigma_j^2 \sim q(\sigma_j^2)} \left[\mathcal{D}_{KL}(q(\mu_j) \| p(\mu_j \mid \sigma_j^2)) \right] \quad \textit{(by Lemma B.4)}$$

$$= \sum_{j=1}^{M} E_{\sigma_j^2 \sim q(\sigma_j^2)} \left[\frac{\sigma_{0,j}^2 + \mu_{0,j}^2}{2\lambda_j^{-1}\sigma_j^2} + \frac{1}{2} \log \frac{\lambda_j^{-1}\sigma_j^2}{\sigma_{0,j}^2} - \frac{1}{2} \right] \quad \textit{(by Lemma B.1)} \qquad (10)$$

$$= \sum_{j=1}^{M} \left[\nu_j \frac{\sigma_{0,j}^2 + \mu_{0,j}^2}{2\lambda_j^{-1}\psi_j} + \frac{1}{2} \log \frac{\lambda_j^{-1}\psi_j}{\sigma_{0,j}^2} - \frac{1}{2} \frac{\Gamma'(\nu_j)}{\Gamma(\nu_j)} - \frac{1}{2} \right], \quad \textit{(by Lemma B.2)}$$

where

$$q(\mu_j) = \mathcal{N}(\mu_j \mid \mu_{0,j}, \sigma_{0,j}^2), \quad p(\mu_j \mid \sigma_j^2) = \mathcal{N}(\mu_j \mid 0, \lambda_i^{-1}\sigma_j^2). \qquad (11)$$

The second term in the KL divergence at the hierarchical-ELBO can be written as:

$$\mathcal{D}_{KL}(q(\sigma^2) \parallel p(\sigma^2))$$

$$= \sum_{j=1}^{M} \mathcal{D}_{KL}(q(\sigma_j^2) \parallel p(\sigma_j^2)) \quad \textit{(by Lemma B.4)} \tag{12}$$

$$= \sum_{j=1}^{M} \left[\nu_j \log \psi_j - \nu_j \frac{\psi_j - 1}{\psi_j} \right] \quad \textit{(by Lemma B.3)}$$

where

$$q(\sigma_j^2) = \mathcal{IG}(\sigma_j^2 \mid \nu_j, \psi_j), \quad p(\sigma_j^2) = \mathcal{IG}(\sigma_j^2 \mid \nu_j, 1). \tag{13}$$

Full expansion of the KL divergence can be computed by the summation of the above two terms Eq. (10) and Eq. (12). The formulation can be written as:

$$\mathcal{D}_{KL}(q(\mu, \sigma^2) \parallel p(\mu, \sigma^2)) = \frac{1}{M} \sum_{j=1}^{M} [\nu_j \frac{\lambda_j(\sigma_{0,j}^2 + \mu_{0,j}^2) + 2}{2\psi_j} + \log \frac{\psi_j^{\frac{2\nu_j+1}{2}}}{(\lambda_i \sigma_{0,j}^2)^{\frac{1}{2}}} - \frac{2\nu_j + 1}{2} - \frac{1}{2} \frac{\Gamma'(\nu_j)}{\Gamma(\nu_j)}], \tag{14}$$

Lemma B.1. *KL divergence between two Gaussian distributions.*

$$\mathcal{D}_{KL}(q(x)\parallel p(x)) = \frac{\sigma_q^2 + (\mu_q - \mu_p)^2}{2\sigma_p^2} + \frac{1}{2} \log \frac{\sigma_p^2}{\sigma_q^2} - \frac{1}{2},$$

where

$$q(x) = \mathcal{N}(x \mid \mu_q, \sigma_q^2), \quad p(x) = \mathcal{N}(x \mid \mu_p, \sigma_p^2).$$

Lemma B.2. *The expected Inverse Gamma distribution*

$$E_{x \sim q(x)} \left[\frac{1}{x} \right] = \frac{\nu}{\psi}, \quad E_{x \sim q(x)} [\log x] = \log \psi - \frac{\Gamma'(\nu)}{\Gamma(\nu)},$$

where

$$q(x) = \mathcal{IG}(x \mid \nu, \psi) = \frac{\psi^\nu}{\Gamma(\nu)} x^{-(\nu+1)} \exp\left(-\psi x^{-1}\right)$$

Lemma B.3. *KL divergence between two Inverse Gamma distributions*

$$\mathcal{D}_{KL}(q(x)||p(x)) = \int q(x) \log \frac{\frac{\psi_q^\nu}{\Gamma(\nu)} x^{-(\nu+1)} \exp\left(-\psi_q x^{-1}\right)}{\frac{\psi_p^\nu}{\Gamma(\nu)} x^{-(\nu+1)} \exp\left(-\psi_p x^{-1}\right)} dx$$

$$= \int q(x) \log \left[\frac{\psi_q^\nu}{\psi_p^\nu} \exp\left(-(\psi_q - \psi_p) x^{-1}\right)\right] dx$$

$$= \int q(x) \left[\nu \log \frac{\psi_q}{\psi_p} - (\psi_q - \psi_p) x^{-1}\right] dx$$

$$= \nu \log \frac{\psi_q}{\psi_p} - (\psi_q - \psi_p) \int \frac{q(x)}{x} dx$$

$$= \nu \log \frac{\psi_q}{\psi_p} - \frac{\nu(\psi_q - \psi_p)}{\psi_q}, \quad \textit{(by Lemma B.2)}$$

where

$$q(x) = \mathcal{IG}(x \mid \nu, \psi_q), \quad p(x) = \mathcal{IG}(x \mid \nu, \psi_p).$$

Lemma B.4. *KL divergence with independent random variables*

$$\mathcal{D}_{KL}(q(x)||p(x)) = \iint \cdots \int q(x) \log \frac{q(x)}{p(x)} dx_1 dx_2 \cdots dx_n$$

$$= \iint \cdots \int q(x) \log \left[\prod_{j=1}^{M} \frac{q(x_j)}{p(x_j)}\right] dx_1 dx_2 \cdots dx_n$$

$$= \sum_{j=1}^{M} \iint \cdots \int q(x) \log \frac{q(x_j)}{p(x_j)} dx_1 dx_2 \cdots dx_n$$

$$= \sum_{j=1}^{M} \underbrace{\int q(x_j) \log \frac{q(x_j)}{p(x_j)} dx_j}_{\mathcal{D}_{KL}(q(x_j)||p(x_j))} \times \underbrace{\prod_{\substack{i=1 \\ i \neq j}}^{M} \int q(x_i) dx_i}_{1}$$

$$= \sum_{j=1}^{M} \mathcal{D}_{KL}(q(x_j)||p(x_j)),$$

where

$$x = (x_1, x_2, \cdots, x_n), \quad q(x) = \prod_{j=1}^{M} q(x_i), \quad p(x) = \prod_{j=1}^{M} p(x_i).$$

C FUNCTION ANALYSIS

(a) The function H (b) The derivative of the function H

Figure 3: Function analysis for (a) the function H, and (b) the derivative of the function H,

where

$$H(\nu_j) = \frac{\nu_j}{2}\frac{d}{d\nu_j}G(\nu_j) - \frac{1}{2}G(\nu_j) + \frac{1}{2}\log\nu_j - \frac{1}{2}$$

$$= \frac{1}{2}\sum_{k=0}^{\infty}\frac{\nu_j}{(\nu_j+k)^2} - \frac{\Gamma'(\nu_j)}{\Gamma(\nu_j)} + \frac{1}{2}\log\nu_j - \frac{1}{2} > 0 \tag{15}$$

and

$$\lim_{\nu_i\to\infty} H(\nu_i) = 0^+. \tag{16}$$

where

$$H'(\nu_j) = \frac{\nu_j}{2}\frac{d^2}{d\nu_j^2}G(\nu_i) + \frac{1}{2\nu_j}$$

$$= -\sum_{k=0}^{\infty}\frac{\nu_j}{(\nu_j+k)^3} + \frac{1}{2\nu_j} < 0 \tag{17}$$

and

$$\lim_{\nu_j\to\infty} H'(\nu_j) = 0^-. \tag{18}$$

D PROOF OF k VALUE

The Normal distribution $q(\mu) = \mathcal{N}(\mu_0, \sigma_0^2)$ is learned to follow the mean prior $p(\mu \mid \sigma^2) = \mathcal{N}(0, (\lambda^*)^{-1}\sigma^2)$, with the optimal value $\lambda^* = \frac{\psi}{\nu(\mu_0^2 + \sigma_0^2)}$. The mean prior's variance equals to $\frac{\nu\sigma^2}{\psi}(\mu_0^2 + \sigma_0^2)$. Here, $\epsilon_{\sigma^2} = \frac{\sigma^2}{\psi}$ is sampled from $\mathcal{IG}(\nu, 1)$, as depicted in the Fig. 1(b). Thus, the variance is written as: $\nu\epsilon_{\sigma^2}(\mu_0^2 + \sigma_0^2)$. Now, we can statistically estimate $\nu\epsilon_{\sigma^2}$ by the expected over $\epsilon_{\sigma^2} \sim \mathcal{IG}(\nu, 1)$. Then, it satisfies $\mathbb{E}_{\epsilon_{\sigma^2}}[\nu\epsilon_{\sigma^2}] = \frac{\nu}{\nu-1} > 1$. Hence, the mean prior $p(\mu \mid \sigma^2)$ can be designed to $\mathcal{N}(0, k(\mu_0^2 + \sigma_0^2))$, where $k > 1$.

E   ROBUSTNESS OF ENHANCED BAYESIAN REGULARIZER AGAINST EOT ATTACK

Let $f(w) = \nabla J(x, w)$ where w denotes the weight parameters $w = \mu + \sigma\epsilon$, and J denotes the cross-entropy loss. Note that for mathematical convenience, the denoted μ and σ correspond to the mean and the variance in both adversarial training with BNN and Ours. Expectation over Transformation (EOT) attack is well-known adaptive attack targeting randomized neural networks. The EOT attack easily bypasses the stochasticity of randomized classifiers by taking the expectation over the multiple weight and computing the actual gradient. If we take expectation of $f(w)$ over weight parameter, then it satisfies

$$\mathbb{E}_w[f(w)] = \mathbb{E}_\epsilon[f(\mu + \sigma\epsilon)] \tag{19}$$

According to Taylor series, Eq. (19) can be written as follows:

$$\mathbb{E}_\epsilon[f(\mu + \sigma\epsilon)] = \mathbb{E}_\epsilon[f(\mu) + \sigma\epsilon f'(\mu) + \frac{(\sigma\epsilon)^2}{2!}f''(\mu) + \cdots]$$

$$= \underbrace{\mathbb{E}_\epsilon[f(\mu)]}_{\text{actual gradient}} + \mathbb{E}_\epsilon[\sigma\epsilon f'(\mu)] + \mathbb{E}_\epsilon[\frac{(\sigma\epsilon)^2}{2!}f''(\mu)] + \cdots \tag{20}$$

For adversarial training (σ is not used), Eq. (20) can be written as:

$$\mathbb{E}_\epsilon[f(\mu)] = f(\mu) \tag{21}$$

For adversarial training with BNN, the variance σ^2 of the posterior becomes infinitesimal value, so Taylor series ends up with first-order approximation. Eq. (20) can be written as:

$$\mathbb{E}_\epsilon[f(\mu + \sigma\epsilon)] = \mathbb{E}_\epsilon[f(\mu)] + \mathbb{E}_\epsilon[\sigma\epsilon f'(\mu)]$$

$$= f(\mu) \tag{22}$$

For our enhanced Bayesian regularizer, the remaining terms of Taylor series still survive at even degree. Eq. (20) can be written as:

$$\mathbb{E}_\epsilon[f(\mu + \sigma\epsilon)] = \mathbb{E}_\epsilon[f(\mu) + \sigma\epsilon f'(\mu) + \frac{(\sigma\epsilon)^2}{2!}f''(\mu) + \cdots]$$

$$= \underbrace{f(\mu)}_{\text{actual gradient}} + \underbrace{\frac{\sigma^2}{2}f''(\mu) + \cdots}_{\text{stochastic tolerant terms}} \tag{23}$$

Thus, the remaining terms of Taylor series make a difference from the actual gradient, and retain stochastic tolerance against EOT adversarial attacks.

F TRAINING THE BNN WITHOUT ADVERSARIAL EXAMPLES

Table 2: Comparison of the statistical summaries of weight parameters without any defense method. We include mean, variance, and KL divergence. The statistical results of our enhanced Bayesian regularizer is marked in **bold**. Note that our proposed model has non-zero mean, higher variance and lower KLD.

	CIFAR-10			STL-10			CIFAR-100			Tiny-ImageNet		
	Mean	Variance	KLD	Mean	Variance	KLD	Mean	Variance	KLD	Mean	Variance	KLD
Ours	0.003	**0.129**	**1.0**	0.002	**0.092**	**0.971**	0.007	**0.109**	**1.4**	0.028	**0.211**	**1.8**
BNN	0	0.071	7.7	0	0.051	2.454	0	0.068	15.4	0	0.064	26.7

Figure 4: Accuracy without adversarial training under L_∞-normal PGD attack(first row) and EOT-PGD attack(second row) on different datasets: CIFAR-10, STL-10, CIFAR-100, and Tiny-ImageNet.