A Mutual Information Duality Algorithm for Multi-Agent Specialization

Abstract

The social behavior change in a population has long been studied as an essential component of multi-agent learning. The learning of behavioral change not only involves reinforcement learning (RL), but also be measured against the general population with mutual information (MI). The combination of RL and MI led us to derive MI optimizations from policy gradient. With MI as multi-agent's optimization objective, we discover that the dual properties of MI can result in distinctly different population behaviors. From MI maximization that maximizes the stability of a population to MI minimization that enables specialization among the agents, the dual of MI creates a significant change in a population's behavioral properties. In this paper, we propose a minimax formulation of MI (M&M) that enables agents specialization with stable regularization. Empirically we evaluated M&M against the prior SOTA MARL framework, and analyze the social behavior change in performance, diversity, and the stability of their social graphs.

1 Introduction

From the success of multi-agent game plays [(OpenAI et al., 2019), (Vinyals et al., 2019)], heterogeneous multi-agent learning is actively studied in areas such as AI game design (Contributors, 2022), embedded IoTs (Toyama et al., 2021), and the research for future Human-AI interaction. With the unique physique and specialized agent attributes, the ability to learn agent specialization are essential. The goal of the research area is to find a general learning algorithm for a diverse agent population, and to understand the social behavior changes during the learning interactions.

To study the learning and behavioral change, multi-agent learning has formed two branches of studies. In the simplest form of multi-agent RL, individualized learning is performed to learn separate behavioral policies for each agent. These prior works include Independent Q-Learning (IQL) (Tan, 1993), Policy Search Response Oracle (PSRO) (Lanctot et al., 2017), and AlphaStar (Vinyals et al., 2019). However, the empirical success of these prior approaches have excluded knowledge sharing. Since the training is done independently, one agent's learned experiences do not transfer to another. The individualized behaviors results in high redundancy of re-exploration and low socialized behaviors among the agents. On the contrary, joint policy optimization is proposed as a solution to these problems. With a population jointly optimize for a single objective, knowledge sharing enables the learned policy skills to transfer across agents. Notable examples include OpenAIFive (OpenAI et al., 2019), HAPPO (Kuba et al., 2021) and NeuPL (Liu et al., 2022) that optimize the multi-agent behaviors under the expected population accumulated rewards.

The joint policy optimization encourages knowledge sharing and social behaviors. We discover that the policy gradient formulation of joint policy optimization can be connected to MI maximization among the agents. The result of agents' social behavior change is a maximization of commonality, stability of social behaviors. However, the stability of MI maximization does not allow agents to form specialization. To circumvent the impact, we derive a novel minimax MI (M&M) algorithm to enable agent specialization via the duality properties of MI. We include a theoretical and experimental analysis on the social behavioral change of agent population and demonstrate that M&M not only recovers the social diversity in a population, the specialized agents - Specialists, also show significant gain in competitive play.

2 BACKGROUND AND RELATED WORK

Multi-agent learning is a broad field of study that not only covers the necessary intelligence of individual agent's reward maximization, but also the social behavior change when agents interact with other agents. Prior researches in population learning have studied the performance of the agent population in competitive and cooperative environments.

2.1 COMPETITIVE BEHAVIORS LEARNING

In a competitive environment, the goal of the multi-agent research is to utilize competition to optimize the performance of an agent population. One approach to perform the learning iteration is individualized learning. Each agent improves its policy through learning a best response (BR) against the prior iterations of agents. The iterated elimination of dominated strategies optimizes a population of policies under Game Theory. Prior studies such as (Jaderberg et al., 2018), PSRO, PS-TRPO (Gupta et al., 2017), (Vinitsky et al., 2020) and Alphastar utilizes different variants of self-play (Heinrich et al., 2015) to learn competitive Nash Equilibrium behaviors for a population. The different variants addresses the stability (TRPO constraint), robustness (adversarial population) and diversity (leagues of policies pretrained on human data) of individualized learning.

In contrast, a joint policy optimization framework is proposed by (Foerster et al., 2016), (Lowe et al., 2017) to optimize the population with Centralized Learning Decentralized Execution (CLDE). The joint optimization has the advantage of common skill transfer across policies. The commonality among the agents can be learned once and the behavior change can be utilized by different agents. This form of joint optimization optimizes the population as an one-body problem with Mean Field Theory (Yang et al., 2018). Under Mean Field Theory, the variations of individual agents can be averaged and the modeling of agents behaviors is reduced from many-body problem to an one-body problem. Prior works include MADDPG, HAPPO (Kuba et al., 2021), OpenAIFive (OpenAI et al., 2019) and NeuPL (Liu et al., 2022), where OpenAIFive and NeuPL have developed efficient graph solvers based on (Shoham & Leyton-Brown, 2008) to further optimize the social graphs of the population. The graph solver F matches the agents (x,y) with weighted edges $\Sigma^{(x,y)}$. The matching graph algorithm is commonly defined for adversarial exploitation or agents of the most similar performance strengths.

2.2 COOPERATIVE BEHAVIORS LEARNING

To develop social behaviors of cooperation, prior studies have proposed auxiliary rewards and regularization of mutual information as part of the objective function. This includes OpenAIFive's team spirit reward, (Chenghao et al., 2021)'s Q-value, (Cuervo & Alzate, 2020)'s PPO, and (Mahajan et al., 2019)'s latent variable regularization of MI maximization. While the above studies suggest that learning of cooperative social behaviors may require auxiliary modifications, (Dobbe et al., 2017) shows an interesting analysis on the distortion rate of the joint policy optimization versus the individualized learning with MI. The study shows that even without auxiliary modification, there is a significant stability difference in distortion rate between the joint optimization and individualized learning. This issue has shown to negatively impact cooperative learning.

2.3 A NEW PERSPECTIVE ON EXISTING WORK: FROM POLICY GRADIENT TO MUTUAL INFORMATION

The finding in our paper aligns with (Dobbe et al., 2017). We discover that when policy gradient (Sutton et al., 1999) is applied to multi-agent joint optimization, the underlying gradient - without auxiliary loss, is transformed to MI maximization. We derive the learning objective of multi-agent learning as the following.

To model a simple two-players competitive game (x, y), the joint policy gradient of one game is defined by:

$$Maximize\ J(\theta) = \mathop{\mathbb{E}}_{s} \mathop{\mathbb{E}}_{a^x} \mathop{\mathbb{E}}_{a^y} [Adv(s, a^x, a^y) * (\Pi_\theta^x(a^x|s)\Pi_\theta^y(a^y|s))] \tag{1}$$

For the gradient, we apply the product rule of the derivative and the log trick (Williams, 1992). Using the product rule, the derivative addresses the non-stationary learning of two or more agents. The expanded form of the joint gradient is:

$$\nabla_\theta J(\theta) = \mathop{\mathbb{E}}_s \mathop{\mathbb{E}}_{a^x} \mathop{\mathbb{E}}_{a^y} [\, Adv(s, a^x, a^y)$$
$$* [\, \Pi_\theta^y(a^y|s)\, \Pi_\theta^x(a^x|s)\, \nabla_\theta log(\Pi_\theta^x(a^x|s))\, +\, \Pi_\theta^x(a^x|s)\, \Pi_\theta^y(a^y|s)\, \nabla_\theta log(\Pi_\theta^y(a^y|s))\,]\,] \quad (2)$$

Here the Advantage function can be expanded to $Q(s, a^x, a^y)$ and $V(s)$. Since $\Pi_\theta^x(a^x|s)$ and $\Pi_\theta^y(a^y|s)$ are specific for each side of x and y, we assume they are independent. By applying probability of independence and logarithmic product rule (A.6), the joint gradient becomes:

$$\nabla_\theta J(\theta) = \mathop{\mathbb{E}}_s \mathop{\mathbb{E}}_{a^x} \mathop{\mathbb{E}}_{a^y} [Q(s, a^x, a^y)[[\, \mathbf{\Pi}_\theta^{(\mathbf{x,y})}(\mathbf{a^x, a^y|s})\,]\, *\, [\nabla_\theta \mathbf{log}(\mathbf{\Pi}_\theta^{(\mathbf{x,y})}(\mathbf{a^x, a^y|s}))\,]\,]$$
$$-[V(s)[\, \mathbf{\Pi}_\theta^{(\mathbf{x,y})}(\mathbf{a^x, a^y|s})\,]\, *\, [\, \nabla_\theta \mathbf{log}(\mathbf{\Pi}_\theta^{\mathbf{x}}(\mathbf{a^x|s}))\, +\, \nabla_\theta \mathbf{log}(\mathbf{\Pi}_\theta^{\mathbf{y}}(\mathbf{a^y|s}))]]] \quad (3)$$

With T steps of optimization, the integration of gradients results to a long-term behavioral change of mutual information maximization:

$$I(X;Y) = \mathop{\mathbb{E}}_x \mathop{\mathbb{E}}_y [[[\, \mathbf{P_{(X,Y)}}(\mathbf{x,y})\,]\, *\, [\, \mathbf{log}(\mathbf{P_{(X,Y)}}(\mathbf{x,y}))\,]]$$
$$-[\, \mathbf{P_{(X,Y)}}(\mathbf{x,y})\,]\, *\, [\, \mathbf{log}(\mathbf{P_X}(\mathbf{x})) + \mathbf{log}(\mathbf{P_Y}(\mathbf{y}))\,]] \quad (4)$$

$$I(X;Y) = \mathop{\mathbb{E}}_x \mathop{\mathbb{E}}_y [-\mathbb{H}(X,Y) + \mathbb{H}(X) + \mathbb{H}(Y)] \quad (5)$$

The formulation can be extended to any two-player exchange of (X,Y) of N distinct agents {i,ii,..N}. MI is expanded as Interaction Information. With the two-player constraint, the interaction probabilities of more than two players $P(x, y, z...)$ is set to zeros. The expected gradient can be simplified to the average of all combinations of MI:

$$\frac{1}{N}\sum_{X=i}^N \frac{1}{N}\sum_{Y=i}^N I(X;Y) = \frac{1}{N}\sum_{X=i}^N \frac{1}{N}\sum_{Y=i}^N \mathop{\mathbb{E}}_x \mathop{\mathbb{E}}_y [\mathbb{H}(X) + \mathbb{H}(Y)] - [\mathbb{H}(X,Y)] \quad (6)$$

The key finding from Eq(3) to Eq(5) is that through *gradient* update, the vanilla joint policy optimization implicitly optimizes the population for mutual information. The maximization of $J(\theta)$ results to MI maximization in policy updates.

3 M&M: MINIMAX MUTUAL INFORMATION SPECIALIZATION

Under joint policy optimization, MI maximization increases the commonality among the agents' strategies. This constrains the policy search space to find skills that are transferable across all policies. As a result, the population learning is stable, but subject to a strong conformity constraint of $-[\mathbb{H}(X,Y)]$. In a heterogeneous population, the direct impact of MI maximization is a fast and stable behavioral convergence, but at the cost of behavioral diversity, performance and population balance.

To address the drawbacks of MI maximization while maintaining the benefit of learning stability, we introduce M&M as a minimax formulation of MI. The goal of the minimax formulation is to rely on the fast convergence of MI maximization to establish a stable population anchor - *Generalists*. Utilizing the conditional MI formulation, the disjoint policies can condition on the stable behaviors of the Generalists to define their specializations - *Specialists*.

3.1 PROBLEM FORMULATION

We consider a non-Markov two-player Game (X,Y) with a heterogeneous population of size N {i, ii...N }. The game is defined by (O, S, A, R) where O is the observation space, $S : O \times O$ is

the joint observation function of the two players. The discounted return for player x is defined as $R_t = \sum_{\tau=t}^{\infty} \gamma^\tau r_\tau^x$ where γ is the discount factor $\gamma \in [0 : 1]$. Additionally, we define F as the graph solver that finds the weighted edges, Σ, as the adversarial interactions from other agents. The exploitability is calculated as a function from each agent's utility, U, to other agents. The learned strategy for each agent will be a mixed strategy σ.

3.2 Conditional Mutual Information Minimization

We define *Generalists* as the $\epsilon-$ Nash joint policy optimization $\{\Pi_{\theta^*}^g\}_{g=i}^N$ and we initialize the Specialists as a set of disjoint policies $\{\pi_{\psi_0^k}\}_{k=1}^N \leftarrow \{\Pi_{\theta^*}^g\}_{g=i}^N$.

To minimize the conditional MI, we derive the disjoint policies gradients as a simple two-player game (X,Y) with a heterogeneous population of size N. The optimization of a Specialist is defined as a single side optimization, where Specialist of player X will learn to specialize against the fixed Generalists $\{\Pi_{\theta^*}^g\}_{g=i}^N$ of player Y. Since the parameters of $\{\Pi_{\theta^*}^g\}_{g=i}^N$ is fixed, the Generalists can be defined as part of the environment with its effect as a^g. With a heterogeneous population of $\{i, ii,...N\}$, the conditioned policy gradient for agent i is then:

$$Maximize\ J(\psi^i) = \frac{1}{N} \sum_{g=i}^N \mathop{\mathbb{E}}_{(s,a^g)} \Pi_{\theta^*}^g \mathop{\mathbb{E}}_{a^i} [[\ Q(s,a^i,a^g) * \pi_{\psi^i}(a^i, a^g|s)\ ]$$
$$-[\ V(s|\Pi_{\theta^*}^g) * \pi_{\psi^i}(a^i,a^g|s)\ ]] \tag{7}$$

With $Q(s,a^i,a^g)$ and $\pi_{\psi^i}(a^i,a^g|s)$ take a^g as an input, $\Pi_{\theta^*}^g$ is marginalized for $Q(s,a^i,a^g)$. Let $V(s|\Pi_{\theta^*}^g)$ be the conditional value function of the Generalists, taking the derivative will expand the formulation to:

$$\nabla_{\psi^i}\ J(\psi^i) = \frac{1}{N} \sum_{g=i}^N \mathop{\mathbb{E}}_{a^i} \mathop{\mathbb{E}}_{(s,a^g)} [Q(s,a^i,a^g) * \pi_{\psi^i}(a^i,a^g|s)\ \nabla_{\psi^i} log(\pi_{\psi^i}(a^i,a^g|s))$$
$$-V(s|\Pi_{\theta^*}^g) * \pi_{\psi^i}(a^i,a^g|s) \nabla_{\psi^i} log(\pi_{\psi^i}(a^i,a^g|s))] \tag{8}$$

$$I(X;Y) \equiv \mathbb{H}(X) - \mathbb{H}(X|Y) \tag{9}$$

With T steps of optimization, the integrated effect of maximization of $J(\psi^i)$ produces a minimization of the conditional I(X,Y) w.r.t. the Generalists. For any finite number of disjoint policies { i, ii,...N } the gradients are defined as Interaction Information with inductive conditional MI. Under the two-player constraint, the formulation can be simplified to the sum of the conditional MI:

$$-\frac{1}{N} \sum_{k=i}^N \frac{1}{N} \sum_{g=i}^N I(X_k;Y_g) \equiv \frac{1}{N} \sum_{k=i}^N \frac{1}{N} \sum_{g=i}^N -[\mathbb{H}(X_k) + \mathbb{H}(X_k|Y_g)] \tag{10}$$

3.3 Specialists PPO Constraint

With MM specialization, the Specialists directly minimizes commonality and maximizes entropy $\mathbb{H}(X_{agent})$ weighted by $Q(s,a^i,a^g)$. To ensure the Specialists specialize under stable constraint, we further utilize PPO clipping (Schulman et al., 2017) as a trust region.

$$\mathop{\mathbb{E}}_{a^g} \Pi_{\theta^*}^g [min(D_{KL}((\pi_{\psi_{old}^k} \Pi_{\theta^*}^g)\ ||\ (\pi_{\psi^k}\ \Pi_{\theta^*}^g)), clip(D_{KL}((\pi_{\psi_{old}^k} \Pi_{\theta^*}^g)\ ||\ (\pi_{\psi^k}\ \Pi_{\theta^*}^g)), 1 \pm \delta))] \tag{11}$$

We add each converged generation of specialized agents $\{\pi_{\psi_{\tau^*}^k}\}_{k=1}^N$ to the population anchor Π^N by $\Pi^N = \Pi^N\ U\ \{\pi_{\psi_{\tau^*}^k}\}_{k=1}^N$. This gradually *expand* the MI maximized region to a larger set and allows the next generation of agents to gradually adjust the D_{kl} constraint throughout training.

Algorithm 1 M&M Multi-Agent Specialization Pseudogecode

Input:

    Population = {i,ii,...N}   // Heterogeneous population of N distinct agents

    $\{\pi_{\psi_0^k}\}_{k=i}^N$,   // N disjoint policies

    $\Pi_{\theta*}^N$,   // Converged Generalists

    $\{\Sigma^k := (\pi_{\psi^k}, \{\Pi_{\theta*}^g\}_{g=i}^N)\}_{k=i}^N$,   // Agent k's social graph

    $F : \mathbb{R}^{1\times N} \to \mathbb{R}^{1\times N}$.   // Graph solver - NeuPL (Chen et al. 2022)

Parameter: $\Pi_{\theta*}^N, \{\pi_{\psi_0^k}\}_{k=i}^N$.

Output: $\{\pi_{\psi_T^k}\}_{k=i}^N, \Pi^N, \{\Sigma^k\}_{k=i}^N$

Algorithm Starts:

  1: **for** $n \in Population$ **do**

  2:     $\pi_{\psi_0^n} \leftarrow \Pi_{\theta*}^n$ // initialize N disjoint policies

  3: **end for**

  4: **while** (true do) **do**

  5:    **for** $k \in Population$ **do**

  6:      $\Pi^{\Sigma^k} \leftarrow \{\Pi^g(a^g|s)\}_{g=i}^N$ // Specialist k's social graph with the Generalists

  7:      $Self\text{-}play(\pi_{\psi_\tau^k}, \sigma_k, \Pi^{\Sigma^k})$ // Learning specialization in Mixed strategy σ_k

  8:      $\pi_{\psi_\tau^k} = D_{kl}(gradient_{step}(\pi_{\psi_\tau^k}))$

  9:      $U^k \leftarrow Eval(\pi_{\psi_\tau^k}, \{\Pi^g\}_{g=i}^N)$ // Evaluate node i's edges to other policies

  10:     $\Sigma^k \leftarrow F(U^k)$ // Define k's social graph

  11:    **end for**

  12:   $\Pi^N = \Pi^N U \{\pi_{\psi_{\tau*}^k}\}_{k=i}^N$ // Relax the kl-divergence with specialized agents

  13: **end while**

  14: **return** $\{\pi_{\psi^k}\}_{k=i}^N, \Pi^N, \{\Sigma^k\}_{k=i}^N$

---

4 EXPERIMENTS

Empirically we evaluate the specialization of agents on the Mobile Fighting Game: Naruto Mobile. In the evaluations the performance and the specialization differences are compared between the Generalists (MI maximized) and the M&M Specialists. All Generalists are optimized via joint policy optimization of 16 unique agents of Naruto Mobile characters. And the Specialists are formed on top of the $\epsilon-$ Nash Generalists. The radial plots are measures in the population's mean-deviation. This measures the relative difference of each agent to the population mean over the max. (The unit of measurement is canceled, and shows the relative differences on unit circle.)

4.1 INTRO TO NARUTO MOBILE GAME MECHANICS

Game mechanics: Naruto Mobile is a real-time 2D mobile Fighting Game of 1 vs 1 gameplay. The game has a pool of over 300 unique characters, and each has different character attributes in attack speed, range and movement variations. Additionally, each character has skills of different cooldown, status effects and duration. The large population of characters and real time competitive interactions create a testbed environment for research on heterogeneous specializations, embedded agents and Game Theory of Nash Equilibria. Before the start of a match, players of both sides select their characters, and can choose to equip a scroll and a pet summon. The key to winning a match is to reduce the opponent's health point (HP) to zero, or having a higher HP at the end of a 60 second match timer.

4.2 AGENT SPECIALIZATION

In our experiments we record the converged Generalists' advantages and the Specialists' against their prior iteration of population policies. The radial charts are plotted to visualize the similarity and differences of agent populations. The recorded vectors are projected on the unit circles to visualize the vectors' magnitude and the vectors' direction components. With the center of the circle

representing zero advantage over the average population, the radial edges represent the maximal deviation gain against that radial opponent.

Figure 1: **Agent's Advantage And Specializations:** From MI maximization optimization, both Generalists Agent I. and Agent K. show low deviations of advantage relative to the general population. This shows MI maximization optimizes the marginalized advantage of the population. In contrast, the Specialists Agent I. and Agent K. have demonstrated strong deviation from the population norm. With MI minimization being the optimization objective, Specialists learn to gain an additional competitive edge by specializing agents' unique agent-attributes.

From before to after agents' specialization, Figure 1 shows Agent I. has an increased magnitude of agents' advantage vectors. This implies that under M&M specialization, the MI between Agent I. and the general population is minimized. Similarly, Agent K. is also able to minimize its MI to achieve its own specialization. While both agents are able to achieve specialization, the direction components are different for the two agents. Agent I. is specialized against prior iteration of itself and Agent K., and Agent K. is specialized against prior iteration of Agent I. and Agent O.. The unique directions of each agent's specialization shows that M&M specialization not only minimizes MI of the population, each agent is also optimized for its own agent-attributes.

Moreover, the Generalists and Specialists populations show different aggregated bounds. With the aggregate of Generalists as the dotted line region and the Specialists population as the solid line region, the radial plot shows that the Generalists dotted bound is restricted close to the center. With the center representing the average population, the closer the region to the center, the more generic the agent population behaves. In the extreme case of conformity behavior convergence, MI maximization can reduce the region and eliminate the diversity in the population. On the other hand, Specialists show individual differences relative to the population norm. The individual specialization creates a collective diversity for the population.

4.3 SOCIAL GRAPHS AND INTERACTION STABILITY

With NeuPL (Liu et al., 2022) and (Shoham & Leyton-Brown, 2008) graph solver, the different social graphs of the Generalists and Specialists are plotted on their corresponding radial charts. In a social graph, the labeled agent is the center node of the graph and is connected with edges $\Sigma(x, y)$ outward to other agent nodes. $\Sigma(x, y)$ are normalized with population mean-deviation. The MI Maximized Social Graph is shown on the left in blue, and M&M's Social Graph on the right in red. The social graphs display the relative frequency agents interact with each other and the deviation from the mean. The larger an edge value is, the more frequent the agent-nodes interact.

Figure 2: **Social Graphs of Generalists and Specialists:** In MI Maximization Social Graph, the uniformity of edge-connection strengths shows each agent approximately interacts with other agents s similar number of times. This result shows each agent receives approximately the same distribution of experiences. In contrast, the social graphs of the Specialists gradual shift away from the symmetry. This allows each agent to interact with more relevant agents, and acquire more individualized information distribution. The differences in social graphs directly influence the stability of population learning and agents' experiences distribution. The more disjoint the experience distributions are, the more polarized the population becomes. Hence the necessity of *conditional* MI minimization and PPO's KL constraint.

MI Maximized Social Graph shown in Figure 2 illustrates that agents are connected with approximately equal connection strength in each edge. This indicates a densely connected social graph. This approximately translate to uniform distribution of $\{P_{X,Y}(x,y)\}_{x,y=i}^{N}$ with high stability in $-\mathbb{H}(X,Y)$. In contrast, M&M's Social Graph shows few strongly connected edges, such as Agent T. to Agent O., and sparse connections with other agents. With sparsity in the social graphs, each agent receives a different shaded region of experiences.

4.4 FROM MONOTONE BEHAVIOR TO DIVERSE INTERACTIONS:

To analyze the agents' behavior, we introduced several metrics to track the *timing* of agents' skills. ForcingMoves are metrics that measure agent's attack initiation prior to the opponent's attacks. CounterMoves measure skills used to interrupt the opponent *during* their skill casting. CloneSubstitute measures the frequency that an agent avoids or escapes from the opponent's attack. The metrics are displayed via mean-deviation frequency to account for the different skill cooldown among the agents. We collect a batch of 100 games for each agent-type to look at how similar or different the learned strategies are.

Figure 3: **Timing and Strategy:** Comparing the behavioral difference between the Generalists and the Specialists, there is a clear difference in how Generalists and Specialists respond. For the Generalists, the mean-deviation shows similar change despite playing four uniquely different agents. Except for the cooldown constraint, the actions of the four Generalists are largely the same response. This shows the drawback of MI maximization optimization. On the contrary, the Specialists are incentivized to formulate creative plays based on their individual agent-attributes. M&M creates a wide variety of strategy timings and competitive behaviors.

In Figure 3, the stacked Generalists and Specialists action timing reveals the similarity and differences in different population's strategy timing. Specialists learn to time their skills differently when embodied in different agents. Each agent adapts its behavior such that it's current strategy is optimal relative to the general population. In contrast, the Generalists population shows low variations in strategies. With the similar action timing, the Generalists have developed social behaviors that *conform* with other agents. While under MI maximization, the optimized generic behavior works across the different agents, but the diverse Specialists behaviors better demonstrate the essence of general intelligent for adaptive learning and creativeness.

4.5 PERFORMANCE COMPARISON:

The ϵ - Nash of the Generalists agents is iteratively optimized with 13 rounds of joint policy optimization via NeuPL's graph solver (Heatmap shown in Appendix A.4). Here we display the top 8 performing Generalists relative to the M&M optimized Specialists. The displayed competitive performance are the weighted win rates of the 8 agents versus the ϵ - Nash of the Generalists population.

Figure 4: **Performance Gain from Specialization:** With joint policy optimization, the top performing NeuPL agents converge to win rates of 58.2 ̃92.5% in deep blue. After M&M specialization, with the exception of Agent T., agents show substantial performance gain. Notably, among the improvements the highest performance gain from weaker agents, Agent A. and Agent K.. As a result, M&M produces a more balanced agent population with win rates of (77.6 ̃97.3%).

Aside from the performance gain from agent specialization, Figure 4 also shows an interesting observation that optimizing for population's commonality (MI maximization) does not translate to a more balanced population. With joint policy optimization, the population converges with high performance differences among the agents. The standard deviation of MI maximized optimization is 9.95, while it is reduced to 5.99 after M&M's specialization. With approximately 30 % reduction in population performance deviation, it shows that equity of a population (performance gap) can be improved when individual agents specialize.

4.6 COMPUTE AND LEARNING EFFICIENCY:

Here we show the learning efficiency of the different optimizations. The joint policy optimization of the Generalists are of 16 agents under MI maximization for 11 rounds. To compare the relative performance before convergence, we specialize the 9th round of Agent K. and Agent M. with M&M. The experiment measures the sample complexity needed for the two methods to reach a similar level of relative performance prior to specialization.

Model Name	Total Training Steps	9th Round Generalist	11th Round Generalist	Agent K. Specialist	Agent M. Specialist
9th Round Generalist	720,000	-	33.9%	21.1%	6.4%
11th Round Generalist	890,000	66.1%	-	44.6%	19.1%
Agent K. Specialist	850,000	78.9%	55.5%	-	36.2%
Agent M. Specialist	850,000	93.6%	80.9%	63.7%	-

Figure 5: **Training Efficiency and Competitiveness**: With 170k additional learning steps, the 11th round of Generalist can efficiently increase the average performance of the 16 agents by 16.1% (50% $\tilde{6}$6.1%). With M&M specialization, Agent K. and Agent M. require an additional 130k learning steps to reach with the same relative win rate against the general population (as the 9th round)

Figure 5 shows the joint policy optimization uses significantly less learning steps to optimize a large population of agents. This shows the learning efficiency of skill transfer and training on common experiences. In contrast, M&M specialization can learn unique strategies, but are not transferable. This requires a magnitude more samples to specialize. The learning efficiency shows it is more efficient to learn the common social behaviors under joint policy optimization. At convergence, M&M specialization can benefit the agent population with higher diversity, performance and equity. The learning process shows a similarity to our education system, where general learning is first instilled to the masses before individuals branch out for high skills specialization.

5 CONCLUSION

In our paper, we have derived two formulations of MI from multi-agent policy gradient. One brings a new perspective on the existing work of joint policy optimization, the other explores the potential of conditional MI minimization. The two learning representations under the dual properties of MI measure a population's long-term social behavioral change with commonality or individuality as the maximization objective. Under MI maximization, the social behavior of the population optimizes for social graph stability and behavioral conformity. In contrast, MI minimization optimizes for individual entropy and behavioral specialization. To balance the trade-off, M&M optimizes agent specialization while regularizes the learning instability with conditional MI minimization. By condition on the stability of the Generalists, Specialists learn to minimizes MI with stable interactions and KL constraint.

Broader Impact: The duality of MI exists ubiquitously. From individual learning of general knowledge to expert specialization, to the stability of the Gold standard to the current days of money creation. The fast contraction followed by a steady expansion of duality shows how the information gradients changes over time. By understanding the dual properties of MI, we are better equipped to navigate the drawbacks as well as the benefits of MI.

Future Work: In our research we have included Game Theory, Information Theory, Graph Theory and Deep Reinforcement Learning to demonstrate the roles of different fields. The individual fields are parts of the larger integral hierarchy of Artificial Intelligence. We believe future research with more cross field studies can give us a better understanding of the larger framing of learning and intelligence. Limitation: We believe potential improvement on social graph and Nash Equilibrium (Nash, 1951) are possible. Since there are large numbers of Nash Equilibria in large Games and each equilibrium may not be the same - Folks Theorem, specialization of agents may benefit with Nash Equilibria Refinement with graph solver to narrow the search to find more suitable Nash Equilibrium strategies.

REFERENCES

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dandelion Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. URL https://www.tensorflow.org/. Software available from tensorflow.org.

Pierpaolo Battigalli and Marciano Siniscalchi. Strong belief and forward induction reasoning. *Journal of Economic Theory*, 106(2):356–391, 2002.

Li Chenghao, Tonghan Wang, Chengjie Wu, Qianchuan Zhao, Jun Yang, and Chongjie Zhang. Celebrating diversity in shared multi-agent reinforcement learning. *Advances in Neural Information Processing Systems*, 34:3991–4002, 2021.

MuJoCo Menagerie Contributors. MuJoCo Menagerie: A collection of high-quality simulation models for MuJoCo, 2022. URL http://github.com/deepmind/mujoco_menagerie.

Santiago Cuervo and Marco Alzate. Emergent cooperation through mutual information maximization. *arXiv preprint arXiv:2006.11769*, 2020.

Roel Dobbe, David Fridovich-Keil, and Claire Tomlin. Fully decentralized policies for multi-agent systems: An information theoretic approach. *Advances in neural information processing systems*, 30, 2017.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Vlad Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *International Conference on Machine Learning*, pp. 1407–1416. PMLR, 2018.

Jakob Foerster, Ioannis Alexandros Assael, Nando De Freitas, and Shimon Whiteson. Learning to communicate with deep multi-agent reinforcement learning. *Advances in neural information processing systems*, 29, 2016.

Jayesh K Gupta, Maxim Egorov, and Mykel Kochenderfer. Cooperative multi-agent control using deep reinforcement learning. In *International conference on autonomous agents and multiagent systems*, pp. 66–83. Springer, 2017.

Johannes Heinrich, Marc Lanctot, and David Silver. Fictitious self-play in extensive-form games. In *International conference on machine learning*, pp. 805–813. PMLR, 2015.

M Jaderberg, WM Czarnecki, I Dunning, L Marris, G Lever, AG Castaneda, et al. Human-level performance in first-person multiplayer games with population-based deep reinforcement learning. arxiv. *arXiv preprint arXiv:1807.01281*, 2018.

Woojun Kim, Whiyoung Jung, Myungsik Cho, and Youngchul Sung. A maximum mutual information framework for multi-agent reinforcement learning. *arXiv preprint arXiv:2006.02732*, 2020.

Jakub Grudzien Kuba, Ruiqing Chen, Munning Wen, Ying Wen, Fanglei Sun, Jun Wang, and Yaodong Yang. Trust region policy optimisation in multi-agent reinforcement learning. *arXiv preprint arXiv:2109.11251*, 2021.

Marc Lanctot, Vinicius Zambaldi, Audrunas Gruslys, Angeliki Lazaridou, Karl Tuyls, Julien Pérolat, David Silver, and Thore Graepel. A unified game-theoretic approach to multiagent reinforcement learning. *Advances in neural information processing systems*, 30, 2017.

Siqi Liu, Luke Marris, Daniel Hennes, Josh Merel, Nicolas Heess, and Thore Graepel. Neupl: Neural population learning. *arXiv preprint arXiv:2202.07415*, 2022.

Ryan Lowe, Yi I Wu, Aviv Tamar, Jean Harb, OpenAI Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. *Advances in neural information processing systems*, 30, 2017.

Anuj Mahajan, Tabish Rashid, Mikayel Samvelyan, and Shimon Whiteson. Maven: Multi-agent variational exploration. *Advances in Neural Information Processing Systems*, 32, 2019.

mickep (https://math.stackexchange.com/users/97236/mickep). Prove log(xy) = log x + log y. Mathematics Stack Exchange. URL https://math.stackexchange.com/q/1115501. URL:https://math.stackexchange.com/q/1115501 (version: 2015-01-22).

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. *Advances in neural information processing systems*, 26, 2013.

John Nash. Non-cooperative games. *Annals of mathematics*, pp. 286–295, 1951.

OpenAI, Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław De-biak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, Rafal Józefowicz, Scott Gray, Catherine Olsson, Jakub Pachocki, Michael Petrov, Henrique Pondé de Oliveira Pinto, Jonathan Raiman, Tim Salimans, Jeremy Schlatter, Jonas Schneider, Szymon Sidor, Ilya Sutskever, Jie Tang, Filip Wolski, and Susan Zhang. Dota 2 with large scale deep reinforcement learning. 2019. URL https://arxiv.org/abs/1912.06680.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Alexander Sergeev and Mike Del Balso. Horovod: fast and easy distributed deep learning in TensorFlow. *arXiv preprint arXiv:1802.05799*, 2018.

Yoav Shoham and Kevin Leyton-Brown. *Multiagent systems: Algorithmic, game-theoretic, and logical foundations*. Cambridge University Press, 2008.

Richard S Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. *Advances in neural information processing systems*, 12, 1999.

Ming Tan. Multi-agent reinforcement learning: Independent vs. cooperative agents. In *Proceedings of the tenth international conference on machine learning*, pp. 330–337, 1993.

Daniel Toyama, Philippe Hamel, Anita Gergely, Gheorghe Comanici, Amelia Glaese, Zafarali Ahmed, Tyler Jackson, Shibl Mourad, and Doina Precup. AndroidEnv: A reinforcement learning platform for android. abs/2105.13231, 2021. URL http://arxiv.org/abs/2105.13231.

user65203. Prove log(xy) = log x + log y. Mathematics Stack Exchange. URL https://math.stackexchange.com/q/1115527. URL:https://math.stackexchange.com/q/1115527 (version: 2015-01-22).

Eugene Vinitsky, Yuqing Du, Kanaad Parvate, Kathy Jang, Pieter Abbeel, and Alexandre Bayen. Robust reinforcement learning using adversarial populations. *arXiv preprint arXiv:2008.01825*, 2020.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3):229–256, 1992.

Yaodong Yang, Rui Luo, Minne Li, Ming Zhou, Weinan Zhang, and Jun Wang. Mean field multi-agent reinforcement learning. In *International conference on machine learning*, pp. 5571–5580. PMLR, 2018.

A APPENDIX

A.1 MOBILE DEEP LEARNING ARCHITECTURE

Figure 6: **DRL architecture for mobile devices:** We build our neural network deployable to mobile devices. We first pass inputs to an embedding layer to reduce the dimension and also use Conv1D as opposed to the Dense layer to reduce compute load. Our input to output is separated into four modules.

1. Basic Module - for game env stat & characters specific information.
2. Buff Module - buff and debuff info during gameplay.
3. Element Module - characters equipment of weapon IDs, armor and etc.
4. Action Masking Module - gives the model the information on whether each action is currently available.

The separation of modules in Figure 6 allow us to have sparse connectivity in the model. The compute load is reduced compare to fully connected layers. This allowed us to inference our models locally on mobile devices.

MDP: The model receives from the Basic Module to identify the characters and equipped Summons and Scrolls. Additionally, characters position, movement and skills' buff & element information are received from Buff and Element Module. The above are the input states s_t to our model. Our model predicts an action output a_t to control the 2D movement of the agent, and the available attack and skills. The reward can be customized, but in our standard mechanics it is based on the (weighting) of agent's own HP(10), opponent's HP(10), the result of the battle(10), combo(5), and mana(5). With the transition of the action, new state s_{t+1} are given to the model for next iteration of MDP.

A.1.1 HYPERPARAMETERS AND HARDWARE USED

Hyperparameters

- PPO: 0.1

- n-step: 100 frames

- Reward discount factor: 0.995

- Learning rate: 1e-4

Hardware Used

- CPUS: 5,300

- GPUS: 0

- max Batch size: 5120

- Average Compute Time:
    - $\approx$ 180 Hrs (Generalist Training)

A.2 HETEROGENEOUS ACTION SPACE REPRESENTATION LEARNING:

With a large collection of distinct agents, the learning problem we face is their unique action sets and their relative similarity. Inspired by word embedding (Mikolov et al., 2013), we approach the problem with a structure of information bottleneck to learn the representation of the action sets as a dense representation of a vector. We define our information bottleneck via the structure of a neural net $\Pi(a|S)$, where S is the learn-able state space that holds the contextual information of the involved agents (x, y), action sets (a^x, a^y) and the joint observations. The goal of the model structure is to compress the large contextual information S to learn a joint policy Π that captures the actions' similarity in a specific interaction context.

A.3 INDEPENDENT CAUSALITY BETWEEN AGENTS' INTERACTIONS:

VM3-AC (Kim et al., 2020) has pointed out the possible causality dependency of multi-agent inter-actions. When player i decides its action a_t^x it may depend on player j's action a_t^y. The obvious problem of reasoning is the circular causality of the two players, a_t^x depends on a_t^y and a_t^y depends on a_t^x. To resolve this issue, (Kim et al., 2020) has introduced a random variable to disassociate the loop dependency via variational lower bound.

We define our agents' causality graph without the Markov Assumption on agent's action. By removing the Markov *Assumption*, we can use opponent's past actions $a_{0:t-1}^{-\pi}$ to predict opponent's current move $a_t^{-\pi}$. This breaks the loop and assume the casual graph of players' actions are independent at time t. This gives the agents temporal consistency of Forward Induction (Battigalli & Siniscalchi, 2002) of Game Theory for self-play. The reached Nash Equilibrium under Forward Induction is self-consistent that the rational opponents in the past will continue to choose rationally in the future.

A.4 GENERALISTS SELF-PLAY ALGORITHM CONSTRUCTION:

Our neural population learning for joint policy optimization is performed under the multi-agent so-cial graph of NeuPL(Liu et al., 2022). The nodes are the different generations of agents, and are connected by the weighted edges of $\{\Sigma^{(x,y)}\}^{NxN}$. NeuPL provides a population self-play frame-work that not only competes the current population $\Pi_{\theta_\tau}^N$ with combinations of distinct agents, but the weighted edge prioritization also extend to different *generations* of ϵ-Nash population $\Pi_{\theta_{0:\tau-1}}^N$. Each population is represented as a conditional joint policy that learns a set of best response (BR) strategy against all previous generations of multi-agents mixed-strategies.

Training Round	Behavior Tree	Round 1	Round 2	Round 3	Round 4	Round 5	Round 6	Round 7	Round 8	Round 9	Round 10	Round 11	Round 12	Round 13
Behavior Tree	-	0.94%	0.21%	0.14%	0.22%	0.29%	0.23%	0.12%	0.12%	0.08%	0.07%	0.09%	0.06%	0.09%
Round 1	99.06%	-	2.56%	1.93%	2.12%	2.06%	2.57%	2.68%	2.01%	2.23%	2.41%	2.46%	2.01%	1.94%
Round 2	99.79%	97.44%	-	4.48%	4.66%	5.75%	7.08%	6.24%	5.44%	5.64%	6.13%	6.71%	5.11%	4.91%
Round 3	99.86%	98.07%	95.52%	-	5.91%	6.90%	8.86%	9.72%	9.18%	10.58%	9.95%	10.78%	8.29%	8.89%
Round 4	99.78%	97.88%	95.34%	94.09%	-	14.29%	16.56%	21.59%	20.24%	20.82%	17.84%	18.25%	15.69%	15.69%
Round 5	99.71%	97.94%	94.25%	93.10%	85.71%	-	18.70%	21.92%	20.82%	21.43%	21.56%	21.77%	19.78%	19.33%
Round 6	99.77%	97.43%	92.92%	91.14%	83.44%	81.30%	-	17.50%	17.33%	18.12%	20.03%	20.05%	20.05%	19.88%
Round 7	99.88%	97.32%	93.76%	90.28%	78.41%	78.08%	82.50%	-	25.02%	25.69%	26.21%	26.16%	25.68%	24.82%
Round 8	99.88%	97.99%	94.56%	90.82%	79.76%	79.18%	82.67%	74.98%	-	33.16%	32.85%	31.30%	31.24%	31.81%
Round 9	99.92%	97.77%	94.36%	89.42%	79.18%	78.57%	81.88%	74.31%	66.84%	-	33.87%	33.96%	31.71%	33.28%
Round 10	99.91%	97.54%	93.29%	89.22%	81.75%	78.23%	79.95%	73.84%	68.70%	66.04%	-	41%	32.12%	33.89%
Round 11	99.93%	97.59%	93.87%	90.05%	82.16%	78.44%	79.97%	73.79%	67.15%	66.13%	59%	-	36.10%	36.71%
Round 12	99.94%	97.99%	94.89%	91.71%	84.31%	80.22%	79.95%	74.32%	68.76%	68.29%	67.88%	63.90%	-	42.39%
Round 13	99.91%	98.06%	95.09%	91.11%	84.31%	80.67%	80.12%	75.18%	68.19%	66.72%	66.11%	63.29%	57.61%	-

Figure 7: The heatmap shows the evaluation matches across the different Generalist iterations $\Pi_{\theta_t}^N$. The ablation evaluation shows joint policy optimization roughly diminished as the training ap-proaches the 11th 13th iteration. In particular, the 13th iteration only has a 57.6 % winrate against the 12th iteration of Generalist, which is close to the Nash equilibrium of 50 %.

In Figure 7, we evaluate all rounds of the Generalist policies against each other. The heatmap shows monotonic convergences of the Generalist population. At the 13th iteration, the Generalists population has converged as $\varepsilon-$ Nash Equilibrium where $\varepsilon \approx 7.6\%$. Further training may minimally increase the performance, but worsen the strategy diversity.

A.5 Correlation of Diversity and Performance

Since Agent T. is the only agent without performance gain after M&M specialization, we compare its Advantage vector change, performance chart with Agent H.'s.

Figure 8: **The performance metric of Agent H. and T. Specialization:** Agent H. shows an initial performance of 72.7 % performance relative to the other 15 Generalists population. With M&M's specialization, Agent H. shows a substantial increase in competitive performance of 87.2 %. On the other hand, Agent T. shows an initial performance of 87 % performance relative to the other 15 Generalists population. With M&M's specialization, Agent T.'s performance does not deviate from the initialization.

From Figure 8, shows the positive correlation of strategy diversity and character performance still holds. With Agent H., the radial plot shows a large deviation when the strategy is being converted from Generalist to Specialist. This correlates with the notable increase in agent performance on the left chart of Figure 8. On the other hand, Agent T. shows a more muted deviation within the Generalist bound. The lower strategy deviation is also reflected to Agent T.'s flat performance on the right chart of Figure 8. The lack of specialization for Agent T. may be due to the Generalists' converged strategy is already close to the optimal strategy for Agent T. This may imply that Agent T. has the most centered agent attributes in relation to the population. As the Generalist policy

converges towards the population mean, the converged strategy can become the optimal strategy for Agent T.

A.6   INTEGRATION:

Let $\Pi_\theta^x(a^x|s) = x$, $\Pi_\theta^y(a^y|s) = y$, and x, y > 0 then the change of variable approach (mickep , https://math.stackexchange.com/users/97236/mickep) (user65203):

$$\text{Let log(x)} = \int_{t=1}^x \frac{\partial t}{t} \tag{12}$$

$$log(xy) = \int_{t=1}^{xy} \frac{\partial t}{t} = \int_1^x \frac{\partial t}{t} + \int_{t=1}^{xy} \frac{\partial t}{t} - \int_{t=1}^x \frac{\partial t}{t} = \int_{t=1}^x \frac{\partial t}{t} + \int_{t=x}^{xy} \frac{\partial t}{t}$$

$$\text{Let } u = \frac{t}{x}, \text{such that} \frac{\partial t}{t} = \frac{\partial u}{u}$$

$$= \int_{t=1}^x \frac{\partial t}{t} + \int_{u=1}^y \frac{\partial u}{u} \tag{13}$$

This gives us $log(Pi_\theta^{(x}(a^x|s)Pi_\theta^{(y}(a^y|s)) = log(\Pi_\theta^{(x}(a^x|s)\Pi_\theta^{(y}(a^y|s))$. With the probability of independence assumption, $Q(a^x, a^y, s)$ function has the joint probability of $\nabla_\theta log(\Pi_\theta^{(x,y)}(a^x, a^y|s))$ in Eq(3).

A.7   SOFTWARE AND LICENSING

The models are implemented via Tensorflow, TensorflowLite (Abadi et al., 2015), IM-PALA(Espeholt et al., 2018), and Horovod(Sergeev & Balso, 2018). These softwares are all licensed under Apache License 2.0.