Structural Concept Learning via Graph Attention for Multi-Level Rearrangement Planning

Abstract: Robotic manipulation tasks, such as object rearrangement, play a crucial role in enabling robots to interact with complex and arbitrary environments. Existing work focuses primarily on single-level rearrangement planning and, even if multiple levels exist, dependency relations among substructures are geometrically simpler, like tower stacking. We propose Structural Concept Learning (SCL), a deep learning approach that leverages graph attention networks to perform multi-level object rearrangement planning for scenes with structural dependency hierarchies. It is trained on a self-generated simulation data set with intuitive structures, works for unseen scenes with an arbitrary number of objects and higher complexity of structures, infers independent substructures to allow for task parallelization over multiple manipulators, and generalizes to the real world. We compare our method with a range of classical and model-based baselines to show that our method leverages its scene understanding to achieve better performance, flexibility, and efficiency.

Keywords: Rearrangement Planning, Robot Manipulation, Graph Attention

Figure 1: Our approach performing progressive pick-and-place (we only show some place steps) actions based on its multi-level rearrangement plan to achieve (middle left) a target arrangement (top left). A complete figure is available in the supplementary.

1 Introduction

Robots operating in the real world will largely encounter a variety of simple objects in more complex arrangements and structures. To that end, recent years have seen rearrangement planning – which involves the reorganization of objects in a given environment to bring them into a goal state – emerging as a prominent area of research within robotics [1]. Simpler applications of this problem include tasks such as setting the table, rearranging furniture, loading a dishwasher, and many more. While manipulation for many real-world tasks performed by robots often reduces to pick-and-place, achieving more structured goals requires compositional interpretation of the target and the execution of long-horizon hierarchical plans. Autonomously solving more complex rearrangement problems, such as constructing a house or mechanical assembly, require robots to interpret internal dependence among the different parts of the whole structure and plan accordingly.

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

Despite the importance of these problems, most solutions addressing rearrangement planning largely consider target configurations with simpler dependencies such as blocking obstacles [2, 3, 4], stacking objects in towers or very simple structures [5, 6, 7, 8], or formulated as bin placement where supporting object is stationary [6, 9] all of which are strict subsets of a more general construction task. One of the major hurdles for this task is to decipher the order in which objects need to be placed so as to properly construct a given target structure since some objects depend on others in that they geometrically support them.

In this paper, we explore a toy scenario of the construction problem with known object primitives which are to be arranged to create some target structure. Our approach takes a multi-view RGB-D observation of the target structure and constructs a dependency graph using graph attention networks. This graph captures the geometrical dependency among the different objects, identifying independent substructures for parallelization. Our structure planner then takes this graph and serializes task executions based on the current observations of the scene. The low-level controller further takes the task sequences and executes the tasks via robot control. Our results show better performance compared to other classical and model-based planners as well as generalizability to unseen structures of varying complexity. The main contributions of our approach are as follows:

- A generated data set and generation procedure of target scenes containing intuitive structures with diverse complexity due to the possibility of a variable number of objects, inclusion of structures with varying levels, and the possibility of independent substructures.
- A scalable dependency graph generator that generalizes to structures with multiple levels and varying numbers of objects.
- A structured planner which uses the dependency graph to create a sequential plan for parallelized multi-level rearrangement planning, which is integrated into a complete pipeline from scene observations to control executions.

2   Related Work

Rearrangement. The most relevant area of research to our work would be that of rearrangement planning, which is a subset of task and motion planning (TAMP). TAMP [10] involves planning for a robotic agent to operate in an environment with several objects by taking actions to move and change the state of said objects. Rearrangement – specifically proposed as an important challenge for embodied AI – narrows this by defining itself as the act of bringing a given environment to a goal state [1]. Various strategies are utilized by systems aiming to address these problems. Some methods propose the combination of a high-level task planner with a low-level motion planner [11, 12, 13, 14]. Others tackle the problem by using sampling-based techniques in conjunction with search algorithms [15, 16, 17]. However, all of these focus on a yet narrower subset of rearrangement where objects are largely restricted to a 2D workspace and the interplay between objects is largely ignored or not present beyond dealing with clutter.

Deep Learning. More recently, advances have been made which utilize deep learning-based approaches toward solving these problems. These allow relaxing the assumptions on objects involved by proposing more flexible collision detection [18, 9], better generalization to the real world [19, 20, 21, 4, 6, 2], and unseen environments [7, 2] through vision-based perception.Other methods utilize semantic information but use it to allow for more general goals like similarity to an inferred target distribution [22, 23, 24] or guidance using language [25, 26]. Perhaps most similar to our method, some approaches make use of graph neural networks to model object relations in the scene [8, 5]. However, in all the methods mentioned above, the target scenes are either restricted to single-level or much simpler in terms of their construction, and the spatially weaker relations are allowed for less closely dependent substructures.

Construction and Assembly. Some works explore the task of assembly or construction [27, 28, 29], which allows objects to become fixed to one another that, unlike our case, does not require the creation of stable non-collapsing structures. Furthermore, in contrast to our approach, Blocks [27] and RoboAssembly [28] also assume perfect information of objects in simulation, making generalization to the real world very difficult and requiring much higher planning steps due to the

Figure 2: Model architecture overview. We segment out object point clouds (PointNet++ [30] based model) and peform pose alignment and establish object correspondences (TEASER++ [31] based) between X_I and X_T. A combination of object level embeddings (another PointNet++ [30] based model) and positional embeddings (positional encoder [32]) creates an initial graph G^T which our node encoder g_Φ takes to give higher-level node features. Our edge decoder h_Ψ uses these to create a dependency graph G^D from which the planner outputs a valid sequence for robot rearrangement.

use of reinforcement learning. Additionally, while the aforementioned approach to construction [29] also performs long-horizon planning like our approach, they restrict their target be one of 4 possible predefined structures, though their focus is on multi-robot planning.

3 Problem Definition

Let $\mathcal{X} = \{x_1, x_2, \ldots, x_n\} \subseteq \mathbb{R}^{n \times 3}$ be the set of all points that can be occupied by a scene, Ξ be the powerset of $\mathcal{X}$, and $\mathcal{O} = \{o_1, o_2, \ldots, o_m\}$ be the set of all object instances in any given scene where each $o \in \mathbb{R}^6 \times \mathcal{C}$ with $\mathcal{C}$ being the set of all classes an object instance can take. Next, we define a scene as two sets of points $X, Y \in \Xi$ such that $X \subseteq Y$ where X represents the observable scene, whereas Y represents the complete scene. Furthermore, we can define a subset selection operator $S \in \mathcal{S}$ as $S : \Xi \mapsto \Xi$ where $S(X) \subseteq X$ for all $X \in \Xi$. The goal is to construct a high-level planner $\pi_H : \Xi \times \Xi \mapsto \mathcal{P}$ that acts on partially observable sets $X_I, X_T \in \Xi$ of the initial and target scene to produce a hierarchical plan $P = \{(S_0, \delta_0), \ldots, (S_M, \delta_M)\} \in \mathcal{P}$ where $S_i \in \mathcal{S}$ is the subset selection operators, $\delta_i \in \Delta \subseteq \mathrm{SE}(3)$ is the valid spatial transformation, $M \in \mathcal{N}$ indicates the number of steps, and each i^{th} step $p_i = (S_i, \delta_i) \in P$ contains the selection and transformation action. Hence, our objective is to determine a plan P that selects subsets of point clouds, $\{S_0(X_I), \cdots, S_M(X_I)\}$, in the initial scene, X_I, and transform them using $\{\delta_0, \cdots, \delta_M\}$, in the minimum number of steps, M, to reach the an achieved state X_A whose object specific point clouds are subsets of those given by the complete target state Y_T. For application to robot rearrangement, we further define a low-level planner $\pi_L : \mathcal{Q} \mapsto \mathcal{A}$ where $\mathcal{Q}$ and $\mathcal{A}$ refer to the configuration and action spaces for the robot. Every step $p_i = \{S_i, \delta_i\} \in P$ from the planned output by π_H will have a sequence of achievable configurations q_{δ_i} associated with it that the low-level planner will take and further produce a sequence of actions $A \in \mathcal{A}$ to achieve the intermediate state defined by the application of p on the previous state. For convenience and brevity, we will denote some more notation for the remainder of this paper. Let any arbitrary set u, where $|u| = n$, be denoted as $u^{\{n\}}$. Also, for any arbitrary set U, we denote its association with a scene ι by specifying a subscript as U_ι and a subset of U associated some object or characteristic ω as a superscript $U^\omega \subseteq U$. And, for any graphs, subscripts denote different graph instances: G^T, G^Z, G^D.

4 Method

This section details our approach for multi-level rearrangement planning to generate a multi-step plan, the execution of which results in achieving the unseen structured target scene. Fig. 2 shows an overview of the model architecture and the basic flow of the approach. Additional model and implementation details are available in Section 2 of the supplementary.

Point Cloud and Feature Extraction. Partial point clouds are generated from the target scene F_T and the initial scene images F_I. First, we obtain the RGB-D images from multiple viewpoint cam-

eras surrounding the scene area and calculate their corresponding point clouds in the world frame from the camera's known world frame positions. We do preliminary filtering to remove outlier points. This is done for both the target scene and the initial scene to obtain X_T and X_I. A trained PointNet++[30] based segmentation network then takes the scene point cloud and returns the segmented identity values for each point. Next, we extract the object-specific point clouds to obtain X_T^o and X_I^o for each object o. This makes up the Segmentation Module. As part of the Initial Graph Generation, we use another PointNet++ based network to extract object-level latent features for each object point cloud and concatenate them to get $w_I^{\{N\}}$ and $w_T^{\{N\}}$ which will act as part of the node features for the scene graphs. Note that N is the number of objects in each scene.

Object Pose Alignment. Now is the task of object alignment and correspondence creation. Between the target and initial scenes, we have multiple objects of the same type so we want to select correspondences such that the orientation change for an object o_i is minimized from the initial to the target scene. To that end, for each object $X_T^{o_i}$ in the target scene, we use its predicted $y_T^{o_i}$ identity and sample its known mesh to obtain a default surface point cloud $X_d^{o_i}$. These complete, $X_d^{o_i}$, and the partial point clouds, $X_T^{o_i}$, from the target scene, are then used to predict a spatial transformation $\mathcal{T}_{T \leftarrow d}^{o_i}$, using TEASER++ [31], which aligns $X_d^{o_i}$ with $X_T^{o_i}$. This process is repeated for each object point cloud $X_I^{o_j}$ in the initial scene matching whose identity $y_I^{o_j}$ matches o_i's identity $y_T^{o_i}$ to get a set of transformations $\{\mathcal{T}_{d \leftarrow I}^{o_0}, \mathcal{T}_{d \leftarrow I}^{o_1}, \mathcal{T}_{d \leftarrow I}^{o_2} \dots\}$. These are then right multiply with $\mathcal{T}_{T \leftarrow d}^{o_i}$ to obtain $\{\mathcal{T}_{T \leftarrow I}^{o_0}, \mathcal{T}_{T \leftarrow I}^{o_1}, \mathcal{T}_{T \leftarrow I}^{o_2} \dots\}$. From these, we choose the one which minimizes the magnitude of rotation from the initial to target scene (to avoid reorienting with multiple pick-and-place actions). This gives us the canonical correspondence (and associated transformations $\mathcal{T}_{T \leftarrow I}^{o_i}, T_{T \leftarrow d}^{o_i}$) for o_i between the initial and target scene. This makes up the Pose Alignment Module. Finally, as part of the Initial Graph Generation, we obtain centroids for $X_d^{o_i} \cdot (\mathcal{T}_{T \leftarrow d}^{o_i})^T$ and $X_d^{o_i} \cdot (\mathcal{T}_{I \leftarrow d}^{o_i})^T$ which are put into a positional encoder [32] to obtain positional features for each object in both the initial and target scenes: $b_I^{\{N\}}, b_T^{\{N\}}$. Together, the object level features and positional features give us the node features $n_I^{\{N\}} = [w_I^{\{N\}} \,||\, b_I^{\{N\}}], n_T^{\{N\}} = [w_T^{\{N\}} \,||\, b_T^{\{N\}}]$ for the objects in the scenes for the initial graph, where $||$ denotes concatenation.

Graph Node Encoder. The graph node encoder, $g_\Phi : \mathcal{G} \mapsto \mathcal{Z}$ is based on a graph attention neural network [33, 34], known as GAT, which takes in an initially fully connected scene graph $G^T = (V, E) \in \mathcal{G}$ of the target scene with the aforementioned $n_T^{\{N\}}$ – which contain both object-level features and positional features for each object in the target scene – serving as the initial node features. These initial node features are updated using a modified convolution that occurs for any node i using its neighbor set $\mathcal{N}(i)$. The exact node feature update done by the convolutional layer is given by $n_i' = \alpha_{i,i}\Phi n_i + \sum_{j \in \mathcal{N}(i)} \alpha_{i,j}\Phi n_i$, where Φ is the learnable parameter for the update mechanism and the attention coefficients α, which quantifies the importance of neighboring nodes, is given by

$$\alpha_{i,j} = \frac{\exp(a^T \sigma(\Phi[n_i \,||\, n_j]))}{\sum_{k \in \mathcal{N}(i) \cup \mathcal{N}(j)} \exp(a^T \sigma(\Phi[n_i \,||\, n_k]))} \tag{1}$$

where ^{T} represents transposition, a is the learnable parameter for the attention mechanism, and σ is the element-wise non-linear activation function LeakyReLU (for derivation and more details, please refer to [33, 34]). The output from the graph encoder is a latent scene graph $G^Z \in \mathcal{Z}$ for the target scene containing high-level features for each of the objects. In our problem setting, a GAT-based model with multi-headed attentions being averaged outperformed a vanilla GCNs.

MLP Edge Decoder. The MLP-based edge decoder $h_\Psi : \mathcal{Z} \to \mathcal{D}$ maps the latent scene graph G^Z to the structural dependency graph G^D for the target scene containing inter-object specific dependency information. Specifically, h_Ψ can be queried with a pair of high-level features z_i, z_j representing objects o_i, o_j and will decode them into the structural relationship between them. This relationship of dependence is asymmetric, and the decoder is used to query every ordered pair of nodes in the graph to obtain the respective dependence probabilities $\rho^{\{N \times N\}}$ where $\rho_{i,j} = h([z_i||z_j]; \Psi)$. Given $\rho^{\{N \times N\}}$, we construct an inferred adjacency matrix for the structural dependency graph G^D of the

target scene with values $G_{i,j}^D = \rho_{i,j} > t^*$ where t^* is some threshold value. The directed edges for this graph are visualized in Figure 2 as green arrows.

Structured Plan Creation. Once we have a directed acyclic graph G^D representing the inferred structural relationship between each pair of objects different objects in the target scene, we perform a topological sorting to obtain a valid sequencing with which the objects can be introduced so as to construct the structure in the target scene. Next, we make use of the aforementioned object correspondences between the initial and target scene to pick the object from its current position (formulated as a point cloud selection of S) in the initial scene and place it in the target position given by the associated spatial transformation $\delta = \mathcal{T}$ obtained from pose alignment. All of this provides us with a plan $P = \{\{S_0, \delta_0, k_0\}, \ldots, \{S_N, \delta_N, k_N\}\}$ where N is the number of objects and, for plan step $p_i = \{S_i, \delta_i, k_i\} \in P$, and $k_i \leqslant N \in \mathbb{N}$ denotes the dependence hierarchy identifier in the target structure that the object represented by the selection S_i belongs to. Particularly, the plan is agnostic to any inversions involving any plan steps $p_i, p_j \in P$ such that their associated hierarchy identifiers match: $k_i = k_i$. That is, objects belonging to the same class of dependence hierarchy can be placed in any order relative to each other. This makes up the Structural Planner Module.

Planning Algorithm. Algorithm 1 defines our planning algorithm, which yields a multi-step plan for performing efficient multi-level rearrangement tasks. For given scenes S_I, S_T, we extract the observable information F_I, F_T and convert them into scene point clouds X_I, X_T. These are taken and segmented into a collection of object point clouds $X_I^{\{N\}}, X_T^{\{N\}}$ and their respective predictive identities $y_I^{\{N\}}, y_T^{\{N\}}$, where N is the number of objects in our scenes (Lines 1-2). Using these, we calculate the correspondences for objects in the initial and target scene to produce reordered versions of the object point cloud along with transformations $\mathcal{T}_{T \leftarrow I}^{\{N\}}$ for each object from the initial to target scene and transformations $\mathcal{T}_{T \leftarrow d}^{\{N\}}$ from objects' known default point cloud to their respective counterparts in the target scene (Line 3). Next, we use the target object point clouds $X_T^{\{N\}}$ with a PointNet++ [30] based model to extract object-level features $w_T^{\{N\}}$ and the default point cloud transformed to the target pose with a positional encoder [32] to get higher level embeddings $b_T^{\{N\}}$ for the target position (Lines 4-6). Together these make up and construct the initial graph G^T, which is provided to the graph encoder network g_Φ to get a graph with higher level node features $z^{\{N\}}$ for each object G^Z (Line 7). Using these, we do ordered pairwise queries to the edge decoder h_Ψ to populate the probabilities $\rho^{\{N \times N\}}$ of the i^{th} object depending on the j^{th} object which are used along with a threshold t^* to determine the canonical structural dependency graph G^D for the target scene (Lines 8-11). Given G^D, we now do a preliminary check of the inferred dependence by seeing whether the dependence graph is directed acyclic because if this is not the case, a circular dependency exists and we report a failure since the dependence graph G^D, which would indicate a prediction error as all target scenes are known to be reachable with one manipulator (Lines 12-13). Finally, we do a topological sorting of the dependence graph G^D and iterate over the result, using the predicted object transformations $\mathcal{T}_{T \leftarrow I}^{\{N\}}$ from the initial scene to the target, to create a rearrangement plan P (Lines 14-18). For each element $p_i = \{S_i, \delta_i = T_i, k_i\} \in P$, the execution will pick the object represented by the set of points $S_i(X_I)$ and execute low level actions to result in an effective transformation of $\delta_i = \mathcal{T}_i$ on said points in an order such that k_i increases monotonically.

Figure 3: Examples of generated structures in dataset

Data Generation and Training. To train our models, we generate synthetic data containing intuitive structures built from a set of 8 possible object primitives, which are captured from 3 fixed viewpoints. We restrict the set of initial orientations for each object which allow only those which provide a non-negligible surface area on the bottom surface to allow for stable placement (e.g., a cylinder is not allowed to be placed in a way where it may roll). For all but the final, only object orientations

Algorithm 1: SCL-Planning($\mathcal{X}$)

---

1 $X_I, X_T \leftarrow \text{PointCloudExtraction}(\mathcal{X})$ ⊳ initial and target scene point clouds

2 $X_I^{\{N\}}, X_T^{\{N\}}, y_I^{\{N\}}, y_T^{\{N\}} \leftarrow \text{Segmentation}(X_I, X_T)$ ⊳ object point clouds and their identities

3 $X_{I,T,d}^{\{N\}}, \mathcal{T}_{T\leftarrow I}^{\{N\}}, \mathcal{T}_{T\leftarrow d}^{\{N\}} \leftarrow \text{PoseAlignment}(X_I^{\{N\}}, X_T^{\{N\}}, y_I^{\{N\}}, y_T^{\{N\}})$ ⊳ align and correspond

4 $w_T^{\{N\}} \leftarrow \text{ObjectFeatures}(X_T^{\{N\}})$

5 $b_T^{\{N\}} \leftarrow \text{PositionalFeatures}(X_d^{\{N\}}, \mathcal{T}_{T\leftarrow d}^{\{N\}})$

6 $n_T^{\{N\}} \leftarrow \text{NodeFeatures}(w_T^{\{N\}}, b_T^{\{N\}})$ ⊳ node features for initial graph

7 $G^Z = (z^{\{N\}}, E) \leftarrow g_\Phi(G^T = (n_T^{\{N\}}, E))$ ⊳ graph with higher level node features

8 $\rho^{\{N \times N\}} \leftarrow \emptyset$

9 **for** $(i,j) \in E$ **do**

10 $\quad \rho_{i,j}^{\{N \times N\}} = h_\Psi([z_i^{\{N\}} \| z_j^{\{N\}}])$ ⊳ edge decoding for each pairwise edge

11 $G^D = (N, \rho^{\{N\}} > t^*)$ ⊳ creation of dependency graph based on threshold

12 **if** $\text{IsNotDAG}(G^D)$ **then**

13 $\quad$ **return** Circular Dependency Failure ⊳ detecting unrecoverable prediction error

14 $P^{\{N\}} \leftarrow \emptyset$

15 **for** $i, k_i \in \text{TopologicalSorting}(G^D)$ **do**

16 $\quad S_i, \delta_i \leftarrow \text{RearrangmentStep}(i, \mathcal{T}_{T\leftarrow I}^{\{N\}})$ ⊳ i^{th} object selection operator and transformation

17 $\quad P \leftarrow P \cup \{S_i, \delta_i, k_i\}$ ⊳ adding step i to plan

18 **return** P

---

that provide a stable surface of non-negligible surface area will be selected for placements (e.g., a pyramid will not be placed upright but may be placed sideways). For the 1^{st} layer, objects are initially placed randomly within the bounds of the target scene, ensuring no collision. Following this, a 2 step process is repeated for each i^{th} layer. First, attempt to place objects supported by 2 objects in the previous layer. For this, we consider each pair of objects in the previous layer with available surface area and attempt to place an object in some valid orientation given the distance between the supporting objects. This is done by sampling some points on the top surface of the supporting objects and fitting a plane to them, which is used as the target pose for the object to be placed. Note that this allows for placements that are not constrained to be axis aligned. Once all such supporting pairs in the previous layer have been exhausted, we move on to the second phase. In the second phase, we repeat the process but attempt to place objects on top of just one object from the previous layer. This is repeated until the step budget is exhausted. In simulation, we calculate the ground truth dependency graph using the y-components of the contact force vectors between each pair of objects. The graph encoder g_Φ and edge decoder h_Ψ were trained together in a supervised manner to minimize the binary cross entropy loss between the adjacency matrices of the predicted and ground truth dependency graphs. Some examples of generated structures are given in Figure. 3. We use PyByllet [35] for the simulation environment and use Trimesh [36] for collision and geometric checking. More information, including the generation algorithm's pseudo-code is provided in Section 1 of the supplementary.

5 Results

We perform five sets of experiments. First, we tested our method on unseen structures in the simulated environment and compared it with some model-based and classical baselines. Second, we show how our method generalizes to multi-level object rearrangement tasks with structures containing a higher number of objects. Thirdly, we show our method's generalization to multi-level object rearrangement tasks with unseen structures consisting of higher number of levels than were in the training set. Fourthly, we measure execution time for completion in the case that the order-agnostic steps in the plan yielded by our algorithm are being performed by 2 manipulators simultaneously. Finally, we demonstrate our method's sim-to-real generalization on multi-level object rearrangement

Planner	Performance Metrics				
	Success (%) ↑	Completion (%) ↑	Steps ↓	Pos Error (m)↓	Orn Error (0-1)↓
SCL (Ours)	95.1	98.7	1.0 ± 0.0	0.002 ± 0.003	0.0024 ± 0.0028
MLP	76.2	81.7	1.0 ± 0.0	0.002 ± 0.004	0.0024 ± 0.0031
Classical Random	90.1	98.0	1.48 ± 0.22	0.002 ± 0.004	0.0029 ± 0.0033
Classical Iterative	45.8	81.8	1.56 ± 0.25	0.002 ± 0.004	0.0021 ± 0.0025

Table 1: Comparison between our approach with classical and model-based baselines. Our approach shows better-performing plans with fewer steps

tasks in the real world. The real world experiments also show our method generalizing to and operating on structures with objects placed in locations that cross between different levels – something also not present in the training data. Also note that the errors and steps were only calculated for successful cases.

Evaluation Metrics. We use the following metrics for quantitative comparisons of different tasks: *Success Rate.* The percentage of successfully solved unseen scenes where success is defined as no object's achieved pose exceeding the target position by 1cm or the target orientation by 0.03 (normalized quaternion distance). *Completion Rate.* The percentage of objects whose achieved pose was within the success threshold of their target in the scene, averaged over all scenes. *Planning Steps.* The ratio of the planning steps required to rearrange the objects from the initial scene to the target scene and the number of objects in the scene, averaged over all scenes. *Position Error.* The mean Euclidean distance between an object's achieved and target position for all objects in the scene, averaged over all scenes. *Orientation Error.* The mean quaternion distance $\varphi(q_1, q_2) = \min\{||q_1 + q_2||_2, ||q_1 - q_2||_2\}$ [37], normalized to be between 0 and 1, between the quaternions representing the achieved and the target orientations for all objects in the scene, averaged over all scenes.

Baselines. The following baseline planners take over once the object correspondences between the target and initial scenes have been calculated. *Classical Iterative Baseline.* This is a model-free planner which iteratively selects objects from the initial scene that are not yet in their target pose. Once it has a candidate selected, it checks whether they can be stably placed in their target pose without falling by attempting a set of ray checks on the target location. If the check fails, it continues the iteration. Once it finds a valid object for placement, it places the object and restarts its iteration. *Classical Random Baseline.* This is a model-free planner which randomly selects objects from the initial scene that are not yet in their target pose. Once it selects a candidate, it does a stability check similarly to the other classical planner. If the check fails, it removes said object from its selection pool and continues random selection. If the check succeeds, it moves the object to its target pose and resets its selection pool to the current set of objects not in its target pose. *MLP Based Baseline.* This is an MLP-based object selection network that was trained on node features $[n_i^{\{N\}} \mid\mid n_T^{\{N\}}]$ obtained from the scene after the execution of step p_i from a ground truth plan with the goal of having the selection network learn and output the correct object selection operation $M_i \in p_i$ for planning. N was set to a maximum value of 10 and node features were padded with zeros if the scene had fewer objects.

Comparison Analysis. Table 1 shows our comparison results with the aforementioned baselines, evaluated on upwards of 400 scenes of unseen structures. Our approach outperforms all baselines in terms of success and completion rate. The MLP baseline had a tendency to get stuck in a local minimum for which object to move next, causing it to sometimes not be able to attempt rearrangement of the remaining objects, resulting in a lower completion rate. Classical baselines were given a budget of $2 \cdot N$, which proves far too little for the iterative approach and also stops the random approach short of ours in terms of performance. Our approach generalizes to multiple objects, unlike MLP, and provides better performance in fewer steps compared to the classical approaches.

Scalability Analysis. Table 2 shows our method's ability to generalize to scenes with a variable number of objects, evaluated over more than 400 unseen scenes of structures with at most 3 layers. Our approach performs very well in scenes with less than 15 objects despite having been trained using a set containing an average of 9 objects. While a higher number of objects in a scene cause

Number of Objects (N)	Performance Metrics			
	Success (%) ↑	Completion (%) ↑	Position Error (m) ↓	Orientation Error (0-1)↓
$8 \leqslant N \leqslant 10$	95.1	98.7	0.002 ± 0.003	0.0021 ± 0.0028
$10 \leqslant N < 15$	93.9	98.2	0.002 ± 0.003	0.0024 ± 0.0036
$15 \leqslant N < 20$	81.1	97.9	0.003 ± 0.004	0.0028 ± 0.0043
$20 \leqslant N < 25$	73.7	96.7	0.003 ± 0.004	0.0031 ± 0.0054

Table 2: Performance of our approach as the number of objects in the scene increases. Larger number of objects in the same space results in occlusion, causing lower success rates but with the completion rates remaining high

occlusion resulting in poorer prediction, our algorithm can still recover and deliver high completion rates even when success rates reduce. Table 3 shows the performance of our approach on over 1000 scenes containing meaningful structures with a variety of levels despite having been trained only on scenes containing at most 3 levels, showing its ability to generalize to novel and unseen structure configurations. On structures with less than 3 levels, it has a 100% success rate. While occlusion due to denser structures causes a lower success rate as the number of levels increases, our algorithm still maintains a high completion rate.

Number of Levels	Performance Metrics			
	Success (%) ↑	Completion (%) ↑	Position Error (m) ↓	Orientation Error (0-1)↓
1	100.0	100.0	0.001 ± 0.000	0.0011 ± 0.0004
2	100.0	100.0	0.002 ± 0.003	0.0025 ± 0.0038
3	94.5	98.6	0.002 ± 0.003	0.0036 ± 0.0045
4	88.0	98.4	0.002 ± 0.003	0.0036 ± 0.0038
5	79.8	97.0	0.002 ± 0.003	0.0038 ± 0.0039

Table 3: Generalization of our approach to structures with higher levels. Meaningful structures with higher levels again cause occlusion, and we see a similar trend of lower success rates but better completion rates. Note that our method only trained on structures containing at most 3 levels.

Sim2Real Generalization. We performed a set of real-world experiments using a UR5e robot with a suction gripper and three Intel RealSense cameras for scene observation. We set up target structures ranging from 8 to 16 blocks with various levels within the structure and block locations that cross between levels, a example shown in Fig. 1. Despite being trained in simulation with structures limited to 3 levels and discrete level layers, our method generalizes well to novel problem settings in the real world. The demonstration videos are provided in the supplementary material.

6 Conclusions, Limitations, and Future Works

We presented Structured Concept Learning (SCL), a graph attention network-based approach for multi-level rearrangement planning. SCL is an end-to-end approach which infers the dependency of objects and substructures to build multi-level structures from point cloud sets of the initial and target scene from RGB-D cameras. Our approach was trained on a novel data set gathered by our intuitive multi-level structure generation procedure[1]. In addition to demonstrating its sim-to-real generalization, we evaluate our approach on challenging problems defined by target scenes containing different unseen structures with a variety of objects and level hierarchies. As far as limitations go, we noticed that very dense structures can cause occlusion which results in very incomplete point clouds and propagates through to SCL as incorrect features (either from incorrect matching or identity prediction). This results in either faulty inferred dependence or incorrect spatial transformations for movement. Hence, for future work, we aim to augment SCL with robust segmentation, point-cloud shape completion, and matching techniques to improve dependence estimation and reduce incorrect predictions. Another future objective to extend SCL so it can utilize its existing ability of finding independent substructures to control multiple robots for faster execution. Furthermore, we would like to extend SCL to more general multi-robot tasks and incorporate multi-agent specific considerations allowing for improved complex execution to accomplish target states not achievable by a single robot.

---

[1]The dataset, its generation heuristic, and SCL implementation will be open-sourced with our final manuscript.

References

[1] D. Batra, A. X. Chang, S. Chernova, A. J. Davison, J. Deng, V. Koltun, S. Levine, J. Malik, I. Mordatch, R. Mottaghi, et al. Rearrangement: A challenge for embodied ai. *arXiv preprint arXiv:2011.01975*, 2020.

[2] A. H. Qureshi, A. Mousavian, C. Paxton, M. C. Yip, and D. Fox. Nerp: Neural rearrangement planning for unknown objects. *Robotics: Science and Systems (RSS)*, 2021.

[3] H. Tian, C. Song, C. Wang, X. Zhang, and J. Pan. Sampling-based planning for retrieving near-cylindrical objects in cluttered scenes using hierarchical graphs. *IEEE Transactions on Robotics*, 39(1):165–182, 2023. doi:10.1109/TRO.2022.3191596.

[4] B. Tang and G. S. Sukhatme. Selective object rearrangement in clutter. In *Conference on Robot Learning*, pages 1001–1010. PMLR, 2023.

[5] Y. Huang, A. Conkey, and T. Hermans. Planning for multi-object manipulation with graph neural network relational classifiers. *IEEE Conference on Robotics and Automation (ICRA)*, 2023.

[6] A. Zeng, P. Florence, J. Tompson, S. Welker, J. Chien, M. Attarian, T. Armstrong, I. Krasin, D. Duong, V. Sindhwani, and J. Lee. Transporter networks: Rearranging the visual world for robotic manipulation. *Conference on Robot Learning (CoRL)*, 2020.

[7] H. Wu, J. Ye, X. Meng, C. Paxton, and G. Chirikjian. Transporters with visual foresight for solving unseen rearrangement tasks. *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2022.

[8] Y. Zhu, J. Tremblay, S. Birchfield, and Y. Zhu. Hierarchical planning for long-horizon manipulation with geometric and symbolic scene graphs. *International Conference on Robotics and Automation (ICRA)*, 2021.

[9] A. Murali, A. Mousavian, C. Eppner, A. Fishman, and D. Fox. Cabinet: Scaling neural collision detection for object rearrangement with procedural scene generation. *arXiv preprint arXiv:2304.09302*, 2023.

[10] C. R. Garrett, R. Chitnis, R. Holladay, B. Kim, T. Silver, L. P. Kaelbling, and T. Lozano-Pérez. Integrated task and motion planning. *Annual review of control, robotics, and autonomous systems*, 4:265–293, 2021.

[11] C. R. Garrett, T. Lozano-Pérez, and L. P. Kaelbling. Pddlstream: Integrating symbolic planners and blackbox samplers via optimistic adaptive planning. In *Proceedings of the International Conference on Automated Planning and Scheduling*, volume 30, pages 440–448, 2020.

[12] S. H. Cheong, B. Y. Cho, J. Lee, C. Kim, and C. Nam. Where to relocate?: Object rearrangement inside cluttered and confined environments for robotic manipulation. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7791–7797. IEEE, 2020.

[13] R. Wang, K. Gao, D. Nakhimovich, J. Yu, and K. E. Bekris. Uniform object rearrangement: From complete monotone primitives to efficient non-monotone informed search. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6621–6627. IEEE, 2021.

[14] K. Gao, D. Lau, B. Huang, K. E. Bekris, and J. Yu. Fast high-quality tabletop rearrangement in bounded workspace. *International Conference on Robotics and Automation (ICRA)*, 2021.

[15] H. Song, J. A. Haustein, W. Yuan, K. Hang, M. Y. Wang, D. Kragic, and J. A. Stork. Multi-object rearrangement with monte carlo tree search: A case study on planar nonprehensile sorting. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 9433–9440. IEEE, 2020.

[16] Y. Labbé, S. Zagoruyko, I. Kalevatykh, I. Laptev, J. Carpentier, M. Aubry, and J. Sivic. Monte-carlo tree search for efficient visually guided rearrangement planning. *IEEE Robotics and Automation Letters*, 5(2):3715–3722, 2020.

[17] J. Lee, C. Nam, J. Park, and C. Kim. Tree search-based task and motion planning with pre-hensile and non-prehensile manipulation for obstacle rearrangement in clutter. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 8516–8522, 2021. doi: 10.1109/ICRA48506.2021.9561895.

[18] M. Danielczuk, A. Mousavian, C. Eppner, and D. Fox. Object rearrangement using learned implicit collision functions. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6010–6017. IEEE, 2021.

[19] W. Goodwin, S. Vaze, I. Havoutis, and I. Posner. Semantically grounded object matching for robust robotic scene rearrangement. In *2022 International Conference on Robotics and Automation (ICRA)*, pages 11138–11144. IEEE, 2022.

[20] L. Weihs, M. Deitke, A. Kembhavi, and R. Mottaghi. Visual room rearrangement. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 5922–5931, 2021.

[21] A. Goyal, A. Mousavian, C. Paxton, Y.-W. Chao, B. Okorn, J. Deng, and D. Fox. Ifor: Iterative flow minimization for robotic object rearrangement. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14787–14797, 2022.

[22] M. Wu, F. Zhong, Y. Xia, and H. Dong. Targf: Learning target gradient field to rearrange objects without explicit goal specification. *Advances in Neural Information Processing Systems*, 35:31986–31999, 2022.

[23] Q. A. Wei, S. Ding, J. J. Park, R. Sajnani, A. Poulenard, S. Sridhar, and L. Guibas. Lego-net: Learning regular rearrangements of objects in rooms. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 19037–19047, 2023.

[24] I. Kapelyukh, V. Vosylius, and E. Johns. DALL-e-bot: Introducing web-scale diffusion models to robotics. *IEEE Robotics and Automation Letters*, 8(7):3956–3963, jul 2023. doi:10.1109/lra.2023.3272516. URL https://doi.org/10.1109%2Flra.2023.3272516.

[25] W. Liu, C. Paxton, T. Hermans, and D. Fox. Structformer: Learning spatial structure for language-guided semantic rearrangement of novel objects. In *2022 International Conference on Robotics and Automation (ICRA)*, pages 6322–6329. IEEE, 2022.

[26] E. Stengel-Eskin, A. Hundt, Z. He, A. Murali, N. Gopalan, M. Gombolay, and G. Hager. Guiding multi-step rearrangement tasks with natural language instructions. In A. Faust, D. Hsu, and G. Neumann, editors, *Proceedings of the 5th Conference on Robot Learning*, volume 164 of *Proceedings of Machine Learning Research*, pages 1486–1501. PMLR, 08–11 Nov 2022. URL https://proceedings.mlr.press/v164/stengel-eskin22a.html.

[27] S. K. S. Ghasemipour, D. Freeman, B. David, S. S. Gu, S. Kataoka, and I. Mordatch. Blocks assemble! learning to assemble with large-scale structured reinforcement learning. *International Conference on Machine Learning (ICML)*, 2022.

[28] M. Yu, L. Shao, Z. Chen, T. Wu, Q. Fan, K. Mo, and H. Dong. Roboassembly: Learning generalizable furniture assembly policy in a novel multi-robot contact-rich simulation environment. *arXiv preprint arXiv:2112.10143*, 2021.

[29] V. N. Hartmann, A. Orthey, D. Driess, O. S. Oguz, and M. Toussaint. Long-horizon multi-robot rearrangement planning for construction assembly. *IEEE Transactions on Robotics*, 2023.

[30] C. R. Qi, L. Yi, H. Su, and L. J. Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *Conference on Neural Information Processing Systems (NIPS)*, 2017.

[31] H. Yang, J. Shi, and L. Carlone. Teaser: Fast and certifiable point cloud registration. *IEEE Transactions on Robotics (T-RO)*, 2020.

[32] J. Ortiz, A. Clegg, J. Dong, E. Sucar, D. Novotny, M. Zollhoefer, and M. Mukadam. isdf: Real-time neural signed distance fields for robot perception. *Robotics: Science and Systems (RSS)*, 2022.

[33] P. Veličković, G. Cucurull, A. Casanova, A. Romero, P. Liò, and Y. Bengio. Graph attention networks. *International Conference on Learning Representations (ICLR)*, 2018.

[34] S. Brody, U. Alon, and E. Yahav. How attentive are graph attention networks? *International Conference on Learning Representations (ICLR)*, 2022.

[35] E. Coumans, Y. Bai, and J. Hsu. Pybullet, 2015. URL https://pybullet.org/.

[36] Dawson-Haggerty et al. trimesh, 2019. URL https://trimsh.org/.

[37] D. Q. Huynh. Metrics for 3d rotations: Comparison and analysis. *Journal of Mathematical Imaging and Vision*, 35:155–164, 2009.