NotInject: Evaluating and Mitigating Over-defense in Prompt Guard Models for Robustness against Prompt Injection Attacks

Abstract

Prompt injection attacks pose a critical threat to *large language models* (LLMs), enabling goal hijacking and data leakage. Prompt guard models, though effective in defense, suffer from over-defense—falsely flagging benign inputs as malicious due to trigger word bias. To address this issue, we introduce NotInject, an evaluation dataset that systematically measures over-defense across various prompt guard models. NotInject contains 339 benign samples enriched with trigger words common in prompt injection attacks, enabling fine-grained evaluation. Our results show that state-of-the-art models suffer from over-defense issues, with accuracy dropping close to random guessing levels (60%). To mitigate this, we propose InjecGuard, a novel prompt guard model that incorporates a new training strategy, *Mitigating Over-defense for Free* (MOF), which significantly reduces the bias on trigger words. InjecGuard demonstrates state-of-the-art performance on diverse benchmarks including NotInject, surpassing the existing best model by 30.8%, offering a robust and open-source solution for detecting prompt injection attacks. Th code and datasets are released at https://anonymous.4open.science/r/InjecGuard-10DA.

1 Introduction

Prompt injection attacks (Perez and Ribeiro, 2022; Greshake et al., 2023; Liu et al., 2024) represent a serious and emerging threat to the security and integrity of *large language models* (LLMs) (Brown et al., 2020). These attacks exploit the models' reliance on natural language inputs by inserting malicious or manipulative prompts, leading to undesirable behaviors such as goal hijacking or sensitive data leakage. For instance, a well-known prompt injection technique involves instructing the LLM to "ignore previous instructions," (Branch et al., 2022; Harang, 2023a; Perez and Ribeiro, 2022; Willison, 2022) which can override built-in safeguards

and enable the execution of unauthorized actions. As the deployment of LLMs continues to expand across industries, the risk posed by prompt injection attacks becomes more pronounced, demanding effective and efficient defense mechanisms.

To address it, prompt guard models (Meta, 2024; ProtectAI.com, 2024; Deepset, 2024b; fmops, 2024) have recently been proposed as a promising solution. These models work by analyzing the semantic meaning of the input data to detect malicious intent before it reaches the LLM. Unlike LLM models, prompt guard models are lightweight and computationally efficient, as they do not require the high inference cost associated with LLMs. Additionally, these models operate independently, without the need for victim LLM's responses, further reducing computation costs compared to approaches like LLM guardrails (Inan et al., 2023). These attributes make prompt guard models adaptable to various environments, and an attractive solution in scenarios where speed and resource optimization are critical.

Despite these advantages, we find that existing prompt guard models face a critical limitation: the issue of over-defense. Over-defense arises when models misclassify inputs due to reliance on shortcuts, resulting in false positives where benign inputs are incorrectly flagged as threats. For instance, as shown in Fig. 1, commonly used words such as "ignore" or "cancel" can be in part of harmless sentences but are misclassified as malicious by many existing (even commercial) prompt guard models. Such over-defense problem reduces LLM accessibility, as the prompt guard model may reject legitimate user requests and block access. It can also cause significant disruptions in real-world applications, particularly in interactive systems like virtual assistants (Dong et al., 2023) and medical diagnostic tools (Thirunavukarasu et al., 2023), where immediate and reliable access is crucial.

To address this issue, we introduce **NotInject**,

Figure 1: Left: PromptGuard (Meta, 2024) [1], Right: ProtectAIv2 (ProtectAI.com, 2024) [2], which is current SotA prompt guard model. We found that existing prompt guard models have an over-defense issue, i.e., misclassify benign inputs as malicious due to an overreliance on specific trigger words, such as "ignore".

an evaluation dataset specifically designed to assess the over-defense issue of existing models. The dataset contains 339 carefully crafted benign inputs, developed using statistical methods on existing benign and attack datasets. The test cases in NotInjectcontain trigger words commonly found in prompt injection attacks, while still preserving benign intent. We further divided the dataset into three levels of difficulty, based on the number of trigger words present, enabling more fine-grained evaluation. Through systematic evaluations based on NotInject, we demonstrate that current prompt guard models, including current *state-of-the-art* (SotA) solutions like ProtectAIv2 (ProtectAI.com, 2024), suffer from significant over-defense issues, with over-defense accuracy falling below 60%, which is close to random guessing (50%).

In addition to the dataset, we also propose (**MOF**), which mitigates the above over-defense issue. Since existing prompt guard models are closed-source and training data is not released, our journey starts with curating a comprehensive collection of training datasets with carefully designed data-centric augmentation techniques for addressing the long-tail problem. To further address the over-defense problem, instead of directly finetuning on a specific dataset (e.g, NotInject), which introduces unfair evaluation results, here, we introduce *Mitigating Over-defense for Free* (MOF), , without relying on any specific over-defense datasets. As a result, **InjecGuard** achieves SotA performance across multiple benchmarks, including NotInject. Evaluation results show that InjecGuard outperforms existing prompt guard models, achieving over 83% average accuracy in detecting benign, malicious, and over-defense inputs, surpassing the runner-up prompt guard model by 30.8%. Remark-

ably, InjecGuard achieves similar performance to GPT-4o (OpenAI, 2024a), a commercial LLM, while being an lightweight model trained on De-BERTa (He et al., 2023). Furthermore, our model reaches this performance using a fully open-source dataset, unlike some existing prompt guard models that rely on closed datasets (Meta, 2024; Protec-tAI.com, 2024), further promoting a transparency and open-source academic research environment.

2 Related Works

Prompt injection attacks. Prompt injection attacks have become a critical threat to LLMs. Since LLMs process inputs in natural language, they often face challenges distinguishing between legitimate user commands and external manipulative inputs, leaving them vulnerable. The concept is first identified in research by Perez and Ribeiro (2022), revealing that LLMs could be misled by simple, crafted inputs, resulting in goal hijacking and prompt leakage. Several studies have been proposed (Greshake et al., 2023; Wang et al., 2023; Pedro et al., 2023; Yan et al., 2023; Yu et al., 2023; Salem et al., 2023; Yip et al., 2024; Zhan et al., 2024; Liu et al., 2024; Pasquini et al., 2024; Shi et al., 2024), addressing various aspects of prompt injection attacks, such as handcrafted methods (Toyer et al., 2023), automatic attack algorithms (Liu et al., 2024), and benchmarks (Liu et al., 2023; Debenedetti et al., 2024). Public discussions (Ha-rang, 2023b; Willison, 2022, 2023) have also underscored the risks of prompt injection attacks on

---

[1] https://huggingface.co/meta-llama/Prompt-Guard-86M
[2] https://huggingface.co/protectai/deberta-v3-base-prompt-injection-v2

commercial LLMs. Prompt Injection datasets are also introduced, such as PINT-benchmark (Lakera, 2024), Safeguard-Injection (Erdogan et al., 2024), Deepset-Injection (Deepset, 2024a), Task-Tracker (Abdelnabi et al., 2024), and BIPIA (Yi et al., 2023).

Prompt guard models. Prompt guard models offer a promising approach to defend against prompt injection attacks by detecting malicious intent in inputs. These methods are computationally efficient and, unlike LLM guardrails (Inan et al., 2023), do not require an additional round of victim LLM inference to generate a response. Several prompt guard models have been proposed recently. Fmops (fmops, 2024) is a guardrail trained by FmopsAI, utilizing Distil-BERT (Sanh et al., 2020) as the backbone. Deepset (Deepset, 2024b), PromptGuard (Meta, 2024), and ProtectAIv2 (ProtectAI.com, 2024) all employ DeBERTaV3-base (He et al., 2023) as the backbone. Deepset (Deepset, 2024b) is trained on Deepset-Injection (Deepset, 2024a), a small open-sourced dataset with 546 samples. PromptGuard is a model trained by Meta with a close-sourced dataset. ProtectAIv2 is also trained with a close-sourced dataset by Protect AI, achieving SotA performance on PINT-benchmark (Lakera, 2024).

However, these prompt guard models suffer from over-defense issues, where they rely on shortcuts triggered by certain keywords to make predictions, leading them to incorrectly categorize a benign input that contains the keywords as malicious. Moreover, some of these models are trained using closed-source data (Meta, 2024; ProtectAI.com, 2024). In this paper, we introduce an over-defense dataset to systematically evaluate the over-defense issue, and propose a novel training approach that achieves SotA performance across diverse benchmarks, including the over-defense dataset.

3 Over-defense Dataset: NotInject

3.1 The Over-defense Issue

While prompt guards offer several advantages, such as low overhead as previously mentioned, we have identified a critical limitation: they exhibit severe over-defense issues, even in some commercial tools (ProtectAI.com, 2024). Specifically, these models learn a shortcut from certain trigger words, like "ignore", directly to the final prediction. As shown in Fig. 2 with red lines, ProtectAIv2 (ProtectAI.com, 2024), one of the SOTA prompt guard

Figure 2: Visualization of attention weight. Given an instruction of "[CLS] Can I ignore this warning appeared in my code? [SEP]", ProtectAIv2 (ProtectAI.com, 2024) assigns extremely high attention weights to the word "ignore," leading to misclassification as Injection. In contrast, our method distributes attention across the entire sentence, successfully predicting it as benign.

models on PINT-benchmark, distributes excessive and unbalanced attention to the word "ignore", leading it to incorrectly categorize a benign input as malicious. To further illustrate this issue, we input a benign sentence containing the word "ignore" into two advanced prompt guard models: PromptGuard (Meta, 2024) and ProtectAIv2 (ProtectAI.com, 2024), and present the results in Fig. 1. Both models incorrectly classify the benign instruction containing the word "ignore" as malicious.

In this paper, **we define the over-defense issue** in prompt guard models as *the tendency to predict malicious labels when benign sentences contain certain trigger words commonly used in prompt injection attacks*.

3.2 Construction of NotInject

To enhance the community's ability to address the above issues, we introduce an over-defense evaluation dataset that supports systematically evaluating the over-defense issue inherent in prompt guard models. As shown in Fig. 3, to build NotInject, there are three main steps: 1) Trigger word identification, which aims to find candidate trigger words likely to cause over-defense; 2) Trigger word refinement, which filters out misidentified words from the first step; and 3) Corpus generation, which uses LLMs to generate over-defense test cases based on the identified trigger words.

Trigger Words Identification. We begin by collecting two primary datasets: a dataset containing known prompt injection attack examples, denoted as D_m (malicious dataset), and a benign dataset comprising typical user inputs devoid of malicious

Figure 3: The pipeline for constructing NotInject dataset.

intent, denoted as D_b. We collect these data from several open-source datasets, such as Alpaca (Taori et al., 2023) and Safeguard-Injection (Erdogan et al., 2024) (detailed information is provided in the Appendix. A). The injection dataset includes various malicious inputs crafted to manipulate LLMs, whereas the benign dataset represents non-harmful user interactions. Then, as illustrated in Fig. 3, we perform a word frequency analysis on both datasets. For each dataset, we compute the word frequencies to obtain frequency lists F_b and F_m for the benign and malicious datasets, respectively. We rank these words based on their frequencies from highest to lowest, resulting in two separate lists sorted by occurrence rates. Next, to identify injection-specific words, we compare the word frequency rank between the two datasets. By calculating the rank difference through, $\Delta r(w) = R_b(w) - R_m(w)$, we recognize words that are more frequent in the injection dataset but less common in the benign dataset. Words that exhibit a significantly higher frequency in the injection dataset are flagged as potential trigger words associated with prompt injections. Our detailed algorithm is shown in Alg. 1. We also visualize the top 20 words identified as trigger words by our method in Fig. 4.

Trigger Words Refinement. Recognizing that automated methods may include irrelevant or common words not indicative of prompt injection attempts, we proceed with a word rectification process. We first employ LLM to automatically filter the list of candidate words to remove any that may not be pertinent. Specifically, We assess the potential harmfulness of words by asking GPT-4o-mini (OpenAI (2024b), we use the 2024-07-18 version by default unless otherwise specified) questions like, "Do you think the word of **{word}** is especially frequent in malicious or prompt attack scenarios?" [1] Next, we perform a manual verification step, where we review the remaining words after

Figure 4: The top-20 rank differences between benign and malicious datasets.

LLM filtering to ensure that any words unrelated to prompt injection attacks are removed. Through these two steps, we have compiled a word list with the highest potential for malicious use.

Corpus Generation. With a refined list of trigger words, we then generate sample sentences. We instruct the GPT-4o-mini to craft new sentences that must include a specified number of the selected trigger words [2]. Specifically, we select the generated 113 trigger words and create three subsets with distinct difficulty levels, determined by the number of trigger words used in the generation of new sentences. Namely, three subsets separately containing 1, 2, and 3 trigger words are built with 113 benign sentences per subset. It is imperative that these sentences are contextually coherent, semantically meaningful, and do not contain any prompt injection instructions or malicious content. The goal is to represent benign usage of the trigger words in everyday language, ensuring that the sentences reflect natural and diverse linguistic patterns. To accomplish this, we design a carefully curated prompt (see Appendix. C) to guide the LLM in generating safe and natural sentences. We then implement a polish process to further ensure the safety of the generated samples. In this process, the generated sentences are re-input into the LLM to identify

any potential injection vulnerabilities, using the prompt detailed in Appendix. C. Following this, we conduct a manual review to confirm the safety of all sentences. This multi-step refinement process guarantees that all generated sentences are harmless. The final output forms the proposed NotInject, which contains a total of 339 generated samples with 113 for one-word subset, 113 for two-word subset, and 113 for three-word subset.

Algorithm 1 Trigger Words Identification

Require: Benign dataset D_b, Malicious dataset D_m, Integer k
1: Compute word frequencies in D_b to get frequency list F_b
2: Compute word frequencies in D_m to get frequency list F_m
3: Sort F_b in descending order to get rank list R_b
4: Sort F_m in descending order to get rank list R_m
5: **for all** words w in $R_b \cup R_m$ **do**
6:     Compute rank difference ($\Delta r(w) = R_b(w) - R_m(w)$)
7:     Add $(w, \Delta r(w))$ to list L
8: **end for**
9: Sort list L in descending order based on $\Delta f(w)$
10: **return** Top k words from list L

3.3 Evaluations on NotInject

Here, we present our evaluations based on the proposed NotInject, assessing 4 existing prompt guard models. To provide a comprehensive evaluation, in addition to the over-defense evaluation, we employ a three-dimensional metric. First, we measure *malicious accuracy*, which reflects how effectively the models detect malicious inputs using attack data from the PINT-benchmark (Lakera, 2024) and BIPIA datasets (Yi et al., 2023). Second, we evaluate *benign accuracy*, i.e., how accurately the models classify benign data as non-malicious, using benign data from both the PINT-benchmark and WildGuard benchmark (Han et al., 2024). Finally, we assess *over-defense accuracy*, which captures the models' performance when encountering benign inputs that contain trigger words like "ignore", using our proposed NotInject dataset.

Based on above, we evaluate existing prompt guard models (i.e., Deepset (Deepset, 2024b), Fmops (fmops, 2024), PromptGuard (Meta, 2024), and ProtectAIv2 (ProtectAI.com, 2024)).

The results are shown in Fig. 5, where the x, y, and z axes represent malicious accuracy, benign accuracy, and over-defense accuracy, respectively. As illustrated, none of the existing prompt guard models (i.e., Deepset (Deepset, 2024b), Fmops (fmops,

---

[1, 2] Detailed prompts are in the Appendix.

Deepset ▲ **PromptGuard** ● **InjecGuard (Ours)** ★
Fmops ▼ **ProtectAI** ◆

Figure 5: Comparison on 3 dimensions of benign, malicious, and over-defense accuracy.

2024), PromptGuard (Meta, 2024), and ProtectAIv2 (ProtectAI.com, 2024)) can achieve high accuracy across all three dimensions simultaneously. More importantly, none of the existing prompt guard models achieve an over-defense accuracy greater than 60%, where 50% represents random guessing. These findings underscore that our NotInject poses a significant challenge for current prompt guard models, effectively revealing the prevalent over-defense issue. This highlights the urgent need to develop a robust prompt guard model that excels in malicious accuracy, benign accuracy, and over-defense accuracy, with particular emphasis on addressing the over-defense issue.

4 InjecGuard

In this section, we aim to develop a robust prompt guard model that excels in malicious accuracy, benign accuracy, and over-defense accuracy. We also want to emphasize that many existing prompt guard models are closed-source and do not disclose their training data. Our objective is to train our model using only publicly available data, thereby promoting transparency and facilitating academic research. Here, we introduce InjecGuard, a prompt guard model that achieves state-of-the-art performance across various benchmarks. To build InjecGuard, we first curate a comprehensive collection of open-source datasets for training and apply data-centric augmentation techniques to address the long-tail problem within the dataset. More importantly, we propose a novel training strategy, MOF, which effectively mitigates over-defense issues without relying on any specific over-defense datasets.

4.1 Data Collection and Augmentation

Similar to existing models, we first collect a wide range of prompt injection and benign corpus as the training data. Specifically, we select 22 open-source datasets, including the benign datasets like Alpaca (Taori et al., 2023), the prompt injection datasets like Safeguard-Injection (Erdogan et al., 2024), and the datasets generated by existing injection attack, such as TaskTrack (Abdelnabi et al., 2024)). However, upon analyzing these datasets, we identify a long-tail issue in these datasets: certain input formats frequently exploited in prompt injection attacks—such as CSV files—are under-represented. To address this, we implement a data-centric augmentation procedure, generating additional data for these long-tail formats. Using GPT-4o-mini, we create both benign and prompt injection samples in 17 formats, including Email, Document, Chat Conversation, JSON, Code, Markdown, HTML, URL, Base64, Table, XML, CSV, Config File, Log File, Image Link, Translation, and Website. After augmentation, our final training dataset for InjecGuard comprises $55,893$ benign samples and $14,496$ prompt injection samples, where 434 samples are generated by our data-centric augmentation procedure. Detailed statistics of the training data and prompt for data-centric augmentation are provided in the Appendix. A and Appendix. C.

4.2 *Mitigating Over-defense for Free* (MOF)

To address the over-defense issue, we propose **M**itigating **O**ver-defense for **F**ree (MOF), a novel method to identify and mitigate such biases, without relying on any specific over-defense datasets.

Specifically, after training our model with the aforementioned data (Sec. 4.1) using standard supervised learning (training details are deferred to the Appendix), we perform a "token-wised recheck" to identify biases in the trained model. This procedure takes every token in the tokenizer vocabulary and inputs each token individually into the trained model. Ideally, these tokens should all be considered "benign" since they are individual tokens without any intent of prompt injection attack. By doing this, we can identify any biased words that are incorrectly predicted as "attack" by the model. We consider the bias toward these tokens as the root cause of the over-defense issue in the model.

After identifying the biased tokens, we prompt GPT-4o-mini to generate benign data using random combinations of these tokens (including one-token,

two-token, and three-token settings, as mentioned in Sec. 3.2). We generate 1,000 benign samples using this method. Subsequently, we incorporate these generated data into the training data introduced in Sec. 4.1 to form the final training dataset. Using this dataset, we retrain our prompt guard model from scratch and get the final InjecGuard.

As illustrated in Fig. 2, the retrained model focuses and makes the final prediction on the overall meaning of the entire input, rather than certain trigger words. And results in Fig. 5 show that our model achieves high accuracy across all three dimensions simultaneously. We also present ablation studies of the aforementioned training design in Tab. 2. More detailed evaluation results are provided in the following section.

5 Evaluations

5.1 Experimental Setups

Evaluation Datasets. As mentioned in Sec. 3.3, we conduct our evaluations based on three aspects: benign accuracy, malicious accuracy, and over-defense accuracy. To fully verify the practicality of our proposed InjecGuard, we ensure that all evaluation datasets are not included in the training data. Specifically, For evaluating the benign accuracy, we utilize benign data from both the Pint-Benchmark and WildGuard benchmark (Han et al., 2024). For evaluating the malicious accuracy, We use attack data from both the PINT-Benchmark (Lakera, 2024) and BIPIA datasets (Yi et al., 2023). For evaluating the over-defense accuracy, we use the proposed NotInject dataset.

Metrics. Since prompt guard models function as text classification systems that predict whether an input text is benign or malicious, we evaluate their performance using *Accuracy*, calculated as the proportion of correct predictions over the total number of test cases in the evaluation dataset:

$$\text{Accuracy} = \frac{\text{Number of Correct Predictions}}{\text{Total Number of Test Cases}} \quad (1)$$

Additionally, we report the computational overhead in terms of *Giga Floating Point Operations* (GFLOPs), which quantifies the total number of floating-point operations required during inference. GFLOPs provide an estimate of the computational resources needed by the model. We also measure the *inference time* to assess the computational overhead introduced by the models.

Training Details of InjecGuard. We employ DeBERTaV3-base (He et al., 2023) as the back-

Category	Model	Performance				Overhead		
		Over-defense (%)	Benign (%)	Malicious (%)	Average (%)	GFLOPs	Inference (ms)	Efficiency
Prompt Guard Model	Fmops (fmops, 2024)	5.60	34.63	93.50	44.58	24.19	4.43	10.06
	Deepset (Deepset, 2024b)	5.31	34.06	91.50	43.62	60.45	15.22	2.87
	PromptGuard (Meta, 2024)	0.88	26.82	97.10	41.60	60.45	15.28	2.72
	ProtectAIv2 (ProtectAI.com, 2024)	56.64	86.20	48.60	63.81	60.45	15.77	4.05
Large Language Model	GPT-4o (OpenAI, 2024a)	86.73	90.78	79.10	85.53	-	7907.18	0.01
	Llama-2-chat (Touvron et al., 2023)	76.40	61.03	31.09	56.17	1387.49	3111.36	0.02
	LlamaGuard3 (Dubey et al., 2024)	99.71	**95**.18	28.28	74.39	1418.38	787.48	0.09
Prompt Guard Model	InjecGuard (Ours)	87.32	85.74	77.39	83.48	60.45	15.34	5.44

Table 1: Performance and overhead comparison between our model, InjecGuard, and other baseline models. InjecGuard surpasses the runner-up (ProtectAIv2) by 30.8% in terms of average accuracy. Additionally, Injec-Guard achieves performance comparable to GPT-4o, a commercial LLM, despite being an lightweight model trained on open-source data. We calculate the Efficiency = Average Accuracy/Inference Time.

bone of InjecGuardand train it with a batch size of 32 for 3 epochs, using Adam (Diederik, 2015) optimizer and linear scheduler. The initial learning rate is set to 2e-5, with a 100-step warm-up phase. Besides, the maximum token length is set to 512.

Baselines. We employ four existing prompt guard models as baselines: Fmops (fmops, 2024), Deepset (Deepset, 2024b), PromptGuard (Meta, 2024), and ProtectAIv2 (ProtectAI.com, 2024), which are introduced in Sec. 2. We also consider LLM-based methods, including LlamaGuard3 (Dubey et al., 2024), Llama-2-chat-7b (Touvron et al., 2023), and GPT-4o (OpenAI, 2024a), which are evaluated by prompting them to determine a given input constitutes a prompt injection attack.

5.2 Main Results

The comparison results of our method and other baselines are shown in Tab. 1. Our Injec-Guard demonstrates superior performance compared to existing prompt guard models and even rivals commercial LLMs like GPT-4o. Specifically, InjecGuard achieves an average accuracy of 83.48%, surpassing the runner-up prompt guard baseline (ProtectAIv2) by 30.83%. Our model excels across all evaluation categories, attaining an over-defense accuracy of 87.32%, benign accuracy of 85.74%, and malicious accuracy of 77.39%. This balanced performance indicates that Injec-Guard is highly effective at correctly identifying benign and malicious inputs while minimizing false positives and negatives. The fact that InjecGuard achieves results comparable to GPT-4o, despite being based on the open-source data and lightweight backbone, highlights the efficiency and effectiveness of our training approach. Notably, according to Tab. 1, the Efficiency (Performance/Inference time) of our model is 503 times

higher than that of GPT-4o.

The results also prove that existing prompt guard models suffer from overwhelming issues with over-defense, as reflected by their low over-defense accuracy scores. Models like Fmops, Deepset, and PromptGuard exhibit over-defense accuracies as low as 5.60%, 5.31%, and 0.88%, respectively, indicating a tendency to incorrectly classify benign inputs that have trigger words as malicious. And ProtectAIv2 has an over-defense accuracy of 56.64%, which is close to random guessing (50.00%). This issue underscores the challenges posed by our proposed over-defense dataset. In addition, the superior over-defense accuracy of InjecGuard demonstrates its robustness in this field. The over-defense accuracy of our InjecGuard surpasses the runner-up prompt guard model (ProtectAIv2) by 54.17%, showing that our model effectively handles the challenging cases presented by the dataset, and confirming the efficacy of our novel training approach MOF in mitigating over-defense issues prevalent in existing models. Note that MOF does not require any over-defense dataset for training; instead, it automatically generates adaptive training data, verifying it as both practical and highly effective.

5.3 Ablation Studies

The ablation study presented in Tab. 2 offers key insights into the effects of our training components on InjecGuardperformance. Starting with the Basic Dataset, the model establishes a baseline average accuracy of 74.64%, with over-defense, benign, and malicious accuracies of 75.22%, 78.53%, and 70.17%, respectively. Introducing Data-centric Augmentation alone leads to a noticeable improvement in benign accuracy (from 78.53% to 81.36%) and malicious accuracy (from 70.17% to 75.95%), enhancing the model's ability to correctly classify both benign and malicious inputs. However, this

Training Design	Over-defense (%)	Benign (%)	Malicious (%)	Average (%)
Training on the Basic Dataset (Sec. 4.1)	75.22	78.53	70.17	74.64
+ Data-centric Augmentation (Sec. 4.1)	64.31	81.36	75.95	73.87
Training on the Basic Dataset (Sec. 4.1)	75.22	78.53	70.17	74.64
+ MOF with Retraining from Scratch (Sec. 4.2)	**89.38**	84.73	71.57	81.89
Training on the Basic Dataset (Sec. 4.1)	75.22	78.53	70.17	74.64
+ Data-centric Augmentation (Sec. 4.1)	64.31	81.36	75.95	73.87
+ MOF with Finetuning (Sec. 4.2)	68.14	82.11	74.81	75.02
Training on the Basic Dataset (Sec. 4.1)	75.22	78.53	70.17	74.64
+ Data-centric Augmentation (Sec. 4.1)	64.31	81.36	75.95	73.87
+ MOF with Retraining from Scratch (Sec. 4.2)	87.32	**85.74**	**77.39**	**83.48**

Table 2: Ablation study of each training design introduced in Sec. 4.

augmentation comes at a cost, as evidenced by a significant reduction in over-defense accuracy from 75.22% to 64.31%. This decline indicates that while data-centric augmentation enriches the training data and improves classification capabilities, it inadvertently exacerbates the over-defense issue, making the model more prone to incorrectly classifying benign inputs as malicious—a challenge commonly observed in existing models.

The introduction of the MOF, particularly when combined with Retraining from Scratch, addresses the adverse effects of data-centric augmentation on over-defense accuracy. Applying MOF with Retraining from Scratch to the Basic Dataset lifts the average accuracy to 81.89%, with over-defense, benign, and malicious accuracies at 89.38%, 84.73%, and 71.57%, respectively. This substantial improvement highlights MOF's effectiveness in mitigating over-defense issues caused by data-centric augmentation. When both Data-centric Augmentation and MOF with Retraining from Scratch are used, the model achieves the highest average accuracy of 83.48%, with over-defense, benign, and malicious accuracies of 87.32%, 85.74%, and 77.39%. This combination leverages the strengths of both data augmentation and mitigation strategies, resulting in a robust model that not only benefits from enhanced classification performance but also maintains high over-defense accuracy. The ablation study demonstrates that data-centric augmentation alone can improve certain aspects of model performance, and the integration of MOF techniques is essential to counterbalance the increased over-defense, thereby ensuring that InjecGuard achieves optimal and balanced performance across all metrics.

5.4 Computational Overhead

Our model, InjecGuard, excels in both computational efficiency and performance compared to ex-

isting baseline models. As shown in Table 1, InjecGuard achieves an average accuracy of 83.48% while maintaining a GFLOPS count of 60.45 and an inference time of only 15.34 milliseconds. With an efficiency score of 5.44 (performance divided by inference time), InjecGuard delivers robust results swiftly and resource-effectively, making it ideal for environments prioritizing both accuracy and efficiency. In contrast, LLMs like GPT-4o achieve slightly higher accuracy (85.53%) but at a significant computational cost, with an inference time of 7907.18 milliseconds and an efficiency score of 0.01. Similarly, models such as Llama-2-chat and LlamaGuard3 require thousands of GFLOPS and longer inference times, resulting in much lower efficiency. This disparity highlights the impracticality of deploying these LLMs in scenarios where computational resources and quick response times are essential. Therefore, InjecGuard presents a highly effective and efficient alternative for real-world applications demanding both high accuracy and operational efficiency.

6 Conclusions

In this study, we delved into the over-defense phenomenon observed in existing injection-based prompt guard models. To address this issue, we proposed a novel over-defense data sampling framework and introduced the NotInject benchmark to systematically evaluate the extent of over-defense in target prompt guard models. Furthermore, we presented InjecAgent, an advanced prompt guard model trained using a novel robust training strategy, MOF, designed to effectively mitigate model bias toward specific words. Our experimental results on various benchmark demonstrate that InjecAgent significantly outperforms existing prompt guard models across multiple dimensions, with substantial improvements in performance and robustness.

Limitations

While our work shows significant improvement in mitigating over-defense in prompt guard models, the NotInject dataset, while carefully designed, may not fully capture the diversity of real-world benign inputs, particularly in domain-specific applications. This could result in the underestimation of models' over-defense tendency in complex, sensitive fields such as healthcare or finance. However, as our comprehensive evaluations have shown, the current design of NotInject is sufficient to reveal the over-defense issue in existing prompt guard models, highlighting the urgent need for improved approaches in this community. To further enhance the diversity of NotInject, our future work will incorporate domain-specific data through collaboration with industry partners.

Ethics Statement

We are committed to advancing the security and integrity of LLMs responsibly. In this research, we introduce NotInject, a dataset designed to assess and mitigate the over-defense issue in prompt guard models. Additionally, we introduce InjecGuard, a powerful prompt guard model developed using our novel approach, MOF, aimed at enhancing LLM security. All data used are synthetically generated or sourced from publicly available datasets, ensuring that no personal or sensitive information is involved. This approach safeguards privacy and complies with ethical standards regarding data use.

While our work focuses on enhancing defensive mechanisms against prompt injection attacks, we acknowledge the potential for dual use in security research. We encourage the ethical and responsible use of NotInject to improve LLM security and not for malicious purposes. By addressing over-defense, we aim to reduce false positives and enhance accessibility for all users when prompt guard models are deployed. Our commitment to transparency is reflected in making both the dataset and model fully open-source, fostering collaboration, and allowing others to verify, replicate, and build upon our work for the betterment of the field.

References

Sahar Abdelnabi, Aideen Fay, Giovanni Cherubin, Ahmed Salem, Mario Fritz, and Andrew Paverd. 2024. Are you still on track!? catching LLM task drift with activations. *Preprint*, arXiv:2406.00799.

Fatih Kadir Akın. 2023. Awesome ChatGPT Prompts Dataset. https://huggingface.co/datasets/natolambert/xstest-v2-copy.

Hezekiah J. Branch, Jonathan Rodriguez Cefalu, Jeremy McHugh, Leyla Hujer, Aditya Bahl, Daniel del Castillo Iglesias, Ron Heichman, and Ramesh Darwishi. 2022. Evaluating the susceptibility of pretrained language models via handcrafted adversarial examples. *Preprint*, arXiv:2209.02128.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. Language models are few-shot learners. *Preprint*, arxiv:2005.14165.

Sizhe Chen, Julien Piet, Chawin Sitawarin, and David A. Wagner. 2024. Struq: Defending against prompt injection with structured queries.

Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. 2024. Agentdojo: A dynamic environment to evaluate attacks and defenses for llm agents. *arXiv preprint arXiv:2406.13352*.

Deepset. 2024a. Deepset Prompt Injection Dataset. https://huggingface.co/datasets/deepset/prompt-injections.

Deepset. 2024b. Deepset Prompt Injection Guardrail. https://huggingface.co/deepset/deberta-v3-base-injection.

P Kingma Diederik. 2015. Adam: A method for stochastic optimization. In the Proceedings of ICLR.

Ning Ding, Yulin Chen, Bokai Xu, Yujia Qin, Zhi Zheng, Shengding Hu, Zhiyuan Liu, Maosong Sun, and Bowen Zhou. 2023. Enhancing chat language models by scaling high-quality instructional conversations. *Preprint*, arXiv:2305.14233.

Xin Luna Dong, Seungwhan Moon, Yifan Ethan Xu, Kshitiz Malik, and Zhou Yu. 2023. Towards nextgeneration intelligent assistants leveraging llm techniques. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, KDD '23, page 5792–5793, New York, NY, USA. Association for Computing Machinery.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien

Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Graeme Nail, Gregoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel Kloumann, Ishan Misra, Ivan Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuenley Chiu, Kunal Bhalla, Lauren Rantala-Yeary, Laurens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Mahesh Pasupuleti, Mannat Singh, Manohar Paluri, Marcin Kardas, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Nikolay Bashlykov, Nikolay Bogoychev, Niladri Chatterji, Olivier Duchenne, Onur Çelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasic, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong, Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ronnie Polidoro, Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sahana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stephane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujjwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whitney Meers, Xavier Martinet, Xiaodong Wang, Xiaoqing Ellen Tan, Xinfeng Xie, Xuchao Jia, Xuewei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yi Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie Delpierre Coudert, Zheng Yan, Zhengxing Chen, Zoe Papakipos, Aaditya Singh, Aaron Grattafiori, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adithya Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alex Vaughan, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Franco, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Bernie Huang, Beth Loyd, Beto De Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Changhan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai, Chris Tindal, Christoph Feichtenhofer, Damon Civin, Dana Beaty, Daniel Kreymer, Daniel Li, Danny Wyatt, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkang Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil, Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Firat Ozgenel, Francesco Caggioni, Francisco Guzmán, Frank Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Govind Thattai, Grant Herman, Grigory Sizov, Guangyi, Zhang, Guna Lakshminarayanan, Hamid Shojanazeri, Han Zou, Hannah Wang, Hanwen Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Ibrahim Damlaj, Igor Molybog, Igor Tufanov, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kai Wu, Kam Hou U, Karan Saxena, Karthik Prasad, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kun Huang, Kunal Chawla, Kushal Lakhotia, Kyle Huang, Lailin Chen, Lakshya Garg, Lavender A, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabsa, Manav Avalani, Manish Bhatt, Maria Tsimpoukelli, Martynas Mankus, Matan Hasson, Matthew Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Maya Lathi, Meghan Keneally, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Munish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navyata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikolay Pavlovich Laptev, Ning Dong, Ning Zhang, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pedro Rittner, Philip Bontrager, Pierre

Roux, Piotr Dollar, Polina Zvyagina, Prashant Ratan-chandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Rohan Mah-eswari, Russ Howes, Ruty Rinott, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, Sasha Sidorov, Satadru Pan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lind-say, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Cindy Zha, Shiva Shankar, Shuqiang Zhang, Shuqiang Zhang, Sinong Wang, Sneha Agar-wal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield, Sudarshan Govindaprasad, Sumit Gupta, Sungmin Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Kohler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria Ajayi, Victoria Montanez, Vijai Mohan, Vinay Satish Kumar, Vishal Mangla, Vítor Albiero, Vlad Ionescu, Vlad Poenaru, Vlad Tiberiu Mihailescu, Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xiaocheng Tang, Xiaofang Wang, Xiao-jian Wu, Xiaolan Wang, Xide Xia, Xilun Wu, Xinbo Gao, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li, Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu, Wang, Yuchen Hao, Yundi Qian, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, and Zhiwei Zhao. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Lutfi Eren Erdogan, Chuyi Shang, Aryan Goyal, and Siddarth Ijju. 2024. Safe-Guard Prompt Injection Dataset. https://huggingface.co/datasets/xTRam1/safe-guard-prompt-injection.

fmops. 2024. Fmops Prompt Injection Guardrail. https://huggingface.co/fmops/distilbert-prompt-injection.

Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. 2023. Not what you've signed up for: Compro-mising Real-World LLM-Integrated Applications with Indirect Prompt Injection. *arXiv preprint*. ArXiv:2302.12173 [cs].

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. 2024. Wildguard: Open one-stop mod-eration tools for safety risks, jailbreaks. *Preprint*, arXiv:2406.18495.

Jack Hao. 2023. Jailbreak Classification Dataset. https://huggingface.co/datasets/jackhhao/jailbreak-classification.

Rich Harang. 2023a. Securing llm systems against prompt injection.

Rich Harang. 2023b. Securing LLM Systems Against Prompt Injection. https://developer.nvidia.com/blog/securing-llm-systems-against-prompt-injection.

Pengcheng He, Jianfeng Gao, and Weizhu Chen. 2023. Debertav3: Improving deberta using electra-style pre-training with gradient-disentangled embedding shar-ing. In the Proceedings of ICLR.

HuggingfaceH4. 2023. Grok Conversation Harmless Dataset. https://huggingface.co/datasets/HuggingFaceH4/grok-conversation-harmless.

Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabsa. 2023. Llama guard: Llm-based input-output safeguard for human-ai conversations. *Preprint*, arXiv:2312.06674.

Lakera. 2024. Prompt Injection Test Dataset. https://www.lakera.ai/product-updates/lakera-pint-benchmark.

Lijun Li, Bowen Dong, Ruohui Wang, Xuhao Hu, Wang-meng Zuo, Dahua Lin, Yu Qiao, and Jing Shao. 2024. Salad-bench: A hierarchical and comprehen-sive safety benchmark for large language models. *Preprint*, arXiv:2402.05044.

Xiaogeng Liu, Zhiyuan Yu, Yizhe Zhang, Ning Zhang, and Chaowei Xiao. 2024. Automatic and universal prompt injection attacks against large language mod-els. *arXiv preprint arXiv:2403.04957*.

Yupei Liu, Yuqi Jia, Runpeng Geng, Jinyuan Jia, and Neil Zhenqiang Gong. 2023. Prompt Injection At-tacks and Defenses in LLM-Integrated Applications. *arXiv preprint*. ArXiv:2310.12815 [cs].

Meta. 2024. PromptGuard Prompt Injec-tion Guardrail. https://www.llama.com/docs/model-cards-and-prompt-formats/prompt-guard/.

OpenAI. 2024a. GPT-4o. https://openai.com/index/hello-gpt-4o/.

OpenAI. 2024b. Gpt-4o mini: Advancing cost-efficient intelligence.

Alessandro Palla. 2024. Chatbot Instruction Prompt Dataset. https://huggingface.co/datasets/alespalla/chatbot_instruction_prompts.

Dario Pasquini, Martin Strohmeier, and Carmela Tron-coso. 2024. Neural exec: Learning (and learning from) execution triggers for prompt injection attacks. *Preprint*, arXiv:2403.03792.

Rodrigo Pedro, Daniel Castro, Paulo Carreira, and Nuno Santos. 2023. From Prompt Injections to SQL Injection Attacks: How Protected is Your LLM-Integrated Web Application? *arXiv preprint*. ArXiv:2308.01990 [cs].

Fábio Perez and Ian Ribeiro. 2022. Ignore Previous Prompt: Attack Techniques For Language Models. *arXiv preprint*. ArXiv:2211.09527 [cs].

ProtectAI.com. 2024. Fine-tuned deberta-v3-base for prompt injection detection.

Nazneen Rajani, Lewis Tunstall, Edward Beeching, Nathan Lambert, Alexander M. Rush, and Thomas Wolf. 2023. No robots. https://huggingface.co/datasets/HuggingFaceH4/no_robots.

Pranav Rajpurkar, Robin Jia, and Percy Liang. 2018. Know what you don't know: Unanswerable questions for squad. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics, ACL 2018, Melbourne, Australia, July 15-20, 2018, Volume 2: Short Papers*, pages 784–789. Association for Computational Linguistics.

Rubén Darío Jaramillo Romero. 2023. Chat-GPT Jailbreak Promtps Dataset. https://huggingface.co/datasets/rubend18/ChatGPT-Jailbreak-Prompts.

Paul Röttger, Hannah Rose Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. 2023. Xstest: A test suite for identifying exaggerated safety behaviours in large language models. *Preprint*, arXiv:2308.01263.

Ahmed Salem, Andrew Paverd, and Boris Köpf. 2023. Maatphor: Automated Variant Analysis for Prompt Injection Attacks. *arXiv preprint*. ArXiv:2312.11513 [cs].

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2020. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *Preprint*, arXiv:1910.01108.

Sander V Schulhoff, Jeremy Pinto, Anaum Khan, Louis-Franĉois Bouchard, Chenglei Si, Jordan Lee Boyd-Graber, Svetlina Anati, Valen Tagliabue, Anson Liu Kost, and Christopher R Carnahan. 2023. Ignore this title and hackaprompt: Exposing systemic vulnerabilities of llms through a global prompt hacking competition. In *Empirical Methods in Natural Language Processing*.

Xinyue Shen, Zeyuan Chen, Michael Backes, Yun Shen, and Yang Zhang. 2023. "do anything now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models. *Preprint*, arXiv:2308.03825.

Jiawen Shi, Zenghui Yuan, Yinuo Liu, Yue Huang, Pan Zhou, Lichao Sun, and Neil Zhenqiang Gong. 2024. Optimization-based prompt injection attack to llm-as-a-judge. *Preprint*, arXiv:2403.17710.

Adam Swanda. 2023. Vigil-Jailbreak-ada Dataset. https://huggingface.co/datasets/deadbits/vigil-jailbreak-ada-002.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. 2023. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca.

Arun James Thirunavukarasu, Darren Shu Jeng Ting, Kabilan Elangovan, Laura Gutierrez, Ting Fang Tan, and Daniel Shu Wei Ting. 2023. Large language models in medicine. *Nature medicine*, 29(8):1930–1940.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Sam Toyer, Olivia Watkins, Ethan Adrian Mendes, Justin Svegliato, Luke Bailey, Tiffany Wang, Isaac Ong, Karim Elmaaroufi, Pieter Abbeel, Trevor Darrell, Alan Ritter, and Stuart Russell. 2023. Tensor Trust: Interpretable Prompt Injection Attacks from an Online Game. *arXiv preprint*. ArXiv:2311.01011 [cs].

VMware. 2023. Open-Instruct Dataset. https://huggingface.co/datasets/VMware/open-instruct.

Chaofan Wang, Samuel Kernan Freire, Mo Zhang, Jing Wei, Jorge Goncalves, Vassilis Kostakos, Zhanna Sarsenbayeva, Christina Schneegass, Alessandro Bozzon, and Evangelos Niforatos. 2023. Safeguarding Crowdsourcing Surveys from ChatGPT with Prompt Injection. *arXiv preprint*. ArXiv:2306.08833 [cs].

Simon Willison. 2022. Prompt injection attacks against GPT-3. https://simonwillison.net/2022/Sep/12/prompt-injection/.

Simon Willison. 2023. Delimiters won't save you from prompt injection. https://simonwillison.net/2023/May/11/delimiters-wont-save-you.

Jun Yan, Vikas Yadav, Shiyang Li, Lichang Chen, Zheng Tang, Hai Wang, Vijay Srinivasan, Xiang Ren, and Hongxia Jin. 2023. Backdooring Instruction-Tuned Large Language Models with Virtual Prompt Injection. *arXiv preprint*. ArXiv:2307.16888 [cs].

Jingwei Yi, Yueqi Xie, Bin Zhu, Keegan Hines, Emre Kiciman, Guangzhong Sun, Xing Xie, and Fangzhao Wu. 2023. Benchmarking and Defending Against Indirect Prompt Injection Attacks on Large Language Models. *arXiv preprint*. ArXiv:2312.14197 [cs].

Daniel Wankit Yip, Aysan Esmradi, and Chun Fai Chan. 2024. A Novel Evaluation Framework for Assessing Resilience Against Prompt Injection Attacks in Large Language Models. *arXiv preprint*. ArXiv:2401.00991 [cs].

Jiahao Yu, Yuhang Wu, Dong Shu, Mingyu Jin, and Xinyu Xing. 2023. Assessing Prompt Injection Risks in 200+ Custom GPTs. *arXiv preprint*. ArXiv:2311.11538 [cs].

Yugen.ai. 2023. Prompt Injection Mixed Techniques Dataset. https://huggingface.co/datasets/Harelix/Prompt-Injection-Mixed-Techniques-2024.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. 2024. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents. *Preprint*, arXiv:2403.02691.

Appendix

A Datasets

A.1 Benign dataset

Our benign data are collected from 14 open-sourced datasets, including Alpaca (Taori et al., 2023), chatbot_instruction_prompts (Palla, 2024), open-instruct (VMware, 2023), xstest-v2-copy (Röttger et al., 2023), grok-conversation-harmless (HuggingfaceH4, 2023), prompt-injections (Deepset, 2024a), safe-guard-prompt-injection (Erdogan et al., 2024), awesome-chatgpt-prompts (Akın, 2023), no_robots (Rajani et al., 2023), ultrachat_200k (Ding et al., 2023), SQuAD_v2 (Rajpurkar et al., 2018), jailbreak-classification (Hao, 2023), and Question Set (Shen et al., 2023). The data distribution is shown in Table. 3.

A.2 Malicious dataset

Our malicious data are built based on 13 open-sourced datasets, and our augmented dataset in Section. 4.1. The open-sourced datasets include InjecAgent (Zhan et al., 2024), prompt-injections (Deepset, 2024a), hackaprompt-dataset (Schulhoff et al., 2023), safe-guard-prompt-injection (Erdogan et al., 2024), ChatGPT-Jailbreak-Prompts (Romero, 2023), vigil-jailbreak-ada-002 (Swanda, 2023), Prompt-Injection-Mixed-Techniques (Yugen.ai, 2023), jailbreak-classification (Hao, 2023), Salad-Data (Li et al., 2024), SQuADv2 (Rajpurkar et al., 2018), StruQ (Chen et al., 2024), TaskTrack (Abdelnabi et al., 2024), and Question Set (Shen et al., 2023). The data distribution is shown in Tab. 4. Our augmented dataset consists of a large number of long-tail data types, such as XML, HTML, Markdown, etc. The specific data type distribution is shown in Tab. 5.

Dataset	Count
alpaca	4,000
chatbot_instruction_prompts	16,000
open-instruct	12,000
xstest-v2-copy	450
grok-conversation-harmless	4,000
prompt-injections	343
safe-guard-prompt-injection	5,740
awesome-chatgpt-prompts	170
no_robots	1,500
ultrachat_200k	3,000
SQuAD_v2	2,000
jailbreak-classification	517
Question Set	6,173

Table 3: Benign Dataset Source.

Source	Count
InjecAgent	62
prompt-injections	203
hackaprompt-dataset	5,000
safe-guard-prompt-injection	2,496
ChatGPT-Jailbreak-Prompts	79
vigil-jailbreak-ada-002	104
LLM Augmentated set	434
Prompt-Injection-Mixed-Techniques	1,170
Salad-Data	3,937
SQuADv2	1,200
StruQ	21
TaskTrack	730
jailbreak-classification	527
Question Set	1,405

Table 4: Injection Dataset Source.

B Additional Experimental Results

B.1 Full Overdefense Results

In Table. 1, we have illustrated the comprehensive results on different dimensions, such as over-defense, benign, and malicious. In this section, we present detailed results for each evaluation benchmark across all dimensions, including our NotInject, Wildguard (Han et al., 2024), PINT-benchmark (Lakera, 2024), and BIPIA (Yi et al., 2023). The results are shown in Tab. 6.

B.2 Visualization of NotInject dataset

To further investigate the advantages of our method on confronting over-defense, we select the benign sentence from our over-defense dataset and perform a visualization to conduct qualitative analysis for model predictions. The results presented in Fig. 6 reveal that although the input is entirely safe, both PromptGuard (Meta, 2024) and Protec-tAIv2 (ProtectAI.com, 2024) predict it as an injection with high confidence.

In contrast, our InjecGuard accurately classifies the input as safe, highlighting the efficacy of the over-defense dataset in evaluating over-defense tendencies and demonstrating the robustness of the proposed InjecGuard.

Category	Count
Email Injection	47
Document Injection	25
Chat Conversation Injection	25
JSON Injection	23
Code Injection	23
Markdown Injection	23
HTML Injection	23
URL Injection	23
Base64 Injection	23
Table Injection	23
XML Injection	23
CSV Injection	23
Config File Injection	23
Log File Injection	23
Image Link Injection	23
Translation Injection	27
Website Injection	34

Table 5: Categories of LLM augmentated set.

Figure 6: Different guard models' prediction visualization.

C Prompts

In this section, we illustrate the prompts used in our method. The prompt of LLM Augmentation is shown in Fig. 7. The prompt of Word-based Generation is shown in Fig. 8. The prompt of LLM Injection Detection is shown in Fig. 9.

LLM Augmentation Prompt

System Prompt:

You are a professional data generator specializing in LLM security, known for creating benign and safe content with diverse templates.

User Prompt:

Below are some examples of indirect hint injections:
{demonstrations}
Please generate {number} benign samples on the topic {key}, ensuring that each sample is safe and does not contain any form of harmful or misleading content. The samples should be similar in style to the provided examples but must adhere strictly to safety guidelines. Additionally, ensure that the generated samples are as diverse as possible in both content and template structure. Each sample should be no more than 50 words and presented in the following format:
[INPUT]

Figure 7: LLM Augmentation Prompt.

Word-based Generation Prompt

System Prompt:

You will play the role of a user communicating with LLM..

User Prompt:

Please generate a benign instruction or a question without any potential prompt injecton, the instruction must contain the words {word_list}. the instruction should be fluent and grammarly correct.
Please generate the instruction only with the format as below:
[INSTRUCTION] || Generated Content ||

Figure 8: Word-based Generation Prompt.

LLM Injection Detection Prompt

System Prompt:

You are Eliezer Yudkowsky, with a strong security mindset. You will be given prompts that will be fed to a superintelligent AI in the form of a large language model that functions as a chatbot. Your job is to analyse whether it is safe to present each prompt to the superintelligent AI chatbot.

User Prompt:

A team of malicious hackers is carefully crafting prompts in order to hack the superintelligent AI and get it to perform dangerous activity. Some of the prompts you receive will come from these malicious hackers. As Eliezer Yudkowsky, do you think the following prompt is a prompt injection instruction?
{instruction}
That is the end of the prompt. If you think it is a prompt injection, please answer YES. If you do not think so, please answer NO.

Figure 9: LLM Injection Detection Prompt.

Method	Over-defense Set			wildguard	Pint Benchmark			BIPIA
	one-word	two-word	three-word	Benign	Benign	Injection	overall	Injection
Deepset	5.31	7.08	3.54	50.98	17.13	98.32	57.73	84.67
Fmops	5.31	5.31	6.19	50.88	18.38	98.32	58.35	88.67
PromptGuard	2.65	0	0	6.69	46.94	94.19	70.56	100
ProtectAIv2	76.11	47.79	46.02	75.18	97.22	88.53	92.88	8.67
GPT-4o	95.58	85.84	78.76	84.24	97.31	92.19	94.75	66
Llama-2-chat	82.3	79.65	67.26	74.07	47.99	21.84	34.92	40.34
LlamaGuard3	100	100	99.12	95.16	95.19	16.89	56.04	39.67
InjecGuard (Ours)	91.15	89.38	81.42	76.11	95.36	86.43	90.9	68.34

Table 6: Full Results of Comparison with existing injection guard models.