Learning Neural Acoustic Fields

Abstract

Our environment is filled with rich and dynamic acoustic information. When
we walk into a cathedral, the reverberations as much as appearance inform us of
the sanctuary's wide open space. Similarly, as an object moves around us, we
expect the sound emitted to also exhibit this movement. While recent advances in
learned implicit functions have led to increasingly higher quality representations of
the visual world, there have not been commensurate advances in learning spatial
auditory representations. To address this gap, we introduce Neural Acoustic Fields
(NAFs), an implicit representation that captures how sounds propagate in a physical
scene. By modeling acoustic propagation in a scene as a linear time-invariant
system, NAFs learn to continuously map all emitter and listener location pairs to a
neural impulse response function that can then be applied to arbitrary sounds. We
demonstrate NAFs on both synthetic and real data, and show that the continuous
nature of NAFs enables us to render spatial acoustics for a listener at arbitrary
locations. We further show that the representation learned by NAFs can help
improve visual learning with sparse views. Finally we show that a representation
informative of scene structure emerges during the learning of NAFs. Project site:
https://sites.google.com/view/nafs-neurips2022

1 Introduction

The sound of the ball leaving the bat, as much as its visible trajectory, tells us whether the hit is likely
to be a home run or not. Our experience of the world around us is rich and multimodal, depending on
integrated input from multiple sensory modalities. In particular, spatial acoustic cues provide us with
a sense of the direction and distance of a sound source without needing visual confirmation, allow
us to estimate the properties of a surrounding environment, and are critical to subjective realism in
gaming and virtual simulations.

Recent progress in implicit neural representations has enabled the construction of continuous, dif-
ferentiable representations of the visual world directly from raw image observations [1, 2, 3, 4].
However, our perception of the physical world is informed not only by our visual observations, but
also by the spatial acoustic cues present in the environment. As a preliminary step in learning the
acoustic properties of scenes, we explore an implicit model that represents the underlying impulse
response of audio reverberations. As shown in Figure 1, our model can model the spatial propagation
of sound in a physical scene.

Past work has explored capturing the underlying acoustics of a scene [5, 6, 7]. These models,
however, require handcrafted parameterizations which, critically, prevent such approaches from being
applied to arbitrary scenes. In this work, we extend this approach by constructing an implicit neural
representation which captures, in a *generic manner*, the underlying acoustics of a scene.

Learning a representation of scene acoustics poses several challenges compared to the visual setting.
First, how do we generate plausible audio impulse responses at each emitter-listener position? While

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

(a)   (b)   (c)   (d)   (e)

Figure 1: Neural Acoustic Field (NAF) learns an implicit representation for acoustic propagation. **(a)** A 3D top-down view of the house with two rooms. **(b)-(e)** The loudness of acoustic field as predicted by our NAF is visualized for an emitter located at the red dot. Notice how sound does not leak through walls, and the portaling effect open doorways can have. Louder regions are shown in yellow.

we may represent the visual appearance of a scene with an underlying three-dimensional vector, an acoustic reverberation (represented as an impulse response) can consist of over 10,000 time-domain values and, thus, is significantly harder to capture. Second, how do we learn an acoustic neural representation that densely generalizes to novel emitter-listener locations? In the visual setting, ray-tracing can enforce view consistency across large portions of a visual scene (modulo occlusions). While in principle, in a similar manner, we may reflect acoustic "rays" in our scene to obtain an impulse response, an intractable number of rays are necessary to obtain the desired representation.

To address both challenges, we propose Neural Acoustic Fields (NAFs). To capture the complex signal representation of impulse responses in a compact and spatially continuous fashion, NAFs encode and represent an impulse-response in the Fourier frequency domain. Motivated by the strong influence of nearby geometry on anisotropic reflections [6], we propose to condition NAFs on local geometric information present at both the listener and emitter locations when decoding the impulse response. In our framework, local geometric information is learned directly from impulse responses. Such a decomposition facilitates the transfer of local information captured from training emitter-listener pairs to novel combinations of emitters and listeners.

We show that NAFs are able to outperform baselines in modeling scene acoustics, and provide detailed analysis of the design choices in NAFs. We further illustrate how the structure learned by NAFs can improve cross-modal generation of novel visual views of a scene. Finally, we illustrate how the learned representation of NAFs enable the downstream application of inferring scene structure.

2 Related Work

Audio Field Coding There is a rich history of encoding methods for 3D spatial audio. These approaches largely fall into two categories. The first approach encodes the sound field at a user-centric location by capturing the sound from spatially distributed sources [8, 9, 10, 11]. While they may leverage perceptual cues to create the sense of spatial audio, they do not allow the listener to freely traverse the scene and experience sound from different locations. The second approach aims to model the sound heard as a listener moves in a scene [5, 12, 6, 7, 13]. Since the complete acoustic field of a scene is computationally prohibitive to simulate in real time, and expensive to store in full fidelity, these methods have relied on a handcrafted encoding of the acoustic field, prioritizing efficiency above reproduction fidelity. Our work allows a listener to move and experience sounds that come from anywhere in a scene, and can represent the acoustic field continuously at high fidelity by directly learning from data.

Implicit representations Our approach towards modeling the underlying acoustics a scene relies on the use of a neural implicit representations. Implicit representations have emerged as a promising representation of 3D geometry [14, 15, 16, 17] and appearance [1, 2, 3, 4, 18] of a scene. Compared to traditional discrete representations, implicit representations are a continuous mapping capable of capturing data at an "infinite resolution". In [19] proposed a grid based representation for implicit scene reconstruction, while more recently [20] has adopted spatial conditioning for 3D image synthesis, where in both settings, the grid enables a higher-fidelity encoding of the scene. Our work also leverages local grids to model acoustics, but as an inductive bias and way to generalize to novel inputs.

Audio-Visual Learning Our work is also closely related to joint modeling of vision and audio. By leveraging the correspondence between vision and audio, work has been done to learn unsupervised video and audio representations [21, 22], localize objects that emit sound [23, 24], and jointly use vision and audio for navigation [25]. Recent work aims to propose plausible reverberations or sounds

Figure 2: Overview of our NAF architecture where listener and emitter share a feature grid. Given a listener position and an emitter location, we first query a grid for local features which are learned together with the network during training. We compute the sinusoidal embedding of the positions, frequency, and time, and query a discrete embedding matrix using the orientation and left/right ear. Our method predicts magnitude and phase.

from image input [26, 27], these approaches model the STFT using either convolution or implicit functions, which we also utilize. Different from them, our work leverages the geometric features learned by modeling acoustic fields to improve the learning of 3D view generation.

3 Methods

We are interested in learning a generic acoustic representation of an arbitrary scene, which can capture the underlying sound propagation of arbitrary sound sources across both seen and unseen locations in a scene. We first review relevant background information towards modeling environment reverberations. We then describe Neural Acoustic Fields (NAFs), a neural field which we show can capture, in a generic manner, the acoustics of arbitrary scenes. We further discuss how we can parameterize NAF so that it can capture acoustics property even at unseen sound sources and listener positions. Finally, we discuss the implementation details of our model illustrated in Figure 2.

3.1 Background on the Propagation of Sound

The sound emitted by a sound source undergoes decay, occlusion, and scattering due to both the geometric and material properties of a scene. For a fixed location pair $(\boldsymbol{q}, \boldsymbol{q}')$, we define the impulse-response at a listener position $\boldsymbol{q}$, as the sound pressure $p(t; \boldsymbol{q}, \boldsymbol{q}')$ induced by an impulse at $\boldsymbol{q}'$. Such behavior can be concisely and elegantly modeled utilizing the linear wave equation [28]:

$$\left[\frac{1}{c^2}\frac{\partial^2}{\partial t^2} - \nabla^2\right] p(t, \boldsymbol{q}, \boldsymbol{q}') = \delta(t)\delta(\boldsymbol{q} - \boldsymbol{q}'), \tag{1}$$

where c is the speed of sound, p is the sound pressure, $(\boldsymbol{q}, \boldsymbol{q}')$ being the listener and emitter location respectively, and δ the Dirac delta representing the forcing function, where we refer to sound pressure $p(t; \boldsymbol{q}, \boldsymbol{q}')$ as the impulse-response observed at listener position $\boldsymbol{q}$.

Given an accurate model of the impulse-response $p(t; \boldsymbol{q}, \boldsymbol{q}')$ described in Eqn (1), we may model audio reverberation of any sound waveform $s(t)$ emitted at $\boldsymbol{q}'$, by computing the response $r(t, \boldsymbol{q}, \boldsymbol{q}')$ at listener location $\boldsymbol{q}$ by querying the continuous field and using temporal convolution:

$$r(t; \boldsymbol{q}, \boldsymbol{q}') = s(t) \circledast p(t; \boldsymbol{q}, \boldsymbol{q}') \tag{2}$$

3.2 Neural Acoustic Fields

We are interested in constructing a continuous representation of the underlying acoustics of a scene, which may specify the reverberation patterns of an arbitrary sound source. The parameterization of an impulse-response introduced in Section 3.1 provides us with a method to model audio propagation when given an omnidirectional listener and emitter. To construct a model of a directional listener, we need to further model the 3D head orientation $\theta \in \mathbb{R}^2$, and ear $k \in \{0, 1\}$ (binary left or right) of a listener, in addition to the spatial position $\boldsymbol{q} \in \mathbb{R}^3$ of the listener and $\boldsymbol{q}' \in \mathbb{R}^3$ of the emitter.

We may then model the time domain impulse response $\boldsymbol{v}$ using a neural field Φ which takes as input the listener and emitter parameters:

$$\Phi : \mathbb{R}^8 \times \{0, 1\} \to \mathbb{R}^T; (\boldsymbol{q}, \theta, k, \boldsymbol{q}') \to \Phi(\boldsymbol{q}, \theta, k, \boldsymbol{q}') = \boldsymbol{v} \tag{3}$$

Directly outputting the impulse-response $\boldsymbol{v} \in \mathbb{R}^T$ magnitude in the time domain with a neural network is difficult due to its high dimensional (over 10,000 elements) and chaotic nature. A naïve

Figure 3: **Qualitative Visualization of Test Set Impulse Response Prediction.** **(a)** Ground truth log-magnitude. **(b)** Ground truth phase. **(c)** NAF predicted log-magnitude. **(d)** NAF predicted phase. **(e)** log-magnitude of an anechoic audio (without any reverberation). **(d)** The sound with a reverberation impulse response from our NAF. **(e)** The sound with the ground truth reverberation impulse response applied. Note phases are unwrapped for visualization purposes.

115 solution would be to further add t as an additional argument to our neural field, but we found that
116 such a solution worked poorly, due to the highly non-smooth representation of the waveform (see
117 supplementary). We instead encode the impulse-response utilizing a short-time Fourier transform
118 (STFT) denoted v_{STFT}, which we find to be significantly more amenable to neural network prediction
119 due to the smooth nature of the frequency space. In Figure 3 we show magnitude spectrograms for
120 ground truth impulse responses and those learned by our network. As v_{STFT} is a complex value, we
121 further factorize v_{STFT} into log-magnitude and phase components. For phase, we use the instantaneous
122 frequency (IF) representation proposed in [29]. Thus, our parameterization of NAF is a neural field
123 Ω that is trained to estimate the impulse response function ϕ, and outputs $[v_{\text{STFT\_mag}}, v_{\text{STFT\_IF}}]$ for a
124 given time and frequency coordinate:

$$\Omega : \mathbb{R}^{10} \times \{0, 1\} \to \mathbb{C}$$
$$(\boldsymbol{q}, \theta, k, \boldsymbol{q}', t, f) \to \Omega(\boldsymbol{q}, \theta, k, \boldsymbol{q}', t, f) \approx [\boldsymbol{v}_{\text{STFT\_mag}}(t, f), \boldsymbol{v}_{\text{STFT\_IF}}(t, f)] \quad (4)$$

125 We train our model using MSE loss between the generated and ground truth spectrograms v_{STFT}:

$$\mathcal{L}_{\text{NAF}} = \|\Omega(\boldsymbol{q}, \theta, k, \boldsymbol{q}', t, f)_{\text{mag}} - \boldsymbol{v}_{\text{STFT\_mag}}(t, f)\|^2 +$$
$$\alpha\|\Omega(\boldsymbol{q}, \theta, k, \boldsymbol{q}', t, f)_{\text{IF}} - \boldsymbol{v}_{\text{STFT\_IF}}(t, f)\|^2 \quad (5)$$

126 across spectrogram coordinates t and f. Where α is a scaling value used to balance the two losses.

3.3 Generalization through Local Geometric Conditioning

128 We are interested in parameterizing the underlying acoustic field, so that we may not only accurately
129 represent impulse-response at emitter-listener pairs we see during training, but also at novel combina-
130 tions of emitter and listener seen at test time. Such generalization may be problematic when directly
131 parameterizing NAFs utilizing a MLP with inputs specified in Eqn (4), as the network may learn to
132 directly overfit and entangle the relation between emitter and listener impulse-responses.

133 What generic information may we extract from a given impulse-response between an emitter and
134 listener? In principle, extracting the full dense geometric information in a scene would enable us
135 to robustly generalize to new emitter and listener locations. However, the amount of geometric
136 information available in a particular impulse-response, especially for positions far away from either
137 current emitter and listener is limited, since these positions have little impact on the underlying
138 impulse-response. In contrast, the local geometry near either emitter and listener positions will
139 have a strong influence in the impulse-response, as much of the anisotropic reflection comes from
140 such geometry [30]. Inspired by this observation, we aim to capture and utilize local geometric
141 information, near either emitter or listener locations, as a means to predict impulse-responses across
142 novel combinations.

143 To parameterize and represent these local geometric features, we learn a 2D grid of spatial latents
144 which we illustrate in Figure 2. When predicting an impulse-response at a given emitter and offset
145 position, we query the learned grid features at both emitter and listener positions, and provide it
146 as additional context into our NAF network Ω . Such features provide rich information on the
147 impulse-response, enabling NAF to generalize better to unseen combinations of both emitter and
148 listener locations. In the rest of this work, we refer to the NAFs with local geometric features as
149 Ω_{grid}. We learn grid latent features jointly with the underlying parameters of NAF. Additional details
150 can be found in the supplementary.

Figure 4: **Qualitative Visualization of Neural Acoustic Fields. (a)** Top down view of the rooms. **(b)** Results as inferred by our neural acooustic field. Loudness of a sound given a emitter location indicated in red, lighter color indicates louder sound. Note how openings and walls lead to portaling and occlusion of the sound.

Such a design choice, however, still requires us to consider how to further combine local geometric information captured separately from either listeners or emitters. A naïve implementation would be to maintain separate feature grids for both listener and emitter positions. Such an approach fails to account for the fact that the local geometric information captured by emitter may also inform the local geometric information around a listener. Examining Eqn (1), we note that it is in fact symmetric with respect to exchanging either listener or emitter positions [7], indicating that the impulse-response does not change when omnidirectional listener and emitters are swapped. Such a result means that we may in fact utilize the local geometric information captured near an emitter position interchangeably for either emitters and listeners. Thus, we propose our local geometric information as a single latent grid, which we show to outperform the naïve dual grid implementation.

4 Experiments

In this section, we demonstrate that our model can faithfully represent the acoustic impulse response at seen and unseen locations. Additional ablation studies verify the importance of utilizing local geometric features to enable test time generation fidelity. Next, we demonstrate that learning acoustic fields could facilitate improved visual representations when training images are sparse. Finally we show that the learned NAF can be used to infer scene structure.

4.1 Setup

For each scene, we holdout 10% of the RIRs randomly as a test set. Each scene is trained for 200 epochs, which takes around 6 hours for the largest scenes on four `Nvidia V100s`. In each batch, we sample 20 impulse responses, and randomly select $2,000$ frequency & time pairs within each spectrogram. An initial learning rate of 5×10^{-4} is used for the network and the grid features. We add a small amount of noise sampled from $\mathcal{N}(0, 0.1)$ to each coordinate during training to prevent degenerate solutions. For evaluating the learned acoustic fields, we use two different datasets:

Soundspaces. Soundspaces [25] is a synthetic dataset generated via ray-tracing, and is auralized with an ambisonic head-related transfer function (HRTF). This dataset consists of R_i probe points for each scene, with each probe capable of representing an emitter or listener location for up to R_i^2 emitter and listener pairs. The emitters are represented as omnidirectional, while the listener acts as a stereo receiver that can have one of four different orientations. The listeners and emitters are at fixed height. Our NAFs are trained on 6 representative scenes. Where 2 consist of multi-room layouts; 2 consist of a single room with a non-rectangular walls; and 2 consist of a single room with rectangular walls as in Figure 4.

MeshRIR. The MeshRIR dataset [31] is recorded from a real scene, and contains data collected from a cuboidal room. The listener locations are at fixed height. The emitters surround the listeners both above and below the listener plane.

4.2 Architecture Details

The Soundspaces dataset lacks the full parameterization of an acoustic field described in Equation 4, so we train NAF with a restricted parameterization that is available in the dataset. This allows for

| GT-nearest | NAFs | AAC-nearest | AAC-linear | Opus-nearest | Opus-linear |

Figure 5: **Comparison of the acoustic fields.** From left to right, we visualize the loudness maps generated by the full ground truth, our NAFs, and by AAC or Opus coding combined with linear and nearest neighbor interpolation on the training set. Emitter location shown in red. Our method can faithfully reproduce the loudness map present in the ground truth.

two degrees of freedom along the $x - y$ plane for the listener locations $q \in \mathbb{R}^2$ and the emitter location $q' \in \mathbb{R}^2$. The listener is binaural with $k \in \{0, 1\}$, and can assume four possible orientations $\theta \in \{0, 90, 180, 270\}$, while the emitter is omnidirectional. In particular, we utilize a parameterization of Ω_{grid} which maps an input tuple $[x, y, x', y', f, t] \times \{0, 90, 180, 270\} \times \{0, 1\}$ to two scalar values that represents the magnitude and phase for a given time and frequency in the STFT:

$$\Omega_{\text{grid}}(x, y, \theta, k, x', y', t, f) \Rightarrow [\boldsymbol{v}_{\text{STFT\_mag}}(t, f), \boldsymbol{v}_{\text{STFT\_IF}}(t, f)] \tag{6}$$

To encode the rotation θ, as there are only 4 possible discrete rotations in the dataset, we directly query into a learnable embedding matrix of shape $\mathbb{R}^{4 \times n}$, returning a $\mathbb{R}^{1 \times n}$ vector. Similarily, to encode the left and right ear k, we similarly query into a learnable embedding matrix of shape $\mathbb{R}^{2 \times n}$, returning a $\mathbb{R}^{1 \times n}$ vector. The f, t tuple representing the frequency and time respectively are scaled to $(-1, 1)$ and processed with sinusoidal encoding using 10 frequencies of $\sin$ and $\cos$. For MeshRIR, we set $q' \in \mathbb{R}^3$ to account for the emitters that can vary in height.

To obtain local geometric features for either an emitter or listener in a scene, we assume that our scene is contained within a set of pixels $\mathcal{P} = \{P_1...P_k\}$ which form a grid over the scene. For a given position tuple (x, y) as query location, we then interpolate the local features. Where $\mathcal{L}(\cdot)$ is the interpolation function. $(p_1^* \ldots p_k^*)$ are the set of all pixel that form the grid, and $\tilde{f}(\cdot)$ represents the features stored at a given pixel:

$$(x, y) \Rightarrow \mathcal{L}(x, y; \tilde{f}(p_1^*), \ldots \tilde{f}(p_k^*)) \tag{7}$$

$$= \sum_{i=1}^{k} w_i \tilde{f}(p_i^*) \tag{8}$$

w_i is determined by a Nadaraya-Watson estimator with a Gaussian weighting kernel applied to the distance between query and grid coordinates:

$$w_i = K((x, y), (x_i, y_i)) / \sum_{j=1}^{k} K((x, y), (x_j, y_j)) \tag{9}$$

$$K(\boldsymbol{x}, \boldsymbol{x}') = \exp(-\|\boldsymbol{x} - \boldsymbol{x}'\|_2^2 / 2\sigma^2) \tag{10}$$

Because this interpolation function is differentiable, we jointly learn the grid features during training. These queried features are combined with the coordinates processed with sinusoidal encoding using 10 frequencies of $\sin$ and $\cos$ functions. We process both the listener and emitter position tuples this way. We combine the grid based features with the sinusoidal embeddings and the discrete indexed embeddings as the input to our multilayer perceptron f_ϕ. Please refer to Figure 2 for a visualization of our model, and supplementary for further details. We compare using a shared local geometric feature with the emitter and listener, as well as using have the emitter and listener query their own individual grids.

4.3 Evaluation of Neural Acoustic Fields

We first validate that we can capture environmental acoustics at unseen emitter-listener positions.

Baselines. We compare our model against two widely used high performance audio coding methods: Advanced Audio Coding (AAC) and Xiph Opus. The bitrates are chosen to approach the storage costs for our NAF. For each method, we apply both linear and nearest neighbor interpolation to the

Model	Large 1 Spec.↓	Large 1 T60↓	Large 2 Spec.↓	Large 2 T60↓	Medium 1 Spec.↓	Medium 1 T60↓	Medium 2 Spec.↓	Medium 2 T60↓	Small 1 Spec.↓	Small 1 T60↓	Small 2 Spec.↓	Small 2 T60↓	MeshRIR Spec.↓	MeshRIR T60↓	Mean Spec.↓	Mean T60↓
AAC-nearest	1.913	9.996	1.989	13.31	2.111	6.148	2.122	6.051	2.296	9.798	2.509	5.809	1.057	4.740	1.999	7.979
AAC-linear	1.904	8.847	1.964	11.63	2.105	4.585	2.116	4.422	2.299	8.253	2.521	6.021	1.081	6.697	1.998	7.208
Opus-nearest	1.740	12.20	1.817	15.15	1.887	7.875	1.898	7.897	2.058	10.68	2.238	7.564	1.711	5.068	1.907	9.493
Opus-linear	1.780	11.30	1.827	13.55	1.922	6.710	1.934	6.917	2.097	9.116	2.284	6.981	1.743	5.768	1.941	8.621
DSP	1.106	14.62	1.170	13.68	1.064	10.24	1.067	9.732	1.079	12.77	1.097	11.03	N/A	N/A	1.097	12.01
NAF (Dual)	0.413	6.288	0.421	7.111	0.386	3.173	0.387	3.169	0.365	3.497	0.361	2.210	**0.403**	4.201	0.388	4.241
NAF (Shared)	**0.396**	**4.166**	**0.413**	**6.075**	**0.384**	**3.110**	**0.384**	**3.072**	**0.356**	**3.378**	**0.344**	**2.098**	**0.403**	**4.191**	**0.380**	**3.650**

Table 1: **Quantitative Results on Test Set Accuracy.** We report the spectral loss between generated and ground truth log spectrograms across methods, as well as the percentage (%) difference for the T60 reverberation time. The best method for each room is **bolded**. For the nearest and linear baselines, we perform interpolation in the time domain using samples from the training set. The DSP is not implemented for MeshRIR due to the lack of absolute room coordinates.

	Large Room 1						Large Room 2					
	PSNR ↑			SSIM ↑			PSNR ↑			SSIM ↑		
Training Images	75	100	150	75	100	150	75	100	150	75	100	150
NeRF	25.41	27.36	29.85	0.872	0.892	0.926	25.70	27.74	29.34	0.821	0.853	0.879
NeRF + NAF	**26.19**	**27.59**	**29.90**	**0.895**	**0.911**	**0.927**	**26.24**	**28.22**	**29.45**	**0.837**	**0.866**	**0.879**

Table 2: **Quantitative Results on Cross-Modal Image Learning.** Quantitative results on joint training of NeRF and NAF jointly conditioned on a single local grid. We use very sparse training images in highly complex scenes. When evaluated on 50 test images, we observe that cross-modal learning helps improve PSNR and SSIM when the visual training data is more sparse.

coded acoustic fields. Both linear and nearest neighbor approaches are widely used [32, 33, 34] in modeling of spatial audio. We implement the binaural DSP baseline described by [35], which uses the image source method and a KEMAR HRTF. We also assess the listener and emitter either sharing or using individual local geometric features in our NAFs.

Each method is provided with the same train-test split. We visualize the acoustic fields produced by different methods in Figure 5. For additional details of our baselines please see the appendix.

Metrics. We evaluate the results of our synthesis by measuring the spectral loss [36] between the generated and the ground truth log-spectrograms, as well as measuring the percentage error between the T60 reverberation time in the time domain. In this case, lower spectral loss and T60-error values indicates a better result. We also perform a human evaluation where subjects are presented with a two-alternative forced-choice task. Each trial requires selecting if the NAFs or the AAC-nearest auralized music samples best match with ground truth auralization.

Results. As shown in Table 1, our NAFs achieve significantly higher quality on the modeling of unseen impulse responses compared to strong interpolation baselines across all six scenes. Observing the qualitative results in Figure 4, we observe that NAFs can predict smoothly varying acoustic fields that are affected by the physical surroundings. Extending our model to MeshRIR which is captured from a real scene, we observe that our NAFs continue to perform better on both spectral and T60 metrics. Comparing our results against baselines in Figure 5 and Table 3, our

Method	Storage (MiB)
AAC	346.74
Opus	181.37
NAF (Shared)	8.41

Table 3: **Average space consumption across 6 Soundspaces scenes.**

methods are able to better approximate the ground truth at a fraction of the storage cost, and does not exhibit the sound energy leakage present in linear interpolation. The size of a spatial acoustic field is important for real life applications. In our human evaluation with 21 subjects who were asked to judge 10 test-time RIRs, 82.38% of responses indicates that our NAFs were higher quality compared to AAC-Nearest.

A comparison of using shared and dual local geometric features indicates that despite having fewer learnable parameters, we achieve better performance by sharing the local geometric features. Examples of individual impulse responses generated by our model are shown in Figure 3.

Generalization through Geometric Conditioning. We next assess the impact of utilizing local geometric conditioning as a means to generalize to novel combinations of emitter-listener positions. On the "Large 1" room, in Figure 7 we evaluate test set spectral er-

ror when NAF is trained with a limited percentage of the training data either with or without local geometric conditioning. We find that such geometric conditioning enables better test set reconstruction error, with the performance gap increasing with less data.

Figure 6: **Qualitative Visualization of Cross-Modal Image Learning.** Qualitative comparison between NeRF+NAFs with RGB and acoustic supervision, and NeRF learned with only RGB supervision. **(a)-(c)** Three views from "Large 1". **(d)-(f)** Three views from "Large 2".

Figure 7: **Local Geometric Conditioning.** Comparison of NAF with and without local geometric conditioning trained with different amounts of data.

4.4 Cross-modal learning

In this experiment, we explore the effect of jointly learning acoustics and visual information when we are given sparse visual information. Recall that our NAF includes a local geometric feature grid $\mathcal{P}$ that covers the entire scene. For our cross-modal learning experiment, we jointly learn this feature grid with a NeRF network modified to accept local features sampled from this grid along with the traditional sinusoidal embedding. In the acoustics branch, we query the grid using emitter and listener positions. In the NeRF branch, we use point samples along the ray projected on the grid plane to query the features. In both cases, the process is fully differentiable. We use a standard implementation of NeRF with a coarse and fine network.

In the NeRF only setting, we minimize color C reconstruction loss for a ray r over a batch of rays $\mathcal{R}$: $\mathcal{L}_{\text{RGB}} = \sum_{r \in \mathcal{R}} ||\hat{C}(r) - C(r)||_2^2$. In contrast, in the NAF + NeRF experiment, we jointly minimize $\mathcal{L}_{\text{RGB}} + \mathcal{L}_{\text{NAF}}$, where $\mathcal{L}_{\text{NAF}}$ is defined in equation 5. We utilize 64 coarse samples and 128 fine samples for each ray, and sample 1024 rays per batch.

Results. We train on the two large rooms in our training set. For each room $75, 100, 150$ images are used for training, while the same 50 images of novel views are used for all configurations during testing. In Table 2 we observe that training with acoustic information helps improve the PSNR and SSIM of the visual output. This effect is more significant when the training images are very sparse, the NAF network helps less when there is sufficient visual information. Qualitative results are shown in Figure 6, we see there is a reduction of floaters in free space.

4.5 Inferring scene structure

Given a reverberant sound, humans are able to build a mental representation of the surrounding room and make a judgement about the distance of nearby obstacles [37]. We investigate the intermediate representations constructed by our neural network in the process of learning an acoustic field, and examine if these representations can be used to decode the scene structure.

Setup. The intermediate representation of the NAF depends on both listener locations q and emitter location q', the rotation angle θ, the ear k, the time t and frequency f. For consistency, at a given location (x^*, y^*) in the scene, we extract the NAF latent by setting the emitter location $q'_i = (x^*, y^*)_i$. For the listener location, we iterate over five randomly selected points in the scene $q \in [q_1, \ldots, q_5]$, which we keep constant for all q'_i. The rotation angle is fixed to $\theta = 0$, and we compute the representation average over all possible (k, t, f), and concatenate latents for the selected q. For our NAFs, latents are extracted from the last layer prior to the output which includes 512 neurons. As a comparison to our learned representation, we extract Mel-frequency cepstral coefficients (MFCCs) from the ground truth impulse response provided by a nearest neighbor interpolator. We use a similar setup as above, for a given location we set this to be q'_i, and iterate over the same five listener locations $q_{1\ldots5}$. We average the MFCCs over the left and right ear, and concatenate for the selected q. After flattening, the MFCC features are approximately 500 dimensional for any given room.

Figure 8: **Visualization of scene structure decoding with a linear layer. Column 1:** The ground truth scene structure map, at each position we visualize the distance to the nearest wall. **2:** Linear decoding results using MFCC features. **3:** Linear decoding results using NAF features. **4:** TSNE applied to the NAF features.

	Explained variance						
Features	Large 1	Large 2	Medium 1	Medium 2	Small 1	Small 2	Mean
MFCC	0.501	0.458	0.614	0.642	0.820	0.723	0.626
NAF latents	**0.908**	**0.891**	**0.900**	**0.923**	**0.936**	**0.916**	**0.913**

Table 4: **Quantitative Results on scene structure decoding.** We measure the explained variance scores of the predicted wall distance against the ground truth wall distance at test time locations after linear decoding. NAF latents consistently achieve higher explained variance scores than MFCC features.

We fit a single linear layer to NAF and MFCC features respectively. For testing and visualization of the linear decoding results, we sample a regular grid of points with $0.1m$ distance between each point. For fitting the linear decoder, we randomly sample points within the scene such that the number of training points are 10% as many as the testing points. For each location in the scene, we extract the distance to the nearest wall as the decoding target.

Results. We visualize the results of our linear decoding in Figure 8. The intermediate representation of our NAFs reveals an underlying structure that is both smooth and semantically meaningful. In the multiroom scenes, the latent is well separated for each room. We are able to successfully decode the scene structure with a linear layer when using our NAFs, but decoding fails when using MFCC features. In Table 4, we show the amount of explained variance of our decoding results on the test set. Our learned features are able to consistently achieve much higher scores than those using MFCC features.

5   Discussion

Limitations and Future Work. Although our method achieves generalization and high quality representations of acoustic fields within a single scene, NAFs do not currently generalize to multiple scenes. Future work may explore generalization to novel scenes. One possible approaches may be to incorporate multi-modal inputs with the goal of synthesizing an acoustic field with few-shot visual or acoustic input.

Conclusion. In summary, this paper introduces Neural Acoustic Fields (NAFs), a compact, continuous, and differentiable acoustic representation which can represent the underlying reverberation of different audio sources in a scene. By conditioning NAFs locally on the underlying scene geometry, we demonstrate that our approach enables the prediction of plausible environmental reverberations even at unseen locations in the scene. Furthermore, we demonstrate that the acoustic representations learned through NAFs are powerful, and may be utilized to facilitate audio-visual cross-modal learning, as well as to infer the structure of scenes.

References

[1] Vincent Sitzmann, Michael Zollhöfer, and Gordon Wetzstein. Scene representation networks: Continuous 3d-structure-aware neural scene representations. In *Proc. NeurIPS 2019*, 2019. 1, 2

[2] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In *Proc. ECCV*, 2020. 1, 2

[3] Michael Niemeyer, Lars Mescheder, Michael Oechsle, and Andreas Geiger. Differentiable volumetric rendering: Learning implicit 3d representations without 3d supervision. In *Proc. CVPR*, 2020. 1, 2

[4] Lior Yariv, Yoni Kasten, Dror Moran, Meirav Galun, Matan Atzmon, Basri Ronen, and Yaron Lipman. Multiview neural surface reconstruction by disentangling geometry and appearance. *Proc. NeurIPS*, 2020. 1, 2

[5] Nikunj Raghuvanshi and John Snyder. Parametric wave field coding for precomputed sound propagation. *ACM Transactions on Graphics (TOG)*, 33(4):1–11, 2014. 1, 2

[6] Nikunj Raghuvanshi and John Snyder. Parametric directional coding for precomputed sound propagation. *ACM Transactions on Graphics (TOG)*, 37(4):1–14, 2018. 1, 2

[7] Chakravarty R Alla Chaitanya, Nikunj Raghuvanshi, Keith W Godin, Zechen Zhang, Derek Nowrouzezahrai, and John M Snyder. Directional sources and listeners in interactive sound propagation using reciprocal wave field coding. *ACM Transactions on Graphics (TOG)*, 39(4):44–1, 2020. 1, 2, 5

[8] Michael A Gerzon. Periphony: With-height sound reproduction. *Journal of the audio engineering society*, 21(1):2–10, 1973. 2

[9] Jeroen Breebaart, Jürgen Herre, Christof Faller, Jonas Rödén, Francois Myburg, Sascha Disch, Heiko Purnhagen, Gerard Hotho, Matthias Neusinger, C Kjörling, et al. Mpeg spatial audio coding/mpeg surround: Overview and current status. *Preprint 119th Conv. Aud. Eng. Soc.*, (CONF), 2005. 2

[10] Ville Pulkki. Spatial sound reproduction with directional audio coding. *Journal of the Audio Engineering Society*, 55(6):503–516, 2007. 2

[11] Alexander Richard, Dejan Markovic, Israel D Gebru, Steven Krenn, Gladstone Butler, Fernando de la Torre, and Yaser Sheikh. Neural synthesis of binaural speech from mono audio. In *International Conference on Learning Representations*, 2021. 2

[12] Ravish Mehra, Lakulish Antani, Sujeong Kim, and Dinesh Manocha. Source and listener directivity for interactive wave-based sound propagation. *IEEE transactions on visualization and computer graphics*, 20(4):495–503, 2014. 2

[13] Anton Ratnarajah, Shi-Xiong Zhang, Meng Yu, Zhenyu Tang, Dinesh Manocha, and Dong Yu. Fast-rir: Fast neural diffuse room impulse response generator. *arXiv preprint arXiv:2110.04057*, 2021. 2

[14] Michael Niemeyer, Lars Mescheder, Michael Oechsle, and Andreas Geiger. Occupancy flow: 4d reconstruction by learning particle dynamics. In *Proc. ICCV*, 2019. 2

[15] Zhiqin Chen and Hao Zhang. Learning implicit fields for generative shape modeling. In *Proc. CVPR*, pages 5939–5948, 2019. 2

[16] Jeong Joon Park, Peter Florence, Julian Straub, Richard Newcombe, and Steven Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *Proc. CVPR*, 2019. 2

[17] Shunsuke Saito, Zeng Huang, Ryota Natsume, Shigeo Morishima, Angjoo Kanazawa, and Hao Li. Pifu: Pixel-aligned implicit function for high-resolution clothed human digitization. In *Proc. ICCV*, pages 2304–2314, 2019. 2

[18] Qianqian Wang, Zhicheng Wang, Kyle Genova, Pratul P Srinivasan, Howard Zhou, Jonathan T Barron, Ricardo Martin-Brualla, Noah Snavely, and Thomas Funkhouser. Ibrnet: Learning multi-view image-based rendering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4690–4699, 2021. 2

[19] Chiyu Jiang, Avneesh Sud, Ameesh Makadia, Jingwei Huang, Matthias Nießner, and Thomas Funkhouser. Local implicit grid representations for 3d scenes. In *Proc. CVPR*, pages 6001–6010, 2020. 2

[20] Terrance DeVries, Miguel Angel Bautista, Nitish Srivastava, Graham W Taylor, and Joshua M Susskind. Unconstrained scene generation with locally conditioned radiance fields. *arXiv preprint arXiv:2104.00670*, 2021. 2

[21] Yusuf Aytar, Carl Vondrick, and Antonio Torralba. Soundnet: Learning sound representations from unlabeled video. *Advances in neural information processing systems*, 29:892–900, 2016. 2

[22] Relja Arandjelovic and Andrew Zisserman. Look, listen and learn. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 609–617, 2017. 2

[23] Arda Senocak, Tae-Hyun Oh, Junsik Kim, Ming-Hsuan Yang, and In So Kweon. Learning to localize sound source in visual scenes. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4358–4366, 2018. 2

[24] Hang Zhao, Chuang Gan, Andrew Rouditchenko, Carl Vondrick, Josh McDermott, and Antonio Torralba. The sound of pixels. In *Proceedings of the European conference on computer vision (ECCV)*, pages 570–586, 2018. 2

[25] Changan Chen, Unnat Jain, Carl Schissler, Sebastia Gari, Ziad Al-Halah, Vamsi Krishna Ithapu, Philip Robinson, and Kristen Grauman. Soundspaces: Audio-visual navigation in 3d environments. In *ECCV*, 2020. 2, 5

[26] Nikhil Singh, Jeff Mentch, Jerry Ng, Matthew Beveridge, and Iddo Drori. Image2reverb: Cross-model reverb impulse response synthesis. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, October 2021. 3

[27] Yilun Du, M. Katherine Collins, B. Joshua Tenenbaum, and Vincent Sitzmann. Learning signal-agnostic manifolds of neural fields. In *Advances in Neural Information Processing Systems*, 2021. 3

[28] Allan D Pierce. *Acoustics: an introduction to its physical principles and applications*. Springer, 2019. 3

[29] Jesse Engel, Kumar Krishna Agrawal, Shuo Chen, Ishaan Gulrajani, Chris Donahue, and Adam Roberts. Gansynth: Adversarial neural audio synthesis. *arXiv preprint arXiv:1902.08710*, 2019. 4

[30] Juhani Paasonen, Aleksandr Karapetyan, Jan Plogsties, and Ville Pulkki. Proximity of surfaces—acoustic and perceptual effects. *Journal of the Audio Engineering Society*, 65(12):997–1004, 2017. 4

[31] Shoichi Koyama, Tomoya Nishida, Keisuke Kimura, Takumi Abe, Natsuki Ueno, and Jesper Brunnström. Meshrir: A dataset of room impulse responses on meshed grid points for evaluating sound field analysis and synthesis methods. In *2021 IEEE Workshop on Applications of Signal Processing to Audio and Acoustics (WASPAA)*, pages 1–5. IEEE, 2021. 5

[32] Lauri Savioja, Jyri Huopaniemi, Tapio Lokki, and Ritta Väänänen. Creating interactive virtual acoustic environments. *Journal of the Audio Engineering Society*, 47(9):675–705, 1999. 7

[33] Nikunj Raghuvanshi, John Snyder, Ravish Mehra, Ming Lin, and Naga Govindaraju. Precomputed wave simulation for real-time sound propagation of dynamic sources in complex scenes. In *ACM SIGGRAPH 2010 papers*, pages 1–11. 2010. 7

[34] Christoph Pörschmann, Johannes M Arend, David Bau, and Tim Lübeck. Comparison of spherical harmonics and nearest-neighbor based interpolation of head-related transfer functions. In *Audio Engineering Society Conference: 2020 AES International Conference on Audio for Virtual and Augmented Reality*. Audio Engineering Society, 2020. 7

[35] Alexander Richard, Dejan Markovic, Israel D Gebru, Steven Krenn, Gladstone Alexander Butler, Fernando Torre, and Yaser Sheikh. Neural synthesis of binaural speech from mono audio. In *International Conference on Learning Representations*, 2020. 7

[36] Alexandre Défossez, Neil Zeghidour, Nicolas Usunier, Léon Bottou, and Francis Bach. Sing: Symbol-to-instrument neural generator. *arXiv preprint arXiv:1810.09785*, 2018. 7

[37] Andrew J Kolarik, Brian CJ Moore, Pavel Zahorik, Silvia Cirstea, and Shahina Pardhan. Auditory distance perception in humans: a review of cues, development, neuronal bases, and effects of sensory loss. *Attention, Perception, & Psychophysics*, 78(2):373–395, 2016. 8