Towards Self-Improvement of LLMs via MCTS: Leveraging Stepwise Knowledge with Curriculum Preference Learning

Abstract

Monte Carlo Tree Search (MCTS) has recently emerged as a powerful technique for enhancing the reasoning capabilities of LLMs. Techniques such as SFT or DPO have enabled LLMs to distill high-quality behaviors from MCTS, improving their reasoning performance. However, existing distillation methods underutilize the rich trajectory information generated by MCTS, limiting the potential for improvements in LLM reasoning. In this paper, we propose ALPHALLM-CPL, a novel pairwise training framework that enables LLMs to self-improve through MCTS behavior distillation. ALPHALLM-CPL efficiently leverages MCTS trajectories via two key innovations: (1) ALPHALLM-CPL constructs stepwise trajectory pairs from child nodes sharing the same parent in the search tree, providing step-level information for more effective MCTS behavior distillation. (2) ALPHALLM-CPL introduces curriculum preference learning, dynamically adjusting the training sequence of trajectory pairs in each offline training epoch to prioritize critical learning steps and mitigate overfitting. Experimental results on mathematical reasoning tasks demonstrate that ALPHALLM-CPL significantly outperforms previous MCTS behavior distillation methods, substantially boosting the reasoning capabilities of LLMs.

1 Introduction

Recent work has shown that large language models (LLMs), trained on trillions of tokens and comprising billions of parameters, exhibit extraordinary capabilities across a wide range of natural language processing tasks (Achiam et al., 2023; Touvron et al., 2023; Team et al., 2023). Nevertheless, they still face challenges in tasks requiring rigorous reasoning and planning, such as math-problem solving (Huang et al., 2023; Valmeekam et al., 2024). Although Chain-of-Thought (CoT) prompting (Wei et al., 2022; Kojima et al., 2022), which encourages LLMs to generate full reasoning steps before

arriving at an answer, has shown promising results, LLMs continue to struggle with problems requiring extended reasoning steps due to the limitations of auto-regressive decoding. Recent work suggests finetuning LLMs using either a substantial amount of high-quality, supervised data (Yu et al., 2023; Yuan et al., 2023; Li et al., 2024a; Mishra et al., 2022; Tong et al., 2024), guidance from a stronger LLM (e.g. GPT4) (Gou et al., 2023; Lee et al., 2023), or a combination of both (Luo et al., 2023; Yue et al., 2023). However, these approaches are constrained by the high cost of extensively querying stronger LLMs and the limited scope and quality of data that humans can provide.

In response to these challenges, the use of Monte Carlo Tree Search (MCTS) within LLMs has garnered increasing attention. By leveraging LLMs as the policy for MCTS in the language space, it becomes possible to generate high-quality data without querying stronger models or relying on human annotation. The high-value behaviors identified through MCTS are subsequently distilled into the LLM's policy via supervised fine-tuning (SFT) or direct preference optimization (DPO) (Rafailov et al., 2024), enabling self-improvement of the LLM. This methodology has demonstrated considerable potential in recent studies, significantly enhancing the reasoning capabilities of LLMs and proving effective in complex reasoning tasks.

However, existing MCTS distillation methods have notable limitations. In SFT-based distillation, only the best trajectory found by MCTS is typically used as training data, while other potentially useful data generated during the search is discarded (Tian et al., 2024; Zhang et al., 2024). Although DPO-based distillation leverages more trajectories as trajectory pairs, it still underutilizes the supervisory information provided by MCTS to optimize the training process (Xie et al., 2024a). As a result, LLMs fail to fully exploit the trajectories generated by MCTS, requiring multiple rounds of online

tree search to continually acquire new samples for improving model performance.

In this paper, we propose ALPHALLM-CPL, a pairwise offline training framework designed to enable LLMs to self-improve through MCTS behavior distillation. As illustrated in Figure 1, ALPHALLM-CPL consists of two key components: **(a) Trajectory Pair Extraction.** After MCTS generates multiple trajectories for a given prompt, we form complete trajectory pairs based on their respective trajectory values. Additionally, we extract stepwise trajectory pairs by selecting child nodes from the same root node in the search tree. These stepwise trajectory pairs provide step-level information that enhances MCTS behavior distillation. Our experiments show that incorporating stepwise trajectory pairs not only stabilizes the preference learning process but also significantly improves LLM performance compared to using only complete trajectory pairs. **(b) Curriculum Preference Learning.** We construct a replay buffer of the extracted trajectory pairs. At each offline training epoch, we dynamically adjust the sequence of trajectory pairs in this replay buffer, prioritizing those more critical to the LLM's learning. The adjustment is based on the preference reward gap provided by MCTS reward model and policy prediction gap provided by LLM policy itself. Compared to a random sampling of trajectory pairs for preference learning, curriculum preference learning consistently improves the LLM's reasoning capabilities across multiple offline training epochs. Together, these two components enable ALPHALLM-CPL to more efficiently utilize the trajectories generated by MCTS, allowing the LLM policy to comprehensively distill and learn from MCTS behavior.

We conduct experiments on two mathematical reasoning tasks, GSM8K and MATH. For the GSM8K benchmark, we select LLaMA2-7B and Mistral-7B as our base models. For the more challenging MATH benchmark, we use the stronger LLaMA3-8B-Instruct as the base model. After applying ALPHALLM-CPL, the performance of LLaMA2-7B and Mistral-7B on GSM8K improve from 14.6 and 38.5 to 36.5 and 57.3, representing gains of **150%** and **48.8%**, respectively. On the more difficult MATH benchmark, ALPHALLM-CPL increases the performance of LLaMA3-8B-Instruct from 28.2 to 33.1, achieving a **17.4%** improvement. Additionally, ALPHALLM-CPL demonstrates a clear advantage over other MCTS behavior distillation methods (Tian et al., 2024; Xie et al., 2024a) in terms of performance.

2 Preliminaries

2.1 Problem Formulation

Formally, given a query $q = [q^1, \ldots, q^n]$, which is typically referred to as prompt, a LLM denoted as policy π_θ is adopted to generate the response $y = [y^1, \ldots, y^m]$. The policy π_θ operates in an autoregressive manner, where each token is generated sequentially, relying solely on the context provided by the previously generated tokens. The policy, therefore, constitutes a Markov process in which the conditional probability distribution $\pi_\theta(y|q)$ can be decomposed and expressed with the chain rule:

$$\pi_\theta(y|q) = \prod_{i=1}^{m} \pi_\theta(y^i|q, y^{<i}; \theta) \qquad (1)$$

This can be formulated as a Markov Decision Process (MDP) problem, with elements $(\mathcal{S}, \mathcal{A}, T, R, \gamma)$. In this structure, the state $s^t \in \mathcal{S}$ represents the current context information in the trajectory, which is the concatenation of q and $y^{<t}$. The action $y^t \in \mathcal{A}$ corresponds to a single token selected from the vocabulary, resulting in a transition to a new state by appending s^t and y^t, and receiving a reward $r_t = R(s^t, y^t)$. This MDP framework sets the stage for applying Reinforcement Learning (RL) methods to optimize the policy π_θ aiming to maximize the expected cumulative reward. Based on these setups, we describe the self-improving problem. Given an LLM π_θ and an initial dataset D_0, which consists of limited expert-generated prompt-response (q, y) pairs, the goal of self-improving is to refine π_θ to maximize the reward. The refinement process includes learning from synthesized prompts and corresponding responses, where the responses are obtained using Monte Carlo Tree Search.

2.2 Monte Carlo Tree Search (MCTS)

MCTS is a sampling-based search algorithm for policy optimization in decision-making problems. It would iteratively build a search tree, by repeating four phases: selection, expansion, evaluation, and back-propagation. In the selection phase, it would recursively select the children from the root node by Upper Confidence Bound (UCB) bandit (Auer et al., 2002), which is

$$UCB(i) = w_i + C \times \sqrt{2 \times \ln \frac{N_i}{n_i}} \qquad (2)$$

Figure 1: ALPHALLM-CPL loop: We first performs MCTS over each input prompt q before extracting stepwise trajectory pairs, and then construct all extracted trajectory pairs into an offline replay buffer. We propose curriculum preference learning to continuously update the weight of each trajectory pair in the replay buffer during each offline training epoch and update the LLM.

where n_i and N_i are the visit counts for the node i and its parent respectively, C represents a hyperparameter balancing exploration and exploitation, and the w_i is the average value of all descendant nodes of i. Following selection, the tree undergoes expansion according to the defined policy in the expansion phase. Then in the evaluation phase, the value of the newly expanded node is estimated, by sampling or model-based methods. Finally, in the back-propagation phase, the estimated value is back-propagated to all ancestor nodes of the newly expanded node.

2.3 Direct Performance Optimization (DPO)

As an off-policy preference learning algorithm, DPO directly takes pair-wise preference data to tune the policy model π_θ (instead of training a reward model using such data) with an optimization objective equivalent to bandit PPO (Schulman et al., 2017). Particularly, given an input prompt q, and a preference data pair (y_w, y_l), the optimization objective is formulated as:

$$\mathcal{L}_{DPO} = -\mathbb{E}_{(q,y_w,y_l)\sim D} \log \sigma \big($$
$$\beta \log \frac{\pi_\theta(y_w|q)}{\pi_{ref}(y_w|q)} - \beta \log \frac{\pi_\theta(y_l|q)}{\pi_{ref}(y_l|q)} \big) \quad (3)$$

where D is the pair-wise preference dataset. DPO enlarges the gap between the probability of the preferred output $\pi_\theta(y_w|q)$ and that of the loss one $\pi_\theta(y_l|q)$ compared to the reference policy π_{ref}. In this way, the policy can learn to better distinguish good responses from bad ones.

3 AlphaLLM-CPL

In this section, we will introduce our proposed method AlphaLLM-CPL. AlphaLLM-CPL builds upon the previous self-improvement work, AlphaLLM (Tian et al., 2024), and consists of two key components: trajectory pair extraction and LLM self-improvement using curriculum preference learning. We will first explain how to generate and construct trajectory pairs for preference learning in Sec 3.1, followed by an introduction to our novel offline preference learning approach, curriculum preference learning, in Sec 3.2. The pseudocode of AlphaLLM-CPL is provided in Algorithm 1.

3.1 Trajectory Pair Extraction

Executing MCTS on Synthetic Queries The first step of data generation is performing Monte-Carlo Tree Search for each input query q that is synthesized from the initial dataset D_0. There have been various strategies, such as Self-instruct (Wang et al., 2023b) and Evol-instruct (Luo et al., 2023). In this work, we adopt a method similar to that described in Yu et al. (2023).

We follow the MCTS setup in Tian et al. (2024) except that the search process is only guided by the value network due to computation budget limitation. In particular, MCTS performs the following operations iteratively:

- **Selection** Starting from the root node, it iteratively selects the child node based on Eq 2.

- **Expansion** Once an expandable leaf node is selected, a new node is generated by starting with the previous state of the parent node as the initial option state. The option is then sampled using the policy π_θ, and its completion is determined by a termination function.

- **Backpropagation** The average value of the newly generated node and all its ancestors is updated using the scaled reward from the evaluation step. Meanwhile, the visit counts for these nodes also increase by one.

Algorithm 1: AlphaLLM-CPL

Input Initial dataset $\mathcal{D}^0 = \{(\boldsymbol{x}_i^0, \boldsymbol{y}_i^0) \mid i \in [N]\}$, policy model π_θ^0, AlphaLLM-pretrained reward model R, number of
    offline training loop K, trajectory value gap margin τ
Generate synthetic prompts $[\hat{\boldsymbol{x}}] = \text{SYN}(\pi_\theta^0, \mathcal{D}^0)$
Collect trajectories with search algorithm, *e.g.,* MCTS guided by R. $[\hat{\boldsymbol{y}}] = \text{MCTS}(\pi_\theta^0, [\hat{\boldsymbol{x}}])$
Construct trajectory pair replay buffer $\hat{\mathcal{D}} = \{(\hat{\boldsymbol{x}}, \hat{\boldsymbol{y}}^w, \hat{\boldsymbol{y}}^l)\}$ with trajectory value gap margin τ
Policy model $\pi = \pi_\theta^0$
for $k \leftarrow 1, \dots, K$ **do**
    Sorted preference pair replay buffer $\hat{\mathcal{D}}_S = []$
    Compute preference reward gap r_g of each trajectory pair in $\hat{\mathcal{D}}$ using R
    Compute policy prediction gap p_g of each trajectory pair in $\hat{\mathcal{D}}$ using π
    for $\hat{x}^i$ *in* $[\hat{\boldsymbol{x}}]$ **do**
        Select all trajectory pairs in $\hat{\mathcal{D}}$ that synthetic prompt is $\hat{x}^i$:
        $\hat{\mathcal{D}}^i = \{(\hat{x}^i, \hat{\boldsymbol{y}}_1^w, \hat{\boldsymbol{y}}_1^l), (\hat{x}^i, \hat{\boldsymbol{y}}_2^w, \hat{\boldsymbol{y}}_2^l), ..., (\hat{x}^i, \hat{\boldsymbol{y}}_n^w, \hat{\boldsymbol{y}}_n^l)\}$
        Sort trajectory pairs in $\hat{\mathcal{D}}^i$ according to Eq.(to be defined)
    end
    while *any $\hat{\mathcal{D}}^i$ is not empty* **do**
        forall $\hat{\mathcal{D}}^i$ **do**
            if *$\hat{\mathcal{D}}^i$ is not empty* **then**
                Remove the first trajectory pair from $\hat{\mathcal{D}}^i$
                Append the removed trajectory pair to $\hat{\mathcal{D}}_S$
            end
        end
    end
    Update policy parameter $\pi_\theta^k = \arg\min_\theta L(\pi_\theta^{k-1}, \hat{\mathcal{D}}_S)$
    Policy model $\pi = \pi_\theta^k$
end

Extracting Stepwise Trajectory Pairs from MCTS Performing MCTS over query q yields a search tree T_q. The next step is to extract representative data pairs that distinguish good reasoning steps from bad ones. One intuitive way is to extract all pairs of child nodes from T_q, where one yields the correct answer while the other yields the wrong one. However, this method may prune out many representative pairs since numerous tree nodes may not have the opportunity to roll out to the final answer. Moreover, an intermediate tree node may yield either a correct or incorrect answer due to the randomness inherent in LLM sampling.

We propose to continue using the value network used by MCTS to select child nodes to form pairs for stepwise comparison. This is because both recent research (Wang et al., 2024a) and our findings show that the trajectory-values are well-calibrated and effectively reflect the quality of deductions that have been made. Particularly, as shown in Figure 1, we empirically set a minimum margin τ of the trajectory-value gap, and any pairs of child nodes with a value gap larger than τ are extracted.

In addition to the stepwise comparison data, we also extract all pairs of complete trajectories based on the same margin τ for the trajectory-value gap. In this case, the two trajectories inside a pair may not share a common prefix.

3.2 Curriculum Preference Learning

After obtaining trajectory pairs, we consider all trajectory pairs as an offline trajectory pair buffer. To more effectively utilize the supervision information provided by MCTS and motivated by previous prioritized experience replay (PER) works in reinforcement learning (Schaul, 2015; Katharopoulos and Fleuret, 2018; Wang et al., 2023a), we propose Curriculum Preference Learning (CPL), an offline training method that performs preference learning by continually updating the order of trajectory pairs to select pairs that are more important for policy learning. We rank the trajectory pairs in the offline buffer based on specific metrics in each offline training epoch, prioritizing training on the more significant pairs. Our metric consists of two components: a static part, the preference reward gap, which remains constant across different offline training epochs, and a dynamic part, the policy prediction gap, which evolves as the policy is updated.

Preference reward gap The preference reward gap is calculated as shown in Eq 4. We leverage the reward model obtained during the pretraining phase to compute the reward for each step in the

positive and negative trajectories within a trajectory pair. Then, we calculate the total reward for each trajectory, and the difference between the total rewards of the positive and negative trajectories is used as the ranking weight for each trajectory pair. Since the reward model remains unchanged during the offline training process, the reward gap for each trajectory pair also remains constant with increasing training epochs. The preference reward gap allows the policy to learn the trajectory pairs in the buffer from easy to difficult in each training epoch, improving learning efficiency through a curriculum learning way.

$$r_g(q, y_w, y_l) = \sum_{t=1}^{T_w} R(y_{w,t}, q) - \sum_{t=1}^{T_l} R(y_{l,t}, q) \tag{4}$$

Policy prediction gap   Policy prediction gap is a policy-related metric that aims to fine-tune the trajectory pair order in each offline training epoch. We first calculate the log-likelihood of the positive and negative trajectories in each trajectory pair under the current policy's prediction (Eq 5), then compute the difference between them as a metric to rank all preference pairs (Eq 6). The trajectory pair with large policy prediction gap means it can provide stronger guidance for policy learning. The more distinct the difference between the positive and negative trajectories, the clearer the feedback signal the model can obtain from these samples, allowing it to update parameters more quickly. This enables the model to better learn the distinguishing features between the positive and negative trajectories, thereby improving its performance. Moreover, as the policy continuously updates, the policy prediction gap for each trajectory pair changes after every offline training epoch. Therefore, this metric dynamically updates the trajectory pair order in the offline trajectory pair buffer, helping the policy converge more efficiently.

$$\log P(y \mid q; \theta) = \sum_{t=1}^{T} \log P(y_t \mid q, y_{<t}; \theta) \tag{5}$$

$$p_g(q, y_w, y_l) = \log \frac{P(y_w \mid q; \theta)}{P(y_l \mid q; \theta)} \tag{6}$$

In the practical implementation, since the scales of the preference reward gap and policy prediction gap are different, we first normalize both the preference reward gap and policy prediction gap to the (0,1) range before adding them together. Thus, the final metric for CPL is the combination of preference reward gap and policy prediction gap with a balance rate α:

$$w_g(q, y_w, y_l) = r_g(q, y_w, y_l) + \alpha * p_g(q, y_w, y_l) \tag{7}$$

Prompt-level ranking   To prevent the training process from overly focusing on a fixed prompt—where all trajectory pairs of a specific prompt are prioritized for training, leading to potential overfitting—we employ a prompt-level ranking approach to sort and train the preference pairs. After obtaining the weight coefficients for each trajectory pair, we first internally rank all preference pairs within the same prompt based on these weight coefficients. Then, we select the highest-priority trajectory pair from each prompt, traverse all prompts, and subsequently choose the second-highest priority trajectory pair from each prompt. This process continues iteratively until all response pairs are traversed, and the training follows this sequence in the DPO process.

4   Experiments

4.1   Benchmark Evaluation

Datasets   ALPHALLM-CPL is generally applicable to a wide spectrum of reasoning tasks. As an early exploration, here we conduct experiments on mathematical reasoning problems where the learning signals are clear to define i.e., , final answer is correct or wrong. We choose to evaluate on two widely used datasets GSM8K (Cobbe et al., 2021) and MATH (Hendrycks et al., 2021). For GSM8K, we utilize prompts from MetaMath (Yu et al., 2023) for extracting pairs based on MCTS. The whole test set of GSM8K is used for evaluation and all training data is taken to train the value network for guiding MCTS. For MATH, we use their whole training set to generate preference pairs for preference learning. Due to computation constraints, we utilize a subset following the same procedure of Lightman et al. (2023) for MATH evaluation.

Baselines   We select three strong open-source LLMs as baselines for our experiments: **LLaMA2-7B** and **Mistral-7B** on GSM8K, and **LLaMA3-8B-instruct** on MATH. Following the steps of AlphaLLM, we conduct MCTS on GSM8K and MATH using the corresponding LLMs, and performed SFTwith the highest value trajectory found through MCTS, resulting in three checkpoints. The three different checkpoints obtained from SFT are

Model	#Stepwise	#Annotation	#SYN	GSM8K
LLaMA-2 7B	–	0	0	14.6
+ AlphaLLM	✗	7.5k	8.6k	26.5
+ AlphaLLM-Q	✓	7.5k	8.6k	31.7
+ AlphaLLM-CO	✗	7.5k	8.6k	29.7
+ AlphaLLM-PL-Shuffle (epoch 1)	✓	7.5k	8.6k	32.4
+ AlphaLLM-PL-Shuffle (epoch 2)	✓	7.5k	8.6k	32.1
+ ALPHALLM-CPL (epoch 1)	✓	7.5k	8.6k	34.3
+ ALPHALLM-CPL (epoch 2)	✓	7.5k	8.6k	36.5
Mistral 7B	–	0	0	38.5
+ AlphaLLM	✗	7.5k	10k	46.7
+ AlphaLLM-Q	✓	7.5k	10k	53.9
+ AlphaLLM-CO	✗	7.5k	10k	52.3
+ AlphaLLM-PL-Shuffle (epoch 1)	✓	7.5k	10k	54.8
+ AlphaLLM-PL-Shuffle (epoch 2)	✓	7.5k	10k	53.6
+ ALPHALLM-CPL (epoch 1)	✓	7.5k	10k	55.8
+ ALPHALLM-CPL (epoch 2)	✓	7.5k	10k	57.3

Model	#Stepwise	#Annotation	#SYN	MATH
Llama3 8B-instruct	–	0	–	28.2
+ AlphaLLM	✗	7.5k	0	31.0
+ AlphaLLM-Q	✓	7.5k	0	31.4
+ AlphaLLM-CO	✗	7.5k	0	31.6
+ AlphaLLM-PL-Shuffle (epoch 1)	✓	7.5k	0	32.2
+ AlphaLLM-PL-Shuffle (epoch 2)	✓	7.5k	0	31.7
+ ALPHALLM-CPL (epoch 1)	✓	7.5k	0	32.6
+ ALPHALLM-CPL (epoch 2)	✓	7.5k	0	33.1

Table 1: Comparison results of ALPHALLM-CPL on the GSM8K and MATH datasets, utilizing LLaMA2-7B and Mistral-7B as base models for GSM8K and LLaMA3-8B-instruct for MATH, respectively. #Stepwise indicates whether stepwise information provided by MCTS is utilized during the training process. #Annotation indicates the quantity of labeled data employed during model development, including training the value networks of MCTS and finetuning the base models. #SYN represents the number of synthetic prompts used for model training, where trajectories are generated using MCTS.

referred to as **AlphaLLM**, which serve as the starting checkpoints for the following preference learning. In the preference learning phase, we used DPO as the objective function and compared three baselines: (1) **AlphaLLM-CO** (Complete Only): This baseline performs DPO using only the complete trajectory pairs obtained from the MCTS search. (2) **AlphaLLM-PL-shuffle**: This method uses both complete trajectory pairs and stepwise trajectory pairs for preference learning, but the training order is randomized. (3) **AlphaLLM-Q**: This approach is proposed by Xie et al. (2024a) which selects steps with the highest and lowest Q values as positive and negative samples at each tree depth, forming preference pairs for DPO. For all methods, we save a checkpoint every 200 training steps

and report the performance of the best one. All experiments are conducted on 8×A6000 GPUs.

Experiment Results (1) ALPHALLM-CPL can significantly boost reasoning ability of LLMs on math tasks. As shown in Table 1, compared to the three LLM baselines (LLaMA2, Mistral, and LLaMA3-instruct), our method achieves significant performance improvement. The baseline models without any preference learning generally have the lowest performance, with LLAMA2 achieving a GSM8K score of 14.6, Mistral achieving 38.5, and LLAMA3-instruct reaching 28.2 on MATH. After applying all preference learning methods, ALPHALLM-CPL achieves the highest performance, with LLAMA-2 7B reaching 36.5 on GSM8K (**150%** improvement), Mistral 7B achiev-

ing 57.3 (**48.8%** improvement), and LLAMA3-instruct scoring 33.1 on MATH (**17.4%** improvement). This suggests that by organizing the learning process more effectively, ALPHALLM-CPL can significantly enhance the reasoning ability of LLMs. **(2) Both components of ALPHALLM-CPL are crucial for enhancing the reasoning ability of LLMs.** Compared to the other three preference learning baselines, our method demonstrates a significant advantage across the two benchmarks. First, after incorporating stepwise trajectory pairs into the training dataset, the performance of AlphaLLM-PL-Shuffle shows a marked improvement over both AlphaLLM-CO and AlphaLLM-Q, highlighting the importance of utilizing the stepwise information provided by stepwise trajectory pairs. Moreover, after applying CPL for offline training on top of AlphaLLM-PL-Shuffle, the performance of the LLM is further enhanced (by 12.6%, 4.5%, and 2.8% across two different benchmarks on three base models). The experimental comparison with the other three baselines clearly demonstrates that both components of our proposed method are crucial for the final model's performance improvement. **(3) ALPHALLM-CPL can continue to improve model performance even after multi-epoch offline training.** We conduct two epochs of offline training on both AlphaLLM-PL-Shuffle and ALPHALLM-CPL without changing any training data. It can be observed that AlphaLLM-PL-Shuffle overfits during the second epoch, resulting in a performance decline, whereas CPL, due to its ability to dynamically adjust the training order and prioritize better trajectory pairs, continues to improve performance in the second epoch. This further demonstrates the importance of the training order of trajectory pairs and the effectiveness of our proposed method.

4.2 Impact of Stepwise Trajectory Pairs

In the Sec 4.1, we experimentally demonstrate the importance of stepwise trajectory pairs in improving LLM performance. In this section, we will further explore the impact of the quantity of stepwise trajectory pairs on performance enhancement and the preference learning process. We choose Mistral-7B as the base model and conduct experiments on GSM8K using Mistral-7B after AlphaLLM SFT. We set the trajectory value gap margin τ between positive and negative trajectories to 1 for constructing trajectory pairs. Under this setting, we obtain a total of 59K complete trajectory pairs and 47K

Figure 2: The accuracy curve of the Mistral-7B under different stepwise trajectory pairs as the DPO training steps progress on GSM8K. The starting checkpoint is the Mistral-7B model after AlphaLLM SFT. We can observe that a larger number of stepwise trajectory pairs leads to better performance and a more stable training process.

stepwise trajectory pairs. To avoid the influence of CPL on the experimental results, we only used DPO for preference learning.

We conduct a total of four experiments: **DPO_comp_only_59k**, which uses only the complete trajectory pairs; **DPO_both_stepwise_10k** and **DPO_both_stepwise_30k**, where 10k and 30k stepwise trajectory pairs are randomly sampled from the 47k stepwise trajectory pairs and mixed with the complete trajectory pairs; and **DPO_both_stepwise_47k**, which uses all 47k stepwise trajectory pairs mixed with the complete trajectory pairs for DPO.

In Figure 2, we present the training curves showing how LLM performance changes with increasing training steps under each setting. From the experimental results, it is evident that when only complete trajectory pairs are used, not only is the performance improvement of the LLM insignificant, but the preference learning process is also highly unstable. The ACC on GSM8K fluctuates significantly, and there is a noticeable decline in performance in the later stages of training. In contrast, as the number of stepwise trajectory pairs increases, we observe that the preference learning process becomes progressively more stable, and the performance of the LLM improves significantly. This experiment further demonstrates the importance of utilizing the stepwise information from stepwise trajectory pairs.

4.3 Ablation Study

In this section, we conduct an ablation study to investigate the effect of the balance rate between the preference reward gap (r_g) and policy prediction gap (p_g) on the performance of ALPHALLM-CPL. We still choose Mistral-7B as the base model and

Figure 3: Ablation study on balance rate and CPL metric. We can observe that the trajectory reward gap needs to play a dominant role in the metric to achieve the best performance.

conduct experiment on GSM8K. We report the results of using only r_g as the metric, only p_g as the metric, as well as five different balance rates ranging from 0.1 to 1. All training is conducted for 2 epochs, and we report the best-performing checkpoint from epoch 2. The experimental results are shown in Figure 3.

Based on the results, when using only one metric, the performance with r_g is better than with p_g. We believe this is because the value network provides more accurate supervisory information. As we gradually increase the weight of p_g in the overall metric (i.e., the balance rate), the performance of ALPHALLM-CPL also improves, reaching its peak at 0.5 with 57.3. After that, ALPHALLM-CPL gradually declines back to the level of using only r_g. This experiment indicates that with a reasonable balance, p_g can effectively improve ALPHALLM-CPL performance by providing dynamic information for adjusting trajectory pairs. However, since the value network obtained through LLM self-training is more accurate, r_g should still play the dominant role in determining the training order to achieve better performance.

5   Related works

As the key to the success of scalable oversight (Bowman et al., 2022), self-improving for LLM aims to align the LLM to human preference and values mainly using the supervision from its internal knowledge (Yuan et al., 2024; Pang et al., 2024; Wang et al., 2024b; Wu et al., 2024). The most crucial part of self-improving is the critiquing signal for selecting high quality LLM responses given input queries for further model training. Initial work (Bai et al., 2022; Wang et al., 2023b) relies on a few hand-crafted principles or heuristic rules to filter out low-quality or redundant data. Since it is non-trivial to reach broad coverage over different

tasks, these efforts only showcase on a specific aspect, such as safety or instruction following. Later work (Sun et al., 2024; Li et al., 2024b; Guo et al., 2024; Lai et al., 2024) composes limited number (usually hundreds) of examples, then representative in-context examples are selected to combine with general principles in order to provide more detailed background information to LLM. They hope LLM can automatically designate selected in-context examples into each data point to better guide data filtering. However, this requires the LLM to have strong abilities to apply these principles for each specific case and make correct judgments.

Recent efforts (Feng et al., 2023; Tian et al., 2024; Chen et al., 2024; Xie et al., 2024b; Zhang et al., 2024) propose MCTS-based self-improvement, taking the outputs from MCTS to train the policy. This is because MCTS can effectively find outputs that are a lot more accurate than vanilla outputs from the same policy model. In terms of self-improvement methods, these efforts typically rely on either basic rejection sampling (Feng et al., 2023; Tian et al., 2024; Zhang et al., 2024) or offline preference-learning (Chen et al., 2024; Xie et al., 2024b) algorithms, such as DPO (Rafailov et al., 2024). Different from previous work, we propose to a more comprehensive training framework: it takes rejection sampling and curriculum preference learning to fully exploit the knowledge provided by MCTS. We also conduct comprehensive ablation to pinpoint the essential information within MCTS for the success of self-improving, shedding some light on the future of self-improving from search.

6   Conclusion

We propose ALPHALLM-CPL, a novel pairwise training framework designed for the self-improvement of LLMs through MCTS behavior distillation. By constructing stepwise trajectory pairs from intermediate nodes in the tree search and employing our proposed curriculum preference learning to dynamically adjust the training order of trajectory pairs, we more effectively leverage the supervisory information provided by MCTS, leading to improved MCTS behavior distillation. Experiments on mathematical reasoning tasks demonstrate that our approach not only significantly enhances the reasoning capabilities of LLMs but also offers clear advantages over previous MCTS behavior distillation methods.

Limitation

One limitation of our work is that ALPHALLM-CPL is an offline learning framework. While it is applicable to any online multi-iteration learning approach, we do not conduct experiments in this direction due to computational resource constraints. We believe that combining our method with online learning and continuing training on new generated data would further enhance the reasoning ability of the LLMs. We will focus on addressing this aspect through detailed experimentation in future work.

Moreover, despite the notable performance improvement achieved by our method, the theoretical explanation of MCTS distillation remains underdeveloped. This limitation is also observed in other papers on MCTS distillation (Tian et al., 2024; Zhang et al., 2024; Chen et al., 2024). In future work, we aim to provide a more comprehensive theoretical analysis of MCTS distillation.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. 2002. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47:235–256.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. 2022. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*.

Samuel R Bowman, Jeeyoon Hyun, Ethan Perez, Edwin Chen, Craig Pettit, Scott Heiner, Kamilė Lukošiūtė, Amanda Askell, Andy Jones, Anna Chen, et al. 2022. Measuring progress on scalable oversight for large language models. *arXiv preprint arXiv:2211.03540*.

Guoxin Chen, Minpeng Liao, Chengxi Li, and Kai Fan. 2024. Step-level value preference optimization for mathematical reasoning. *arXiv preprint arXiv:2406.10858*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Xidong Feng, Ziyu Wan, Muning Wen, Ying Wen, Weinan Zhang, and Jun Wang. 2023. Alphazero-like tree-search can guide large language model decoding and training. *arXiv preprint arXiv:2309.17179*.

Zhibin Gou, Zhihong Shao, Yeyun Gong, Yujiu Yang, Minlie Huang, Nan Duan, Weizhu Chen, et al. 2023. Tora: A tool-integrated reasoning agent for mathematical problem solving. *arXiv preprint arXiv:2309.17452*.

Hongyi Guo, Yuanshun Yao, Wei Shen, Jiaheng Wei, Xiaoying Zhang, Zhaoran Wang, and Yang Liu. 2024. Human-instruction-free llm self-alignment with limited samples. *arXiv preprint arXiv:2401.06785*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the math dataset. *Sort*, 2(4):0–6.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. 2023. Large language models cannot self-correct reasoning yet. In *The Twelfth International Conference on Learning Representations*.

Angelos Katharopoulos and François Fleuret. 2018. Not all samples are created equal: Deep learning with importance sampling. In *International conference on machine learning*, pages 2525–2534. PMLR.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35:22199–22213.

Xin Lai, Zhuotao Tian, Yukang Chen, Senqiao Yang, Xiangru Peng, and Jiaya Jia. 2024. Step-dpo: Step-wise preference optimization for long-chain reasoning of llms. *Preprint*, arXiv:2406.18629.

Ariel N Lee, Cole J Hunter, and Nataniel Ruiz. 2023. Platypus: Quick, cheap, and powerful refinement of llms. *arXiv preprint arXiv:2308.07317*.

Chen Li, Weiqi Wang, Jingcheng Hu, Yixuan Wei, Nanning Zheng, Han Hu, Zheng Zhang, and Houwen Peng. 2024a. Common 7b language models already possess strong math capabilities. *arXiv preprint arXiv:2403.04706*.

Xian Li, Ping Yu, Chunting Zhou, Timo Schick, Omer Levy, Luke Zettlemoyer, Jason E Weston, and Mike Lewis. 2024b. Self-alignment with instruction back-translation. In *The Twelfth International Conference on Learning Representations*.

Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2023. Let's verify step by step. *arXiv preprint arXiv:2305.20050*.

Haipeng Luo, Qingfeng Sun, Can Xu, Pu Zhao, Jianguang Lou, Chongyang Tao, Xiubo Geng, Qingwei Lin, Shifeng Chen, and Dongmei Zhang. 2023. Wizardmath: Empowering mathematical reasoning for

large language models via reinforced evol-instruct. *arXiv preprint arXiv:2308.09583*.

Swaroop Mishra, Matthew Finlayson, Pan Lu, Leonard Tang, Sean Welleck, Chitta Baral, Tanmay Rajpurohit, Oyvind Tafjord, Ashish Sabharwal, Peter Clark, et al. 2022. Lila: A unified benchmark for mathematical reasoning. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 5807–5832.

Richard Yuanzhe Pang, Weizhe Yuan, Kyunghyun Cho, He He, Sainbayar Sukhbaatar, and Jason Weston. 2024. Iterative reasoning preference optimization. *arXiv preprint arXiv:2404.19733*.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2024. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36.

Tom Schaul. 2015. Prioritized experience replay. *arXiv preprint arXiv:1511.05952*.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Zhiqing Sun, Yikang Shen, Qinhong Zhou, Hongxin Zhang, Zhenfang Chen, David Cox, Yiming Yang, and Chuang Gan. 2024. Principle-driven self-alignment of language models from scratch with minimal human supervision. *Advances in Neural Information Processing Systems*, 36.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.

Ye Tian, Baolin Peng, Linfeng Song, Lifeng Jin, Dian Yu, Haitao Mi, and Dong Yu. 2024. Toward self-improvement of llms via imagination, searching, and criticizing. *arXiv preprint arXiv:2404.12253*.

Yuxuan Tong, Xiwen Zhang, Rui Wang, Ruidong Wu, and Junxian He. 2024. Dart-math: Difficulty-aware rejection tuning for mathematical problem-solving. *Preprint*, arXiv:2407.13690.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Karthik Valmeekam, Matthew Marquez, Alberto Olmo, Sarath Sreedharan, and Subbarao Kambhampati. 2024. Planbench: An extensible benchmark for evaluating large language models on planning and reasoning about change. *Advances in Neural Information Processing Systems*, 36.

Ante Wang, Linfeng Song, Ye Tian, Baolin Peng, Dian Yu, Haitao Mi, Jinsong Su, and Dong Yu. 2024a. Litesearch: Efficacious tree search for llm. *arXiv preprint arXiv:2407.00320*.

Xiyao Wang, Jiuhai Chen, Zhaoyang Wang, Yuhang Zhou, Yiyang Zhou, Huaxiu Yao, Tianyi Zhou, Tom Goldstein, Parminder Bhatia, Furong Huang, et al. 2024b. Enhancing visual-language modality alignment in large vision language models via self-improvement. *arXiv preprint arXiv:2405.15973*.

Xiyao Wang, Wichayaporn Wongkamjan, Ruonan Jia, and Furong Huang. 2023a. Live in the moment: Learning dynamics model adapted to evolving policy. In *International Conference on Machine Learning*, pages 36470–36493. PMLR.

Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A Smith, Daniel Khashabi, and Hannaneh Hajishirzi. 2023b. Self-instruct: Aligning language models with self-generated instructions. In *The 61st Annual Meeting Of The Association For Computational Linguistics*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Tianhao Wu, Weizhe Yuan, Olga Golovneva, Jing Xu, Yuandong Tian, Jiantao Jiao, Jason Weston, and Sainbayar Sukhbaatar. 2024. Meta-rewarding language models: Self-improving alignment with llm-as-a-meta-judge. *arXiv preprint arXiv:2407.19594*.

Yuxi Xie, Anirudh Goyal, Wenyue Zheng, Min-Yen Kan, Timothy P. Lillicrap, Kenji Kawaguchi, and Michael Shieh. 2024a. Monte carlo tree search boosts reasoning via iterative preference learning. *Preprint*, arXiv:2405.00451.

Yuxi Xie, Anirudh Goyal, Wenyue Zheng, Min-Yen Kan, Timothy P Lillicrap, Kenji Kawaguchi, and Michael Shieh. 2024b. Monte carlo tree search boosts reasoning via iterative preference learning. *arXiv preprint arXiv:2405.00451*.

Longhui Yu, Weisen Jiang, Han Shi, YU Jincheng, Zhengying Liu, Yu Zhang, James Kwok, Zhenguo Li, Adrian Weller, and Weiyang Liu. 2023. Metamath: Bootstrap your own mathematical questions for large language models. In *The Twelfth International Conference on Learning Representations*.

Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Sainbayar Sukhbaatar, Jing Xu, and Jason Weston. 2024. Self-rewarding language models. *arXiv preprint arXiv:2401.10020*.

Zheng Yuan, Hongyi Yuan, Chengpeng Li, Guanting Dong, Chuanqi Tan, and Chang Zhou. 2023. Scaling relationship on learning mathematical reasoning with large language models. *arXiv preprint arXiv:2308.01825*.

Xiang Yue, Xingwei Qu, Ge Zhang, Yao Fu, Wen-hao Huang, Huan Sun, Yu Su, and Wenhu Chen. 2023. Mammoth: Building math generalist models through hybrid instruction tuning. *arXiv preprint arXiv:2309.05653*.

Dan Zhang, Sining Zhoubian, Yisong Yue, Yuxiao Dong, and Jie Tang. 2024. Rest-mcts*: Llm self-training via process reward guided tree search. *arXiv preprint arXiv:2406.03816*.

A Hyperparameters

In this section, we present hyperparameters used in our experiments. For trajectory pair extraction, both complete and stepwise trajectory pairs are selected for training with the margin τ as 1. In the curriculum preference learning (CPL), we set the balance rate between the trajectory reward gap and policy prediction gap to 0.5. The batch size for SFT is 128 and the batch size for preference learning is set to 64. The learning rates used at different stages are shown in Table 2.

Model	SFT	CPL-epoch 1	CPL-epoch 2
LLaMA-2 7B	1e-5	5e-7	5e-8
Mistral 7B	1e-7	2e-7	1e-8
LLaMA-3 8B-instruct	1e-6	5e-7	5e-8

Table 2: Learning rate used in different stages of different LLMs.