REVISITING UNCERTAINTY ESTIMATION FOR NODE CLASSIFICATION: NEW BENCHMARK AND INSIGHTS

ABSTRACT

Uncertainty estimation is an important task that can be essential for high-risk applications of machine learning. This problem is especially challenging for node-level prediction in graph-structured data, as the samples (nodes) are interdependent. Recently, several studies addressed node-level uncertainty estimation. However, there is no established benchmark for evaluating these methods in a unified setup covering diverse distributional shift. In this paper, we address this problem and propose such a benchmark together with a technique for the controllable generation of data splits with various types of distributional shift. Importantly, besides the standard feature-based distributional shift, we also consider shifts specifically designed for graph-structured data. In summary, our benchmark consists of several graph datasets equipped with various distributional shift on which we evaluate the robustness of models and uncertainty estimation performance. This allows us to compare existing solutions in a unified setup. Moreover, we decompose the current state-of-the-art Dirichlet-based framework and perform an ablation study on its components. In our experiments, we demonstrate that when faced with complex yet realistic distributional shift, most models fail to maintain high classification performance and consistency of uncertainty estimates with prediction errors. However, ensembling techniques help to partially overcome significant drops in performance and achieve better results than distinct models. Among single-pass models, Natural Posterior Network with GNN encoder achieves the best performance.

1 INTRODUCTION

Uncertainty estimation is an important and challenging task with many applications in financial systems, medical diagnostics, autonomous driving, etc. It aims at quantifying the confidence of machine learning models and can be used to design more reliable decision-making systems. In particular, it enables one to solve such problems as misclassification detection, where the model has to assign higher uncertainty to the potential prediction errors, or out-of-distribution (OOD) detection, when the model is required to yield higher uncertainty for the samples from an unknown distribution. Depending on the source of uncertainty, it can be divided into *data uncertainty*, which describes the inherent noise in data due to the labeling mistakes or class overlap, and *knowledge uncertainty*, which accounts for insufficient amount of information for accurate predictions when the distribution of test data is different from the training one (Gal, 2016; Malinin, 2019).

The problem of uncertainty estimation for graph-structured data has recently started to gain attention. It is especially complex at the node level as one has to deal with interdependent samples that may come from different distributions, so their predictions can change significantly depending on the neighborhood. This problem has already been addressed in several studies, and the proposed methods are commonly based on the Dirichlet distribution and introduce various extensions to the Dirichlet framework (Sensoy et al., 2018; Malinin & Gales, 2018; Malinin, 2019; Charpentier et al., 2020), such as graph-based kernel Dirichlet estimation (Zhao et al., 2020) or graph propagation of Dirichlet parameters (Stadler et al., 2021).

However, the field of robustness and uncertainty estimation for node-level graph problems suffers from the absence of diverse and meaningful benchmarks with reasonable distributional shift. Usually, the evaluation is limited to somewhat unrealistic distributional shift, such as noisy node fea-

tures (Stadler et al., 2021) or left-out classes (Zhao et al., 2020; Stadler et al., 2021). Importantly, Gui et al. (2022) try to overcome this issue and systematically construct a graph OOD benchmark, in which they explicitly make distinctions between covariate and concept shifts. However, the authors either consider synthetic datasets or ignore the graph structure when creating distributional shifts. The problem with the mentioned approaches is that, in real applications, distributional shift can be much more complex and diverse, and may depend on the global graph structure. Thus, the existing benchmarks can be insufficient to reliably and comprehensively evaluate uncertainty estimation methods for graph-structured data. Therefore, the current status quo about the best uncertainty estimation methods for node classification remains unclear and requires further investigation.

In this work we propose a new benchmark for evaluating robustness and uncertainty estimation in transductive node classification tasks. It consists of 7 datasets, for which we consider 4 strategies to constructing data splits with distribution shifts. Our approach to induce them is universal: it can be applied to any graph dataset, allows for generating shifts of different nature, and one can easily vary the size of the training data. Using the proposed benchmark, we evaluate the robustness of various models and their ability to detect errors and OOD inputs. Thus, we show that the recently proposed Graph Posterior Network (Stadler et al., 2021) is consistently the best method for detecting OOD inputs. However, the best results for the other tasks are achieved using Natural Posterior Networks (Charpentier et al., 2021). We also confirm that ensembling often allows one to improve the model performance — ensembles of GPNs achieve the best performance for OOD detection, while ensembles of NatPNs have the best predictive performance and error detection.

2 PROBLEM STATEMENT

We consider the problem of transductive node classification in an attributed graph $\mathcal{G} = (\mathbf{A}, \mathbf{X}, \mathbf{Y})$ with an adjacency matrix $\mathbf{A} \in \{0, 1\}^{n \times n}$, a node feature matrix $\mathbf{X} \in \mathbb{R}^{n \times d}$ and categorical targets vector $\mathbf{Y} \in \{1, \dots, C\}^n$. We split the set of nodes $\mathcal{V}$ into several non-intersecting subsets depending on whether they are used for training, validation, or testing and if they belong to in-distribution (ID) or out-of-distribution (OOD) subset. Let $\mathbf{Y}_{\text{train}}$ denote the labels of train nodes $\mathcal{V}_{\text{train}}$. Given a graph $\mathcal{G}_{\text{train}} = (\mathbf{A}, \mathbf{X}, \mathbf{Y}_{\text{train}})$, we aim at predicting the labels $\mathbf{Y}_{\text{test}}$ of test nodes $\mathcal{V}_{\text{test}}$ and estimating the uncertainty measure $u_i \in \mathbb{R}$ associated with these predictions. The obtained uncertainty estimates are used to solve the misclassification detection and OOD detection problems.

3 PROPOSED BENCHMARK

This section describes our benchmark for evaluating uncertainty estimates and robustness to distributional shift for node-level graph problems. The most important ingredient of our benchmark is a unified approach for the controllable generation of diverse distributional shift that can be applied to any graph dataset. Our benchmark includes a collection of common node classification datasets, several data split strategies, a set of problems for evaluating robustness and uncertainty estimation performance, and the associated metrics. We describe these components below.

3.1 GRAPH DATASETS

While our approach can potentially be applied to any node classification or node regression dataset, for our experiments, we pick the following 7 datasets commonly used in the literature: 5 citation networks, including **CoraML** and **CiteSeer** (McCallum et al., 2000; Giles et al., 1998; Getoor, 2005; Sen et al., 2008), **PubMed** (Namata et al., 2012), **CoauthorPhysics** (Shchur et al., 2018) and **CoauthorCS** (Shchur et al., 2018)), and 2 co-purchase datasets — **AmazonPhoto** and **Amazon-Computers** (McAuley et al., 2015; Shchur et al., 2018).

3.2 DATA SPLITS

The most important ingredient of our benchmark is a general approach to generating data splits in a graph $\mathcal{G}$ to yield non-trivial yet reasonable distributional shift. For this purpose, we make a distinction between the ID parts that are described by $p(\mathbf{Y}_{\text{in}} | \mathbf{X}, \mathbf{A})$ and shifted (OOD) parts where the targets may come from a significantly different distribution $p(\mathbf{Y}_{\text{out}} | \mathbf{X}, \mathbf{A})$.

We define the following ID parts:

- `Train` contains the nodes $\mathcal{V}_{\text{train}}$ that are used for the regular training of models and represent the only observations that take part in gradient computation;
- `Valid-In` enables us to monitor the best model during the training stage by computing the validation loss for the nodes $\mathcal{V}_{\text{valid-in}}$ and choose the best checkpoint;
- `Test-In` is used for testing on the remaining in-distribution nodes $\mathcal{V}_{\text{test-in}}$ and represents the most simple setup that requires the model to reproduce in-distribution dependencies. Both `Valid-In` and `Test-In` parts are assumed to come from the exact same distribution as `Train`.

At the same time, we introduce the following OOD parts:

- `Valid-Out` contains the validation nodes $\mathcal{V}_{\text{valid-out}}$ that also can be used for monitoring but tends to be a more difficult part of graph with potentially different dependencies;
- `Test-Out` represents the most shifted part $\mathcal{V}_{\text{test-out}}$ and can be used for evaluating robustness of models to distributional shift.

To construct a particular data split, we choose some characteristic σ_i and compute it for every node $i \in \mathcal{V}$, as described Section 3.3. This characteristic reflects some node property that may depend on features or graph structure. After that, we sort all nodes in ascending order of σ_i. Some fraction of nodes with the smallest values of σ_i is considered to be ID, while the remaining one become OOD and is split into `Valid-Out` and `Test-Out` based on their values of σ_i.

In our experiments, we split the dataset in the following proportions. The half of the nodes with the smallest values of σ_i are assumed to be ID and are split into `Train`, `Valid-In`, and `Test-In` uniformly at random in proportion 30%/10%/10%. The second half contains the remaining OOD nodes split into `Valid-Out` and `Test-Out` in the ascending order of σ_i in proportion 10%/40%. As a result, the `Test-Out` part has the most significant distribution shift.

3.3 DISTRIBUTIONAL SHIFT

To define our data splits it is necessary to choose a node characteristic σ_i to be used as a split factor. We aim to consider diverse characteristics to cover a variety of distributional shift that may happen in practice. In a standard non-graph ML setup, shifts typically happen only in feature space, or, more generally, the joint distribution of features and targets may become shifted. In graph tasks, there can be shifts specifically related to the graph structure: the training part can be biased towards more popular elements or may consist of nodes from a particular region in the graph. Thus, we consider the following representative data split strategies.

- **Random**. This strategy represents a classic approach to constructing data splits, where the nodes are selected uniformly at random, so the measure σ_i can be considered as a random position in the sorted list.
- **Feature**. This approach represents a family of possible feature-based shifts that do not take into account graph structure explicitly. We project the original features $\boldsymbol{x}_i \in \mathbb{R}^d$ into $\mathbb{R}^2$ via a random linear transform $\mathbf{W}$, where all entries w_{ij} are independent and come from $\mathcal{N}(0, 1)$. After that, the measure σ_i is set to the distance between the node $i \in \mathcal{V}$ and the centroid of the projected data, so the most *central* nodes in terms of features are said to be ID, while OOD parts are close to *periphery*.
- **PageRank**. This strategy represents a possible popularity-based bias. It is natural to expect that the train set may consist of more popular items: for instance, if one labels the most influential users in a social network. To cover such a scenario, we compute the PageRank (PR) (Page et al., 1999) values for every node $i \in \mathcal{V}$ and define the measure σ_i as the negative PR score, which means that the nodes with smaller values of PR (i.e., less important ones) come to the OOD subsets.
- **Personalized PageRank**. This strategy represents a possible locality-based bias. For instance, when labeling is performed by exploring the graph starting from some node. To model such bias, we use the concept of Personalized PageRank (PPR) (Page et al., 1999).

|(a) Feature|(b) PageRank|(c) Personalized PageRank|

Figure 1: Visualization of data splits for AmazonPhoto dataset: ID is blue, OOD is red.

> PPR is a stationary distribution of a random walk that restarts from a fixed node. We select the node $j \in \mathcal{V}$ with the highest PR score as a restarting node. Then, we compute the PPR score for every node $i \in \mathcal{V}$ and define the measure σ_i as negative PPR. Nodes with high PPR are expected to be close to the restarting node, and they belong to the ID part, while far away nodes go to the OOD subsets.

In Figure 1, we visualize our split strategies applied to the AmazonPhoto dataset. The figures for the remaining datasets can be found in Appendix D. First, we see that the PPR split is specific to locality — ID nodes cover a local region in the graph, as desired. In contrast, according to the PageRank split, ID nodes are the most central ones in all clusters in the graph. Finally, we note that there is no significant relation between feature-based split and graph structure. We expect PPR to be the most challenging split for graph models as OOD nodes are well separated from ID and thus may not have neighbors belonging to the train set. Our experiments confirm that this is indeed the case. Moreover, such a noticeable graph-based shift also induces a significant change in the feature-target distribution which can be illustrated by a substantial drop in performance for graph-agnostic models. In contrast, our feature-based turns out to be the simplest one for the considered models.

3.4 METRICS

To evaluate the classification performance, we exploit standard *Accuracy* and compute these metrics on `Test-In` and `Test-Out` parts. To analyze the aggregated performance, we also report Accuracy and AUROC on the mixture of `Test-In` and `Test-Out`.

To evaluate the quality of uncertainty estimates, we consider two problems: error (misclassification) detection and OOD detection. To assess how well a model can detect misclassified samples, we use the concept of *Prediction Rejection Curve* (PRC) (Malinin et al., 2021; 2022). PRC traces the error rate as we replace model predictions with ground-truth labels in the order of decreasing uncertainty. If uncertainty is high for incorrectly classified samples, then the error rate is expected to drop quickly as we replace such predictions with ground true labels. Thus, the *Area Under Prediction Rejection Curve* (AUPRC) evaluates the joint classification and uncertainty estimation performance, requiring the model not only to provide high prediction accuracy but also to signalize about possible errors through higher uncertainty scores. In our experiments, we compute $\text{AUPRC}_{\text{model}}$ on the merged test subset of nodes $\mathcal{V}_{\text{test}}$ using *total uncertainty* (TU), as the errors may occur due to the inherent noise in data or because of predicting on OOD samples.

A measure called *Prediction Rejection Ratio* (PRR) is also based on the Prediction Rejection Curve but evaluates only the ability of a model to detect misclassified samples. For this purpose, AUPRC is normalized as follows. Let $\text{PRC}_{\text{model}}$ be the predicted uncertainty estimates, $\text{PRC}_{\text{random}}$ be random uncertainty estimates, and $\text{PRC}_{\text{oracle}}$ be estimates that perfectly sort samples according to the prediction errors (i.e., all misclassified samples have higher oracle uncertainty). Then, the PRR metric is defined as follows:

$$\text{PRR} = \frac{\text{AUPRC}_{\text{random}} - \text{AUPRC}_{\text{model}}}{\text{AUPRC}_{\text{random}} - \text{AUPRC}_{\text{oracle}}}$$

The best value of this measure is 1 (for the perfect uncertainty estimates), while random uncertainty estimates give PRR $= 0$.

We also evaluate the ability of models to detect OOD samples. For this, we consider the mixture of `Test-In` and `Test-Out`. A good model is expected to have higher *knowledge uncertainty* (KU) (Gal, 2016; Malinin, 2019) values for the observations from `Test-Out` compared to `Test-In`. Here, we use the standard AUROC for the binary classification with positive events corresponding to the observations coming from the OOD subset.

4 METHODS

We consider several methods for estimating uncertainty in graph-related problems. Specifically, we cover message-passing neural networks, ensemble approaches Lakshminarayanan et al. (2017), and Dirichlet-based methods that are currently considered to be state-of-the-art for OOD detection that is called GPN (Stadler et al., 2021). For Dirichlet-based approaches, we conduct an ablation study to evaluate which design choices contribute most to performance.

4.1 STANDARD METHODS

In this class of methods, the constructed model f_θ predicts the parameters $\boldsymbol{\mu}_i = f_\theta(\boldsymbol{x}_i)^1$ of the categorical distribution $\mathrm{P}_\theta(y_i|\boldsymbol{x}_i) = \mathrm{P}(y_i|\boldsymbol{\mu}_i)$ in the standard classification task, while the uncertainty estimates are obtained based on the entropy of this distribution.

A simple baseline that serves us as a lower bound for our further experiments with more advanced methods is **MLP**, which represents a graph-agnostic MLP model and takes into account only the features of the current observation. In contrast, **GNN** is a simple GNN model based on a two-layer SAGE convolution (Hamilton et al., 2017), which combines the information from both the central node and its neighborhood. As a training objective, these methods use the standard *Cross-Entropy* loss between the one-hot-encoded target y_i and the predicted categorical vector $\boldsymbol{\mu}_i$: $\mathcal{L}_i = -\log \mathrm{P}(y_i|\boldsymbol{\mu}_i)$. For these methods, we can only define uncertainty as the entropy $u_i = \mathbb{H}\big[\mathrm{P}(y_i|\boldsymbol{\mu}_i)\big]$ of the predictive categorical distribution.

4.2 DIRICHLET-BASED METHODS

The core idea behind the Dirichlet-based uncertainty estimation methods is to model the point-wise Dirichlet distribution $\mathrm{p}_\theta(\boldsymbol{\mu}_i|\boldsymbol{x}_i) = \mathrm{p}(\boldsymbol{\mu}_i|\boldsymbol{\beta}_i^{\mathrm{post}})$ by predicting its concentration parameters $\boldsymbol{\beta}_i^{\mathrm{feat}} = f_\theta(\boldsymbol{x}_i)$ and updating the uniform prior distribution with parameters $\boldsymbol{\beta}^{\mathrm{prior}} = \mathbf{1}$ by taking their sum: $\boldsymbol{\beta}_i^{\mathrm{post}} = \boldsymbol{\beta}_i^{\mathrm{feat}} + \boldsymbol{\beta}_i^{\mathrm{prior}}$. Using this Dirichlet distribution, one can obtain the target categorical one as follows:

$$\mathrm{P}_\theta(y_i|\boldsymbol{x}_i) = \mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}_i|\boldsymbol{\beta}_i^{\mathrm{post}})}\mathrm{P}(y_i|\boldsymbol{\mu}_i).$$

It implies that $\mathrm{P}_\theta(y_i|\boldsymbol{x}_i)$ has parameters $\boldsymbol{\beta}_i^{\mathrm{post}}/S_i$, where $S_i = \sum_k \beta_{ik}^{\mathrm{post}}$ is called *evidence* or *precision*. In other words, the parameters of the categorical distribution can be obtained from the Dirichlet ones by normalization. Importantly, the Dirichlet-based methods allow us to distinguish between total and knowledge uncertainty as follows:

$$u_i^{\mathrm{total}} = \mathbb{H}\big[\mathrm{P}_\theta(y_i|\boldsymbol{x}_i)\big] = \mathbb{H}\big[\mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}_i|\boldsymbol{\beta}_i^{\mathrm{post}})}\mathrm{P}(y_i|\boldsymbol{\mu}_i)\big], \quad u_i^{\mathrm{know}} = -S_i.$$

For this class of methods, the training objective is *Expected Cross-Entropy* with an optional regularisation term that is equal to the entropy of the predicted Dirichlet distribution $\mathrm{p}(\boldsymbol{\mu}_i|\boldsymbol{\beta}_i^{\mathrm{post}})$:

$$\mathcal{L}_i = \mathbb{E}_{\mathrm{p}(\boldsymbol{\mu}_i|\boldsymbol{\beta}_i^{\mathrm{post}})}\big[-\log \mathrm{P}(y_i|\boldsymbol{\mu}_i)\big] - \lambda\mathbb{H}\big[\mathrm{p}(\boldsymbol{\mu}_i|\boldsymbol{\beta}_i^{\mathrm{post}})\big]. \tag{1}$$

This loss function can be computed in closed form (Malinin & Gales, 2018; Charpentier et al., 2020).

As the most straightforward method in this class, we consider a modification of **GNN** that is referred to as **EN** (Evidential Network) (Sensoy et al., 2018) — while exploiting the same architecture, it is trained to predict the Dirichlet parameters via (1).

---

[1] For GNNs, we formally have $\boldsymbol{\mu}_i = f_\theta(\mathbf{A}, \mathbf{X}, i)$ but we write $f_\theta(\boldsymbol{x}_i)$ for simplicity of notation and consistency with non-graph methods.

There are also more advanced methods based on the Dirichlet distribution which induce the behavior of the underlying model by estimating the density function in the latent space using *Normalizing Flows* (Kingma et al., 2016; Huang et al., 2018). These methods can be united within the recently proposed framework *Posterior Networks* (Charpentier et al., 2020; 2021). It was applied to the node-level problems in (Stadler et al., 2021). In this paper, we provide a detailed study of this framework and consider different variations depending on how the density estimation is performed and how the graph information is used.

4.2.1 STANDARD OR NATURAL DENSITY ESTIMATION

One property that we vary in these methods is the number of Normalizing Flows and how we use their density estimates. In particular, we consider a *Standard* approach (Charpentier et al., 2020), where distinct Normalizing Flows $p_\psi(z_i|k)$ are used per each class k to predict the corresponding Dirichlet parameter β_{ik}^{feat} based on the representation $z_i = f_\phi(x_i)$:

$$\beta_{ik}^{\text{feat}} = n \cdot p_\psi(z_i, k) = n \cdot p_\psi(z_i|k) \cdot P(k) = n_k \cdot p_\psi(z_i|k),$$

where the probability $P(k)$ of class k is approximated by the ratio of train observations from class k, n is usually equal to the dataset size (but can, in general, be a hyper-parameter), and $n_k := n \cdot P(k)$.

Another approach is the *Natural* version of Posterior Network that is proposed by Charpentier et al. (2021). It exploits a single Normalizing Flow $p_\psi(z_i)$ to predict the evidence S_i, while the normalized Dirichlet parameters μ_i are obtained using one-layer linear transformation $g_\omega(z_i)$. The final predictions are obtained as follows:

$$S_i = n \cdot p_\psi(z_i), \ \mu_i = g_\omega(z_i) \implies \beta_{ik}^{\text{feat}} = S_i \cdot \mu_{ik}$$

4.2.2 GRAPH ENCODING OR GRAPH PROPAGATION

Another aspect that we analyze is how the graph structure can be combined with Posterior Networks. Here, we consider two approaches — use the graph for the *encoding* to obtain z_i or use *graph propagation* to smooth the predicted parameters as the post-processing step.

In the case of graph encoding, we use a two-layer SAGE convolution to produce the representations z_i and then estimate the density as usual via Normalizing Flows. Thus, the graph structure is used for the pre-processing step.

The second approach is adopted by Stadler et al. (2021). In this case, the initial representations z_i are obtained using a graph-agnostic two-layer MLP, while graph propagation is applied to smooth the Dirichlet parameters β_i^{feat}. Graph propagation is performed in several steps via some transformation $\pi : \mathbb{R}^{n \times C} \to \mathbb{R}^{n \times C}$ as follows:

$$\mathbf{B}^{t+1} = (1 - \alpha)\pi(\mathbf{B}^t) + \alpha\mathbf{B},$$

where $\mathbf{B}^0 = \mathbf{B} \in \mathbb{R}^{n \times C}$ is formed by the parameters β_{ik}^{feat} and α is a hyperparameter that controls the smoothing effect of the propagation step. Similarly to Stadler et al. (2021), we use a *Personalized Propagation* scheme (Klicpera et al., 2018), which takes into account the mutual importance of nodes and is defined as $\pi(\mathbf{B}) = \mathbf{D}^{-1/2}\mathbf{A}\mathbf{D}^{-1/2}\mathbf{B}$.

We refer to the method with graph propagation as **GPN** (Graph Posterior Network) and with Graph Encoding as **PN** (Posterior Network). Further, if the Natural version of the Posterior Network is used instead of the Standard one, we denote the models **NatGPN** and **NatPN**, respectively.

4.3 ENSEMBLES

In our study, we also consider *ensembling* techniques that proved to increase the predictive performance of models and provide instruments for estimating uncertainty.

Among the methods that predict the parameters μ_i of categorical distributions $P(y_i|\mu_i)$, there is a widely used approach for uncertainty estimation introduced by Lakshminarayanan et al. (2017). It can be formulated as an empirical distribution of model parameters $q(\theta|\mathcal{G}_{\text{train}})$ that can be obtained after training several instances of the model with different random seeds for initialization:

$$P_\theta(y_i|x_i) = \mathbb{E}_{q(\theta|\mathcal{G}_{\text{train}})}P(y_i|\mu_i).$$

Table 1: Accuracy of **GNN** on ID vs OOD test subsets for every split strategy.

	Feature			**PageRank**			**PPR**		
	ID	OOD	Diff, %	ID	OOD	Diff, %	ID	OOD	Diff, %
AmazonComputers	84.88	84.86	-0.02	87.86	82.36	-6.27	86.40	58.77	-31.97
AmazonPhoto	94.90	92.23	-2.82	97.07	88.94	-8.38	92.68	43.89	-52.64
CoauthorCS	92.44	93.74	$+1.41$	94.81	91.33	-3.66	92.67	91.63	-1.12
CoauthorPhysics	96.57	96.06	-0.54	97.52	94.44	-3.15	97.72	93.68	-4.14
CoraML	83.68	86.96	$+3.92$	89.90	82.89	-7.80	86.76	75.51	-12.96
CiteSeer	70.87	71.50	$+0.88$	74.47	71.42	-4.10	74.11	59.25	-20.06
PubMed	87.58	86.01	-1.79	88.69	83.39	-5.98	85.88	84.53	-1.57

Given this, we can split the total uncertainty into data and knowledge uncertainty through the following expression (Malinin & Gales, 2018):

$$u_i^{\text{total}} = \mathbb{H}\big[\mathrm{P}_\theta(y_i|\boldsymbol{x}_i)\big] = \mathbb{H}\big[\mathbb{E}_{\mathsf{q}(\theta|\mathcal{G}_{\text{train}})}\mathrm{P}(y_i|\boldsymbol{\mu}_i)\big],$$

$$u_i^{\text{data}} = \mathbb{E}_{\mathsf{q}(\theta|\mathcal{G}_{\text{train}})}\mathbb{H}\big[\mathrm{P}(y_i|\boldsymbol{\mu}_i)\big], \quad u_i^{\text{know}} = u_i^{\text{total}} - u_i^{\text{data}}.$$

We apply this approach to **GNN** models and denote the obtained ensemble as **EnsGNN**. As for the Dirichlet-based approaches, we follow Charpentier et al. (2021) and define an ensemble of models that predict the parameters $\boldsymbol{\beta}_i^{\text{post}}$ of Dirichlet distribution $\mathrm{P}(\boldsymbol{\mu}_i|\boldsymbol{\beta}_i^{\text{post}})$ as follows:

$$\boldsymbol{\beta}_i^{\text{ens}} = \mathbb{E}_{\mathsf{q}(\theta|\mathcal{G}_{\text{train}})}\boldsymbol{\beta}_i^{\text{post}}.$$

For this method, uncertainty is estimated in the same way as for a single Dirichlet-based model.

5   EXPERIMENTS AND ABLATION

Setup   As discussed in Section 3.4, we provide the comparison of the methods for four different problems using their associated metrics. In particular, we report the standard Accuracy for general classification performance, PRR@TU for consistency of *total uncertainty* estimates u_i^{total} with the prediction errors, AUPRC@TU for the joint classification and confidence performance, and AUROC@KU for the OOD detection using *knowledge uncertainty* estimates u_i^{know}. The details of our experimental setup can be found in Appendix B.

Our code and benchmark are publicly available at `https://anonymous.4open.science/r/revisiting-uncertainty-estimation-F4B6`, together with a framework for evaluating a variety of baseline models, Dirichlet-based methods, and ensembling techniques.

We run each algorithm 5 times with different random seeds and report the mean and standard deviation. To compare a pair of algorithms and analyze whether one is noticeably better than the other, we report `win/tie/loss` counts aggregated over the datasets and, in some cases, over different distributional shifts. We say an algorithm wins on a particular dataset if it is better than its competitor and the difference is larger than the sum of their standard deviations. If the difference is smaller — there is a tie. Note that we do not compute the standard deviation for the ensembles since they combine all five models. Finally, to conveniently compare all the algorithms, we aggregate their results over all the datasets as follows. First, for each dataset, metric, and distribution shift, we rank all the algorithms according to their performance (the smaller, the better). Then, we average the obtained ranks over all the datasets.

Results and insights   In this section, we address several research questions. First, we analyze the complexity and diversity of the proposed data split strategies. Then, we demonstrate the performance of existing methods on our benchmark. After that, we investigate the Dirichlet-based methods to figure out which of them is superior for each task. In conclusion, we find out whether the best-performing models can further be improved via ensembling.

Q1: How complex and diverse are the proposed data splits?

Table 2: Average ranks of standard uncertainty estimation methods over graph datasets.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	GNN	2.3	1.7	2.3	*n/a*
	GPN	2.6	3.0	2.6	*n/a*
	EnsGNN	1.1	1.3	1.1	*n/a*
Feature	GNN	2.3	1.6	2.1	2.3
	GPN	2.6	2.9	2.7	1.0
	EnsGNN	1.1	1.6	1.1	2.7
PageRank	GNN	2.3	1.9	2.1	2.7
	GPN	2.4	2.7	2.7	1.0
	EnsGNN	1.3	1.4	1.1	2.3
PPR	GNN	2.4	2.3	2.6	2.9
	GPN	2.1	1.7	2.0	1.0
	EnsGNN	1.4	2.0	1.4	2.1

Table 3: Average ranks of Dirichlet-based methods over datasets, including **EN**, **PN**, **NatPN**, **GPN** and **NatGPN**, which are obtained for every considered split strategy and prediction task.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	EN	2.0	1.7	2.0	*n/a*
	PN	3.7	3.7	3.4	*n/a*
	NatPN	1.9	1.4	1.9	*n/a*
	GPN	3.0	4.0	3.3	*n/a*
	NatGPN	4.4	4.1	4.4	*n/a*
Feature	EN	2.3	1.6	2.0	3.3
	PN	3.6	3.4	3.6	3.9
	NatPN	1.9	1.7	1.7	4.6
	GPN	2.9	4.4	3.3	1.4
	NatGPN	4.4	3.9	4.4	1.9
PageRank	EN	2.1	2.0	2.1	4.4
	PN	3.9	3.4	3.6	3.1
	NatPN	1.7	1.9	1.7	4.4
	GPN	2.7	3.7	3.3	1.1
	NatGPN	4.6	4.0	4.3	1.9
PPR	EN	3.0	3.0	2.9	3.3
	PN	3.7	3.9	3.9	3.4
	NatPN	2.0	1.7	1.9	5.0
	GPN	2.1	2.4	2.1	1.0
	NatGPN	4.1	4.0	4.3	2.3

To answer this question, we analyze the predictive performance of the models on `Test-In` (ID) and `Test-Out` (OOD) parts. Table 1 shows this comparison for **GNN**, and similar results for **GPN**, **EnsGNN**, and **MLP** can be found in Tables 8–7 in Appendix. We can see that feature-based splits are the easiest for **GNN**: the difference between ID and OOD parts is sufficiently small, and the performance on the latter can be even better for some datasets. The PageRank splits are noticeably more complicated, but the most difficult split strategy is based on Personalized PageRank — the performance drop is dramatic on some datasets. This can be explained by the locality of the ID part (see Figure 1): the clear separation of ID from OOD in terms of the graph structure makes graph-based learning significantly more complicated.

Q2: How do existing methods perform in our setup, and what is the current status quo?

To answer this question, we compare the following models: **GNN** as the classic Graph Neural Network, **EnsGNN** as the standard and universal approach allowing for getting uncertainty estimates, and **GPN** which is known to be state-of-the-art for the OOD detection (Stadler et al., 2021). Table 2 compares these algorithms aggregated over all datasets. We see that, according to AUROC@KU, the best results in OOD detection are achieved by **GPN** for all types of shifts, which is consistent with previously reported results (Stadler et al., 2021). Unsurprisingly, **EnsGNN** shows the best predictive

Table 4: `Win/tie/loss` counts for some pairs of Dirichlet-based methods across all the considered graph datasets and split strategies (except Random).

	Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
NatPN vs EN	3/18/0	6/14/1	8/12/1	3/3/15
GPN vs NatGPN	14/5/2	8/11/2	15/2/4	12/8/1
NatPN vs GPN	12/2/7	14/5/2	13/3/5	0/0/21

Table 5: `Win/tie/loss` counts for ensembles vs the corresponding single models across all the considered graph datasets and split strategies (except Random).

	Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
EnsGPN vs GPN	9/11/1	6/14/1	14/7/0	4/17/0
EnsNatPN vs NatPN	14/7/0	6/15/0	15/6/0	5/9/7

performance, as measured by Accuracy. Moreover, it has the most consistent uncertainty estimates in context of PRR@TU and provides the best joint performance via AUPRC@TU. In summary, ensembles are the best for all tasks but OOD detection, where the best model is **GPN**.

Q3: Which Dirichlet-based methods are the best for each prediction task?

We provide a detailed analysis of the Dirichlet-based framework. The simplest model here is **EN**, which represents a standard GNN trained with the loss (1). Further, we consider the methods using Normalizing Flows and compare Standard vs Natural density estimation and Graph Encoding vs Graph Propagation. Based on Table 3, we can make the following conclusions. First, **GPN** is still the best method for OOD detection. Then, **NatPN** is the best according to all other tasks. Finally, **EN** is a strong baseline that shows competitive results in Accuracy, PRR@TU, and AUCPRC@TU, often staying close to **NatPN**. To show whether the difference is statistically significant, we report the `win/tie/loss` counts for some pairs of models. See Table 4 for the aggregated results and Tables 10, 12–15 in Appendix for more details.

Q4: Do ensembles consistently improve the performance of complex models?

Ensemble are known to consistently improve model performance in non-graph based tasks. We aim to confirm that this result hold in the transductive node classification setting. We examine ensembles of the two most promising methods **GPN** and **NatPN**. The aggregated results are shown in Table 5, see also Tables 11–15 in Appendix for more details. We can see that ensembling via **EnsGPN** consistently improves **GPN** for OOD detection, but the difference is mostly insignificant. In contrast, **EnsNatPN** is noticeably better than **NatPN**, and this gain is especially significant for Accuracy and the joint performance measured by AUPRC.

To summarize our findings, we refer to Table 16 for the comparison of all the methods in terms of ranks and to Tables 12–15 for the detailed comparison of their `win/tie/loss` counts. We conclude that **GPN** is the best single model for OOD detection, while **NatPN** is the best single model for all other tasks. Moreover, their performance can be further improved by ensembling, so **EnsNatPN** appears to be the best method in terms of Accuracy, PRR, and AUPRC. However, **EnsGNN** provides comparable results.

6 CONCLUSION

In this work, we propose a new benchmark for evaluating robustness and uncertainty estimation in transductive node classification tasks. For this, we suggest a universal approach to inducing distribution shifts in data splits: it can be applied to any graph dataset and allows for generating shifts of different nature. In particular, we show that the recently proposed Graph Posterior Network (Stadler et al., 2021) is consistently the best method for detecting OOD inputs, while the best results for the other tasks are achieved using Natural Posterior Networks (Charpentier et al., 2021). We also confirm that ensembling often allows one to improve the model performance. We believe that our benchmark will be useful for future studies of node-level uncertainty estimation.

REFERENCES

Bertrand Charpentier, Daniel Zügner, and Stephan Günnemann. Posterior network: Uncertainty estimation without ood samples via density-based pseudo-counts. *Advances in Neural Information Processing Systems*, 33:1356–1367, 2020.

Bertrand Charpentier, Oliver Borchert, Daniel Zügner, Simon Geisler, and Stephan Günnemann. Natural posterior network: Deep bayesian predictive uncertainty for exponential family distributions. In *International Conference on Learning Representations*, 2021.

Yarin Gal. Uncertainty in deep learning. *University of Cambridge, Cambridge*, 2016.

Lise Getoor. Link-based classification. In *Advanced methods for knowledge discovery from complex data*, pp. 189–207. Springer, 2005.

C Lee Giles, Kurt D Bollacker, and Steve Lawrence. Citeseer: An automatic citation indexing system. In *Proceedings of the third ACM conference on Digital libraries*, pp. 89–98, 1998.

Shurui Gui, Xiner Li, Limei Wang, and Shuiwang Ji. GOOD: A graph out-of-distribution benchmark. *arXiv preprint arXiv:2206.08452*, 2022.

Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. *Advances in Neural Information Processing Systems*, 30, 2017.

Chin-Wei Huang, David Krueger, Alexandre Lacoste, and Aaron Courville. Neural autoregressive flows. In *International Conference on Machine Learning*, pp. 2078–2087. PMLR, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Durk P Kingma, Tim Salimans, Rafal Jozefowicz, Xi Chen, Ilya Sutskever, and Max Welling. Improved variational inference with inverse autoregressive flow. *Advances in neural information processing systems*, 29, 2016.

Johannes Klicpera, Aleksandar Bojchevski, and Stephan Günnemann. Predict then propagate: Graph neural networks meet personalized pagerank. *arXiv preprint arXiv:1810.05997*, 2018.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. *Advances in neural information processing systems*, 30, 2017.

Andrey Malinin. *Uncertainty estimation in deep learning with application to spoken language assessment*. PhD thesis, University of Cambridge, 2019.

Andrey Malinin and Mark Gales. Predictive uncertainty estimation via prior networks. *Advances in neural information processing systems*, 31, 2018.

Andrey Malinin, Neil Band, German Chesnokov, Yarin Gal, Mark JF Gales, Alexey Noskov, Andrey Ploskonosov, Liudmila Prokhorenkova, Ivan Provilkov, Vatsal Raina, et al. Shifts: A dataset of real distributional shift across multiple large-scale tasks. *arXiv preprint arXiv:2107.07455*, 2021.

Andrey Malinin, Andreas Athanasopoulos, Muhamed Barakovic, Meritxell Bach Cuadra, Mark JF Gales, Cristina Granziera, Mara Graziani, Nikolay Kartashev, Konstantinos Kyriakopoulos, Po-Jui Lu, et al. Shifts 2.0: Extending the dataset of real distributional shifts. *arXiv preprint arXiv:2206.15407*, 2022.

Julian McAuley, Christopher Targett, Qinfeng Shi, and Anton Van Den Hengel. Image-based recommendations on styles and substitutes. In *Proceedings of the 38th international ACM SIGIR conference on research and development in information retrieval*, pp. 43–52, 2015.

Andrew Kachites McCallum, Kamal Nigam, Jason Rennie, and Kristie Seymore. Automating the construction of internet portals with machine learning. *Information Retrieval*, 3(2):127–163, 2000.

Galileo Namata, Ben London, Lise Getoor, Bert Huang, and U Edu. Query-driven active surveying for collective classification. In *10th International Workshop on Mining and Learning with Graphs*, volume 8, pp. 1, 2012.

Lawrence Page, Sergey Brin, Rajeev Motwani, and Terry Winograd. The pagerank citation ranking: Bringing order to the web. Technical report, Stanford InfoLab, 1999.

Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Galligher, and Tina Eliassi-Rad. Collective classification in network data. *AI magazine*, 29(3):93–93, 2008.

Murat Sensoy, Lance Kaplan, and Melih Kandemir. Evidential deep learning to quantify classification uncertainty. *Advances in neural information processing systems*, 31, 2018.

Oleksandr Shchur, Maximilian Mumme, Aleksandar Bojchevski, and Stephan Günnemann. Pitfalls of graph neural network evaluation. *arXiv preprint arXiv:1811.05868*, 2018.

Maximilian Stadler, Bertrand Charpentier, Simon Geisler, Daniel Zügner, and Stephan Günnemann. Graph posterior network: Bayesian predictive uncertainty for node classification. *Advances in Neural Information Processing Systems*, 34:18033–18048, 2021.

Xujiang Zhao, Feng Chen, Shu Hu, and Jin-Hee Cho. Uncertainty aware semi-supervised learning on graph data. *Advances in Neural Information Processing Systems*, 33:12827–12836, 2020.

A DATASET DETAILS

Table 6: Description of the considered graph datasets for node classification task.

	#Nodes	#Edges	#Classes	#Features
AmazonComputers	13,381	259,159	10	767
AmazonPhoto	7,484	126,530	8	745
CoauthorCS	18,333	163,788	15	6,805
CoauthorPhysics	34,493	495,924	5	8,415
CoraML	2,995	16,316	7	2,879
CiteSeer	3,327	4,732	6	3,703
PubMed	19,717	44,338	3	8,415

B EXPERIMENTAL SETUP

We evaluate all the methods discussed in Section 4 using the benchmark proposed in Section 3. Some of the considered methods require a specific training procedure consisting of several stages. Methods without Normalizing Flows, including **MLP**, **GNN**, **EnsGNN**, and **EN**, have only one training stage when the corresponding models train in the standard end-to-end mode. Methods with Normalizing Flows have at least three phases of training — warm-up of exclusively Flow neural layers, end-to-end training of the entire model, and finetuning the same Flow layers. In this regard, we follow the setup of Stadler et al. (2021). Further details can be found in Appendix B.

In our experiments, one training stage (i.e., warm-up, main training stage, or finetuning) takes 200 epochs, while the best loss value on the `Valid-In` part serves as a criterion for saving the model checkpoint. We exploit the standard Adam optimizer (Kingma & Ba, 2014) with a learning rate of 0.001 for Normalizing Flows and 0.0003 for other neural modules. For all the considered models, we utilize weight decay of 0.00001 and set $\lambda = 0.001$ in Expected Cross-Entropy.

As for model configurations, we set the hidden size of linear layers to 64, the number of layers in Normalizing Flows to 8 and the latent space dimension to 16. Also, Graph Propagation is performed in 5 steps with $\alpha = 0.2$.

C ADDITIONAL RESULTS

In this section, we provide additional experimental results.

Tables 7–9 are similar to Table 1 in the main text. They show how difficult our splits are for different models. These results are consistent: the feature-based split is the easiest for all models, while the split based on PPR is the hardest. Interestingly, the PPR-based split is very hard for the graph-agnostic **MLP**, which means that this graph-based shift also implies a noticeable shift in the feature space.

Table 10 is a detalization of Table 4, where we consider different distributional shift separately and add a random partition. Similarly, Table 11 detalizes Table 5.

Tables 12–15 aggregates `win/tie/loss` counts for all pairs of algorithms.

Table 16 compares all the algorithms in terms of ranks (averaged over the datasets).

Finally, Tables 17–23 provide the results for all the algorithms on all the datasets. All other aggregated results can be deduced from these tables.

D VISUALIZATION OF SPLIT STRATEGIES

In this section, we visualize the dataset split strategies for all the datasets, see Figures 2–8. Some graphs have multiple connected components — in that case, we keep only the largest one.

Table 7: Accuracy of **MLP** on ID vs OOD test subsets for every split strategy.

	Feature			PageRank			PPR		
	ID	OOD	Diff, %	ID	OOD	Diff, %	ID	OOD	Diff, %
AmazonComputers	75.80	77.69	+2.50	81.09	75.49	−6.91	81.18	50.23	−38.13
AmazonPhoto	89.44	84.42	−5.61	92.84	83.50	−10.06	89.67	39.69	−55.74
CoauthorCS	92.02	92.52	+0.54	93.97	92.95	−1.09	92.39	89.98	−2.61
CoauthorPhysics	95.36	95.58	+0.23	96.72	93.98	−2.84	96.55	87.25	−9.63
CoraML	75.18	70.78	−5.85	75.18	68.88	−8.38	72.04	52.50	−27.12
CiteSeer	65.35	64.54	−1.24	68.35	65.36	−4.37	68.17	52.37	−23.18
PubMed	85.29	84.50	−0.93	86.15	85.10	−1.21	84.43	84.04	−0.46

Table 8: Accuracy of **GPN** on ID vs OOD test subsets for every split strategy.

	Feature			PageRank			PPR		
	ID	OOD	Diff, %	ID	OOD	Diff, %	ID	OOD	Diff, %
AmazonComputers	88.05	89.19	+1.30	89.83	83.58	−6.95	88.63	65.84	−25.71
AmazonPhoto	92.89	91.32	−1.69	94.77	87.48	−7.69	89.78	65.25	−27.32
CoauthorCS	89.02	91.06	+2.29	92.14	87.99	−4.51	89.80	87.93	−2.08
CoauthorPhysics	95.45	95.03	−0.44	96.31	92.68	−3.77	95.93	88.90	−7.32
CoraML	84.01	84.72	+0.85	86.96	83.11	−4.43	84.48	75.81	−10.26
CiteSeer	67.63	68.10	+0.70	72.25	70.49	−2.44	74.95	51.60	−31.16
PubMed	88.95	86.38	−2.89	88.45	85.46	−3.37	86.12	86.03	−0.10

Table 9: Accuracy of **EnsGNN** on ID vs OOD test subsets for every split strategy.

	Feature			PageRank			PPR		
	ID	OOD	Diff, %	ID	OOD	Diff, %	ID	OOD	Diff, %
AmazonComputers	86.63	85.91	−0.83	88.08	83.53	−5.17	86.63	59.97	−30.77
AmazonPhoto	95.16	92.68	−2.61	97.65	89.77	−8.07	92.68	45.03	−51.41
CoauthorCS	92.58	94.00	+1.53	94.65	91.40	−3.44	92.80	91.86	−1.01
CoauthorPhysics	96.52	96.07	−0.47	97.56	94.49	−3.15	97.74	93.79	−4.04
CoraML	84.62	87.48	+3.38	90.30	83.31	−7.75	87.63	77.05	−12.07
CiteSeer	72.07	72.50	+0.60	74.77	71.90	−3.84	74.77	61.91	−17.21
PubMed	88.64	86.78	−2.10	89.20	84.06	−5.76	86.66	85.61	−1.22

| (a) Feature | (b) PageRank | (c) Personalized PageRank |

Figure 2: Visualization of data splits for CoraML dataset: ID is blue, OOD is red.

Table 10: `Win/tie/loss` counts for some pairs of Dirichlet-based methods across all the considered graph datasets.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
NatPN vs EN	Random	0/7/0	1/6/0	2/4/1	n/a
	Feature	1/6/0	2/5/0	2/4/1	1/1/5
	PageRank	1/6/0	1/6/0	3/4/0	2/1/4
	PPR	1/6/0	3/3/1	3/4/0	0/1/6
GPN vs NatGPN	Random	4/2/1	1/5/1	4/2/1	n/a
	Feature	5/1/1	1/6/0	5/0/2	2/5/0
	PageRank	5/2/0	3/3/1	5/1/1	5/1/1
	PPR	4/2/1	4/2/1	5/1/1	5/2/0
NatPN vs GPN	Random	5/0/2	6/1/0	5/1/1	n/a
	Feature	4/1/2	7/0/0	5/1/1	0/0/7
	PageRank	5/0/2	5/1/1	5/1/1	0/0/7
	PPR	3/1/3	2/4/1	3/1/3	0/0/7

Table 11: `Win/tie/loss` counts for ensembles vs the corresponding single models across all the considered graph datasets.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
EnsGPN vs GPN	Random	6/1/0	1/4/2	6/1/0	n/a
	Feature	2/4/1	3/4/0	6/1/0	0/7/0
	PageRank	4/3/0	1/5/1	4/3/0	4/3/0
	PPR	3/4/0	2/5/0	4/3/0	0/7/0
EnsNatPN vs NatPN	Random	3/4/0	2/5/0	4/3/0	n/a
	Feature	3/4/0	2/5/0	5/2/0	1/3/3
	PageRank	5/2/0	3/4/0	6/1/0	3/2/2
	PPR	6/1/0	1/6/0	4/3/0	1/4/2

Table 12: Pariwise `win/tie/loss` counts for Accuracy across all graph datasets and split strategies (except Random).

	MLP	GNN	EN	PN	NatPN	GPN	NatGPN	EnsGNN	EnsNatPN	EnsGPN
MLP	0/21/0	2/0/19	2/1/18	10/2/9	2/1/18	5/1/15	6/6/9	2/0/19	2/0/19	5/0/16
GNN	19/0/2	0/21/0	1/20/0	17/1/3	0/18/3	12/2/7	16/5/0	0/6/15	1/5/15	13/0/8
EN	18/1/2	0/20/1	0/21/0	16/1/4	0/18/3	12/3/6	14/7/0	0/7/14	0/6/15	12/1/8
PN	9/2/10	3/1/17	4/1/16	0/21/0	3/2/16	0/8/13	10/5/6	3/1/17	3/1/17	1/3/17
NatPN	18/1/2	3/18/0	3/18/0	16/2/3	0/21/0	12/2/7	17/4/0	3/6/12	0/7/14	12/2/7
GPN	15/1/5	7/2/12	6/3/12	13/8/0	7/2/12	0/21/0	14/5/2	6/1/14	6/1/14	1/11/9
NatGPN	9/6/6	0/5/16	0/7/14	6/5/10	0/4/17	2/5/14	0/21/0	0/1/20	0/1/20	4/2/15
EnsGNN	19/0/2	15/6/0	14/7/0	17/1/3	12/6/3	14/1/6	20/1/0	0/21/0	9/0/12	14/0/7
EnsNatPN	19/0/2	15/5/1	15/6/0	17/1/3	14/7/0	14/1/6	20/1/0	9/0/12	0/21/0	14/0/7
EnsGPN	16/0/5	8/0/13	8/1/12	17/3/1	7/2/12	9/11/1	15/2/4	7/0/14	7/0/14	0/21/0

Table 13: Pariwise `win/tie/loss` counts for PRR@TU across all graph datasets and split strategies (except Random).

	MLP	GNN	EN	PN	NatPN	GPN	NatGPN	EnsGNN	EnsNatPN	EnsGPN
MLP	0/21/0	0/2/19	0/2/19	2/8/11	1/2/18	3/5/13	3/9/9	1/0/20	1/0/20	6/0/15
GNN	19/2/0	0/21/0	0/21/0	7/11/3	0/15/6	10/8/3	13/7/1	1/17/3	0/12/9	14/1/6
EN	19/2/0	0/21/0	0/21/0	8/10/3	1/14/6	10/7/4	14/6/1	7/8/6	3/8/10	12/4/5
PN	11/8/2	3/11/7	3/10/8	0/21/0	0/11/10	8/6/7	7/10/4	3/8/10	0/9/12	8/5/8
NatPN	18/2/1	6/15/0	6/14/1	10/11/0	0/21/0	14/5/2	14/6/1	8/7/6	0/15/6	15/3/3
GPN	13/5/3	3/8/10	4/7/10	7/6/8	2/5/14	0/21/0	8/11/2	5/3/13	2/4/15	1/14/6
NatGPN	9/9/3	1/7/13	1/6/14	4/10/7	1/6/14	2/11/8	0/21/0	1/4/16	1/4/16	5/5/11
EnsGNN	20/0/1	3/17/1	6/8/7	10/8/3	6/7/8	13/3/5	16/4/1	0/21/0	9/0/12	14/0/7
EnsNatPN	20/0/1	9/12/0	10/8/3	12/9/0	6/15/0	15/4/2	16/4/1	12/0/9	0/21/0	16/0/5
EnsGPN	15/0/6	6/1/14	5/4/12	8/5/8	3/3/15	6/14/1	11/5/5	7/0/14	5/0/16	0/21/0

Table 14: Pariwise `win/tie/loss` counts for AUPRC@TU across all graph datasets and split strategies (except Random).

	MLP	GNN	EN	PN	NatPN	GPN	NatGPN	EnsGNN	EnsNatPN	EnsGPN
MLP	0/21/0	0/1/20	0/2/19	7/4/10	1/0/20	3/2/16	6/6/9	0/0/21	0/0/21	3/0/18
GNN	20/1/0	0/21/0	1/20/0	17/3/1	0/15/6	13/3/5	16/5/0	0/6/15	0/4/17	13/1/7
EN	19/2/0	0/20/1	0/21/0	16/1/4	1/12/8	13/3/5	18/3/0	0/4/17	0/2/19	13/0/8
PN	10/4/7	1/3/17	4/1/16	0/21/0	2/2/17	3/6/12	10/5/6	1/3/17	1/3/17	2/6/13
NatPN	20/0/1	6/15/0	8/12/1	17/2/2	0/21/0	13/3/5	17/4/0	6/2/13	0/6/15	13/2/6
GPN	16/2/3	5/3/13	5/3/13	12/6/3	5/3/13	0/21/0	15/2/4	4/2/15	5/0/16	0/7/14
NatGPN	9/6/6	0/5/16	0/3/18	6/5/10	0/4/17	4/2/15	0/21/0	0/2/19	0/1/20	5/0/16
EnsGNN	21/0/0	15/6/0	17/4/0	17/3/1	13/2/6	15/2/4	19/2/0	0/21/0	12/0/9	15/0/6
EnsNatPN	21/0/0	17/4/0	19/2/0	17/3/1	15/6/0	16/0/5	20/1/0	9/0/12	0/21/0	16/0/5
EnsGPN	18/0/3	7/1/13	8/0/13	13/6/2	6/2/13	14/7/0	16/0/5	6/0/15	5/0/16	0/21/0

Table 15: Pariwise `win/tie/loss` counts for AUROC@KU across all graph datasets and split strategies (except Random).

	MLP	GNN	EN	PN	NatPN	GPN	NatGPN	EnsGNN	EnsNatPN	EnsGPN
MLP	0/21/0	10/3/8	10/3/8	8/3/10	15/1/5	3/1/17	4/0/17	10/1/10	14/1/6	3/0/18
GNN	8/3/10	0/21/0	1/18/2	6/6/9	15/3/3	0/3/18	1/3/17	5/4/12	15/0/6	0/1/20
EN	8/3/10	2/18/1	0/21/0	5/7/9	15/3/3	0/3/18	1/6/14	7/4/10	15/1/5	0/1/20
PN	10/3/8	9/6/6	9/7/5	0/21/0	17/3/1	0/1/20	1/3/17	10/3/8	17/1/3	0/0/21
NatPN	5/1/15	3/3/15	3/3/15	1/3/17	0/21/0	0/0/21	0/3/18	4/1/16	7/9/5	0/0/21
GPN	17/1/3	18/3/0	18/3/0	20/1/0	21/0/0	0/21/0	12/8/1	20/1/0	21/0/0	0/17/4
NatGPN	17/0/4	17/3/1	14/6/1	17/3/1	18/3/0	1/8/12	0/21/0	17/2/2	19/1/1	3/6/12
EnsGNN	10/1/10	12/4/5	10/4/7	8/3/10	16/1/4	0/1/20	2/2/17	0/21/0	15/0/6	0/0/21
EnsNatPN	6/1/14	6/0/15	5/1/15	3/1/17	5/9/7	0/0/21	1/1/19	6/0/15	0/21/0	0/0/21
EnsGPN	18/0/3	20/1/0	20/1/0	21/0/0	21/0/0	4/17/0	12/6/3	21/0/0	21/0/0	0/21/0

Table 16: Average ranks of the considered methods across all datasets.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	MLP	8.4	8.7	8.9	*n/a*
	GNN	4.4	4.0	4.6	*n/a*
	EN	4.6	3.6	4.9	*n/a*
	PN	7.4	6.7	6.9	*n/a*
	NatPN	4.6	3.0	4.4	*n/a*
	GPN	6.6	7.7	6.9	*n/a*
	NatGPN	8.7	8.1	8.7	*n/a*
	EnsGNN	1.7	3.1	2.3	*n/a*
	EnsNatPN	3.0	2.3	1.9	*n/a*
	EnsGPN	5.6	7.7	5.7	*n/a*
Feature	MLP	8.7	8.3	9.1	4.9
	GNN	4.0	4.3	4.4	5.7
	EN	5.4	2.6	4.7	6.3
	PN	7.4	6.4	7.0	7.1
	NatPN	4.7	3.3	4.4	8.0
	GPN	6.3	8.4	6.9	2.4
	NatGPN	8.4	7.3	8.4	3.4
	EnsGNN	1.7	4.3	2.0	6.9
	EnsNatPN	3.0	2.7	2.1	8.1
	EnsGPN	5.3	7.4	5.9	2.1
PageRank	MLP	6.9	9.0	7.9	6.4
	GNN	5.0	4.3	4.7	7.9
	EN	5.3	3.3	5.0	7.9
	PN	8.0	6.6	7.3	4.7
	NatPN	4.3	3.4	4.3	7.7
	GPN	6.0	7.0	7.0	1.9
	NatGPN	9.0	7.6	8.6	2.7
	EnsGNN	2.9	3.1	2.1	6.9
	EnsNatPN	2.6	3.6	2.0	7.6
	EnsGPN	5.1	7.1	6.1	1.4
PPR	MLP	8.6	9.0	9.0	6.9
	GNN	5.1	5.3	5.6	6.1
	EN	6.4	5.6	6.1	5.6
	PN	7.4	7.3	7.6	6.4
	NatPN	4.9	3.7	4.3	9.0
	GPN	5.0	5.0	4.9	1.6
	NatGPN	8.4	7.6	8.4	3.7
	EnsGNN	3.0	4.9	3.1	5.0
	EnsNatPN	2.4	3.1	2.6	9.3
	EnsGPN	3.7	3.6	3.4	1.4

(a) Feature   (b) PageRank   (c) Personalized PageRank

Figure 3: Visualization of data splits for CiteSeer dataset: ID is blue, OOD is red.

Table 17: Experiment results on **AmazonComputers** dataset.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	MLP	78.44 ± 0.57	58.44 ± 1.88	88.32 ± 0.27	n/a
	GNN	86.33 ± 0.56	63.26 ± 1.49	93.80 ± 0.27	n/a
	EN	83.73 ± 1.20	67.42 ± 3.81	92.93 ± 0.28	n/a
	PN	88.18 ± 0.23	65.19 ± 2.06	94.98 ± 0.22	n/a
	NatPN	85.75 ± 1.45	65.22 ± 3.38	93.73 ± 0.45	n/a
	GPN	87.70 ± 0.14	59.35 ± 0.25	94.10 ± 0.08	n/a
	NatGPN	82.83 ± 1.31	56.45 ± 2.69	90.85 ± 0.88	n/a
	EnsGNN	$86.67 \pm n/a$	$64.22 \pm n/a$	$94.09 \pm n/a$	n/a
	EnsNatPN	$86.67 \pm n/a$	$64.52 \pm n/a$	$94.12 \pm n/a$	n/a
	EnsGPN	$87.99 \pm n/a$	$58.91 \pm n/a$	$94.22 \pm n/a$	n/a
Feature	MLP	77.31 ± 0.41	63.17 ± 1.23	88.39 ± 0.17	44.38 ± 0.26
	GNN	84.87 ± 1.08	68.37 ± 3.64	93.66 ± 0.23	47.45 ± 0.52
	EN	82.83 ± 0.76	72.01 ± 2.81	93.07 ± 0.33	47.38 ± 0.40
	PN	88.39 ± 0.50	64.29 ± 2.33	94.98 ± 0.44	51.53 ± 0.33
	NatPN	85.34 ± 1.26	65.52 ± 4.06	93.56 ± 0.20	51.19 ± 0.96
	GPN	88.97 ± 0.21	56.81 ± 1.16	94.54 ± 0.12	53.33 ± 0.31
	NatGPN	81.87 ± 1.34	63.70 ± 6.12	91.35 ± 0.58	53.46 ± 0.57
	EnsGNN	$86.05 \pm n/a$	$67.15 \pm n/a$	$94.11 \pm n/a$	$48.36 \pm n/a$
	EnsNatPN	$86.29 \pm n/a$	$64.76 \pm n/a$	$93.95 \pm n/a$	$51.92 \pm n/a$
	EnsGPN	$89.34 \pm n/a$	$56.23 \pm n/a$	$94.70 \pm n/a$	$53.46 \pm n/a$
PageRank	MLP	76.61 ± 0.42	55.61 ± 1.97	86.58 ± 0.27	59.34 ± 0.34
	GNN	83.46 ± 0.62	66.38 ± 0.91	92.62 ± 0.35	56.53 ± 0.68
	EN	81.72 ± 1.14	68.72 ± 2.71	91.99 ± 0.43	56.32 ± 1.33
	PN	84.70 ± 0.69	65.96 ± 0.97	93.25 ± 0.37	65.04 ± 1.96
	NatPN	83.03 ± 1.28	66.84 ± 2.34	92.45 ± 0.41	48.01 ± 2.04
	GPN	84.83 ± 0.22	59.26 ± 1.69	92.46 ± 0.23	90.58 ± 0.49
	NatGPN	78.44 ± 1.16	57.22 ± 3.61	88.10 ± 1.33	87.31 ± 2.33
	EnsGNN	$84.44 \pm n/a$	$65.98 \pm n/a$	$93.11 \pm n/a$	$61.00 \pm n/a$
	EnsNatPN	$84.44 \pm n/a$	$65.73 \pm n/a$	$93.08 \pm n/a$	$44.68 \pm n/a$
	EnsGPN	$85.05 \pm n/a$	$58.39 \pm n/a$	$92.48 \pm n/a$	$91.59 \pm n/a$
PPR	MLP	56.42 ± 3.97	54.18 ± 3.29	69.68 ± 3.26	79.23 ± 0.76
	GNN	64.30 ± 0.93	70.18 ± 3.24	80.41 ± 1.02	79.69 ± 1.07
	EN	63.44 ± 0.84	66.23 ± 3.19	78.79 ± 1.23	81.23 ± 0.83
	PN	68.11 ± 1.14	61.39 ± 4.21	81.44 ± 0.86	69.79 ± 2.28
	NatPN	64.10 ± 1.26	69.25 ± 2.63	80.03 ± 1.21	53.22 ± 6.98
	GPN	70.40 ± 0.31	73.80 ± 1.84	85.78 ± 0.30	93.20 ± 0.63
	NatGPN	58.25 ± 4.36	51.29 ± 8.28	70.60 ± 5.99	85.60 ± 3.98
	EnsGNN	$65.30 \pm n/a$	$71.37 \pm n/a$	$81.48 \pm n/a$	$79.78 \pm n/a$
	EnsNatPN	$65.30 \pm n/a$	$69.48 \pm n/a$	$81.05 \pm n/a$	$51.25 \pm n/a$
	EnsGPN	$70.77 \pm n/a$	$74.65 \pm n/a$	$86.21 \pm n/a$	$93.38 \pm n/a$

(a) Feature   (b) PageRank   (c) Personalized PageRank

Figure 4: Visualization of data splits for PubMed dataset: ID is blue, OOD is red.

Table 18: Experiment results on **AmazonPhoto** dataset.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	MLP	89.49 ± 0.25	73.44 ± 0.65	96.40 ± 0.06	n/a
	GNN	94.34 ± 0.24	83.81 ± 1.38	98.82 ± 0.10	n/a
	EN	94.25 ± 0.19	83.18 ± 1.53	98.76 ± 0.10	n/a
	PN	93.01 ± 0.27	81.37 ± 1.28	98.30 ± 0.08	n/a
	NatPN	94.04 ± 0.15	83.96 ± 1.53	98.75 ± 0.05	n/a
	GPN	92.67 ± 0.13	67.44 ± 1.36	97.25 ± 0.08	n/a
	NatGPN	89.09 ± 4.56	73.52 ± 3.20	96.10 ± 2.29	n/a
	EnsGNN	$94.61 \pm n/a$	$85.78 \pm n/a$	$98.99 \pm n/a$	n/a
	EnsNatPN	$94.51 \pm n/a$	$84.87 \pm n/a$	$98.91 \pm n/a$	n/a
	EnsGPN	$92.92 \pm n/a$	$67.50 \pm n/a$	$97.36 \pm n/a$	n/a
Feature	MLP	85.43 ± 0.55	72.02 ± 1.41	94.40 ± 0.14	57.38 ± 0.27
	GNN	92.76 ± 0.63	80.34 ± 1.63	98.16 ± 0.14	59.36 ± 0.39
	EN	91.60 ± 0.57	82.66 ± 1.75	97.96 ± 0.22	58.41 ± 2.29
	PN	91.63 ± 0.45	77.16 ± 2.06	97.55 ± 0.21	57.29 ± 1.10
	NatPN	92.15 ± 0.33	80.57 ± 1.29	97.98 ± 0.16	49.08 ± 1.57
	GPN	91.63 ± 0.37	74.08 ± 0.85	97.31 ± 0.09	61.70 ± 0.49
	NatGPN	87.83 ± 1.31	77.90 ± 3.96	96.12 ± 0.91	59.80 ± 0.32
	EnsGNN	$93.18 \pm n/a$	$81.62 \pm n/a$	$98.37 \pm n/a$	$60.81 \pm n/a$
	EnsNatPN	$92.44 \pm n/a$	$81.86 \pm n/a$	$98.16 \pm n/a$	$46.46 \pm n/a$
	EnsGPN	$91.76 \pm n/a$	$75.26 \pm n/a$	$97.45 \pm n/a$	$61.75 \pm n/a$
PageRank	MLP	85.36 ± 0.10	66.95 ± 0.59	93.73 ± 0.10	62.74 ± 0.25
	GNN	90.57 ± 0.24	75.05 ± 0.75	96.98 ± 0.13	63.09 ± 0.77
	EN	90.33 ± 0.37	75.18 ± 1.10	96.90 ± 0.13	62.20 ± 0.95
	PN	88.26 ± 0.21	73.56 ± 1.40	95.88 ± 0.20	66.92 ± 1.18
	NatPN	90.04 ± 0.38	75.31 ± 1.00	96.79 ± 0.22	47.23 ± 2.53
	GPN	88.94 ± 0.64	67.40 ± 0.86	95.57 ± 0.26	90.45 ± 1.76
	NatGPN	80.45 ± 6.19	70.93 ± 1.25	91.40 ± 3.66	82.22 ± 4.95
	EnsGNN	$91.35 \pm n/a$	$74.81 \pm n/a$	$97.26 \pm n/a$	$65.54 \pm n/a$
	EnsNatPN	$90.75 \pm n/a$	$74.69 \pm n/a$	$97.02 \pm n/a$	$42.47 \pm n/a$
	EnsGPN	$89.75 \pm n/a$	$66.27 \pm n/a$	$95.85 \pm n/a$	$92.39 \pm n/a$
PPR	MLP	49.68 ± 0.80	45.47 ± 3.75	61.05 ± 0.60	78.29 ± 1.27
	GNN	53.65 ± 2.91	54.98 ± 10.32	67.28 ± 3.57	86.94 ± 1.93
	EN	52.89 ± 3.08	47.70 ± 6.44	64.74 ± 3.15	88.03 ± 1.88
	PN	60.22 ± 2.81	50.42 ± 11.67	72.29 ± 3.33	82.47 ± 2.45
	NatPN	53.15 ± 1.93	62.85 ± 4.67	68.78 ± 1.24	49.36 ± 11.49
	GPN	70.16 ± 0.36	33.12 ± 16.84	77.10 ± 3.51	91.90 ± 3.24
	NatGPN	48.62 ± 2.94	77.97 ± 6.97	68.04 ± 2.65	91.17 ± 1.60
	EnsGNN	$54.56 \pm n/a$	$58.28 \pm n/a$	$69.01 \pm n/a$	$89.05 \pm n/a$
	EnsNatPN	$55.24 \pm n/a$	$62.02 \pm n/a$	$70.58 \pm n/a$	$43.71 \pm n/a$
	EnsGPN	$70.30 \pm n/a$	$34.13 \pm n/a$	$77.43 \pm n/a$	$92.21 \pm n/a$

(a) Feature   (b) PageRank   (c) Personalized PageRank

Figure 5: Visualization of data splits for CoauthorCS dataset: ID is blue, OOD is red.

Table 19: Experiment results on **CoauthorCS** dataset.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	MLP	93.28 ± 0.11	64.47 ± 1.27	97.32 ± 0.05	n/a
	GNN	93.41 ± 0.08	73.37 ± 1.09	97.93 ± 0.05	n/a
	EN	93.33 ± 0.12	74.24 ± 0.84	97.95 ± 0.05	n/a
	PN	90.29 ± 0.78	75.42 ± 0.98	96.90 ± 0.29	n/a
	NatPN	93.42 ± 0.08	77.37 ± 0.34	98.18 ± 0.04	n/a
	GPN	90.51 ± 0.15	65.11 ± 0.84	96.10 ± 0.10	n/a
	NatGPN	88.91 ± 0.28	63.57 ± 1.44	95.18 ± 0.24	n/a
	EnsGNN	$93.61 \pm n/a$	$73.36 \pm n/a$	$98.00 \pm n/a$	n/a
	EnsNatPN	$93.50 \pm n/a$	$77.84 \pm n/a$	$98.23 \pm n/a$	n/a
	EnsGPN	$90.89 \pm n/a$	$64.94 \pm n/a$	$96.27 \pm n/a$	n/a
Feature	MLP	92.42 ± 0.20	62.88 ± 1.39	96.83 ± 0.08	64.00 ± 0.40
	GNN	93.48 ± 0.11	71.83 ± 0.70	97.86 ± 0.04	50.67 ± 0.82
	EN	93.44 ± 0.07	72.68 ± 0.63	97.90 ± 0.02	51.47 ± 0.95
	PN	89.72 ± 0.52	76.57 ± 1.28	96.78 ± 0.24	50.25 ± 0.68
	NatPN	93.60 ± 0.09	75.68 ± 0.31	98.13 ± 0.03	44.86 ± 1.22
	GPN	90.65 ± 0.18	66.68 ± 0.39	96.30 ± 0.08	60.59 ± 0.48
	NatGPN	88.07 ± 0.43	67.63 ± 2.67	95.18 ± 0.20	61.80 ± 0.87
	EnsGNN	$93.72 \pm n/a$	$71.61 \pm n/a$	$97.93 \pm n/a$	$49.91 \pm n/a$
	EnsNatPN	$93.64 \pm n/a$	$76.41 \pm n/a$	$98.19 \pm n/a$	$43.61 \pm n/a$
	EnsGPN	$91.00 \pm n/a$	$67.16 \pm n/a$	$96.50 \pm n/a$	$60.47 \pm n/a$
PageRank	MLP	93.15 ± 0.25	60.50 ± 1.14	97.01 ± 0.08	68.00 ± 0.38
	GNN	92.03 ± 0.12	70.03 ± 0.58	97.17 ± 0.06	52.17 ± 0.29
	EN	92.01 ± 0.15	70.48 ± 0.83	97.19 ± 0.05	52.92 ± 0.50
	PN	88.46 ± 0.66	74.08 ± 1.62	96.02 ± 0.29	60.17 ± 0.88
	NatPN	92.12 ± 0.05	74.94 ± 0.37	97.56 ± 0.03	48.79 ± 1.89
	GPN	88.82 ± 0.40	67.52 ± 0.64	95.53 ± 0.18	82.05 ± 2.57
	NatGPN	86.51 ± 0.37	61.35 ± 1.43	93.67 ± 0.30	79.99 ± 1.09
	EnsGNN	$92.05 \pm n/a$	$70.57 \pm n/a$	$97.21 \pm n/a$	$51.54 \pm n/a$
	EnsNatPN	$92.22 \pm n/a$	$75.38 \pm n/a$	$97.63 \pm n/a$	$48.16 \pm n/a$
	EnsGPN	$89.12 \pm n/a$	$68.56 \pm n/a$	$95.77 \pm n/a$	$80.38 \pm n/a$
PPR	MLP	90.46 ± 0.35	61.93 ± 1.70	95.81 ± 0.10	73.96 ± 1.06
	GNN	91.84 ± 0.13	67.13 ± 0.82	96.87 ± 0.08	66.72 ± 1.59
	EN	91.77 ± 0.09	67.66 ± 0.81	96.88 ± 0.08	67.42 ± 2.19
	PN	85.21 ± 0.79	73.32 ± 1.56	94.44 ± 0.56	66.03 ± 2.59
	NatPN	92.29 ± 0.08	74.19 ± 0.79	97.57 ± 0.08	42.36 ± 2.24
	GPN	88.31 ± 0.38	71.15 ± 0.29	95.65 ± 0.18	88.38 ± 0.78
	NatGPN	85.07 ± 0.48	63.26 ± 2.25	93.10 ± 0.39	80.75 ± 1.98
	EnsGNN	$92.05 \pm n/a$	$66.82 \pm n/a$	$96.94 \pm n/a$	$71.42 \pm n/a$
	EnsNatPN	$92.41 \pm n/a$	$74.70 \pm n/a$	$97.65 \pm n/a$	$40.08 \pm n/a$
	EnsGPN	$88.74 \pm n/a$	$72.05 \pm n/a$	$95.94 \pm n/a$	$88.81 \pm n/a$

(a) Feature	(b) PageRank	(c) Personalized PageRank

Figure 6: Visualization of data splits for CoauthorPhysics dataset: ID is blue, OOD is red.

Table 20: Experiment results on **CoauthorPhysics** dataset.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	MLP	95.53 ± 0.03	75.21 ± 0.34	98.74 ± 0.02	n/a
	GNN	96.32 ± 0.06	81.17 ± 0.47	99.20 ± 0.01	n/a
	EN	96.35 ± 0.04	81.01 ± 0.92	99.20 ± 0.03	n/a
	PN	95.28 ± 0.26	80.14 ± 1.01	98.88 ± 0.10	n/a
	NatPN	96.31 ± 0.05	82.37 ± 0.61	99.24 ± 0.02	n/a
	GPN	95.32 ± 0.08	79.13 ± 0.44	98.85 ± 0.03	n/a
	NatGPN	94.37 ± 0.32	79.53 ± 1.17	98.59 ± 0.16	n/a
	EnsGNN	$96.33 \pm n/a$	$81.47 \pm n/a$	$99.21 \pm n/a$	n/a
	EnsNatPN	$96.30 \pm n/a$	$82.77 \pm n/a$	$99.25 \pm n/a$	n/a
	EnsGPN	$95.45 \pm n/a$	$79.41 \pm n/a$	$98.90 \pm n/a$	n/a
Feature	MLP	95.54 ± 0.03	75.55 ± 0.27	98.76 ± 0.02	52.04 ± 0.08
	GNN	96.16 ± 0.05	81.91 ± 0.73	99.18 ± 0.03	51.82 ± 0.25
	EN	96.13 ± 0.05	82.17 ± 1.06	99.19 ± 0.04	51.73 ± 0.46
	PN	95.31 ± 0.16	80.88 ± 1.07	98.93 ± 0.08	51.48 ± 0.57
	NatPN	96.09 ± 0.06	84.92 ± 0.27	99.28 ± 0.02	48.32 ± 0.54
	GPN	95.12 ± 0.07	82.13 ± 0.57	98.93 ± 0.02	54.36 ± 0.22
	NatGPN	93.92 ± 0.36	80.34 ± 0.79	98.50 ± 0.15	54.30 ± 0.31
	EnsGNN	$96.16 \pm n/a$	$82.27 \pm n/a$	$99.20 \pm n/a$	$51.11 \pm n/a$
	EnsNatPN	$96.10 \pm n/a$	$85.17 \pm n/a$	$99.29 \pm n/a$	$47.89 \pm n/a$
	EnsGPN	$95.15 \pm n/a$	$82.75 \pm n/a$	$98.97 \pm n/a$	$54.50 \pm n/a$
PageRank	MLP	94.53 ± 0.09	72.39 ± 0.40	98.27 ± 0.03	73.99 ± 0.28
	GNN	95.06 ± 0.07	76.52 ± 0.27	98.65 ± 0.02	60.23 ± 0.20
	EN	95.07 ± 0.05	76.70 ± 0.82	98.66 ± 0.03	61.02 ± 1.03
	PN	93.43 ± 0.39	76.39 ± 1.30	98.12 ± 0.16	65.12 ± 1.62
	NatPN	95.08 ± 0.06	78.15 ± 0.69	98.73 ± 0.03	47.06 ± 3.39
	GPN	93.41 ± 0.08	75.97 ± 0.33	98.09 ± 0.04	78.31 ± 0.88
	NatGPN	91.68 ± 0.58	72.12 ± 1.44	97.17 ± 0.35	82.95 ± 3.02
	EnsGNN	$95.11 \pm n/a$	$76.61 \pm n/a$	$98.67 \pm n/a$	$58.45 \pm n/a$
	EnsNatPN	$95.11 \pm n/a$	$78.39 \pm n/a$	$98.75 \pm n/a$	$45.49 \pm n/a$
	EnsGPN	$93.56 \pm n/a$	$76.09 \pm n/a$	$98.14 \pm n/a$	$78.72 \pm n/a$
PPR	MLP	89.11 ± 0.24	45.53 ± 2.19	93.53 ± 0.29	91.39 ± 0.19
	GNN	94.49 ± 0.15	57.61 ± 2.31	97.49 ± 0.13	90.71 ± 0.12
	EN	94.26 ± 0.34	54.63 ± 2.40	97.22 ± 0.21	90.69 ± 0.34
	PN	88.58 ± 1.89	59.44 ± 4.95	94.60 ± 0.92	81.37 ± 4.48
	NatPN	94.53 ± 0.10	68.02 ± 0.75	98.05 ± 0.07	34.41 ± 6.64
	GPN	90.31 ± 0.71	67.05 ± 0.76	96.17 ± 0.37	91.95 ± 1.21
	NatGPN	88.29 ± 1.37	49.35 ± 2.15	93.39 ± 0.90	86.99 ± 1.45
	EnsGNN	$94.58 \pm n/a$	$57.81 \pm n/a$	$97.54 \pm n/a$	$90.42 \pm n/a$
	EnsNatPN	$94.67 \pm n/a$	$67.86 \pm n/a$	$98.09 \pm n/a$	$27.08 \pm n/a$
	EnsGPN	$90.63 \pm n/a$	$68.17 \pm n/a$	$96.42 \pm n/a$	$92.58 \pm n/a$

(a) Feature	(b) PageRank	(c) Personalized PageRank

Figure 7: Visualization of data splits for CoauthorPhysics dataset: ID is blue, OOD is red.

Table 21: Experiment results on **CoraML** dataset.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	MLP	72.08 ± 0.65	57.70 ± 1.27	83.69 ± 0.41	n/a
	GNN	86.95 ± 0.33	70.63 ± 1.64	94.97 ± 0.12	n/a
	EN	87.01 ± 0.33	70.14 ± 2.07	94.94 ± 0.13	n/a
	PN	78.81 ± 0.79	62.59 ± 3.10	89.26 ± 0.71	n/a
	NatPN	87.08 ± 0.66	70.83 ± 2.21	95.06 ± 0.12	n/a
	GPN	85.42 ± 0.17	65.41 ± 0.94	93.57 ± 0.08	n/a
	NatGPN	86.28 ± 0.18	63.90 ± 1.44	93.84 ± 0.17	n/a
	EnsGNN	$87.31 \pm n/a$	$71.37 \pm n/a$	$95.22 \pm n/a$	n/a
	EnsNatPN	$87.44 \pm n/a$	$71.43 \pm n/a$	$95.29 \pm n/a$	n/a
	EnsGPN	$85.64 \pm n/a$	$64.25 \pm n/a$	$93.54 \pm n/a$	n/a
Feature	MLP	71.66 ± 1.08	54.74 ± 1.24	82.78 ± 0.60	62.42 ± 0.49
	GNN	86.31 ± 0.44	66.29 ± 2.42	94.15 ± 0.11	52.56 ± 0.55
	EN	86.25 ± 0.33	66.77 ± 1.59	94.17 ± 0.10	52.70 ± 0.38
	PN	77.61 ± 1.77	62.83 ± 3.97	88.52 ± 1.21	49.55 ± 0.67
	NatPN	86.09 ± 0.32	67.00 ± 2.20	94.12 ± 0.24	43.51 ± 1.20
	GPN	84.58 ± 0.22	61.94 ± 1.00	92.66 ± 0.17	54.97 ± 0.88
	NatGPN	85.16 ± 0.40	63.19 ± 1.60	93.14 ± 0.24	55.16 ± 0.80
	EnsGNN	$86.91 \pm n/a$	$66.17 \pm n/a$	$94.44 \pm n/a$	$50.77 \pm n/a$
	EnsNatPN	$86.57 \pm n/a$	$66.70 \pm n/a$	$94.33 \pm n/a$	$40.67 \pm n/a$
	EnsGPN	$84.30 \pm n/a$	$62.47 \pm n/a$	$92.57 \pm n/a$	$54.24 \pm n/a$
PageRank	MLP	70.14 ± 0.66	56.09 ± 1.64	81.89 ± 0.23	56.16 ± 0.61
	GNN	84.29 ± 0.14	66.28 ± 1.00	93.07 ± 0.09	53.23 ± 0.65
	EN	84.57 ± 0.36	65.17 ± 1.12	93.07 ± 0.07	53.27 ± 0.59
	PN	74.96 ± 1.50	56.41 ± 3.92	85.53 ± 1.57	59.91 ± 1.52
	NatPN	84.82 ± 0.30	64.28 ± 1.05	93.10 ± 0.10	59.95 ± 2.45
	GPN	83.87 ± 0.28	65.16 ± 1.11	92.69 ± 0.24	82.48 ± 2.87
	NatGPN	83.74 ± 0.28	66.33 ± 1.04	92.77 ± 0.22	74.32 ± 1.97
	EnsGNN	$84.70 \pm n/a$	$67.09 \pm n/a$	$93.40 \pm n/a$	$54.17 \pm n/a$
	EnsNatPN	$84.97 \pm n/a$	$65.42 \pm n/a$	$93.32 \pm n/a$	$65.41 \pm n/a$
	EnsGPN	$83.77 \pm n/a$	$64.28 \pm n/a$	$92.51 \pm n/a$	$81.42 \pm n/a$
PPR	MLP	56.41 ± 0.41	37.24 ± 0.92	65.56 ± 0.47	63.84 ± 0.53
	GNN	77.76 ± 0.60	58.02 ± 3.22	87.79 ± 0.50	69.36 ± 0.82
	EN	77.33 ± 0.72	59.21 ± 2.36	87.71 ± 0.35	68.21 ± 0.94
	PN	59.39 ± 2.60	51.36 ± 6.21	71.73 ± 3.51	72.71 ± 4.29
	NatPN	78.40 ± 0.74	60.01 ± 1.57	88.56 ± 0.34	58.37 ± 4.00
	GPN	77.54 ± 1.46	59.74 ± 1.79	87.93 ± 1.04	92.77 ± 0.77
	NatGPN	77.49 ± 1.37	56.85 ± 3.25	87.39 ± 1.24	84.86 ± 1.65
	EnsGNN	$79.16 \pm n/a$	$56.34 \pm n/a$	$88.45 \pm n/a$	$73.52 \pm n/a$
	EnsNatPN	$79.23 \pm n/a$	$59.96 \pm n/a$	$89.09 \pm n/a$	$63.61 \pm n/a$
	EnsGPN	$78.62 \pm n/a$	$60.95 \pm n/a$	$88.87 \pm n/a$	$92.32 \pm n/a$

(a) Feature   (b) PageRank   (c) Personalized PageRank

Figure 8: Visualization of data splits for AmazonComputers dataset: ID is blue, OOD is red.

Table 22: Experiment results on **CiteSeer** dataset.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	MLP	66.57 ± 0.33	53.58 ± 0.56	78.50 ± 0.27	n/a
	GNN	72.39 ± 0.44	56.19 ± 1.65	83.62 ± 0.16	n/a
	EN	72.34 ± 0.53	56.17 ± 1.67	83.58 ± 0.20	n/a
	PN	64.44 ± 0.86	48.78 ± 1.91	75.61 ± 0.86	n/a
	NatPN	72.52 ± 0.49	55.19 ± 1.83	83.52 ± 0.41	n/a
	GPN	69.94 ± 0.42	50.41 ± 1.42	80.54 ± 0.22	n/a
	NatGPN	70.88 ± 0.58	50.44 ± 0.64	81.29 ± 0.56	n/a
	EnsGNN	$73.50 \pm n/a$	$55.15 \pm n/a$	$84.24 \pm n/a$	n/a
	EnsNatPN	$73.20 \pm n/a$	$53.89 \pm n/a$	$83.77 \pm n/a$	n/a
	EnsGPN	$70.43 \pm n/a$	$49.69 \pm n/a$	$80.78 \pm n/a$	n/a
Feature	MLP	64.70 ± 0.36	50.93 ± 1.11	76.33 ± 0.17	55.84 ± 0.19
	GNN	71.37 ± 0.23	49.62 ± 1.14	81.51 ± 0.26	51.09 ± 0.91
	EN	71.26 ± 0.39	49.82 ± 1.60	81.46 ± 0.29	50.96 ± 1.27
	PN	62.21 ± 0.49	48.65 ± 2.11	73.65 ± 0.48	50.70 ± 0.24
	NatPN	71.50 ± 0.56	49.10 ± 0.67	81.51 ± 0.35	47.09 ± 1.81
	GPN	68.00 ± 0.46	42.05 ± 1.82	77.15 ± 0.17	51.76 ± 0.37
	NatGPN	69.15 ± 0.32	44.22 ± 1.07	78.58 ± 0.16	50.30 ± 1.40
	EnsGNN	$72.42 \pm n/a$	$47.84 \pm n/a$	$81.97 \pm n/a$	$50.18 \pm n/a$
	EnsNatPN	$72.12 \pm n/a$	$48.70 \pm n/a$	$81.91 \pm n/a$	$45.65 \pm n/a$
	EnsGPN	$68.27 \pm n/a$	$42.19 \pm n/a$	$77.41 \pm n/a$	$51.62 \pm n/a$
PageRank	MLP	65.96 ± 0.34	46.36 ± 0.54	76.37 ± 0.22	54.33 ± 0.23
	GNN	72.03 ± 0.31	51.64 ± 1.39	82.44 ± 0.19	50.82 ± 0.43
	EN	71.79 ± 0.23	52.28 ± 1.41	82.38 ± 0.16	50.73 ± 0.78
	PN	62.51 ± 0.98	46.12 ± 2.34	73.32 ± 0.65	56.33 ± 1.41
	NatPN	72.62 ± 0.10	50.76 ± 1.02	82.71 ± 0.17	54.78 ± 1.55
	GPN	70.84 ± 0.46	41.23 ± 2.81	79.36 ± 0.26	74.78 ± 1.42
	NatGPN	71.65 ± 0.39	42.54 ± 1.84	80.29 ± 0.34	59.46 ± 3.89
	EnsGNN	$72.48 \pm n/a$	$52.17 \pm n/a$	$82.88 \pm n/a$	$52.31 \pm n/a$
	EnsNatPN	$72.90 \pm n/a$	$51.35 \pm n/a$	$83.04 \pm n/a$	$57.63 \pm n/a$
	EnsGPN	$70.91 \pm n/a$	$42.07 \pm n/a$	$79.59 \pm n/a$	$77.27 \pm n/a$
PPR	MLP	55.53 ± 0.28	39.66 ± 1.44	65.32 ± 0.23	69.37 ± 0.39
	GNN	62.22 ± 0.60	44.67 ± 2.44	72.72 ± 0.68	81.83 ± 0.54
	EN	62.18 ± 0.91	44.78 ± 1.08	72.70 ± 0.89	80.35 ± 0.77
	PN	46.30 ± 2.63	33.99 ± 8.13	54.74 ± 4.41	80.83 ± 1.27
	NatPN	63.09 ± 0.58	41.88 ± 1.41	72.84 ± 0.37	47.42 ± 6.69
	GPN	56.27 ± 1.23	40.11 ± 3.87	66.14 ± 0.75	93.34 ± 4.34
	NatGPN	64.00 ± 1.40	36.33 ± 0.48	72.37 ± 1.17	88.78 ± 4.75
	EnsGNN	$64.48 \pm n/a$	$43.41 \pm n/a$	$74.42 \pm n/a$	$85.18 \pm n/a$
	EnsNatPN	$64.54 \pm n/a$	$42.71 \pm n/a$	$74.32 \pm n/a$	$44.31 \pm n/a$
	EnsGPN	$59.38 \pm n/a$	$37.66 \pm n/a$	$68.46 \pm n/a$	$92.86 \pm n/a$

Table 23: Experiment results on **PubMed** dataset.

		Accuracy	PRR@TU	AUPRC@TU	AUROC@KU
Random	MLP	85.59 ± 0.20	58.82 ± 0.43	92.85 ± 0.06	n/a
	GNN	86.74 ± 0.22	64.45 ± 0.74	94.15 ± 0.12	n/a
	EN	86.90 ± 0.28	64.78 ± 0.77	94.27 ± 0.12	n/a
	PN	85.89 ± 0.38	57.80 ± 1.45	92.89 ± 0.17	n/a
	NatPN	86.58 ± 0.31	63.84 ± 0.84	94.00 ± 0.11	n/a
	GPN	87.34 ± 0.23	63.46 ± 0.41	94.36 ± 0.11	n/a
	NatGPN	85.08 ± 0.81	60.22 ± 1.96	92.71 ± 0.72	n/a
	EnsGNN	$87.43 \pm n/a$	$66.12 \pm n/a$	$94.70 \pm n/a$	n/a
	EnsNatPN	$87.15 \pm n/a$	$65.21 \pm n/a$	$94.45 \pm n/a$	n/a
	EnsGPN	$87.39 \pm n/a$	$64.30 \pm n/a$	$94.48 \pm n/a$	n/a
Feature	MLP	84.66 ± 0.14	60.50 ± 0.34	92.52 ± 0.04	48.63 ± 0.09
	GNN	86.32 ± 0.17	65.27 ± 0.39	94.03 ± 0.06	50.50 ± 0.24
	EN	86.36 ± 0.30	65.81 ± 1.03	94.11 ± 0.06	50.27 ± 0.31
	PN	85.46 ± 0.19	58.47 ± 1.87	92.73 ± 0.24	49.03 ± 0.84
	NatPN	86.15 ± 0.17	64.99 ± 0.40	93.91 ± 0.06	50.73 ± 0.28
	GPN	86.89 ± 0.29	62.46 ± 0.73	94.00 ± 0.14	52.47 ± 0.37
	NatGPN	84.76 ± 1.06	60.53 ± 1.60	92.56 ± 0.84	50.83 ± 0.28
	EnsGNN	$87.15 \pm n/a$	$66.24 \pm n/a$	$94.57 \pm n/a$	$50.33 \pm n/a$
	EnsNatPN	$86.67 \pm n/a$	$66.59 \pm n/a$	$94.36 \pm n/a$	$51.47 \pm n/a$
	EnsGPN	$87.17 \pm n/a$	$62.69 \pm n/a$	$94.18 \pm n/a$	$52.77 \pm n/a$
PageRank	MLP	85.31 ± 0.11	58.78 ± 0.43	92.68 ± 0.05	51.32 ± 0.09
	GNN	84.45 ± 0.20	60.85 ± 0.86	92.44 ± 0.19	55.99 ± 0.39
	EN	84.77 ± 0.33	60.97 ± 0.57	92.64 ± 0.21	56.80 ± 0.38
	PN	83.12 ± 0.25	52.37 ± 1.29	90.47 ± 0.23	66.37 ± 3.42
	NatPN	84.29 ± 0.38	61.00 ± 0.40	92.37 ± 0.20	56.87 ± 1.97
	GPN	86.06 ± 0.18	63.96 ± 0.42	93.73 ± 0.12	82.67 ± 0.59
	NatGPN	82.66 ± 0.79	59.50 ± 2.85	91.17 ± 0.91	74.55 ± 1.56
	EnsGNN	$85.09 \pm n/a$	$63.43 \pm n/a$	$93.14 \pm n/a$	$60.77 \pm n/a$
	EnsNatPN	$84.88 \pm n/a$	$62.66 \pm n/a$	$92.92 \pm n/a$	$61.38 \pm n/a$
	EnsGPN	$86.41 \pm n/a$	$64.25 \pm n/a$	$93.95 \pm n/a$	$83.77 \pm n/a$
PPR	MLP	84.12 ± 0.05	53.29 ± 0.34	91.24 ± 0.05	56.44 ± 0.24
	GNN	84.80 ± 0.20	60.82 ± 0.70	92.64 ± 0.10	58.41 ± 1.03
	EN	85.04 ± 0.31	61.21 ± 0.65	92.83 ± 0.16	66.78 ± 2.97
	PN	83.31 ± 0.40	48.27 ± 1.77	90.02 ± 0.47	72.08 ± 1.95
	NatPN	84.50 ± 0.43	60.66 ± 1.06	92.44 ± 0.24	61.40 ± 4.36
	GPN	86.05 ± 0.14	62.12 ± 1.35	93.50 ± 0.13	74.88 ± 1.93
	NatGPN	82.85 ± 1.88	57.71 ± 2.81	91.01 ± 1.60	68.86 ± 0.67
	EnsGNN	$85.82 \pm n/a$	$62.38 \pm n/a$	$93.41 \pm n/a$	$62.02 \pm n/a$
	EnsNatPN	$85.18 \pm n/a$	$62.19 \pm n/a$	$93.03 \pm n/a$	$64.73 \pm n/a$
	EnsGPN	$86.18 \pm n/a$	$62.76 \pm n/a$	$93.65 \pm n/a$	$74.62 \pm n/a$