SiT: Simulation Transformer for Particle-based Physics Simulation

Abstract

Most existing particle-based simulators adopt graph convolutional networks (GCNs) to model the underlying physics of particles. However, they force particles to interact with all neighbors without selection, and they fall short in capturing material semantics for different particles, leading to unsatisfactory performance, especially in generalization. This paper proposes Simulation Transformer (SiT) to simulate particle dynamics with more careful modeling of particle states, interactions, and their intrinsic properties. Specifically, besides the particle tokens, SiT generates interaction tokens and selectively focuses on essential interactions by allowing both tokens to attend to each other. In addition, SiT learns material-aware representations by learnable abstract tokens, which will participate in the attention mechanism and boost the generalization capability further. We evaluate our model on diverse environments, including fluid, rigid, and deformable objects, which cover systems of different complexity and materials. Without bells and whistles, SiT shows strong abilities to simulate particles of different materials and achieves superior performance and generalization across these environments with fewer parameters than existing methods. Codes and models will be released.

1 Introduction

Particle-based physics simulation is a classic and important topic in computer science. It not only facilitates the exploration of underlying principles in physics, chemistry and biology, but also enables the creation of vivid visual effects such as explosion and fluid dynamic in films and games. Different from traditional simulators, particle-based simulators view a system as a composition of particles and imitate system changes over time by predicting the changes of particle-wise states according to current particle states and particle interactions. Consequently, they follow the same pipeline to simulate different systems with varying materials, requiring no system-specific physical priors. Moreover, since in particle-based simulators the dynamics of a system is modeled by the states of particles and their interactions, they also have the potential to possess a strong generalization ability, where they can robustly estimate the dynamics of a system with varying number and configuration of particles. After learning the dynamics of fluid water in a sandbox, the same particle-based simulator can be used to simulate a waterfall and a river.

Recent particle-based simulators (Battaglia et al., 2016; Schenck & Fox, 2018; Mrowca et al., 2018; Li et al., 2019; Sanchez-Gonzalez et al., 2020; Ummenhofer et al., 2020) often view a system as a graph, and adopt graph convolutional network (GCN) (Kipf & Welling, 2016) as the basic network structure. In these attempts, each particle is treated as a node in the graph, with edges linking it to all its neighboring particles, assuming interactions mainly occur between particles that are close to each other. Subsequently, state updates of particles are achieved by combining node features with the summation of edge features. While such a GCN-based formulation obtains satisfying simulation results, it faces two issues that affect efficiency and generality. First, it forces each particle to interact with all its nearby particles without providing a selection mechanism, which leads to computational redundancy and prevents the discovery of inherent patterns of particle interaction. Second, the GCN-based formulation uses particle-wise attributes to capture both material characteristics and system-specific semantics, such as the shape of a rigid material. Therefore, it may regard the latter as part of the intrinsic material semantics and fail to generalize to systems with the same materials but different particle amounts and configurations.

Figure 1: (a). Samples of the datasets. *FluidFall* contains two drops of water. *FluidShake* simulates a block of water in a moving box. *RiceGrip* has a deformable object squeezed by two grippers. *BoxBath* contains a rigid cubic washed by water. (b). Rollouts from generalizations of *RiceGrip*, where we increase the number of particles. SiT with abstract tokens, marked by +, can still maintain the object's shape, while DPI-Net (Li et al., 2019) fail to simulate the deformable object.

In this paper, we propose a novel Transformer-based framework, referred to as Simulation Transformer (SiT), for particle-based physics simulation. The model inherits the powerful multi-head self-attention mechanism in Transformer (Vaswani et al., 2017) to capture particle interactions. To further encourage efficient modeling of complex interactions, instead of treating particle interactions as attention weights obtained by dot-product , we introduce the notion of interaction tokens to model the rich semantics of particle interactions. In addition, to disentangle local material-specific characteristics from global system-specific semantics, SiT further deploys an abstract token for each type of material, forcing particles of the same material to interact with their corresponding abstract token.

The proposed SiT is more appealing than previous methods in several aspects. First, through capturing particle interactions explicitly with interaction tokens and allowing dynamic inter-token attention, SiT makes a good balance between efficiency and complexity, focusing only on essential particle interactions. This is crucial for particle-based simulation, especially for systems containing hundreds and thousands of densely placed particles, where the modeling of all particle interactions is redundant, expensive and noisy in practice. Second, thanks to the trainable abstract tokens that disentangle intrinsic material characteristics from system-specific semantics, we can reuse them to apply SiT to unseen systems of the same materials without retraining. As shown in our experiments, after training a system consisting of fluid water and a rigid cubic, SiT still yields fairly faithful simulations when the cubic is replaced with a ball or a bunny comparing with previous work.

To show the effectiveness of SiT, we perform extensive evaluations on four standard environments commonly used in the literature (Li et al., 2019; Sanchez-Gonzalez et al., 2020), covering systems of different complexity and materials. The proposed method achieves superior performance across all these environments with fewer parameters compared to existing methods. We further demonstrate the generalization ability of SiT by adjusting the environments to create new systems and applying SiT to these systems without retraining. In all cases, SiT obtains more realistic simulation results than previous methods, which tend to overfit to the training systems.

2 RELATED WORK

Physics simulation by neural networks. There are many different kind of representations for physics simulations. Grid-based methods (Lee & You, 2019; Thuerey et al., 2020; Wang et al., 2020) adopt convolutional architectures for learning high-dimensional physical system, while Mesh-based simulations (Bronstein et al., 2017; Luo et al., 2020; Hanocka et al., 2019; Nash et al., 2020; Qiao et al., 2020; Weng et al., 2021; Pfaff et al., 2021) typically simulate objects with continuous surfaces, such as clothes, rigid objects, surfaces of water and so on.

Many works (Battaglia et al., 2016; Schenck & Fox, 2018; Mrowca et al., 2018; Li et al., 2019; Sanchez-Gonzalez et al., 2020; Ummenhofer et al., 2020) simulate physics on particle-based systems, where all objects are represented by groups of particles. Specifically, Interaction Network

(IN) (Battaglia et al., 2016) simulated interactions in object-level. Smooth Particle Networks (SP-Nets) (Schenck & Fox, 2018) implemented fluid dynamics using position-based fluids (Macklin & Müller, 2013). Hierarchical Relation Network (HRN) (Mrowca et al., 2018) predicted physical dynamics based on hierarchical graph convolution. Dynamic Particle Interaction Networks (DPI-Net) (Li et al., 2019) combined dynamic graphs, multi-step spatial propagation, and hierarchical structure to simulate particles. Graph Network-based Simulators (GNS) (Sanchez-Gonzalez et al., 2020) computed dynamics via learned message-passing. CConv (Ummenhofer et al., 2020) used spatial convolutions to simulate fluid particles.

Previous work mostly adopted graph networks for simulations and required each particle to interact with all its nearby particles without providing a selection mechanism. In contrast, our SiT employs both particle and interaction tokens and selectively focus on necessary particle interactions through attention mechanism. Experiments show that SiT surpasses existing GCN-based methods and has more robust performances in generalizations.

Transformer. Transformer (Vaswani et al., 2017) was designed for machine translation and achieved state-of-the-art performance in many natural langruage processing tasks (Devlin et al., 2019; Radford et al., 2019; Brown et al., 2020). Recently, Transformer starts to show great expandability and applicability in many other fields, such as computer vision (Wang et al., 2018; Carion et al., 2020; Dosovitskiy et al., 2021; Wang et al., 2021; Liu et al., 2021), and graph representations (Zhou et al., 2020; Zhang et al., 2020; Dwivedi & Bresson, 2020). To our knowledge, no attempt has been made to apply Transformer on physics simulation.

Our SiT models the interactions between particles by trainable sub-network given corresponding particle tokens. The same notion of extracting potential semantics between nodes is also applied in Graph Transformer (Dwivedi & Bresson, 2020), which is Transformer-based model for graphs. In the following paper, we refer Graph Transformer as GraphTrans for short. However, there are differences in our formulations. Specifically, GraphTrans adopts element-wise product between node representations followed by multi-layer perceptron (MLP) to update the interaction embeddings, which store the attention scores in each dimension. Before forwarding to MLP, GraphTrans computes a scalar according to the interaction embeddings and apply standard attention mechanism to update the node embeddings. In contrast, our model learns semantic tokens for interactions through sub-network instead of element-wise product. When updating the particle tokens, which are referred as node representations in GraphTrans, both particle and interaction tokens will attend to each other. The interaction tokens are not weighted scores any more. We adopt GraphTrans (Dwivedi & Bresson, 2020) in particle-based simulation and compare it with SiT in experiments. The quantitative results show that SiT achieves better results than GraphTrans.

3 METHODOLOGY

3.1 PROBLEM FORMULATION

For a particle-based system composed of N particles, we use $\mathcal{X}^t = \{\boldsymbol{x}_i^t\}_{i=1}^N$ to denote the system state at time step t, where $\boldsymbol{x}_i^t$ denotes the state of i-th particle. Specifically, $\boldsymbol{x}_i^t = [\boldsymbol{p}_i^t, \boldsymbol{q}_i^t, \boldsymbol{a}_i]$, where $\boldsymbol{p}_i^t, \boldsymbol{q}_i^t \in \mathbb{R}^3$ refer to position and velocity, and $\boldsymbol{a}_i \in \mathbb{R}^{d_a}$ represents fixed particle attributes such as its material type. The goal of a simulator is to learn a model $\phi(\cdot)$ from previous rollouts of a system to causally predict a rollout trajectory in a specific time period conditioned on the initial system state $\mathcal{X}^0$. The prediction is run in a recursive manner, where the simulator will predict the state $\hat{\mathcal{X}}^{t+1} = \phi(\mathcal{X}^t)$ at time step $t + 1$ based on the state $\mathcal{X}^t = \{\boldsymbol{x}_i^t\}$ at time step t. In practice, we will predict the velocities of particles $\hat{Q}^{t+1} = \{\hat{\boldsymbol{q}}_i^{t+1}\}$, and obtain their positions via $\hat{\boldsymbol{p}}_i^{t+1} = \boldsymbol{p}_i^t + \Delta t \cdot \hat{\boldsymbol{q}}_i^{t+1}$, where Δt is a system specific constant.

3.2 SIMULATION VIA VANILLA TRANSFORMER

To accurately simulate the changes of a system over time, it is crucial to effectively model the interactions among particles, as they indicate the energy transition of a system when constrained by material characteristics and physical laws. However, it is infeasible to know a priori how should particles interact with each other, a selective mechanism is thus in great need to help the simulator focus only on necessary interactions.

Figure 2: Overview of our transformer-based model with abstract tokens, which are optional. SiT is composed of an encoding layer, stacks of L blocks extended from Transformer encoder blocks, and a decoding layer. Given the particles states at time t, the encoding layer will first encode the particles' states and learnable embeddings into particle tokens and abstract tokens. The interaction tokens are also initialized by particles' states through the encoding layer. In each blocks, the sub-network will first update interaction tokens given particle tokens. Then all tokens will dynamically attend to each other via uniform attention and update particle and abstract tokens. An MLP is attached after attention. Finally, the decoding layer will predict the particles' velocities at time $t + 1$ given the particle tokens.

Since Transformer (Vaswani et al., 2017) is capable of capturing the dynamical interactions among its tokens via the self-attention module, it is naturally a good backbone of building an efficient particle-based simulator. To apply vanilla Transformer in particle-based simulation, we first encode the states of particles into corresponding particle tokens $V = \{\boldsymbol{v}_i^t\}$ by

$$\boldsymbol{v}_i^t \;=\; f_V^{\text{enc}}(\boldsymbol{x}_i^t), \tag{1}$$

where $\boldsymbol{v}_i^t \in \mathbb{R}^{d_h}$ is a d_h dimensional vector and $f_V^{\text{enc}}(\cdot)$ is an encoding layer implemented as a MLP. Subsequently, particle interactions are achieved by L blocks of self-attention modules, where in the l-th block, particle tokens will attend to each other selectively as:

$$\boldsymbol{v}_i^{l+1,t} \;=\; \sum_j \hat{w}_{ij}^v \boldsymbol{v}_j^{l,t}, \tag{2}$$

$$\hat{w}_{ij}^v \;=\; \frac{\exp(w_{ij}^v)}{\sqrt{d_h} \cdot \sum_j \exp(w_{ij}^v)}, \tag{3}$$

$$w_{ij}^v \;=\; (\boldsymbol{v}_i^{l,t})^\top \boldsymbol{v}_j^{l,t}. \tag{4}$$

Since a system usually contains hundreds of particles, considering all possible interactions is computationally redundant and inefficient. Therefore, we follow previous literature Li et al. (2019); Sanchez-Gonzalez et al. (2020) to assume that interactions of distant particles can be omitted, which is realized by defining a window function:

$$g(\boldsymbol{p}_i^t, \boldsymbol{p}_j^t) \;=\; \mathbb{I}\left(\|\boldsymbol{p}_i^t - \boldsymbol{p}_j^t\|_2 < R \right), \tag{5}$$

where $\mathbb{I}(\text{condition})$ is a indicator function that returns 1 if the condition is satisfied, and R defines the extent of the window. This window function will generate a mask to retain only interactions between neighboring particles as potential candidates in the self-attention modules.

To predict particle states in the next time step, a decoding layer is applied to the updated token of i-th particle to obtain its velocity:

$$\hat{\boldsymbol{q}}_i^{t+1} \;=\; f_V^{\text{dec}}(\boldsymbol{v}_i^{L,t}), \tag{6}$$

where $f_V^{\text{dec}}(\cdot)$ is implemented by another MLP.

3.3 SIMULATION TRANSFORMER (SIT)

Although the vanilla Transformer provides a flexible approach for particle-based simulation, directly applying it leads to inferior simulation results as shown in our experiments. In particular, a vanilla Transformer uses attention weights, which are scalars obtained via dot-product, to represent particle interactions. A single scalar is insufficient to reflect the rich semantics of particle interactions. For

example, in the case of fluid water, when two particles get closer and closer, their interaction will at first act as surface tension to push them towards each other. And when they are sufficiently close, the repulsion between them will dominate the interaction and stop them from further moving towards each other. In addition, since the semantics of a system is scattered in the tokens of different particles, system-specific semantics such as the shape of a rigid object are mixed with system-agnostic semantics. In such cases, the former may be misinterpreted as the latter, leading to poor generalization ability. To overcome the limitations of vanilla Transformer, we propose a novel Transformer-based simulator, referred to as Simulation Transformer (SiT), that extends vanilla Transformer with two new types of tokens, namely interactions tokens and abstract tokens. An overview of SiT is included in Figure 2.

Interaction Tokens. To capture the rich semantics of particle interactions, instead of a scalar, SiT assigns an interaction token to each potential particle interaction. Specifically, the token for the interaction between particles $\boldsymbol{x}_i^t$ and $\boldsymbol{x}_j^t$ is initialized by

$$\boldsymbol{u}_{ij}^t \quad = \quad f_I^{\mathrm{enc}}(\boldsymbol{x}_i^t, \boldsymbol{x}_j^t), \tag{7}$$

where $\boldsymbol{u}_{ij}^t \in \mathbb{R}^{d_h}$ is a d_h dimensional vector and $f_I^{\mathrm{enc}}(\cdot)$ is the encoding function for interactions.

Subsequently, in each self-attention block SiT will update the interaction tokens as

$$\boldsymbol{u}_{ij}^{l+1,t} \quad = \quad \psi\left(\boldsymbol{v}_i^{l,t}, \boldsymbol{v}_j^{l,t}, \boldsymbol{u}_{ij}^{l,t}, g(\boldsymbol{p}_i^t, \boldsymbol{p}_j^t)\right), \tag{8}$$

where $\psi(\cdot)$ is a learnable sub-network shared for all interaction tokens. Inspired by GCN-based methods (Mrowca et al., 2018; Li et al., 2019; Sanchez-Gonzalez et al., 2020) , SiT adopts the learnable sub-network to enlarge its capacity for handling complex particle interactions. In practice, the sub-network is implemented as

$$\psi\left(\boldsymbol{v}_i^{l,t}, \boldsymbol{v}_j^{l,t}, \boldsymbol{u}_{ij}^{l,t}, g(\boldsymbol{p}_i^t, \boldsymbol{p}_j^t)\right) \quad = \quad \mathrm{MLP}([\boldsymbol{v}_i^{l,t}, \boldsymbol{v}_j^{l,t}, \boldsymbol{u}_{ij}^{l,t}]) \cdot g(\boldsymbol{p}_i^t, \boldsymbol{p}_j^t). \tag{9}$$

As is shown in Figure 6, the update of particle tokens in the self-attention module is thus achieved by

$$\boldsymbol{v}_i^{l+1,t} \quad = \quad \alpha \sum_j \hat{w}_{ij}^v \boldsymbol{v}_j^{l,t} + \beta \sum_k \hat{w}_{ik}^u \boldsymbol{u}_{ik}^{l+1,t}, \tag{10}$$

$$\hat{w}_{ij}^v \quad = \quad \frac{\exp(w_j^v)}{\sqrt{d_h} \cdot \left(\alpha \sum_j \exp(w_j^v) + \beta \sum_k \exp(w_{ik}^u)\right)}, \tag{11}$$

$$\hat{w}_{ik}^u \quad = \quad \frac{\exp(w_{ik}^u)}{\sqrt{d_h} \cdot \left(\alpha \sum_j \exp(w_j^v) + \beta \sum_k \exp(w_{ik}^u)\right)}, \tag{12}$$

$$w_{ij}^v \quad = \quad (\boldsymbol{v}_i^{l,t})^\top \boldsymbol{v}_j^{l,t}, \tag{13}$$

$$w_{ik}^u \quad = \quad (\boldsymbol{v}_i^{l,t})^\top \boldsymbol{u}_{ik}^{l+1,t}, \tag{14}$$

where $\alpha, \beta \in \{0, 1\}$ are the gate controllers, j and k are the indexes of particles within the reception window defined by Equation 5. Equation 13 computes the attention scores between particle tokens, and Equation 14 computes the attention scores between particle and interaction tokens. Subsequently, these attention scores are normalized by Equation 11 and Equation 12. They are then used by Equation 10 to aggregate semantics of particle and interaction tokens, where the gate controllers α, β are hyper-parameters that work as balancing coefficients. When $\alpha = 1, \beta = 0$, Equation 10 becomes the original self-attention formula in vanilla Transformer. The multi-head attention version of Equation 10 can be found in Appendix 6.1.2.

It is worth noting that SiT provides a more flexible way for further extensions when compared to vanilla Transformer. Specifically, we can change the value of α and β in Equation 10 to adjust the significance of different tokens. And changing the window function in Equation 5 allows SiT to consider different interaction patterns. Finally, by adjusting the learnable sub-network, we can also generalize SiT to consider more complex particle interactions such as interactions beyond a pair of particles and interactions of interactions.

Abstract Tokens. To improve the generalization ability of SiT and disentangle system-specific semantics from its system-agnostic counterparts, we further apply SiT with material-specific abstract tokens.

For N_a types of materials, SiT adopts N_a abstract tokens $A = \{a_k\}_{k=1}^{N_a}$, each of which is a learnable vector of the same length of particle tokens. Ideally, the abstract token a_k should capture the system-agnostic semantics of k-th material. They act as particle tokens for additional abstract particles, following the same update formula as particle tokens. Therefore with N_a abstract tokens SiT will have $N + N_a$ particle tokens in total: $\{a_1, \cdots, a_{N_a}, x_1^t, \cdots, x_N^t\}$, as is show in Figure 2. Although abstract tokens share the same update formula as particle tokens, unlike particle tokens that decide their potential interactions via the window function in Equation 5, abstract tokens are forced to interact with all particle tokens of its corresponding material, which is achieved by setting the reception field of abstract tokens to the particles of the same material.

Once abstract tokens capture system-agnostic semantics, they can be reused by SiT when generalizing to systems that have same materials but vary in particle amount and configuration.

3.4 TRAINING OBJECTIVE

To train SiT with previous rollouts, the standard mean square error (MSE) loss is applied on the output of our SiT:

$$\text{MSE}(\hat{Q}^{t+1}, Q^{t+1}) \quad = \quad \frac{1}{N} \sum_i (\hat{q}_i^{t+1} - q_i^{t+1})^2, \tag{15}$$

where $\hat{Q}^{t+1} = \{\hat{q}_i^{t+1}\}$ is the estimated velocity and and $Q^{t+1} = \{q_i^{t+1}\}$ is the ground truth.

While the MSE loss works well for cases with relatively low complexity, in practice systems often contain multiple types of materials with imbalance numbers of particles. In such cases, the MSE loss will be biased to the material with more particles. Therefore, we further apply a material weighted MSE (WMSE) loss to reduce the effect of imbalance:

$$\text{WMSE}(\hat{Q}^{t+1}, Q^{t+1}) \quad = \quad \sum_k \frac{N_k}{K} \text{MSE}(\hat{Q}_k^{t+1}, Q_k^{t+1}), \tag{16}$$

where K is the number of material types, N_k is the number of particles belonging to the k-th material and $N = \sum_k N_k$, $\hat{Q}_k^{t+1}$ and Q_k^{t+1} denote the estimated velocity and ground truth for k-th material.

4 EXPERIMENTS

4.1 BASE ENVIRONMENTS

We adopt the environments commonly used in the literature (Li et al., 2019; Sanchez-Gonzalez et al., 2020; Ummenhofer et al., 2020). Samples are displayed in Figure 1. There are four environments in total: *FluidFall* is a basic simulation for two drops of water; *FluidShake* is more complex and simulate the water in a randomly moving box; *BoxBath* simulates the water washing a rigid cubic in fixed box; *RiceGrip* simulates the interactions between deformable rice and two rigid grippers. More details of data generalization can be found in Appendix 6.1.3.

We compare SiT with 4 recent approaches: DPI-Net (Li et al., 2019), CConv (Ummenhofer et al., 2020), GNS (Sanchez-Gonzalez et al., 2020), and GraphTrans (Dwivedi & Bresson, 2020). For fair comparison, we adopt similar training schedules. Quantitative results and model parameters are in Table 4. We also render some sample rollouts in Figure 3 to show the qualitative results. More model details and qualitative results can be found in Appendix 6.1.3 and 6.2.2

SiT achieves superior performance on all environments with fewer model parameters. The effectiveness of abstract tokens are more obvious for *RiceGrip* and *BoxBath*, which are more complex. Quantitative results show that SiT can better simulate the dynamics on different environments.

Comparison with DPI-Net and GNS. DPI-Net (Li et al., 2019) and GNS (Sanchez-Gonzalez et al., 2020) adopt message-passing graph networks for particle-based simulation. They require the particles to interact with all nearby neighbors without selections, which will aggregate redundant and

Table 1: Quantitative results and model parameters on four environments. SiT achieves superior and reasonable performance with less model parameters on all environments. When adding trainable abstract tokens, which introduce a few more parameters, SiT, marked by +, further improves performance in complex environments. As CConv is designed for fluid dynamics, we report the results on *BoxBath* for reference of the simulation on fluid parts, which is marked by *.

Methods	FluidFall		FluidShake		RiceGrip		BoxBath		
	MSE	Params	MSE	Params	MSE	Params	MSE	WMSE	Params
DPI-Net	0.12±0.06	0.62M	1.43±0.52	1.02M	0.11±0.21	2.17M	1.91±0.08	1.52±0.33	1.98M
CConv	0.08±0.02	0.84M	1.34±0.45	0.84M	N/A	N/A	1.98 ±0.11*	3.06±0.47*	0.84M
GNS	0.05±0.02	4.77M	N/A	N/A	N/A	N/A	**1.45±0.12**	2.86±0.83	4.77M
GraphTrans	0.12±0.03	0.49M	8.77±3.97	0.96M	0.36±0.27	0.96M	3.17±0.07	2.33±0.47	0.97M
SiT (Ours)	0.05±0.02	0.40M	**1.08±0.36**	0.77M	0.15±0.12	0.82M	1.74±0.08	1.42±0.29	0.77M
SiT+ (Ours)	**0.04±0.01**	**0.40M**	1.08±0.39	**0.77M**	**0.07±0.07**	**0.82M**	1.57±0.06	**1.39±0.31**	**0.77M**

Figure 3: Qualitative results on *FluidFall* and *BoxBath*. When the two drops are getting closer in *FluidFall*, previous methods are likely to mix them together, suggesting the wrong estimations of viscosity. But SiT can still predict faithful rollouts.

irrelevant neighbors. SiT can eliminate those unnecessary information by the selective mechanism, which is further demonstrated by the heat map in Appendix 6.2.1. As is shown in the results, SiT achieves better performance than DPI-Net and GNS, suggesting the effectiveness of the selective mechanism and abstract tokens. For *BoxBath*, GNS does not adopt rotation constrains on rigid particles and fails to maintain the shape in the long period, which is shown by the larger WMSE results and the rendered rollout. On the other hand, DPI-Net and SiT maintain same rotation speed for rigid particles as mentioned in Appendix 6.1.3. But SiT can better simulate interactions between different materials especially with abstract tokens, as is shown by the similar positions of rigid box in the qualitative results. For *FluidFall*, though the MSE results are close to each other, SiT can better maintain the shape of drops while DPI-Net and GNS fail due to the wrong prediction of viscosity.

Comparison with CConv. CConv (Ummenhofer et al., 2020) designs convolutional layers carefully tailored to modeling fluid dynamics, such as an SPH(Monaghan, 1992)-like local kernel, different sub-networks for fluid and boundary particles. Without modeling interactions, CConv propagates information only among particles weighted by distances. On the other hand, SiT assigns high-level tokens for interactions and achieves better results, suggesting the necessity of interaction tokens. Notice that CConv is not suitable for rigid box, we only report result on *BoxBath* for reference of simulation on fluid parts.

Comparison with GraphTrans (Dwivedi & Bresson, 2020). The GraphTrans is also a Transformer-based method and updates the interactions using element-wise product from node representations. We represent particles by nodes and adopt layers in GraphTrans as our backbone, which and use the same hidden dimensions and number of blocks. Other settings are completely the same as SiT for better comparison. As is shown in experiments, GraphTrans fails to simulate particles on all cases with much higher errors. This is because our SiT directly models the interactions by interaction tokens generated by sub-network, which is necessary to capture high-level semantics.

4.2 GENERALIAZTIONS

To challenge the robustness of our model on more complex settings, we add more particles for *RichGrip* and *FluidShake*, and change the size and shape of rigid object for *BoxBath*. Table 4 shows

Table 2: MSE results on generalizations. The lists of numbers in *FluidShake* and *RiceGrip* are the range of particles, while the tuples in *BoxBath* denotes number of fluid particles, number of rigid particles, and shape of rigid objects respectively. Training settings are marked by *. We compare SiT with abstract tokens and DPI-Net. SiT+ achieves the best results on all cases.

Methods	FluidShake [450,627]*			RiceGrip [570,980]*	
	[720,900]	[924,1080]	[1104,1368]	[1060,1345]	[1347,1640]
DPI-Net	2.14±0.36	2.78±0.58	3.53±0.71	2.33±30.64	0.87±4.00
SiT+ (Ours)	**1.54±0.37**	**1.90±0.63**	**2.30±0.69**	**0.14±0.10**	**0.17±0.15**

Methods	BoxBath (960,64,cubic)*				
	(1280,64,cubic)	(960,41,bunny)	(960,125,cubic)	(960,136,ball)	(960,120,cuboid)
DPI-Net	4.28±0.11	2.49±0.23	2.75±0.42	2.71±0.35	2.97±0.38
SiT+ (Ours)	**2.64±0.11**	**1.72±0.08**	**1.74±0.14**	**1.67±0.13**	**1.92±0.32**

Figure 4: Rendered rollouts on generalized *FluidShake* and *BoxBath*. More particles participate in simulations. SiT with abstract tokens (SiT+) can still faithfully predict the wave of fluid in *FluidShake* and the positions of rigid cubic in *BoxBath*.

the upper and lower bound for the number of particles in training set and generalization validation set, as well as the shapes of rigid object.

We mainly compare SiT with DPI-Net, which has fairly good and reasonable performance on all environments. Quantitative results are summarized in Table 4, while qualitative results are depicted in Figure 4 and Figure 1 (b). As shown in the results, SiT with abstract tokens can better simulate particle dynamics in generalized environment. suggesting that the abstract tokens and the selective mechanism involving interaction tokens can provide more stable and robust performance. The WMSE results and other models' performance with rollouts can be found in Appendix 6.2.3, which shows that previous methods overfit the training set to get good performance on validation set, while SiT can learn the material characteristics and maintain reasonable performance on different generalized environment.

4.3 ABLATION STUDIES

We comprehensively analyze our SiT and explore the effectiveness of our model in the following ways: (a) the necessity of interaction tokens; (b) the architectures of sub-network, which generates interaction tokens; (c) the values for gate controllers α, β; (d) the usage of multi-head in uniform attention. We conduct our experiments on *FluidShake* and report the results in Table 3.

Necessity of interaction tokens. We apply the vanilla Transformer encoder denoted by configuration A, which uses the same hidden dimension and number of blocks as SiT. For more strict comparison, we also modify SiT by configuration B which only changes the output of sub-network to one dimension. As a result, both configuration A and configuration B have low performance, which suggests that the scalars are insufficient to describe the complex interactions.

Architectures of sub-network. We try different architectures for our sub-network to generate the interaction tokens. Configuration C adopts element-wise product between particle tokens, which follows the GraphTrans (Dwivedi & Bresson, 2020); configuration D adopts self-attention blocks, where q is the interaction token from previous layer, k and v are the neighbor particle tokens. As is shown in the results, configuration C and D have worse performance than SiT, which suggests that the element-wise product is insufficient to model complex interactions, while self-attention block introduces more parameters and complexities, making it harder to train.

Hyper-paramters for α, β. We set $\alpha = 1, \beta = 0$ in configuration E, $\alpha = 1, \beta = 1$ in configuration F, and $\alpha = 0, \beta = 1$ in configuration H, Consequently, both configuration E and H achieve good results, suggesting that the participants of interaction tokens are the key to boost the performance, which agrees with the intuition that the interactions indicate how the particles should behave. In practice, we use configuration H for SiT which shows the best results.

Table 3: Ablation studies. We comprehensively explore the effectiveness of SiT, including the necessity of interaction tokens, the structure of sub-network, the value of gate controller α, β, and the usage of multi-head in uniform attention. We report the MSE results on *FluidShake*, which is a complex environments involving outer forces.

Configurations	Interaction modeling	α	β	Multi-head	FluidShake
A(Transformer)	Scalar by dot product	1	0	✓	21.03±10.54
B	Scalar by MLP	0	1		300.43±70.16
C	Tokens by element-wise product	0	1		17.70±6.99
D	Tokens by self attention	0	1		3.17±0.81
E	Tokens by MLP	1	0		14.27±42.08
F	Tokens by MLP	1	1		1.19±0.44
G	Tokens by MLP	0	1	✓	1.04±0.36
H(SiT)	Tokens by MLP	0	1		1.08±0.36

Multi-head uniform attention. We apply multi-head mechanism in configuration G. and set head number as 8. The results show that multi-head mechanism can bring us some improvement. But it also introduces more parameters and consumes lots of memory when computing. In practice, we make a balance between computations and performance and adopt self-attention in SiT.

4.4 FEW SHOTS LEARNING

(a) (b)

Figure 5: Few shots learning on *FluidShake*. Figure (a) display some rollouts. With 60% of training examples, SiT can achieve fairly good results. Figure (b) draws the MSE curves as the number of training examples increase. The x-axis denotes the percentage of training examples. Our model are robust even with only 60% of training examples.

As is shown in 5, we conduct few shots learning experiments on *FluidShake* using SiT without abstract tokens. The quantitative and qualitative results show the strong robustness of SiT on fewer data. As the percentage of training examples decreases from 100% to 60%, SiT can still maintain low MSEs and predict rollouts similar to the ground truth. When trained with less data, SiT learns not well enough. As the number of particles differs in each rollout, SiT does not have enough training on all possible cases, leading to larger MSEs and worse rollouts.

5 CONCLUSION

In this paper, we propose Simulation Transformer (SiT) and introduce interaction tokens and abstract tokens to simulate systems of different complexity and materials, including hundreds and thousands of particles. Our experimental results show the necessity and effectiveness of interaction and abstract tokens as well as selective mechanism in attention for particle-based simulation. Generalization results further suggest the robustness of SiT. SiT is also flexible for extensions and applications, such as more complex and efficient architectures for sub-network, changing the particle dynamics by attending to alternative abstract tokens with different materials semantics. Finally, SiT makes a successful attempt to apply Transformer into physics simulation and achieve superior performances over existing methods.

REFERENCES

Peter W. Battaglia, Razvan Pascanu, Matthew Lai, Danilo Jimenez Rezende, and Koray Kavukcuoglu. Interaction networks for learning about objects, relations and physics. In *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, 2016.

Michael M. Bronstein, Joan Bruna, Yann LeCun, Arthur Szlam, and Pierre Vandergheynst. Geometric deep learning: Going beyond euclidean data. *IEEE Signal Process. Mag.*, 2017.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part I*, 2020.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*, 2021.

Vijay Prakash Dwivedi and Xavier Bresson. A generalization of transformer networks to graphs. *CoRR*, 2020.

Rana Hanocka, Amir Hertz, Noa Fish, Raja Giryes, Shachar Fleishman, and Daniel Cohen-Or. MeshCNN: a network with an edge. *ACM Trans. Graph.*, 2019.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *CoRR*, 2016.

Sangseung Lee and Donghyun You. Data-driven prediction of unsteady flow over a circular cylinder using deep learning. *Journal of Fluid Mechanics*, 2019.

Yunzhu Li, Jiajun Wu, Russ Tedrake, Joshua B. Tenenbaum, and Antonio Torralba. Learning particle dynamics for manipulating rigid bodies, deformable objects, and fluids. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*, 2019.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin Transformer: Hierarchical vision transformer using shifted windows. *CoRR*, 2021.

Ran Luo, Tianjia Shao, Huamin Wang, Weiwei Xu, Xiang Chen, Kun Zhou, and Yin Yang. NNWarp: Neural network-based nonlinear deformation. *IEEE Trans. Vis. Comput. Graph.*, 2020.

Miles Macklin and Matthias Müller. Position based fluids. *ACM Trans. Graph.*, 2013.

Joe J Monaghan. Smoothed particle hydrodynamics. *Annual review of astronomy and astrophysics*, 30(1):543–574, 1992.

Damian Mrowca, Chengxu Zhuang, Elias Wang, Nick Haber, Li Fei-Fei, Josh Tenenbaum, and Daniel L. Yamins. Flexible neural representation for physics prediction. In *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada*, 2018.

Charlie Nash, Yaroslav Ganin, S. M. Ali Eslami, and Peter W. Battaglia. PolyGen: An autoregressive generative model of 3d meshes. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, 2020.

Tobias Pfaff, Meire Fortunato, Alvaro Sanchez-Gonzalez, and Peter W. Battaglia. Learning mesh-based simulation with graph networks. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*, 2021.

Yi-Ling Qiao, Junbang Liang, Vladlen Koltun, and Ming C. Lin. Scalable differentiable physics for learning and control. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, 2020.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 2019.

Alvaro Sanchez-Gonzalez, Jonathan Godwin, Tobias Pfaff, Rex Ying, Jure Leskovec, and Peter W. Battaglia. Learning to simulate complex physics with graph networks. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, 2020.

Connor Schenck and Dieter Fox. SPNets: Differentiable fluid dynamics for deep neural networks. In *2nd Annual Conference on Robot Learning, CoRL 2018, Zürich, Switzerland, 29-31 October 2018, Proceedings*, 2018.

Nils Thuerey, Konstantin Weißenow, Lukas Prantl, and Xiangyu Hu. Deep learning methods for reynolds-averaged navier–stokes simulations of airfoil flows. *AIAA Journal*, 2020.

Benjamin Ummenhofer, Lukas Prantl, Nils Thuerey, and Vladlen Koltun. Lagrangian fluid simulation with continuous convolutions. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, 2017.

Huiyu Wang, Yukun Zhu, Hartwig Adam, Alan L. Yuille, and Liang-Chieh Chen. MaX-DeepLab: End-to-end panoptic segmentation with mask transformers. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, 2021.

Rui Wang, Karthik Kashinath, Mustafa Mustafa, Adrian Albert, and Rose Yu. Towards physics-informed deep learning for turbulent flow prediction. In *KDD '20: The 26th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, Virtual Event, CA, USA, August 23-27, 2020*, 2020.

Xiaolong Wang, Ross B. Girshick, Abhinav Gupta, and Kaiming He. Non-local neural networks. In *2018 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2018, Salt Lake City, UT, USA, June 18-22, 2018*, 2018.

Zehang Weng, Fabian Paus, Anastasiia Varava, Hang Yin, Tamim Asfour, and Danica Kragic. Graph-based task-specific prediction models for interactions between deformable and rigid objects. *CoRR*, 2021.

Jiawei Zhang, Haopeng Zhang, Congying Xia, and Li Sun. Graph-Bert: Only attention is needed for learning graph representations. *CoRR*, 2020.

Dawei Zhou, Lecheng Zheng, Jiawei Han, and Jingrui He. A data-driven graph generative model for temporal interaction networks. In *KDD '20: The 26th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, Virtual Event, CA, USA, August 23-27, 2020*, 2020.

6 APPENDIX

6.1 MODEL DETAILS

6.1.1 UNIFORM ATTENTION

Figure 6: Overview of our uniform attention. The abstract tokens are optional. The tokens will attend to each other and update accordingly.

Figure 6 illustrates how our uniform attention works. Our uniform attention extend self-attention (Vaswani et al., 2017) by additional tokens. The queries are the abstract tokens, which are optional, and particle tokens, while the keys and values are all three types of tokens. Each token will attend to tokens within its reception fields defined by the window function 5. For the abstract tokens, they are forced to attend only to the particles belonging to the same material. The output of uniform attention is the updated tokens except interaction tokens.

6.1.2 MULTI-HEAD UNIFORM ATTENTION

The multi-head version of uniform attention is formulated by

$$\boldsymbol{v}_i^{l,t} = \boldsymbol{W}^l \left[\mathrm{SA}_1, \mathrm{SA}_2, \cdots, \mathrm{SA}_M \right]^\top, \tag{17}$$

$$\mathrm{SA}_m = \alpha \sum_j \hat{w}_{ij}^{m,v} (\boldsymbol{V}^{m,l} \boldsymbol{v}_j^{l-1,t}) + \beta \sum_k \hat{w}_{ik}^{m,u} (\boldsymbol{V}^{m,l} \boldsymbol{u}_{ik}^{l,t}), \tag{18}$$

$$\hat{w}_{ij}^{m,v} = \frac{\exp(w_j^{m,v})}{\sqrt{d_h} \cdot \left(\alpha \sum_j \exp(w_j^{m,v}) + \beta \sum_k \exp(w_{ik}^{m,u}) \right)}, \tag{19}$$

$$\hat{w}_{ik}^{m,u} = \frac{\exp(w_{ik}^{m,u})}{\sqrt{d_h} \cdot \left(\alpha \sum_j \exp(w_j^{m,v}) + \beta \sum_k \exp(w_{ik}^{m,u}) \right)}, \tag{20}$$

$$w_{ij}^{m,v} = (\boldsymbol{Q}^{m,l} \boldsymbol{v}_i^{l-1,t})^\top (\boldsymbol{K}^{m,l} \boldsymbol{v}_j^{l-1,t}), \tag{21}$$

$$w_{ik}^{m,u} = (\boldsymbol{Q}^{m,l} \boldsymbol{v}_i^{l-1,t})^\top (\boldsymbol{K}^{m,l} \boldsymbol{u}_{ik}^{l,t}), \tag{22}$$

where $m \in 1, 2, \cdots, M$ is the index of head, $W^l \in \mathbb{R}^{d_h \times d_h}$ is the output weight for the concatenation of M heads; $Q^{m,l}, K^{m,l}, V^{m,;}$ are the projection weights of query, key, value for head m at block l. The rest symbols are the same with those in uniform attention.

6.1.3 IMPLEMENTATION DETAILS

Inputs and outputs details. For *FluidFall*, *FluidShake*, and *BoxBath*, we only use particles' states at time t as inputs and output the velocities at time $t+1$. For *RiceGrip*, we concatenate particles states

from $t-2$ to t as inputs and output 6-dim vector for the velocity of the current observed position and the resting position, which is the same setting as DPI-Net for better comparison. For *BoxBath*, we output 7-dim vectors, where 3 dimensions for the predicted velocities, and 4 dimensions for rotation constrains. The rotation constrains are applied only on rigid particles which predict the rotation velocities. We use particles' states at time t as inputs and output the velocities at time $t + 1$ except *RiceGrip*, where we concatenate particles states from $t - 2$ to t as inputs for better comparison with DPI-Net (Li et al., 2019).

SiT details. We set $R = 0.08$ across all environments. All hidden dimensions in SiT are 128 for default. The MLP after uniform attention has two layers with dimensions 512 and 128. We use 2 blocks for *FluidFall* and 4 blocks for the other three environments. We set $\alpha = 0, \beta = 1$ in our model for default, which show the best results in ablation studies. The learnable embeddings for abstract tokens have the same dimensions as inputs.

Training. We train four models independently on these four environments. For common settings, we use Adam optimizer with initial learning rate 0.0008 and plateau scheduler with patience 3 and decreasing factor 0.8. We choose batch size 16 for all environments and train the models for 5 epochs on *FluidShake*, 5 epochs for *BoxBath*, 13 epochs for *FluidFall*, and 20 epochs for *RiceGrip*. No augmentation is involved, such as adding noises to particles states during training. We adopt WMSE loss on *BoxBath* and MSE loss on the rest environments for training.

Evaluation. We evaluate the positions between predictions and ground truths by MSE as is shown in equation 15. For *BoxBath*, we also report the WMSE results by equation 16 to better show the performance of simulating different materials.

Baseline details. For fair comparison, the following settings are the same with SiT: inputs for models, number of training epochs on different environments, learning rate schedules, and training loss on velocities. Other hyper-parameters for baselines are chosen for their best performance.

6.2 EXPERIMENTS

6.2.1 ADDTIONAL ABLATION STUDIES

(a) Sample in *BoxBath* at time $t = 42$.

(b) Attention scores at block 1. (c) Attention scores at block 2. (d) Attention scores at block 3. (e) Attention scores at block 4.

Figure 7: (a) is a sample frame on *BoxBath*. We select one particle in the center of red circle to show its attention scores on interactions from neighbors. (b)(c)(d)(e) show the heat maps from uniform attention in each block of SiT. The attention scores on interactions are assigned to the corresponding neighbors, which are shown by different colors. The darker the color, the lower attention score on particles.

We also visualize the attention scores in each block for a specific particle on *BoxBath* in Figure 7. The red dot in the center is the given particle. Other dots are the neighors. The red particle

will attend selectively to its neighbors rather than treating them equally. Different layers focus on different aspect of semantics. Specifically, the particle will focus mainly on closer neightbors in the first layer as is shown in Figure 7 (b).

6.2.2 BASE ENVIRONMENTS

Dataset details. We use the same setting for our datasets as mentioned in previous work (Li et al., 2019). *FluidFall* contains two fluid drops with different sizes. The size for each drop are randomly generated with one drop larger than the other. Position and viscosity for drops are randomly initialized. This environment contains 189 particles with 121 frames for each rollout. There are 2700 rollouts in training set and 300 rollouts in validation set. *FluidShake* simulates the water in a moving box. The speed of the box is randomly generated at each timestamp. In addition, the size of the box and the number of particles are various for different rollouts. In basic training and validation sets, the number of particles changes from 450 to 627. This environment has 301 frames for each rollout. There are 1800 rollouts in training set and 200 rollouts in validation set. *RiceGrip* contains two grippers and a sticky rice. The grippers' positions and orientation are randomly initialized. The number of particles for rice changes from 570 to 980 with 41 frames for each rollout in training and validation sets. There are 4500 rollouts in training set and 500 rollouts in validation set. *BoxBath* simulates a rigid cubic washed by water in a fixed container. The initial position of fluid block and rigid cubic are randomly initialized. This environment contains 960 fluid particles and 64 rigid particles with 151 frames for each rollout. There are 2700 rollouts in training set and 300 rollouts in validation set.

Results. We display some rollouts for all experiments in this section. The results on *RiceGrip* and *FluidShake* are not available because GNS was designed for containers with fixed size, the obstacles were also fixed during simulation. Such designation was coded in the GNS's encoder. But the containers in *FluidShake* have different sizes and the grippers in *RiceGrip* are not fixed. Therefore, GNS is not suitable on these two environments. The results on *RiceGrip* for CConv are not available for the same reason. Notice that the CConv is designed for fluid dynamics. The results on *BoxBath* for CConv are only used as reference of the simulation on fluid parts.

Figure 8: Rollouts on *FluidFall*. DPI-Net and GNS are likely to mix the drops together, while CConv alters the shape of the upper drop before falling on the floor. GraphTrans has worse performance of maintaining the shape of water drops. SiT changes a little for the shape of the upper drop. When using abstract tokens, which is marked by +, SiT can achieve better results which are closer to the ground truth.

Figure 9: Rollouts on *FluidShake*. CConv, which is designed specifically for fluid dynamics, rollouts fairly good results, such as the surface of water, in this domain. SiT can also achieve compatible results with less parameters. DPI-Net still has some flaws in predicting the wave of water, such as the rollout at $t = 63$. GraphTrans fails in this domain, suggesting the insufficiency of capturing the complex interactions from outer forces.

Figure 10: Rollouts on *RiceGrip*. For the surface of the rice, we can see at $t = 38$ that DPI-Net seems to put more pressure to the rice, while SiT without abstract tokens does the same. GraphTrans predicts worse results for the front surface of rice. SiT with abstract tokens can better simulate the deformable object.

Figure 11: Rollouts on *BoxBath*. As CConv is designed for fluid dynamics, it treats all particles as fluid and fails in this domain. GNS tries to maintain the shape of the cubic, while it predicts wrong rollouts in the long term. For models using rotation constrains on rigid object, SiT with abstract tokens achieves more faithful results in terms of the rotation of rigid cubics, the interactions between fluid particles.

Table 4: MSE and WMSE results from all models on generalizations. The lists of numbers in *FluidShake* and *RiceGrip* are the range of particles, while the tuples in *BoxBath* denotes number of fluid particles, number of rigid particles, and shape of rigid objects respectively. Training settings are marked by *. Notice that GNS overfits to fluid parts on *BoxBath*, which is shown by larger WMSE and lower MSE.

Methods	FluidShake [450,627]*			RiceGrip [570,980]*	
	[720,900]	[924,1080]	[1104,1368]	[1060,1345]	[1347,1640]
DPI-Net	2.14±0.36	2.78±0.58	3.53±0.71	2.33±30.64	0.87±4.00
CConv	1.86±0.42	2.23±0.72	2.50±0.77	N/A	N/A
GraphTrans	10.24±3.58	12.27±4.80	12.72±3.75	0.63±0.28	0.68±0.37
SiT+ (Ours)	**1.54±0.37**	**1.90±0.63**	**2.30±0.69**	**0.14±0.10**	**0.17±0.15**

Methods	BoxBath (960,64,cubic)*				
	(1280,64,cubic)	(960,41,bunny)	(960,125,cubic)	(960,136,ball)	(960,120,cuboid)
DPI-Net	4.28±0.11	2.49±0.23	2.75±0.42	2.71±0.35	2.97±0.38
CConv	4.30±1.73	3.03±0.18	3.21±0.82	3.80±0.22	3.05±1.55
GNS	**2.09±0.10**	**1.56±0.11**	2.02±0.25	2.03±0.29	2.33±0.42
GraphTrans	3.87±0.08	3.55±0.07	3.92±0.15	3.86±0.17	3.56±0.13
SiT+ (Ours)	2.64±0.11	1.72±0.08	**1.74±0.14**	**1.67±0.13**	**1.92±0.32**

Methods	BoxBath WMSE (960,64,cubic)*				
	(1280,64,cubic)	(960,41,bunny)	(960,125,cubic)	(960,136,ball)	(960,120,cuboid)
DPI-Net	3.14±0.39	3.65±1.72	3.42±0.90	3.13±0.68	3.96±1.39
CConv	4.30±1.09	3.59±0.51	4.09±0.62	4.43±0.35	3.43±0.90
GNS	3.73±0.80	3.75±1.03	4.41±0.98	4.33±0.96	5.82±1.94
GraphTrans	3.37±0.75	3.59±0.76	5.31±0.73	5.38±0.69	3.81±0.75
SiT+ (Ours)	**1.82±0.21**	**1.81±0.64**	**1.94±0.51**	**1.76±0.35**	**2.86±1.41**

Table 5: Details of generalization settings.

Environments	Number of training particles	Number of generalization particles
FluidShake Large	[450, 720]	[720, 1500]
RiceGrip Large	[558, 1060]	[1060, 1798]
BoxBath Large Fluid	Fluid: 960. Rigid: 64	Fluid: 1280. Rigid 64
BoxBath Bunny	Fluid: 960. Rigid: 64	Fluid: 960. Rigid: 41
BoxBath Large Cubic	Fluid: 960. Rigid: 64	Fluid: 960. Rigid: 125
BoxBath Large Ball	Fluid: 960. Rigid: 64	Fluid: 960. Rigid: 136
BoxBath Large Cuboid	Fluid: 960. Rigid: 64	Fluid: 960. Rigid: 120

6.2.3 GENERALIZATION DETAILS

We report WMSE results on *BoxBath* and other models' generalization performance for references in Table 4. SiT with abstract tokens achieves reasonable and superior performance.

We release the details of generalization settings in Table 5. For the generalizations of *FluidShake* and *RiceGrip*, we display the range of particle numbers. For the generalizations of *BoxBath*, we change the shape of rigid box into bunny, ball, cuboid, and larger cubic. Specifically, the generalized *RiceGrip* contains particles from 1060 to 1640, while the training set contains particles from 570 to 980; the generalized *FluidShake* contains particles from 720 to 1368, while the training set has 450 to 627 particles; For *BoxBath*, the training set has 960 fluid particles and 64 rigid particles. We first separately increase the fluid particles and rigid particles to 1280 and 125 respectively. Then, we change the shape of rigid object into bunny, ball, and cuboid with particles 41, 136, and 120 respectively. The followings are the rollouts on all environments.

Figure 12: Rollouts on generalized *FluidShake*. CConv achieves fairly good performance, while it still has difficulties to correctly predict the waves, such as the rollout at $t = 215$. DPI-Net has similar problems, such as the rollout at $t = 123$. GraphTrans still fails in this environment. Our SiT+ can still achieve better performance.

Figure 13: Rollouts on generalized *RiceGrip*. DPI-Net fails and cannot maintain the shape of the deformable object, as is shown in the prediction at $t = 38$. Our SiT+ has better rollouts than GraphTrans, suggesting the effectiveness and robustness of our method.

Figure 14: Rollouts on generalized *BoxBath*, where we add more fluid particles. DPI-Net misses the cubic at the end. While SiT+ predicts wrong motions of several fluid particles at the beginning, it still achieve better results compared with other models. Both CConv and GNS fail in this environment.

Figure 15: Rollouts on generalized *BoxBath*, where we add more rigid particles. DPI-Net starts to predict wrong rollouts for fluid particles at the beginning, and worse results for the rigid cubic. SiT+ achieves better results comparing with other models.

Figure 16: Rollouts on generalized *BoxBath*, where we change the shape from cubic to bunny. The shape of bunny is more challenging, as the ears of the bunny do not have direct connections to the body. While DPI-Net fails in this scene, SiT+ predicts rollouts as correctly as possible.

Figure 17: Rollouts on generalized *BoxBath*, where we use a rigid ball. For simple comparison, the positions of the rigid ball suggest models' abilities of simulation. SiT+ predicts more faithful positions of the ball and overall shapes of the fluid.

Figure 18: Rollouts on generalized *BoxBath*, where we use a rigid cubiod. It seems that the cuboid is harder to move. DPI-Net fails in this scenes by predicting wrong rotations for the cuboid, while SiT+ achieves better results.