Stationary Deep Reinforcement Learning with Quantum K-spin Hamiltonian Equation

Abstract

A foundational issue in deep reinforcement learning (DRL) is that *Bellman's optimality equation has multiple fixed points*—failing to return a consistent one. A direct evidence is the instability of existing DRL algorithms, namely, the high variance of cumulative rewards over multiple runs. As a fix of this problem, we propose a quantum K-spin Hamiltonian regularization term (H-term) to help a policy network stably find a *stationary* policy, which represents the lowest energy configuration of a system. First, we make a novel analogy between a Markov Decision Process (MDP) and a *quantum K-spin Ising model* and reformulate the objective function into a quantum K-spin Hamiltonian equation, a functional of policy that measures its energy. Then, we propose a generic actor-critic algorithm that utilizes the H-term to regularize the policy/actor network and provide Hamiltonian policy gradient calculations. Finally, on six challenging MuJoCo tasks over 20 runs, the proposed algorithm reduces the variance of cumulative rewards by $65.2\% \sim 85.6\%$ compared with those of existing algorithms.

1 Introduction

Deep reinforcement learning (DRL) [31] algorithms are quite unstable, namely, agents trained with different random seeds may have dramatically different performance. Existing works [1, 12, 6, 20] reported a high variance over multiple runs, thus it requires to train tens of agents and then pick the best one. Such a high variance puts a challenge on reliability and reproducibility [14, 13], limiting the wider adoption in real-world tasks.

The difficulty of guaranteeing stability lies in a foundational issue that **Bellman's optimality equation has multiple fixed points** [4, 26, 18, 16] —failing to return a consistent one. Consider MDP examples with an terminal state 0, as shown in Fig. 1 (we adapt dynamic programming examples [4, 26] into reinforcement learning settings; observational experiments in Section 2.2),

- **Shortest path problem (deterministic)** in Fig. 1(a): At state 1, an agent transits to either state 1 or 0 with reward 0 or b, respectively. Assume the value function for state 0 is $V(0) = 0$. The Bellman's optimality equation for state 1 is $V(1) = \max\{V(1), b\}$, where any $V(1) \geq b$ is a feasible solution. If initialize $V_0(1) \geq b$, a resulting policy is that an agent at state 1 always transits back to state 1; otherwise, drives to terminal state 0 (always returns back to itself with reward 0).

- **Blackmailer's problem (stochastic)** in Fig. 1(b): At state 1, a profit maximizing blackmailer demands a cash amount $a \in (0, 1]$; a victim transits to state 1 with probability a or state 0 with probability $1 - a$, respectively. At state 0, a victim always refuses to yield, i.e., $V(0) = 0$. The Bellman's optimality equation for state 1 is $V(1) = \max_a\{a + (1 - a)V(1)\}$, where any $V(1) \geq 1$ is a feasible solution. If initialize $V_0(1) > 1$, the blackmailer's policy is demanding $a \to 0$ to keep the victim at state 1; otherwise, demanding $a = 1$ that drives the victim to terminal state 0.

| (a) Shortest path problem | (b) Blackmailer's problem | (c) Optimal stopping problem |

Figure 1: MDP examples where $\gamma = 1$. More examples are given in Fig. 5 in Appx. A.

- **Optimal stopping problem (terminating policies)** in Fig. 1(c): In a space $\mathbb{R}^2$ with terminal state of point 0, an agent at point $x \neq 0$ moves to either point 0 with negative reward $-c$ or point αx with reward $-||x||$, respectively, where $\alpha \in (0, 1)$. The Bellman's optimality equation is $V(x) = \max\{-c, -||x|| + V(\alpha x)\}$ and the optimal policy is to continue inside the sphere of radius $(1 - \alpha)c$ and to stop outside. If add a cone region C within which an agent always receives a reward $-c$, a second policy is jumping to point 0 at any point in region C.

The instability problem has been partially addressed, such as ensemble methods [2, 7], regularization approaches [33, 8], and baseline-correction approaches [28, 36]. In particular, Generalized Advantage Estimation (GAE) [28] is a widely used one that significantly reduces the variance of the advantage function. However, they did NOT fix the foundational issue of Bellman's optimality equation in Fig. 1, thus the objective function inherently fails to search for a consistent policy. For practical usage, we expect a DRL algorithm stably converges to a certain policy independent of initialization and noises.

As a fix of the problem, we make a novel analogy between an MDP and a *quantum K-spin Ising model* [22, 11], and reformulate a reward-maximization RL task into an energy-minimization problem, namely, finding the lowest-energy configuration of a quantum spin system. We hypothesize that *a physically stationary policy would have the lowest energy*. Different from our quantum K-spin perspective, several recent papers utilized the (classical) Hamiltonian equation to endow RL agents the capability of inductive biases. For example, [17, 35] used Hamiltonian mechanics to train an agent that learns and respects *conservation laws*; [37] applied a Hamiltonian Monte Carlo (HMC) simulator to approximate the posterior action probability; and [24] proposed an unbiased estimator for the stochastic Hamiltonian gradient methods for min-max optimization problems.

In this paper, we propose a quantum-inspired *K-spin Hamiltonian regularization term (H-term)* that helps policy gradient algorithms stably converge to a physically stationary policy. Our contributions are as follows: 1) we derive a novel regularizer, *H-term*, by a novel reformulation of the RL's objective as a K-spin Hamiltonian equation that measures the energy of a policy; 2) we propose a generic actor-critic algorithm that utilizes the H-term to regularize the policy/actor network and provide Hamiltonian policy gradient calculations on both deterministic and stochastic cases; and 3) on six challenging MuJoCo tasks over 20 runs, we show that the proposed algorithm reduces the variance of cumulative rewards by $65.2\% \sim 85.6\%$ compared with those of existing algorithms.

2 Bellman's Optimality Equation and Multiple Fixed Points

We describe Bellman's optimaility equation and provide observational experiments to verify the existence of multiple policies.

2.1 Bellman's Optimality Equation

A reinforcement learning (RL) [31] agent interacts with an unknown environment and learns an optimal policy that maximizes the cumulative reward. Mathematically, the environment can be formulated as a Markov Decision Process (MDP) with the five-tuple $\langle \mathcal{S}, \mathcal{A}, \mathbb{P}, R, \gamma \rangle$. Here $\mathcal{S}$ and $\mathcal{A}$ denote the state and action spaces; $\mathbb{P} : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ denotes a transition probability function, where Δ is a probability simplex; $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ denotes a reward function; and $\gamma \in (0, 1]$ denotes a discount factor. The objective is to find an optimal policy $\pi^* : \mathcal{S} \to \Delta(\mathcal{A})$ that maximizes (discounted) expected reward.

Figure 2: Different policy types for four MuJoCo [34] tasks. **Two-legs running**, one-leg running, and running backward for Humanoid; **running**, diving, and balancing for Hopper; **running**, diving, balancing and flipping for HalfCheetah; **running** and flipping for Ant. The bold ones indicate physically stationary policies.

Consider a discrete, finite, discounted MDP with infinite horizon, one can define the Q-value function of a state-action pair (s, a) under policy π as follows

$$Q^\pi(s, a) = \mathbb{E}_{S_{k+1} \sim \mathbb{P}(\cdot | S_k, A_k), A_{k+1} \sim \pi(S_{k+1}, \cdot)} \left[\sum_{k=0}^{\infty} \gamma^k \cdot R(S_k, A_k, S_{k+1}) | S_0 = s, A_0 = a \right], \quad (1)$$

where $R(S_k, A_k, S_{k+1})$ denotes the immediate reward when taking action A_k at state S_k and arriving at state S_{k+1}, capital letters denote random variables and lowercase letters denote values. The conventional objective function $J(\theta)$ of reinforcement learning [31] takes the following form

$$J(\theta) \triangleq \mathbb{E}_{S_0, A_0}[Q^\pi(S_0, A_0)] = \mathbb{E}_{\tau \sim \pi}[R(\tau) \cdot P(\tau | \pi)], \quad (2)$$

where τ is a trajectory, i.e., $\tau = (S_0, A_0, \cdots)$, and $P(\tau | \pi) = d_0(s_0) \cdot \prod_{k=0}^T \mathbb{P}(S_{k+1} | s_k, a_k) \pi(a_k | s_k)$.

The Bellman equation [31] converts (1) into a recursive form as follows

$$\begin{aligned}
Q^\pi(s, a) &= \sum_{s' \in \mathcal{S}} \mathbb{P}(s' \mid s, a) \left[R(s, a, s') + \gamma \sum_{a' \in \mathcal{A}} \pi(s', a') Q^\pi(s', a') \right] \\
&= R(s, a) + \gamma \sum_{s' \in \mathcal{S}} \mathbb{P}(s' \mid s, a) \sum_{a' \in \mathcal{A}} \pi(s', a') Q^\pi(s', a'),
\end{aligned} \quad (3)$$

which expresses the expected reward as a summation of immediate reward $R(s, a)$ and discounted future rewards, and the immediate reward $R(s, a)$ is defined as $R(s, a) = \sum_{s' \in \mathcal{S}} \mathbb{P}(s' \mid s, a) R(s, a, s')$.

The Bellman's optimality equation [31] is

$$Q^*(s, a) = \sum_{s' \in \mathcal{S}} \mathbb{P}(s' \mid s, a) \left[R(s, a, s') + \gamma \max_{a'} Q^*(s', a') \right]. \quad (4)$$

The optimal policy π^* is given by a greedy strategy such that $\pi^* = \arg\max_\pi Q^\pi(s, a)$.

2.2 Observational Experiments for Multiple Polices and Physically Stationary Policy

As we pointed out in Fig. 1, theoretically there exists multiple policies. Here, we perform observational experiments on four challenging MuJoCo tasks [34], namely, Humanoid, Hopper, HalfCheetah, and Ant (details given in Appx. B.1), which are typical examples of the locomotion control of a robot.

We render the obtained policies over multiple runs and then identify physically stationary ones. We observe various types of moving strategies, as shown in Fig. 2, which verifies that multiple policies are very common. For example, the Humanoid agent learns either jumping with a single leg or running with two legs, as shown in Fig. 2 (top-left); another interesting example is HalfCheetah, in which an agent can run normally or in a flipped manner, as shown in Fig. 2(bottom-left). Among the obtained policies, one can easily identify the physically stationary polices that control the robot moving forward with a *stable gait* (defined as gait that does not lead to fall).

Table 1: Analogy between MDP and quantum K-spin Ising model.

MDP (Our formulation in (7))		Quantum K-spin Ising Model [22, 11] in (5)	
State-action pairs	$\mu_0, ..., \mu_{K-1}$	Spins	$j_0, \cdots, j_{K-1}$
Optimal policy	$\pi^*_{\mu_0} \times \pi^*_{\mu_1} \times \cdots \times \pi^*_{\mu_{K-1}}$	Quantum field	$\sigma_{j_0} \times \sigma_{j_1} \times \cdots \times \sigma_{j_{K-1}}$
Cumulative rewards	$L_{\mu_0...\mu_{K-1}}$	Density function	$L_{j_0 \cdots j_{K-1}}$
Functional of policy	$H(\pi_{\mu_0}, ..., \pi_{\mu_{K-1}})$	Functional of spins	$H(\sigma_{j_0}, \cdots, \sigma_{j_{K-1}})$
Stationary condition	$\frac{\delta H(\pi_{\mu_0}, \cdots, \pi_{\mu_{K-1}})}{\delta \pi_\mu} = 0$	Stationary condition	$\frac{\delta H(\sigma_{j_0}, \cdots, \sigma_{j_{K-1}})}{\delta \sigma_j} = 0$

3 Reinforcement Learning as Quantum K-spin Hamiltonian Equation

First, we make a novel analogy between the MDP and a quantum K-spin Ising model, and reformulate the objective function (2) into a quantum K-spin Hamiltonian equation. Then, we show that this Hamiltonian equation helps fix the issue of multiple fixed points in Fig. 1.

3.1 Motivation through Analogy with Quantum K-spin Ising Model

Given the multiple policies in Section 2.2, it is critical to employ a proper criteria to search for a physically stationary policy. In Table 1, we make a novel analogy between an MDP and a quantum K-spin Ising model [22, 11].

The Hamiltonian equation for a quantum K-spin Ising model [22] [11] measures the energy of a particular configuration of a quantum K-spin system and takes the following form

$$H = -\sum_{k=0}^{K-1} \sum_{j_0=1}^{N} \cdots \sum_{j_k=1}^{N} L_{j_0 \cdots j_k} \sigma_{j_0} \cdots \sigma_{j_k}, \tag{5}$$

where N is the number of spins in the k-th configuration, $\sigma_{j_k} = \pm 1$ are spin variables, and $L_{j_0 \dots j_k}$ is an energy density function for k nearest spins' configuration $(\sigma_{j_0}, \dots, \sigma_{j_k})$.

Analogy in Table 1. Starting from an analogy between a state-action pair $\mu_k = (S_k, A_k)$ and a spin j_k, we can map an optimal policy $\pi^*(\mu_k) \in \{0, 1\}$ in (4) to a single-qubit spin operator $\sigma_{j_k} \in \{-1, 1\}$ via $\pi^*(\mu_k) \longleftrightarrow (\mathbb{1}_{\mu_k} - \sigma_{\mu_k})/2$, where $\pi_\theta(\mu_k)$ denotes the probability of taking action A_k at state S_k, following policy π_θ. The energy density function $L_{j_0 \dots j_k}$ can be defined as the discounted cumulative reward on a path $(\mu_0, \cdots, \mu_{k-1})$ of length k, i.e.,

$$L_{\mu_0, \dots, \mu_k} = \gamma^k \cdot R(\mu_k) \cdot d_0(S_0) \cdot \prod_{i=0}^{k-1} \mathbb{P}(S_{i+1}|\mu_i), \quad \text{(obtained via Monte Carlo simulation)} \tag{6}$$

where $d_0(S_0)$ denotes the distribution of initial state S_0. Analogy to the quantum K-spin Ising model, we can derive a functional of policy $H(\pi_{\mu_0}, ..., \pi_{\mu_{K-1}})$ in the context of MDP, which measures the energy of an RL policy. In this case, a physically stationary policy satisfies the stationary condition $\delta H(\pi_{\mu_0}, \cdots, \pi_{\mu_{K-1}})/\delta \pi_\mu = 0$.

3.2 Reformulation into Quantum K-spin Hamiltonian Equation

We formally reformulate (2) into a K-spin Hamiltonian equation

$$H(\theta) \triangleq -\mathbb{E}_{S_0, A_0}[Q^{\pi_\theta}(S_0, A_0)] = -\sum_{k=0}^{K-1} \sum_{\mu_0}^{\mathcal{S} \times \mathcal{A}} \cdots \sum_{\mu_k}^{\mathcal{S} \times \mathcal{A}} L_{\mu_0, \dots, \mu_k} \pi_\theta(\mu_0) \cdots \pi_\theta(\mu_k), \tag{7}$$

where $K \to \infty$, the expectation is taken over $S_0 \sim d_0(\cdot)$, $A_0 \sim \pi_\theta(S_0, \cdot)$, and the density function $L_{\mu_0, \dots, \mu_k}$ is given in (6).

Physical interpretation: Analogy to a quantum K-spin system, $H(\theta)$ in (7) measures the energy of policy π. We hypothesize that the energy of a policy is a favorable criteria, since a stationary policy with minimum energy: 1). *achieves a relative high reward independent of the initialization*; and 2). *is robust to interference/noise in the inference stage*.

K-step truncation in practice. Minimizing (7) is NP-hard [10]. Since $\gamma \in (0, 1)$, γ^K monotonically decreased with look-ahead steps K, therefore, we truncate (7) to finite K terms. One can show that these K terms in (7) is a geometric sequence with a truncation error ratio $1 - \gamma^K$. Assuming $1 - \gamma^K \leq 1 - \epsilon$, where $\epsilon > 0$ is small, thus we have the look-ahead steps satisfies $K \geq \log_\gamma \epsilon$.

3.3 Revisiting Examples in Fig. 1

We elaborate how adding the energy measured by (7) onto each state can help drive to the terminal state (a stationary policy), which fixes the foundational issue of multiple fixed points in Fig. 1 where $\gamma = 1$. We have $H(0) = 0$ for the terminal state 0.

- (a) **Shortest path problem (deterministic)**: $H(1) = -\sum_{k=1}^{\infty} b = -\infty$. At state 1, the Bellman's optimality equation becomes $V(1) = \max\{V(1) + \lambda H(1), b\}$. Independent of the initial value $V_0(1)$, an agent obtains a policy that always transits back to terminal state 0.

- (b) **Blackmailer's problem (stochastic)**: $H(1) = -\infty$. The Bellman's optimality equation becomes $V(1) = \max_a\{a + (1-a)(V(1) + \lambda H(1))\}$ for state 1. For any $V_0(1) < \infty$, the optimal policy becomes $a = 1$ that drives to the terminal state 0.

- (c) **Optimal stopping problem (terminating policies)**: any policy that takes infinite steps will have $H(x) = -\infty$, since at each step number k, there are always trajectories that jump to point 0 with reward $-c$; and a direct jumping policy will have $H(x) = -c$. Therefore, adding $H(x)$ to each point $x \neq 0$ will lead to a policy of *jumping back to point* 0.

4 Actor-Critic Algorithm with Quantum K-spin Hamiltonian Regularization

We propose a generic actor-critic algorithm with a H-term, derive two Hamiltonian's policy gradient theorems for both deterministic and stochastic cases, and present the Monte Carlo gradient estimation.

4.1 Stationary Actor-Critic Algorithm with H-term

Actor-critic algorithms in reinforcement learning perform a bilevel optimization, namely alternating between approximating a value function and optimizing a policy. In practice, a critic network with parameter ϕ approximates the Q-value function, and an actor network with parameter θ approximates the policy π, details given in Appx. E. However, since the critic's update is governed by the Bellman's optimality equation, actor-critic algorithms suffer the multiple fixed points problem.

Motivated by Section 3.3, we propose a novel H-term for both deterministic and stochastic actor-critic algorithms. Similar to the entropy term in [19], the proposed H-term is an add-on term to regularize the actor network and help it converge to a stationary policy. Specifically, the objective functions of actor and critic networks become:

$$
\begin{cases}
\text{Actor}: \max_{\theta} J_\pi(\theta, \phi) \triangleq (1-\gamma)\mathbb{E}_{S_0 \sim d_0, A_0 \sim \pi_\theta(S_0, \cdot)}\left[Q_\phi(S_0, A_0)\right] - \lambda H(\theta), \\
\text{Critic}: \min_{\phi} J_Q(\theta, \phi) \triangleq \frac{1}{2}\mathbb{E}_{S \sim d_\theta(\cdot), A \sim \pi_\theta(S, \cdot)}\left[(Q_\phi(S, A) - y(S, A))^2\right],
\end{cases}
\tag{8}
$$

where a target Q-value is $y(S_k, A_k) = R(S_k, A_k) + \gamma Q_\phi(S_{k+1}, A_{k+1})$, and $\lambda > 0$ is a temperature parameter. As an interpretation, the second term $-\lambda H(\theta)$ in the maximization objective function of actor network aims to find a minimum energy configuration for the MDP problem, namely, a policy π that will add a minimum amount of energy to each state's value function (as in Section 3.3).

New algorithm. In Alg. 1, an agent interacts with an environment and alternatively updates its actor network and critic network. The algorithm has M episodes and each episode consists of a (Monte Carlo) simulation process and a learning process (gradient estimation) as follows:

- During the (Monte Carlo) simulation process (lines 5-10 of Alg. 1), an agent takes action a_t according to a policy $\pi_\theta(\cdot|s_t)$, $t = 0, \cdots, T-1$, generating a trajectory of T steps/transitions. Then, these T transitions are stored into a replay buffer $\mathcal{D}_1$, while the full trajectory $\tau = (s_0, a_0, r_0, s_1, \cdots, s_{T-1}, a_{T-1}, r_{T-1}, s_T)$ is stored in replay buffer $\mathcal{D}_2$.

- During the learning process ($G \geq 1$ updates in one episode) (lines 11-16 of Alg. 1), a mini-batch of B transitions $\{(s_i, a_i, r_i, s_{i+1})\}_{i=1}^{B}$ and a mini-batch of B' trajectories (of length K) $\{\tau_j = (s_0^j, a_0^j, r_0^j, s_1^j, \cdots, s_{K-1}^j, a_{K-1}^j, r_{K-1}^j, s_K^j)\}_{j=1}^{B'}$ are sampled from $\mathcal{D}_1$ and $\mathcal{D}_2$, respectively. The critic network is updated by a conventional method, e.g., minimizing the mean squared error (MSE) between an estimated Q-value and a target value. The actor is updated by a Monte Carlo gradient estimator over B transitions and B' trajectories.

Algorithm 1 Stationary Actor-Critic Algorithm with H-term

1: **Input**: learning rate α, temperature λ, look-ahead step K, and parameters M, T, G, B, B'
2: Initialize actor network π and critic network Q with parameters θ, ϕ, and replay buffers $\mathcal{D}_1, \mathcal{D}_2$
3: **for** episode $= 1, \cdots, M$ **do**
4:     Initialize state s_0
5:     **for** $t = 0, \cdots, T - 1$ **do**
6:         Select action $a_t \sim \pi_\theta(\cdot|s_t)$
7:         Execute action a_t, receive reward r_t, and observe new state s_{t+1}
8:         Store a transition (s_t, a_t, r_t, s_{t+1}) in $\mathcal{D}_1$
9:     **end**
10:    Store a trajectory τ of length T in $\mathcal{D}_2$
11:    **for** $g = 1, \cdots, G$ **do**
12:        Randomly sample a mini-batch of B transitions $\{(s_i, a_i, r_i, s_{i+1})\}_{i=1}^{B}$ from $\mathcal{D}_1$
13:        Randomly sample a mini-batch of B' trajectories (of length K) $\{\tau_j\}_{j=1}^{B'}$ from $\mathcal{D}_2$
14:        Update critic network using a conventional method
15:        Update actor network as $\theta \leftarrow \theta + \alpha \left(\nabla_\theta \widehat{J}(\theta) - \lambda \nabla_\theta \widehat{H}(\theta) \right)$.
16:    **end**
17: **end**

Two new hyperparameters. We introduce two hyperparameters: a temperature $\lambda > 0$ that is a relative weight of the H-term, and a look-ahead step $K \leq T$ that defines the horizon of the H-term.

Implementation of replay buffer $\mathcal{D}_2$. After a full trajectory τ of length T is generated, it is partitioned into $T - K + 1$ trajectories of length K. We rank them according to the cumulative reward and store the top portion, say 80%, into a new replay buffer $\mathcal{D}_2$ (line 10 of Alg. 1). We randomly sample a mini-batch of B' trajectories from $\mathcal{D}_2$ (line 13 of Alg. 1) to compute the H-term.

4.2 Hamiltonian Policy Gradient and Monte Carlo-based Gradient Estimator

We provide the policy gradient of the quantum K-spin Hamiltonian equation in (7), which are variants of the well-known policy gradient theorem [31]. We provide detailed derivations in Appx. D.

Stochastic version. The Hamiltonian stochastic gradient of (7) w.r.t. parameter θ is

$$\nabla_\theta H(\theta) = -\mathbb{E}_{\mu_0, \ldots, \mu_{K-1}} \left[\sum_{k=0}^{K-1} \gamma^k \cdot R(\mu_k) \cdot \nabla_\theta \log \left(\pi_\theta(\mu_0) \cdot \pi_\theta(\mu_1) \cdots \pi_\theta(\mu_k) \right) \right]. \quad (9)$$

Deterministic version. Let $\eta_\theta(\cdot) : \mathcal{S} \to \mathcal{A}$ denote a deterministic policy, while we use $\widetilde{\pi}_{\theta,\delta}(\mu)$ to represent that a Gaussian noise (a.k.a, an exploration noise) with standard deviation $\delta > 0$ is added in the exploration process. The Hamiltonian deterministic gradient of (7) w.r.t. parameter θ is

$$\nabla_\theta H'(\theta) = -\mathbb{E}_{\mu_0, \ldots, \mu_{K-1}} \left[\sum_{k=0}^{K-1} \gamma^k \cdot R(\mu_k) \cdot \nabla_\theta \log \left(\widetilde{\pi}_{\theta,\delta}(\mu_0) \cdot \widetilde{\pi}_{\theta,\delta}(\mu_1) \cdots \widetilde{\pi}_{\theta,\delta}(\mu_k) \right) \right]. \quad (10)$$

The quantum K-spin Hamiltonian equation in (7) is a reformulation of (2). We verify the gradient calculation by showing that: when $K \to \infty$, the Hamiltonian stochastic and deterministic policy gradient $\nabla_\theta H(\theta)$ and $\nabla_\theta H'(\theta)$ are equal to the stochastic policy gradient $\nabla_\theta J(\theta)$ in [32] and deterministic policy gradient $\nabla_\theta J'(\theta)$ in [30], respectively.

Note that the gradient $\nabla_\theta H(\theta)$ in (9) and $\nabla_\theta H'(\theta)$ in (10) w.r.t. a distributional parameter θ takes an expectation form. Thus, a Monte Carlo gradient estimator is practically useful. We obtain the Monte Carlo gradient estimator of $\nabla_\theta H(\theta)$, illustrated in Fig. 3 (right), as follows

$$\nabla_\theta \widehat{H}(\theta) = -\frac{1}{N'} \sum_{i=1}^{N'} \left[\sum_{k=0}^{K-1} \gamma^k \cdot R(\mu_k^i) \cdot \nabla_\theta \log \left[\pi_\theta(\mu_0^i) \cdots \pi_\theta(\mu_k^i) \right] \right]. \quad (11)$$

Figure 3: Comparison of REINFORCE's (left) and Hamiltonian's policy gradient (right).

As a contrast, we provide the Monte Carlo gradient estimator of REINFORCE's [32] policy gradient, as illustrated in Fig. 3 (left), as follows

$$\nabla_\theta \widehat{J}(\theta) = \frac{1}{NT} \sum_{i=1}^{N} \left[\sum_{t=0}^{T-1} G_t^i \cdot \nabla_\theta \log \pi_\theta(\mu_t^i) \right], \text{ where } G_t^i = \sum_{t'=t+1}^{T} \gamma^{t'-t-1} R(\mu_{t'}^i). \quad (12)$$

An interesting observation is that both gradient calculations follow a similar pattern as shown in Fig. 3. REINFORCE's policy gradient [32] in Fig. 3 (left) employs an estimate of future rewards, while Hamiltonian policy gradient in Fig. 3 (right) uses trajectories in replay buffer $\mathcal{D}_2$.

Computational complexity: we measure the computation complexity by the times of computing one $\nabla_\theta \log \pi_\theta(\mu)$. Assume $N = B$ and $N' = B'$, since most DRL algorithms use a mini-batch stochastic gradient decent methods. REINFORCE's [32] policy gradient in (12) takes $O(BT)$ computations, while Alg. 1 adds $O(B'K(K+1)/2)$ computations in each gradient update step, thus a total complexity of $O(BT + B'K(K+1)/2)$.

5 Performance Evaluation

We evaluate the proposed H-term from four aspects: 1) increasing cumulative reward, 2) reducing variance, 3) driving to physically stationary policy, and 4) the impact of trajectory length K. All experiments were executed on an NVIDIA DGX-2 server [9]. The server contains 8 A100 GPUs, 320 GB GPU memory, and 128 CPU cores running at 2.25 GHz.

5.1 Experimental Settings

Environments (tasks). We consider six challenging MuJoCo tasks [34] as in Section 2.2. The agent learns to control the locomotion of a robot and aims to move forward as quickly as possible. These tasks have high-dimensional continuous state and action spaces, in which there exists multiple locally optimal polices as revealed in Section 2.2.

Compared algorithms. To evaluate deterministic and stochastic algorithms, we choose Deep Deterministic Policy Gradient (DDPG) [23] and Proximal Policy Optimization (PPO) [29]. Since the H-term is compatible with existing variance reduction techniques, we implement the PPO algorithm with GAE [28]. For a fair comparison, we keep the hyperparameters (listed in Appx. G) the same and make sure that the obtained results reproduce existing benchmark tests [12].

Performance metrics. We employ two performance metrics, the cumulative rewards and variance, while in Section 5.4, we further consider different policies and report the number of convergence. We run each experiment with 20 random seeds and in each run we test 100 episodes.

5.2 H-term Increases Cumulative Reward

Experience replay is crucial in improving performance in terms of cumulative reward. The proposed H-term in (11) can be viewed as a novel experience replay technique for an actor network. Here, we add a compared algorithm, DDPG with Prioritized Experience Replay [27] (DDPG+PER), where PER prioritizes experience by the TD error to update a critic network.

In Fig. 4, both DDPG+PER and DDPG+H achieve a substantial improvement of cumulative reward. In particular, DDPG+H achieves the highest cumulative rewards in all six tasks, which are comparable to PPO's performance in Fig. 4. It is worthwhile to discuss the advantage of DDPG+H over DDPG+PER. DDPG+PER utilizes a prioritized replay strategy to obtain a more accurate critic network, however, it is updated via the Bellman equation with the trouble of multiple fixed points. In contrast, the H-term in DDPG+H is performed on the actor network. Our results indicate that an experience replay technique on actor network may be much more powerful.

Figure 4: Cumulative rewards vs. #samples for compared DRL algorithms on six MuJoCo tasks.

5.3 H-term Reduces Variance

The PPO algorithm with GAE is regarded as the state-of-the-art algorithm in MuJoCo environments. However, it still has a very high variance (the shaded area) after the policies have converged, as shown in Fig. 4. We observe that, at the end of training, the PPO algorithm has a variance of 969.2, $1563.4, 2513.5, 905.3, 60.7, 1290.1$ in the six tasks, respectively. Such a high variance is mainly due to the fact that the agent may converge to a random one of multiple policies.

In Fig. 4, the shaded areas of PPO+H ($K = 16$) are dramatically smaller, i.e., a variance of 228.4, $225.4, 683.7, 184.2, 31.6,$ and 296.8, respectively. The variance has been reduced by $65.2\% \sim 85.6\%$, which verifies the effectiveness of the proposed H-term. In Fig. 4, we also observe that the H-term can help the DDPG algorithm reduce variances, namely, the variances of DDPG+H are much smaller than those of vanilla DDPG and DDPG+PER. Therefore, we may conclude that the H-term guides the agent to search for a stationary policy among multiple feasible ones.

More experimental results are given in Appx. G due to the space limit, including the cases of $K = 8$ and $K = 24$, and the curves of the H-term value during the training process. One may verify that the stationary policies have relative lower H-values.

5.4 H-term Drives to Physically Stationary Policy

A key question needs to be answered: *is H-term really guiding the agent converge to a physically stationary policy?* Similar to Section 2.2, we perform observational experiments on the six MuJoCo tasks and measure the number of convergence to the different policies over 20 runs. As shown in

Table 2: Experimental results on six challenging MuJoCo tasks.

Tasks	Policies	PPO		PPO+H ($K=8$)		PPO+H ($K=16$)		PPO+H ($K=24$)	
HalfCheetah	**running**	**13**	4720.8 ±969.2	**19**	5028.4 ±211.3	**20**	5104.3 ±228.4	**20**	4995.1 ±383.3
	flipping	5		0		0		0	
	diving	1		1		0		0	
	balancing	1		0		0		0	
Ant	**running**	**17**	4164 ±1563.4	**20**	4505.3 ±253.6	**20**	4645.6 ±225.4	**20**	4662.5 ±277.5
	jumping	0		0		0		0	
	flipping	3		0		0		0	
Humanoid	**two-legs**	**7**	9433.4 ±2513.5	**17**	9670.3 ±497.2	**16**	10189.1 ±683.7	**17**	9942.2 ±538.4
	one-leg	12		3		4		3	
	backward	1		0		0		0	
Hopper	**hopping**	**10**	2659.3 ±905.3	**18**	3116.5 ±289.4	**20**	3300.1 ±184.2	**20**	3340.7 ±191.5
	diving	8		2		0		0	
	balancing	2		0		0		0	
Swimmer	**moving**	**14**	110.7 ±60.7	**20**	130.6 ±33.5	**20**	132.5 ±31.6	**19**	132.2 ±36.2
	balancing	6		0		0		1	
Walker	**walking**	**5**	5461.7 ±1290.1	**16**	5819.9 ±315.6	**16**	5927.2 ±296.8	**15**	6089.3 ±314.7
	diving	8		2		4		5	
	balancing	7		2		0		0	

Table 2, the vanilla PPO algorithm converges to the physically stationary policy (**bold**) with 13, 17, 7, 10, 14, and 5 times for the six tasks, while the PPO+H ($K = 16$) converges to the stationary policy with 20, 20, 16, 20, 20, and 16 times, respectively. From the empirical observation, we find that the PPO gets stuck in locally optimal policies, failing to find a consistent one. As expected, PPO+H can converge to the stationary policy with a substantially higher ratio, which verifies the effectiveness of the proposed H-term in finding a physically stationary policy.

5.5 Impact of Trajectory Length K

We investigate the impact of trajectory length K that defines the horizon of the H-term. Based on (11), we foresee that a large K means a more accurate estimation of $\nabla_\theta H(\theta)$ but at a price of computations. Here, we evaluate the PPO+H with $K = 8, 16$ and set the size of replay buffer $\mathcal{D}_2$ to $1,000$. In Table 2, we observe that the cumulative reward increases and the variance decreases as K increases from 8 to 16. However, for the case $K = 24$, both metrics get worse due to the out-of-memory issue. For $K = 24$, we reduce the replay buffer size to 800 to meet the memory limit. The smaller replay buffer size hurts the diversity of the trajectories and may lead to a small performance drop.

6 Conclusions

In this paper, we have addressed a foundational issue of existing deep reinforcement learning algorithms that **Bellman's optimality equation has multiple fixed points**. This issue leads to the instability of DRL algorithms, puts a challenge on their reliability and reproducibility, and thus limits the wider adoption in real-world tasks. As a fix of the problem, we propose a novel H-term, a physically inspired regularizer, by making a novel analogy between a MDP and a quantum K-spin Ising model. Experimentally, we show that the H-term helps DRL algorithms find a stationary policy that has the lowest energy in a system and reduces the variance of cumulative rewards by $65.2\% \sim 85.6\%$ compared with those of existing algorithms.

For future works, we will explore the potential of directly training a policy network using (7) as in Appx. H, quantum simulator [21] and quantum reinforcement learning [5][15]. It is interesting to apply Monte Carlo estimator for unbiased policy gradient calculations. We would like to show that the proposed H-term can help distributional RL algorithms [3] find a stationary policy, since the distributional Bellman optimality operator is not a contraction and thus there is also no unique policy.

Broader Impact Statement

In the field of DRL research, this paper points out the issue of multiple fixed points and may attract more attention from various perspectives. In terms of applications, this paper moves toward the reliable and reproducible research by improving the stability of existing DRL algorithms. On the other hand, the obtained stationary policy may have broad practical impact in many real-world application areas, including but not limited to robotics, transportation, and finance.

From an interdisciplinary perspective, our approach lies at the intersection of (quantum) Hamiltonian mechanics and DRL, espcially the explicit analogy between an MDP and a quantum K-spin Ising model. We hope that our study will attract more attention to bring together the strengths of both approaches and yield new insights in both fields.

In terms of broader societal impact of this work, we do not see any foreseeable strongly negative impacts. However, this work essentially makes a tradeoff between the computational resource and stability, which may lead to future works with higher computational cost.

References

[1] Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron C Courville, and Marc Bellemare. Deep reinforcement learning at the edge of the statistical precipice. *Advances in Neural Information Processing Systems*, 2021.

[2] Oron Anschel, Nir Baram, and Nahum Shimkin. Averaged-DQN: Variance reduction and stabilization for deep reinforcement learning. In *International Conference on Machine Learning*, pages 176–185. PMLR, 2017.

[3] Marc G Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. In *International Conference on Machine Learning*, pages 449–458. PMLR, 2017.

[4] Dimitri Bertsekas. *Reinforcement Learning and Optimal Control*. Athena Scientific, 2019.

[5] Jacob Biamonte, Peter Wittek, Nicola Pancotti, Patrick Rebentrost, Nathan Wiebe, and Seth Lloyd. Quantum machine learning. *Nature*, 549(7671):195–202, 2017.

[6] Stephanie CY Chan, Samuel Fishman, Anoop Korattikara, John Canny, and Sergio Guadarrama. Measuring the reliability of reinforcement learning algorithms. 2019.

[7] Xinyue Chen, Che Wang, Zijian Zhou, and Keith Ross. Randomized ensembled double q-learning: Learning fast without a model. *ICLR*, 2021.

[8] Richard Cheng, Abhinav Verma, Gabor Orosz, Swarat Chaudhuri, Yisong Yue, and Joel Burdick. Control regularization for reduced variance reinforcement learning. In *International Conference on Machine Learning*, pages 1141–1150. PMLR, 2019.

[9] Jack Choquette, Wishwesh Gandhi, Olivier Giroux, Nick Stam, and Ronny Krashinsky. NVIDIA A100 Tensor Core GPU: Performance and innovation. *IEEE Micro*, 41(2):29–35, 2021.

[10] Barry A Cipra. The ising model is np-complete. *SIAM News*, 33(6):1–3, 2000.

[11] Vasil S Denchev, Sergio Boixo, Sergei V Isakov, Nan Ding, Ryan Babbush, Vadim Smelyanskiy, John Martinis, and Hartmut Neven. What is the computational value of finite-range tunneling? *Physical Review X*, 6(3):031015, 2016.

[12] Yan Duan, Xi Chen, Rein Houthooft, John Schulman, and Pieter Abbeel. Benchmarking deep reinforcement learning for continuous control. In *International Conference on Machine Learning*, pages 1329–1338. PMLR, 2016.

[13] Gabriel Dulac-Arnold, Nir Levine, Daniel J Mankowitz, Jerry Li, Cosmin Paduraru, Sven Gowal, and Todd Hester. An empirical investigation of the challenges of real-world reinforcement learning. *arXiv preprint arXiv:2003.11881*, 2020.

[14] Gabriel Dulac-Arnold, Daniel Mankowitz, and Todd Hester. Challenges of real-world reinforcement learning. 2019.

[15] Vedran Dunjko, Jacob M Taylor, and Hans J Briegel. Quantum-enhanced machine learning. *Physical review letters*, 117(13):130501, 2016.

[16] Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. *ICLR*, 2019.

[17] Samuel Greydanus, Misko Dzamba, and Jason Yosinski. Hamiltonian neural networks. *Advances in Neural Information Processing Systems*, 32, 2019.

[18] Agrim Gupta, Silvio Savarese, Surya Ganguli, and Li Fei-Fei. Embodied intelligence via learning and evolution. *Nature Communications*, 12(1):1–12, 2021.

[19] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pages 1861–1870. PMLR, 2018.

[20] Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.

[21] Eric B Jones, Peter Graf, Eliot Kapit, and Wesley Jones. K-spin Hamiltonian for quantum-resolvable markov decision processes. *Quantum Machine Intelligence*, 2(2):1–11, 2020.

[22] Scott Kirkpatrick, C Daniel Gelatt Jr, and Mario P Vecchi. Optimization by simulated annealing. *Science*, 220(4598):671–680, 1983.

[23] Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *ICLR*, 2016.

[24] Nicolas Loizou, Hugo Berard, Alexia Jolicoeur-Martineau, Pascal Vincent, Simon Lacoste-Julien, and Ioannis Mitliagkas. Stochastic Hamiltonian gradient methods for smooth games. In *International Conference on Machine Learning*, pages 6370–6381. PMLR, 2020.

[25] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing Atari with deep reinforcement learning. *ICLR*, 2013.

[26] Alexey B Piunovskiy. *Examples in Markov Decision Processes*, volume 2. World Scientific, 2013.

[27] Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. *ICLR*, 2016.

[28] John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *ICLR*, 2016.

[29] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017.

[30] David Silver, Guy Lever, Nicolas Heess, Thomas Degris, Daan Wierstra, and Martin Riedmiller. Deterministic policy gradient algorithms. In *International Conference on Machine Learning*, pages 387–395. PMLR, 2014.

[31] Richard S Sutton and Andrew G Barto. *Reinforcement Learning: An Introduction*. MIT press, 2018.

[32] Richard S Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. *Advances in Neural Information Processing Systems*, 12, 1999.

[33] Pierre Thodoroff, Audrey Durand, Joelle Pineau, and Doina Precup. Temporal regularization for markov decision process. *Advances in Neural Information Processing Systems*, 31, 2018.

[34] Emanuel Todorov, Tom Erez, and Yuval Tassa. MuJoCo: A physics engine for model-based control. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5026–5033. IEEE, 2012.

[35] Peter Toth, Danilo Jimenez Rezende, Andrew Jaegle, Sébastien Racanière, Aleksandar Botev, and Irina Higgins. Hamiltonian generative networks. *ICLR*, 2019.

[36] Cathy Wu, Aravind Rajeswaran, Yan Duan, Vikash Kumar, Alexandre M Bayen, Sham Kakade, Igor Mordatch, and Pieter Abbeel. Variance reduction for policy gradient with action-dependent factorized baselines. *ICLR*, 2018.

[37] Duo Xu and Faramarz Fekri. Improving actor-critic reinforcement learning via Hamiltonian Monte Carlo method. *Deep Reinforcement Learning Workshop at NeurIPS*, 2021.