KItCAT: Knowledge Injection via Input Corruption for Auto-regressive Training

Abstract

LLMs acquire vast amounts of knowledge during pre-training, but often lack the specialized knowledge needed to answer questions from niche sources such as manuals or technical documents unseen during pre-training. Continued pre-training (CPT) is widely used to inject such knowledge into model parameters. However, niche documents seldom repeat facts, making it difficult for CPT to robustly acquire such knowledge. Recent works address this by generating multiple paraphrases of the new knowledge, but paraphrasing is computationally expensive and typically requires powerful LLMs. In this work, we introduce KItCAT: Knowledge Injection via Corrupted Auto-regressive Training, a lightweight training strategy that reduces the need for paraphrasing in decoder-only LLMs. KItCAT augments standard next-token prediction by stochastically corrupting the input sequence. During training, a random subset of input tokens is replaced with other vocabulary tokens while the original next-token labels are kept unchanged. This simple intervention generates diverse training inputs from each sample, enabling large-scale data augmentation at negligible cost. We show that KItCAT consistently improves over CPT across multiple datasets.

1 Introduction

LLMs are pre-trained on massive web corpora, yet they often fail to capture specialized knowledge that is absent or underrepresented on the public web, such as information contained in proprietary manuals or technical documents. Continued Pre-Training (CPT) (Ke et al., 2023, 2025) is a common approach for injecting such specialized knowledge into the parameters of the LLMs.

A key challenge, however, is that the niche documents seldom repeat facts or present them in varied contexts. Consequently, CPT receives limited repeated exposure to newly introduced knowledge, making it difficult for the model to robustly internalize these facts (Allen-Zhu and Li, 2024). In such low-diversity training settings, models can instead overfit to surface-level lexical patterns and spurious correlations that recur across epochs, rather than learning the underlying semantics.

To mitigate the limited diversity in the training documents, recent works propose to synthetically generate multiple paraphrases of the text (Ovadia et al., 2024; Yang et al., 2025). While effective, these approaches rely on large proprietary LLMs (Achiam et al., 2023; Team et al., 2023), which can be costly and slow when generating sizable synthetic datasets. They may also be infeasible in settings with privacy restrictions.

In this work, we ask - *can we introduce effective data diversity without relying on external synthetic data generation*? We observe that overfitting in low-diversity regimes is amplified by the fact that the model encounters the exact same training samples in every epoch. If the model latches onto a spurious pattern in one pass, repeated identical exposure reinforces this shortcut, degrading generalization.

Our key insight is that preventing the model from ever seeing the exact same input twice can mitigate this reinforcement effect. Motivated by this idea, we propose KItCAT - Knowledge Injection via Corrupted Auto-regressive Training, a simple yet effective strategy for injecting diversity through controlled corruption of the input. During training, KItCAT perturbs input sequences by replacing a random subset of tokens with other tokens from the vocabulary.

We explore two corruption schemes: (1) random replacement, where selected tokens are substituted with randomly sampled vocabulary items, and (2) mask replacement, where tokens are replaced with a special mask token (e.g., [MASK]). In decoder-only models, corruption is applied solely to the conditioning input while the target labels remain

unchanged. Under random replacement, the model must learn to ignore irrelevant noise, whereas in mask-based corruption, the missing information is explicitly signaled. By preventing the model from encountering identical inputs across epochs, KItCAT reduces reinforcement of spurious lexical patterns and encourages learning more semantically grounded representations.

Experiments across multiple knowledge-injection benchmarks show that KItCAT consistently outperforms standard CPT. Notably, KItCAT is agnostic to the input text and can be applied directly to original corpora as well as to paraphrases used to strengthen CPT. This makes it complementary to existing approaches and reduces the reliance on paraphrasing. Overall, our contributions are:

(1) We propose Knowledge Injection via Corrupted Auto-regressive Training(KItCAT), a lightweight and generalizable data augmentation method for fine-tuning decoder-only language models by stochastically corrupting input tokens while preserving the original autoregressive training objective.

(2) We empirically demonstrate that KItCAT consistently improves standard CPT.

(3) We posit KItCAT as the most lightweight data augmentation technique that induces effective data diversity to prevent overfitting, significantly reducing the need of expensive synthetic data.

2 Related Work

Approaches to injecting knowledge into LLM parameters can be broadly categorised as CPT-based methods and SFT-based methods. CPT-based methods inject knowledge using raw domain text and its paraphrases (Wu et al., 2024; Christophe et al., 2024; Ke et al., 2023; Zhao et al., 2025; Zhang et al., 2024; Wu et al., 2023; Shah et al., 2022; Xie et al., 2023). SFT-based methods use powerful LLMs to transform raw text into task-oriented formats such as QA, summarization, or reading comprehension (Ovadia et al., 2025; Bhushan et al., 2025). Both approaches benefit from high-diversity training data and, in its absence, often rely on generating large amounts of synthetic paraphrases or SFT data using powerful LLMs. In contrast, our work focuses on CPT-style knowledge injection and proposes lightweight input corruption as an alternative to expensive paraphrase generation.

We discuss works that study input corruption for training LLMs in Appendix A.2.

3 The KItCAT approach

Preliminaries: Let $\mathcal{D}$ be the new knowledge that we want to inject in our pretrained model p_θ. Let $\mathcal{V}$ denote the vocabulary and $\mathbf{s} = (s_1, ..., s_T)$ be a token sequence drawn from $\mathcal{D}$, where $s_t \in \mathcal{V}, 1 \leq t \leq T$.

$$\mathcal{L}_{\text{NTP}}(\theta) = \mathbb{E}_{\mathbf{s} \sim \mathcal{D}} \sum_{t=1}^{T} -\log p_\theta(s_t | s_{<t}) \quad (1)$$

Here, $s_{<t}$ is a prefix of the sequence $\mathbf{s}$.

Knowledge Injection via Input Corruption: The $\mathcal{L}_{\text{NTP}}$ objective maximizes the likelihood of a token s_t conditioned on its exact prefix $s_{<t}$. When seen multiple times across epochs, the model may overfit to spurious correlations between $s_{<t}$ and s_t.

To mitigate this, we propose KItCAT: Knowledge Injection via Corrupted Auto-regressive Training. Let $\mathcal{Q}(\tilde{\mathbf{s}} \mid \mathbf{s})$ denote a distribution over corrupted versions of the input sequence $\mathbf{s}$. Instead of conditioning only on the exact prefix, KItCAT trains on corrupted prefixes sampled from $\mathcal{Q}(\tilde{\mathbf{s}} \mid \mathbf{s})$ while preserving the target token as a likely continuation. The model is thus encouraged to predict the same target under perturbed contexts.

$$\mathcal{L}_{\text{CAT}}(\theta) =$$
$$\mathbb{E}_{\mathbf{s} \sim \mathcal{D}} \mathbb{E}_{\tilde{\mathbf{s}} \sim \mathcal{Q}(.|\mathbf{s})} \sum_{t=1}^{T} -\log p_\theta(s_t | \tilde{s}_{<t}), \quad (2)$$

where $\tilde{s}_{<t}$ is a prefix of the corrupted input $\tilde{\mathbf{s}}$. Intuitively, training on perturbed prefixes prevents reliance on spurious lexical patterns. Instead, it encourages the model to use information that remains present across perturbations.

To construct perturbations $\tilde{\mathbf{s}}$, we consider two stochastic in-place token modifications in the sequence $\mathbf{s}$: (1) *KItCAT-mask*, which replaces tokens with a special mask token, and (2) *KItCAT-rand*, which replaces tokens with randomly sampled vocabulary tokens. For both, we sample a binary corruption indicator $c_j \sim \text{Bernoulli}(p)$ independently for each position $j \leq T$.

KItCAT-mask. If $c_j = 1$, the token is replaced with a special mask token, i.e., $r_j = [\text{MASK}]$.

KItCAT-rand. If $c_j = 1$, the token is replaced with a uniformly sampled token, i.e., $r_j \sim \text{Unif}(\mathcal{V})$.

In both cases, the corrupted token is given by

$$\tilde{s}_j = \begin{cases} r_j & \text{if } c_j = 1 \\ s_j & \text{otherwise.} \end{cases}$$

where corruption is applied only to the conditioning prefix and the target token s_t remains unchanged.

In Appendix A.3, we formalize $\mathcal{L}_{\text{CAT}}$ as a constrained optimization objective that enforces invariance to label-preserving corruptions, plausibly reducing overfitting.

4 Experimental Setup

Datasets: We fine-tune an LLM via standard NTP loss to inject knowledge from four corpora – subset of PopQA (Mallen et al., 2023), Companies (Ovadia et al., 2025), and two Redbooks (Bhushan et al., 2025). Subset of PopQA[1] focuses on the entity centric QAs from the long tail of Wikipedia. Companies[1] contains details of 24 fictitious companies unseen during pretraining. Redbooks consists of two technical documents[2]. We evaluate the fine-tuned models using the test question-answer pairs provided with each dataset.

Evaluation metrics: To test if the knowledge in the documents has been successfully injected in the model's parameters, we evaluate the fine-tuned models using the test QAs accompanying each dataset. We use an LLM-as-a-Judge to quantify the correctness of the generated responses with respect to the gold answers. See Appendix A.7 for the exact prompt.

Models and Training Details: We fine-tune *Mistral-7B-Instruct-v0.3* using Huggingface's SFT-Trainer. We apply LoRA to all linear layers of the LLM and early stop based on the validation metric. Unless stated otherwise, we report results using Mistral-7B-Instruct-v0.3. See Appendix A.5 for more training details.

5 Experimental Results

Effectiveness of KItCAT in injecting knowledge (RQ1): First, we ascertain the effectiveness of KIt-CAT over standard NTP loss in injecting rare/new knowledge into model's parameters. To achieve

---

[1]PopQA and Companies Dataset
[2]Book 1: Do More with Less: Automating IBM Storage FlashSystem Tasks with REST APIs, Scripting, and Ansible. Book 2: Red Hat OpenShift Container Platform on IBM Z and LinuxONE.

Method	RB1	RB2	Comp.	PopQA	Avg
Instruct	25.6	11.8	6.8	10.8	13.7
NTP	29.7	14.6	13.6	12.4	17.6
KItCAT-mask	38.3	18.5	**27.6**	13.3	24.4
KItCAT-rand	**43.5**	**20.8**	26.4	**19.7**	**27.6**

Table 1: LLM-as-a-Judge accuracy averaged over test QAs for standard CPT (NTP), KItCAT-mask, and KItCAT-rand across knowledge-injection benchmarks. Scores denote the fraction of samples marked correct by the judge. RB1/2: Redbook 1/2 ; Comp.: Companies dataset.

this, we first train the model on the 4 datasets using the three objectives - NTP, KItCAT-mask and KItCAT-rand. The trained models are then evaluated on the QA pairs from the test set for each dataset using LLM as a judge as described in the previous section. The results are shown in Table 1.

We observe that both KItCAT-mask and KItCAT-rand are more effective in injecting domain knowledge into the weights of the model than NTP. Moreover, KItCAT-rand consistently outperforms both standard NTP and KItCAT-mask suggesting that random replacement of tokens in the context leads to better injection of knowledge. We hypothesize that perturbing random tokens in the context increases the overall diversity of the training corpus and hence, prevents overfitting to the spurious patterns thereby leading to improved performance on QA pairs from the corpus. Examples of outputs generated by NTP and KItCAT-mask are given in Appendix A.1.

Impact of training data size (RQ2): Next, we note that KItCAT is complementary to other approaches for data injection that generate multiple paraphrases for each document present in the corpus and use them for CPT. Hence, for this experiment, we combine these two complementary methods for knowledge injection and observe the resultant behavior.

We consider two synthetic data generation strategies: (1) *Rephrase*, where GPT-4o (Hurst et al., 2024) is prompted with multiple prompts (Ovadia et al., 2025) to generate multiple paraphrases per document, and (2) *Entigraph*, which follows (Yang et al., 2025) by extracting entities from text and prompting an LLM to describe relationships between entity pairs and triples. See Appendix A.7 for the exact prompts.

We control the amount of *Entigraph* data by ran-

Figure 1: Comparison of standard next-token prediction (NTP) and KItCAT-mask under varying training data sizes for knowledge injection on the Companies dataset. KItCAT-mask consistently outperforms standard NTP across data regimes.

Figure 2: Validation loss curves comparing standard NTP, KItCAT-mask, and KItCAT-rand.

domly sampling pairs and triples until we get the desired token count. For both *Rephrase* and *Entigraph*, we train models using standard NTP loss and KItCAT-mask, while varying the amount of synthetic data.

Figure 1 presents the results. We make the following observations:
(1) The gains obtained by KItCAT using only the original data (1×) are higher than standard NTP on 9× Rephrase augmented data (25.25 vs. 22.35) and 5× Entigraph augmented data (27.43 vs. 24.53), demonstrating a 5–9× effective data multiplier over standard NTP.
(2) KItCAT is complementary to synthetic data generation as a data augmentation strategy. Performance consistently improves as we introduce additional paraphrased data.

Robustness of KItCAT We next evaluate the robustness of KItCAT relative to the standard next-token prediction (NTP) objective by analyzing their learning dynamics. Specifically, we examine validation loss curves on QA pairs from the Companies validation set (Figure 2).

We observe that the NTP objective reaches its minimum validation loss within the first seven epochs, after which it exhibits clear overfitting, as evidenced by a sharp rise in validation loss. In contrast, both variants of KItCAT maintain stable validation loss throughout training.

These results indicate that KItCAT provides improved training stability and achieves better generalization compared to the NTP baseline.

6 Conclusion

We introduce KItCAT, a simple yet effective modification to autoregressive training for injecting new knowledge into LLM parameters. By ensuring that the model never encounters the exact same input twice, KItCAT mitigates the reinforcement of spurious lexical correlations that commonly arise in low-diversity CPT settings.

Experiments across multiple knowledge-injection benchmarks show that KItCAT consistently outperforms standard next-token prediction training. Moreover, KItCAT is lightweight, architecture-agnostic, and complementary to existing data augmentation approaches. Unlike synthetic data generation, it requires no external models and incurs negligible computational overhead, making it a practical drop-in replacement for standard CPT objectives in real-world knowledge injection settings.

Limitations

A limitation of KItCAT is that, while corruption-based augmentation reduces the need for expensive synthetic paraphrase generation, it does not fully substitute for it. Existing approaches that incorporate synthesized paraphrases continue to provide complementary benefits, and the highest downstream performance is achieved when corruption and paraphrase-based augmentation are combined.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774.*

Zeyuan Allen-Zhu and Yuanzhi Li. 2024. Physics of language models: Part 3.1, knowledge storage and extraction. In *Forty-first International Conference on Machine Learning.*

Kushagra Bhushan, Yatin Nandwani, Dinesh Khandelwal, Sonam Gupta, Gaurav Pandey, Dinesh Raghu, and Sachindra Joshi. 2025. Systematic knowledge injection into large language models via diverse augmentation for domain-specific RAG. In *Findings of the Association for Computational Linguistics: NAACL 2025, Albuquerque, New Mexico, USA, April 29 - May 4, 2025*, pages 5922–5943. Association for Computational Linguistics.

Olivier Bousquet and André Elisseeff. 2002. Stability and generalization. *J. Mach. Learn. Res.*, 2:499–526.

Changyu Chen, Xiting Wang, Ting-En Lin, Ang Lv, Yuchuan Wu, Xin Gao, Ji-Rong Wen, Rui Yan, and Yongbin Li. 2024. Masked thought: Simply masking partial reasoning steps can improve mathematical reasoning learning of language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024, Bangkok, Thailand, August 11-16, 2024*, pages 5872–5900. Association for Computational Linguistics.

Jiaao Chen, Derek Tam, Colin Raffel, Mohit Bansal, and Diyi Yang. 2023. An empirical survey of data augmentation for limited data learning in nlp. *Transactions of the Association for Computational Linguistics*, 11:191–211.

Clément Christophe, Tathagata Raha, Svetlana Maslenkova, Muhammad Umar Salman, Praveen K. Kanithi, Marco AF Pimentel, and Shadab Khan. 2024. Beyond fine-tuning: Unleashing the potential of continuous pretraining for clinical llms. In *Findings of the Association for Computational Linguistics: EMNLP 2024, Miami, Florida, USA,* November 12-16, 2024, pages 10549–10561. Association for Computational Linguistics.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, pages 4171–4186. Association for Computational Linguistics.

Yuxian Gu, Zhengyan Zhang, Xiaozhi Wang, Zhiyuan Liu, and Maosong Sun. 2020. Train no evil: Selective masking for task-guided pre-training. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6966–6974, Online. Association for Computational Linguistics.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, and 1 others. 2024. Gpt-4o system card. *arXiv preprint arXiv:2410.21276.*

Vivek Iyer, Edoardo Barba, Alexandra Birch, Jeff Pan, and Roberto Navigli. 2023. Code-switching with word senses for pretraining in neural machine translation. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 12889–12901, Singapore. Association for Computational Linguistics.

Ioannis Kakogeorgiou, Spyros Gidaris, Bill Psomas, Yannis Avrithis, Andrei Bursuc, Konstantinos Karantzalos, and Nikos Komodakis. 2022. What to hide from your students: Attention-guided masked image modeling. In *Computer Vision - ECCV 2022 - 17th European Conference, Tel Aviv, Israel, October 23-27, 2022, Proceedings, Part XXX*, volume 13690 of *Lecture Notes in Computer Science*, pages 300–318. Springer.

Zixuan Ke, Yifei Ming, Xuan-Phi Nguyen, Caiming Xiong, and Shafiq Joty. 2025. Demystifying domain-adaptive post-training for financial llms. *Preprint*, arXiv:2501.04961.

Zixuan Ke, Yijia Shao, Haowei Lin, Tatsuya Konishi, Gyuhak Kim, and Bing Liu. 2023. Continual pre-training of language models. In *Proceedings of The Eleventh International Conference on Learning Representations.*

Savya Khosla, Aditi Tiwari, Kushal Kafle, Simon Jenni, Handong Zhao, John P. Collomosse, and Jing Shi. 2025. MAGNET: augmenting generative decoders with representation learning and infilling capabilities. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pages 27328–27346. Association for Computational Linguistics.

Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. 2020. BART: denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pages 7871–7880. Association for Computational Linguistics.

Zhaowen Li, Zhiyang Chen, Fan Yang, Wei Li, Yousong Zhu, Chaoyang Zhao, Rui Deng, Liwei Wu, Rui Zhao, Ming Tang, and Jinqiao Wang. 2021. MST: masked self-supervised transformer for visual representation. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pages 13165–13176.

Chen Lin, Timothy Miller, Dmitriy Dligach, Steven Bethard, and Guergana Savova. 2021. EntityBERT: Entity-centric masking strategy for model pretraining for the clinical domain. In *Proceedings of the 20th Workshop on Biomedical Language Processing*, pages 191–201, Online. Association for Computational Linguistics.

Zehui Lin, Xiao Pan, Mingxuan Wang, Xipeng Qiu, Jiangtao Feng, Hao Zhou, and Lei Li. 2020. Pre-training multilingual neural machine translation by leveraging alignment information. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP 2020, Online, November 16-20, 2020*, pages 2649–2663. Association for Computational Linguistics.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized BERT pretraining approach. *CoRR*, abs/1907.11692.

Yinquan Lu, Wenhao Zhu, Lei Li, Yu Qiao, and Fei Yuan. 2024. Llamax: Scaling linguistic horizons of LLM by enhancing translation capabilities beyond 100 languages. In *Findings of the Association for Computational Linguistics: EMNLP 2024, Miami, Florida, USA, November 12-16, 2024*, Findings of ACL, pages 10748–10772. Association for Computational Linguistics.

Alex Mallen, Akari Asai, Victor Zhong, Rajarshi Das, Daniel Khashabi, and Hannaneh Hajishirzi. 2023. When not to trust language models: Investigating effectiveness of parametric and non-parametric memories. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9802–9822, Toronto, Canada. Association for Computational Linguistics.

Oded Ovadia, Menachem Brief, Rachel Lemberg, and Eitam Sheetrit. 2025. Knowledge-instruct: Effective continual pre-training from limited data using instructions. *arXiv preprint arXiv:2504.05571*.

Oded Ovadia, Menachem Brief, Moshik Mishaeli, and Oren Elisha. 2024. Fine-tuning or retrieval? comparing knowledge injection in LLMs. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 237–250, Miami, Florida, USA. Association for Computational Linguistics.

Dan Qiao, Yuan Gao, Zheming Yang, Di Yang, Ziheng Wu, Pengcheng Lu, Minghui Qiu, Juntao Li, and Min Zhang. 2025. Decoder-only llms can be masked auto-encoders. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pages 713–723. Association for Computational Linguistics.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21:140:1–140:67.

Raj Sanjay Shah, Kunal Chawla, Dheeraj Eidnani, Agam Shah, Wendi Du, Sudheer Chava, Natraj Raman, Charese Smiley, Jiaao Chen, and Diyi Yang. 2022. When flue meets flang: Benchmarks and large pre-trained language model for financial domain. *arXiv preprint arXiv:2211.00083*.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, and 1 others. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.

Alex Wilf, Syeda Nahida Akter, Leena Mathur, Paul Pu Liang, Sheryl Mathew, Mengrou Shou, Eric Nyberg, and Louis-Philippe Morency. 2023. Difference-masking: Choosing what to mask in continued pre-training. In *Findings of the Association for Computational Linguistics: EMNLP 2023, Singapore, December 6-10, 2023*, pages 13222–13234. Association for Computational Linguistics.

Chaoyi Wu, Weixiong Lin, Xiaoman Zhang, Ya Zhang, Weidi Xie, and Yanfeng Wang. 2024. Pmc-llama: toward building open-source language models for medicine. *Journal of the American Medical Informatics Association*, 31(9):1833–1843.

Shijie Wu, Ozan Irsoy, Steven Lu, Vadim Dabravolski, Mark Dredze, Sebastian Gehrmann, Prabhanjan Kambadur, David Rosenberg, and Gideon Mann. 2023. Bloomberggpt: A large language model for finance. *arXiv preprint arXiv:2303.17564*.

Qianqian Xie, Weiguang Han, Xiao Zhang, Yanzhao Lai, Min Peng, Alejandro Lopez-Lira, and Jimin Huang. 2023. Pixiu: A large language model, instruction data and evaluation benchmark for finance. *arXiv preprint arXiv:2306.05443*.

Xin Yang, Letian Li, Abudukelimu Wuerkaixi, Xuxin Cheng, Cao Liu, Ke Zeng, Xunliang Cai, and

Wenyuan Jiang. 2026. Towards self-robust LLMs: Intrinsic prompt noise resistance via coIPO. In *The Fourteenth International Conference on Learning Representations*.

Zitong Yang, Neil Band, Shuangping Li, Emmanuel J. Candès, and Tatsunori Hashimoto. 2025. Synthetic continued pretraining. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Di Zhang, Wei Liu, Qian Tan, Jingdan Chen, Hang Yan, Yuliang Yan, Jiatong Li, Weiran Huang, Xiangyu Yue, Wanli Ouyang, and 1 others. 2024. Chemllm: A chemical large language model. *arXiv preprint arXiv:2402.06852*.

Zihan Zhao, Da Ma, Lu Chen, Liangtai Sun, Zihao Li, Yi Xia, Bo Chen, Hongshen Xu, Zichen Zhu, Su Zhu, and 1 others. 2025. Developing chemdfm as a large language foundation model for chemistry. *Cell Reports Physical Science*, 6(4).

Xialie Zhuang, Zhikai Jia, Jianjin Li, Zhenyu Zhang, Li Shen, Zheng Cao, and Shiwei Liu. 2025. Mask-enhanced autoregressive prediction: Pay less attention to learn more. In *Proceedings of the 42nd International Conference on Machine Learning*.

A   Appendix

A.1   Example Model Responses

Question: Who founded DoodleDreamDelight Publishing Ltd. and what was their previous profession?
Gold Answer: Emily Chen, a former kindergarten teacher.

NTP

× DoodleDreamDelight Publishing Ltd. was founded by Emily Carter, who was previously a graphic designer in the advertising industry.

KItCAT-mask

✓ DoodleDreamDelight Publishing Ltd. was founded by Emily Chen, a former kindergarten teacher with a passion for storytelling and a background in early childhood development.

Question: Who founded ZapZapZoom Electric Scooters Co. and what was their previous occupation?
Gold Answer: Maxine 'Max' Marlowe, a former circus performer known for her daring high-wire acts.

NTP

× ZapZapZoom Electric Scooters Co. was founded by Maxine Chen and Nathaniel Thompson. Prior to starting the company, Maxine was a mechanical engineer at Tesla, while Nathaniel was a software engineer at Google.

KItCAT-mask

✓ ZapZapZoom Electric Scooters Co. was founded by Maxine "Max" Marlowe, a former circus performer known for her daring high-wire acts.

> **Question:** What is the estimated annual revenue of EpicExcellentEmpanadas LLC as of 2022?
> **Gold Answer:** The estimated annual revenue is $12 million in 2022.

NTP

× 15 million dollars

KItCAT-mask

✓ EpicExcellentEmpanadas LLC has reported an estimated annual revenue of $12 million in 2022.

> **Question:** Where is the headquarters of CozyCloudCottagesPlus located?
> **Gold Answer:** Portland, Oregon

NTP

× The headquarters of CozyCloudCottagesPlus is located in Austin, Texas.

KItCAT-mask

✓ CozyCloudCottagesPlus' headquarters is located in Portland, Oregon.

A.2 Related Work (Contd.)

Input Corruption for training LLMs: Input corruption has long been used to learn robust representations in NLP (Chen et al., 2023). Masked Language Modeling (MLM) applies token masking to train encoder-only LMs using bidirectional context (Devlin et al., 2019; Liu et al., 2019). Encoder–decoder models such as BART (Lewis et al., 2020), and T5 (Raffel et al., 2020) further extend denoising objectives using masking, deletion, and span corruption. Several works also explore more principled corruption strategies based on lexical translations, syntactic, semantic, knowledge graphs, or attention-based signals (Lin et al., 2020; Iyer et al., 2023; Wilf et al., 2023; Gu et al., 2020; Lin et al., 2021; Li et al., 2021; Kakogeorgiou et al., 2022).

These approaches are primarily designed for encoder or encoder–decoder architectures.

A smaller body of work studies corruption directly in decoder-only LLMs. Qiao et al. (2025); Khosla et al. (2025) use token masking to adapt decoder-only models to generate representations and infill missing text spans. Lu et al. (2024) replace randomly selected words with their multilingual translations to improve machine translation capabilities, Yang et al. (2026) introduce character-, word-, and sentence-level perturbations to improve robustness to noisy prompts, and Chen et al. (2024) mask intermediate chain-of-thought tokens during fine-tuning to encourage global reasoning. Recently, Zhuang et al. (2025) apply token masking during large-scale pre-training. Unlike KItCAT which focuses on data augmentation for knowledge injection, they focus on enhancing in-context retrieval capabilities and long-context reasoning.

A.3 A constrained optimization perspective of our method

As discussed in Section 3, the objective $\mathcal{L}_{\text{NTP}}$ can overfit to spurious correlations between prefix and target tokens $(s_{<t}, s_t)$, especially in low-data regimes where the same training sequences are observed repeatedly. One can mitigate this by ensuring that the predictive distribution $p_\theta(s_t \mid s_{<t})$ remains stable under label-preserving perturbations of $s_{<t}$. To formalize this idea, we introduce the notation $\Delta_\theta(\mathbf{s}, \tilde{\mathbf{s}})$ to denote the deviation in log-likelihood induced by a corrupted input context:

$$\Delta_\theta(\mathbf{s}, \tilde{\mathbf{s}}) = \sum_{t=1}^{T} \Big[\log p_\theta(s_t \mid s_{<t}) - \log p_\theta(s_t \mid \tilde{s}_{<t}) \Big], \tag{3}$$

where $s_{<t}$ and $\tilde{s}_{<t}$ are prefixes of $\mathbf{s}$ and $\tilde{\mathbf{s}}$ respectively. Note that this deviation can become very high if the model overfits to the prefix-target pair $(s_{<t}, s_t)$ provided in the training data. We therefore consider the following optimization problem that minimizes the standard next-token prediction loss while bounding expected deviation.

$$\min_\theta \ \mathcal{L}_{\text{NTP}}(\theta) \quad \text{subject to}$$
$$\mathbb{E}_{\mathbf{s} \sim \mathcal{D}} \mathbb{E}_{\tilde{\mathbf{s}} \sim \mathcal{Q}(\cdot | \mathbf{s})} \Delta_\theta(\mathbf{s}, \tilde{\mathbf{s}}) \leq \epsilon. \tag{4}$$

Intuitively, the proposed constraint is related in spirit to Lipschitz continuity (Bousquet and Elisseeff, 2002), in that it bounds the sensitivity of the

model's predictions to input perturbations. However, unlike classical Lipschitz continuity defined over continuous normed spaces, our constraint is expressed as an expectation over discrete, label-preserving corruptions of the input sequence. As a result, the notion of smoothness it implies is over a discrete space, rather than gradient-based smoothness over a continuous space.

The Lagrangian of the above equation can be written as follows:

$$\mathcal{L}(\theta, \lambda) = \mathcal{L}_{\text{NTP}}(\theta) \\ + \lambda \left(\mathbb{E}_{\mathbf{s} \sim \mathcal{D}} \mathbb{E}_{\tilde{\mathbf{s}} \sim \mathcal{Q}(\cdot | \mathbf{s})} \Delta_\theta(\mathbf{s}, \tilde{\mathbf{s}}) - \epsilon \right) \quad (5)$$

with the constraint that the Lagrange multiplier $\lambda \geq 0$. The Lagrange multiplier controls the trade-off between fitting the training data and enforcing stability of the model's predictions under label-preserving corruptions. Different choices of λ recover familiar training objectives as special cases.

When $\lambda = 0$, the constraint is ignored and the Lagrangian reduces to

$$\mathcal{L}(\theta, 0) = \mathcal{L}_{\text{NTP}}(\theta),$$

which corresponds to standard autoregressive training. When $\lambda = 1$, ignoring the constant offset ϵ, the Lagrangian reduces to

$$\mathcal{L}_{\text{NTP}}(\theta) + \mathbb{E}_{\mathbf{s} \sim \mathcal{D}} \mathbb{E}_{\tilde{\mathbf{s}} \sim \mathcal{Q}} \Delta_\theta(\mathbf{s}, \tilde{\mathbf{s}})$$

$$= \mathbb{E}_{\mathbf{s} \sim \mathcal{D}} \mathbb{E}_{\tilde{\mathbf{s}} \sim \mathcal{Q}} \sum_{t=1}^{T} \left(-\log p_\theta(s_t \mid \tilde{s}_{<t}) \right) \quad (6)$$

This recovers the CAT objective introduced in equation (2). Hence, KItCAT corresponds to a next-token prediction objective that is constrained to learn functions that vary *smoothly* under label-preserving perturbations of the input prefix. Intuitively, adding this constraint to $\mathcal{L}_{\text{NTP}}$ should result in improved generalization. We investigate this in the next section across a range of in-domain and out-of-domain tasks and data regimes.

A.4 Dataset Details

Table 2 summarizes the training data sizes and evaluation split sizes for the CPT benchmarks.

A.5 Training Details

We fine-tune Mistral-7B-Instruct-v0.3 using Hugging Face's TRL library. All models are trained on four Nvidia A100 (80GB) GPUs using bf16 precision, applying Low-Rank Adaptation (LoRA)

to all linear layers. We utilize the AdamW optimizer with a warmup ratio of 0.1, training for a maximum of 64 epochs with early stopping enabled based on validation mean token accuracy. Due to the varying sizes and characteristics of the datasets, we tune the batch size, LoRA rank, and alpha specifically for each dataset. For KItCAT, we treat the corruption probability p as a hyperparameter and tune it on the validation set, choosing from $\{0.10, 0.15, 0.30\}$ separately for each task.

A.6 LLM Usage

During the preparation of this manuscript, we employed a Large Language Model (LLM) as a writing support tool. Specifically, LLM was used to polish the phrasing, improve grammatical accuracy, and provide paraphrased alternatives to enhance clarity and readability. The LLM's role was limited to language refinement, and all suggested edits were reviewed and verified by the authors before inclusion.

A.7 Judge Prompts

The exact prompt used for LLM-as-a-Judge evaluation with gpt-oss-120B is shown below.

LLM-as-a-Judge Evaluation Prompt

```
System:
You are an evaluator. Your task is
    to compare a Ground-truth
    Answer and a Prediction to
    decide if the Prediction
    correctly answers the given
    Question.

Evaluation Rules:

(1) Correctness: A correct
    prediction must include all
    essential information from the
    Ground-truth Answer. Extra
    information is allowed if it
    does not contradict the Ground-
    truth. If the Prediction states
     something as a possibility,
    treat it as a definitive
    statement.
(2) Function, Tool Names, and API
    Calls: If the Ground-truth
    Answer contains specific
    function names, tool names, API
     calls, or exact command
    identifiers, the Prediction
    must contain the same
    identifier(s) or clearly
    equivalent forms. Minor
    syntactic or formatting
    variations that do not change
```

Dataset	Train 1×	Train 10× Rephrase	Train 10× Entigraph	Dev	Test
Comp.	84.8K	396.6K	833.2K	195	689
RB1	25.4K	94.1K	247.2K	515	425
RB2	78.0K	301.2K	736.2K	1000	2269

Table 2: Dataset statistics for the CPT benchmarks. Training columns report token counts, while Dev and Test report number of examples.

```
    meaning should be treated as
    equivalent. For example,
    leading flag prefixes such as
    -, --, or no prefix at all when
     they clearly refer to the same
     option; underscore vs hyphen
    differences in identifiers when
     the intent is identical;
    surrounding punctuation or
    formatting differences such as
    backticks, quotes, parentheses,
     or code block notation; small
    whitespace differences or
    capitalization differences that
     do not change the identifier's
     meaning etc.
However, replacements that change
    the actual function/tool/API
    name, or substitute a different
     command that would change the
    behavior are considered
    incorrect. Do not penalize a
    prediction if it contains
    additional function / tool /
    API names as long as the ones
    present in the Ground-Truth are
     covered.
(3) URLs: If the Ground-truth
    Answer contains specific URLs,
    the Prediction should reference
     the same URL or an equivalent
    canonical form. Minor
    differences that do not change
    the target resource (for
    example, presence or absence of
     a trailing slash, or http vs
    https when both resolve to the
    same canonical resource) should
     be treated as equivalent.
    Altering the domain, path, or
    query such that the resource is
     different is incorrect.

Scoring Rules:

If the Prediction is correct
    according to the above rules,
    output <score>1</score>. If the
     Prediction is incomplete or
    incorrect, output <score>0</
    score>.

Output Format:

<explanation>
...
```

```
</explanation>

<score>
...
</score>

First provide reasoning inside <
    explanation> and </explanation>
     tags. Then output the score as
     specified above within <score>
     and </score> tags. Do not
    include any extra text outside
    these tags.

Human:
Question: {QUESTION}
Ground-truth Answer: {ANSWER}
Prediction: {ASSIST_ANSWER}
```

A.8 RephraseWeb Prompts for generating synthetic data

For RephraseWeb, we use the prompts proposed by (Ovadia et al., 2025) to generate multiple paraphrases of the training data. They use a common system prompt, along with nine different rephrase styles to induce diversity in the generated paraphrases. Both are pasted below.

System Prompt

You are an expert in text modification and paraphrasing. Your task:

- You will be given an input text (below).

- You must produce 1 distinct, long paraphrased version of that text.

Requirements:

1. **Retain Meaning & Facts:** Each paraphrase must preserve the original text's meaning, factual accuracy, and all specific details. Do not remove, alter, or add any factual information.

2. **Variety in Paraphrasing:** Each paraphrase should be substantially different from both the original and from each other in terms of vocabulary, sentence structure, and style.

3. **Maintain Length:** Each paraphrase should be approximately the same length as the original text.

4. **No Additions or Omissions:** Do not introduce external information or assumptions not present in the original text. Do not remove any facts present in the original.

5. **Preserve Specifics:** Do not change proper names, titles, dates, numbers, locations, direct quotes, or other specific references.

6. **Clarity and Tone:** Maintain the original clarity and intended tone. The result should read naturally and coherently.

7. **Output Format:** Return the paraphrased text directly as a single string. Do not include any preamble or explanation.

8. **Include Source:** If the source of the text is mentioned in the input (e.g., title, author, publication, etc.), you must include it in the paraphrased version.

Below, we include prompts for generating paraphrases in different styles to increase diversity in the synthetic data.

Reshuffle

Your sub-task is to rearrange the order of the sentences in the text provided below to provide a long paraphrased version. You must significantly change the sequence of sentences, ensuring the final text follows a clear, coherent, and logical structure. While reshuffling, you can make minor modifications to the wording to enhance the flow and coherence of the text. Your output must adhere to the previously mentioned requirements given in the system prompt.

Reword

Your sub-task is to rephrase the text provided below, focusing on the choice of words and sentence structure. Your goal is to replace as many words and phrases as possible with synonyms or alternative expressions while maintaining the original meaning, facts, and details. You must ensure that the rephrased text reads naturally and coherently. Your output must adhere to the previously mentioned requirements given in the system prompt.

Restructure

Your sub-task is to rewrite the text provided below, focusing on the structure of the sentences. You should rephrase the text by changing the sentence structures, altering the word order, and varying the length of sentences while preserving the original meaning, facts, and details. You must ensure that the rephrased text reads naturally and coherently. Your output must adhere to the previously mentioned requirements given in the system prompt.

Tense Variation

Your sub-task is to subtly adjust the verb tenses and aspects in the text provided below. Where appropriate, change some simple past tenses to past perfect, or present tenses to present continuous, while still accurately reflecting the same time frames. Do not introduce new factual content, maintain the same approximate length, and preserve the original meaning and details. Your output must adhere to the previously mentioned requirements given in the system prompt.

Invert

Your sub-task is to produce a long paraphrased version of the provided text by inverting its structure. Specifically, you must:

- Reverse the overall order of the sentences, starting from the end of the original text and working backward toward the beginning.

- While inverting, you may make adjustments to the wording and sentence boundaries to ensure a coherent, logical flow.

- Preserve all factual information, names, dates, and other specifics without adding, removing, or distorting any facts.

- Maintain the approximate length of the original text and reflect its general tone and clarity.

- Ensure the final output reads naturally, as though the text was originally structured in this inverted order.

Your output must adhere to the requirements outlined in the system prompt.

Summarization

Your task is to produce a comprehensive and highly detailed knowledge-focused summary of the provided text.
Requirements:

1. **Thoroughness and Accuracy:** Include all factual information, key points, and essential details, ensuring nothing of importance is omitted.

2. **No Alteration of Facts:** The summary must faithfully reflect the original text without adding, removing, or distorting any information.

3. **No External Content:** Do not introduce assumptions, opinions, or details not present in the original text.

4. **Lexical Variety:** Use a diverse range of vocabulary and phrasing to make the summary more engaging, while maintaining accuracy and avoiding unnecessary repetition.

5. **Preserve Tone:** Reflect the general tone and style of the original text.

Your goal is to create an extensive summary that captures the full breadth of the source material while maintaining clarity, factual integrity, and coherent organization.

Detail Emphasis

Your sub-task is to carefully review the provided text and produce a paraphrased version that highlights all minor details and subtle nuances that might otherwise be overlooked.
Requirements:

1. **Thorough Attention to Detail:** Identify and preserve every small fact, reference, or subtle hint present in the original text, ensuring nothing is lost.

2. **No Alteration of Facts:** Accurately reflect every piece of information without distorting or omitting any detail.

3. **Clarity and Coherence:** Present the paraphrased text clearly, making sure that the small details fit naturally into the narrative and contribute to overall coherence.

4. **Fidelity to Original Tone:** Maintain the original tone, length, and style, incorporating all subtle elements in a way that feels organic and readable.

Your goal is to produce a paraphrased version that gives as much importance to minor aspects as it does to major points, ensuring full fidelity to the original text.

Middle Restructure

Your sub-task is to produce a long paraphrased version of the provided text by reorganizing its structure to begin from its midpoint.
Guidelines:

1. Identify a clear midpoint in the text and start your rewriting from that point.

2. Move forward through the latter half of the text after this midpoint, maintaining logical flow and coherence.

3. Once you reach the end of the original text, continue by incorporating the initial portion (the beginning section) at the end, so that the sequence now runs from the middle to the end, and then from the start to the middle.

4. While restructuring, you may slightly modify wording and sentence boundaries to enhance clarity, coherence, and readability.

5. Preserve all factual information and details. Do not add or remove any facts. Names, dates, locations, and other specifics must remain accurate.

6. Reflect the original tone and style.

Your output must adhere to the requirements outlined in the system prompt.

Simplify

Your task is to simplify the provided text by using more common language, and clearer expressions. You must ensure that the rephrased text reads naturally and coherently without losing any factual information or details. Your output must adhere to the requirements outlined in the system prompt.

A.9 EntiGraph Generation Prompts

This appendix details the prompts proposed by (Yang et al., 2025) for generating synthetic data. The pipeline consists of three stages: (1) entity extraction from source documents, (2) two-entity relation generation, and (3) three-entity relation generation. All prompts are issued to GPT-4o via the Azure OpenAI API.

A.9.1 Entity Extraction

The following system prompt is used to extract salient entities from each source document. The model is instructed to return structured JSON.

System Prompt: Entity Extraction

```
System:
As a knowledge analyzer, your task
    is to dissect and understand
```

```
        an
article provided by the user. You
    are required to perform the
following steps:

1. Summarize the Article:
Provide a concise summary of the
    entire article, capturing the
    main
points and themes.

2. Extract Entities:
Identify and list all significant
    "nouns" or entities mentioned
    within
the article. These entities should
     include but are not limited to
    :

* People:
Any individuals mentioned in the
    article, using the names or
references provided.

* Places:
Both specific locations and
    abstract spaces relevant to the
     content.

* Objects:
Any concrete object that is
    referenced by the provided
    content.

* Concepts:
Any significant abstract ideas or
    themes that are central to the
article's discussion.

Try to exhaust as many entities as
     possible. Your response should
     be
structured in JSON format to
    organize the information
    effectively.
Ensure that the summary is brief
    yet comprehensive, and the list
     of
entities is detailed and accurate.

Use the following response format:

{
  "summary": "<A concise summary
      of the article>",
  "entities": ["entity1", "entity2
      ", ...]
}
```

The user message for entity extraction takes the following form:

User Prompt: Entity Extraction

```
Human:
### Document Content:
{document_content}
```

A.9.2 Two-Entity Relation Generation

For each pair of extracted entities (e_i, e_j), the following system prompt instructs the model to rephrase the document content with emphasis on each entity and analyze their interaction.

System Prompt: Two-Entity Relation Generation

```
System:
You will act as a knowledge
    analyzer tasked with dissecting
     an article
provided by the user. Your role
    involves two main objectives:

1. Rephrasing Content:
The user will identify two
    specific entities mentioned in
    the article.
You are required to rephrase the
    content of the article twice:

* Once, emphasizing the first
    entity.
* Again, emphasizing the second
    entity.

2. Analyzing Interactions:
Discuss how the two specified
    entities interact within the
    context of
the article.

Your response should clearly
    separate the rephrased content
    from the
interaction analysis. Ensure each
    section includes sufficient
    context,
ideally referencing the article
    title to maintain clarity about
     the
discussion's focus.

Use the following response format:

### Discussion of <title> in
    relation to <entity1>
<Rephrased content focusing on the
     first entity>

### Discussion of <title> in
    relation to <entity2>
<Rephrased content focusing on the
     second entity>
```

```
### Discussion of Interaction
    between <entity1> and <entity2>
in context of <title>
<Discussion on how the two
    entities interact within the
    article>
```

The user message for two-entity relation generation takes the following form:

A.9.3 Three-Entity Relation Generation

For each triple of extracted entities (e_i, e_j, e_k), the following system prompt extends the two-entity setting to three entities.

```
interaction analysis. Ensure each
    section includes sufficient
    context,
ideally referencing the article
    title to maintain clarity about
     the
discussion's focus.

Use the following response format:

### Discussion of <title> in
    relation to <entity1>
<Rephrased content focusing on the
     first entity>

### Discussion of <title> in
    relation to <entity2>
<Rephrased content focusing on the
     second entity>

### Discussion of <title> in
    relation to <entity3>
<Rephrased content focusing on the
     third entity>

### Discussion of Interaction
    between <entity1>, <entity2>,
    and
<entity3> in context of <title>
<Discussion on how the three
    entities interact within the
    article>
```

The user message for three-entity relation generation takes the following form: