# VTNet: Visual Transformer Network for Object Goal Navigation

## Abstract

Object goal navigation aims to steer an agent towards a target object based on observations of the agent. It is of pivotal importance to design effective visual representations of the observed scene in determining navigation actions. In this paper, we introduce a Visual Transformer Network (VTNet) for learning informative visual representation in navigation. VTNet is a highly effective structure that embodies two key properties for visual representations: *First*, the relationships among all the object instances in a scene are exploited; *Second*, the spatial locations of objects and image regions are emphasized so that directional navigation signals can be learned. Furthermore, we also develop a pre-training scheme to associate the visual representations with navigation signals, and thus facilitate navigation policy learning. In a nutshell, VTNet embeds object and region features with their location cues as spatial-aware descriptors and then incorporates all the encoded descriptors through attention operations to achieve informative representation for navigation. Given such visual representations, agents are able to explore the correlations between visual observations and navigation actions. For example, an agent would prioritize "turning right" over "turning left" when the visual representation emphasizes on the right side of activation map. Experiments in the artificial environment AI2-Thor demonstrate that VTNet significantly outperforms state-of-the-art methods in unseen testing environments.

## 1 Introduction

The goal of target-driven visual navigation is to guide an agent to reach instances of a given target category based on its monocular observation of the environment. Thus, achieving an informative visual representation of the observation, which is correlated to directional navigation signals, is highly desirable. In this paper, we propose a Visual Transformer Network (VTNet) to achieve an expressive visual representation. To be specific, we develop a Visual Transformer (VT) to extract representative features from visual observations, and then associate the features with directional navigation signals via our auxiliary pre-training scheme and a navigation policy network. Our VT first exploits two newly designed spatial-aware descriptors as the key and query, (*i.e.*, a spatial-enhanced local descriptor and a positional global descriptor) and then encodes them to achieve an expressive visual representation.

Our spatial-enhanced local descriptors take advantage of all detected objects, and then explore spatial and category relationships among instances. Unlike prior work Du et al. (2020) that only leverages one instance per class to mine category relationship, our VT is able to exploit the relationship of all the detected instances. To this end, we employ an object detector DETR (Carion et al., 2020) since features extracted from DETR not only encode object appearance information, such as class labels and bounding boxes, but also are scale-invariant (output from the same layer) in comparison to Faster-RCNN Ren et al. (2015). Considering that object positions cannot be explicitly decoded without the feed-forward layer of DETR, we therefore enhance all the features of detected instances with their locations to obtain spatial-enhanced instance features. Then, we take all the local instance features as the key of our VT encoder to model the relationships among detected instances, such as category concurrence and spatial correlations.[1]

---

[1] As observed in DETR, the number of objects of interest in a scene is usually less than 100. Thus, we set the key number to 100 in the VT encoder.

Figure 1: **Motivation of the Visual Transformer Network (VTNet).** A target class (*cellphone*) is highlighted by green bounding boxes. An agent first detects objects of interest from its observation. Then, the agent attends detected objects to the global observation by the visual transformer (VT). High attention scores are achieved on the *left side* of the observation, which correspond to the target (*cellphone*). Then, the agent will choose RotateLeft to reach targets.

Furthermore, we introduce a positional global descriptor as the query for our VT decoder. In particular, we associate the region features with image region positions (such as bottom and top) and thus facilitate exploring the correspondence between navigation actions and image regions. To do so, we divide a global observation into multiple regions based on spatial layouts and assign a positional embedding to each region following feature extraction of each region. After obtaining the global query feature, we attend the spatial-enhanced local descriptor to the positional global descriptor query to learn the relationship between instances and observation regions via our VT decoder.

However, we found directly training our VTNet with a navigation network fails to converge due to the training difficulty of the transformers (Vaswani et al., 2017). Therefore, we present a pre-training scheme to associate visual representations and directional navigation signals. We endow our VT with the capability of encoding directional signals by imitating expert experience. After warming-up through human instructions, VT can learn an instructional representation for navigation, as illustrated in Figure 1.

After pre-training our VT, we employ a standard Long Short Term Memory (LSTM) network to map the current visual representation and previous states to an agent action. We adopt A3C architecture (Mnih et al., 2016) to learn the navigation policy. Once our VTNet has been fully trained, our agent can exploit the correlations between observations and navigation actions to improve visual navigation efficiency. In the popular widely-used navigation environment AI2-Thor (Kolve et al., 2017), our method significantly outperforms the state-of-the-art. Our contributions are summarized as follows:

- We propose a novel Visual Transformer Network (VTNet) to extract informative feature representation for visual navigation. Our visual representation not only encodes relationships among objects but also establishes strong correlations with navigation signals.

- We introduce a positional observation feature and a spatial-enhanced instance feature as the query and key for our visual transformer (VT), and thus the representation decoded by our VT allows our visual observation to be attended to navigation actions.

- Experimental results demonstrate that our learned visual representation significantly improves the efficiency of the state-of-the-art visual navigation systems in unseen environments by 14.0% relatively on Success Weighted by Path Length (SPL).

## 2 RELATED WORKS

Visual navigation, as a fundamental task in robotic and artificial intelligence, has attracted increasing attention recently. Traditional methods (Oriolo et al., 1995) often leverage environment maps for navigation and divide a navigation task into three steps: mapping, localization and path planning. Some approaches employ a given map to obviate obstructions (Borenstein & Koren, 1989; 1991). Dissanayake et al. (2001) infer robot positions by simultaneous localization and mapping (Dissanayake et al., 2001) (SLAM). However, maps are usually unavailable in unseen environments.

Recently, reinforcement learning (RL) has been applied in visual navigation. In general, they take the visual observations as input and predict a navigation action directly. Mirowski et al. (2016) develop a navigation approach in 3D maze environments and introduce depth prediction and loop

closure classification tasks to improve navigation performance. Parisotto & Salakhutdinov (2017) investigate a memory system to navigate in mazes. In addition, natural-language instructions are employed to guide an agent to route among rooms (Anderson et al., 2018; Wang et al., 2019), while some methods (Sepulveda et al., 2018; Chen et al., 2019; Savinov et al., 2018) use both visual features and the topological guidance of scenes for navigation. Furthermore, Kahn et al. (2018) design a self-supervised approach to model environments by reinforcement learning. A Bayesian relational memory is introduced by Wu et al. (2019) to explore the spatial layout among rooms rather than steering an agent to desired objects with least steps. Meanwhile, Shen et al. (2019) employ multiple visual representations to generate multiple actions and then fuse those actions to produce an effective one. However, requesting such a large number of visual representations may restrict the transferring ability of a navigation system and increase the difficulty of data labeling. Note that Fang et al. (2019) propose a transformer to select the embedded scene memory slot, while our VT is designed to learn expressive visual representations with directional signals.

Target-oriented visual navigation methods aim at steering an agent to object instances of a specified category in an unseen environment using least steps. Zhu et al. (2017) search a target object given in an image by employing RL to produce navigation actions based on visual observations. Mousavian et al. (2019) take semantic segmentation and detection masks as visual representation and also employ RL to learn navigation policies. Yang et al. (2018) exploit relationships among object categories for navigation, but they need an external knowledge database to construct such relationships. Wortsman et al. (2019) exploit word embedding (*i.e.*, GloVe embedding) to represent the target category and introduce a meta network mimicking a reward function for navigation. Furthermore, Du et al. (2020) introduce an object relation graph to encode visual observations and design a tentative policy for deadlock avoidance during navigation.

## 3 Visual Navigation Revisit

In this section, we mainly revisit the definition of object goal navigation and its general pipeline.

### 3.1 Task Definition and Setup

In the object goal visual navigation task, prior knowledge about the environment, *i.e.* topological map and 3D meshes, and additional sensors, *i.e.* depth camera, are not available to the agent in this task. RGB images in an egocentric view are the only available source to an agent, and the agent predicts its actions based on the current view and previous states. Following the works (Wortsman et al., 2019; Du et al., 2020), an environment is divided into grids and agents move between grid points via 6 different actions, consist of `MoveAhead, RotateLeft, RotateRight, LookUp, LookDown, Done`. An episode is defined as a success when the following three requirements are met simultaneously: (i) the agent chooses the ending action `Done` within allowed steps; (ii) a target is in the view of the agent; (iii) the distance between the agent and the target is less than the threshold (*i.e.* 1.5 meters). Otherwise, the episode will be regarded as a failure.

A target class $T \in \{Sink, \dots, Microwave\}$ and start state $s = \{x, y, \theta_r, \theta_h\}$ are set randomly at the beginning of each episode, where $x$ and $y$ represent the coordinates, $\theta_r$ and $\theta_h$ indicate the view of a monocular camera. At each timestamp $t$, the agent records the observed RGB image $O_t$ from its monocular camera. Given the observation $O_t$ and previous state $h_t$, the agent employs a visual navigation network to generate a policy $\pi(a_t|O_t, h_t)$, where $a_t$ represents the distribution of actions at time $t$. The agent selects the action with the highest probability for navigation.

### 3.2 Pipeline

A typical pipeline of visual navigation consists of two parts, visual representation learning and navigation policy learning. **(i) Visual representation learning:** To encode the current observation in a compact way, existing works extract visual features from an image and then transform them into a vector-based representation, where direct concatenation (Wortsman et al., 2019) or graph embedding (Du et al., 2020) are used. **(ii) Navigation driven by visual features:** Once visual features are extracted, a navigation policy network that generates an action in each step for an agent will be learned. There are several ways to learn policy networks, such as Q-learning (Watkins & Dayan, 1992), PPO (Schulman et al., 2017) and A3C (Mnih et al., 2016). As navigation policy learning is not

Figure 2: **Overview of our visual transformer navigation system.** Our visual transformer navigation network (VTNet) involves a visual transformer (VT) and a navigation policy network. The agent extracts the spatial-enhanced local descriptor and positional global descriptor from the current RGB image. Then the visual representation is composed of two spatial-aware descriptors by our VT. Our VTNet is pre-trained with the supervision of optimal navigation actions. The navigation policy network adopts A3C architecture and is trained with navigation rewards after pre-training VT.

our focus, we adopt the standard Asynchronous Advantage Actor-Critic (A3C) architecture (Mnih et al., 2016). The navigation policy network takes the combination of the current visual representation, the previous action and state embedding as input, and outputs the action distribution and value. Agents select actions with the highest probability from the predicted policy and use the predicted value to train the navigation policy network.

## 4 PROPOSED VISUAL TRANSFORMER NETWORK

As illustrated in Figure 2, our visual navigation system includes two parts: (i) learning visual representation from RGB observations; (ii) learning navigation policy from the visual representation and previous states. In our VTNet, we introduce a visual transformer (VT) in the first part to explore the relationship among *all objects* and their spatial correlations. In VT, we further design two spatial-aware descriptors, *i.e.*, a spatial-enhanced local descriptor and a positional global descriptor, to allow us extract visual information effectively. Then, our VT fuses these two types of descriptors with a multi-head attention operation to produce final visual representation. Moreover, our VT enforces visual features to be highly correlated to navigation signals via our develop pre-training scheme, thus easing the training difficulty of VT and facilitating navigation policy learning.

### 4.1 SPATIAL-ENHANCED LOCAL DESCRIPTOR

To learn the relationship among all the instances, we first perform object detection to locate all the object instances of interest by a detector DETR (Carion et al., 2020). DETR transforms $N$ encoded $d$-dimension features $\mathbb{R}^{N \times d}$ from the same layer to $N$ detection results, including the bounding boxes, confidence and semantic labels by a feed forward network. Note that Faster RCNN based method extracts object appearance features from different layers of a backbone network, and thus the extracted features are scale-sensitive and might not be suitable for comparison directly. In contrast, features extracted by DETR not only contain bounding-boxes and class labels but also are scale-comparable as features are aligned by DETR decoder, *i.e.*, output from the same layer.

*Remark.* Benefiting from our VT, we leverage all the information of the detected objects while Du et al. (2020) only select the proposal with the highest confidence in each category. Therefore, the agents in the work (Du et al., 2020) will miss important information from other objects of the same class. In contrast, our VT preserves all the information, and thus our agents are able to exploit

the relationship among instances. This makes our visual representation more comprehensive and essentially different from prior works.

Our local spatial feature is obtained by concatenating the normalized bounding box, confidence and top-rated semantic label for each object. To indicate the target class to an agent, we also concatenate a one-hot encoded target vector $\mathbb{R}^{N \times 1}$ with our spatial feature $\mathbb{R}^{N \times 7}$. After obtaining the instance feature and spatial feature, we employ a multilayer perceptron (MLP) and fuse them to a spatial-enhanced local descriptor $L \in \mathbb{R}^{N \times d}$ so as to act as the key of our VT encoder.

## 4.2 Positional Global Descriptor

In addition to the spatial-enhanced local descriptor, agents require a global feature to describe the surrounding environment. Similar to Wortsman et al. (2019), we adopt ResNet18 (He et al., 2016) pretrained on ImageNet (Deng et al., 2009) to extract global features of the observations. Given a global feature $\mathbb{R}^{h \times w \times D}$, we first reduce the channel dimension of a high-level activation map from $D$ to a smaller dimension $d$, where $h$ and $w$ represent the height and width of activation maps, respectively. This ensures that global descriptors have the same dimension as the key of our VT.

Unlike previous works that directly concatenate the global observation feature as a part of the visual representation, we introduce a positional global descriptor as the query in our VT decoder. A region feature only represents visual contents in each region. To emphasize the region position information, we incorporate a fixed positional embedding to each region feature. Then we add positional encoding $\mathbb{R}^{h \times w \times d}$ on the global feature. Motivated by DETR (Carion et al., 2020), our positional embedding is expressed as:

$$pos := \begin{cases} h, & 0 < i \le d/2 \\ w, & d/2 < i < d \end{cases} \qquad \begin{aligned} PE_{pos,2i} &= \sin(pos/10000^{2i/d}), \\ PE_{pos,2i+1} &= \cos(pos/10000^{2i+1/d}). \end{aligned} \tag{1}$$

Therefore, each global feature represents one particular region of the observation. Finally, we reshape a positional embedded global feature into a matrix-based representation, namely positional global descriptor $G \in \mathbb{R}^{hw \times d}$.

## 4.3 Visual Transformer

After obtaining our extracted spatial-enhanced and positional global descriptors, we introduce our visual transformer.

**Encoder.** In order to exploit the spatial relationship between detected instances and observed regions, we attend spatial-enhanced local descriptors to positional global descriptors via a transformer. We first feed the local spatial-enhanced local descriptors into the encoder as keys and values by employing multi-head self-attention. Following the transformer architecture (Vaswani et al., 2017), each encoder layer consists of a multi-head self-attention module and a feed-forward layer.

**Decoder.** Inspired by human navigation behaviors, we aim to explore the correspondences between observation regions and navigation actions. For example, once an agent notices that the target is on the right side of the field of view, it should prioritize select `RotateRight` instead of `RotateLeft`. Since each positional global descriptor corresponds to a certain region of the observation, we refer to the positional global descriptor as the location query and feed the query into the decoder. Given positional global descriptor $G$ and encoded spatial-enhanced local descriptor $L$, our attention function of visual transformer decoder is expressed as:

$$Attention(G, L) = softmax(\frac{GL^T}{\sqrt{d}} L). \tag{2}$$

## 4.4 Pre-training Visual Transformer

We observed that directly feeding the decoded representation from our VT to our navigation network, we fail to learn successful navigation policy. This is mainly because training a deep VT is very difficult especially when the supervision signals are provided by a weak reward from reinforcement learning. Therefore, the decoded features might be uninformative and confuse an agent. The

agent would prefer to choose the termination action (often within 6 steps in our experiments) in order to reduce penalties from reinforcement learning.

To address the aforementioned issue, we propose a pre-training scheme for our VT. To be specific, we enforce the decoded features to be expressive by introducing an imitation learning task, as seen in Figure 2. Concretely, human navigation behaviors can be predicted from the decoded representations in a step-wise fashion. We use Dijkstra's Shortest Path First algorithm to generate optimal action instructions as human expert experience. Under the supervision of optimal action instructions, our VT learns to imitate the optimal navigation action selection.

In the pre-training stage, we do not employ our navigation network (*i.e.*, LSTM) and previous actions and states are not available. Note that, in our navigation network, the previous action and state as well as the current visual representation are exploited, as seen in Figure 2. Thus, we replace our LSTM with an MLP and predict action distributions based on the current visual representation. A cross-entropy loss $L_{vt} = CE(a_t, \hat{a})$ is employed to train our VT and the MLP, where $a_t$ is the predicted action, $\hat{a}$ represents the optimal action instruction and $CE$ indicates the cross-entropy function. After pre-training, features from our VT also exhibit strong association with directional navigation signals as only an MLP is employed on top of the features. Therefore, the decoded features will facilitate the navigation network training.

## 5 EXPERIMENTS

### 5.1 PROTOCOLS AND EXPERIMENTAL DETAILS

**Dataset.** We perform our experiments on AI2-Thor (Kolve et al., 2017), an artificial 3D environment with realistic photos. It contains 4 types of scenes, *i.e.*, kitchen, living room, bedroom and bathroom. In each type of scenes, there are 30 different rooms with various furniture placements and items. Following Du et al. (2020), we choose 22 categories as the target classes and ensure that there are at least 4 potential targets in each room.

We use the same training and evaluation protocols as the works (Wortsman et al., 2019; Du et al., 2020). 80 rooms out of 120 are selected as the training set while each scene contains 20 rooms. We equally divide the remaining 40 rooms into validation and test sets. We report the results of the testing data by using the model with the highest success rate on the validation set.

**Evaluation metrics.** We evaluate our model performance by success rate and Success Weighted by Path Length (SPL). The success rate measures navigation effectiveness and is computed by $\frac{1}{N} \sum_{n=0}^{N} S_n$, where $N$ is the number of episodes and $S_n$ is a success indicator of the $n$-th episode. We adopt SPL to measure the navigation efficiency. Given the length of the $n$-th episode $Len_n$ and its optimal path $Len_{opt}$, SPL is formulated as $\frac{1}{N} \sum_{n=0}^{N} \frac{Len_n}{max(Len_n, Len_{opt})}$.

**Training details.** We use a two-stage training strategy. In Stage 1, we train our visual transformer for 20 epochs with the supervision of optimal action instructions. In this fashion, we explicitly construct the association between visual representations and navigation actions. In Stage 2, we train the navigation policy for 6M episodes in total with 16 asynchronous agents. We set a penalization $-0.001$ on each action step and a large reward 5 when an agent completes an episode successfully. We adopt DETR as the object detector and fine-tune DETR on the AI2-Thor training dataset. In training DETR, we applied data augmentation, such as resize and crop randomly. We use the Adam optimizer (Kingma & Ba, 2014) to update the policy network with a learning rate $10^{-4}$ and the pre-trained VT with a learning rate $10^{-5}$. Our codes and pre-trained model will be publicly release for reproducibility.

### 5.2 COMPETING METHODS

We compare our method with the following ones: **Random policy.** An agent chooses actions based on a uniform action probability. Thus, the agent will walk or stop in a scene randomly. **Scene Prior (SP)** (Yang et al., 2018) learns a graph neural network from the FastText database (Joulin et al., 2016) and leverages the scene prior knowledge and category relationships for navigation. **Word Embedding (WE)** uses GloVe embedding (Pennington et al., 2014) to indicate the target category rather than detection. The association between object appearances and GloVe embeddings is learned

Table 1: Comparison with SOTA. The success rate (%) and SPL are reported. $L > 5$ represents the episodes which require at least 5 steps.

| Method | ALL | | $L \geq 5$ | |
|---|---|---|---|---|
| | Success | SPL | Success | SPL |
| Random | 8.0 | 0.036 | 0.3 | 0.001 |
| WE | 33.0 | 0.147 | 21.4 | 0.117 |
| SP (Yang et al., 2018) | 35.1 | 0.155 | 22.2 | 0.114 |
| SAVN (Wortsman et al., 2019) | 40.8 | 0.161 | 28.7 | 0.139 |
| ORG (Du et al., 2020) | 65.3 | 0.375 | 54.8 | 0.361 |
| ORG+TPN (Du et al., 2020) | 69.3 | 0.394 | 60.7 | 0.386 |
| Baseline | 62.6 | 0.364 | 51.5 | 0.345 |
| VTNet | 72.2 | **0.449** | 63.4 | **0.440** |
| **VTNet + TPN** (Du et al., 2020) | **73.5** | 0.440 | **63.9** | **0.440** |

through trail and error. **Self-adaptive Visual Navigation (SAVN)** (Wortsman et al., 2019) introduces a meta reinforcement learning method that allows an agent to adapt to unseen environments. **Object Relationship Graph (ORG)** (Du et al., 2020) is a visual representation learning method to encode correlation among categories and employs a tentative policy network (TPN) to escape from deadlocks. **Baseline** is a vanilla version of VTNet. We feed the concatenation of the local instance features from DETR and the global feature to A3C for navigation. Note that, our baseline does not employ spatial-enhanced local and positional global descriptors as well as our visual transformer.

### 5.3 EVALUATION RESULTS

**Improvement over Baseline.** Table 1 indicates that VTNet surpasses the baseline by a large margin on both success rate (+9.6%) and SPL (+0.085). **Baseline** only resorts to the detection features and global feature for navigation. The relations among local instances and the association between the visual observations and actions are not exploited. This comparison suggests that our VT leads to informative visual representations for navigation, and thus significantly improves the effectiveness and efficiency of our navigation system.

**Comparison with competing methods.** As indicated in Table 1, we observe that VTNet significantly outperforms SP (Yang et al., 2018) and SAVN (Wortsman et al., 2019). Since SP and SAVN employ word embedding as a target indicator while VTNet replaces word embedding with our VT, our method achieves expressive object and image region representations for navigation. In addition, SP and SAVN concatenate features from various modalities directly to generate the visual representation. The gap between different modalities may not facilitate navigation policy learning. In contrast, benefiting from our pre-training, features from our VT are more correlated to navigation actions, thus expediting navigation policy learning.

Our method outperforms the state-of-the-art method ORG (Du et al., 2020) by +2.9% in success rate and +0.055 in SPL. Moreover, when ORG does not employ TPN, the advantage of our method becomes more obvious (6.9% improvement), and this mainly comes from our superior visual presentations. Since ORG only chooses an object with the highest confidence in each class, the relationship among objects is not comprehensive. On the contrary, our method can exploit all the detected instances to deduce the relationships among objects due to our VT architecture. Moreover, as the local visual features are output by the DETR, they are more compatible compared to the direct concatenation of features from different layers of a CNN backbone in ORG. This can be proved by the result when we use Faster-RCNN as our backbone. We also show a case study in Figure 3 (more visual results are provided in the appendix). Furthermore, we also try to employ TPN to improve our navigation policy. As seen in Table 1, VTNet+TPN improves the success rates but the improvement is not as much as ORG+TPN. This also implies that our visual representations significantly facilitate navigation action selections.

**Case Study.** As illustrated in Figure 3, SAVN and baseline fail to reach the target after taking a few steps (7 and 19 steps, respectively) and then issuing a termination command. An implication is that the relationship among categories is not clear in SAVN and Baseline. In contrast, both ORG and VTNet find the target. Since the visual transformer provides clear directional signals, VENet uses the least steps to find the object.

### 5.4 VARIANT AND ABLATION STUDY

We analyze the impact of each component in VTNet, including the spatial-enhanced local descriptor, positional global descriptor and visual transformer which fuses these two spatial-aware descriptors.

Figure 3: **Visual results of four different models in testing environments.** The target objects (*i.e.*, *RemoteControl*) are highlighted by the blue boxes. Green and red curves represent success and failure cases, respectively. The episode produced by our VTNet is successful in reaching the target and use shortest steps. In comparison, ORG takes more steps to reach the target. SAVN and baseline miss both targets.

Table 2: Impacts of different components on navigation performances

| Method | | w/o global | w/o decoder | w/o pe | Baseline | | VTNet | |
|---|---|---|---|---|---|---|---|---|
| | | | | | Faster RCNN | DETR | Faster RCNN | **DETR** |
| ALL | Success | 67.0 | 67.0 | 71.0 | 56.4 | 62.6 | 70.1 | **72.2** |
| | SPL | 0.390 | 0.373 | 0.432 | 0.319 | 0.365 | 0.396 | **0.449** |
| $L \geq 5$ | Success | 54.5 | 53.2 | 61.2 | 42.5 | 51.5 | 61.7 | **63.4** |
| | SPL | 0.357 | 0.343 | 0.416 | 0.270 | 0.345 | 0.399 | **0.440** |

To illustrate the necessity of the spatial enhancement, we directly use the object features without spatial enhancement. In this case, our network fails to converge because the feed-forward layers that predict bounding-boxes and class labels in DETR are not used in VTNet and spatial information cannot be decoded by the navigation network. Thus, spatial enhancement allows an agent to exploit instance location information explicitly.

As indicated in Table 2, using object instance features from DETR, we achieve better navigation performance compared to the features from Faster-RCNN backbone. Note that, Faster-RCNN and DETR obtain similar detection accuracy (AP50) on the validation set, *i.e.*, 0.729 vs. 0.752. We speculate the improvements mainly come from the fact that the features outputted by DETR decoder have been scale aligned, and those features are more suitable for the following feature fusion operations.

As seen in Table 2, we first remove the global feature from our system ("VTNet w/o global"), and the navigation performance degrades significantly. This validates the importance of global features, which provide contextual guidance to an agent. Morevoer, when we remove the positional embedding from the global feature ("VTNet w/o pe"), we observe that both effectiveness and efficiency of the navigation decrease. This indicates that the position embeddings enable agents to encode spatial information of observation regions. Furthermore, we remove the VT decoder ("VTNet w/o decoder") and concatenate the global and local descriptors directly, our method suffers performance degradation. This demonstrates that our VT plays an critial role in attending the global descriptors to local ones.

When the pre-training scheme is not applied to our VT, agents fail to learn any navigation policy and thus we do not report the performance. This manifests that our VT pre-training procedure provides prior knowledge on associating visual observations with navigation actions to agents.

## 6 CONCLUSION

In this paper, we proposed a powerful visual representation learning method for visual navigation, named Visual Transformer Network (VTNet). In our VTNet, a visual transformer (VT) is developed to encode visual observations. Our VT leverages two newly designed spatial-aware descriptors, *i.e.*, spatial-enhanced local object descriptor and positional global descriptor, and then fuses those two descriptors via multi-head attention to our final visual representation. Thanks to our VT architecture, all the detected instances will be exploited for understanding the current observation. Therefore, our visual representation is more informative compared to that used in state-of-the-art navigation methods. Benefiting from our pre-training strategy, our VT is able to associate our visual representation with navigation actions, thus significantly expediting navigation policy learning. Extensive results demonstrate that our VTNet outperforms the state-of-the-art.

## REFERENCES

Peter Anderson, Qi Wu, Damien Teney, Jake Bruce, Mark Johnson, Niko Sünderhauf, Ian Reid, Stephen Gould, and Anton van den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3674–3683, 2018.

Johann Borenstein and Yoram Koren. Real-time obstacle avoidance for fast mobile robots. *IEEE Transactions on systems, Man, and Cybernetics*, 19(5):1179–1187, 1989.

Johann Borenstein and Yoram Koren. The vector field histogram-fast obstacle avoidance for mobile robots. *IEEE transactions on robotics and automation*, 7(3):278–288, 1991.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. *arXiv preprint arXiv:2005.12872*, 2020.

Kevin Chen, Juan Pablo de Vicente, Gabriel Sepulveda, Fei Xia, Alvaro Soto, Marynel Vázquez, and Silvio Savarese. A behavioral approach to visual navigation with graph localization networks. *arXiv preprint arXiv:1903.00445*, 2019.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

MWM Gamini Dissanayake, Paul Newman, Steve Clark, Hugh F Durrant-Whyte, and Michael Csorba. A solution to the simultaneous localization and map building (slam) problem. *IEEE Transactions on robotics and automation*, 17(3):229–241, 2001.

Heming Du, Xin Yu, and Liang Zheng. Learning object relation graph and tentative policy for visual navigation. *arXiv preprint arXiv:2007.11018*, 2020.

Kuan Fang, Alexander Toshev, Li Fei-Fei, and Silvio Savarese. Scene memory transformer for embodied agents in long-horizon tasks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 538–547, 2019.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Armand Joulin, Edouard Grave, Piotr Bojanowski, and Tomas Mikolov. Bag of tricks for efficient text classification. *arXiv preprint arXiv:1607.01759*, 2016.

Gregory Kahn, Adam Villaflor, Bosen Ding, Pieter Abbeel, and Sergey Levine. Self-supervised deep reinforcement learning with generalized computation graphs for robot navigation. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1–8. IEEE, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Daniel Gordon, Yuke Zhu, Abhinav Gupta, and Ali Farhadi. AI2-THOR: An Interactive 3D Environment for Visual AI. *arXiv*, 2017.

Piotr Mirowski, Razvan Pascanu, Fabio Viola, Hubert Soyer, Andrew J Ballard, Andrea Banino, Misha Denil, Ross Goroshin, Laurent Sifre, Koray Kavukcuoglu, et al. Learning to navigate in complex environments. *arXiv preprint arXiv:1611.03673*, 2016.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937, 2016.

Arsalan Mousavian, Alexander Toshev, Marek Fišer, Jana Košecká, Ayzaan Wahid, and James Davidson. Visual representations for semantic target driven navigation. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 8846–8852. IEEE, 2019.

Giuseppe Oriolo, Marilena Vendittelli, and Giovanni Ulivi. On-line map building and navigation for autonomous mobile robots. In *Proceedings of 1995 IEEE International Conference on Robotics and Automation*, volume 3, pp. 2900–2906. IEEE, 1995.

Emilio Parisotto and Ruslan Salakhutdinov. Neural map: Structured memory for deep reinforcement learning. *arXiv preprint arXiv:1702.08360*, 2017.

Jeffrey Pennington, Richard Socher, and Christopher Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pp. 1532–1543, 2014.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. In *Advances in neural information processing systems*, pp. 91–99, 2015.

Nikolay Savinov, Alexey Dosovitskiy, and Vladlen Koltun. Semi-parametric topological memory for navigation. *arXiv preprint arXiv:1803.00653*, 2018.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Gabriel Sepulveda, Juan Carlos Niebles, and Alvaro Soto. A deep learning based behavioral approach to indoor autonomous navigation. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 4646–4653. IEEE, 2018.

William B Shen, Danfei Xu, Yuke Zhu, Leonidas J Guibas, Li Fei-Fei, and Silvio Savarese. Situational fusion of visual representation for visual navigation. *arXiv preprint arXiv:1908.09073*, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Xin Wang, Qiuyuan Huang, Asli Celikyilmaz, Jianfeng Gao, Dinghan Shen, Yuan-Fang Wang, William Yang Wang, and Lei Zhang. Reinforced cross-modal matching and self-supervised imitation learning for vision-language navigation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6629–6638, 2019.

Christopher JCH Watkins and Peter Dayan. Q-learning. *Machine learning*, 8(3-4):279–292, 1992.

Mitchell Wortsman, Kiana Ehsani, Mohammad Rastegari, Ali Farhadi, and Roozbeh Mottaghi. Learning to learn how to learn: Self-adaptive visual navigation using meta-learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6750–6759, 2019.

Yi Wu, Yuxin Wu, Aviv Tamar, Stuart Russell, Georgia Gkioxari, and Yuandong Tian. Bayesian relational memory for semantic visual navigation. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2769–2779, 2019.

Wei Yang, Xiaolong Wang, Ali Farhadi, Abhinav Gupta, and Roozbeh Mottaghi. Visual semantic navigation using scene priors. *arXiv preprint arXiv:1810.06543*, 2018.

Yuke Zhu, Roozbeh Mottaghi, Eric Kolve, Joseph J Lim, Abhinav Gupta, Li Fei-Fei, and Ali Farhadi. Target-driven visual navigation in indoor scenes using deep reinforcement learning. In *2017 IEEE international conference on robotics and automation (ICRA)*, pp. 3357–3364. IEEE, 2017.

# A APPENDIX

## A.1 FEATURE DETAILS IN VTNET

Figure 4: Illustration feature flowchart in VTNet.

For reproducibility, we illustrate our detailed feature flowchart in VTNet, as seen in Figure 4. We extract instance feature $\mathbb{R}^{100 \times 256}$ and location feature $\mathbb{R}^{100 \times 249}$, and concatenate them into the spatial-enhanced local descriptor $\mathbb{R}^{100 \times 256}$. This local branch integrates semantic labels $\mathbb{R}^{100 \times 1}$, bounding boxes $\mathbb{R}^{100 \times 4}$, confidences $\mathbb{R}^{100 \times 1}$ and the target labels $\mathbb{R}^{100 \times 1}$ from the current observation. In the global branch, the positional embedding $\mathbb{R}^{7 \times 7 \times 256}$ is added to the global feature $\mathbb{R}^{7 \times 7 \times 256}$, leading to the positional global descriptor $\mathbb{R}^{49 \times 256}$. Together with the spatial-enhanced local descriptor, they are fused by VT encoder and decoder to the visual representation $\mathbb{R}^{49 \times 256}$.

## A.2 FAILURE CASE STUDY

Figure 5: **Visual results of failure cases in testing environments.** The target objects (*i.e.*, Bowl and Laptop) are highlighted by the blue box. Red lines indicate the distance between the agent and the target object. Gray curves present trajectories of agents. Both episodes are failed because distances (*i.e.*, 1.530m and 1.572m) between the agent and target in the field of view are farther than the threshold (*i.e.*, 1.5m).

As demonstrated in Figure 5, our VTNet fails to reach targets because of the distance between the agent and the target is farther than the threshold distance (*i.e.*, 1.5m). In two failure cases, agents find and navigate towards targets but select the termination action before reaching a position closer than the threshold. Due to the lack of depth information and the diversity of target object sizes, an agent terminates the navigation by wrong judgment on the distance to the target.

## A.3 CASE STUDY

Figure 6: **Visual results of four different models in testing environments.** We compare VTNet with SAVN (Wortsman et al., 2019), the baseline and ORG (Du et al., 2020). The target objects are highlighted by the blue boxes. Green and red curves are success and failure cases, respectively. Episodes produced by our VTNet are successful in reaching the target and use the shortest steps.

## A.4 ASSESSING DIFFERENT VISUAL TRANSFORMER ARCHITECTURES.

Table 3: Comparison of visual transformer architectures. We report the pre-training accuracy on the validation dataset, navigation success rate and SPL on the test dataset.

| Multi-head numbers | Encoder layers | Decoder layers | Accuracy | Success | SPL |
|---|---|---|---|---|---|
| **4** | 1 | 1 | 0.722 | 71.2 | 0.433 |
| | **2** | **2** | **0.723** | **72.2** | **0.449** |
| | 4 | 4 | 0.715 | 70.0 | 0.419 |
| 8 | 1 | 1 | 0.707 | 70.4 | 0.422 |
| | 2 | 2 | 0.718 | 70.9 | 0.436 |
| | 4 | 4 | 0.710 | 68.9 | 0.423 |
| | 6 | 6 | 0.701 | 68.2 | 0.411 |

We construct different transformers by varying the number of encoder and decoder layers. Table 3 summarizes the performance of these structures. We find that a visual transformer too deep to converge to the optimal policy, while a single encoder and decoder layer suffers lower network capability. The highest success rate is achieved with four heads of the multi-head self-attention mechanism, two layers of encoder and decoder.