Controlling directions orthogonal to a classifier

Abstract

We propose to identify directions invariant to a given classifier so that these directions can be controlled in tasks such as style transfer. While orthogonal decomposition is directly identifiable when the given classifier is linear, we formally define a notion of orthogonality, and when it exists, in the non-linear case. We also provide a surprisingly simple method for constructing the orthogonal classifier (a classifier utilizing directions other than the given classifier). Empirically, we present three use cases where controlling orthogonal variation is important: style transfer, domain adaptation, and fairness. The orthogonal classifier enables desired style transfer when domains vary in multiple aspects, improves domain adaptation with label shifts and mitigates the unfairness as a predictor.

1 Introduction

Many machine learning applications require explicit control of directions that are orthogonal to a predefined one. For example, to ensure fairness, we can learn a classifier that is orthogonal to sensitive attributes such as gender or race (Zemel et al., 2013; Madras et al., 2018). Similar, if we transfer images from one style to another, content other than style should remain untouched. Therefore images before and after transfer should align in directions orthogonal to style. Common to these problems is the task of finding an orthogonal classifier. Given any *principal classifier* operating on the basis of *principal variables*, our goal is to find a classifier, termed *orthogonal classifier*, that predicts the label on the basis of *orthogonal variables*, defined formally later.

The notion of orthogonality is clear in the linear case. Consider a joint distribution where label $Y \sim \mathcal{B}(0.5)$ and class-conditional distributions are $X|Y = y \sim \mathcal{N}(\mu_y, \sigma_y^2 I)$ with label dependent means μ_0, μ_1 and variances σ_0, σ_1. If the principal classifier is linear, $w_1 = \Pr(Y = 1|\theta_1^\top x)$, then the orthogonal classifier $w_2 = \Pr(Y = 1|\theta_2^\top x)$ must satisfy $\theta_1^\top \theta_2 = 0$, implying orthogonal decision boundaries (Fig. 1). Thus the two classifiers w_1, w_2 focus on distinct but complementary attributes for predicting the same label.

Finding the orthogonal classifier is no longer straightforward in the non-linear case. To rigorously define what we mean by the orthogonal classifier, we first introduce the notion of mutually orthogonal random variables that correspond to (conditinally) independent latent variables mapped to observations through diffeomorphism (or bijection if discrete). Each r.v. is predictive of the label but represents complementary information. Indeed, we show that the orthogonal random variable maximizes the conditional mutual information with the label given the principal counterpart, subject to the independence constraint (ensuring complementarity).

Our search for the orthogonal classifier can be asked now as follows: given a principal classifier w_1 using some unknown principal r.v. for prediction, how do we find its orthogonal classifier w_2 relying solely on the orthogonal random variable? The solution to this problem, which we call *classifier orthogonalization*, turns out to be surprisingly simple, making use of an overall classifier w_x in addition to the principal one. We denote the outcome of this orthogonalization process as $w_2 = w_x \smallsetminus w_1$. The advantage of this construction is that it is based only on the classifiers, not needing to uncover the exact latent mechanism referred to in the definition.

(a) Distribution $p_{X|Y}$ (b) $w_x(x)$ (c) $w_1(x)$ (d) $w_2(x)$

Figure 1: An illustrative example of orthogonal classifier in a linear case. (a) is the data distributions in two classes; (b,c,d) are the probabilities of the data from class 1 predicted by the full/principle/orthogonal classifiers. Red and blue colors mean a probability close to 1 or 0. The white color indicates regions with a probability close to 0.5, which are classifiers' decision boundaries. Clearly, w_1 and w_2 have orthogonal decision boundaries.

We provide several use cases for the orthogonal classifier, either as a predictor or as a discriminator. As a predictor, the orthogonal classifier predictions are invariant to the principal sensitive r.v., thus ensuring fairness. As a discriminator, the orthogonal classifier enforces a partial alignment of distributions, allowing changes in the principal direction. We demonstrate the value of such discriminator in 1) *controlled style transfer* where the source and target domains differ in multiple aspects, but we only wish to align domain A's style to domain B, leaving other aspects intact; 2) *domain adaptation with label shift* where we align feature distributions between the source and target domains, allowing shifts in label proportions. Our results show that the simple method is on par with the state-of-the-art methods in each task.

2 NOTATIONS AND DEFINITION

Symbols. We use the uppercase to denote random variable (*e.g.*, data X, label Y), the lowercase to denote the corresponding samples and the calligraphic letter to denote the sample spaces of r.v., *e.g.*, data sample space $\mathcal{X}$. We focus on the setting where label space $\mathcal{Y}$ is discrete, *i.e.*, $\mathcal{Y} = \{1, \cdots, C\}$, and denote the $C-1$ dimensional probability simplex as Δ^C. A classifier $w : \mathcal{X} \to \Delta^C$ is a mapping from sample space to the simplex. It's y-th dimension $w(x)_y$ denotes the predicted probability of label y for sample x.

Distributions. For random variables A, B, we use the notation p_A, $p_{A|B}$, p_{AB} to denote the marginal/conditional/joint distribution, *i.e.*, $p_A(a) = p(A = a)$, $p_{A|B}(a|b) = p(A = a|B = b)$, $p_{AB}(a, b) = p(A = a, B = b)$. Sometimes, for simplicity, we may ignore the subscript if there is no ambiguity, *e.g.*, $p(a|b)$ is an abbreviation for $p_{A|B}(a|b)$.

We begin by defining the notion of an orthogonal random variable. We consider continuous X, Z_1, Z_2 and assume their supports are manifolds diffeomorphic with the Euclidean space. The probability density functions (PDF) are in $\mathcal{C}^1$. Given a joint distribution p_{XY}, we define the orthogonal random variable as follows:

Definition 1 (Orthogonal random variables). *We say Z_1 and Z_2 are orthogonal random variables w.r.t p_{XY} if they satisfy the following properties:*

(i) There exists a diffeomorphism $f : \mathcal{Z}_1 \times \mathcal{Z}_2 \to \mathcal{X}$ such that $f(Z_1, Z_2) = X$.

(ii) Z_1 and Z_2 are statistically independent given Y, i.e., $Z_1 \perp\!\!\!\perp Z_2|Y$.

The orthogonality relation is symmetric by definition. Note that the orthogonal pair perfectly reconstructs the observations via diffeomorphism f; as random variables they are also sampled independently from class conditional distributions $p(Z_1|Y)$ and $p(Z_2|Y)$. For example, we can regard foreground objects and background scenes in natural images as being mutually orthogonal random variables.

Remark. The definition of orthogonality can be similarly developed for the discrete variables and discrete-continuous mixtures. For discrete variables, for example, we can replace the requirement of diffeomorphism with bijection.

Since the diffeomorphism f is invertible, we can use $z_1 : \mathcal{X} \to \mathcal{Z}_1$ and $z_2 : \mathcal{X} \to \mathcal{Z}_2$ to denote the two parts of the inverse mapping so that $Z_1 = z_1(X)$ and $Z_2 = z_2(X)$. Note that, for a given joint distribution p_{XY}, the decomposition into orthogonal random variables is not unique. There are multiple pairs of random variables that represent valid mutually orthogonal latents of the data. We can further justify our definition of orthogonality from an information theoretic perspective by showing that the choice of z_2 attains the maximum of the following constrained optimization problem.

Proposition 1. *Suppose the orthogonal r.v. of $z_1(X)$ w.r.t p_{XY} exists and is denoted as $z_2(X)$. Then $z(X) = z_2(X)$ is a maximizer of $I(z(X), Y | z_1(X))$ subject to $I(z(X); z_1(X)|Y) = 0$.*

We defer the proof to Appendix B.1. Proposition 1 shows that the orthogonal random variable maximizes the additional information about the label we can obtain from X while remaining conditionally independent of the principal random variable. This ensures complementary in predicting the label.

3 CONSTRUCTING THE ORTHOGONAL CLASSIFIER

Let $Z_1 = z_1(X)$ and $Z_2 = z_2(X)$ be mutually orthogonal random variables w.r.t p_{XY}. We call Z_1 the principal variable and Z_2 the orthogonal variable. In this section, we describe how we can construct the Bayes optimal classifier operating on features Z_2 from the Bayes optimal classifier relying on Z_1. We formally refer to the classifiers of interests as: (1) principal classifier $w_1(x)_y = p(Y = y|Z_1 = z_1(x))$; (2) orthogonal classifier $w_2(x)_y = p(Y = y|Z_2 = z_2(x))$; (3) full classifier $w_x(x)_y = p(Y = y|X = x)$.

3.1 CLASSIFIER ORTHOGONALIZATION

Our key idea relies on the bijection between the density ratio and the Bayes optimal classifier (Sugiyama et al., 2012). Specifically, the ratio of densities $p_{X|Y}(x|i)$ and $p_{X|Y}(x|j)$, assigned to an arbitrary point x, can be represented by the Bayes optimal classifier $w(x)_i = \Pr(Y = i|x)$ as $\frac{p_{X|Y}(x|i)}{p_{X|Y}(x|j)} = \frac{p_Y(j)w(x)_i}{p_Y(i)w(x)_j}$. Similar, the principal classifier w_1 gives us associated density ratios of class-conditional distributions over Z_1. For any $i, j \in \mathcal{Y}$, we have $\frac{p_{Z_1|Y}(z_1(x)|i)}{p_{Z_1|Y}(z_1(x)|j)} = \frac{p_Y(j)w_1(x)_i}{p_Y(i)w_1(x)_j}$. These can be combined to obtain density ratios of class-conditional distribution $p_{Z_2|Y}$ and subsequently calculate the orthogonal classifier w_2. We additionally rely on the fact that the diffeomorphism f permits us to change variables between x and z_1, z_2: $p_{X|Y}(x|i) = p_{Z_1|Y}(z_1|i)p_{Z_2|Y}(z_2|i)\mathrm{vol}J_f(z_1, z_2)$. Taken together,

$$\frac{p_{Z_2|Y}(z_2|i)}{p_{Z_2|Y}(z_2|j)} = \frac{p_{Z_1|Y}(z_1|i)p_{Z_2|Y}(z_2|i)\mathrm{vol}J_f(z_1, z_2)}{p_{Z_1|Y}(z_1|j)p_{Z_2|Y}(z_2|j)\mathrm{vol}J_f(z_1, z_2)} \Big/ \frac{p_{Z_1|Y}(z_1|i)}{p_{Z_1|Y}(z_1|j)} = \frac{w_x(x)_i}{w_x(x)_j} \Big/ \frac{w_1(x)_i}{w_1(x)_j}$$

where $\mathrm{vol}J_f$ is the volume of Jacobian (Berger et al., 1987) of the diffeomorphism mapping. Note that since the diffeomorphism f is shared with all classes, the Jacobian is the same for all label-conditioned distributions on Z_1, Z_2. Hence the Jacobian volume terms cancel each other in the above equation. We can then finally work backwards from the density ratios of $p_{Z_2|Y}$ to the orthogonal classifier:

$$\Pr(Y = i|Z_2 = z_2(x)) = \Pr(Y = i)\frac{w_x(x)_i}{w_1(x)_i} \Big/ \sum_j \left(\Pr(Y = j)\frac{w_x(x)_j}{w_1(x)_j} \right) \tag{1}$$

We call this procedure *classifier orthogonalization* since it adjust the full classifier w_x to be orthogonal to the principal classifier w_1. The validity of this procedure is subject to overlapping support of class-conditional distributions, ensures that w_x, w_1 remain non-zero.

Empirically, we usually have access to a dataset $\mathcal{D} = \{(x_t, y_t)\}_{t=1}^n$ with n iid samples from the joint distribution p_{XY}. To obtain the orthogonal classifier, we need to first train the full classifier $\hat{w}_x$ based on the dataset $\mathcal{D}$. We can then follow the classifier orthogonalization to get an empirical orthogonal classifier, denoted as $w_2 = \hat{w}_x \setminus w_1$. We use symbol $\setminus$ to emphasize that the orthogonal classifier uses complementary information relative to z_1. Algorithm 1 summarizes the construction of the orthogonal classifier.

Generalization bound. Since w_x is trained on a finite dataset, we consider the generalization bound of the constructed orthogonal classifier. We denote the population risk as

---

Algorithm 1 Classifier Orthogonalization

Input: principal classifier w_1, dataset $\mathcal{D}$.
Train an empirical full classifier $\hat{w}_x$ on $\mathcal{D}$ by empirical risk minimization.
Construct an orthogonal classifier $\hat{w}_x \smallsetminus w_1$ via classifier orthogonalization (Eq. (1)).
return the empirical orthogonal classifier $\hat{w}_2 = \hat{w}_x \smallsetminus w_1$

$R(w) = -\mathbb{E}_{p_{XY}(x,y)}\left[\log w(x)_y\right]$ and the empirical risk as $\hat{R}(w) = -\frac{1}{|\mathcal{D}|}\sum_{(x_i,y_i)\in\mathcal{D}}\log w(x_i)_{y_i}$. For a function family $\mathcal{W}$ whose elements map $\mathcal{X}$ to the simplex Δ^C, we define $\hat{w}_x = \inf_{w_x\in\mathcal{W}}\hat{R}(w_x), w_x^* = \inf_{w_x\in\mathcal{W}} R(w_x)$. We further denote the Rademacher complexity of function family $\mathcal{W}$ with sample size $|\mathcal{D}|$ as $\mathfrak{R}_{|\mathcal{D}|}(\mathcal{W})$.

Theorem 1. *Assume* $\forall w_x \in \mathcal{W}$ *takes values in* $(m, 1-m)^C$ *with* $m \in (0, \frac{1}{2})$, *and* $p_{X|Y}(x|i)/p_{X|Y}(x|j) \in (a,b) \subset (0,+\infty)$ *holds for* $\forall x \in \mathcal{X}, i,j \in \mathcal{Y}$. *Denote* $\gamma = \max(\frac{1}{a}, b)$, *then for any* $\delta \in (0,1)$ *with probability at least* $1-\delta$, *we have:*

$$|R(\hat{w}_x \smallsetminus w_1) - R(w_x^* \smallsetminus w_1)| \leq 2(2+\gamma)\mathfrak{R}_{|\mathcal{D}|}(\mathcal{W}) + 2\log\frac{1}{m}\sqrt{\frac{2\log\frac{1}{\delta}}{|\mathcal{D}|}}$$

Theorem 1 shows that the population risk of the empirical orthogonal classifier in Algorithm 1 would be closed to the optimal risk if the maximum density ratio of class-conditioned distributions and the Rademacher term are small. Typically, the Rademacher complexity term satisfies $\mathfrak{R}_{|\mathcal{D}|}(\mathcal{W}) = \mathcal{O}(|\mathcal{D}|^{-\frac{1}{2}})$ (Bartlett & Mendelson, 2001; Gao & Zhou, 2016).

3.2 ALTERNATIVE METHOD: IMPORTANCE SAMPLING

An alternative way to get the orthogonal classifier is via importance sampling. For each sample point (x,y), we construct its importance $\phi(x,y) := \frac{p_{Z_1}(z_1(x))}{p_{Z_1|Y}(z_1(x)|y)}$. Via Bayes' rule, the importance $\phi(x,y)$ can be calculated from the principal classifier by $\phi(x,y) = \frac{p_Y(y)}{w_1(x)_y}$. We define the importance sampling (IS) objective as $\mathcal{L}_{\text{IS}}(w) := \mathbb{E}_{x,y\sim p_{XY}}[\phi(x,y)\log w(x)_y]$. It can be shown that the orthogonal classifier w_2 maximize the IS objective, *i.e.*, $w_2 = \arg\max \mathcal{L}_{\text{IS}}$. However, importance sampling method has an Achilles' heel, variance. A few bad samples with large weights can drastically deviates the estimation, which is problematic for mini-batch learning in practice. We provide an analysis to the variance of the IS objective. It shows the variance increases with the divergences between Z_1's marginal and its label-conditioned marginals, $\{D_f(p_{Z_1}\|p_{Z_1|Y=y})\}_{y=1}^C$ even when the learned classifier w is approaching to the optimal, *i.e.*, $w \approx w_2$. Let $\widehat{\mathcal{L}_{\text{IS}}^n}(w) := \frac{1}{n}\sum_{t=1}^n \phi(x_t,y_t)\log w(x_t)_{y_t}$ be the empirical IS objective estimated with n iid samples. Clearly, $\text{Var}(\widehat{\mathcal{L}_{\text{IS}}^n}(w)) = \frac{1}{n}\text{Var}(\widehat{\mathcal{L}_{\text{IS}}^1}(w))$. While $\text{Var}(\widehat{\mathcal{L}_{\text{IS}}^1}(w))$ at w_2 is the following,

$$\text{Var}(\widehat{\mathcal{L}_{\text{IS}}^1}(w_2)) = \mathbb{E}_Y\left[\left(D_f(p_{Z_1}\|p_{Z_1|Y=y})+1\right)\mathbb{E}_{Z_2|Y=y}\log^2 p_{Y|Z_2}(y|z_2)\right] - \mathcal{L}(w_2)^2$$

where D_f is the Pearson χ^2-divergence. The expression indicates that the variance grows linearly with the expected divergence. In contrast, the divergences have little effect when training the empirical full classifier in classifier orthogonalization. We provide further experimental results in section 4.1.2 to demonstrate that classifier orthogonalization has better stability than the IS objective with increasing divergences and learning rates.

4 ORTHOGONAL CLASSIFIER FOR CONTROLLED STYLE TRANSFER

In style transfer, we have two domains A, B with distributions P_{XY}, Q_{XY}. We use binary label Y to indicate the domain of data X (0 for domain A, 1 for domain B). Assume Z_1 and Z_2 are latent variables that mutually orthogonal w.r.t both P_{XY} and Q_{XY}. The goal is to conduct controlled style transfer between the two domains. By controlled style transfer, we mean transferring the style domain A's data to domain B via only making changes on partial latent (Z_1) while not touching the other latent (Z_2). Mathematically, we aim to transfer the latent distribution from $P_{Z_1}P_{Z_2}$ to $Q_{Z_1}P_{Z_2}$. This task cannot be achieved by traditional style transfer algorithms such as CycleGAN (Zhu et al., 2017), since they directly

(a) (b) (c)

Figure 2: **(a,b):** Test loss versus log expected divergence and learning rate. **(c):** The histogram of predicted probability of different methods. The two red lines are the ground-truth probabilities for $P(Y = 1|\text{Brown background})$ and $P(Y = 1|\text{Green background})$.

transfer data distributions from P_X to Q_X, or equivalently from the perspective of latent distributions, from $P_{Z_1}P_{Z_2}$ to $Q_{Z_1}P_{Z_2}$.

Below we utilize the empirical orthogonal classifier $\hat{w}_x \smallsetminus w_1$ to perform controlled style transfer. Our strategy is to plug the orthogonal classifier into the objective of CycleGAN. The original CycleGAN objective defines a min-max game between two generators/discriminator pairs G_{AB}/D_{AB} and G_{BA}/D_{BA}. G_{AB} transforms the images from domain A to domain B. We use $\widetilde{P}$ to denote the transformed distribution, *i.e.*, $G_{AB}(X) \sim \widetilde{P}$ for $X \sim P$. Similarly, $\widetilde{Q}$ denotes the generative distribution of generator G_{BA}. The minimax game of CycleGAN is given by

$$\min_{G_{AB},G_{BA}} \max_{D_{AB},D_{BA}} \mathcal{L}_{\text{GAN}}^{AB}(G_{AB}, D_{AB}) + \mathcal{L}_{\text{GAN}}^{BA}(G_{BA}, D_{BA}) + \mathcal{L}_{\text{cyc}}(G_{AB}, G_{BA}) \quad (2)$$

where GAN losses $\mathcal{L}_{\text{GAN}}^{AB}, \mathcal{L}_{\text{GAN}}^{BA}$ minimize the divergence between the generative distributions and the targets, and the cycle consistency loss $\mathcal{L}_{\text{cyc}}$ is used to regularize the generators (Zhu et al., 2017). The GAN loss $\mathcal{L}_{\text{GAN}}^{AB}$ is defined as follows,

$$\mathcal{L}_{\text{GAN}}^{AB}(G_{AB}, D_{AB}) := \mathbb{E}_{x \sim Q}[\log D_{AB}(x)] + \mathbb{E}_{x \sim \widetilde{P}}[\log(1 - D_{AB}(x))]$$

Now we tilt the GAN losses in CycleGAN objective to guide the generators to perform controlled transfer. Specially, we replace $\mathcal{L}_{\text{GAN}}^{AB}$ in Eq. (2) with the orthogonal GAN loss $\mathcal{L}_{\text{OGAN}}^{AB}$ when updating the generator G_{AB}:

$$\mathcal{L}_{\text{OGAN}}^{AB}(G_{AB}, D_{AB}) := \mathbb{E}_{x \sim \widetilde{P}}[\log(1 - \phi(D_{AB}(x), r(x)))]$$

where $\phi(D_{AB}(x), r(x)) = \frac{D_{AB}(x)r(x)}{(1-D_{AB}(x))+D_{AB}(x)r(x)}$ and $r(x) = \frac{\hat{w}_x \smallsetminus w_1(x)_0}{1-\hat{w}_x \smallsetminus w_1(x)_0}$. Consider an extreme case where we allow the model to change all latent, *i.e.*, $z_1(x) = x$. As a result, $\mathcal{L}_{\text{OGAN}}$ degenerates to the original $\mathcal{L}_{\text{GAN}}$ since $w_2 \equiv \frac{1}{2}$ and $\phi(D_{AB}(x), r(x)) \equiv D_{AB}(x)$. The other orthogonal GAN loss $\mathcal{L}_{\text{OGAN}}^{BA}$ can be similarly derived. For a given generator G_{AB}, the discriminator's optimum is achieved at $D_{AB}^*(x) = Q(x)/(\widetilde{P}(x) + Q(x))$. Assuming the discriminator is always trained to be optimal, the generator G_{AB} can be viewed as optimizing the following virtual objective: $\mathcal{L}_{\text{OGAN}}^{AB}(G_{AB}) := \mathcal{L}_{\text{OGAN}}^{AB}(G_{AB}, D_{AB}^*) = \mathbb{E}_{x \sim \widetilde{P}} \log \frac{\widetilde{P}(x)}{\widetilde{P}(x)+Q(x)r(x)}$. The optimal generator in the new objective satisfies the following property.

Proposition 2. *The global minimum of $\mathcal{L}_{\text{OGAN}}^{AB}(G_{AB})$ is achieved if and only if $\widetilde{P}_{Z_1,Z_2}(z_1, z_2) = Q_{Z_1}(z_1)P_{Z_2}(z_2)$.*

We defer the proof to Appendix B.4. The proposition states that the new objective $\mathcal{L}_{\text{OGAN}}^{AB}$ converts the original global minimum $Q_{Z_1}Q_{Z_2}$ in $\mathcal{L}_{\text{GAN}}^{AB}$ to the desired one $Q_{Z_1}P_{Z_2}$. Symmetric statement holds for $\mathcal{L}_{\text{OGAN}}^{BA}(G_{BA})$.

4.1 EXPERIMENTS

4.1.1 SETUP

Datasets. (a) *MNIST-C*: We construct MNIST-C(olors) dataset based on MNIST digits (LeCun & Cortes, 2005). MNIST-C has two domains and 60000 images with size $(3, 28, 28)$. The

Table 1: MNIST-C

	Z_1 acc.	Z_2 acc.
Vanilla	90.2	14.3
$w_x \smallsetminus w_1$ (MLDG)	76.9	91.1
$w_x \smallsetminus w_1$ (Fish)	93.9	98.0
IS (Oracle)	90.0	100
$w_x \smallsetminus w_1$ (Oracle)	94.9	100

Table 2: CelebA-GH

	Z_1 acc.	Z_2 acc.	FID ↓
Vanilla	88.4	16.8	**38.5**
$w_x \smallsetminus w_1$ (MLDG)	90.9	53.0	46.2
$w_x \smallsetminus w_1$ (Fish)	88.8	42.9	43.4
IS (Oracle)	89.1	40.6	44.3
$w_x \smallsetminus w_1$ (Oracle)	**93.7**	**57.4**	39.7

majority of the images in each domain will have a digit color and a background color correspond to the domain: domain A ↔ "red digit/green background" and domain B ↔ "blue digit/brown background". We define two *bias degree*s λ_d, λ_b to control the probability of the images having domain associated colors, *e.g.*, for an image in domain A, with λ_d probability, its digit is set to be red; otherwise, its digit color is randomly red or blue. The background colors are determined similarly with parameter λ_b. In our experiments, we set $\lambda_d = 0.9$ and $\lambda_b = 0.8$. Our goal is to transfer the digit color (Z_1) while leaving the background color (Z_2) invariant. (b) *CelebA-GH*: We construct the CelebA-G(ender)H(air) dataset based on the gender and hair color attributes in CelebA (Liu et al., 2015). CelebA-GH consists of 110919 images resized to $(3, 128, 128)$. In CelebA-GH, domain A is non-blond-haired males, and the domain B is blond-haired females. Our goal is to transfer the facial characteristic of gender (Z_1) while keeping the hair color (Z_2) intact.

Models. We compare variants of orthogonal classifiers to the vanilla CycleGAN (**Vanilla**) and the importance sampling objective (**IS**). We consider two ways of obtaining w_1 classifier: (a) *Oracle:* The principal classifier w_1 is trained on an oracle dataset where Z_1 is the only discriminative direction,*e.g.*, setting bias degrees $\lambda_d = 0.9$ and $\lambda_b = 0$ in MNIST-C such that only digit colors vary across domains. (b) *Domain generalization:* Domain generalization algorithms aim to learn the prediction mechanism that is invariant across environments and thus generalizable to unseen environments (Blanchard et al., 2011; Arjovsky et al., 2019). The variability of environments is considered as nuisance variation. We construct environments such that only $Y|Z_1$ is invariant. We defer details of the environments to Appendix E.1. We use two representative domain generalization algorithms, Fish (Shi et al., 2021) and MLDG (Li et al., 2018), to obtain w_1. We indicate different approaches by the parentheses after $w_x \smallsetminus w_1$ and IS. For example, $w_x \smallsetminus w_1$ (Oracle) is the orthogonal classifier with w_1 trained on Oracle datasets.

Metric. We use three metrics for quantitative evaluation: 1) Z_1 accuracy: the success rate of transferring image's latent z_1 from domain A to domain B; 2) Z_2 accuracy: percentage of transferred images whose latent z_2 unchanged; 3) FID scores: a standard metric evaluates image quality (Heusel et al., 2017). We only report FID scores on CelebA-GH dataset since it is not common to compute FID on MNIST images. Z_1, Z_2 accuracies are measured by two oracle classifiers that output an image's latents z_1 and z_2 (Appendix E.1.3).

For more details of datasets, models and training procedure, please refer to Appendix E.

4.1.2 RESULTS

Comparison to IS. In section 3.2, we demonstrate that IS suffers from high variance when the divergences of marginal and label-conditioned latent distributions are large. In this paragraph, we provide empirical evidence that our classifier orthogonalization method is more robust than IS. Fig. 2(a) shows that the test loss of IS, increases dramatically with the divergences. Fig. 2(b) further displays that IS's test loss grows rapidly when enlarging learning rate, which corroborates the observation that gradient variances are more detrimental to the model's generalization with larger learning rates (Wang et al., 2013). In contrast, the test loss of $w_x \smallsetminus w_1$ remains stable with varying divergences and learning rates. In Fig. 2(c), we visualize the histograms of predicted probabilities of $w_x \smallsetminus w_1$ (light color) and IS (dark color). We observe that the predicted probabilities of $w_x \smallsetminus w_1$ better concentrate around the ground-truth probabilities (red lines).

Main result. As shown in Table 1 and 2, adding orthogonal classifier to the vanilla Cycle-GAN significantly improve its z_2 accuracy (from 14 to $90+$ in MNIST-C, from 16 to $40+$ in CelebA-GH) while paying a slight loss of the image quality. We observe that the oracle version of orthogonal classifier ($w_x \smallsetminus w_1$ (Oracle)) achieves best z_2 accuracy on both datasets.

In addition, class orthogonalization is compatible with domain generalization algorithms when the prediction mechanism $Z_1|Y$ is invariant across collected environments.

Fig. 3 displays the transferred samples from domain A. We see that vanilla CycleGAN models change the background colors/hair colors along with digit colors/facial characteristics in MNIST-C and CelebA. In contrast, orthogonal classifiers better preserve the orthogonal aspects Z_2 in the input images. We also provide visualizations for domain B in Appendix C.

(a) MNIST-C: Domain A   (b) CelebA-GH: Domain A

Figure 3: Style transfer samples on the domain A of MNIST-C and CelebA-GH. We visualize the inputs (top row) and the corresponding transferred samples of different methods.

5 ORTHOGONAL CLASSIFIER FOR DOMAIN ADAPTATION

In unsupervised domain adaptation, we have two domains, source and target with data distribution p_s, p_t. Each sample comes with three variables, data X, task label Y and domain label U. We assume U is uniformly distributed in $\{0 \text{ (source)}, 1 \text{ (target)}\}$. The task label is only accessible in the source domain. Consider learning a model $h = g \circ f$ that is the composite of the encoder $f : \mathcal{X} \to \mathcal{Z}$ and the predictor $g : \mathcal{Z} \to \mathcal{Y}$. A common practice of domain adaptation is to match the two domain's feature distributions $p_s(f(X)), p_t(f(X))$ via domain adversarial training (Ganin & Lempitsky, 2015; Long et al., 2018; Shu et al., 2018). The encoder f is optimized to extract useful feature for the predictor while simultaneously to bridge the domain gap via the following domain adversarial objective:

$$\min_f \max_D \mathcal{L}(f, D) := \mathbb{E}_{x \sim p_s}[\log D(f(x))] + \mathbb{E}_{x \sim p_t}[\log(1 - D(f(x)))] \tag{3}$$

where discriminator $D : \mathcal{Z} \to [0,1]$ distinguishes features from two domains. The equilibrium of the objective is achieved when the encoder perfectly align the two domain, *i.e.*, $p_s(f(x)) = p_t(f(x))$. We highlight that such equilibrium is not desirable when the target domain has shifted label distribution (Azizzadenesheli et al., 2019; des Combes et al., 2020). Instead of, when the label shift appears, it is more preferred to align the conditioned feature distribution,*i.e.*, $p_s(f(x)|y) = p_t(f(x)|y), \forall y \in \mathcal{Y}$.

Now we show that our classifier orthogonalization technique can be applied to the discriminator for making it "orthogonal to" the task label. Specifically, consider the original discriminator as full classifier w_x, *i.e.*, for a given f, $w_x(x)_0 = \arg\max_D \mathcal{L}(f, D) = \frac{p_s(f(x))}{p_s(f(x))+p_t(f(x))}$. We then construct the principle classifier w_1 that discriminates the domain purely via the task label Y, *i.e.*, $w_1(x)_0 = \Pr(U = 0|Y = y(x))$. Note that here we assume the task label Y can be determined by the data X, *i.e.*, $Y = y(X)$. We focus on the case that Y is discrete thus w_1 could be directly computed via frequency count. We propose to training the encoder f with the orthogonalized discriminator $w_x \smallsetminus w_1$,

$$\min_f \mathcal{L}(f, (w_x \smallsetminus w_1)(\cdot)_0) = \mathbb{E}_{x \sim p_s}[\log(w_x \smallsetminus w_1)(x)_0] + \mathbb{E}_{x \sim p_t}[\log(1 - (w_x \smallsetminus w_1)(x)_0)] \tag{4}$$

Proposition 3. *Suppose there exists random variable $Z_2 = z_2(X)$ that orthogonal to $y(X) = Y$ w.r.t both $p_s(f(X), U)$ and $p_t(f(X), U)$. Then f achieves global optimum if and only if it aligns all label-conditioned feature distributions, i.e., $p_s(f(x)|y) = p_t(f(x)|y), \forall y \in \mathcal{Y}$.*

Note that in practice, we have no access to the target domain label prior $p_t(Y)$ and the label $y(x)$ for target domain data $x \sim p_t$. Thus we use the pseudo label $\hat{y}$ as a surrogate to construct the principle classifier, where $\hat{y}(x) = \arg\max_y h(x)_y$ is generated by our model h.

5.1 EXPERIMENTS

Models. We take a renowned domain adaptation algorithm **VADA** (Shu et al., 2018) as our baseline. VADA is based on domain adversarial training and combined with techniques of virtual adversarial training and entropy regularization. We show that utilizing orthogonal classifier can improve its robustness to label shift. We compare it with two improvements: (1) **VADA+**$w_x \smallsetminus w_1$ which is our method that plugs in the orthogonal classifier as a discriminator in VADA; (2) **VADA+IW**: We tailor the SOTA method for label shifted domain adaptation, importance-weighted domain adaptation (des Combes et al., 2020), and apply it to VADA.

Setup. We focus on visual domain adaptation and directly borrow the datasets, architectures and domain setups from Shu et al. (2018). To add label shift between domains, we control the label distribution in the two domains. For source domain, we sub-sample 70% data points from the first half of the classes and 30% from the second half. We reverse the sub-sampling ratios on the target domain. Please see Appendix E.2 for more details.

Results. Table 3 reports the test accuracy on seven domain adaptation tasks. We observe that VADA+$w_x \smallsetminus w_1$ improves over VADA across all tasks and outperforms VADA+IW on five of seven tasks. We find VADA-IW performs worse than VADA in three tasks, MNIST↔SVHN and MNIST→MNIST-M. Our hypothesis is that the domain gap is large between these datasets, hindering the estimation of importance weight. Hence, VADA-IW is unable to adapt the label shift appropriately.

Table 3: Test accuracy on visual domain adaptation benchmarks

| Source
Target | MNIST
MNIST-M | SVHN
MNIST | MNIST
SVHN | DIGITS
SVHN | SIGNS
GTSRB | CIFAR
STL | STL
CIFAR |
|---|---|---|---|---|---|---|---|
| Source-Only | 51.8 | 75.7 | 34.5 | 85.0 | 74.7 | 68.7 | 47.7 |
| VADA | 77.8 | 79.0 | 35.7 | 90.3 | 93.6 | 72.4 | 53.1 |
| VADA + IW | 71.2 | 87.1 | 34.5 | **90.7** | **95.4** | 74.0 | 53.8 |
| VADA + $w_x \smallsetminus w_1$ | **79.1** | **88.0** | **40.5** | 90.6 | 95.2 | **74.5** | **54.1** |

6 ORTHOGONAL CLASSIFIER FOR FAIRNESS

We are given a dataset $\mathcal{D} = \{(x_t, y_t, u_t)\}_{t=1}^n$ that is sampled iid from the distribution p_{XYU}, which contains the observations $x \in \mathcal{X}$, the sensitive attributes $u \in \mathcal{U}$ and the labels $y \in \mathcal{Y}$. Our goal is to learn a classifier that is accurate w.r.t y and fair w.r.t u. We frame the fairness problem as finding the orthogonal classifier of an "totally unfair" classifier w_1 that only uses the sensitive attributes u for prediction. We can directly get the unfair classifier w_1 from the dataset statistics, i.e., $w_1(x)_y = p(Y = y|U = u(x))$. Below we show that the orthogonal classifier of unfair classifier meets equalized odds, one metric that evaluates the fairness.

Proposition 4. *If the orthogonal random variable of $U = u(X)$ w.r.t p_{XY} exits, then the orthogonal classifier $w_x \smallsetminus w_1$ satisfies the criterion of equalized odds.*

We emphasize that, unlike existing algorithms for learning fairness classifier, our method does not require additional training. We obtain a fair classifier via orthogonalize a existing model w_x which is simply the vanilla model trained by ERM on the dataset $\mathcal{D}$.

6.1 EXPERIMENTS

Setup. We experiment on the UCI Adult dataset, which has gender as the sensitive attribute and the UCI German credit dataset, which has age as the sensitive attribute (Zemel et al., 2013; Madras et al., 2018; Song et al., 2019). We compare the orthogonal classifier $w_x \smallsetminus w_1$ to three baselines: **LAFTR** (Madras et al., 2018), which proposes adversarial objective functions that upper bounds the unfairness metrics, and **L-MIFR** (Song et al., 2019), which uses mutual information objectives to control the expressiveness-fairness trade-off, as well as the **Vanilla** (w_x) trained by ERM. We employs two fairness metrics – demographic parity distance (Δ_{DP}) and equalized odds distance (Δ_{EO}) – defined in Madras et al. (2018). We denote the penalty coefficient of the adversarial objective as γ, whose values govern a trade-off between prediction accuracy and fairness, in both baselines. We borrow experiment configurations, like CNN architecture, from Song et al. (2019). Please refer to Appendix E.3 for more details.

Table 4: Accuracy v.s. Fairness (Adults)

	Acc.↑	Δ_{DP} ↓	Δ_{EO} ↓
Vanilla	**84.5**	0.19	0.20
LAFTR ($\gamma = 0.1$)	84.2	0.14	0.09
LAFTR ($\gamma = 0.5$)	84.0	0.12	**0.07**
L-MIFR ($\gamma = 0.05$)	81.6	**0.04**	0.15
L-MIFR ($\gamma = 0.1$)	82.0	0.06	0.16
$w_x \smallsetminus w_1$	81.6	0.12	0.12

Table 5: Accuracy v.s. Fairness (German)

	Acc.↑	Δ_{DP} ↓	Δ_{EO} ↓
Vanilla	**76.0**	0.19	0.33
LAFTR ($\gamma = 0.1$)	73.0	0.11	**0.17**
LAFTR ($\gamma = 0.5$)	72.7	0.11	0.19
L-MIFR ($\gamma = 0.1$)	75.8	0.10	0.21
L-MIFR ($\gamma = 0.05$)	75.6	**0.08**	0.18
$w_x \smallsetminus w_1$	75.4	0.09	0.18

Results. Table 4, 5 reports the test accuracy, Δ_{DP} and Δ_{EO} on Adults and German datasets. We observe that the orthogonal classifier decreases the degree of unfairness on the Vanilla model and has competitive performances to existing baselines. Especially in the German dataset, compared to LAFTR, our method has the same Δ_{EO} but better Δ_{DP} and test accuracy. It is surprising that our method outperforms LAFTR, even though it is not specially designed for fairness. Further, our method has merit of training-free, which allow it to be applied to improve any off-the-shelf classifier's fairness without requiring additional training.

7 RELATED WORKS

Disentangled representation learning Similar to orthogonal random variables, disentangled representation learning associates a definition of independence of dimensions in the representation. Higgins et al. (2018) defines the disentangled representations based on the equivalence and independence of group transformations, Kim & Mnih (2018) relates disentanglement to distribution factorization and Shu et al. (2018) characterizes disentanglement via generator consistency and restrictiveness. There are two key differences. First, most disentanglement definitions do not take the diffeomorphism and the labels into account. In contrast, our definition requires diffeomorphism and label-conditioned independence. Further, disentanglement learning does not learn discriminative models on different latents as ours. Several works aim to learn the disentangled representations (Chen et al., 2016; Higgins et al., 2017; Chen et al., 2018). However, Locatello et al. (2019) shows that unsupervised learning of disentangled representation is impossible without inductive bias.

Model debiasing A line of works focuses on prevent model replying on the dataset biases. Bahng et al. (2020) learns the debiased representation by imposing HSIC penalty with designed biased representation, and Nam et al. (2020) trains an unbiased model by up-weighting the high loss samples in the biased model. Li et al. (2021) de-bias training data through data augmentation. However, these works lack theoretical definition for the debiased model in general cases and often require explicit dataset biases.

Density ratio estimation using classifier Using binary classifier for estimating the density ratio (Sugiyama et al., 2012) enjoys widespread attention in machine learning. The density ratio estimated by classifier has been applied to Monte Carlo inference (Grover et al., 2019; Azadi et al., 2019), class imbalance (Byrd & Lipton, 2019) and domain adaptation (Azizzadenesheli et al., 2019).

8 CONCLUSION

We consider finding a discriminative direction that is orthogonal to a principal classifier. The solution in the linear case is straightforward but cannot immediately generalize to the non-linear case. To tackle the problem, we define and investigate orthogonal random variables, which characterize the orthogonality of the data. We further propose a simple but effective algorithm (classifier orthogonalization) to construct the orthogonal classifier.

With both theoretical analysis and empirical evidence, we show that the orthogonal classifier makes accurate predictions on the orthogonal aspects of the principal classifier. Experimentally, we apply classifier orthogonalization on partial style transfer, domain adaptation and fairness. We demonstrate that the orthogonal classifier enables controlled style transfer, improves existing alignment methods for domain adaptation with label shifts, and has a lower degree of unfairness.

REFERENCES

Martín Arjovsky, L. Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *ArXiv*, abs/1907.02893, 2019.

Samaneh Azadi, Catherine Olsson, Trevor Darrell, Ian J. Goodfellow, and Augustus Odena. Discriminator rejection sampling. *ArXiv*, abs/1810.06758, 2019.

K. Azizzadenesheli, Anqi Liu, Fanny Yang, and Anima Anandkumar. Regularized learning for domain adaptation under label shifts. *ArXiv*, abs/1903.09734, 2019.

Hyojin Bahng, Sanghyuk Chun, Sangdoo Yun, Jaegul Choo, and Seong Joon Oh. Learning de-biased representations with biased representations. In *ICML*, 2020.

Peter L. Bartlett and Shahar Mendelson. Rademacher and gaussian complexities: Risk bounds and structural results. *J. Mach. Learn. Res.*, 3:463–482, 2001.

M. Berger, Bernard Gostiaux, and S. Levy. Differential geometry: Manifolds, curves, and surfaces. 1987.

G. Blanchard, Gyemin Lee, and C. Scott. Generalizing from several related classification tasks to a new unlabeled sample. In *NIPS*, 2011.

Jonathon Byrd and Zachary Chase Lipton. What is the effect of importance weighting in deep learning? In *ICML*, 2019.

Tian Qi Chen, Xuechen Li, Roger B. Grosse, and David Kristjanson Duvenaud. Isolating sources of disentanglement in variational autoencoders. In *NeurIPS*, 2018.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and P. Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *NIPS*, 2016.

Rémi Tachet des Combes, Han Zhao, Yu-Xiang Wang, and Geoffrey J. Gordon. Domain adaptation with conditional distribution matching and generalized label shift. *ArXiv*, abs/2003.04475, 2020.

Yaroslav Ganin and V. Lempitsky. Unsupervised domain adaptation by backpropagation. *ArXiv*, abs/1409.7495, 2015.

Wei Gao and Zhi-Hua Zhou. Dropout rademacher complexity of deep neural networks. *Science China Information Sciences*, 59(7):072104, 2016.

Aditya Grover, Jiaming Song, Alekh Agarwal, Kenneth Tran, Ashish Kapoor, E. Horvitz, and S. Ermon. Bias correction of learned generative models using likelihood-free importance weighting. In *DGS@ICLR*, 2019.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and S. Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *NIPS*, 2017.

Irina Higgins, Loïc Matthey, Arka Pal, Christopher P. Burgess, Xavier Glorot, Matthew M. Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *ICLR*, 2017.

Irina Higgins, David Amos, David Pfau, Sébastien Racanière, Loïc Matthey, Danilo Jimenez Rezende, and Alexander Lerchner. Towards a definition of disentangled representations. *ArXiv*, abs/1812.02230, 2018.

Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *ICML*, 2018.

Y. LeCun and Corinna Cortes. The mnist database of handwritten digits. 2005.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M. Hospedales. Learning to generalize: Meta-learning for domain generalization. *ArXiv*, abs/1710.03463, 2018.

Yingwei Li, Qihang Yu, Mingxing Tan, Jieru Mei, Peng Tang, Wei Shen, Alan Loddon Yuille, and Cihang Xie. Shape-texture debiased neural network training. *ArXiv*, abs/2010.05981, 2021.

Z. Liu, Ping Luo, Xiaogang Wang, and X. Tang. Deep learning face attributes in the wild. *2015 IEEE International Conference on Computer Vision (ICCV)*, pp. 3730–3738, 2015.

Francesco Locatello, Stefan Bauer, Mario Lucic, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. *ArXiv*, abs/1811.12359, 2019.

Mingsheng Long, Zhangjie Cao, Jianmin Wang, and Michael I. Jordan. Conditional adversarial domain adaptation. In *NeurIPS*, 2018.

David Madras, Elliot Creager, T. Pitassi, and R. Zemel. Learning adversarially fair and transferable representations. In *ICML*, 2018.

Jun Hyun Nam, Hyuntak Cha, Sungsoo Ahn, Jaeho Lee, and Jinwoo Shin. Learning from failure: Training debiased classifier from biased classifier. *ArXiv*, abs/2007.02561, 2020.

Yuge Shi, Jeffrey S. Seely, Philip H. S. Torr, N. Siddharth, Awni Y. Hannun, Nicolas Usunier, and Gabriel Synnaeve. Gradient matching for domain generalization. *ArXiv*, abs/2104.09937, 2021.

Rui Shu, H. Bui, H. Narui, and S. Ermon. A dirt-t approach to unsupervised domain adaptation. *ArXiv*, abs/1802.08735, 2018.

Jiaming Song, Pratyusha Kalluri, Aditya Grover, Shengjia Zhao, and S. Ermon. Learning controllable fair representations. In *AISTATS*, 2019.

Masashi Sugiyama, Taiji Suzuki, and T. Kanamori. Density ratio estimation in machine learning. 2012.

Chong Wang, X. Chen, Alex Smola, and E. Xing. Variance reduction for stochastic gradient optimization. In *NIPS*, 2013.

R. Zemel, Ledell Yu Wu, Kevin Swersky, T. Pitassi, and C. Dwork. Learning fair representations. In *ICML*, 2013.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A. Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. *2017 IEEE International Conference on Computer Vision (ICCV)*, pp. 2242–2251, 2017.

A   More properties of orthogonal random variable

In this section we demonstrate the properties of orthogonal random variables. We also discuss the existence and uniqueness of orthogonal classifier when given the principal classifier. Below we list some useful properties of orthogonal random variables.

Proposition 5. *Let Z_1 and Z_2 be any mutually orthogonal w.r.t P_{XY}, then we have*

(i) **Invariance**: *For any diffeomorphism g, $g(Z_1)$ and $g(Z_2)$ are also mutually orthogonal.*

(ii) **Distribution-free**: *Z_1, Z_2 are mutually orthogonal w.r.t $P_{X'Y}$ if and only if there exists a diffeomorphism mapping between X and X'.*

(iii) **Existence**: *Suppose the label-conditioned distributions $p_y \in \mathcal{C}^1, supp(p_y) = \mathcal{X}, \forall y \in \mathcal{Y}$. For $z_1 \in \mathcal{C}^1$ and $z_1(\mathcal{X})$ is diffeomorphism to Euclidean space, then $\forall i \in \mathcal{Y}$, there exists a diffeomorphism mapping $(z_1(X), z_{2,i}(X))$ such that $z_1(X) \perp\!\!\!\perp z_{2,i}(X)|Y = i$. Further if there exists diffeomorphism mappings between $z_{2,i}s$, then the orthogonal r.v. of $z_1(X)$ exists.*

In the following theorem, we justify the validity of the classifier orthogonalization when $z_1(x)$ satisfies some regularity conditions.

Theorem 2. *Suppose $w_1(x)_i = p(Y = i|z_1(x))$. If the label-condition distributions $p_y s$, and z_1 satisfy the conditions in Proposition 5.(iii), then $w_x \smallsetminus w_1$ is the unique orthogonal classifier of w_1.*

Note that our construction of $w_x \smallsetminus w_1$ does not require the exact expression of $z_1(X)$, its orthogonal r.v or data generation process. The theorem states that the orthogonal classifier constructed by classifier orthogonalization is the Bayesian classifier for any orthogonal random variables of $z_1(X)$.

B   Proofs

B.1   Proof for Proposition 1

Proposition 1. *Suppose the orthogonal r.v. of $z_1(X)$ w.r.t p_{XY} exists and is denoted as $z_2(X)$. Then $z(X) = z_2(X)$ is a maximizer of $I(z(X), Y|z_1(X))$ subject to $I(z(X); z_1(X)|Y) = 0$.*

Proof. For any function z, by chain rule we have $I(z_1(X), z_2(X); Y) = I(z_1(X); Y) + I(z_2(X); Y|z_1(X))$ and $I(z_1(X), z(X); Y) = I(z_1(X); Y) + I(z(X); Y|z_1(X))$. Further, since there exists a differmorphism f between $z_1(X), z_2(X)$, $I(z_1(X), z(f(z_1(X), z_2(X))); Y) = I(z_1(X), z(X); Y)$.

Hence by data processing inequality we have:

$$I(z_1(X), z_2(X); Y) \geq I(z_1(X), z(f(z_1(X), z_2(X))); Y)$$
$$\Leftrightarrow I(z_1(X); Y) + I(z_2(X); Y|z_1(X)) \geq I(z_1(X); Y) + I(z(X); Y|z_1(X))$$
$$\Leftrightarrow I(z_2(X); Y|z_1(X)) \geq I(z(X); Y|z_1(X))$$

Apparently the equality holds when $z = z_2$. Further, z_2 meets the constraints $z_2(X) \perp\!\!\!\perp z(X)|Y$ hence $I(z(X); z_1(X)|Y)$. Note that if $z_1(X) \perp\!\!\!\perp z(X), z_2(X)$, the maximizers in the problem must be the orthogonal random variable of $z_1(X)$. $\square$

B.2   Proof for Theorem 1

Theorem 1. *Assume $\forall w_x \in \mathcal{W}$ takes values in $(m, 1 - m)^C$ with $m \in (0, \frac{1}{2})$, and $p_{X|Y}(x|i)/p_{X|Y}(x|j) \in (a, b) \subset (0, +\infty)$ holds for $\forall x \in \mathcal{X}, i, j \in \mathcal{Y}$. Denote $\gamma = \max(\frac{1}{a}, b)$, then for any $\delta \in (0, 1)$ with probability at least $1 - \delta$, we have:*

$$|R(\hat{w}_x \smallsetminus w_1) - R(w_x^* \smallsetminus w_1)| \leq 2(2 + \gamma)\mathfrak{R}_{|\mathcal{D}|}(\mathcal{W}) + 2\log\frac{1}{m}\sqrt{\frac{2\log\frac{1}{\delta}}{|\mathcal{D}|}}$$

Proof. Denote the empirical risk of w as

$$\hat{R}(w) = \hat{R}(w) = -\frac{1}{|\mathcal{D}|}\sum_{(x_i, y_i) \in \mathcal{D}} \log w(x_i)_{y_i}$$

and the population risk as

$$R(w) = -\mathbb{E}_{p(x,y)}\left[\log w(x)_y\right]$$

Step 1: bounding $|R(\hat{w}_x) - R(w_x^*)|$.

By the classical result in theorem 8 in Bartlett & Mendelson (2001), we know that for any $w \in \mathcal{W}$, $\delta \in (0,1)$, since $-\log w(x)_y \in (0, \log \frac{1}{m})$, with probability at least $1 - \delta$,

$$|\hat{R}(w) - R(w)| = |\frac{1}{n}\sum_{i=1}^{n}\log(w(x_i))_{y_i} - \mathbb{E}_p[\log(w(x)_y)]| \le 2\mathfrak{R}_n(\mathcal{W}) + 2\log\frac{1}{m}\sqrt{\frac{2\log\frac{1}{\delta}}{n}}$$

Since $\hat{w}_x = \inf_{w_x \in \mathcal{W}}\hat{R}(w_x), w_x^* = \inf_{w_x \in \mathcal{W}}R(w_x)$, and $|\hat{R}(\hat{w}_x) - R(\hat{w}_x)| \le 2\mathfrak{R}_n(\mathcal{W}) + 2\log\frac{1}{m}\sqrt{\frac{2\log\frac{2}{\delta}}{n}}, |\hat{R}(w_x^*) - R(w_x^*)| \le 2\mathfrak{R}_n(\mathcal{W}) + 2\log\frac{1}{m}\sqrt{\frac{2\log\frac{2}{\delta}}{n}}$, we have

$$|R(\hat{w}_x) - R(w_x^*)| \le 2\mathfrak{R}_n(\mathcal{W}) + 2\log\frac{1}{m}\sqrt{\frac{2\log\frac{1}{\delta}}{n}} \tag{5}$$

Step 2: bounding $|R(\hat{w}_x \smallsetminus w_1) - R(w_x^* \smallsetminus w_1)|$ by $|R(\hat{w}_x) - R(w_x^*)|$

$$R(w \smallsetminus w_1) = -\mathbb{E}_{p(x,y)}\left[\log\frac{\frac{w(x)_y}{w_1(x)_y}}{\sum_{y'}\frac{w(x)_{y'}}{w_1(x)_{y'}}}\right] = R(w) + \mathbb{E}_{p(x,y)}\left[\log w_1(x)_y\sum_{y'}\frac{w(x)_{y'}}{w_1(x)_{y'}}\right]$$

Then we have:

$$|R(\hat{w}_x \smallsetminus w_1) - R(w_x^* \smallsetminus w_1)|$$

$$\le |R(\hat{w}_x) - R(w_x^*)| + \left|\mathbb{E}_{p(x,y)}\left[\log w_1(x)_y\sum_{y'}\frac{\hat{w}_x(x)_{y'}}{w_1(x)_{y'}}\right] - \mathbb{E}_{p(x,y)}\left[\log w_1(x)_y\sum_{y'}\frac{w_x^*(x)_{y'}}{w_1(x)_{y'}}\right]\right|$$

$$= |R(\hat{w}_x) - R(w_x^*)| + \left|\mathbb{E}_{p(x,y)}\left[\log\frac{\sum_{y'}\frac{\hat{w}_x(x)_{y'}}{w_1(x)_{y'}}}{\sum_{y'}\frac{w_x^*(x)_{y'}}{w_1(x)_{y'}}}\right]\right|$$

$$\le |R(\hat{w}_x) - R(w_x^*)| + \left|\mathbb{E}_{p(x,y)}\left[\log\max_{y'}\frac{\frac{\hat{w}_x(x)_{y'}}{w_1(x)_{y'}}}{\frac{w_x^*(x)_{y'}}{w_1(x)_{y'}}}\right]\right|$$

$$= |R(\hat{w}_x) - R(w_x^*)| + \mathbb{E}_{\tilde{p}(x,y)}\left[\frac{p(x,y)}{\tilde{p}(x,y)}\log\max_{y'}\frac{\hat{w}_x(x)_{y'}}{w_x^*(x)_{y'}}\right]$$

$$= |R(\hat{w}_x) - R(w_x^*)| + \int_{\arg\max_{y'}\frac{\hat{w}_x(x)_{y'}}{w_x^*(x)_{y'}}=y}p(x,y)\log\frac{\hat{w}_x(x)_y}{w_x^*(x)_y}dxdy + \int_{\arg\max_{y'}\frac{\hat{w}_x(x)_{y'}}{w_x^*(x)_{y'}}\ne y}p(x,y)\log\max_{y'}\frac{\hat{w}_x(x)_{y'}}{w_x^*(x)_{y'}}dxdy$$

$$\le 2|R(\hat{w}_x) - R(w_x^*)| + \int_{\arg\max_{y'}\frac{\hat{w}_x(x)_{y'}}{w_x^*(x)_{y'}}\ne y}p(x,y')\frac{p_y(x)}{p_{y'}(x)}\log\max_{y'}\frac{\hat{w}_x(x)_{y'}}{w_x^*(x)_{y'}}dxdy$$

$$\le 2|R(\hat{w}_x) - R(w_x^*)| + \gamma\int p(x,y)\log\frac{\hat{w}_x(x)_y}{w_x^*(x)_y}dxdy$$

$$\le (2+\gamma)|R(\hat{w}_x) - R(w_x^*)| \tag{6}$$

Combining Eq. (5) and Eq. (6), we know that with probability $1 - \delta$, we have:

$$|R(\hat{w}_x \smallsetminus w_1) - R(w_x^* \smallsetminus w_1)| \le 2(2+\gamma)\mathfrak{R}_n(\mathcal{W}) + 2\log\frac{1}{m}\sqrt{\frac{2\log\frac{1}{\delta}}{n}}$$

We arrive at the results. $\qquad\square$

B.3 PROOF FOR PROPOSITION 5 AND THEOREM 2

Proposition 5. *Let Z_1 and Z_2 be any mutually orthogonal w.r.t P_{XY}, then we have*

(i) **Invariance**: *For any diffeomorphism g, $g(Z_1)$ and $g(Z_2)$ are also mutually orthogonal.*

(ii) **Distribution-free**: *Z_1, Z_2 are mutually orthogonal w.r.t $P_{X'Y}$ if and only if there exists a diffeomorphism mapping between X and X'.*

(iii) **Existence**: *Suppose the label-conditioned distributions $p_y \in \mathcal{C}^1, supp(p_y) = \mathcal{X}, \forall y \in \mathcal{Y}$. For $z_1 \in \mathcal{C}^1$ and $z_1(\mathcal{X})$ is diffeomorphism to Euclidean space, then $\forall i \in \mathcal{Y}$, there exists a diffeomorphism mapping $(z_1(X), z_{2,i}(X))$ such that $z_1(X) \perp\!\!\!\perp z_{2,i}(X)|Y = i$. Further if there exists diffeomorphism mappings between $z_{2,i}s$, then the orthogonal r.v. of $z_1(X)$ exists.*

Proof. (i) Since Z_1 and Z_2 are independent, the independence also holds for $g(Z_1)$ and $g(Z_2)$. In addition, we construct the diffeomorphism between $(g(Z_1), g(Z_2))$ and X as $\hat{f}(g(Z_1), g(Z_2)) = f(g^{-1}(g(Z_1)), g^{-1}(g(Z_2))) = X$. Apparently $f(g^{-1}(Z_1), g^{-1}(Z_2))$ is a diffeomorphism.

(ii) We denote the diffeomorphism between X' and X as $\hat{f}$. Then the diffeomorphism mapping between (Z_1, Z_2) and X is $\hat{f} \circ f$. Thus Z_1, Z_2 are mutually orthogonal w.r.t X'.

(iii) We will use a constructive proof.

Step 1: Denote $\dim(\mathcal{X}) = d, \dim(z_1(\mathcal{X})) = k$, then we can prove that the manifold $[z_1(\mathcal{X}), \mathbb{R}^{d-k}]$ is diffeomorphism of $\mathcal{X}$. We denote the diffeomorphism as f, and denote $f(x) = [z_1(x), t(x)]$ where $z_1 : \mathcal{X} \to z_1(\mathcal{X}), t : \mathcal{X} \to \mathbb{R}^{d-k}$.

Step 2: For $X|Y = y$, let $F_j(t(x)_j \mid t(x)_1, \cdots, t(x)_{j-1}, z_1(x), 1) : \mathbb{R} \to [0,1], j \in \{1, \ldots, d - k\}$ be the CDF corresponding to the distribution of $t(x)_j \mid t(X)_1 = t(x)_1, \cdots, t(X)_{j-1} = t(x)_{j-1}, z_1(X) = z_1(x), Y = y$.

$$h(t(x); z_1(x))_1 = F_1(t(x)_1 \mid z_1(x), y)$$
$$h(t(x); z_1(x))_i = F_i(t(x)_i \mid t(x)_1, \cdots, t(x)_{i-1}, z_1(x), 1), i \in \{2, \ldots, d\}$$

The conditions $p \in C^1, p(x) > 0, \forall x \in \mathcal{X}$ ensure that the PDF of $f(X)$ is also in $\mathcal{C}^1$ and takes values in $(0, \infty)$. Thus the above CDFs are all diffeomorphism mapping. By the inverse CDF theorem, for any $z_1(x), h(t(X); z_1(X) = z_1(x))$ is a uniform distribution in $(0,1)^{d-k}$. Hence the random variable defined by the mapping h, *i.e.*, $z_{2,y}(X) = h(t(X); z_1(X))$, is independent of $z_1(X)$ given $Y = 1$.

In addition, by the construction of $z_{2,y}(x)$ we know that there exists a diffeomorphism $\hat{f}$ between $(z_1(\mathcal{X}), t(\mathcal{X}))$ and $(z_1(\mathcal{X}), z_{2,y}(\mathcal{X}))$ such that $\hat{f}(z_1(X), t(X)) = (z_1(X), z_{2,y}(X))$. Then $f^{-1} \circ \hat{f}^{-1}(z_1(X), z_{2,y}(X)) = X$ is also a diffeomorphsim mapping.

Step 3: From the condition we know that for every $y \in \mathcal{Y}$, there exists a diffeomorphism function m_y such that $m_y \circ z_{2,y}(x) = z_{2,1}(x)$. Apparently $\forall y, m_y \circ z_{2,y}(X) \perp\!\!\!\perp z_{2,1}(X)|Y = y$ by $z_{2,y}(X) \perp\!\!\!\perp z_1(X)|Y = y$. Further, $(z_1, z_{2,1})$ is a diffeomorphism. Hence $z_{2,1}(X)$ is the orthogonal r.v. of $z_1(X)$ w.r.t P_{XY}.

$\square$

Theorem 2. *Suppose $w_1(x)_i = p(Y = i|z_1(x))$. If the label-condition distributions $p_y s$, and z_1 satisfy the conditions in Proposition 5.(iii), then $w_x \smallsetminus w_1$ is the unique orthogonal classifier of w_1.*

Proof. By the existence property in Proposition 5, we know that for X, there exists a orthogonal r.v. of $z_1(X)$ and denote it as $z_2(X_1)$. By the proposition we know that there exists a common diffeomorphism f mapping $(z_1(X|y), z_2(X|y))$ to $X|y, \forall y \in \mathcal{Y}$.

Further, by change of variables and the definition of orthogonal r.v., we have $\frac{p_{i,2}(z_2)}{p_{j,2}(z_2)} = \frac{p_{i,1}(z_1)p_{i,2}(z_2)\text{vol}J_f(z_1,z_2)}{p_{j,1}(z_1)p_{j,2}(z_2)\text{vol}J_f(z_1,z_2)} / \frac{p_{i,1}(z_1)}{p_{j,1}(z_1)} = \frac{p_i(x)}{p_j(x)} / \frac{p_{i,1}(z_1)}{p_{j,1}(z_1)} = \frac{w_x(x)_i}{w_x(x)_j} / \frac{w_1(x)_i}{w_1(x)_j}$. Thus via the bijection of classifier and density ratios we know that $w_x \smallsetminus w_1(x)_i = p(Y = i|z_2(x))$. $\square$

B.4 PROOF FOR PROPOSITION 2

Proposition 2. *The global minimum of $\mathcal{L}_{\text{OGAN}}^{AB}(G_{AB})$ is achieved if and only if $\widetilde{P}_{Z_1,Z_2}(z_1,z_2) = Q_{Z_1}(z_1)P_{Z_2}(z_2)$.*

Proof. By definition, $r(x) = \frac{w_2(x)}{1-w_2(x)} = \frac{P(z_2(x))}{Q(z_2(x))}$. Thus we can reformulate the criterion $\mathcal{L}_{\text{OGAN}}^{AB}$ as the following, :

$$\mathcal{L}_{\text{OGAN}}^{AB}(G_{AB}) = \mathbb{E}_{x \sim \widetilde{P}} \log \frac{\widetilde{P}(x)}{\widetilde{P}(x) + Q(x)r(x)}$$

$$= \mathbb{E}_{z_1,z_2 \sim \widetilde{P}} \log \frac{\widetilde{P}(z_1,z_2)}{\widetilde{P}(z_1,z_2) + Q(z_1)Q(z_2)\frac{P(z_2)}{Q(z_2)}}$$

$$\geq -\log \mathbb{E}_{z_1,z_2 \sim \widetilde{P}} \Big[\frac{\widetilde{P}(z_1,z_2) + Q(z_1)P(z_2)}{\widetilde{P}(z_1,z_2)} \Big] = -\log 2$$

where we get the lower bound by Jensen's inequality. The equality holds when $\widetilde{P}(z_1,z_2) = Q(z_1)P(z_2)$. $\qquad\square$

B.5 PROOF FOR PROPOSITION 3

Proposition 3. *Suppose there exists random variable $Z_2 = z_2(X)$ that orthogonal to $y(X) = Y$ w.r.t both $p_s(f(X),U)$ and $p_t(f(X),U)$. Then f achieves global optimum if and only if it aligns all label-conditioned feature distributions, i.e., $p_s(f(x)|y) = p_t(f(x)|y), \forall y \in \mathcal{Y}$.*

Proof. By definition, optimal classifier $w_x(x)_0 = \frac{p_s(f(x))}{p_s(f(x))+p_t(f(x))}$, principle classifier $w_1(x)_0 = \frac{p_s(y(x))}{p_s(y(x))+p_t(y(x))}$. By the definition of orthogonal r.v., Y, Z_2 and $f(X)$ have a bijection between them. It suggests, conditioned on Y, the supports of $f(X)|Y = y$ is non-overlapped for different y in both domains p_s and p_t. It means if $p_s(f(x)|y) > 0$ then $\forall y' \neq y$, $p_s(f(x)|y') = 0$.

Thus the orthogonal classifier $w_x \smallsetminus w_1$ satisfies:

$$(w_x \smallsetminus w_1)(x)_0 = \frac{p_s(f(x))}{p_s(y(x))} \Big/ \Big(\frac{p_s(f(x))}{p_s(y(x))} + \frac{p_t(f(x))}{p_t(y(x))} \Big)$$

$$= \frac{\sum_{y'} p_s(f(x)|y')p_s(y')}{p_s(y(x))} \Big/ \Big(\frac{\sum_{y'} p_s(f(x)|y')p_s(y')}{p_s(y(x))} + \frac{\sum_{y'} p_t(f(x)|y')p_t(y')}{p_t(y(x))} \Big)$$

$$= \frac{p_s(f(x)|y(x))p_s(y(x))}{p_s(y(x))} \Big/ \Big(\frac{p_s(f(x)|y(x))p_s(y(x))}{p_s(y(x))} + \frac{p_t(f(x)|y(x))p_t(y(x))}{p_t(y(x))} \Big)$$

$$= \frac{p_s(f(x)|y(x))}{p_s(f(x)|y(x)) + p_t(f(x)|y(x))}$$

Thus the objective in Eq. (4) can be reformulated as,

$$\mathcal{L}(f, (w_x \smallsetminus w_1)(\cdot)_0)$$

$$= \mathbb{E}_{x \sim p_s} \Big[\log \frac{p_s(f(x)|y(x))}{p_s(f(x)|y(x)) + p_t(f(x)|y(x))} \Big] + \mathbb{E}_{x \sim p_t} \Big[\log \frac{p_t(f(x)|y(x))}{p_s(f(x)|y(x)) + p_t(f(x)|y(x))} \Big]$$

$$= \mathbb{E}_{y \sim p_s} \mathbb{E}_{x \sim p_s(x|y)} \Big[-\log \frac{p_s(f(x)|y) + p_t(f(x)|y)}{p_s(f(x)|y)} \Big] + \mathbb{E}_{y \sim p_t} \mathbb{E}_{x \sim p_t(x|y)} \Big[-\log \frac{p_s(f(x)|y) + p_t(f(x)|y)}{p_t(f(x)|y)} \Big]$$

$$\geq -\mathbb{E}_{y \sim p_s} \Big[\log \mathbb{E}_{x \sim p_s(x|y)} \Big[\frac{p_s(f(x)|y) + p_t(f(x)|y)}{p_s(f(x)|y)} \Big] \Big] - \mathbb{E}_{y \sim p_t} \Big[\log \mathbb{E}_{x \sim p_t(x|y)} \Big[\frac{p_s(f(x)|y) + p_t(f(x)|y)}{p_t(f(x)|y)} \Big] \Big]$$

$$= -2\log 2.$$

The lower-bound holds due to Jensen's inequality. The equality is achieved if and only if $\frac{p_s(f(x)|y)}{p_t(f(x)|y)}$ is invariant to x, for all y.

□

B.6 PROOF FOR PROPOSITION 4

Proposition 4. *If the orthogonal random variable of $U = u(X)$ w.r.t p_{XY} exits, then the orthogonal classifier $w_x \smallsetminus w_1$ satisfies the criterion of equalized odds.*

Proof. We denote the orthogonal random variables as $z_2(X)$, and $w_x \smallsetminus w_1(x) = \Pr[y|z_2(x)]$. Since $z_2(X) \perp\!\!\!\perp U|Y$, we know that $w_x \smallsetminus w_1(X) \perp\!\!\!\perp U|Y$. Hence the prediction of the classifier $w_x \smallsetminus w_1$ is conditional independent of sensitive attribute U on the ground-truth label Y, which meets the equalized odds metric. □

C EXTRA SAMPLES

(a) MNIST-C: Domain A

(b) MNIST-C: Domain B

(c) CelebA-GH: Domain A

(d) CelebA-GH: Domain B

Figure 4: MNIST-C and CelebA-GH

D EXTRA EXPERIMENTS

D.1 STYLE TRANSFER

Table 6: CelebA

	Z_1 acc.	Z_2 acc.	FID ↓
Vanilla	75.3	87.0	36.2
$w_x \smallsetminus w_1$-MLDG	81.8	93.5	35.2
$w_x \smallsetminus w_1$-Fish	74.2	93.3	33.1
IS-Oracle	73.3	88.1	36.5
$w_x \smallsetminus w_1$-Oracle	**84.0**	**95.2**	38.5

We show transferred samples for both domains in Fig. 4 on MNIST-C and CelebA-GH.

Unlike the split in CelebA-GH dataset, domain A is males, and domain B is females. The two domains together form the full CelebA (Liu et al., 2015) with 202599 images. Note that there exists large imbalance of hair colors within the male group, with only around 2% males have blond hair. Table 6 reports the Z_1 / Z_2 accuracies and FID scores on the full CelebA datasets. We find that our method improves the style transfer on the original CelebA

dataset, especially the Z_2 accuracy. It shows that our method can help style transfer in real-world datasets with multiple varying factors.

E   EXTRA EXPERIMENT DETAILS

E.1   STYLE TRANSFER

E.1.1   DATASET DETAILS

We randomly sampled two digits colors and two background colors for MNIST-C. For CelebA-GH, we extract two subsets—male with non-blond hair and female with blond hair—by the attributes provided in CelebA dataset. For all datasets, we use 0.8/0.2 proportions to split the train/test set.

For CelebA dataset, follow the implementation of Zhu et al. (2017) (`https://github.com/junyanz/CycleGAN`), we use 128-layer UNet as the generator and the discriminator in PatchGAN. For MNIST-C dataset, we use a 6-layer CNN as the generator and a 5-layer CNN as the discriminator. We adopt Adam with learning rate 2e-4 as the optimizer and batch size 128/32 for MNIST-C/CelebA.

E.1.2   DETAILS OF MODELS

We craft datasets for training the oracle $w_1(x) = \Pr(Y|z_1(x))$. For MNIST-C, oracle dataset has bias degrees 0.9/0. For CelebA-GH, oracle dataset has {male, female} as classes and the hair colors under each class are balanced.

For each dataset, we construct two environments to train the domain generalization models. For MNIST-C, the two environments are datasets with bias degrees 0.9/0.5 and 0.9/0.8. For CelebA-GH, the two environments consist of different groups of equal size: one is {non-blond-haired males, blond-haired females} and the other is {non-blond-haired males, blond-haired females, non-blond-haired females, blond-haired males}. Note that the facial characteristic of gender (Z_1) is the invariant prediction mechanism across environments, instead of the hair color.

E.1.3   EVALUATION FOR Z_1/Z_2 ACCURACY

To evaluate the accuracies on Z_1, Z_2 latents, we train two oracle classifiers $w_1^*(x) = \Pr(Y|z_1(x))$, $w_2^*(x) = \Pr(Y|z_2(x))$ on two designed datasets. Specifically, w_1/w_2 are trained on datasets $\mathcal{D}_1/\mathcal{D}_2$ with Z_1/Z_2 as the only discriminative direction. For MNIST-C, $\mathcal{D}_1$ is the dataset with bias degrees 0.9/0 and $\mathcal{D}_2$ is the dataset with bias degrees 0/0.8. For CelebA-GH, $\mathcal{D}_1$ is the dataset with {male, female} as classes and the hair colors under each class are balanced. $\mathcal{D}_2$ is the dataset with {blond hair, non-blond hair} as classes and the males/females under each class are balanced.

The Z_1 accuracy on dataset $\mathcal{D}$ for transfer model G is:

$$Z_1 \text{ accuracy} = \frac{1}{|\mathcal{D}|} \sum_{x \in \mathcal{D}} \mathbb{I}\left(\arg\max_y w_1^*(x) \neq \arg\max_y w_1^*(G(x)) \right)$$

And Z_2 accuracy is:

$$Z_1 \text{ accuracy} = \frac{1}{|\mathcal{D}|} \sum_{x \in \mathcal{D}} \mathbb{I}\left(\arg\max_y w_2^*(x) = \arg\max_y w_2^*(G(x)) \right)$$

where $\mathbb{I}$ is the indicator function. Z_1 accuracy measures the success rate of transferring the Z_1 and Z_2 accuracy measures the success rate of keeping Z_2 aspects unchanged.

E.2   DOMAIN ADAPTATION

The full names for the seven datasets are MNIST, MNIST-M, SVHN, GTSRB, SYN-DIGITS (DIGITS), SYN-SIGNS (SIGNS), CIFAR-10 (CIFAR) and STL-10 (STL). We sub-sample each dataset by the designated imbalance ratio to construct the pairs.

We use the 18-layer neural network in Shu et al. (2018) with pre-process via instance-normalization. Following Shu et al. (2018), Smaller CNN is used for digits (MNIST, MNIST-M, SVHN, DIGITS) and traffic signs (SIGNS, GTSRB) and larger CNN is used for CIFAR-10 and STL-10. We use the Adam optimizer and hyper-parameters in Appendix B in Shu et al.

(2018) except for MNIST → MNIST-M, where we find that setting $\lambda_s = 1, \lambda_d = 1e - 1$ largely improves the VADA performance over label shifts. Furthermore, we set $\lambda_d = 1e - 2$, *i.e.*, the default value suggested by Shu et al. (2018), to enable adversarial feature alignment.

E.3 FAIRNESS

The two datasets are: the UCI Adult dataset[1] which has gender as the sensitive attribute; the UCI German credit dataset[2] which has age as the sensitive attribute. We borrow the encoder, decoder and the final fc layer from Song et al. (2019). For fair comparison, we use the same encoder+fc layer as the function family $\mathcal{W}$ of our classifier since our method do not need decoder for reconstruction. We use Adam with learning rate 1e-3 as the optimizer, and a batch size of 64.

---

[1]https://archive.ics.uci.edu/ml/datasets/adult
[2]https://archive.ics.uci.edu/ml/datasets/Statlog+%28German+Credit+Data%29