Inherently Explainable Reinforcement Learning in Natural Language

Abstract

We focus on the task of creating a reinforcement learning agent that is inherently explainable—with the ability to produce immediate local explanations by thinking out loud while performing a task and analyzing entire trajectories post-hoc to produce temporally extended explanations. This Hierarchically Explainable Reinforcement Learning agent (HEX-RL), operates in Interactive Fictions, text-based game environments in which an agent perceives and acts upon the world using textual natural language. These games are usually structured as puzzles or quests with long-term dependencies in which an agent must complete a sequence of actions to succeed—providing ideal environments in which to test an agent's ability to explain its actions. Our agent is designed to treat explainability as a first-class citizen, using an extracted symbolic knowledge graph-based (KG) state representation coupled with a Hierarchical Graph Attention mechanism that points to the facts in the internal graph representation that most influenced the choice of actions. Experiments show that this agent provides significantly improved explanations over strong baselines, as rated by human participants generally unfamiliar with the environment, while also matching state-of-the-art task performance.

1 Introduction

Explainable AI refers to artificial intelligence methods and techniques that provide human-understandable insights into how and why an AI system chooses actions or makes predictions. Such explanations are critical for ensuring reliability and improving trustworthiness by increasing user understanding of the underlying model. In this work we specifically focus on creating deep reinforcement learning (RL) agents that can explain their actions in sequential decision making environments through natural language.

In contrast to the majority of contemporary work in the area which focuses on supervised machine learning problems which require singular instance level *local explanations* You et al. (2016); Xu et al. (2015); Wang et al. (2017); Wiegreffe and Marasovic (2021), such environments—in which agents need to reason causally about actions over a long series

Figure 1: Excerpt from *zork1* with *immediate step-by-step explanations* constructed from the KG represented by ⚡ and *temporally extended explanations* by ⊞ . Colors represent different categories of KG facts seen in Fig. 2.

of steps—require an agent to take into account both environmentally grounded context as well as goals when producing explanations. Agents implicitly contain beliefs regarding the down-stream effects—the changes to the world—that actions taken at the current timestep will have. This requires explanations in these environments to contain an additional *temporally extended* component taking the full trajectory's context into account—complementary to the *immediate* step-by-step explanations.

Interactive Fiction (IF) games (Fig. 1) are partially observable environments where an agent perceives and acts upon a world using potentially incomplete textual natural language descriptions. They are structured as long puzzles and quests that require agents to reason about thousands of locations, characters, and objects over hundreds of steps, creating chains of dependencies that an agent must fulfill to complete the overall task. They provide ideal experimental test-beds for creating agents that can both reason in text and explain it.

We introduce an approach to game playing agents—**Hierarchically Explainable Reinforcement Learning (HEX-RL)**—that is designed to be *inherently* explainable, in the sense that its internal state representation—i.e. belief state about the world—takes the form of a symbolic, human-interpretable knowledge graph (KG) that is built as the agent explores the world. The graph is encoded by a Graph Attention network (GAT) (Veličković et al., 2017) *extended* to contain a hierarchical graph attention mechanism that focuses on different sub-graphs in the overall KG representation. Each of these sub-graphs contains different information such as attributes of objects, objects the player has, objects in the room, current location, etc. Using these encoding networks in conjunction with the underlying world KG, the agent is able to create *immediate explanations* akin to a running commentary that points to the facts within this knowledge graph that most influence its current choice of actions when attempting to achieve the tasks in the game on a step-by-step basis.

While graph attention can tell us which elements in the KG are attended to when maximizing expected reward from the current state, it cannot explain the intermediate, unrewarded dependencies that need to be satisfied to meet the long term task goals. For example, in the game *zork1,* the agent needs to pick up a lamp early on in the game—an unrewarded action—but the lamp is only used much later on to progress through a location without light. Thus, our agent additionally analyzes an overall episode trajectory—a sequence of knowledge graph states and actions from when the agent first starts in a world to either task completion or agent death—to find the intermediate set of states that are most important for completing the overall task. This information is used to generate a *temporally extended explanation* that condenses the *immediate step-by-step explanations* to only the most important steps required to fulfill dependencies for the task.

Our contributions are as twofold: (1) we create an inherently explainable agent that uses an ever-updating knowledge-graph based state representation to generate step-by-step immediate explanations for executed actions as well as performing a post-hoc analysis to create temporal explanations; and (2) a thorough experimental study against strong baselines that shows that our agent generates significantly improved explanations for its actions when rated by human participants *unfamiliar with the domain* while not losing any task performance compared to the current state-of-the-art knowledge graph-based agents.

2   Background and Related Work

Interactive Fiction (IF) games are simulations featuring language-based state and action spaces. It provides a platform for exploring lifelong open-domain dialogue learning Shuster et al. (2020) and action elimination with deep reinforcement learning Zahavy et al. (2018). In this paper, we use IF games as our test-bed because they provide an ideal platform for collecting data, linking game states and actions to the corresponding natural language explanations. We use the definition of text-adventure games as seen in Côté et al. (2018) and Hausknecht et al. (2020). We take Jericho Hausknecht et al. (2020), a framework for interacting with text games, as the interface connecting learning agents with interactive fiction games. A text game can be defined as a partially-observable Markov Decision Process: $G = \langle S, P, A, O, \Omega, R, \gamma \rangle$, representing the set of environment states, conditional transition probabilities between states, the vocabulary or words used to compose text

Figure 2: Knowledge graph extraction and the (HEX-RL) agent's architecture at step t.

commands, observations, observation conditional probabilities, reward function, and discount factor, respectively. The reinforcement learning agent is trained to learned a policy $\pi_G(o) \rightarrow a$.

Knowledge Graphs for Text Games. Ammanabrolu et al. (2020) proposed Q*BERT, a reinforcement learning agent that learns a KG of the world by answering questions. Xu et al. (2020) introduce the SHA-KG, a stacked Hierarchical Graph Attention mechanism to construct an explicit representation of the reasoning process by exploiting the structure of the KG. Adhikari et al. (2020) present the Graph-Aided Transformer Agent (GATA) which learns to construct a KG during game play and improves zero-shot generalization on procedurally generated TextWorld games. Other works such as Murugesan et al. (2020) explore how to use KGs to endow agents with commonsense. While these works showcase the effectiveness of KGs on task performance and do not focus on how explainable their architectures are. We further note that these architectures do now allow for as fine-grained attention-based attribution as HEX-RL's architecture does—e.g. Q*BERT does not use relationship information in their policy and SHA-KG averages attention across large portions of the graph and is unable to point to specific triples in its KG representation to explain an action.

Explainable Deep RL. Contemporary work on explaining deep reinforcement learning policies can be broadly categorized based on: (1) how the information is extracted, either via intrinsic motivation during training Shu et al. (2017); Hein et al. (2017); Verma et al. (2018) or through post-hoc analysis Rusu et al. (2015); Hayes and Shah (2017); Juozapaitis et al. (2019); Madumal et al. (2020); and (2) the scope—either global Zahavy et al. (2016); Hein et al. (2017); Verma et al. (2018); Liu et al. (2018) or local Shu et al. (2017); Liu et al. (2018); Madumal et al. (2020); Guo et al. (2021). In our work, we create an agent that spans more than one of these categories providing immediately local explanations through extracted knowledge graph representations and post-hoc temporal explanations. Inspired by Madumal et al. (2020), we learn a graphical causal model which focuses on using relations between steps in a puzzle to generate temporal explanations instead of generating counterfactuals.

3 Hierarchically Explainable RL

Our work aims to generate (1) *immediate step-by-step explanations* of an agent's policy by capturing the importance of the current game state observation and (2) *temporally extended explanations* that take into context an entire trajectory via a post-hoc analysis. Formally, let $\mathbf{X} = \{\mathbf{s}_t, \mathbf{a}_t\}_{t=1:T}$ be the set of game steps that compose a trajectory. Each game state s_t consists of a knowledge graph G_t representing all the information learned since the start of the game. This graph is further split into four sub-knowledge graphs each containing different, semantically related relationship types. This section first describes a graph attention based architecture that uses these sub-graphs to produce immediate explanations. We then describe how to filter the game states in a trajectory into a condensed set of the most important ones $\mathbf{X}' \subset \mathbf{X}$ that best capture the underlying dependencies that need to be fulfilled to complete the task—enabling us to produce temporal explanations.

Knowledge Graph State Representation. Building on Ammanabrolu et al. (2020), constructing the knowledge graph is treated as a question-answering task. KGs in these games take the form of RDF triples (Klyne, 2004) of $\langle subject, relation, object\rangle$—extracted from text observations and update as the agent explores the world. The agent answers questions about the environment such as, "What am I carrying?" or "What objects are around me?". A specially constructed dataset for question answering in text games—JerichoQA—is used to fine-tune ALBERT (Lan et al., 2019) to answer these questions (See Appendix A.3). The answers form a set of candidate graph vertices V_t for the current step and questions form the set of relations R_t. Both V_t and R_t are then combined with the graph at the previous step G_{t-1} to update the agent's belief about the world state into G_t. The left side of Figure 2 showcases this.

In an attempt to enable more fine grained explanation generation and inspired by Xu et al. (2020), we divide the knowledge graph G into multiple sub-graphs $G^{atr}, G^{inv}, G^{obj}, G^{loc}$, each representing (1) attributes of objects, (2) objects the player has, (3) objects in the room, and (4) other information such as location (right side of Fig. 2) based on the corresponding relationship types extracted by the ALBERT-QA module. The union of all sub-graphs is equivalent of V_t and R_t extracted from the current game state. The full knowledge graph G_t captures the overall game state since the start of the game. The sub-graphs easily reflect different relationships of the current game state.

Template Action Space. Agents output a language string into the game to describe the actions that they want to perform. To ensure tractability, this action space can be simplified down into templates. Templates consist of interchangeable verbs phrases (VP), optionally followed by prepositional phrases ($VP\ PP$), e.g. ($[carry/take]$ __) and ($[throw/discard/put]$ __ $[against/on/down]$ __), where the verbs and prepositions within [.] are aliases. Actions are constructed from templates by filling in the template's blanks using words in the game's vocabulary. Size of action space is shown in Appendix A.1.

3.1 Immediate Explanations

Our immediate explanations consist of finding the subset of triplets in sub-graphs $G^{atr}, G^{inv}, G^{obj}, G^{loc}$ that most influence the action decision made at the current step—is capable of explaining the action. We introduce a deep RL architecture capable of this.

Hierarchical Knowledge Graph Attention Architecture. At each step, a total score R_t and an observation o_t is received—consisting of $\left(o_{t_{\text{desc}}}, o_{t_{\text{game}}}, o_{t_{\text{inv}}}, a_{t-1}\right)$ corresponding to the room description, game feedback, inventory, and previous action and are processed using a GRU based encoder using the hidden state from the previous step, combining them into a single observation embedding $\mathbf{o}_t \in \mathbb{R}^{d_{text} \times c}$ (bottom of Fig. 2).

The full knowledge graph G_t is processed via Graph Attention Networks (GATs) Veličković et al. (2017) followed by a linear layer to get the graph representation $\mathbf{g_t} \in \mathbb{R}^{d_{text}}$ (middle of Fig. 2). We compute *LSTM attention* between $\mathbf{o}_t$ and $\mathbf{g_t}$ as:

$$\boldsymbol{\alpha}_{\text{LSTM}} = \text{softmax}\left(W_l \boldsymbol{h}_{\text{LSTM}} + \boldsymbol{b}_l\right) \tag{1}$$

$$\boldsymbol{h}_{\text{LSTM}} = \tanh\left(W_o \boldsymbol{o}_t \oplus \left(W_g \mathbf{g_t} + \boldsymbol{b}_g\right)\right) \tag{2}$$

where $\oplus$ denotes the addition of a matrix and a vector. $W_l \in \mathbb{R}^{d_{text} \times d_{text}}$, $W_g \in \mathbb{R}^{d_{text} \times d_{text}}$, $W_o \in \mathbb{R}^{d_{text} \times d_{text}}$ are weights and $\boldsymbol{b}_l \in \mathbb{R}^{d_{text}}$, $\boldsymbol{b}_o \in \mathbb{R}^{d_{text}}$ are biases. The overall representation vector is updated as:

$$\mathbf{q_t} = \mathbf{g_t} + \sum_i^c \boldsymbol{\alpha}_{\text{LSTM},i} \odot \boldsymbol{o}_{t,i} \tag{3}$$

where $\odot$ denotes dot-product and c is the number of $\boldsymbol{o}_t$'s components.

Sub-graphs are also encoded by GATs to get the graph representation $\mathbf{g'_t} \in \mathbb{R}^{d_{G_t,sub} \times m}$ (no. of subgraphs). The *Hierarchical Graph Attention* between $\mathbf{q}_t \in \mathbb{R}^{d_{G_t,sub}}$[1] and $\mathbf{g'_t}$ is calculated by:

$$\boldsymbol{\alpha}_{\text{Hierarchical}} = \text{softmax}\left(W_H \boldsymbol{h}_H + \boldsymbol{b}_H\right) \tag{4}$$

$$\boldsymbol{h}_H = \tanh\left(W_{g'} \boldsymbol{g'_t} \oplus \left(W_q \boldsymbol{q_t} + \boldsymbol{b}_q\right)\right) \tag{5}$$

---

[1]A linear transformation ensures that $\mathbf{q}_t \in \mathbb{R}^{d_{G_t,sub}}$.

where $\boldsymbol{W}_{\mathrm{H}} \in \mathbb{R}^{d_{G_t,sub} \times d_{G_t,sub}}$, $\boldsymbol{W}_{\mathrm{g'}} \in \mathbb{R}^{d_{G_t,sub} \times d_{G_t,sub}}$, $\boldsymbol{W}_{\mathrm{q}} \in \mathbb{R}^{d_{G_t,sub} \times d_{G_t,sub}}$ are weights and $\boldsymbol{b}_{\mathrm{H}} \in \mathbb{R}^{d_{G_t,sub}}$, $\boldsymbol{b}_{\mathrm{q}} \in \mathbb{R}^{d_{G_t,sub}}$ are biases. Then we get state representation, consisting of the textual observations full knowledge graph and sub-knowledge graph.

$$\mathbf{v_t} = \mathbf{q_t} + \sum_i^s \boldsymbol{\alpha}_{\mathrm{Hierarchical},i} \odot \boldsymbol{g}'_{\mathrm{t},i} \tag{6}$$

where s is the number of sub-graphs (4 in our paper). The full architecture can be found in Figure 2.

The agent is trained via the Advantage Actor Critic (A2C) Mnih et al. (2016) method to maximize long term expected reward in the game in a manner otherwise unchanged from Ammanabrolu et al. (2020) (See Appendix A.2). These attention values thus reflect the portions of the knowledge graphs that the agent must focus on to best achieve this goal of maximizing reward.

Hierarchical Graph Attention Explanation. The graph attention $\boldsymbol{\alpha}_{\mathrm{Hierarchical}}$ is used to capture the relative importance of game state observations and KG entities in influencing action choice. For each sub-graph, the graph attention, $\boldsymbol{\alpha}_{\mathrm{Hierarchical},i} \in \mathbb{R}^{n_{\mathrm{nodes}} \times m}$ is summed over all the channels m to obtain $\boldsymbol{\alpha}'_{\mathrm{Hierarchical},i} \in \mathbb{R}^{n_{\mathrm{nodes}} \times 1}$, showing the importance of the KG nodes in the ith sub-graph. The top-k valid entities (and corresponding edges) with highest absolute value of its attention form the set of knowledge graph triplets that best locally explain the action a_t.

In order to make the explanation more readable for a human reader, we further transform knowledge graph triplets to natural language by template filling. We create templates for each type of sub-graphs $G^{atr}, G^{inv}, G^{obj}, G^{loc}$.

3.2 Temporally Extended Explanations

Graph attention tells us which entities in the KG are attended to when making a decision, but is not enough alone for explaining "why" actions are the right ones in the context of fulfilling dependencies that may potentially be unrewarded by the game—especially given the fact that there are potentially multiple ways of achieving the overall task. HEX-RL thus saves trajectories for hundreds of test time rollouts of the games, performed once a policy has been trained (Table 1 and Appendix A.5). The game trajectories consist of all the game states, actions taken, predicted critic values, game scores, the knowledge graphs, and the immediate step level explanations generated as previously described. HEX-RL produces a temporal explanation by performing a post-hoc analysis on these game trajectories. The agent then analyzes and filters these trajectories in an attempt to find the subset of states that are most crucial to achieving the task as summarized in Figure 3—then using that subset of states to generate temporal trajectory level explanations.

Figure 3: Temporal explanation pipeline for why the agent chose the action—"*go north*" at "*Behind House*".

Bayesian State Filter. We first train a Bayesian model to predict the conditional probability $\mathbb{P}(A \mid B_i)$ of a game step (A) given any other possible game step (B_i) in the game trajectories. More specifically, each game step is composed of 3 elements, game state o_t, action a_t and the current knowledge graph G_t. The key intuition here being that state, action pairs that appear in a certain ordering in multiple trajectories are more likely to dependant on each other.

The set of game steps with the highest $\mathbb{P}(A \mid B_i)$ is used to explain taking the action associated with game state A. For example, "take egg" (A) is required to "open egg" (B), and $\mathbb{P}(A \mid B) = 1$, hence

"open egg" is used as a reason why action "take egg" must be taken first. The initial set of game states $\mathbf{X}$ is filtered into $\mathbf{X}_1$ by working backwards from the final goal state by finding the set of states that form the most likely chain of causal dependencies that lead to it. Details can be found in Appendix A.5 and A.6.

Language Model Action Filter. Following this, we apply a GPT-2 (Radford et al., 2019) language model trained to generate actions based on transcripts of text games from human play-throughs to further filter out important states—known as the Contextual Action Language Model (CALM) Yao et al. (2020). As this language model is trained on human transcripts, we hypothesize that it is able to further filter down the set of important states by finding the states that have corresponding actions that a human player would be more likely to perform—thus potentially leading to more natural explanations. CALM takes into observation o_t, action a_t and the following observation o_{t+1}, and predicts next valid actions a_{t+1}. In our work, we use CALM as a filter to look for the relations between a game step A and the explanation candidates $B_i \in \mathbf{X}_1$. We feed CALM with the prompt o_A, a_A, o_{B_i} to get an action candidate set. When the two game steps A and B_i are highly correlated, given o_A, a_A and o_{B_i}, CALM should successfully predict a_{B_i} with high probability. The game steps B_i, whose associated action a_{B_i} is in this generated action candidates set, are saved as the next set of filtered important candidate game states ($\mathbf{X}_2$).

Semantic State-Action Filter. To better account for the irregularities of the puzzle like environment, we adopt a *semantic filter* to obtain the final important state set $\mathbf{X}_3$. Here, given $A, B_i \in \mathbf{X}_2$, states are further filtered on the basis of whether one of these scenarios occurs: (1) a_A and a_{B_i} contain the same entities, e.g. "*take egg*" and "*open egg*". (2) G_A and G_{B_i} share the same entities, e.g. "lamp" occurs in both observations. (3) A and B_i occur in the same location, e.g. after taking action a_A, the player enters "kitchen" and B occurs in "kitchen". (4) The state has a non-zero reward or a high absolute critic value, indicating that it is either a state important for achieving the goals of the

Table 1: Example state saved during game play.

STEP: 16
Text Observation:
Up a Tree
Beside you on the branch is a small birds nest.
In the birds nest is a large egg encrusted with jewels...
Knowledge graph:
$\langle tree, in, forest \rangle, \langle egg, is, interactable \rangle$...
Action: take egg
Immediate explanation: egg is interactable
Game Score:5
Critic Value: 5.7457

game or it is a state to be avoided. The final set of important game states $\mathbf{X}_3$ is used to synthesize post-hoc temporal explanations for why an action was performed in a particular state—as seen in Figure 1—taking into account the overall context of the dependencies required to be satisfied and building on the immediate step level explanations for each given state in $\mathbf{X}_3$. Ablation studies pinpointing the relative contributions of the different filters are found in Appendix C. We concluded that all three steps of the filtering process to identify important states are necessary for creating coherent temporal explanations that effectively take into account the context of the agent's goals.

4 Evaluation

Our evaluation consists of three phases: (1) We show that HEX-RL has the comparable performance to state-of-art reinforcement learning agents on text games in Section 4.1. (2) Then in Section 4.2, we evaluate our immediate attention explanation model by comparing the explanations generated by HEX-RL and agents that do not use knowledge graphs (See Fig. 2 and Section 3.1). (3) In Section 4.3 we compare immediate to temporal explanations, focusing on the effects that including trajectory level context when evaluating explanations in the context of agent goals.

4.1 Task Performance Evaluation

We compare HEX-RL with four strong state-of-art reinforcement learning agents—focusing on contemporary agents that use knowledge graphs—on an established test set of 9 games from the Jericho benchmark (Hausknecht et al., 2020).

LSTM-A2C is a baseline that only uses natural language observations as state representation that is encoded with an LSTM-based policy network.

Table 2: Asymptotic scores on games by different methods across 5 independent runs. *Eps.* indicates normalized scores averaged across 100 episodes of testing which occurs at the end of the training period and *Max* indicates the maximum score seen by the agent over the same period. We present results on two training rewards for HEX-RL, *game only* and *game and IM*.

Experiment	LSTM-A2C		KG-A2C		SHA-KG		Q*BERT		HEX-RL *Game Only*		HEX-RL *Game and IM*		Max
Metric	Eps.	Max	Eps.	Max	Eps.	Max	Eps.	Max	Eps.	Max	Eps.	Max	-
zork1	27	31.2	34	35	33.6	34.5	35	35	29.8	40	30.2	40	350
library	8.2	10	14.3	19	10.0	15.8	18	18	16.0	19	13.8	21	30
detective	141	188	207.9	214	246.1	308	274	310	276.7	330	276.9	330	360
balances	10	10	10	10	9.8	10	10	10	10.0	10	10.0	10	51
pentari	50.4	55	50.7	56	48.2	51.3	50	56	34.6	55	44.7	60	70
ztuu	5	5	5	5	5	25	5	5	5.0	5	5.1	9	100
ludicorp	14.4	18	17.8	19	17.6	17.8	18	19	14.0	18	17.6	18	150
deephome	1	1	1	1	1	1	1	1	1.0	1	1.0	1	300
temple	8	8	7.6	8	7.9	6.9	8	8	8.0	8	7.6	8	35
% compl.	22.6	25.9	27.3	30.8	27.2	33.1	**30.8**	34.9	27.2	33.9	28.2	**35.8**	100
std dev	0.02	0.01	0.06	0.01	-	-	0.03	0.00	0.03	0.01	0.03	0.02	-

KG-A2C. Instead of training a question-answering system like Q*BERT to build knowledge graph state representation, KG-A2C Ammanabrolu and Hausknecht (2020) extracts knowledge graph triplets from the text observations using a rules based approach built on OpenIE Angeli et al. (2015).

SHA-KG is adapted from Xu et al. (2020) and uses a rules-based approach to construct a knowledge graph for the agent which is then fed into a Hierarchical Graph Attention network as in HEX-RL. This agent separates the sub-graphs out using a rules-based approach and makes no use of any graph edge relationship information.

Q*BERT. Ammanabrolu et al. (2020) uses a similar method of creating the knowledge graph through question answering but does not use the hierarchical graph attention architecture combined with the sub-graphs.

These baselines are all trained via the Advantage Actor Critic (A2C) Mnih et al. (2016) method—further comparisons to other contemporary agents can be found in Appendix A.7. It is also worth noting that most contemporary state of the art deep RL agents for text games use recurrent neural policy networks as opposed to transformer networks due to their improved performance in this domain.

HEX-RL Training. We trained HEX-RL on two reward types: (a) *game only*, which indicates that we only use score obtained from the game as reward. (2) *game with intrinsic motivation (game and IM)*, which contains an additional intrinsic motivation reward based on knowledge graph expansion as seen in Ammanabrolu et al. (2020)—where the agent is additionally rewarded for learning more about the world by finding new facts for knowledge graph (see Appendix A.8, A.9 and A.10).

Table 2 shows the performance of HEX-RL and the other four baselines. We can see that designing the HEX-RL agent to be inherently explainable through the use of Hierarchical Graph Attention and the sub-graphs improves the overall maximum score seen during training when compared to any of the other agents. In terms of the average score seen during the final 100 episodes, HEX-RL wth intrinsic motivation outperforms all baselines with the exception of Q*BERT—there HEX-RL significantly outperforms Q*BERT on one game, is outperformed on two games, and comparable on the remaining six games. HEX-RL thus performs comparably to other state-of-the-art baselines in terms of overall task performance while also boasting the additional ability to explain its actions.

4.2 Immediate Explanation Evaluation

Having established that HEX-RL's performance while playing text games is comparable to other state-of-the-art agents, we attempt to answer the question of exactly how useful the knowledge graph based architecture is when generating immediate step-by-step explanations by comparing HEX-RL to a baseline that doesn't use knowledge graphs in a human participant study. Two models for step-by-step explanations are compared:

- **LSTM Attention explanations.** Extracts the most important substring in the observations through LSTM attention α_{LSTM} and then uses those words to create an explanation.
- **Hierarchical Graph Attention explanations.** Extracts KG triplets most influenced the choice of actions by Hierarchical Attention $\alpha_{\text{Hierarchical}}$ and then transforming them into readable language explanations through templates.

We recruited 40 participants—generally unfamiliar with the environment at hand—on a crowd sourcing platform. Each participant reads a randomly selected subset of 10 explanation pairs (drawn randomly from a pool totaling 60 explanation pairs), generated by Hierarchical Graph Attention and LSTM attention explanation on three games in the Jericho benchmark: *zork1*, *library*, and *balances*. We choose three games with very different structures and genres as defined in Hausknecht et al. (2020). They each require a diverse set of action types and solutions to complete and thus provide a wide area of coverage when used as test beds for human evaluation of explanations. Then they are given the following metrics and asked to choose which explanation they prefer for that metric:

- *Confidence*: This explanation makes you more confident that the agent made the right choice.
- *Human-likeness*: This explanation expresses more human-like thinking on the action choice.
- *Understandability*: This explanation makes you understand why the agent made the choice.

Variations of these questions have been used to evaluate other explainable AI systems (eg. Ehsan et al. (2019)). At least 5 participants give their preference for each explanation pair. We take the majority preference from humans participants as the result. More details are shown in Appendix B.1.

Figure 4 shows the result of the human evaluation of attention explanations. Hierarchical graph attention explanation is preferred over LSTM attention explanation in all three dimensions. These results are statistically significant ($p < 0.05$) with fair inter-rater reliabilities. We also observe that these three dimensions are highly, positively correlated using Spearman's Rank Order Correlation.[2]

A slightly higher proportion of participants preferred the LSTM Attention explanations in the human-likeness dimension compared to the other two. The participants preferring LSTM Attention explanation stated that they found it intuitive but often incoherent and found the Hierarchical Graph Attention explanations to be more robotic. LSTM attention explanations are substrings of the human-written observation and thus have the potential to be more natural sounding than the templated Hierar-

Figure 4: Human evaluation results showing the proportion of participants that prefer Hierarchical Graph Attention vs. LSTM Attention explanations, $**$ indicates $p < 0.01$, † indicates $\kappa > 0.2$ or fair agreement. ‡ indicates $\kappa > 0.4$ or moderate agreement. Evaluation results on each game are shown in Appendix A.11.

chical Graph Attention explanations when they are coherent enough to be understood. The KG sacrifices a small amount of human-likeness in return for much greater overall coherence and accuracy. KGs with Hierarchical Graph Attention give us explanations that are more easily understood and inspire greater confidence in the agent's decisions.

Example qualitative LSTM Attention and Hierarchical Graph Attention explanations can be found in Appendix D.2. As our system relies on graph hierarchical graph attention to generate immediate explanations, a well-trained knowledge graph representation module of the world knowledge is required. Most cases where the agent fails to provide satisfactory immediate explanations are either when: (1) the explanation is not directly linked to the one of the facts we choose to extract from the knowledge graph, such as object/location information; and (2) due to the error of knowledge graph extraction models themselves.

---

[2]$r_s = 0.70$, $p < 0.01$, between "confidence" and "understandability"; $r_s = 0.67$, $p < 0.01$, between "confidence" and "human-likeness"; $r_s = 0.89$, $p < 0.01$, between "human-likeness" and "understandability"

4.3 Immediate vs. Temporal Explanations

Having proved the effectiveness of the knowledge graph at the immediate step-by-step explanation level, we evaluate our method of producing temporal explanations and how they compare to the immediate explanations along two dimensions: (1) coherence; and (2) explanation accuracy when taken in the context of the agent's goals. An ablation study finding that all the three major components of the temporal explanations are all necessary for producing satisfactory explanations can be found in Appendix C.

Participants first read a trajectory of the game combined with step-by-step immediate explanations and the game goal, then indicate how much they agree with the statements on a Likert scale of 1 (strong disagree) to 5 (strong agree). Here, we add two metrics from the previous study:

- *Goal context*: You are able to understand why the agent takes this particular sequence of actions given what you know about the goal.
- *Readability*: This explanation is easy to read.

Figure 5 shows the average scores for each question for the immediate and temporal explanations. The temporal explanations achieve comparable performance to the immediate explanations on all metrics except for the the metric relating to goal context where they significantly out-perform the immediate explanations. A majority of participants stated that a condensed trajectory level explanation made the goals of the agent easier to understand than reading through each step level explanation. These results indicate that HEX-RL can generally successfully identify the most important states in a trajectory and use them to create temporal explanations that are on par with immediate explanations in terms of co-

Figure 5: Human judgment[5] results on immediate and temporal explanation, $*$ indicates $p <$ 0.05. Error bars indicate a confidence level of 95%.

herence but provide significantly more context in terms of explaining an agent's actions with respect to its task-based goals.

Cases where the agent does not provide a temporally coherent and goal-driven explanation revolve around failures—particularly by the Bayesian State Filter—in detecting the most important states in the trajectory. A qualitative analysis (as seen in Appendix D.3) suggests that this occurs in cases where there are a large number of branching paths that lead to the same end state. Thus, the quality of the generated temporal explanations appears to be inversely proportional to the relative complexity of the game as measured by its branching factor.

5   Conclusions

Explaining deep RL policies for sequential decision making problems in natural language is a sparsely studied problem despite a steadily growing need. An oft given reason for this phenomenon is that deep RL methods perform better without the additional burden of being explainable. In an attempt to encourage work in this area, we create the Hierarchically Explainable Reinforcement Learning (HEX-RL) agent which treats explainability as a first-class citizen in its design by using a readily interpretable knowledge graph state representation coupled with a Hierarchical Graph Attention network. This agent is able to produce step-by-step commentary-like immediate explanations and also a condensed temporal trajectory level explanation via a post-hoc analysis. We show that with careful design, it is possible to create inherently explainable RL agents that do not lose performance when compared to contemporary state-of-the-art agents and simultaneously are able to generate significantly higher quality explanations of actions.

References

Ashutosh Adhikari, Xingdi Yuan, Marc-Alexandre Côté, Mikuláš Zelinka, Marc-Antoine Rondeau, Romain Laroche, Pascal Poupart, Jian Tang, Adam Trischler, and William L. Hamilton. 2020. Learning dynamic belief graphs to generalize on text-based games. *CoRR*, abs/2002.09127.

Prithviraj Ammanabrolu and Matthew Hausknecht. 2020. Graph constrained reinforcement learning for natural language action spaces. In *International Conference on Learning Representations*.

Prithviraj Ammanabrolu, Ethan Tien, Matthew Hausknecht, and Mark O Riedl. 2020. How to avoid being eaten by a grue: Structured exploration strategies for textual worlds. *arXiv preprint arXiv:2006.07409*.

Gabor Angeli, Melvin Jose Johnson Premkumar, and Christopher D Manning. 2015. Leveraging linguistic structure for open domain information extraction. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 344–354.

Marc-Alexandre Côté, Akos Kádár, Xingdi Yuan, Ben Kybartas, Tavian Barnes, Emery Fine, James Moore, Matthew Hausknecht, Layla El Asri, Mahmoud Adada, et al. 2018. Textworld: A learning environment for text-based games. In *Workshop on Computer Games*, pages 41–75. Springer.

Upol Ehsan, Pradyumna Tambwekar, Larry Chan, Brent Harrison, and Mark O Riedl. 2019. Automated rationale generation: a technique for explainable ai and its effects on human perceptions. In *Proceedings of the 24th International Conference on Intelligent User Interfaces*, pages 263–274.

Wenbo Guo, Xian Wu, Usmann Khan, and Xinyu Xing. 2021. Edge: Explaining deep reinforcement learning policies. In *Thirty-Fifth Conference on Neural Information Processing Systems*.

Matthew Hausknecht, Prithviraj Ammanabrolu, Marc-Alexandre Côté, and Xingdi Yuan. 2020. Interactive fiction games: A colossal adventure. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 7903–7910.

Bradley Hayes and Julie A Shah. 2017. Improving robot controller transparency through autonomous policy explanation. In *2017 12th ACM/IEEE International Conference on Human-Robot Interaction (HRI*, pages 303–312. IEEE.

Daniel Hein, Alexander Hentschel, Thomas Runkler, and Steffen Udluft. 2017. Particle swarm optimization for generating interpretable fuzzy reinforcement learning policies. *Engineering Applications of Artificial Intelligence*, 65:87–98.

Zoe Juozapaitis, Anurag Koul, Alan Fern, Martin Erwig, and Finale Doshi-Velez. 2019. Explainable reinforcement learning via reward decomposition. In *IJCAI/ECAI Workshop on Explainable Artificial Intelligence*.

Graham Klyne. 2004. Resource description framework (rdf): Concepts and abstract syntax. *http://www. w3. org/TR/2004/REC-rdf-concepts-20040210/*.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. 2019. Albert: A lite bert for self-supervised learning of language representations. *arXiv preprint arXiv:1909.11942*.

Guiliang Liu, Oliver Schulte, Wang Zhu, and Qingcan Li. 2018. Toward interpretable deep reinforcement learning with linear model u-trees. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 414–429. Springer.

Prashan Madumal, Tim Miller, Liz Sonenberg, and Frank Vetere. 2020. Explainable reinforcement learning through a causal lens. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 2493–2500.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. 2016. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pages 1928–1937. PMLR.

Keerthiram Murugesan, Mattia Atzeni, Pushkar Shukla, Mrinmaya Sachan, Pavan Kapanipathi, and Kartik Talamadupula. 2020. Enhancing text-based reinforcement learning agents with commonsense knowledge. *CoRR*, abs/2005.00811.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners.

Pranav Rajpurkar, Robin Jia, and Percy Liang. 2018. Know what you don't know: Unanswerable questions for SQuAD. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 784–789, Melbourne, Australia. Association for Computational Linguistics.

Andrei A Rusu, Sergio Gomez Colmenarejo, Caglar Gulcehre, Guillaume Desjardins, James Kirkpatrick, Razvan Pascanu, Volodymyr Mnih, Koray Kavukcuoglu, and Raia Hadsell. 2015. Policy distillation. *arXiv preprint arXiv:1511.06295*.

Tianmin Shu, Caiming Xiong, and Richard Socher. 2017. Hierarchical and interpretable skill acquisition in multi-task reinforcement learning. *arXiv preprint arXiv:1712.07294*.

Kurt Shuster, Jack Urbanek, Emily Dinan, Arthur Szlam, and Jason Weston. 2020. Deploying lifelong open-domain dialogue learning. *arXiv preprint arXiv:2008.08076*.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. 2017. Graph attention networks. *arXiv preprint arXiv:1710.10903*.

Abhinav Verma, Vijayaraghavan Murali, Rishabh Singh, Pushmeet Kohli, and Swarat Chaudhuri. 2018. Programmatically interpretable reinforcement learning. In *International Conference on Machine Learning*, pages 5045–5054. PMLR.

Fei Wang, Mengqing Jiang, Chen Qian, Shuo Yang, Cheng Li, Honggang Zhang, Xiaogang Wang, and Xiaoou Tang. 2017. Residual attention network for image classification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3156–3164.

Sarah Wiegreffe and Ana Marasovic. 2021. Teach me to explain: A review of datasets for explainable natural language processing. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 1)*.

Kelvin Xu, Jimmy Ba, Ryan Kiros, Kyunghyun Cho, Aaron Courville, Ruslan Salakhudinov, Rich Zemel, and Yoshua Bengio. 2015. Show, attend and tell: Neural image caption generation with visual attention. In *International conference on machine learning*, pages 2048–2057. PMLR.

Yunqiu Xu, Meng Fang, Ling Chen, Yali Du, Joey Tianyi Zhou, and Chengqi Zhang. 2020. Deep reinforcement learning with stacked hierarchical attention for text-based games. *Advances in Neural Information Processing Systems*, 33.

Shunyu Yao, Rohan Rao, Matthew Hausknecht, and Karthik Narasimhan. 2020. Keep calm and explore: Language models for action generation in text-based games. *arXiv preprint arXiv:2010.02903*.

Quanzeng You, Hailin Jin, Zhaowen Wang, Chen Fang, and Jiebo Luo. 2016. Image captioning with semantic attention. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4651–4659.

Tom Zahavy, Nir Ben-Zrihem, and Shie Mannor. 2016. Graying the black box: Understanding dqns. In *International Conference on Machine Learning*, pages 1899–1908. PMLR.

Tom Zahavy, Matan Haroush, Nadav Merlis, Daniel J Mankowitz, and Shie Mannor. 2018. Learn what not to learn: Action elimination with deep reinforcement learning. *Advances in neural information processing systems*, 31.

A Implementation Details

A.1 Full Action Space Size

Jericho provides the capability to extract game-specific vocabulary and action templates (Section 3). These templates contain up to two blanks, so a typical game with 200 templates and a 700 word vocabulary yields an action space of $\mathcal{O}(TV^2) \approx 98$ million, three orders of magnitude smaller than the 240-billion space of 4-word actions using vocabulary alone.

A.2 A2C Architecture

Further details of what is found in Figure 2. The sequential action decoder consists two GRUs that are linked together as seen in Ammanabrolu and Hausknecht (2020). The first GRU decodes an action template and the second decodes objects that can be filled into the template. These objects are constrained by a *graph mask*, i.e. the decoder is only allowed to select entities that are already present in the knowledge graph.

Same with Ammanabrolu and Hausknecht (2020), the loss consists of template loss, object loss, value loss, actor loss and entropy loss. The template loss given a particular state and current network parameters is applied to the decoder. Similarly, the object loss is applied across the decoder is calculated by summing cross-entropy loss from all the object decoding steps. Entropy loss over the valid actions, is designed to prevent the agent from prematurely converging on a trajectory. The following hyperparameters are taken from the original paper and known to work well on text games.

Parameters	Value
discount factor	0.9
entropy coefficient	0.03
value coefficient	9
template coefficient	3
object coefficient	9

A.3 Knowledge Graph Representation QA Model

The question answering network based on ALBERT (Lan et al., 2019) has the following hyperparameters, taken from the original paper and known to work well on the SQuAD 2.0 (Rajpurkar et al., 2018) dataset. No further hyperparameter tuning was conducted.

Parameters	Value
batch size	8
learning rate	3e-5
max seq len	512
doc stride	128
warmup steps	814
max steps	8144
gradient accumulation steps	24

A.4 Templates of Immediate Explanation

We consider four types of sub-graphs $G^{atr}, G^{inv}, G^{obj}, G^{loc}$, each representing (1) attributes of objects, (2) objects the player has, (3) objects in the room, and (4) other information such as location (see right side of Figure 2). Hence, we create one template for each sub-graph with converting conjugated forms of verbs,

- $\langle object, is, attribute \rangle$ is converted to "*Object is attribute*".
  For example, $\langle trees, is, interactable \rangle$ is converted to "*trees are interactable.*". $\langle egg, is, interactable \rangle$ is converted to "*egg is interactable*".
- $\langle player, has, object \rangle$ is converted to "*I have object*".
  For example, $\langle player, has, eggs \rangle$ is converted to "*I have eggs*". $\langle player, has, knife \rangle$ is converted to "*I have knife*".

- ⟨*object, in, location*⟩ is converted to "*Object is in location*".
  For example, ⟨*egg, in, forest*⟩ is converted to "*egg is in forest*".
  ⟨*trees, in, forest*⟩ is converted to "*trees are in forest*".
- ⟨*location_1, direction, location_2*⟩ is converted to "*location_1 is in the direction of location_2*".
  For example, ⟨*forest, north, house*⟩ is converted to "*forest is in the north of house*".

A.5   HEX-RL explanation parameters

There are some other parameters which may affect the results of explanations. Our initial experiments suggested that the larger the number of trajectories we use, the more accurate the Bayesian State Filter.

Parameter	Value	Explanation of Use
trajectories for test time rollouts	300	Number of saved trajectories of test time rollouts of the games, which is performed once a policy has been trained
Bayesian State Filter threshold	0.5	Larger threshold filters more steps out.
topk of CALM	20	Topk sampling of CALM model

A.6   Bayesian State Filter Detail

We first train a Bayesian model to predict the conditional probability $\mathbb{P}(A \mid B_i)$ of a game step (A) given any other possible game step (B_i) in the game trajectories. More specifically, current game step (A) is composed of 3 elements, game state o_t, action a_t and knowledge graph G_t. We count the occurrence of A ($\mathbb{C}(A)$), and all the game steps occurred in the game logs ($\mathbb{C}(B_i)$), and also count the co-occurrence of A and B_i, $\mathbb{C}(A \cap B_i)$ in the same trajectory. $\mathbf{X} = \{A, B_1, ..., B_i\}$. The conditional probability $\mathbb{P}(A \mid B_i)$ is calculated by,

$$\mathbb{P}(A \mid B_i) = \frac{\mathbb{P}(B_i \mid A)\mathbb{C}(A)}{\mathbb{C}(B_i)} \tag{7}$$

where $\mathbb{C}(A)$ and $\mathbb{C}(B_i)$ stand for the raw count of game step A and B_i in the collected trajectories. The key intuition here being that state, action pairs that appear in a certain ordering in multiple trajectories are more likely to dependant on each other. Higher $\mathbb{P}(A \mid B_i)$ indicates the necessity of A to B. The set of game steps with the highest $\mathbb{P}(A \mid B_i)$ is used to explain taking the action associated with game state A. For example, "take egg" (A) is required to "open egg" (B), and $\mathbb{P}(A \mid B) = 1$, hence "open egg" is used as a reason why action "take egg" must be taken first. The initial set of game states $\mathbf{X}$ is filtered into $\mathbf{X}_1$ by working backwards from the final goal state by finding the set of states that form the most likely chain of causal dependencies that lead to it. As shown in Figure 3, we obtain the explanation candidate game steps $\mathbf{X}_1$ by filtering all the possible game steps following current game step A in the game logs with $\mathbb{P}(A \mid B_i) > p$, where p is the threshold.

A.7   Raw scores across Jericho supported games

Table 3: Raw scores across Jericho supported games. *Eps.* indicates scores averaged across the final 100 episodes and *Max* indicates the maximum score seen by the agent over the same period. We present results on *game and IM* reward.

Exp.	TDQN	DRRN	HEX-RL		Max
			Game and IM		
Metric	Eps.	Eps.	Eps.	Max	-
zork1	9.9	24.6	30.2	40	350
library	6.3	17	13.8	21	30
detective	169	197.8	276.93	330	360
balances	4.8	10	10	10	51
pentari	17.4	27.2	44.7	60	70
ztuu	4.9	**21.6**	5.08	9	100
ludicorp	6	13.8	17.6	18	150
deephome	1	1	1	1	300
temple	7.9	7.4	7.58	8	35
% compl.	15.2	25.5	**28.2**	**35.8**	100

A.8 Reward types

To alleviate the issue that rewards are sparse and often delayed, Ammanabrolu et al. defined an *intrinsic motivation* for the agent that leverages the knowledge graph being built during exploration. The motivation is for the agent to learn more information regarding the world and expand the size of its knowledge graph. They formally define $game\_and\_IM$ reward in terms of new information learned.

$$r_{IM_t} = \Delta(KG_{\text{global}} - KG_t) \tag{8}$$

where $KG_{\text{global}} = \bigcup_{i=1}^{t-1} KG_i$ Here KG_{global} is the set of all edges that the agent has ever had in its knowledge graph and the subtraction operator is a set difference.

A.9 HEX-RL Architecture Hyperparameters

The additional hyperparamters used for training HEX-RL are detailed below, same with (Ammanabrolu et al., 2020). *graph dropout* and *mask dropout* are used for encouraging graph network to actually learn a sparse representation.

Parameters	Value
buffer size	40
batch size	16
graph dropout	0.2
mask dropout	0.1
embedding size	50
hidden size	100
GAT embedding size	25

A.10 Task Performance

We plot the training reward curve for 9 games in Figure 6 and Figure 7. Reward curves are shown until they reach asymptotic performance, i.e. the number of steps until the score no longer increases. All agents were trained with the same number of steps (100,000) and the results at the end of this training is what is reported in Table 2.

Figure 6: Eps. initial reward curves for the exploration strategies—*Game only* Reward

Figure 7: Eps. initial reward curves for the exploration strategies—*Game and IM* Reward

 A.11   Immediate Explanation Evaluation

 We plot the immediate explanation evaluation result per game in Figure 8.

(a) zorkI

(b) library

(c) balances

Figure 8: Human evaluation results comparing Hierarchical Graph Attention vs. LSTM Attention, $*$ indicates $p < 0.05$, $**$ indicates $p < 0.01$, † indicates $\kappa > 0.2$ or fair agreement. ‡ indicates $\kappa > 0.4$ or moderate agreement.

B Human Evaluation Details

B.1 Immediate Explanation Evaluation

We firstly ask participants to read an interactive game description and then ask them to answer a set of questions about this game to make sure they are qualified. They will also play a demo of an interactive text game and answer a question based on the game they played. The details can be found in Figure 9 and Figure 10. These questions are designed to improve the quality of human evaluation. At least 5 participants give their preference for each explanation pair.

Each participant reads a randomly selected subset of 10 explanation pairs (drawn randomly from a pool totaling 60 explanation pairs), generated by Hierarchical Graph Attention and LSTM attention explanation on three games in the Jericho benchmark, *zork1*, *library*, and *balances*. The following three questions are asked,

- Which explanation makes you more confident that the agent made the right choice?
- Which explanation expresses more human-like thinking on the action choice?
- Which explanation makes you understand why the agent made the choice?

You will be asked to read a game trajectory of an **interactive fiction** game and then evaluate the explanations of choices in the game.

Please read this **interactive narrative game** description carefully!

Balances is the game in this study.

Description:
Balances is a relatively short, old-fashioned puzzle game set in the world of the Enchanter series and riffing on Spellbreaker in particular: the player must find scrolls, learn their spells, and cast them in order to collect white cubes. It shares a number of design characteristics with those games: rooms represent fairly large open spaces, there are more animal NPCs than humans to interact with, and a loose, playful approach to world-building means that the various areas don't have a great deal to do with one another.

>> We trained an AI agent to play the game and also automatically generate explanations for its choices. Your job is to read these stories and evaluate the **automatic explanations** by answering 3 questions.

You will first read one game step: a description and an action.
Description is to describe the room or location which the AI agent was in, and *action* is the agent's choice based on the descriptions.
Then you will **read two explanations** of the above action. 3 questions will be asked for PAIRWISE COMPARISON:
1. Which explanation makes you more **confident** that the agent made the right choice?
2. Which explanation expresses more **human-like** thinking on the action choice?
3. Which explanation makes you **understand** why the agent made the choice?

What will you do in *Balances*?
(Multiple choices, select all that apply)

☐ Get treasure

☐ Find scrolls

☐ Find murderers

☐ Learn spells

Figure 9: Screenshot of the human study instruction—game description.

Figure 10: Screenshot of the human study instruction—task description.

Figure 11: Screenshot of the human study instruction.

B.2 Immediate vs. Temporal Explanation Evaluation

Participants first read the full trajectory of the game (Figure 12) combined with step-by-step immediate explanations, along with summary of the game goal, and indicate how much they agree with the five statements on a Likert scale (Figure 13). The following five statements are used in human study.

- I am confident that I can get the same score as the agent when following this explanation.
- This explanation look like it was made by human.
- This explanation is easy to understand.
- I am able to understand why the agent takes this particular sequence of actions given what I know about the goal.
- This explanation is easy to read.

At least 5 crowd workers rated each explanation.

Please read this transcript of a player playing **Library**:

Goal: Take the book

Description:
Second Floor Stacks
This cavernous room is filled with shelves as far as the eye can see. A doorway to the east is labelled "Computer Room", and the stairwell lies to the north. The door is unlocked but shut.

Action: undo door

Description:
You open the rare books door.

Action: south

Description after taking the above action:
Rare Books Room The shelves are nearly bare, although there is a complete set of the "New ork Times", a box labeled "Avalon", and several biographies of various computer game authors. The door out is to the north You can see a biography of Graham Nelson here.

Description:
Rare Books Room
The shelves are nearly bare, although there is a complete set of the "New ork Times", a box labeled "Avalon", and several biographies of various computer game authors. The door out is to the north You can see a biography of Graham Nelson here.

Action: take all

Description after taking the above action:
biography of Graham Nelson Taken. Your score has just gone up by five points.

Can you **summarize** what is happening in this transcript in less than 100 words?

Figure 12: Screenshot of Immediate vs. Causal Explanation Evaluation —Text Summary.

Please answer the following questions about the game transcript given what you know about the goals of the game.

	Strongly Agree	Agree	Undecided	Disagree	Strongly Disagree
1. I am **confident** that I can get the same score as the agent when following this explanation.	○	○	○	○	○
2. This explanation look like it was made by **human**.	○	○	○	○	○
3. This explanation is easy to **understand**.	○	○	○	○	○
4. I am able to understand why the agent takes this particular sequence of actions given what I know about the goal.	○	○	○	○	○
5. This explanation is easy to **read**.	○	○	○	○	○

Figure 13: Screenshot of Immediate vs. Causal Explanation Evaluation—Likert Scale.

C Temporal Explanation Ablation Study

Having established the overall effectiveness of the filters in HEX-RL that create the temporal explanations, we perform pair-wise ablation studies to pinpoint the relative contributions of the different filters seen in Fig. 3. We first compare explanations generated using a set of important states filtered from the trajectory using the Bayes model compared to Bayes+CALM explanation. This how applying the language model action filter affects the quality of the temporal explanations. As before, we recruited 30 participants on a crowd sourcing platform. Each participant reads a randomly selected subset of explanation pairs, comprised of temporal explanations filtered by Bayes and Bayes+CALM models. Figure 14a shows that after applying the CALM model to filter explanation candidates, generated explanations are significantly preferred on the "Confidence" and "Understandability" dimensions.

Similarly, we then conducted another ablation study to validate the contribution of semantic filter by comparing the Bayes+CALM filtering method to the full HEX-RL using Bayes+CALM+Semantic filters. The experiment setup is the same as the previous ablation study. Figure 14b shows that Bayes+CALM+Semantic performs significantly better than Bayes+CALM on all three dimensions.

We additionally observe that these three metrics are highly, positively correlated using Spearman's Rank Order Correlation in both of these ablation studies[3]. When asked to justify their choices, participants indicated that the full HEX-RL system with Bayes+CALM+Semantic filters provided temporal explanations that they felt was more understandable than alternatives. These results indicate that all three steps of the filtering process to identify important states are necessary for creating coherent temporal explanations that effectively take into account the context of the agent's goals.

(a) Bayes vs. Bayes + CALM explanation

(b) Bayes + CALM vs. Bayes + CALM + Semantic explanation

Figure 14: Human evaluation results on ablation study, $*$ indicates $p < 0.05$, $\dagger$ indicates $\kappa > 0.2$ or fair agreement.

---

[3] $r_s = 0.86$, $p < 0.01$, between "confidence" and "understandability"; $r_s = 0.79$, $p < 0.01$, between "confidence" and "human-likeness"; $r_s = 0.90$, $p < 0.01$, between "human-likeness" and "understandability"

632   We also plot the causal explanation ablation study result per game in Figure 15 and Figure 16.

(a) ZorkI

(b) library

(c) balances

Figure 15: Human evaluation results on ablation study, $*$ indicates $p < 0.05$, † indicates $\kappa > 0.2$ or fair agreement.

(a) ZorkI

(b) library

(c) balances

Figure 16: Human evaluation results on ablation study, $*$ indicates $p < 0.05$, † indicates $\kappa > 0.2$ or fair agreement.

D Explanations Analysis

In this section we provide descriptions of each of the games as well as qualitative samples of trajectories in the format shown to the human participants. We pick out two types of examples where the HEX-RL explanations of the trajectories were rated highly by the human participants and rated poorly in terms of the quality of the explanations—attempting to analyze the failure cases of our method.

D.1 Text Game Descriptions

We list the descriptions[4] of our selected text games for a better undestanding of our explanations and game trajectories in Appendix D.2 and D.3.

1. *zork1*: Many strange tales have been told of the fabulous treasure, exotic creatures, and diabolical puzzles in the Great Underground Empire. As an aspiring adventurer, you will undoubtedly want to locate these treasures and deposit them in your trophy case. Zork creates a wondrous, magical realm that is a veritable feast for the imagination. You find that you have stumbled upon the ancient ruins of a vast empire lying far underground. Yes, you will find many more treasures for your trophy case. But to do so, you will have to search far and wide, solve diabolical puzzles, and defend your treasures (and yourself!) from a few very nasty characters... and one monster, a vicious GRUE that lurks in the dark!

2. *Library*: Escape the library using knowledge and objects found in and about the library.

3. *Balances*: Balances is a relatively short, old-fashioned puzzle game set in the world of the Enchanter series and riffing on Spellbreaker in particular: the player must find scrolls, learn their spells, and cast them in order to collect white cubes. It shares a number of design characteristics with those games: rooms represent fairly large open spaces, there are more animal NPCs than humans to interact with, and a loose, playful approach to world-building means that the various areas don't have a great deal to do with one another.

D.2 Immediate Explanations Analysis

Table 4 shows some example trajectories with its immediate explanations where Hierarchical Graph Attention Explanations did a better job than LSTM Attention. We can see when the player interacts with objects or the subset of sub knowledge graph can explain the action, Hierarchical Graph Attention is able to present a high-quality immediate explanation.

Table 5 shows some example trajectories with its immediate explanations where HEX-RL fails to produce correct immediate explanations. We see that when there is no clear clue in the observations, i.e. the potential gold truth explanation is does not belong knowledge graph, HEX-RL fails to produce immediate explanations.

Hence, we conclude that the performance of immediate explanations is limited: (1) to the cases in which explanation is directly linked to the one of the facts we choose to extract from the knowledge graph, such as object/location information; and (2) by the relative error of knowledge graph extraction models themselves.

D.3 Temporally Extended Explanations Analysis

Table 6, 7 and 8 show example game trajectories with its corresponding temporally extended explanations for game *zork1*, *library* and *balances*. HEX-RL finds the subset of states that are most crucial to achieving the task goals.

We also show one trajectory where HEX-RL fails to produce a high-quality temporally extended explanations in *zork1*. Here, in order to achieve the goal "open window", the player has to get to the location "North of House". However, there exists too many different combinations of actions,

---

[4]https://ifdb.org/

i.e. branching paths, which the player can take to go to "North of House". Bayesian State Filter thus fails to find the most essential steps for achieving this goal.

The performance of the temporally extended explanation system is hindered by the complexity of the game—the more possible ways of achieving the same overall goal, the harder it is to generate an explanation for why the agent has chosen to perform an action to achieve the goal.

Table 4: Example game trajectories with its immediate explanations – Part 1.

[*zork1*]Description before the action:
North of House
You are facing the north side of a white house.
There is no door here, and all the windows are boarded up.
To the north a narrow path winds through the trees.
Action: go north

| LSTM:
You are facing the north side of a white house. | Hierarchical Graph :
Trees is north of north of house. |
| --- | --- |

[*zork1*]Description before the action:
Kitchen
You are in the kitchen of the white house.
A table seems to have been used recently for the preparation of food.
A passage leads to the west and a dark staircase can be seen leading upward.
A dark chimney leads down and to the east is a small window which is open.
On the table is an elongated brown sack, smelling of hot peppers.
A bottle is sitting on the table. The glass bottle contains A quantity of water.
Action: open bottle

| LSTM:
On the table is an elongated brown sack,
smelling of hot peppers. | Hierarchical Graph :
I am in the Kitchen now.
I have bottle.
Bottle is interactable. |
| --- | --- |

[*zork1*]Description before the action:
Up a Tree
You are about 10 feet above the ground nestled among some large branches.
The nearest branch above you is above your reach.
Beside you on the branch is a small birds nest.
In the birds nest is a large egg encrusted with precious jewels,
apparently scavenged by a childless songbird.
The egg is covered with fine gold inlay, and ornamented in lapis lazuli and motherofpearl.
Unlike most eggs, this one is hinged and closed with a delicate looking clasp.
The egg appears extremely fragile.
Action: take egg

| LSTM:
In the birds nest is a large egg encrusted
with precious jewels. | Hierarchical Graph :
egg is interactable. |
| --- | --- |

[*library*]Description before the action:
Rare Books Room
The shelves are nearly bare, although there is a complete set of the "New ork Times",
a box labeled "Avalon", and several biographies of various computer game authors.
The door out is to the north You can see a copy of "Debt of Honor" here.
Action: use key

| LSTM:
The shelves are nearly bare. | Hierarchical Graph :
I have key.
key is interactable. |
| --- | --- |

Table 5: Example game trajectories with its immediate explanations – Part 2.

[*zork1*]Description before the action:	
Forest Path	
This is a path winding through a dimly lit forest.	
The path heads northsouth here.	
One particularly large tree with some low	
branches stands at the edge of the path.	
Action: go up	

LSTM:	Hierarchical Graph :
This is a path winding through a dimly lit forest.	tree is interactable.

[*library*]Description before the action:	
Rare Books Room	
The shelves are nearly bare, although there is a complete set of the "New ork Times",	
a box labeled "Avalon", and several biographies of various computer game authors.	
The door out is to the north	
You can see a biography of Graham Nelson here.	
Action: go west	

LSTM:	Hierarchical Graph :
The door out is to the north.	I am in the Rare Books now.

[*balances*]Description before the action:	
Grasslands, near Hut	
The grasslands sway over low hills in all directions it is a peaceful wilderness,	
broken only by this hut and a faint path to the north.	
You are carrying a cedarwood box, a spell book, a silver coin and a magic burin.	
Action: go north	

LSTM:	Hierarchical Graph :
You are carrying a cedarwood box.	I am in the near Hut now.

Table 6: Example game trajectories for *zork1* with its temporally extended explanations – part 1.

Goal: Take Egg

Description:
Kitchen
You are in the kitchen of the white house. A table seems to have been used recently for the preparation of food. A passage leads to the west and a dark staircase can be seen leading upward. A dark chimney leads down and to the east is a small window which is open. On the table is an elongated brown sack, smelling of hot peppers. Sitting on the kitchen table is A glass bottle The glass bottle contains A quantity of water
Action: east

Description:
Behind House
You are behind the white house. A path leads into the forest to the east. In one corner of the house there is a small window which is open.
Action: east

Description:
North of House
You are facing the north side of a white house. There is no door here, and all the windows are boarded up. To the north a narrow path winds through the trees.
Action: north

Description:
Forest Path
This is a path winding through a dimly lit forest. The path heads northsouth here. One particularly large tree with some low branches stands at the edge of the path.
Action: up

Description:
Up a Tree
You are about 10 feet above the ground nestled among some large branches. The nearest branch above you is above your reach. Beside you on the branch is a small birds nest. In the birds nest is a large egg encrusted with precious jewels, apparently scavenged by a childless songbird. The egg is covered with fine gold inlay, and ornamented in lapis lazuli and mother of pearl. Unlike most eggs, this one is hinged and closed with a delicate looking clasp. The egg appears extremely fragile.
Action: take egg

Description:
Taken.

Temporally Extended Explanations

Description:
Forest Path
This is a path winding through a dimly lit forest. The path heads northsouth here. One particularly large tree with some low branches stands at the edge of the path.
Action: up

Description:
Up a Tree
You are about 10 feet above the ground nestled among some large branches. The nearest branch above you is above your reach. Beside you on the branch is a small birds nest. In the birds nest is a large egg encrusted with precious jewels, apparently scavenged by a childless songbird. The egg is covered with fine gold inlay, and ornamented in lapis lazuli and mother of pearl. Unlike most eggs, this one is hinged and closed with a delicate looking clasp. The egg appears extremely fragile.
Action: take egg

Description after taking the above action:
Taken.

Table 7: Example game trajectories for *library* with its temporally extended explanations.

Goal: Take the book
Description:
Second Floor Stacks
This cavernous room is filled with shelves as far as the eye can see. A doorway to the east is labelled "Computer Room", and the stairwell lies to the north. A heavy wooden door bars the way to the rare books room. A sign indicates that the key may be obtained from the circulation desk.
Action: undo door with key
Description:
You unlock the rare books door.
Action: east
Description:
Computer Lab
This entire room hums with the combined output of several dozen computers. All of them are hopelessly out of date, but at least theyre still good for word processing. A bank of printers on one side of the room frantically churns out paper. You can see a technician here.
Action: west
Description:
Second Floor Stacks
This cavernous room is filled with shelves as far as the eye can see. A doorway to the east is labelled "Computer Room", and the stairwell lies to the north. The door is unlocked but shut.
Action: undo door
Description:
You open the rare books door.
Action: south
Description:
Rare Books Room
The shelves are nearly bare, although there is a complete set of the "New ork Times", a box labeled "Avalon", and several biographies of various computer game authors. The door out is to the north You can see a biography of Graham Nelson here.
Action: take all

Temporally Extended Explanations
Description: Second Floor Stacks
This cavernous room is filled with shelves as far as the eye can see. A doorway to the east is labelled "Computer Room", and the stairwell lies to the north. The door is unlocked but shut.
Action: undo door
Description: You open the rare books door.
Action: south
Description after taking the above action: Rare Books Room The shelves are nearly bare, although there is a complete set of the "New ork Times", a box labeled "Avalon", and several biographies of various computer game authors. The door out is to the north You can see a biography of Graham Nelson here.
...
Description: Rare Books Room
The shelves are nearly bare, although there is a complete set of the "New ork Times", a box labeled "Avalon", and several biographies of various computer game authors. The door out is to the north You can see a biography of Graham Nelson here.
Action: take all
Description after taking the above action: biography of Graham Nelson Taken.
Your score has just gone up by five points.

Table 8: Example game trajectories for *balances* with its temporally extended explanations.

Goal: Examine Pile

Description: Grasslands, near Hut
The grasslands sway over low hills in all directions it is a peaceful wilderness, broken only by this hut and a faint path to the north. You can see a spell book here.
Action: east

Description: Ramshackle Hut
Until quite recently, someone lived here, you feel sure. Now the furniture is matchwood and the windows are glassless. Outside, it is a warm, sunny day, and grasslands extend to the low hills on the horizon.
Action: take inventory

Description: The wooden furniture is already on the floor.
Action: west

Description: Grasslands, near Hut
The grasslands sway over low hills in all directions it is a peaceful wilderness, broken only by this hut and a faint path to the north. You can see a spell book here.
Action: east

Description: Ramshackle Hut
Until quite recently, someone lived here, you feel sure. Now the furniture is matchwood and the windows are glassless. Outside, it is a warm, sunny day, and grasslands extend to the low hills on the horizon.
Action: west

Description: Grasslands, near Hut
The grasslands sway over low hills in all directions it is a peaceful wilderness, broken only by this hut and a faint path to the north. You can see a spell book here.
Action: east

Description: Ramshackle Hut
Until quite recently, someone lived here, you feel sure. Now the furniture is matchwood and the windows are glassless. Outside, it is a warm, sunny day, and grasslands extend to the low hills on the horizon.
Action: examine book

Description: My Spell Book gnusto spell copy a scroll into your spell book. frotz spell cause an object to give off light. yomin spell mind probe. rezrov spell open even locked or enchanted objects.
Action: examine furniture

Description: You see nothing special about the wooden furniture.
Action: west

Description: Grasslands, near Hut
The grasslands sway over low hills in all directions it is a peaceful wilderness, broken only by this hut and a faint path to the north.
Action: north

Description: Pocket Valley
A pleasant pocket valley in the grassy hills, through which a trail runs northtosouth. There is a chestnut horse here, munching on a pile of oats.
Action: examine pile

Temporally Extended Explanations

Description: Ramshackle Hut
Until quite recently, someone lived here, you feel sure. Now the furniture is matchwood and the windows are glassless. Outside, it is a warm, sunny day, and grasslands extend to the low hills on the horizon.
Action: examine book

Description: My Spell Book gnusto spell copy a scroll into your spell book. frotz spell cause an object to give off light. yomin spell mind probe. rezrov spell open even locked or enchanted objects.
Action: examine furniture
Description after the action:
Searching through the furniture, which is good for nothing but firewood now, you come across an old cedarwood box, which you pick up for a closer look. Your score has just gone up by five points.
...

Description: Pocket Valley A pleasant pocket valley in the grassy hills, through which a trail runs north-tosouth. There is a chestnut horse here, munching on a pile of oats.
Action: examine pile

Table 9: Example game trajectories for *zork1* with its temporally extended explanations – part 2.

Goal: Open Window

Description:
Forest Path
This is a path winding through a dimly lit forest.
The path heads northsouth here.
One particularly large tree with some low branches stands at the edge of the path.
Action: go east

Description:
Forest This is a dimly lit forest, with large trees all around.
Action: go south

Description:
Clearing
You are in a small clearing in a well marked forest path that extends to the east and west.
Action: go west

Description:
Behind House
You are behind the white house. A path leads into the forest to the east. In one corner of the house there is a small window which is open.
Action: go west

Description:
Clearing
You are in a small clearing in a well marked forest path that extends to the east and west.
Action: go north

Description:
West of House
You are standing in an open field west of a white house, with a boarded front door. There is a small mailbox here.
Action: go north

Description:
North of House
You are facing the north side of a white house. There is no door here, and all the windows are boarded up. To the north a narrow path winds through the trees.
Action: go east

Description:
Behind House
You are behind the white house. A path leads into the forest to the east. In one corner of the house there is a small window which is slightly ajar.
Action: open window

Temporally Extended Explanations

Description:
Behind House
You are behind the white house. A path leads into the forest to the east. In one corner of the house there is a small window which is slightly ajar.
Action: open window

E Broader Impacts

The ability to explain the reinforcement learning actions in text games has downstream applications beyond understanding how to play text games. Text games are regarded as simplified analogues for systems capable of long-term dialogue with humans, such as in assistance with planning complex tasks, and also discrete planning domains such as logistics. Our work is applicable to provide understanding of domains where change in the world is affected via language. Systems prone to error, both in performing a given task as well as in explaining them, should not be relied upon in more critical applications.