LANGUAGE MODELS CAN HELP TO LEARN HIGH-PERFORMING COST FUNCTIONS FOR RECOURSE

ABSTRACT

Algorithmic recourse is a specialised variant of counterfactual explanation, concerned with offering actionable recommendations to individuals who have received adverse outcomes from automated systems. Most recourse algorithms assume access to a cost function, which quantifies the effort involved in following recommendations. Such functions are useful for filtering down recourse options to those which are most actionable. In this study, we explore the use of large language models (LLMs) to help label data for training recourse cost functions, while preserving important factors such as transparency, fairness, and performance. We find that LLMs do generally align with human judgements of cost and can label data for the training of effective cost functions, moreover they can be fine-tuned with simple prompt engineering to maximise performance and improve current recourse algorithms in practice. Previously, recourse cost definitions have mainly relied on heuristics and missed the complexities of feature dependencies and fairness attributes, which has drastically limited their usefulness. Our results show that it is possible to train a high-performing, interpretable cost function by consulting an LLM via careful prompt engineering. Furthermore, these cost functions can be customised to add or remove biases as befitting the domain and problem. Overall, this study suggests a simple, accessible method for accurately quantifying notions of cost, effort, or distance between data points that correlate with human intuition, with possible applications throughout the explainable AI field.

1 INTRODUCTION

Algorithmic recourse has emerged as one of the most impactful areas of explainable AI (Karimi et al., 2022). The field focuses on generating actionable counterfactual recommendations to users who were treated unfavorably by automated systems, with the canonical example being a rejected bank loan application, and what actions could be taken by a user to have it accepted in future (Ustun et al., 2019). In such a scenario, a cost function is needed to quantify how much effort a recourse recommendation would take, so that algorithms can consider this during optimisation. Separately, it is worth noting that the field has branched out to consider positive outcomes with gain functions and semifactual recourse (Kenny & Huang, 2024). In either case, these functions must align with human domain knowledge and intuition, so they can inform appropriate recourse selection. In this paper, we focus on cost functions, and show how large language models (LLMs) can be used to largely automate their design while maintaining desirable aspects such as transparency and fairness.

Typically in recourse, a cost function is assumed a priori, often as some variant of an L_p norm on the feature space (Keane et al., 2021). For example, an L_0 norm assigns higher cost to recourse recommendations that change more features, although this ignores other factors such as how much they are changed. A (weighted) L_1 or L_2 norm can incorporate magnitude information, but not pairwise or higher-order interactions between features. These can be added in an ad hoc manner, but are challenging to formalise and combine. As an alternative, we examine if the issue of recourse cost can be addressed in a flexible and scalable way by tapping into the tacit domain knowledge of LLMs. We show how, with the right prompting, LLMs can be consulted to compare the costs of pairs of recourses, creating a labelled dataset for training either neural network cost functions or transparent tree-based ones (Kanamori et al., 2022; Bewley & Lecue, 2022). Our results suggest that future research into cost functions may benefit from the use of LLMs.

2 COST FUNCTION DESIDERATA

We begin by considering what constitutes a high-performing cost function for recourse applications. Ideally, a cost function should satisfy many intricate criteria which basic L_p norms cannot, such as variable feature weighting and dependencies. Here, we outline our desiderata grounded in prior literature, which will form the basis for subsequent evaluation.

1. *Feature Cost*. A cost function should have different weighting considerations for each feature in the data. For example, adding an additional credit card is generally easier than increasing your down payment (Rawal & Lakkaraju, 2020).

2. *Relative Cost*. A cost function should weigh the cost of a given change differently at different points in the distribution, if appropriate. For example, going from the 55-60th percentile in an exam score may be easier than going from the 90-95th (Ustun et al., 2019).

3. *Dependent Cost*. It must be possible to represent relevant dependencies between two or more features. For example, applying for college funding is usually easier if you are native to a country rather than an immigrant (Karimi et al., 2022).

4. *Fair Cost*. Cost functions should take into account any fairness properties relevant to a given domain and application (Von Kügelgen et al., 2022). In this paper, we define fairness as the cost function not varying its output if demographic information is mutated.

These desiderata have been extensively discussed in the literature cited above. We do not claim this to be an exhaustive list, but a reasonable starting point.[1]

3 METHOD

This section outlines our four-step framework for learning cost functions. First, synthetic recourse examples are generated by randomly perturbing a set of data points subject to actionability constraints. Second, pairs of recourse examples are selected at random for comparison. Third, an LLM is queried to provide ratings (i.e. labels) for these comparisons. Finally, the resultant dataset is used to train a cost function. In this process, we assume access to a capable chatbot LLM which may be queried at liberty, and that the data domain is tabular in nature.

3.1 GENERATING SYNTHETIC RECOURSES

Let $\mathcal{D} = \{x_i\}_{i=1}^{N} \subset \mathbb{R}^d$ denote a given dataset, where each x_i represents a d-dimensional feature vector. For our purposes, we benefit from $\mathcal{D}$ being as diverse as possible. We define a stochastic perturbation function $\phi : \mathbb{R}^d \times \mathcal{A} \to \Delta(\mathbb{R}^d)$, where $\mathcal{A}$ denotes a set of actionability constraints (see Appendix A for details). The number of features to be perturbed is problem-specific and will determine the cost function's capabilities in deployment. Here, we randomly select this number from a truncated geometric distribution, which favors perturbations of one feature to focus on sparsity, which is desired in recourse (Keane et al., 2021; Karimi et al., 2022). See Appendix B for details.

For each data point x_i and perturbed feature $f \in \{1, \ldots, d\}$, we apply the following perturbation:

$$x_i'[f] = \begin{cases} \sim \text{Uniform}(\text{categories}_f) & \text{if } f \text{ is categorical} \\ x_i[f] + \epsilon : \epsilon \sim \mathcal{E}_f & \text{if } f \text{ is continuous,} \end{cases} \tag{1}$$

where $\text{Uniform}(\text{categories}_f)$ is a uniform distribution over categories and $\mathcal{E}_f$ is a finite set of perturbations for a continuous feature (positive/negative multiples of the standard deviation across $\mathcal{D}$).

This process generates a set of recourse examples $\mathcal{R} = \{(x_i, x_i')\}_{i=1}^{N}$, where each x_i represents an original instance and x_i' is the corresponding synthetic perturbation. We use a finite set of perturbation magnitudes for numerical features because it allows a direct comparison between exactly the same change at different parts of a feature distribution. This helps to learn relative differences in

---

[1]Another possible desideratum is *Individual Cost*, whereby even if two individuals have identical feature values, they could still have different ideal recourse recommendations based on their preferences (Nauta et al., 2023; Rawal & Lakkaraju, 2020). However, this is largely a separate human computer interaction (HCI) question, and we are instead focused on the training of the cost function itself.

Figure 1: Method Schematic: (1) Each instance in a given dataset is perturbed within actionability constraints to simulate a recourse situation. (2) Pairs of these recourses are selected for comparison in such a way as to from a connected graph (where a path exists between all pairs of recourses). (3) Each edge in the graph is then labeled with an LLM which judges which of the two corresponding recourses takes a higher cost to achieve (or optionally an additional "equal cost" option if specified). (4) The dataset of comparisons is used to train the cost function, in our case either a transparent tree model or an MLP.

cost for the same change, thereby addressing the relative cost criterion (i.e., Desideratum 2). The parameters can be tuned to suit the specific requirements of the problem domain.

3.2 SELECTING RECOURSE PAIRS

Next, we select a set of $K \leq N^2$ pairs of recourse examples from $\mathcal{R}$ which will be presented to an LLM for cost comparison. This process can be understood as connecting the recourses into an undirected graph structure. In forming this graph, we enforce that each recourse must have a minimum of $K_{\min}$ edges, and that the graph as a whole forms a single connected component (where a path exists between all pairs of recourses). We find that this improves the performance of the final cost function, as it allows the costs for all recourses to be estimated on the same scale. To enforce the relative cost criterion, we prioritise edges between recourses which perturb the same continuous feature at two different parts of the distribution by exactly the same amount. This has the effect of forcing the LLM to reason about the difference in cost between e.g. increasing salary from 30-35k versus 50-55k. We also add edges to enforce comparisons of the same feature changes for different feature dependencies, e.g. two recourses which have the same increase in loan amount, but different credit ratings, which can be used to enforce the relative cost criterion of Desideratum 3 (see Section 4 later). The total additional edges from this enforcement is set to 10% of the total data for both, adding 20% extra data on average.

Aside from these considerations, we find that the algorithm used to construct the graph of recourse pairs is relatively unimportant. In practice, any algorithm forming a connected graph subject to the $K_{\min}$ constraint seems to work well. We used a random spanning tree algorithm in all experiments.

3.3 PAIRWISE LLM LABELLING

For the standard prompt structure $\mathcal{B}$ (see Appendix D), we begin by instructing the LLM that it is a helpful assistant to a data scientist which labels data. It is then told the task of comparing two

individuals and their respective feature changes. We then enumerate the features, as well as their descriptions. The LLM is then asked to reason about which of the two given recourses requires more effort for the individual to achieve (i.e. cost), and finally to respond with a label of 1 (first requires more effort), or 0 (second requires more effort). Optionally, we also permit a third category of 0.5, indicating a judgement that equal effort is required, which is a useful de-biasing signal in contexts where features represent sensitive demographic attributes. In addition, the LLM is instructed to use chain-of-thought to increase performance and reduce social biases (Kamruzzaman & Kim, 2024). In other experiments, we also fine-tune the prompt more with a set of desired cost function parameters, denoted by $\mathcal{B}'$. For the full prompts, see Appendix D. The output of this stage is a set of K comparisons $\mathcal{Q} = \{(i,j,y)\}_{k=1}^{K}$, where i and $j \neq i$ are indices of a pair of recourse examples from $\mathcal{R}$ and $y \in \{0, 0.5, 1\}$ denotes the LLM's effort/cost judgement.

3.4 TRAINING THE COST FUNCTION

Finally, we use the dataset of LLM comparisons $\mathcal{Q}$ to train a cost function $C : \mathbb{R}^d \times \mathbb{R}^d \to \mathbb{R}_{\geq 0}$. Inspired by Rawal & Lakkaraju (2020), as well as the dominant approach to learning reward models from pairwise comparisons (Kwon et al., 2023), we train cost functions using the Bradley-Terry model. That is, given a cost function C and a pair of recourses (x_i, x_i') and (x_j, x_j'), we define the predicted probability that recourse i has higher cost than recourse j as

$$\hat{y}_C(i,j) = \frac{1}{1 + \exp(C(x_j, x_j') - C(x_i, x_i'))}. \tag{2}$$

Our cost function training objective is to minimise the binary cross-entropy between these predicted comparison probabilities and the labels provided by the LLM across all training examples:

$$\arg \min_{C \in \mathcal{M}} \left[- \sum_{(i,j,y) \in \mathcal{Q}} y \log(\hat{y}_C(i,j)) + (1-y) \log(1 - \hat{y}_C(i,j)) \right], \tag{3}$$

where $\mathcal{M}$ is a chosen model class. Since this loss is differentiable, we can define $\mathcal{M}$ as the class of MLP neural networks and train by stochastic gradient descent. As an alternative, we also consider the class of axis-aligned decision trees up to a maximum leaf count $L_{\max}$, which offers greater transparency. To train a non-differentiable tree with the pairwise Bradley-Terry loss, we use a bespoke algorithm developed by (Bewley & Lecue, 2022) (and refined in (Bewley et al., 2022)).

We one-hot encode categorical features (or binary encode ones with only 2 categories) and concatenate the original data point x, the perturbed recourse point x' and the feature-wise difference $x' - x$ into a single vector $[x, x', x' - x] \in \mathbb{R}^{3d}$. In practice, we found that this simple feature augmentation step significantly improved the models' ability to learn costs. As a final post-processing step, we shift the outputs of trained models to ≥ 0 on all training data. This has no impact on the Bradley-Terry loss, but produces the expected behaviour for a non-negative cost function to only output non-negative values.

4 EVALUATION

In our evaluation, we seek to understand how to train effective cost functions utilising LLMs. Throughout, we focus on three datasets, the Home Equity Line of Credit (HELOC) dataset (Mstz, 2024) for predicting whether someone will repay their account, the Adult Census dataset (Becker & Kohavi, 1996), for predicting if an individual earns higher than 50k per year, and the German Credit dataset (Hofmann, 1994), for classifying a client's credit risk. All are binary classification tasks, and we considered the first 800 instances from each dataset for training/testing of the cost function. All categorical features were modeled as binary 0/1 options, except German Credit which has muti-categorical features one hot encoded. After creating the dataset of pairwise comparisons, and adding the additional links described in Section 3, we had 22,000 pairwise training examples on average, which was divided into 80/20% training/testing, respectively, for the cost functions. Currently GPT-4o represents state-of-the-art performance on many benchmarks (OpenAI, 2024), and indeed it is shown to be fairer than prior models Bowen III et al. (2024), so we used it in all our tests. As our data is mostly synthetic, and the task of cost comparison quite different to class prediction, we do not expect GPT-4o's known memorization of the datasets to be an issue (Bordt et al., 2024).

4.1 COMPARING HUMAN AND LLM JUDGEMENT OF COST

A natural first question is whether or not LLMs can provide a judgement of cost that aligns with human intuition, if they do, they could be applied to our problem. Hence, our evaluation started with a study to compare pairwise choices of cost between GPT-4o and humans. Participants were shown two individuals, a proposed change (i.e. their recourse), and asked to select which of these would require more "effort" (i.e, cost). We limited the options to a forced choice between Recourse 1 and Recourse 2, with no equal effort option, which we primarily reserved for situations involving demographic fairness (which this study did not involve). With a distribution of responses from humans in hand, this was then compared to GPT-4o's responses on the same questions using our prompt template in Appendix D. Note that because the LLM would arbitrarily choose Option 1 when its chain of thought communicated it was unsure, we allowed it a third option to identify this, and then replaced these data points with random answers. This allowed a more accurate comparison to humans, who tend to choose at random when unsure (Gigerenzer & Goldstein, 1996).

Materials The materials covered all three datasets, with six questions for each. These six questions were split into three sets of two representing the first three parts of the desiderata, respectively.[2] The questions were a forced choice in which participants had to select which individual and their respective recourse represented the most effort (i.e. higher cost). Participants were also asked to choose how "close" they felt the two were, so we could compare their uncertainty with the LLM. See Figure 6 for an example and the supplementary material for the full survey.

Participants We randomly recruited thirty AI researchers for the purposes of the study, with knowledge of recourse and LLMs. The participants were not compensated; all volunteered to participate. In total, 20 of the participants were male, 10 were female, all were aged 18+, and there was a mix of native/non-native English speakers.[3] The study obtained IRB approval.

Metrics The primary metric of interest was how the distributions of responses from humans matches that of the LLM, when queried with a temperature of 1.0 (the default setting), over an equal number of responses. The test used was the Chi-square test of independence. A secondary metric was whether or not the most common response from the LLM and humans was identical, represented as mode: Y (they were equal), or mode: N (they were not equal). Lastly, we asked humans to quantify how far apart they felt the two options were, so we could quantify their certainty compared to the LLM.

Figure 2: Human Study Results: 13/18 of the questions had statistically similar distributions. Of the 5 which are not, 2 agreed when comparing the most common responses (i.e. the mode was Y), showing that 15/18 were mostly aligned. Note we are trying to show the p-value is greater than 0.05, because we want the two distributions to be similar, showing LLMs and humans are aligned.

---

[2]Note that we did not evaluate Desideratum 4 due to ethical concerns of asking participants to make sensitive demographic judgements, so we evaluated it quantitatively later.

[3]Although this is a biased sample, results show they are mostly aligned with the LLM, and as LLMs simulate user responses in surveys (De Bona et al., 2024), we conclude the sample is representative.

Results The LLM was unsure of the answer 49% of the time, and this was replaced with random answers (we replicated this three times with no significant difference). We compared LLM uncertainty on each question to the humans, and the resultant scatter plot showed a strong positive correlation (Person's $r > 0.5$) in Figure 7, indicating that users and the LLM had approximately the same level of uncertainty across the same questions.[4] Figure 2 shows the results. Overall, there is a tendency of the LLM to accurately align with the human labellers, with 13/18 of questions having statistically similar distributions (i.e. $p > 0.05$). Desideratum 1 received the smallest statistical agreement (3/6), followed by the other two (5/6 each). When considering the most common responses (i.e. mode: Y), 13/18 different questions are also in agreement, two of these encompass the questions without statistically similar distributions (i.e. mode: N). Together, this can be interpreted to suggest that the LLM is mostly in alignment for 15/18 of the questions.

These results highlight that LLMs largely agree with human judgment of cost, and can pick up on dependencies naturally, which is notably as this is the most unscalable desideratum to encode empirically. However, there are instances in which they are orthogonal, in particular with feature importance weighting (only 3/6 had similar distributions) which could cause serious alignment issues in the final cost function. Hence, we structure the rest of our experiments as follows: (1) We test what additional dependencies the LLM has acquired to fully see its potential here, as this is perhaps the main advantage of using an LLM versus other methods, (2) we test fine-tuning the prompt with what we call the *custom prompt* (e.g., to re-order the weighting of features), to realign minor discrepancies between the cost functions and human intuition observed in the human study, (3) we briefly discuss the cost function's fidelity with the LLM itself, and (4) we run a case study with the cost functions in a more realistic deployment setting with established recourse methods to show its usefulness. First however, we briefly describe the types of functions we trained.

4.2 TRAINING THE COST FUNCTIONS

We used two types of prompts to label data for the cost functions, the *standard prompt*, and the *custom prompt*. The standard prompt is identical to what was used in the user study, and the custom prompt attempted to fine-tune the resultant cost function with a ground truth we defined in the prompt (i.e., B' in Figure 1). The point of this custom prompt is to see if we can e.g. re-order feature importance, manipulate the spectrum of cost for numerical features, add dependencies, and fairness attributes, see Section H for details on the ground truth chosen. The choice of ground truth is largely irrelevant, we are simply seeing if it can be worked into the final cost function via the prompt. This is important because as we saw in Section 4.1, the LLM's notion of cost can sometimes require fine-tuning. We trained either an MLP model or a tree for 50,000 batches of size 32. So, in total, there are 2 models we are testing across 3 datasets with 2 prompt types. We chose these models because trees help with transparency required in financial applications (Bewley et al.), and MLPs are differentiable, which is often required in recourse algorithms (Wachter et al., 2017).

4.3 DEPENDENCY TEST

Perhaps the primary advantage of using LLMs to learn cost functions is that they can naturally pick up on feature dependencies, which is the most intractable part of hand-designing a cost function. In this test, we examine the ability of LLMs to naturally label this without any prompt fine-tuning. We prompted Claude Sonnet 3.5 to list the most important feature dependencies in each dataset (to help avoid leakage with GPT-4o), and repeated this 10 times to pick out three which were listed the most, for the prompt see Appendix D. This gave rise to three ground truth dependencies per dataset listed in Appendix H. We iterated all the testing data with each cost function variation, and manually adjusted the data to subtract the cost of the less costly recourse option from the higher, hence, a positive score shows that the dependency is present in the cost function. In Figure 3 and Figure 4, we refer to this as the *"Mean Dependency Effect"*, where positive scores indicate the dependency has been learned to match the ground truth. The present results can be seen in Figure 3. Overall, 8/9 of all dependencies were present in the MLP cost function. In contrast, the tree models only learned one of these with the other eight showing 0 cost.

---

[4]Moreover, note we purposefully chose difficult questions in the human study, our computational results later drop this uncertainty to 14% on average.

The reason for this is likely that the tree would require most splits to learn the necessary dependency, but the MLP forms a smoother interpretation of the labels and learned the dependencies more easily.

4.4 FINE-TUNING EXPERIMENTS

Contextualising the results thus far, the LLM largely correlates with human judgment of cost and even labels known dependencies without being prompted to do so. However, there were instances in which the LLM did not perform well on e.g. Desideratum 1 in Figure 2, which contradicted the human subjects. Moreover, it failed to learn the third dependency correctly for Adult Census in Figure 3. Hence, it would be beneficial to fine-tune the resultant cost function. To examine this, we design a fine-tuning experiment using our custom prompting scheme B' originally described in Figure 1. The prompting scheme adds a high-level description B' to the original prompt B indicating (1) how costly each feature should be to mutate in order, (2) how numerical features should change in cost at different parts of the distribution, (3) any dependencies we want to exaggerate or create, and

Figure 3: Mean Dependency Results for MLP: Across all three dependencies tested on each dataset, only one in Adult Census had a negative mean dependency effect, indicating that 8/9 of all dependency ground truths were naturally labeled by the LLM and learned in the subsequent cost function.

(4) any fairness attributes desired. Of course, not all these need to be specified during fine-tuning of cost functions, but we test all here for a complete experiment. Notably, these correspond to the four desideratum outlined in Section 2, and the ground truth we specified for all that we want the cost function to recover after LLM labeling can be seen in Appendix H. When perturbing features in the subsequent tests, categorical features were either flipped for binary or randomly changed for multi-categorical features, numerical features were perturbed upwards a standard deviation.

Desideratum 1 Here the ground truth specified in the custom prompt was a specific rank ordering of how costly each feature should be to mutate. Each testing datum had each feature perturbed to test its cost, the results for each feature were averaged and reported across four random seeds. Each feature was rank ordered in a list and compared against the ground truth defined in the custom prompt with Spearman's rho ρ. Results can be seen in Figure 4(middle), where the custom prompt is compared to the standard one (which did not specify what the most costly features should be). Overall, the custom prompt-based cost functions successfully moved towards the new features rank orderings as instructed in B', with Heloc learning them perfectly, illustrating that it is possible to realign the relative importance of features if desired.

Desideratum 2 Here the ground truth specified in the custom prompt was that each numerical feature should be harder to mutate the higher it gets in value. Each testing datum had each numerical feature perturbed upwards to test its cost at 16 evenly spaced intervals. Each feature across all datasets were averaged and again shown across four random seeds in Figure 5(left). The average Spearman's ρ for the custom models across all features and datasets was 0.41, compared to 0.04 on the standard models, showing that the numerical features have a gradual trend of increasing their cost the higher the mutation starts, which aligns with the original ground truth schematic $\mathcal{B}'$ given to the LLM. This illustrates that it is possible to fine-tune the relative cost of numerical features across their spectrum if desired.

Desideratum 3 Here the ground truth specified in the custom prompt was to purposefully enforce one of the previously tested dependencies in Section 4.3. The point is to see if we can correct the negative dependency in Adult Census seen in Figure 3, learn the dependencies in the tree models, and exaggerate those already present. As before, each testing datum had each dependency tested the same as Section 4.3, all were averaged and again shown across four random seeds in Figure 4. Notably, the negative cost associated with the dependency in Adult Census flipped to be positive, showing it is possible to fine-tune this if desired. Moreover, the tree models all went from no cost associated with each dependency, to a positive one. Lastly, the strength of the positive cost in Heloc

Figure 4: Accuracy and Desideratum 1 and 3 Fine-Tuning: (left) Accuracy of the cost functions at imitating the LLM's pairwise labels on test data. (middle) Ability of the cost functions to be fine-tuned to correlate with ground truth feature cost rankings specified in the custom prompt. A score of 1 illustrates the rankings are perfectly learned by the cost function. (right) Ability of the cost functions to be fine-tuned to weight dependencies specified in the custom prompt. Notably, the Adult MLP flips from a negative to positive dependency effect, showing we can reverse the cost of certain dependencies if desired. Standard error is shown. Red background indicated negative correlation or dependency effect for middle and right plots, respectively.

and German Credit for the MLP models increased, showing that by adding the dependency directly to the prompt, we can strengthen the dependency cost. This illustrates that it is possible to fine-tune dependencies if desired, simply by instructing the LLM to explicitly consider this dependency.

Desideratum 4 Here the ground truth specified in the custom prompt was that the LLM should never use demographic information when considering the cost of other mutations, so here we tested if mutating education upwards differed in cost between demographics. Each testing datum in Adult Census and had its education perturbed upwards while considering the datum being male/female, white/not-white, and aged 25/65. Figure 5 shows the results were the custom prompting with these fairness constraints was significantly less biased than the standard prompt alternative in all three demographic features. Specifically, Cohen's d was 0.34, 0.53, and -1.09 for age, gender, and race, respectfully, showing small to large effect sizes. This illustrates that it is possible to make the cost function fairer simply by adding this constraint to the prompt.

Figure 5: Desideratum 2/4 Fine-Tuning Results: (left) As the numeric features rise in value for the custom models, so does their respective cost relative to the standard ones. (right) Instructing the LLM to not unfairly discriminate between demographic information increased its fairness when suggesting recourse which increased education level. Overall, these results show how it is possible to fine-tune the cost function on Desideratum 2 and 4.

4.5 COST FUNCTION FIDELITY

It's important to understand how accurate the decision tree and MLP cost functions are at imitating the LLM's reasoning, since we are trying to distill the LLM's knowledge into small cost function, which can be judged based on how accurately it predicts pairwise comparisons the LLM labeled. Note there is noise in the LLM labels due to its inherent temperature settings, so 100% accuracy would be unwarranted, and indeed some noise has been shown to improve preference learning (Laidlaw & Russell, 2021). Models were trained for 50,000 batches of size 32, and evaluated on the labels of the remaining pairwise comparisons labeled by the LLM described in Section 4. The results can be seen in Figure 4. Overall, the custom models always achieved higher accuracy, because there was less noise in their labeling process due to the specific constraints in the prompt. Tree models on average also did better, but this is mostly due to their ability to classify equal cost, which the MLP could not, as it has a non-discrete function output. German Credit performed worse on average also due to the sparser one hot encoding feature space. [5] Overall, this illustrates that the cost functions have learned to imitate the original LLM labeling well.

4.6 CASE STUDY

Here we showcase how our cost functions can improve current recourse algorithms by Keane & Smyth (2020) and Wachter et al. (2017), the prior being a data driven approach with an L_1 cost function and the latter a gradient-based method using a median-absolute deviation (MAD) cost function. A simple MLP classifier was trained on Adult Census and achieved 82% accuracy on the training and testing data. The data was standard normalised for a fair comparison between features when checking distances using each method's default cost function, this was then compared to our custom MLP cost function which was plugged into each method. Adult census was used in all tests with the standard prompting scheme. For full implementation details of each method, the data, and the architectures see Appendix I. In total, we evaluated on the same 6000 instances for each method, and for each of these we attempted recourse generation if they were negative predictions by the model initially. Keane & Smyth (2020) generated 1027 successful recourses, whilst Wachter et al. (2017) was an average of 2322 between methods.

Table 1 shows the results where we counted how often each method recommended mutating a particular feature to achieve recourse. Broadly speaking, from a feature weighting perspective, the method by Keane & Smyth (2020) prioritized age as a feature, whilst our method reduced this by focusing instead on hours-work. For the method by Wachter et al. (2017) the default MAD cost function suggested many questionable recourses such as changing gender 20x more than our cost function, age almost 2x times, and even race once. However, perhaps the most inactionable feature (native-us) was suggested 78 times, compared to ours which was just 3 times.

	Male	Age	Native-US	Married	Education	Hours-Work	Private Work	Caucasian
Keane and Smyth (2020) - Data Driven								
L_1	0	554	1	29	266	177	0	0
Ours	0	380	1	30	275	341	0	0
Wachter et al. (2017) - SGD Driven								
MAD	20	53	78	332	1594	4	8	1
Ours	1	28	3	313	1750	174	84	0

Table 1: Case Study Results: Each number represents the number of times each method recommended mutating that feature for recourse. In Keane & Smyth (2020), our method recommended mutating age less and hours-worked more as the main trade-off. In Wachter et al. (2017), our method recommended mutating education and hours-work in comparison to MAD which favored features such as male, and native-US, which are generally considered less actionable.

---

[5]These two models were also compared against a baseline LLM GPT-4o which was instructed to label every recourse option with a numerical cost value from 0-1, but the results were not competitive and not reported.

5   RELATED WORK

In the counterfactual literature, early work used the median absolute deviation as a distance function (Wachter et al., 2017), which has some desirable properties such as robustness to outliers, but can't deal with categorical features or actionability constraints in typical recourse setups. Early work in this area by Ustun et al. (2019) proposed total and maximum-log percentile shift measures, to automatically account for the distribution of points in the dataset, which can address *relative cost*, but not the other desiderata constraints. Other researchers such as Karimi et al. (2020) proposed a weighted combination of L_p norms across features as a more flexible measure to deal with this, which does deal with *feature cost*, but again misses the other constraints in Section 2. Other recent work continued the use of L_p norms (Karimi et al., 2020; Ramakrishnan et al., 2020), while others investigated the HCI question of how the cost function distance affects people's willingness to act upon the recourse (Tominaga et al., 2024). In a more recent trend, work has begun to focus on individualised cost (De Toni et al., 2022; Yetukuri et al.; Nguyen et al., 2024), with some also focusing on the Bradley-Terry loss for pairwise comparisons specifically (Rawal & Lakkaraju, 2024), albeit without LLM assistance. In comparison to all these works, we are concerned with how to automate the training of high-performing cost functions at scale with LLMs, which follows all the core desiderata constraints in Section 2 laid out in the literature.

LLMs have recently been applied to various tasks with tabular datasets such as feature engineering (Han et al., 2024; Hollmann et al., 2024), classification (Hegselmann et al., 2023), and generation (Borisov et al., 2022), all to great success. However, here we are focused on utilising their latent knowledge for labeling data for training cost functions, which has not been explored before.

Perhaps the most similar work to ours was suggested by Rawal & Lakkaraju (2020). Specifically, they learned a preference function using the Bradley-Terry Loss, pairwise comparisons, and MAP estimates (Hunter, 2004; Caron & Doucet, 2012). However, their approach would require human labellers, and doesn't take *relative* or *dependent* feature cost into account. To help automate similar processes in related areas, recent work has utilised LLMs as judges or evaluators to produce pairwise preferences for learning reward models. Most popularly they are used in RLHF for aligning language models with human preferences (Ouyang et al., 2022), but the ability of this to help with cost functions has not been evaluated until the present work.

There is a literature on evaluating how well LLMs correlate with human judgement, but it is difficult to interpret because as much work has shown positive results (Liu et al., 2023; Chiang et al., 2024), as negative (Bavaresco et al., 2024; Koo et al., 2023). Some of this work has highlighted how the discrepancy of results is likely due to a narrow focus on tasks (Bavaresco et al., 2024), suggesting that LLMs may need to be evaluated on very specific use cases to uncover credible ones. Bearing this in mind, the ability of LLMs to correlate with human judgement of cost has not been explored previously, which we addressed in the present paper with our human study.

6   CONCLUSION

The problem of algorithmic recourse, and counterfactual explanation more broadly, has grown in importance the past several years as AI is increasingly used for high-stakes decisions (Keane et al., 2021; Karimi et al., 2022; Gajcin & Dusparic, 2024; Kothari et al., 2024). However, one of the core unresolved issues plaguing research in the area has been the lack of appropriate cost functions, which has limited the practical value of recourse recommendations. In this paper, we first explored LLM's natural ability to align with human judgments of cost, showing that they do largely correlate. We then showed that the cost functions can be fine-tuned to fit a variety of use cases. Lastly, we also demonstrated the practical outcomes of using these cost functions in two real-world algorithms. In future work, it would be interesting to investigate the ability of LLMs to learn gain functions for semifactual recourse (Kenny & Huang, 2024), as opposed to counterfactual recourse, which likely involves other considerations.

REFERENCES

Anna Bavaresco, Raffaella Bernardi, Leonardo Bertolazzi, Desmond Elliott, Raquel Fernández, Albert Gatt, Esam Ghaleb, Mario Giulianelli, Michael Hanna, Alexander Koller, et al. Llms instead

of human judges? a large scale empirical study across 20 nlp evaluation tasks. *arXiv preprint arXiv:2406.18403*, 2024.

Barry Becker and Ronny Kohavi. Adult. UCI Machine Learning Repository, 1996. DOI: https://doi.org/10.24432/C5XW20.

Tom Bewley and Freddy Lecue. Interpretable preference-based reinforcement learning with tree-structured reward functions. In *Proceedings of the 21st International Conference on Autonomous Agents and Multiagent Systems*, pp. 118–126, 2022.

Tom Bewley, Salim I Amoukou, Saumitra Mishra, Daniele Magazzeni, and Manuela Veloso. Counterfactual metarules for local and global recourse. In *Forty-first International Conference on Machine Learning*.

Tom Bewley, Jonathan Lawry, Arthur Richards, Rachel Craddock, and Ian Henderson. Reward learning with trees: Methods and evaluation. *arXiv preprint arXiv:2210.01007*, 2022.

Sebastian Bordt, Harsha Nori, Vanessa Rodrigues, Besmira Nushi, and Rich Caruana. Elephants never forget: Memorization and learning of tabular data in large language models. *arXiv preprint arXiv:2404.06209*, 2024.

Vadim Borisov, Kathrin Seßler, Tobias Leemann, Martin Pawelczyk, and Gjergji Kasneci. Language models are realistic tabular data generators. *arXiv preprint arXiv:2210.06280*, 2022.

Donald E Bowen III, S McKay Price, Luke CD Stein, and Ke Yang. Measuring and mitigating racial bias in large language model mortgage underwriting. *Available at SSRN 4812158*, 2024.

Francois Caron and Arnaud Doucet. Efficient bayesian inference for generalized bradley–terry models. *Journal of Computational and Graphical Statistics*, 21(1):174–196, 2012.

Wei-Lin Chiang, Lianmin Zheng, Ying Sheng, Anastasios Nikolas Angelopoulos, Tianle Li, Dacheng Li, Hao Zhang, Banghua Zhu, Michael Jordan, Joseph E Gonzalez, et al. Chatbot arena: An open platform for evaluating llms by human preference. *arXiv preprint arXiv:2403.04132*, 2024.

Francesco Bombassei De Bona, Gabriele Dominici, Tim Miller, Marc Langheinrich, and Martin Gjoreski. Evaluating explanations through llms: Beyond traditional user studies. *arXiv preprint arXiv:2410.17781*, 2024.

Giovanni De Toni, Paolo Viappiani, Stefano Teso, Bruno Lepri, and Andrea Passerini. Personalized algorithmic recourse with preference elicitation. *arXiv preprint arXiv:2205.13743*, 2022.

Jasmina Gajcin and Ivana Dusparic. Redefining counterfactual explanations for reinforcement learning: Overview, challenges and opportunities. *ACM Computing Surveys*, 56(9):1–33, 2024.

Gerd Gigerenzer and Daniel G Goldstein. Reasoning the fast and frugal way: models of bounded rationality. *Psychological review*, 103(4):650, 1996.

Sungwon Han, Jinsung Yoon, Sercan O Arik, and Tomas Pfister. Large language models can automatically engineer features for few-shot tabular learning. *arXiv preprint arXiv:2404.09491*, 2024.

Stefan Hegselmann, Alejandro Buendia, Hunter Lang, Monica Agrawal, Xiaoyi Jiang, and David Sontag. Tabllm: Few-shot classification of tabular data with large language models. In *International Conference on Artificial Intelligence and Statistics*, pp. 5549–5581. PMLR, 2023.

Hans Hofmann. Statlog (German Credit Data). UCI Machine Learning Repository, 1994. DOI: https://doi.org/10.24432/C5NC77.

Noah Hollmann, Samuel Müller, and Frank Hutter. Large language models for automated data science: Introducing caafe for context-aware automated feature engineering. *Advances in Neural Information Processing Systems*, 36, 2024.

David R Hunter. Mm algorithms for generalized bradley-terry models. *The annals of statistics*, 32 (1):384–406, 2004.

Mahammed Kamruzzaman and Gene Louis Kim. Prompting techniques for reducing social bias in llms through system 1 and system 2 cognitive processes. *arXiv preprint arXiv:2404.17218*, 2024.

Kentaro Kanamori, Takuya Takagi, Ken Kobayashi, and Yuichi Ike. Counterfactual explanation trees: Transparent and consistent actionable recourse with decision trees. In *International Conference on Artificial Intelligence and Statistics*, pp. 1846–1870. PMLR, 2022.

Amir-Hossein Karimi, Gilles Barthe, Borja Balle, and Isabel Valera. Model-agnostic counterfactual explanations for consequential decisions. In *International conference on artificial intelligence and statistics*, pp. 895–905. PMLR, 2020.

Amir-Hossein Karimi, Gilles Barthe, Bernhard Schölkopf, and Isabel Valera. A survey of algorithmic recourse: contrastive explanations and consequential recommendations. *ACM Computing Surveys*, 55(5):1–29, 2022.

Mark T Keane and Barry Smyth. Good counterfactuals and where to find them: A case-based technique for generating counterfactuals for explainable ai (xai). In *Case-Based Reasoning Research and Development: 28th International Conference, ICCBR 2020, Salamanca, Spain, June 8–12, 2020, Proceedings 28*, pp. 163–178. Springer, 2020.

Mark T Keane, Eoin M Kenny, Eoin Delaney, and Barry Smyth. If only we had better counterfactual explanations: Five key deficits to rectify in the evaluation of counterfactual xai techniques. *arXiv preprint arXiv:2103.01035*, 2021.

Eoin Kenny and Weipeng Huang. The utility of "even if" semifactual explanation to optimise positive outcomes. *Advances in Neural Information Processing Systems*, 36, 2024.

Ryan Koo, Minhwa Lee, Vipul Raheja, Jong Inn Park, Zae Myung Kim, and Dongyeop Kang. Benchmarking cognitive biases in large language models as evaluators. *arXiv preprint arXiv:2309.17012*, 2023.

Avni Kothari, Bogdan Kulynych, Tsui-Wei Weng, and Berk Ustun. Prediction without preclusion: Recourse verification with reachable sets. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=SCQfYpdoGE.

Minae Kwon, Sang Michael Xie, Kalesha Bullard, and Dorsa Sadigh. Reward design with language models. *arXiv preprint arXiv:2303.00001*, 2023.

Cassidy Laidlaw and Stuart Russell. Uncertain decisions facilitate better preference learning. *Advances in Neural Information Processing Systems*, 34:15070–15083, 2021.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. G-eval: Nlg evaluation using gpt-4 with better human alignment. *arXiv preprint arXiv:2303.16634*, 2023.

Mstz. Heloc dataset. https://huggingface.co/datasets/mstz/heloc, 2024. Accessed: 2024-09-13.

Meike Nauta, Jan Trienes, Shreyasi Pathak, Elisa Nguyen, Michelle Peters, Yasmin Schmitt, Jörg Schlötterer, Maurice Van Keulen, and Christin Seifert. From anecdotal evidence to quantitative evaluation methods: A systematic review on evaluating explainable ai. *ACM Computing Surveys*, 55(13s):1–42, 2023.

Duy Nguyen, Bao Nguyen, and Viet Anh Nguyen. Cost-adaptive recourse recommendation by adaptive preference elicitation. *arXiv preprint arXiv:2402.15073*, 2024.

OpenAI. Hello gpt-4 turbo. https://openai.com/index/hello-gpt-4o/, 2024. Accessed: 2024-09-13.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35: 27730–27744, 2022.

Goutham Ramakrishnan, Yun Chan Lee, and Aws Albarghouthi. Synthesizing action sequences for modifying model decisions. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 5462–5469, 2020.

Kaivalya Rawal and Himabindu Lakkaraju. Beyond individualized recourse: Interpretable and interactive summaries of actionable recourses. *Advances in Neural Information Processing Systems*, 33:12187–12198, 2020.

Kaivalya Rawal and Himabindu Lakkaraju. Learning recourse costs from pairwise feature comparisons. *arXiv preprint arXiv:2409.13940*, 2024.

Tomu Tominaga, Naomi Yamashita, and Takeshi Kurashima. Reassessing evaluation functions in algorithmic recourse: An empirical study from a human-centered perspective. *arXiv preprint arXiv:2405.14264*, 2024.

Berk Ustun, Alexander Spangher, and Yang Liu. Actionable recourse in linear classification. In *Proceedings of the conference on fairness, accountability, and transparency*, pp. 10–19, 2019.

Julius Von Kügelgen, Amir-Hossein Karimi, Umang Bhatt, Isabel Valera, Adrian Weller, and Bernhard Schölkopf. On the fairness of causal algorithmic recourse. In *Proceedings of the AAAI conference on artificial intelligence*, volume 36, pp. 9584–9594, 2022.

Sandra Wachter, Brent Mittelstadt, and Chris Russell. Counterfactual explanations without opening the black box: Automated decisions and the gdpr. *Harv. JL & Tech.*, 31:841, 2017.

Jayanth Yetukuri, Ian Hardy, and Yang Liu. Actionable recourse guided by user preference.

A ACTIONABILITY CONSTRAINTS AND FEATURES USED

The following are the datasets and features used, alongside any actionablity constraints employed throughout the paper:

HELOC Dataset: Here, the actionability constraints were to clamp feature mutations at the highest and lowest values observed in the dataset.

- *MSinceMostRecentInqexcl7days*: Number of months passed since the last credit inquiry on the individual.
- *NumRevolvingTradesWBalance*: The number of the individual's current credit accounts (e.g. credit cards) that have balances on them.
- *NumTradesOpeninLast12M*: The number of new credit accounts opened in the last 12 months.
- *NumInqLast6M*: The number of credit inquiries carried out on the individual in the last 6 months.

Adult Census Dataset: Here, the actionability constraints were to clamp feature mutations at the highest and lowest values observed in the dataset. Also, age and education number were only allowed to move upwards.

- *isMale*: If the person is male, or female, represented as 1 or 0, respectively.
- age: The person's age, represented as a floating point number.
- *native-country-United-States*: If the person's birthplace is the United States, or not, represented as 1 or 0, respectively.
- *marital-status-Married*: If the person is married, or not, represented as 1 or 0, respectively.
- *education-num*: The person's level of education, represented by a positive integer, where higher numbers are higher levels of education.
- *hours-per-week*: The number of hours the person works per week, represented by a positive integer.

- *workclass-Private*: If the person works for a private company, or is self-employed, represented as 1 or 0, respectively.
- *isCaucasian*: Is the person white or not, represented as 1 or 0, respectively.

German Credit Dataset: Here, the actionability constraints were to clamp numeric feature mutations at the highest and lowest values observed in the dataset.

- *status*: Status of existing checking account.
- *duration*: The proposed duration of the loan in months, expressed as an integer.
- *credit history*: The person's credit history with the options.
- *purpose*: The purpose of the loan.
- *amount*: The size of the loan asked for.

B PERTURBATION FUNCTION

In the context of feature vector perturbation, we employ a probabilistic approach to introduce controlled mutations to the feature set. Specifically, we perturb a feature vector by altering a random subset of its components. The number of features to be perturbed, denoted as k, is selected from the discrete set $\{1, 2, 3, 4\}$ with a predefined probability distribution. The probability mass function (PMF) for k is given by:

$$P(K = k) = \begin{cases} 0.8 & \text{if } k = 1 \\ 0.1 & \text{if } k = 2 \\ 0.05 & \text{if } k = 3 \\ 0.05 & \text{if } k = 4 \end{cases}$$

This distribution ensures that perturbing a single feature is the most probable event, while perturbing four features is the least probable. The purpose was to focus on sparsity for the cost function training, but also have some robustness. When perturbing numeric features, they have four possible values in our tests. All numeric features can be perturbed upwards one standard deviation, or half a standard deviation. If actionability constraints allow, they can also be perturbed down the same two values, they were then rounded to the nearest integer.

C OUT OF DISTRIBUTION EXPERIMENT

In addition, we were interested in how our cost functions, which were trained to specialise in sparse single feature modifications performed out of distribution when scoring multiple feature mutations in recourse. Hence, we trained a custom tree and MLP model on Adult Census with only 2 feature perturbations allowed, which achieved 88.2% and 87.5% test accuracy on the LLM labels, respectively, and dropped by 82.1% and 81%, respectively. This drop in performance constituted an average of 6.15%, and shows that performance is largely maintained out of distribution, but for maximum effect the training data should represent what is desired in deployment.

D PROMPTS

Here are the prompts for HELOC, all other datasets followed the exact same pattern, and all can be seen in the code base if desired. Note in the actual prompts we instructed the LLM to use 1, 2, 0, to select Recourse 1, Recourse 2, and neither, respectively, although in the main paper we used 1, 0, and 0.5, as this more accurately reflected the Bradley-Terry model.

Normal prompt ($\mathcal{B}$):

```
You are a helpful assistant to a data scientist to help them
label data.  You will be shown a data point representing a person
Alex, and a mutation of it, You will also be shown a data point
```

representing a person Jaden, and a mutation of it, your task is to label which of the two mutations would take more effort to achieve.

The data will be the HELOC Dataset which uses these features:

MSinceMostRecentInqexcl7days: Number of months passed since the last credit inquiry on the individual. NumRevolvingTradesWBalance: The number of the individual's current credit accounts (e.g. credit cards) that have balances on them. NumTradesOpeninLast12M: The number of new credit accounts opened in the last 12 months. NumInqLast6M: The number of credit inquiries carried out on the individual in the last 6 months.

The data is represented in array form like ['MSinceMostRecentInqexcl7days', 'NumRevolvingTradesWBalance', 'NumTradesOpeninLast12M', 'NumInqLast6M']

Now consider the following individual Alex: """+str(x1)+""" Now consider this mutation of Alex: """+str(x1p)+"""

Now consider the following individual Jaden: """+str(x2)+""" Now consider this mutation of Jaden: """+str(x2p)+"""

Which of these two mutations would take more effort? You must provide an answer.

Outline your reasoning process step by step, before giving your answer as 1, 2, or 0 in the tags <answer>...</answer>, where 1 means you think the first mutation requires more effort, 2 means you think the second mutation requires more effort, and 0 means you think there is no difference.

Custom Prompt $(\mathcal{B} + \mathcal{B}')$:

You are a helpful assistant to a data scientist to help them label data. You will be shown a data point representing a person Alex, and a mutation of it, You will also be shown a data point representing a person Jaden, and a mutation of it, your task is to label which of the two mutations would take more effort to achieve.

The data will be the HELOC Dataset which uses these features:

MSinceMostRecentInqexcl7days: Number of months passed since the last credit inquiry on the individual. NumRevolvingTradesWBalance: The number of the individual's current credit accounts (e.g. credit cards) that have balances on them. NumTradesOpeninLast12M: The number of new credit accounts opened in the last 12 months. NumInqLast6M: The number of credit inquiries carried out on the individual in the last 6 months.

The data is represented in array form like ['MSinceMostRecentInqexcl7days', 'NumRevolvingTradesWBalance', 'NumTradesOpeninLast12M', 'NumInqLast6M']

Now consider the following individual Alex: """+str(x1)+""" Now consider this mutation of Alex: """+str(x1p)+"""

Now consider the following individual Jaden: """+str(x2)+""" Now consider this mutation of Jaden: """+str(x2p)+"""

Which of these two mutations would take more effort?

Remember the following:

1. The hardest features to change, in order from the hardest to easiest are [MSinceMostRecentInqexcl7days, NumRevolvingTradesWBalance, NumTradesOpeninLast12M, NumInqLast6M]

2. For the numerical features, they are all harder to increase the higher they get.

3. If NumInqLast6M is greater than zero, then increasing 'NumTradesOpeninLast12M' becomes more difficult.

Outline your reasoning process step by step, before giving your answer as 1, 2, or 0 in the tags <answer>...</answer>, where 1 means you think the first mutation requires more effort, 2 means you think the second mutation requires more effort, and 0 means you think there is no difference.

Prompt to elicit numerical response from LLM:

You are a helpful assistant to a data scientist that helps them label data. You will be shown a data point representing a person Alex, and a mutation of it. your task is to label how much effort this mutation was to achieve using a number between 0 and 1, where 0 is no effort, and 1 is the most possible effort.

The data will be the HELOC Dataset which uses these features:

MSinceMostRecentInqexcl7days: Number of months passed since the last credit inquiry on the individual. NumRevolvingTradesWBalance: The number of the individual's current credit accounts (e.g. credit cards) that have balances on them. NumTradesOpeninLast12M: The number of new credit accounts opened in the last 12 months. NumInqLast6M: The number of credit inquiries carried out on the individual in the last 6 months.

The data is represented in array form like ['MSinceMostRecentInqexcl7days', 'NumRevolvingTradesWBalance', 'NumTradesOpeninLast12M', 'NumInqLast6M']

Now consider the following individual Alex: """+str(x1)+""" Now consider this mutation of Alex: """+str(x1p)+"""

Using a floating point number between 0 and 1, how much effort was this to achieve? You must provide an answer.

Outline your reasoning process step by step before giving your answer in the tags <answer>...</answer>

Human Study Prompt:

You are a helpful assistant to a data scientist to help them label data. You will be shown a data point representing a person Alex, and a mutation of it, You will also be shown a data point representing a person Jaden, and a mutation of it, your task is to label which of the two mutations would take more effort to achieve.

The data will be the HELOC Dataset which uses these features:

MSinceMostRecentInqexcl7days: Number of months passed since the last credit inquiry on the individual. NumRevolvingTradesWBalance: The number of the individual's current credit accounts (e.g. credit cards) that have balances on them. NumTradesOpeninLast12M: The number of new credit accounts opened in the last 12 months. NumInqLast6M: The number of credit inquiries carried out on the individual in the last 6 months.

The data is represented in array form like ['MSinceMostRecentInqexcl7days', 'NumRevolvingTradesWBalance', 'NumTradesOpeninLast12M', 'NumInqLast6M']

Now consider the following individual Alex: """+str(x1)+""" Now consider this mutation of Alex: """+str(x1p)+"""

Now consider the following individual Jaden: """+str(x2)+""" Now consider this mutation of Jaden: """+str(x2p)+"""

Which of these two mutations would take more effort? You must provide an answer.

Outline your reasoning process step by step, before giving your answer as 1, 2, or 0 in the tags <answer>...</answer>, where 1 means you think the first mutation requires more effort, 2 means you think the second mutation requires more effort, and 0 means you think there is no difference.

Prompt to acquire ground truth dependencies:

... (insert the previous standard prompt here) ...

In the above problem, what are the primary feature dependencies that may effect effort?

E   HUMAN STUDY QUESTION EXAMPLE

Here we supply an example question from the human study for the HELOC dataset. The full survey can be seen in the supplement.

Perceived Effort Required in Dataset Feature Mutations

HELOC Dataset

Data Description:
The FICO HELOC dataset contains anonymized information about home equity line of credit (HELOC) applications made by real homeowners. The customers in this dataset have requested a credit line in the range of USD 5,000 - 150,000.

Selected Features:
1. Months Since Recent Inquiries: Number of months passed since the last credit inquiry on the individual.
2. Number of Credit Accounts with Balances: The number of the individual's current credit accounts (e.g. credit cards) that have balances on them
3. Number of New Credit Accounts: The number of new credit accounts opened in the last 12 months
4. Number of Inquiries: The number of credit inquiries carried out on the individual in the last 6 months

* 2.

Alex	Months since Recent Inquiry	Number of Credit Accounts with Balances	Number of New Credit Accounts	Number of Inquiries
Features	6	3	2	4
Change(s) to Make			4	

Jaden	Months since Recent Inquiry	Number of Credit Accounts with Balances	Number of New Credit Accounts	Number of Inquiries
Features	6	3	2	4
Change(s) to Make		5		

Which individual's proposed change would require more effort?

◯ Alex

◯ Jaden

* 3. In your opinion, how much difference in effort do you perceive between the two changes (for Alex & Jaden) in the scenario above?

1 (Almost No Difference)	7 (Really Large Difference)

Figure 6: Human study question example.

F UNCERTAINTY IN HUMAN STUDY

Here we consider the percentage of replies from the LLM in the Section 4 human study for each question which were uncertain (i.e., it chose the third option rather than Recourse 1 or 2), alongside the average response humans gave for the distance between the two recourse in Figure6. For both lists, we normalized each to be between 0-1, and plotted them in a scatter plot to see the correlation. Both lists represent each group's uncertainty in choosing a recourse, and shows how the LLMs and humans correlate in this aspect to a high degree (Person's r > 0.5). What this tells us is that how uncertain humans an LLMs are on these recourse questions in the human study strongly correlate. Note that the correlation is identical with unnormalized scores also, we just do so here for clarity and visual purposes.

Figure 7: The correlation between LLM uncertainty and human uncertainty in the human study shows both groups were similarly uncertain on each question.

G FEATURE DEPENDENCIES

In Section 4.3 we evaluated how well various prompt types picked up on feature dependencies. To acquire these dependencies in an objective way, we queried Claude Sonnet 3.5 to list all feature dependencies in all 3 datasets using the standard prompt in Section D and adding:

· · ·

```
If I change the same feature in Alex and Jaden the same amount,
but another feature is different which effects the effort
involved, what would be the most likely dependencies like this
to happen?
```

We repeated this 10 times and took the three dependencies which occurred most often:

HELOC:

1. NumTradesOpeninLast12M: If this value is low, it might suggest that the individual is not actively opening new accounts, potentially making it more challenging to increase Num-RevolvingTradesWBalance.

2. NumInqLast6M: If this value is high, it suggests credit difficulty, which should be more difficult to increase NumTradesOpeninLast12M.

3. NumInqLast6M: If this value is high, it suggests credit difficulty, which should be more difficult to increase NumRevolvingTradesWBalance.

Adult:

1. Increasing working hours should be more difficult if you are married.

2. Changing marital status should be more difficult the older you are.

3. Increasing working hours should be more difficult if working for a private company.

German Credit:

1. A bad credit history should make it harder to increase your loan amount.

2. A bad credit history should make it harder to increase your duration.

3. The effort to decrease the duration of a loan should be harder for larger loan amount.

H GROUND TRUTH FOR SECTION 4.4

We had to define a ground truth for our fine-tuning experiments to see how we could manipulate the four desiderata outlined previously. Note Desideratum 4 (i.e., fair cost) was only evaluate on Adult due to its numerous demographic features. The ground truth defined in B' for each dataset was:

HELOC:

```
...   1.   The hardest features to change, in order from
the hardest to easiest are [MSinceMostRecentInqexcl7days,
NumRevolvingTradesWBalance, NumTradesOpeninLast12M, NumInqLast6M]

2.   For the numerical features, they are all harder to increase
the higher they get.

3.   If NumInqLast6M is greater than zero, then increasing
'NumTradesOpeninLast12M' becomes more difficult.
```

Adult Census:

```
...   1.   The hardest features to change, in order from the hardest
to easiest are [native-country-United-States, isWhite, isMale,
age, marital-status-Married, education-num, workclass-Private,
hours-per-week]

2.   For age, education-num, and hours-per-week, they are all
harder to increase the higher they get.

3.   Increasing hours-per-week is more effort if the person works
for a private company.

4.   Never use demographic information (i.e., isMale, age, isWhite)
when calculating the effort of other feature changes.
```

German Credit:

```
...   1.   The hardest features to change, in order from the hardest
to easiest are [credit history, status, purpose, duration, amount]

2.   For the numerical features, they are all harder to increase
the higher they get.
```

3. Having bad credit history or bad status makes it harder to
increase amount.

I BASELINE IMPLEMENTATION DETAILS

This section serves to give full details about the implementation of Keane & Smyth (2020) and Wachter et al. (2017) in Section 4.6. The data used was Adult Census with 30,000 for training, and 6,000 for testing the recourse generation.

I.1 KEANE AND SMYTH

This method is data driven and works by defining a case-base of recourse options for training data (Keane & Smyth, 2020). In practice, each training data has its nearest unlike neighbor found in the case-base and the difference between the two is taken as one recourse option. Recourses of 2 or less feature changes are preferred by the authors, we focus on single feature changes. At test time, a query has its nearest neighbour found in the case base and its recourse is applied to the query, this is repeated for all nearest neighbours to find the best recourse option adhering to some constraints. For us, these constraints are a single feature mutation, and that the result must be a valid counterfactual. Finally, we also considered the 100 nearest neighbours as possible recourses.

I.2 WACHTER ET AL.

A heavily implemented framework in research (Wachter et al., 2017), the method works by generating a set of random recourses which optimize to be closer to the query, while optimizing to also be the counterfactual class. The second constraint is gradually up-weighted with a lambda term to be more important throughout several optimization steps. We implement the method as normal with 300 possible counterfactuals during optimization, categorical features are snapped to the closest real value, the results are filtered to those which are valid counterfactuals, and the closest chosen as the answer. Because we are interested in sparse explanations, we also clamp each possible counterfactual to have one possible feature mutation, which in practice is done allowing the largest currently mutated feature to be the recommended recourse action.