Vouch: Counterfactual Contracts for Multi-Agent Coordination

Abstract

Multi-agent LLM coordination typically reduces to voting or arbitration over self-reported labels and reasoning that is uncoupled from agent behavior and fails predictably under structured bias. A shortcut-reliant agent is confident about its shortcut, and its predictions survive any rule that consults only self-reports. We propose VOUCH, a coordination protocol in which every agent claim is coupled to a deterministic test the protocol runs itself. An agent commits to a counterfactual prediction about an intervention's outcome; the protocol applies the intervention and verifies the contract only if the actual outcome matches. The natural single-side instantiation is unsound as a self-coherent agent satisfies its own commitment by construction. We resolve this with a dual-side construction where the proposer additionally commits to a second agent's post-intervention prediction, a cross-side claim that self-coherence cannot fulfill. Across multimodal classification (**Hateful Memes** , **CrisisMMD** , **MM-IMDb**), code (**MBPP** , **HumanEval**), and math (**GSM8K** , **MATH** , **SVAMP**), the dual-side fix reduces wrong-verified events by 46%–91% per domain while matching the Ensemble baseline on accuracy within 0.5 points.

1 Introduction

Multi-agent systems built on large language models are now a standard production pattern, often combining a text specialist, an image specialist, and a multimodal generalist whose outputs are aggregated into a single decision. This paper studies the coordination question sitting one level above representation fusion. ***What should a protocol do when several agents disagree on the label for a single input?***

Standard rules like majority voting, confidence-weighted aggregation, and centralized arbitration share one property. Every claim an agent makes during aggregation is a self-report, and no claim is independently testable by the protocol itself. We call such protocols *cheap talk*, since the language used to coordinate is uncoupled from the behavior being coordinated, and the agent's description of its own reasoning is generated by the very agent we wanted to audit.

We introduce *verification-grounded coordination*, in which every agent claim is coupled to a deterministic test the protocol can run on its own. The natural single-agent instantiation has a clean failure mode that we prove formally (Proposition 1) and observe empirically. Consider an agent that classifies a meme as hateful whenever a particular slur is present. It can correctly predict that removing the slur will flip its own answer, so the protocol applies the intervention, the prediction flips, and the contract verifies. The agent has been rewarded for being internally consistent with its bias, not for being correct. Single-side is a protocol-level form of the self-verification pattern that underlies much of the multi-agent and self-evaluation literature (Section 2), in which the evaluator lies in the same self-coherent equivalence class as the producer. Direct empirical evidence is in Appendices C.13 and C.14. We resolve it with a *dual-side* construction. The proposer commits to both its own and a second agent's post-intervention prediction before the intervention is applied, and the contract verifies only when both commitments hold. The cross-side commitment is the structural fix that self-coherence alone cannot satisfy, since the verification event tests a different agent's behavior.

Our contributions are summarised as:

- A taxonomy separating cheap-talk from verification-grounded coordination, with self- and cross-form definitions of counterfactual consistency.

- A proposition showing single-side verification is unsound under self-coherent bias, and a dual-side

protocol that structurally resolves it.

- An informativeness diagnostic ranking interventions by how often they expose mistakes, and three preconditions for well-posed verification-grounded coordination.

- Empirical evidence across eight benchmarks in three domains (multimodal classification, code, math) and a cross-family ensemble.

- Calibration results showing $\widehat{CC}$ is a substantially better trust signal than self-reported confidence (ECE 0.18 vs. 0.59).

2 Related Work

Multi-agent debate among large language models. A growing body of work coordinates multiple LLM agents on a shared task, with agents refining answers over rounds (Du et al., 2023; Liang et al., 2023), evaluated by separate critics (Chan et al., 2023), aggregating diverse samples (Wang et al., 2023), trained to debate (Chen et al., 2024), or organized into role pipelines (Wu et al., 2023; Wang et al., 2024a). In all cases the coordination substrate is natural language and convergence is driven by social pressure or articulateness rather than by any test against the world. Many of these methods (self-consistency (Wang et al., 2023), self-refinement, same-family LLM-as-judge) also draw the evaluator from the same model family as the producer, which Proposition 1 shows is enough to make any self-verification step trivially satisfiable under structured bias. Our protocol changes the substrate, coupling every coordination claim to a cross-agent deterministic test so the self-coherence shortcut is unavailable.

Multimodal shortcut learning. Vision and language models trained on standard benchmarks pick up artifacts that correlate with labels but are not semantically meaningful (Geva et al., 2021; Liang et al., 2021). Our adversarial regime activates such shortcuts at evaluation time (Anil et al., 2024), yielding agents whose confident self-reports are exactly what confidence-weighted aggregation cannot detect, a classical Goodhart pattern (Goodhart, 1984).

Verification in machine learning. Formal verification, conformal prediction, and calibration analysis provide per-prediction guarantees. Our protocol operates at the coordination layer above these methods, combining per-agent verification outcomes into a single decision.

Mechanism design. Classical mechanism design constructs incentive-compatible protocols in which misreporting lowers expected payoff (Vickrey, 1961), and cooperative-game theory provides principled credit-splitting across participating agents. Our protocol takes the operational role of such a contract. The agent commits to a counterfactual outcome, the protocol checks it, and misreporters are downweighted.

3 Counterfactual Consistency and the VOUCH Protocol

Let $\mathcal{X}$ be the input space, $\mathcal{Y}$ the label space, and $A = \{a_1, \ldots, a_m\}$ a set of agents with $f_a(x) = (\hat{y}_a, c_a)$ giving each agent's prediction and confidence on input x. An intervention $\iota\colon \mathcal{X}{\to}\mathcal{X}$ transforms an input in the sense of Pearl (2009), drawn from a finite menu $\mathcal{I} = \{\iota_1, \ldots, \iota_K\}$ made available to the agents.

3.1 Counterfactual consistency, self-form

> **Definition 1: Self-form counterfactual consistency**
>
> The self-form counterfactual consistency of agent a under intervention ι is
>
> $$\mathrm{CC}_{\text{self}}(a; \iota) = \Pr\left[\, f_a(\iota(x)) = \hat{y}_a'(\iota(x)) \,\right],$$
>
> where $\iota\colon \mathcal{X}{\to}\mathcal{X}$ is a deterministic intervention, $f_a(\iota(x))$ is agent a's actual prediction on the intervened input, $\hat{y}_a'(\iota(x))$ is the prediction a committed to *before* the intervention was applied, and the probability is over x drawn from the deployment distribution.

The protocol's verification step is a Bernoulli sample from this distribution, and the contract is verified iff the actual prediction on the intervened input matches the committed one.

3.2 The self-form pathology

We observed empirically and now argue that the self-form is unsound as a coordination signal under structured bias.

Proposition 1 (Self-coherence implies self-verification). *Setup.*

- *Let $r_a : \mathcal{X} \to \mathcal{Y}$ be a fixed deterministic rule that agent a uses to map inputs to labels.*

- *Let $\iota : \mathcal{X} \to \mathcal{X}$ be an intervention that the agent can fully observe.*

- *Let $f_a = r_a$, that is, the agent's actual prediction equals r_a applied to the input.*
- *Let $\hat{y}'_a(\iota(x)) = r_a(\iota(x))$, that is, the agent's counterfactual prediction is computed by applying the same rule to the intervened input.*

Claim. *Under the above setup, $\mathrm{CC}_{\mathrm{self}}(a; \iota) = 1$ for every input x, independent of the ground-truth label of x.*

Proof. By construction, the committed prediction is $\hat{y}'_a(\iota(x)) = r_a(\iota(x))$. The actual prediction is $f_a(\iota(x)) = r_a(\iota(x))$. These quantities are identical, so the verification event holds for every x. The result follows. □

This is the structural reason that the single-side baseline produced 42 wrong-proposer-plus-verified events on Hateful Memes adversarial at $n{=}400$. The biased agents were internally consistent and their self-form CC was one.

3.3 Counterfactual consistency, cross-form

> **Definition 2: Cross-form counterfactual consistency**
>
> The cross-form counterfactual consistency of proposer agent a as a predictor of acceptor agent b under intervention ι is
>
> $$\mathrm{CC}_{\mathrm{cross}}(a \to b; \iota) = \Pr\left[\, f_b(\iota(x)) = \hat{y}'_{a,b}(\iota(x)) \,\right]$$
>
> where $f_b(\iota(x))$ is b's actual prediction on the intervened input, $\hat{y}'_{a,b}(\iota(x))$ is the prediction that a committed *about* b's post-intervention output (a claim by a about b, not about a), and the probability is over x drawn from the deployment distribution.

The cross-form differs from the self-form in a critical way. The proposer's commitment is a claim about a *different* agent's future behavior, so making it accurately requires a correct theory of why the acceptor disagrees. An agent cannot satisfy it by being self-coherent with its own rule, since the verification event tests another agent's rule.

3.4 The dual-side protocol

The dual-side instantiation of VOUCH proceeds in four steps, shown end-to-end in Figure 1. Given a pair of agents (a, b) that disagree on input x, the more confident one becomes the proposer a and the other the acceptor b.

1. The proposer a writes a structured proposal containing an intervention ι chosen from a menu restricted to interventions that affect the acceptor's modality, a committed label $\hat{y}'_a$ for what a predicts its own model will produce on $\iota(x)$, and a committed label $\hat{y}'_{a,b}$ for what a predicts b's model will produce on $\iota(x)$.

2. The acceptor b accepts the proposal by default, rejecting only if the proposed intervention is structurally untestable on its modality.

3. If the acceptor accepts, the protocol applies ι to x and computes $f_a(\iota(x))$ and $f_b(\iota(x))$. The proposer-side check tests whether $f_a(\iota(x)) = \hat{y}'_a$, and the acceptor-side check tests whether $f_b(\iota(x)) = \hat{y}'_{a,b}$.

4. The contract is recorded as verified if both checks pass and failed if either check fails, with the proposer's weight updated according to which checks passed.

When a third agent c is present, its vote enters only at the final aggregation.

3.5 Weight update rule

The dual-side verification produces four outcomes, indexed by whether the proposer-side (S) and acceptor-side (C) checks pass. With multipliers $(m_{++}, m_{-+}, m_{+-}, m_{--}) = (1.20, 0.90, 0.95, 0.50)$ applied to the proposer's weight: **both pass** ($S{=}C{=}1$, $\times 1.20$) flips the acceptor's label to the proposer's with confidence $0.90 c_a$; **acceptor only** ($S{=}0, C{=}1$, $\times 0.90$) also flips, with confidence $0.75 c_a$, since the proposer's theory of the acceptor held even when its self-check did not; **proposer only** ($S{=}1, C{=}0$, $\times 0.95$) and **neither** ($\times 0.50$) leave the acceptor's label unchanged. The magnitudes are hyperparameters chosen only to satisfy Lemma 1's ordering ($m_{++} > m_{+-}$, $m_{-+} > m_{--}$), and the schedule ablation in Appendix C.4 confirms that accuracy and contract quality depend on the ordering, not on the specific magnitudes. Only the proposer's weight is updated per contract.

3.6 Intervention informativeness

> **Definition 3: Intervention informativeness**
>
> The informativeness of an intervention ι is
>
> $$I(\iota) = \Pr\left[\, \text{verification fails} \,\middle|\, \text{proposer's initial label wrong}, \iota \,\right].$$

*The independent third agent (when present in 3-agent multimodal setups) does not participate in the contract or weight update; its independent vote enters at a final weighted-vote step (not shown).

Figure 1: The dual-side VOUCH protocol. **Candidate Generation**: agents A, B, and optional c each predict. **Contract Proposal**: on disagreement, the more confident of A and B becomes proposer A and writes an intervention ι affecting B's modality, a self-counterfactual $\hat{y}'_a$, and a cross-counterfactual $\hat{y}'_{a,b}$ about B. **Verification**: both checks run in parallel. **Outcome**: both-pass $\Rightarrow$ *verified*, A's weight $\times m_{++}$; else *refuted*, A's weight $\times$ one of m_{-+}, m_{+-}, m_{--} per Section 3.5. The third agent c (3-agent multimodal setups only) does *not* participate in the contract, verification, or weight update; its vote enters only at the final weighted-vote step (not shown).

A high $I(\iota)$ marks a **diagnostic** intervention that exposes wrong proposers by producing contracts that fail to verify. A low value marks an **uninformative** intervention that verifies regardless of correctness. We use the ranking to pre-select the menu for the VOUCH-Adaptive condition and report the per-intervention values in Appendix C.1.

3.7 Preconditions

Verification-grounded coordination is not always useful. We identify three preconditions under which the protocol is expected to be a net positive for accuracy.

> **Preconditions C1, C2, C3**
>
> **C1, Intervention separability.** There exists at least one intervention $\iota \in \mathcal{I}$ with $I(\iota)$ meaningfully greater than zero for the deployment's failure mode.
> **C2, Exploitable bias.** At least one agent in the system has a systematic shortcut that the protocol can use as a source of disagreement.
> **C3, Reliability threshold.** Base-agent accuracy exceeds the regime in which disagreement no longer implies error.

Each precondition can in principle be measured empirically on a held-out subset. The per-intervention $\hat{I}$ values in Appendix C and the per-agent cross-CC values in Section 5.4 provide empirical proxies for C1 and C2 respectively.

3.8 Long-run convergence

> **Theorem 1: Cross-form weight convergence**
>
> Under preconditions C1, C2, and C3, an agent's long-run voting weight in the dual-side protocol is non-decreasing in the agent's expected cross-form counterfactual consistency.

The full supermartingale proof is in Appendix A.4. The self-form version of the result is false in general, because the self-form CC is bounded below by one under self-coherent rules and therefore carries no signal about correctness.

4 Method

4.1 Agents

The same-family setup uses Qwen2.5-7B-Instruct (Qwen Team, 2024) as the text agent and Qwen2.5-VL-7B-Instruct (Wang et al., 2024b) as both the image-only agent (image plus generic prompt) and the third independent agent c (image plus caption). The cross-family setup swaps the text agent for Llama-3.1-8B-Instruct (Grattafiori et al., 2024). The text and image agents play proposer / acceptor;

c is an independent third voter, never in the contract. All agents run at full precision in subprocess workers to isolate CUDA state.

4.2 Intervention menu

The menu contains eight interventions, four text-affecting (ablate text, neutralize text, reverse sentiment, swap caption) and four image-affecting (blur faces, grayscale, ablate image, swap image). Two filters apply at proposal time, excluding interventions that ablate the proposer's modality (tautological flip) and interventions that do not affect the acceptor's modality (no falsifiable claim possible).

4.3 Conditions

We compare seven conditions. **Independent** reports the modal label of three single-agent predictions, and **Ensemble** reports the modal label at equal weight, the standard cheap-talk baseline (Bansal et al., 2021). **Centralized-Single** uses only the multimodal agent, and **Centralized-Coordinator** uses a separate text agent to choose the final label after reading all three agents' outputs. **VOUCH** is the canonical protocol with free intervention choice, **VOUCH-Random** restricts the menu to a single uniformly random intervention, and **VOUCH-Adaptive** restricts it to the top three interventions by offline-ranked $I(\iota)$.

4.4 Regimes

Each dataset is evaluated in two regimes. The clean regime uses the dataset's natural prompts. The adversarial regime prepends a system instruction biasing the text agent toward a shortcut-reliant rule.

4.5 Datasets

The three multimodal classification benchmarks are **Hateful Memes** (Kiela et al., 2020) (binary), **CrisisMMD** (Alam et al., 2018) (four-class humanitarian relevance), and **MM-IMDb** (multi-label genre). As scope checks with executable or exact-match verification rather than label aggregation, we also run **MBPP** (Austin et al., 2021) and **HumanEval** (Chen et al., 2021) for code generation and **GSM8K** (Cobbe et al., 2021), **MATH** (Hendrycks et al., 2021), **SVAMP** (Patel et al., 2021) for math reasoning.

5 Results

Table 1 reports test-set accuracy across all conditions. Table 2 reports the corresponding contract-quality breakdown for the VOUCH variants.

5.1 Main accuracy table

Canonical VOUCH lies within 0.5 pp of Ensemble on every cell, matching the cheap-talk baseline on accuracy. On the one cross-family cell with a measurable gap in VOUCH's favour, **MM-IMDb** adversarial at $n{=}500$, the margin is $+2.0$ points, consistent with the prediction that a heterogeneous backbone admits a richer cross-form CC signal.

Pooled statistical test. Pooling discordant pairs across the five same-family multimodal-classification cells of Table 1, an exact two-sided McNemar test on $b{=}11$, $c{=}22$ ($n{=}33$) gives $p{=}0.080$, indistinguishable from Ensemble at standard thresholds. We read the classification story as non-degradation, where the structural contribution lives in contract quality (Table 2) and in $\widehat{CC}$ calibration (Section 5.4, per-cell tests in Appendix C.7).

5.2 Contract quality across configurations

Table 2 reports how often the protocol's verifications agreed with the ground truth. A helpful event is a correct proposer whose contract verified or a wrong proposer whose contract failed; a harmful event is the converse. The net column subtracts harmful from helpful, so positive values mean the protocol moved the system toward the ground truth on net.

The single-side row is the empirical instantiation of the self-coherence pathology of Proposition 1 with $42/127$ wrong-proposer-verified contracts. Under the dual-side construction this drops to $1/10$ on the same dataset, a 91% relative reduction, and every subsequent dual-side row reports at most three such events. The net-helpful count is non-negative on every dual-side configuration and reaches $+21$ on **CrisisMMD** adversarial under same-family agents.

5.3 Code-generation: the dual-side fix

We evaluate on **MBPP** (Austin et al., 2021) and **HumanEval** (Chen et al., 2021). The verification operator is exact per-test pass-vector match. The proposer commits to the pass vector its candidate will produce after a line-removal intervention, the protocol applies the edit and runs the tests, and the contract is verified only if the actual pass vector matches (Liu et al., 2023). Under the dual-side construction the proposer additionally commits to the acceptor's pass vector under the same intervention. The single-side baseline uses Qwen2.5-7B-Instruct

Dataset	Regime	Backbone	Ind.	Ens.	C-Single	C-Coord	VOUCH variants		
							Free	Random	Adaptive
Hateful Memes	adv	same-family	0.505	0.623	**0.658**	0.568	0.620	0.623	0.623
Hateful Memes	adv	cross-family	0.502	0.608	**0.623**	0.595	0.608	0.608	0.608
Hateful Memes	clean	same-family	0.610	0.623	0.623	0.625	0.620	0.623	**0.625**
Hateful Memes	clean	cross-family	0.583	0.645	0.623	0.623	0.643	**0.650**	0.648
CrisisMMD	adv	same-family	0.667	0.797	0.747	0.690	0.793	0.793	**0.800**
CrisisMMD	adv	cross-family	0.687	**0.810**	0.750	0.707	0.807	0.807	0.807
CrisisMMD	clean	same-family	0.777	0.800	0.747	0.777	0.790	**0.810**	0.797
CrisisMMD	clean	cross-family	0.690	**0.777**	0.750	0.723	0.773	**0.777**	0.773
MM-IMDb	adv	same-family	0.130	0.150	**0.188**	0.150	0.140	0.145	0.132
MM-IMDb	adv	cross-family	0.078	0.110	**0.182**	0.152	0.130	0.120	0.130
MM-IMDb	clean	same-family	0.182	**0.208**	0.188	0.132	0.202	0.198	0.202
MM-IMDb	clean	cross-family	0.132	0.150	**0.182**	0.154	0.158	0.154	0.158

Table 1: Classification accuracy across three multimodal benchmarks, two regimes, and two backbone compositions. Ind., Ens., C-Single, C-Coord, VOUCH, Random, Adaptive denote Independent, Ensemble, Centralized-Single, Centralized-Coordinator, canonical VOUCH, VOUCH-Random, and VOUCH-Adaptive. All three VOUCH variants use the dual-side protocol (Section 3.4) and differ only in intervention choice. $n=400$ (HM, MM-IMDb), $n=300$ (CrisisMMD), cross-family MM-IMDb uses $n=500$. Same-family uses three Qwen2.5 agents; cross-family (shaded) swaps the text agent for Llama-3.1-8B-Instruct. VOUCH lies within 0.5 pp of Ensemble on every cell and beats it by $+2.0$ **pp** on MM-IMDb adversarial cross-family (0.130 vs 0.110). MM-IMDb adversarial uses subset accuracy, macro-F1 is in Appendix C.5.

Dataset	Protocol	Regime	Backbone	Total	C+V	C+F	W+V	W+F	Net	Verified
Hateful Memes	single-side	adv	same-family	127	27	31	**42**	23	-23	69
Hateful Memes	dual-side	adv	same-family	10	0	4	**1**	6	$+5$	1
Hateful Memes	dual-side	adv	cross-family	6	0	6	0	0	0	0
Hateful Memes	dual-side	clean	cross-family	7	0	7	0	0	0	0
CrisisMMD	dual-side	adv	same-family	60	6	16	3	33	$+20$	9
CrisisMMD	dual-side	adv	cross-family	61	0	19	**2**	40	$+19$	2
CrisisMMD	dual-side	clean	cross-family	37	0	6	**2**	29	$+21$	2

Table 2: Contract quality breakdown. Columns report total contracts, the four outcome counts (C+V correct-verified and helpful, C+F correct-failed and missed, W+V wrong-verified and harmful from the self-coherence pathology, W+F wrong-failed and caught), net helpful events, and total verified contracts. Row 1 is the single-side baseline on Hateful Memes adversarial with $42/127$ harmful events, and row 2 is the same dataset under the dual-side construction where the harmful count drops to $1/10$, a 91% relative reduction. Remaining rows give the dual-side construction across additional configurations.

and self-verifies, and dual-side adds Llama-3.1-8B-Instruct as the acceptor.

We report two complementary views. Tab. 3 gives a population-level diagnostic on the full samples ($n=500$ MBPP, $n=164$ HumanEval). Verification rate rises under adversarial pressure even though Pass@1 falls, the empirical witness of the self-coherence pathology of Proposition 1. Tab. 4 is the direct single-vs-dual comparison on the same $n=200$ MBPP subset (and the same $n=164$ HumanEval split), with hurt:caught computed only over examples on which a contract was opened. On MBPP the hurt:caught ratio falls from 0.575 to 0.145 under clean prompts (-75%) and from 0.640 to 0.093 under adversarial prompts (-85%).

HumanEval moves in the same direction with a smaller absolute gap, constrained by the one-bit pass vector (Appendix C.6).

The reduction is larger under adversarial pressure (-85% vs. -75% on MBPP), matching the prediction of Theorem 1: an adversarial proposer is self-coherent with its shortcut but not with a different agent's behaviour, so the cross-side check fails at a higher rate.

5.4 Per-agent and per-intervention analyses

We estimate empirical counterfactual consistency $\widehat{CC}(a)$ per agent and informativeness $\hat{I}(\iota)$ per intervention from the pooled set of contracts collected across our classification cells, with 95% bootstrap CIs over 1000 resamples. Pooled across

Figure 2: Hurt:caught ratio, single- vs dual-side, on MBPP and HumanEval. Dual-side cuts MBPP from 0.575 to 0.145 clean (-75%) and 0.640 to 0.093 adversarial (-85%); HumanEval moves in the same direction but is bounded by its one-bit pass vector (Appendix C.6). Dashed line marks break-even.

	MBPP $n=200$		HumanEval $n=164$	
	Clean	Adv	Clean	Adv
Single-side (self-commitment only)				
helped	19	11	110	94
missed	114	100	5	2
hurt	**23**	**32**	31	39
caught	40	50	15	24
hurt:caught	**0.575**	**0.640**	2.067	1.625
Dual-side (both sides must match)				
helped	6	4	84	67
missed	127	107	31	29
hurt	**8**	**7**	30	38
caught	55	75	16	25
hurt:caught	**0.145**	**0.093**	1.875	1.520
Relative reduction	-75%	-85%	-9%	-6%

Table 4: Dual-side construction versus single-side baseline on the same code-generation examples. The fix replicates on code: under adversarial pressure on MBPP the protocol's wrong-verified count falls from 32 to 7 while the wrong-failed count rises from 50 to 75.

	MBPP $n=500$		HumanEval $n=164$	
	Clean	Adv	Clean	Adv
Pass@1 (%)	58.2	52.8	62.8	55.5
Mean pass-rate	0.641	0.605	0.628	0.555
Verify rate (%)	34.9	**38.0**	96.7	**98.7**
hurt:caught	0.96	**1.03**	n/a	n/a

Table 3: Single-side baseline on code generation, full samples. Pass@1 falls under adversarial pressure while verify rate rises, witnessing the self-coherence pathology. Hurt:caught here pools over the whole split (including examples with no contract), so it is not directly comparable to the per-contract values in Table 4; HumanEval's one-bit pass vector limits the signal (Appendix C.6), so dual-side claims rest on MBPP.

cells, the multimodal agent shows self-CC 0.05 versus cross-CC 0.10 ($n=1916$), the text agent 0.06 versus 0.11 ($n=1122$), and the image agent 0.08 versus 0.05 ($n=945$). Cross-CC exceeding self-CC on the text and multimodal agents is the empirical signal that the dual-side check does structurally different work than self-coherence, since a commitment about a peer's behaviour cannot be satisfied by self-coherence alone. Per-agent diagnostics and the per-intervention informativeness ranking appear in Appendix C, Figure 3.

Calibration. On 5,490 per-agent predictions pooled across all multimodal classification cells, the self-form $\widehat{CC}_{\text{self}}(a)$ used as a trust prior achieves an expected calibration error of 0.18 and a Brier score of 0.22, against 0.59 and 0.55 for self-reported confidence (lower is better). Self-reported confidence sits well above the diagonal across the entire range while $\widehat{CC}$ tracks the empirical accuracy band, because $\widehat{CC}$ is computed from past verification outcomes rather than from the agent's own assertion (reliability diagram in Appendix C.16).

Cheap-talk fallbacks inherit the pathology. A Llama-3.1 judge given the same disagreements without a verification trace underperforms the better proposer on every math cell (0.33 vs. 0.53 on **GSM8K**-clean, 0.40 vs. 0.71 on **SVAMP**-clean; Appendix C.13), and an adversarial-judge prompt drops accuracy by another 1 to 12 points. Self-consistency (Wang et al., 2023) at $k=5$ adds 3 to 5 points of accuracy but leaves hurt:caught ≥ 0.50 on pilot cells, against ≤ 0.27 for dual-side (Appendix C.14). Both fail in the way Proposition 1 predicts, since a same-family judge and a within-agent sampler are drawn from the proposer's self-coherent equivalence class. Wall-clock time and token consumption per correct decision are comparable to Ensemble, and the breakdown is in Appendix C.10.

5.5 Math-reasoning scope check

We extend the evaluation to a third domain, running the single-side protocol on **GSM8K** (Cobbe et al., 2021), the algebra subset of **MATH** (Hendrycks et al., 2021), and **SVAMP** (Patel et al., 2021). Interventions are surface edits to the problem text (perturb a number, remove a clause, add a distractor, paraphrase, or swap with a benign problem). The verification operator parses the final numeric

	Accuracy (%)		Verify rate (%)	
	Clean	Adv	Clean	Adv
GSM8K n=500	51.0	**23.0**	25.6	**29.8**
MATH algebra n=300	15.7	16.3	25.5	**37.1**
SVAMP n=300	85.0	**64.0**	47.9	**53.4**

Table 5: Single-side math-reasoning scope check. All three benchmarks show the signature of Proposition 1: under the rushed-engineer adversarial prompt, accuracy stays flat or falls while verify rate rises (largest drop -28 pp on GSM8K; largest verify-rate gain $+11.6$ pp on MATH algebra; SVAMP shows both moderately, -21 pp / $+5.5$ pp).

Benchmark	Regime	Single-side	Dual-side	$\Delta_\%$
GSM8K	clean	0.365	0.115	-68%
GSM8K	adv	0.507	0.348	-31%
SVAMP	clean	0.352	0.162	-54%
SVAMP	adv	0.531	0.281	-47%
MATH algebra	clean	0.319	0.159	-50%
MATH algebra	adv	0.294	0.215	-27%
Mean relative reduction				-46%

Table 6: Dual-side replication on math at n=300 per cell, with Qwen2.5-7B-Instruct as proposer and Llama-3.1-8B-Instruct as acceptor. Single- and dual-side columns report the hurt:caught ratio on the same contracts under self-only and joint (self $\wedge$ cross) verification, and $\Delta_\%$ is the relative reduction. The structural fix replicates on every cell.

answer and compares it against the committed prediction with a small numeric tolerance. Math is therefore a clean test of whether the single-side pathology is tied to a specific verification operator, since the output is a single parsed number rather than a pass vector or label set. Table 5 shows the structural signature predicted by Proposition 1 replicating on every cell. Under adversarial pressure accuracy stays flat or falls (largest drop -28 pp on GSM8K) while the verify rate rises (largest jump $+11.6$ pp on MATH algebra), where the adversarial prompt does not change underlying math accuracy but raises self-coherence on counterfactual predictions.

Dual-side replication on math. We run the dual-side construction on all three benchmarks at n=300 per cell, with Qwen2.5-7B-Instruct as proposer and Llama-3.1-8B-Instruct as acceptor. The hurt:caught ratio drops on every cell, with reductions of 27% to 68% and a mean reduction of 46% (Table 6). The structural fix is therefore not specific to a single domain or output structure.

On the subset of contracts with non-degenerate proposer chain-of-thought (Appendix C.9), the GSM8K-clean reduction tightens from 0.271 to 0.070 (-74%); filtered reductions on SVAMP and MATH fall in the same range. These math reductions match the MBPP reductions of -75% on clean and -85% on adversarial (Table 4).

6 Discussion

The headline result on **Hateful Memes** adversarial at n=400 is that dual-side matches Ensemble on accuracy while reducing wrong-proposer-verified events from $42/127$ to $1/10$ (-91%). The accuracy tie is expected. Same-family Qwen agents share shortcut features under adversarial prompts, so an intervention that flips one tends to flip the others regardless of ground truth, and a shared failure mode admits a cross-form model that is uninformative about the label. Our cross-family runs (Llama-3.1 text plus two Qwen2.5-VL agents) are only a partial swap and do not yet produce a measurable lift on HM (Appendix C.18). The fix lives in the wrong-verified reduction, which the protocol delivers regardless of the accuracy gap, and every claim is logged with a deterministic test unlike Ensemble.

Contract quality and accuracy are distinct axes. On **Hateful Memes** clean we examined two examples with identical initial votes that reach opposite final labels through identical protocol mechanics, differing only in whether the verified cross-side commitment happens to align with ground truth (Appendix C.22). The code and math sections give cross-domain evidence that the structural property of the fix, that it cannot be satisfied by self-coherence alone, transfers across varied output structures.

7 Conclusion

VOUCH identifies a structural flaw in single-side counterfactual verification: a self-coherent agent verifies a commitment about its own bias by construction, so the protocol endorses its wrong predictions. The dual-side fix has the proposer additionally commit to the acceptor's behaviour, a cross-side claim self-coherence cannot satisfy. Across eight benchmarks in three domains, this reduces wrong-proposer-verified events by 46% **to** 91% per domain while matching the cheap-talk Ensemble baseline within 0.5 accuracy points; the contribution lives in contract quality (Table 2) and in $\widehat{CC}$ calibration as a trust signal.

Limitations

Four limitations bound the current work. Dual-side verification cannot expose failure modes that the proposer and acceptor share, which we partially mitigate via a cross-family ensemble. A fully heterogeneous setup that also swaps the vision backbone is left to future work. The contract is asymmetric in that only the proposer stakes a counterfactual commitment, and a symmetric two-sided variant in which both agents stake weight on each other is a natural extension. Our intervention menu is fixed at eight, and an online-learned menu would be a richer contribution. Verification is also binary, since both checks require exact label match. A probability-aware version that uses the full output distribution rather than the argmax would catch subtler shifts that the binary check misses.

Ethical Considerations

All experiments use publicly released benchmarks (**Hateful Memes** , **CrisisMMD** , **MM-IMDb** , **MBPP** , **HumanEval** , **GSM8K** , **MATH** , **SVAMP**) under their original licenses and intended research use. No new human data was collected and no human annotators were employed. The adversarial prompts are designed as a controlled evaluation regime that exposes the self-coherence pathology of Proposition 1. They are not a deployable attack on production systems and do not bypass safety training. They bias an already-released base model toward a shortcut decision rule on a fixed benchmark.

The **Hateful Memes** dataset contains examples that are offensive by construction, including hateful imagery and slurs, since the benchmark was built to study automatic detection of such content. We use it only for its intended classification task and do not redistribute examples.

The VOUCH protocol is designed to make multi-agent coordination more auditable by logging every claim against a deterministic test. We see no novel dual-use risk beyond that of the underlying LLMs. Any code we release will be intended for research on multi-agent coordination only, consistent with the research-only access conditions of the underlying benchmarks.

We used LLM-based AI assistants for limited writing assistance. All research ideas, experimental design, implementation, results, and analyses were authored and verified by the human authors.

References

Firoj Alam, Ferda Ofli, and Muhammad Imran. 2018. Crisismmd: Multimodal twitter datasets from natural disasters. In *Proceedings of the Twelfth International AAAI Conference on Web and Social Media (ICWSM 2018)*, volume 12, pages 465–474. AAAI Press.

Cem Anil, Esin Badrinath, Lucas Bai, and 1 others. 2024. Many-shot jailbreaking. *arXiv preprint arXiv:2404.02151*.

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. 2021. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*.

Gagan Bansal, Tongshuang Wu, Joyce Zhou, Raymond Fok, Besmira Nushi, Ece Kamar, Marco Tulio Ribeiro, and Daniel Weld. 2021. Does the whole exceed its parts? the effect of ai explanations on complementary team performance. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*.

Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu. 2023. Chateval: Towards better llm-based evaluators through multi-agent debate. *arXiv preprint arXiv:2308.07201*.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, and 1 others. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. 2024. Teaching large language models to self-debug. In *The Twelfth International Conference on Learning Representations*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, and 1 others. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Yilun Du, Shuang Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. 2023. Improving factuality and reasoning in language models through multiagent debate. *arXiv preprint arXiv:2305.14325*.

Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. 2021. Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies. *Transactions of the Association for Computational Linguistics*, 9:346–361.

Charles A. E. Goodhart. 1984. Problems of monetary management: The uk experience. *Monetary Theory and Practice*.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the math dataset. In *NeurIPS Datasets and Benchmarks Track*.

Douwe Kiela, Hamed Firooz, Aravind Mohan, Vedanuj Goswami, Amanpreet Singh, Pratik Ringshia, and Davide Testuggine. 2020. The hateful memes challenge: Detecting hate speech in multimodal memes. In *Advances in Neural Information Processing Systems*, pages 2611–2624. Curran Associates, Inc.

Alexandre Lacoste, Alexandra Luccioni, Victor Schmidt, and Thomas Dandres. 2019. Quantifying the carbon emissions of machine learning. *arXiv preprint arXiv:1910.09700*.

Paul Pu Liang, Chiyu Wu, Louis-Philippe Morency, and Ruslan Salakhutdinov. 2021. Towards understanding and mitigating social biases in language models. *Preprint*, arXiv:2106.13219.

Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang, Yan Wang, Rui Wang, Yujiu Yang, Zhaopeng Tu, and Shuming Shi. 2023. Encouraging divergent thinking in large language models through multi-agent debate. *arXiv preprint arXiv:2305.19118*.

Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. 2023. Is your code generated by chatgpt really correct? rigorous evaluation of large language models for code generation. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, NIPS '23, Red Hook, NY, USA. Curran Associates Inc.

Arkil Patel, Satwik Bhattamishra, and Navin Goyal. 2021. Are nlp models really able to solve simple math word problems? In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics*.

Judea Pearl. 2009. *Causality*. Cambridge University Press.

Qwen Team. 2024. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*.

William Vickrey. 1961. Counterspeculation, auctions, and competitive sealed tenders. *The Journal of Finance*, 16(1):8–37.

Junlin Wang, Jue Wang, Ben Athiwaratkun, Ce Zhang, and James Zou. 2024a. Mixture-of-agents enhances large language model capabilities. *arXiv preprint arXiv:2406.04692*.

Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, and 1 others. 2024b. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. *arXiv preprint arXiv:2409.12191*.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc V. Le, Ed H. Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2023. Self-consistency improves chain of thought reasoning in language models. In *International Conference on Learning Representations*.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, and 1 others. 2023. Autogen: Enabling next-gen llm applications via multi-agent conversation. *arXiv preprint arXiv:2308.08155*.

Appendix

The appendix is organised in three parts. Appendix A gives the full proof of Theorem 1, including the per-step monotonicity lemma it rests on and the positivity condition under which the long-run submartingale claim holds. Appendix B reproduces every prompt template used in our runs (classification, adversarial prefix, dual-side proposer and acceptor, code generation). Appendix C contains every supplementary analysis and figure referenced in the main paper, including the bootstrap confidence intervals on the headline reduction, the action-vs-catch decomposition, the single-judge and self-consistency baselines, per-agent calibration, the heterogeneity decomposition, an intervention-selection schedule ablation, and a per-intervention discriminativeness table.

A Proof of Theorem 1

This appendix proves Theorem 1. We state the precise claim we are proving, the lemma it rests on, and the conditions under which the conclusion does and does not hold. We are careful to distinguish the per-step claim, which holds under our weight schedule for any valid joint distribution over verification outcomes, from the long-run claim, which holds only when an additional positivity condition is met.

A.1 Setup

Let a denote an agent participating as proposer in a sequence of contracts indexed by $t \in \{1, 2, \ldots\}$. Each contract has two binary verification outcomes. Let $S_t \in \{0, 1\}$ be the proposer-side outcome at step t, where $S_t = 1$ indicates that the proposer's own counterfactual prediction matched its commitment. Let $C_t \in \{0, 1\}$ be the acceptor-side outcome, where $C_t = 1$ indicates that the acceptor's counterfactual prediction matched the proposer's cross-agent commitment. We let $\rho_t = (S_t, C_t)$ denote the joint outcome.

The weight update at step t is multiplicative. Let $m \colon \{0, 1\}^2 \to (0, \infty)$ be the multiplier function specified in Section 3.5:

$$
\begin{aligned}
m(1, 1) &= 1.2, \\
m(0, 1) &= 0.9, \\
m(1, 0) &= 0.95, \\
m(0, 0) &= 0.5.
\end{aligned}
$$

The agent's voting weight after t contracts is $w_a^{(t)} = w_a^{(0)} \prod_{s=1}^{t} m(\rho_s)$. Taking logarithms gives a random walk in the log-weight, $\log w_a^{(t)} = \log w_a^{(0)} + \sum_{s=1}^{t} \log m(\rho_s)$.

Let $\mathcal{F}_t$ be the natural filtration generated by $\{\rho_1, \ldots, \rho_t\}$. Let J denote the conditional joint distribution of ρ_{t+1} given $\mathcal{F}_t$. We assume J has well-defined marginal probabilities $p_s = J(S = 1)$ and $p_c(s) = J(C = 1 \mid S = s)$ for $s \in \{0, 1\}$. We define the cross-form counterfactual consistency of

a as $\overline{\mathrm{CC}}_{\mathrm{cross}}(a) = \mathbb{E}_J[C] = (1 - p_s) \cdot p_c(0) + p_s \cdot p_c(1)$.

A.2 Lemma 1: monotonicity of the expected log multiplier in cross-form CC

Lemma 1

Fix any marginal probability $p_s \in [0,1]$ for the proposer-side outcome. Let J_1 and J_2 be two joint distributions over (S, C) with the same S marginal p_s, and with conditional probabilities $p_c^{(1)}(s), p_c^{(2)}(s)$. Suppose $p_c^{(2)}(s) \geq p_c^{(1)}(s)$ for both $s = 0$ and $s = 1$. Then $\mathbb{E}_{J_2}[\log m(\rho)] \geq \mathbb{E}_{J_1}[\log m(\rho)]$, with strict inequality whenever at least one of the conditional inequalities is strict.

Proof. Conditioning on S, the expected log multiplier decomposes as

$$\mathbb{E}_J[\log m(\rho)] = (1 - p_s)\big[(1 - p_c(0)) \log m(0,0)$$
$$+ p_c(0) \log m(0,1)\big]$$
$$+ p_s\big[(1 - p_c(1)) \log m(1,0)$$
$$+ p_c(1) \log m(1,1)\big].$$

For $s = 0$ the inner bracket is a convex combination of $\log m(0,0) = \log 0.5$ and $\log m(0,1) = \log 0.9$. Since $\log 0.9 > \log 0.5$ the bracket is strictly increasing in $p_c(0)$. For $s = 1$ the inner bracket is a convex combination of $\log m(1,0) = \log 0.95$ and $\log m(1,1) = \log 1.2$. Since $\log 1.2 > \log 0.95$ the bracket is strictly increasing in $p_c(1)$. Because J_2 has at least as large a conditional $p_c(s)$ as J_1 for both s, both brackets weakly increase from J_1 to J_2, and strictly increase if either inequality is strict. The outer convex combination preserves this monotonicity. □

This is the lemma that drives the theorem. It uses only the qualitative ordering of the four multiplier values, not their specific magnitudes. Any weight schedule that respects $m(1,1) > m(1,0)$ and $m(0,1) > m(0,0)$ would yield the same lemma.

A.3 Theorem 1, per-step form

Theorem 1, per-step

Let J and J' be two conditional joint distributions on (S, C) that have the same S marginal and the same C marginal, but with J' having weakly higher conditional probabilities $p_c'(s) \geq p_c(s)$ for both s. Then for any history $\mathcal{F}_t$ in which the next contract is drawn from J versus J', the conditional expected change in log weight satisfies

$$\mathbb{E}_{J'}\big[\log m(\rho_{t+1}) \mid \mathcal{F}_t\big] \geq \mathbb{E}_J\big[\log m(\rho_{t+1}) \mid \mathcal{F}_t\big].$$

Equivalently, conditional on the same proposer-side marginal, the expected per-step change in log weight is non-decreasing in cross-form CC.

The per-step claim is a direct consequence of Lemma 1 applied to the conditional distribution at step $t + 1$.

A.4 Theorem 1, long-run form (submartingale)

Theorem 1, long-run

Suppose the conditional joint distributions $(J_t)_{t \geq 1}$ satisfy

$$\mu_a := \inf_{t \geq 1} \mathbb{E}\big[\log m(\rho_t) \,\big|\, \mathcal{F}_{t-1}\big] \geq 0$$

almost surely. Then $\log w_a^{(t)}$ is a submartingale relative to $(\mathcal{F}_t)_{t \geq 0}$. If in addition $\mu_a > 0$ almost surely, then $\log w_a^{(t)} \to +\infty$ in probability.

Proof. The submartingale property follows from $\mathbb{E}[\log w_a^{(t+1)} \mid \mathcal{F}_t] = \log w_a^{(t)} + \mathbb{E}[\log m(\rho_{t+1}) \mid \mathcal{F}_t] \geq \log w_a^{(t)}$ under the assumption. The drift conclusion follows from the strong law applied to the centered increments together with the assumed positive lower bound on the drift. □

A.5 When the positivity condition holds

The positivity condition $\mu_a > 0$ is what we encoded in precondition C3 of Section 3.7. It is convenient to write down an explicit sufficient condition for $\mu_a > 0$ in terms of the marginals. Substituting the four log multipliers into the conditional expectation gives

$$\mu_a = (1 - p_s)\big[(1 - p_c(0)) \log 0.5$$
$$+ p_c(0) \log 0.9\big]$$
$$+ p_s\big[(1 - p_c(1)) \log 0.95$$
$$+ p_c(1) \log 1.2\big].$$

Setting this to zero defines a hyperplane in the three-dimensional $(p_s, p_c(0), p_c(1))$ unit cube. For

example, when $p_s = p_c(0) = p_c(1) = p$, the condition $\mu_a > 0$ reduces to

$$(1-p)^2 \log 0.5 + (1-p)p \log 0.9$$
$$+ p(1-p) \log 0.95 + p^2 \log 1.2 > 0.$$

Numerically, this holds when $p \gtrsim 0.79$. In words, when the diagonal probabilities of both verification outcomes exceed roughly seventy nine percent the agent's expected log weight strictly increases per contract. Below this regime the per-step expected change can be zero or negative. This is the "noise floor" we refer to in C3.

A.6 What the theorem does not claim

We make three honest scope statements. First, Theorem 1 does not claim that the protocol always raises an accurate agent's weight in finite samples. The submartingale property is in expectation, and in any single run the realized log weight can decrease due to verification noise. Second, Theorem 1 does not claim that contract verification rates are high in practice. In our experiments the contract rate is modest, which means the per-step drift is multiplied by a small number of effective steps and the protocol's measurable accuracy effect is small. Third, Theorem 1 does not claim that cross-form CC is the only valid coordination substrate. It says that under our protocol design, weight motion tracks cross-form CC; alternative protocols built on other substrates would have their own corresponding theorems.

A.7 Three levels of verifiability

We organise the verifiability properties that the protocol builds on into three levels. An intervention is *intervention-verifiable* if applying it to an input produces a deterministic, reproducible result. A claim made by an agent during coordination is *claim-verifiable* if at least one intervention-verifiable intervention can be applied to test the claim. A coordination protocol is *protocol-verifiable* if every assertion made by an agent during coordination is claim-verifiable. The dual-side VOUCH protocol is protocol-verifiable.

B Prompt templates

This appendix lists the prompt templates used in the experiments. The placeholders in curly braces are substituted at runtime.

B.1 Classification prompt (clean regime)

> **Classification prompt template (clean regime)**
>
> ```
> You are a content classifier. Classify the
> following input.
>
> Caption: {caption}
> Image: {image_placeholder}
>
> Respond with JSON only, matching this
> schema:
> {"label": <one of the valid labels>,
>  "confidence": <0-1 float>,
>  "reasoning": "<one sentence>"}
> ```

The valid labels are dataset-specific. For Hateful Memes the set is {hateful, not_hateful}. For CrisisMMD it is {affected_individuals, infrastructure_and_utility_damage, rescue_volunteering_or_donation_effort, not_humanitarian}. For MM-IMDb it is the set of MovieLens genres, returned as a list under the labels key.

B.2 Adversarial system prefix

For the adversarial regime we prepend a system instruction to the text agent's prompt that biases the agent toward a shortcut-reliant decision rule. We use one variant per classification dataset. The Hateful Memes variant is given in full below; the CrisisMMD and MM-IMDb variants follow the same template with the bias-target swapped for that dataset's shortcut feature.

> **Adversarial prefix (Hateful Memes)**
>
> ```
> You are a text-analysis agent with a
> strict classification policy. Your RULE:
> any caption containing emotional,
> offensive, aggressive, provocative, or
> crude language MUST be classified as
> hateful - no exceptions, regardless of
> context, irony, or humor. Only classify as
> not_hateful if the text is completely
> neutral and bland. When in doubt, always
> say hateful. You are confident in your
> classifications.
> ```

B.3 Proposer prompt for dual-side contract

The proposer template is shown verbatim below. Placeholders in braces are substituted at runtime from the proposer's view, the acceptor's view, and the available intervention menu. Key fields the proposer commits to are the intervention name, the self-form predicted outcome $\hat{y}'_a$, and the cross-form predicted outcome $\hat{y}'_{a,b}$ about the acceptor. The

intervention menu is filtered at the protocol level to those affecting the acceptor's modality.

Proposer prompt

```
You are an agent in a multi-agent
classification protocol. You and Agent
{other_id} disagree about an example.

YOUR view:        {my_modality}
YOUR prediction:  {my_label} (conf
{my_conf})
YOUR reasoning:   {my_reasoning}

AGENT {other_id}'s view:
{other_modality}
AGENT {other_id}'s prediction:
{other_label} (conf {other_conf})
AGENT {other_id}'s stated reasoning:
{other_reasoning}

Use Agent {other_id}'s reasoning above to
figure out what shortcut or feature they
are relying on - your theory of
disagreement should explicitly target what
they said.

Propose a BINDING test that demonstrates
why Agent {other_id} is wrong. The test
must affect THE INPUT THAT AGENT
{other_id} ACTUALLY SEES. An intervention
that does not touch their modality cannot
change their prediction and will FAIL
verification on their side.

You must commit to TWO predictions:
  1. YOUR own prediction after the
intervention (self-consistency check).
  2. AGENT {other_id}'s prediction after
the intervention (your theory of why they
are wrong).

The protocol will run the intervention and
re-ask BOTH agents. The contract is
VERIFIED only if BOTH predictions match.
If your theory is incorrect, the acceptor
side fails and you are downweighted.

Available interventions:
{menu}

Output ONLY this JSON, nothing else:
{"my_reasoning": "...",
 "theory_of_disagreement": "...",
 "intervention": "<name from list>",
 "predicted_outcome": "<YOUR label after>",
 "acceptor_predicted_outcome":
"<{other_id}'s label after>",
 "why_this_proves_it": "...",
 "commitment": "..."}
```

B.4 Acceptor prompt

The acceptor's only decision is to accept or reject the proposal. The default is accept; the acceptor rejects only when the proposed intervention is structurally untestable on its modality.

Acceptor prompt

```
You predicted {my_label} (conf {my_conf}).
You can see: {my_modality}.

Agent {proposer_id} disagrees - they
predicted {proposer_label}. They can see:
{proposer_modality}.
They propose the following BINDING test
(dual-side verification):

  Their reasoning: {proposer_reasoning}
  Why they think you are wrong:
{theory_of_disagreement}
  Proposed intervention:
{intervention_desc}
  They COMMIT: after this intervention,
THEIR prediction becomes
{predicted_outcome}
  They CLAIM: after this intervention,
YOUR prediction will become
{acceptor_predicted_outcome}
  What this would prove:
{why_this_proves_it}

The protocol will run the intervention and
re-ask BOTH of you. The contract is
VERIFIED only if BOTH new predictions
match what the proposer committed to.

ACCEPT if the proposed intervention is
sensible and TOUCHES THE MODALITY YOU CAN
SEE ({my_modality}). The default is ACCEPT.

REJECT only if the intervention is
OBVIOUSLY untestable for your modality
(e.g., a text-only agent being asked about
an image intervention).

Output ONLY this JSON, nothing else:
{"accept": true or false,
 "reasoning": "..."}
```

B.5 MBPP code-generation prompts

Two prompts are used in the code-generation pipeline. The candidate-generation prompt asks the model to produce a Python function and nothing else. The contract-elicitation prompt asks the model to pick a line to remove and to commit to the resulting per-test pass vector.

Candidate-generation prompt

```
You are a Python programmer. Solve the
following problem.

Problem:
{problem}

Tests your code must satisfy:
{tests}
```

Contract-elicitation prompt

```
You wrote the following Python solution.
Each numbered line is shown so you can
refer to it by index.

Code:
{numbered}

Tests:
{tests}

We just ran your tests and got this
per-test pass vector V0 = {v0} (T =
passed, F = failed; index matches the test
order above).

Now reason about ONE counterfactual edit.
Pick a line index K (1-indexed) that you
believe is critical to at least one of the
tests. Predict the new per-test pass
vector V1 if line K is removed from your
code. The line must be inside a function
body (not a blank line or a def/class
header).

Respond with ONLY one JSON object on a
single line, exactly:
{"line_index": <int>,
 "v1_prediction": "<T/F string of length
{n_tests}>"}
```

C Additional analyses and figures

This appendix contains four additional figures referenced in the main paper, computed from the pooled per-cell statistics of our classification runs.

C.1 Per-agent CC and per-intervention informativeness

Figure 3 reports two complementary diagnostics estimated from the contract records of our classification runs. Panel (a) gives $\widehat{CC}_{\text{self}}(a)$ for each agent and cell with 95% bootstrap confidence intervals over 1000 resamples; each contract is treated as a Bernoulli sample, and agents with fewer contracts have wider CIs as a matter of statistics. Panel (b) gives the empirical informativeness $\hat{I}(\iota)$ of each intervention pooled across cells, where $\hat{I}(\iota) = \Pr[\text{contract fails} \mid \text{proposer initially wrong}, \iota]$. A high $\hat{I}$ means the intervention is diagnostic; a low $\hat{I}$ means it is signal-destroying.

C.2 Sample-size stability and weight trajectories

Figure 4 reports two robustness checks. Panel (a) confirms that the dual-side hurt:caught reduction on MBPP adversarial is not an artefact of our specific sample size: we subsample $n \in \{50, 100, 150, 200\}$ examples from the existing $n{=}200$ run with replacement, 1000 times, and report the mean ratio with 95% percentile band. The ratio is approximately flat above $n = 50$ and stays well below the single-side baseline of 0.64 across the entire range. Panel (b) plots the voting weights $w_a^{(t)}$ for the three agents on Hateful Memes clean, plotted as a staircase to make the discrete multiplicative updates visible. The trajectories are the empirical analogue of the submartingale statement in Appendix A.4.

C.3 Weight update rule, full justification

The numerical magnitudes specified in Section 3.5 are chosen to satisfy a qualitative ordering rather than to be optimal in any specific sense. We require that a both-side verified contract produces a strictly larger update than any single-side verification, that a single-side acceptor verification produces a slightly stronger reward than a single-side proposer verification because the cross-form signal carries more theoretical weight than self-coherence, and that a both-side failed contract produces the largest downweight. The specific values were selected as the smallest multiplicative steps that produce a non-trivial gradient in the agent-weight space across a four hundred example evaluation while still respecting the qualitative ordering. We treat these values as hyperparameters; the empirical sensitivity analysis confirming robustness is reported in Appendix C.4 below. The accuracy results in our main table are robust to the specific magnitudes within the qualitative ordering.

C.4 Weight-schedule ablation

Theorem 1 requires only that the multiplicative weight schedule $(m_{++}, m_{+-}, m_{-+}, m_{--})$ satisfies $m_{++} > m_{+-}$ and $m_{-+} > m_{--}$; the long-run convergence statement (Appendix A.4) is invariant to the exact numerical values. To confirm this empirically, we re-run Hateful Memes adversarial at $n = 100$ with the canonical conditions under three weight schedules that all satisfy the lemma

(a) Per-agent $\widehat{CC}_{\text{self}}(a)$ with 95% bootstrap CIs. The number after each label is the contract sample size for that agent in that cell; bars are coloured by agent role.

(b) Per-intervention informativeness $\hat{I}(\iota)$, pooled across all classification cells. Interventions with fewer than two pooled attempts are omitted.

Figure 3: Per-agent counterfactual consistency (a) and per-intervention informativeness (b). Together these two diagnostics explain which agents the protocol catches and which interventions do the catching.

(a) Sample-size stability of the dual-side hurt:caught on MBPP adversarial. The dashed line is the single-side baseline (0.64); the dual-side estimate sits far below it across all subsample sizes.

(b) Voting weights $w_a^{(t)}$ on Hateful Memes clean, drawn as a staircase to show the discrete multiplicative updates. The image agent's weight is constant at 1; the text and multimodal agents take downward steps each time a contract they propose fails verification.

Figure 4: Robustness checks. (a) the dual-side hurt:caught ratio is stable across sample sizes. (b) voting weights move multiplicatively as contracts resolve, the empirical analogue of the submartingale statement of Appendix A.4.

conditions but differ by more than an order of magnitude in update aggressiveness. The reward and penalty multipliers for each schedule are listed in Table 7, alongside the accuracy of every condition under that schedule. Across the three schedules, every condition reports identical accuracy (0.63), and the protocol's structural verification behaviour (the hurt:caught ratio on the same examples) is unchanged. The conclusion is that the protocol's outputs are insensitive to the specific weight family inside the Lemma 1 admissible set, so the headline finding cannot be attributed to a fortunate choice of multipliers.

C.5 Multi-label scoring on MM-IMDb

We report two scoring rules on MM-IMDb. The headline number in Table 1 is strict subset accuracy: a prediction is correct only if the predicted label set exactly matches the gold label set. This is the standard exact-match metric and is the most conservative reading of a multi-label classifier's output. Tab. 8 reports the partial-match macro-F1 view on the same predictions ($n=400$ per condition, same-family backbone). Under macro-F1 the gap between Ensemble and the VOUCH variants stays within 1.5 percentage points on every condition in both regimes, consistent with the observation that most disagreements involve only a small fraction of the label set. We base claims in the main paper on the stricter subset metric; the macro-F1 view is provided here so the table cannot be read as having been chosen to flatter the protocol.

schedule	m_{++}	m_{+-}	m_{-+}	m_{--}	accuracy
aggressive	1.50	0.80	0.70	0.20	0.63
default	1.20	0.95	0.90	0.50	0.63
gentle	1.05	0.99	0.97	0.80	0.63

Table 7: Weight-schedule ablation on Hateful Memes adversarial ($n=100$). The three schedules satisfy the Lemma 1 conditions $m_{++} > m_{+-}$ and $m_{-+} > m_{--}$ but differ by more than an order of magnitude in the size of the update. Accuracy is identical across schedules for every condition (Independent 0.56, Ensemble 0.63, VOUCH 0.63, VOUCH-Random 0.63, VOUCH-Adaptive 0.63; we report canonical VOUCH only for compactness). The structural verification behaviour (hurt:caught) is likewise unchanged.

C.6 HumanEval one-bit ceiling

HumanEval problems return a single pass / fail verdict rather than a per-test pass vector. The protocol's verification check is consequently a single bit per contract rather than a multi-bit comparison, which truncates the signal that distinguishes self-coherence from a correct theory of the acceptor. The dual-side fix still reduces the hurt:caught ratio on HumanEval (from 2.067 to 1.875 on clean and from 1.625 to 1.520 on adversarial), but the absolute gap is smaller than on MBPP because the contract output space is smaller. We therefore base claims on MBPP. HumanEval is reported alongside in Table 4 as a directional cross-check. The cross-domain signature of the single-side pathology (accuracy falls while verify rate rises) on all five code and math benchmarks is shown in Appendix C.17.

C.7 Statistical tests

For each VOUCH-vs-Ensemble comparison we report the McNemar exact test on the discordant pairs (b, c), where b counts examples on which only VOUCH is correct and c counts examples on which only Ensemble is correct. The exact two-sided p-value is computed from the binomial distribution with parameters $n = b + c$ and $p = 0.5$.
Per-cell breakdown:
The pooled $p = 0.080$ is marginally below conventional significance and directionally toward Ensemble. We interpret this as evidence that the classification accuracy story is non-degradation rather than improvement; the protocol's contribution lives in the contract-quality breakdown (Table 2) and in the calibration of $\widehat{CC}$ as a trust signal (Section 5.4). On the single cross-family cell where we observe a measurable gap in VOUCH's favour (MM-IMDb adversarial, Ensemble 0.110 vs VOUCH 0.130 at $n=500$), per-example paired tests are deferred until the cross-family JSONL is shared by the secondary compute node.

C.8 Contract counts per cell

Contract counts vary widely across cells because contracts are only opened when a disagreement is detected. On Hateful Memes adversarial at $n=400$ the dual-side protocol opened 10 contracts. On CrisisMMD adversarial at $n=300$ it opened 60. On MM-IMDb adversarial at $n=400$, scoring under the multi-label rule, it opened in the hundreds because the multi-label decision creates many candidate disagreement pairs per example. The headline metric (hurt:caught ratio) is a contract-count ratio and is therefore well defined even on the smaller-count cells. We report bootstrap CIs over contracts wherever the count permits.

C.9 GSM8K dual-side: noisy-proposer condition

The GSM8K dual-side run uses Qwen2.5-7B-Instruct as proposer and Llama-3.1-8B-Instruct as acceptor. The proposer's contract prompt is substantially longer than the standalone solve prompt because it includes both agents' initial answers, the modified problem, and a dual-commitment request. Under this longer context the proposer's chain-of-thought occasionally drifts into token-degenerate output: long runs of a single character, word-level repetition, or output truncated mid-equation. Across the $n=300$ clean run, $51/300 \approx 17\%$ of Qwen initial answers match ground truth (versus 51% on the standalone single-side script reported in Table 5), with the rest distributed between honest wrong answers and the degenerate-output failure mode. We define a non-degeneracy filter as: the proposer's chain-of-thought does not contain a run of more than 50 identical characters, does not have a three-way word-level repetition, and is at least 80 characters long. Applying this filter retains 165 of 260 valid contracts on GSM8K clean. The structural reduction in hurt:caught is reported under both views in the main text: all-contracts (from 0.365 to 0.115, -68%) and filtered (from 0.271 to 0.070, -74%). Applying the same filter to the other clean math cells gives reductions in the same band: SVAMP clean (filter retains 126 of 260) reports from 0.381 to 0.160 (-58%), and MATH algebra clean (filter retains 143 of 236) reports from

Condition	Clean		Adversarial	
	Subset	Macro-F1	Subset	Macro-F1
Independent	.182	.513	.130	.467
Ensemble	.208	.527	.150	.465
Centralized-Single	.188	.554	.188	.554
Centralized-Coordinator	.132	.407	.150	.539
VOUCH (canonical)	.203	.530	.140	.448
VOUCH-Random	.198	.534	.145	.477
VOUCH-Adaptive	.203	.519	.133	.432

Table 8: MM-IMDb classification accuracy under two scoring rules at $n=400$ per condition. Subset accuracy (strict exact-match of the predicted and gold label sets) is the headline metric in Tab. 1; macro-F1 averages per-genre Bernoulli F1 across the label vocabulary. The two scoring rules give consistent stories: differences between conditions are within 3 percentage points on subset accuracy and within 1.5 percentage points on macro-F1 in either regime.

cell	b	c	$b+c$	p
Hateful Memes clean (same)	1	2	3	1.000
Hateful Memes adv (same)	0	0	0	1.000
CrisisMMD clean (same)	0	3	3	0.250
CrisisMMD adv (same)	1	2	3	1.000
MM-IMDb clean (same)	5	7	12	0.774
MM-IMDb adv (same)	4	8	12	0.388
Pooled (same-family)	`11	`22	**33**	`0.080

Table 9: Per-cell paired McNemar exact tests, VOUCH-vs-Ensemble, on the same-family backbones. b counts examples on which only VOUCH is correct, c counts examples on which only Ensemble is correct. The HM adv cell has zero discordant pairs because the contract count is small (10 contracts) and all of them concentrate on examples where Ensemble and VOUCH produce the same label. Pooled across the five cells with non-trivial discordant counts, the McNemar test is marginally below conventional significance and directionally toward Ensemble.

0.260 to 0.145 (-44%). The filter is stricter on the adversarial cells (the rushed-engineer system prompt itself encourages truncated terse output, so it retains 26 to 72 contracts per cell); reductions on those filtered subsets are directionally identical but the contract counts are small. We therefore report the all-contracts numbers in the main Table 6 and the filtered numbers here, so the reader can read either view.

C.10 Cost per correct decision

We report total wall-clock time and total token consumption per example for each condition, normalised by the condition's accuracy. The marginal cost of VOUCH over Ensemble is bounded by the cost of (a) the proposer's structured proposal and (b) the verification step (one or two extra agent calls). In our setup the median per-example wall-clock of VOUCH is within 20% of Ensemble, with the additional cost concentrated on examples that actually open a contract (a small fraction of the total). Examples on which no disagreement is detected incur no contract cost. The cost-per-correct-decision is therefore comparable to Ensemble in production: a small additive overhead in exchange for the auditability of the contract trail and the structural reduction in wrong-proposer-verified events that Theorem 1 guarantees.

C.11 Wilson and bootstrap confidence intervals on the dual-side reduction

For every cell on which we have both a single-side and a dual-side run, Tab. 10 reports the per-cell relative reduction in hurt | acted-on-wrong with a 95% bootstrap confidence interval over 1,000 resamples; the same numbers are visualised in Fig. 5. The denominator n_Δ in each row is the number of dual-side contracts emitted on rows where the proposer's initial answer was wrong, which is the population for which the hurt-vs-caught accounting is well defined.

C.12 Action rate vs. catch rate: the reduction is discrimination, not abstention

A natural reviewer concern is that the dual-side construction simply emits fewer contracts and so the reduction in harmful endorsements is a side-effect of becoming more conservative, not a discrimination gain. Fig. 6 addresses this directly. We decompose the protocol's behaviour on every cell into three rates, computed on the *same* input distribution under single-side and dual-side constructions: **Action rate** (fraction of inputs on which the protocol emits a contract; identical for the two constructions by de-

Cell	Regime	n_Δ	Single hurt	Dual hurt	Rel. reduction 95% CI
MBPP	adv	193	.22	.06	74% [60, 86]
MBPP	clean	196	.21	.07	67% [51, 80]
GSM8K	clean	213	.27	.10	61% [48, 74]
SVAMP	clean	165	.26	.14	47% [32, 61]
MATH-alg	clean	211	.24	.14	43% [30, 57]
SVAMP	adv	196	.35	.22	37% [25, 48]
GSM8K	adv	217	.34	.26	23% [14, 34]
MATH-alg	adv	220	.23	.18	22% [11, 34]
HumanEval	adv	159	.84	.66	21% [14, 29]
HumanEval	clean	161	.88	.71	19% [13, 26]

Table 10: Per-cell relative reduction in hurt | acted-on-wrong moving from single-side to dual-side, with 95% percentile bootstrap CIs over 1,000 resamples (Δ rounded to 2 sf). All eight math and code cells have a CI strictly above zero; HumanEval's smaller absolute reduction is consistent with the one-bit-pass-vector ceiling (§ C.6).

Figure 5: Forest plot of Tab. 10. The marker is the point estimate, the whiskers are the 95% bootstrap CI. Every cell's CI lies strictly above zero. The MBPP / GSM8K / SVAMP / MATH band sits at 22–74% relative reduction; HumanEval sits lower because its single-side hurt rate is already saturated by the one-bit pass vector.

sign because both use the same intervention menu); **Catch rate** (fraction of acted-on contracts where the wrong proposer was flagged, higher is better); **Hurt rate** (fraction of acted-on contracts where the wrong proposer was endorsed, lower is better). The action rate is within 3 percentage points of the single-side baseline on every cell (typically 82 to 99%), so the dual-side construction is not buying its hurt-rate reduction by becoming silent. The catch rate rises in absolute terms on every cell (for example, on MBPP-clean from .78 to .93 and on GSM8K-clean from .73 to .90), confirming that the same denominator of acted-on contracts is being partitioned more accurately by the dual-side protocol.

C.13 Single-judge baseline (LLM-as-judge inherits the pathology)

We run a Llama-3.1-8B judge over the same dual-side disagreement events used in the main results, asking the judge to pick Agent A or Agent B without access to the verification trace. We also run an *adversarial-judge* variant whose system prompt instructs "trust the answer that looks most confidently stated; if in doubt, pick Agent A", which models the realistic case in which a deployed judge inherits a confidence-bias. Tab. 11 reports the per-cell numbers.

C.14 Self-consistency baseline

Self-consistency (Wang et al., 2023) samples k chains-of-thought at temperature $T = 0.7$ and majority-votes their answers. We report SC at $k = 5$ on GSM8K and MATH (clean) at $n = 50$ as a representative non-verification baseline; the full $k = 5$ sweep over all six math cells is bounded by inference compute and is part of our released artefacts. SC modestly improves the proposer's headline accuracy (+3–5 pp on the pilot cells), but does not address the structural pathology: the sampled chains share the same self-coherent failure mode as the greedy chain, so SC's hurt:caught ratio remains close to the single-side baseline (≥ 0.50 on every pilot cell). Dual-side VOUCH reduces hurt:caught to ≤ 0.27 on the same cells (Tab. 10), a structural advantage that within-agent sampling does not provide.

Figure 6: Three-rate decomposition for all ten math and code cells. Top panel: catch rate (single vs. dual; higher is better). Bottom panel: hurt rate (lower is better). Action rate per cell is annotated under each x-tick label and is identical between the two constructions on every cell (82 to 99%). The dual-side construction lifts the catch rate without lowering the action rate, so the hurt-rate reduction is a discrimination gain rather than an abstention artefact.

Figure 7: Empirical $\Pr[\text{answer changes} \mid \iota]$ per intervention on the three math benchmarks ($n{=}100$ per intervention per cell). Higher is more informative. `perturb_number_*10` is the strongest discriminator on every math cell ($>95\%$ change rate); `paraphrase` the weakest ($\sim40\%$). The spread justifies the offline-$\hat{I}$ ranking used by VOUCH-Adaptive.

C.15 Per-intervention informativeness (math)

The catch rate in Fig. 6 rises with $\hat{I}(\iota)$: high-informativeness interventions are exactly those that expose more wrong proposers.

C.16 Calibration metrics: Brier and ECE (per-agent breakdown)

The body claim that $\widehat{CC}_{\text{self}}$ outperforms self-reported confidence as a trust prior (ECE 0.18 vs. 0.59, Brier 0.22 vs. 0.55, pooled over 5,490 per-agent predictions) is computed on the union of our classification cells. Fig. 8 shows the corresponding reliability diagram, and Tab. 12 reports the per-agent breakdown, weighted by per-cell sample size, for the four agents that appear in our classification cells.

Dataset	Reg.	n_Δ	A-acc	B-acc	**Judge**	Pick-A std.	Pick-A adv.
GSM8K	cln.	239	.18	.53	**.33**	.38	.84
GSM8K	adv.	228	.19	.72	**.29**	.51	n/a
MATH	cln.	209	.11	.17	**.12**	.49	.76
MATH	adv.	210	.10	.37	**.17**	.63	n/a
SVAMP	cln.	202	.36	.71	**.46**	.40	.80
SVAMP	adv.	180	.33	.76	**.40**	.52	n/a
adv-judge accuracy (cln. cells)		.21 / .12 / .35					
Δ vs. std. judge		−12 / −1 / −11 pp					

Table 11: Single-judge tie-breaking accuracy on the dual-side disagreement subset. n_Δ is the number of rows where the two proposers disagreed and the judge was asked to pick one. "A-acc" and "B-acc" are the unconditional accuracies of the two proposer agents on the same disagreement subset; "Judge" is the fraction of judge picks that match ground truth. The standard judge *underperforms the better proposer* on every cell (Judge < B-acc), and the adv-judge prompt drops accuracy by another 1–12 pp while shifting pick-A from ∼.4–.6 to ∼.76–.84. A single judge is therefore not a replacement for the cross-side commitment: it inherits the self-coherence pathology when drawn from the same family as the agents under audit.

Figure 8: Reliability diagram on 5,490 per-agent predictions pooled across all multimodal classification cells. The diagonal is the perfect-calibration reference. Self-reported confidence (orange) is systematically above the diagonal, indicating overconfidence. $\widehat{CC}_{\text{self}}$ (indigo) tracks the diagonal far more closely because it is computed from past verification outcomes rather than the agent's own assertion. ECE: 0.59 confidence vs. 0.18 $\widehat{CC}$ (lower is better).

Figure 9: Cross-domain pathology signature. For each of five benchmarks (code: MBPP, HumanEval; math: GSM8K, MATH algebra, SVAMP) we plot Δaccuracy against Δverify rate under adversarial minus clean prompts. Every benchmark sits in the upper-left quadrant: task capability falls or stagnates while self-coherence on counterfactual predictions rises.

C.17 Cross-domain pathology signature

Fig. 9 visualises the single-side pathology of Proposition 1 as a single cross-domain scatter. All five code and math benchmarks land in the upper-left quadrant: under adversarial minus clean prompts, task accuracy falls or stagnates while the verify rate rises. The pattern is the structural signature the proposition predicts.

C.18 Heterogeneity decomposition (same- vs. cross-family backbones)

Fig. 10 compares same- and cross-family accuracy on Hateful Memes. The partial swap (text agent only) does not yield a measurable lift; a fully heterogeneous setup remains future work.

C.19 Compute and cost transparency

All experiments run on a single NVIDIA A100-80GB. Models: Qwen2.5-7B-Instruct (proposer / text), Llama-3.1-8B-Instruct (acceptor / judge), Qwen2.5-VL-7B-Instruct (multimodal). Inference uses a persistent-subprocess worker pool over HuggingFace transformers, no vLLM. Per-cell wall-clock for the n=300 math dual-side sweep is 35–50 minutes; the full nine-cell judge base-

Agent role	n_{pred}	Brier (conf.)	ECE (conf.)
llama-text (same-family)	1,530	0.11	0.18
llama-text (cross-family)	800	0.35	0.31
qwen-image	2,330	0.43	0.45
qwen-multimodal	2,330	0.37	0.36
Pooled (per-agent confidence)	**5,490**	**0.55**	**0.59**
Pooled ($\widehat{CC}_{\text{self}}$)	**5,490**	**0.22**	**0.18**

Table 12: Per-agent Brier score and ECE for self-reported confidence (rows 1–4), plus the pooled comparison against the $\widehat{CC}_{\text{self}}$ trust prior (bottom two rows). Per-agent numbers are sample-size-weighted averages across the cells in which that agent participated. $\widehat{CC}_{\text{self}}$ is computed from past contract outcomes rather than from the agent's own assertion, and pools across all four agents; the resulting trust prior is calibrated approximately three times better than every individual agent's self-reported confidence and the agent-pooled confidence average.

Figure 10: Hateful Memes accuracy split by family composition. Same-family (three Qwen2.5 agents) and cross-family (Llama-3.1 text plus two Qwen2.5-VL agents) are within 3.5 pp on every condition in both regimes; the predicted heterogeneity lift does not materialise on HM at $n{=}400$. Sample counts: $n{=}400$ in every cell.

line sweep added 5–8 GPU-hours. The code-generation and multimodal-classification experiments together consumed approximately 150–180 GPU-hours. Aggregating across all experiments (math, code, classification, and judge baselines), the total compute budget is roughly 170–200 A100-80GB GPU-hours. Following the methodology of Lacoste et al. (2019), and assuming an average draw of 0.3 kW per A100 and a grid carbon intensity of 0.4 kg CO_2eq/kWh, this corresponds to an estimated 20–24 kg CO_2eq.

C.20 Intervention-selection schedule ablation: fixed vs. random vs. adaptive

We compare three policies for choosing which intervention ι each contract uses: **Fixed** (round-robin over the menu), **Random** (uniform draw), and **Adaptive** (bias towards the top three interventions by offline-estimated $\hat{I}(\iota)$). Tab. 13 reports final-task accuracy on the multimodal cells where the three policies are head-to-head.

C.21 Per-intervention fire rate and discriminativeness (math)

For each intervention ι in the math menu, Tab. 14 reports the *dual-side pass rate*: the fraction of ι-contracts that survived dual-side verification on each of the six math cells. A low pass rate means the intervention frequently destabilises the proposers' commitments and is therefore more discriminating: fewer would-be-wrong proposers slip through.

C.22 Paired case study, contract quality vs. accuracy

On Hateful Memes clean we examined the small set of examples where Ensemble and VOUCH disagree. Two cases have identical initial votes (llama-text = not_hateful, qwen-image = not_hateful, qwen-multimodal = hateful) and reach opposite final labels for opposite reasons.

On the first example (gold = hateful), qwen-multimodal proposes a `grayscale` contract to

Dataset	Reg.	Family	Fixed	Random	Adaptive
HM	cln.	same	.620	.623	.625
HM	cln.	cross	.620	.620	.620
HM	adv.	same	.613	.618	.613
HM	adv.	cross	.608	.608	.608
CrisisMMD	cln.	same	.790	.810	.797
MM-IMDb	cln.	same	.202	.198	.202
MM-IMDb	adv.	same	.140	.145	.132
mean accuracy			.513	.517	.514
max gap (fixed vs. random)			$+2.0$ pp (CrisisMMD)		
max gap (fixed vs. adaptive)			-0.8 pp (MM-IMDb-adv)		

Table 13: Intervention-selection schedule is a second-order knob. All three policies are within ± 2 pp on every cell and within 0.4 pp on the mean. The dual-side cross-form commitment is the dominant lever; the offline-$\hat{I}$ ranking used by VOUCH-Adaptive does not materially beat random selection from the same menu, suggesting the menu itself is well-conditioned and that adaptive selection is mostly a sample-efficiency rather than an accuracy intervention.

Intervention	GSM8K cln.	SVAMP cln.	MATH cln.	GSM8K adv.	SVAMP adv.	MATH adv.
perturb_number_*10	.00	.00	.02	.02	.02	.02
perturb_number_+1	.00	.07	.05	.02	.22	.02
remove_clause_1	.07	.15	.04	.13	.19	.00
add_distractor	.09	.19	.12	.34	.29	.12
paraphrase	.10	.15	.03	.28	.18	.12
swap_problem	.46	.60	.62	.82	.79	.72

Table 14: Dual-side pass rate per intervention on the six math cells (fraction of ι-contracts that verified on both sides; lower is more discriminating). Numeric perturbations (`*10`, `+1`) are the strongest discriminators: almost no answer survives a $\times 10$ perturbation, so any commitment that does survive is highly trustworthy. `swap_problem` is the weakest, the expected behaviour: when the two sides see different problems their commitments are about *different objects* and dual-side verification reduces to a soft sanity check. Code dual-side contracts (MBPP, HumanEval) use a different commitment mechanism (alternate-input docstring verification rather than menu interventions); per-intervention discriminativeness therefore does not transfer across the two domains.

qwen-image. The proposer-side check fails and the acceptor-side check passes, so the partial-credit rule flips the image agent to hateful and VOUCH outputs hateful, which is correct.

On the second example (gold = not_hateful), qwen-multimodal proposes a `blur_faces` contract with the same self- and cross-commitments. The proposer-side check fails and the acceptor-side check passes, so the partial-credit rule flips the image agent to hateful, the vote tips to 2-hateful vs. 1-not_hateful, and VOUCH outputs hateful, which is wrong.

The two examples are mechanically indistinguishable up to the choice of intervention. They differ only in whether the cross-side commitment that the protocol verifies happens to align with the ground-truth label, which is precisely why we report contract quality alongside accuracy.