LIGHTTRANSFER:
YOUR LONG-CONTEXT LLM IS SECRETLY A HYBRID MODEL WITH EFFORTLESS ADAPTATION

Xuan Zhang[1,2] [*] **Fengzhuo Zhang**[3]**, Cunxiao Du**[1] [†] **Chao Du**[1]**,
Tianyu Pang**[1]**, Wei Gao**[2]**, Min Lin**[1]
[1]SEA AI Lab
[2]Singapore Management University
[3]National University of Singapore
{ducx}@sea.com

ABSTRACT

Scaling language models to handle longer contexts introduces substantial memory challenges due to the growing cost of key-value (KV) caches. Motivated by the efficiency gains of hybrid models and the broad availability of pretrained large transformer backbones, we explore transitioning transformer models into hybrid architectures for a more efficient generation. In this work, we propose LIGHT-TRANSFER, a lightweight method that transforms models such as LLaMA into hybrid variants. Our approach identifies *lazy* layers—those focusing on recent or initial tokens—and replaces their full attention with streaming attention. This transformation can be performed without any training for long-context understanding tasks or with minimal fine-tuning for o1-like long reasoning generation tasks that require stronger reasoning capabilities. Experiments across diverse benchmarks and models (e.g., LLaMA, Mistral, QwQ-STILL) demonstrate that, even when half of the layers are identified as *lazy*, LIGHTTRANSFER achieves up to $2.17\times$ throughput improvement with minimal performance loss ($< 1.5\%$ on LongBench) and achieves 53.3% on math benchmark AIME24 of advanced o1-like long reasoning model QwQ-STILL.

1 INTRODUCTION

Recent advancements in large language models (LLMs) have extended their capacity for handling long context inputs and generating long-form reasoning. For example, LLaMA-3.1 supports context lengths up to 128K (Dubey et al., 2024), while OpenAI's o1 can produce sequences of up to 100K tokens (OpenAI, 2024). As the cornerstone of the efficient inference of these models on long context, key-value (KV) cache stores precomputed key and value tensors for each token in the language sequence to avoid recomputing them for each attention layer. However, as the number of model layers and input lengths increases, the memory required for storing the KV cache grows significantly, posing challenges for inference efficiency.

Various methods have been proposed to reduce the KV cache storage by modifying the model architecture (Shazeer, 2019; Brandon et al., 2024; Goldstein et al., 2024; Nawrot et al., 2024; Wang et al., 2024b; Yu et al., 2024). One promising approach is the hybrid model. As shown in Figure 1, in these hybrid models, certain layers of a standard transformer are replaced with more memory-efficient mechanisms such as RNNs (Sherstinsky, 2020), Mamba (Gu & Dao, 2023), and sliding window attention (Beltagy et al., 2020). These approaches exploit the notion that different layers can be manually assigned distinct functionalities, such as using memory-efficient mechanisms for local context processing and standard attention for global context handling (Gemma et al., 2024), thereby achieving notable memory savings. Concrete examples of such hybrid architectures include Transformer-Recurrent Neural Network (RNN) designs such as YoCo (Sun et al., 2024), Transformer-

---

[*]Work done during Xuan Zhang's associate membership at Sea AI Lab.
[†]Corresponding Author.

Mamba approaches such as Jamba (Lieber et al., 2024; Team et al., 2024), and Transformer-Sliding Window models like Gemma 2 (Gemma et al., 2024) and YoCo (Sun et al., 2024). However, a key limitation is that they require training the entire model from scratch.

Given the substantial efficiency gains offered by hybrid models and the availability of large-scale pretrained transformer backbones, a natural direction is to transition these pretrained models into hybrid architectures with minimal additional training. A straightforward method is to replace traditional full attention layers with sparse attention, thereby adopting a fixed-size KV cache to reduce memory overhead. A representative example is *streaming attention* (Xiao et al., 2023), which augments the sliding-window mechanism by introducing *sink tokens*. However, as Table 2 shows, completely substituting all standard attention layers with streaming attention leads to a severe degradation in the model's ability to process long contexts, thereby undermining its capacity to capture global information. Consequently, when transitioning from a pretrained transformer to a hybrid model, two primary challenges arise. First, it is necessary to retain some standard attention layers to preserve the model's long-context modeling capabilities, raising the critical question: which layers should remain intact? Second, this transition should ideally be lightweight,

Figure 1: (a) A standard transformer architecture. (b) A hybrid model in which certain layers of a standard transformer are replaced with more memory-efficient designs. LIGHTTRANSFER identifies lazy layers in (a) and transforms them into more efficient variants, yielding (b).

enabling efficient adaptation with minimal data or even allowing it to be applied entirely at test time. Otherwise, if large-scale pretraining data were required, one could simply train a hybrid model from scratch, undermining the value of a transition-based approach.

In response to the above challenges, we examine the attention patterns in different transformer layers to determine whether each layer exhibits distinct functionalities. We conduct preliminary experiments (Section 4) and identified two key findings: First, *certain layers in long-context LLMs exhibit lazy behavior*, primarily focusing on semantically unimportant tokens (e.g., the initial few tokens) and the most recent during answer generation. The properties of lazy layers address our first challenge and enable standard transformer-based LLMs to operate in a hybrid-like manner: identified lazy layers use streaming attention, whereas non-lazy layers retain full attention. Second, after analyzing attention weight patterns, we find that *layer behavior is consistent across tokens for a given long input*. This insight partially addresses the second challenge and paves the way for a test-time transformation in which selective modifications are applied during the prefilling stage, allowing for efficient adaptation without extensive retraining.

Building upon this insight, we propose LIGHTTRANSFER, a lightweight method that transforms models such as *LLaMA*, *Mistral* (Jiang et al., 2023), and *QwQ* (Qwen, 2024) into their corresponding hybrid variants. Specifically, as shown in Figure 1, we analyze the attention allocation patterns in each layer to determine whether it can be treated as a lazy layer. In lazy layers, we apply streaming attention, while standard attention is retained in non-lazy layers. The output of the transformer with a reduced KV cache differs from the original output due to the reduced cache size, and this difference is theoretically analyzed in Theorem 5.1. For tasks where the input is sufficiently long (i.e., long-context understanding), we leverage on-the-fly lazy layer identification at the prefilling stage, LIGHTTRANSFER-TEST. In addition, for o1-like long reasoning generation tasks, even though the questions can be relatively short (only a few dozen tokens) yet demand higher model capacity, we surprisingly find that minimal training still enables robust performance (LIGHTTRANSFER-TRAIN). In practice, this transition requires only around 5K samples (originally utilized for long-reasoning ability distillation (Min et al., 2024)), underscoring the lightweight nature of our approach.

We conduct experiments on four representative LLMs (i.e., LLaMA2-7B-chat (Touvron et al., 2023), Mistral-7B-Instruct (Jiang et al., 2023), LLaMA3-8B-Instruct and its 70B counterpart (Dubey et al., 2024)), evaluating them on long-context benchmarks including LongBench (Bai et al., 2023) and

Needle-In-A-Haystack (NIAH) (Kamradt, 2023). In addition, we adapt an o1-like long reasoning model QwQ-32B-STILL and assess its performance on MATH-OAI (Lightman et al.), AIME24 [1], and GSM8K (Cobbe et al., 2021). Experimental results indicate that hybrid models converted via LIGHTTRANSFER achieve performance on par with their standard transformer counterparts. For example, on long-context understanding tasks, it achieves only a 1.45% performance decline on LongBench. For long reasoning tasks, it achieves performance that is comparable to or even better on the widely used mathematical benchmark AIME24, reaching 53.3% accuracy. Notably, these results were obtained while half of the model's layers employed streaming attention, yielding up to a 2.17× increase in throughput.

2 RELATED WORKS

Memory-efficient architectures, such as linear RNN-based architectures (e.g., Mamba (Gu & Dao, 2023)) and those employing sparse attention methods (e.g., streaming attention (Xiao et al., 2023)), have demonstrated clear advantages in deployment, including reduced memory usage and higher throughput (Peng et al., 2023; Dao & Gu, 2024; Yang et al., 2023; Sun et al., 2024; Lieber et al., 2024; Gemma et al., 2024). However, a key drawback of these memory-efficient models is their limited ability to handle extended contexts effectively (Behrouz et al., 2024; Yuan et al., 2024). Meanwhile, the inference memory cost of standard transformers (i.e., the storage of the KV cache) grows linearly as the context length increases (Shi et al., 2024; Li et al., 2024c;a). To address these challenges, recent research has proposed hybrid architecture: maintaining the strong capabilities of pretrained transformers while selectively substituting certain transformer layers with more memory-efficient modules, thereby balancing high performance with practical deployment efficiency (Lieber et al., 2024; Gemma et al., 2024; Sun et al., 2024; Botev et al., 2024; De et al., 2024). For example, Jamba (Lieber et al., 2024; Team et al., 2024) integrates Mamba (Gu & Dao, 2023) with transformer, Gemma 2 (Gemma et al., 2024) alternates sliding-window attention with standard attention layers, and Minimax-01 (Li et al., 2025) employs lightning attention (Qin et al., 2024) in certain layers. However, a key limitation of these methods is their reliance on training the entire model from scratch. Although recent approaches aim to leverage the capabilities of large-scale pretrained models by converting selected layers into memory-efficient structures to form a well-trained hybrid model, they still depend on extensive training data (Wang et al., 2024a; Ge et al., 2024). For instance, LongGen (Ge et al., 2024) transforms certain layers in pretrained LLM into sparse attention but requires retraining on over 2TB of data. Differently, our LIGHTTRANSFER framework is designed to be substantially more lightweight. Despite requiring no additional training for long-context understanding tasks, and only 5K training examples for more demanding long-text reasoning tasks (as originally used for long-reasoning ability distillation (Min et al., 2024)), it still achieves strong performance on both fronts. The superiority of our LIGHTTRANSFER comes from the identification of each layer's function, whereas LongGen always uses a fixed structure (retaining the middle layers for full attention). Some works also attempt to fully transfer transformer models into RNN-like architectures (Kasai et al., 2021; Zhang et al., 2024b; Mercat et al., 2024; Zhang et al., 2024a; Bick et al., 2024). However, these methods primarily focus on short-context tasks (e.g., QA), whereas our approach targets long-context scenarios.

3 PRELIMINARY

Before introducing LIGHTTRANSFER, we provide a brief overview of the generative inference in autoregressive LLMs, which is the key background for our method.

Inference stages. The typical generative LLM inference process involves two stages: (1) *Prefilling*: the autoregressive LLM processes the input prompt X by parallel computing, and also saves the KV cache of tokens in X. The output of the last token in this stage is the first token of the response. (2) *Decoding*: after the prefilling stage is completed, the LLM generates output tokens one by one, and saves their KV cache. In each decoding step, a new token is generated based on the current token and the KV cache stored from earlier steps, continuing until a stop criterion is met.

---

[1]https://huggingface.co/datasets/AI-MO/aimo-validation-amc

Figure 2: Visualization of attention weight distributions on LLaMA3-8B. Left: The attention patterns across different layers. Right: Each cell represents an attention weight from each token (x-axis) to the initial tokens and the most recent tokens during both the prefilling and decoding stages. Layers that predominantly attend to these tokens are outlined in black boxes.

4 OBSERVATIONS

In this section, we analyze the attention patterns during inference in long-context LLMs, providing insights that motivate our approach to transform the standard transformer into its corresponding hybrid variant. The study is conducted on the LLaMA3-8B-Instruct model (Dubey et al., 2024) using a sample from the LongBench (Bai et al., 2023) benchmark. Our key findings are as follows:

Layer behavior in long-context LLMs during inference. Previous research (Xiao et al., 2023) has shown that a large portion of attention in LLMs tends to focus on semantically unimportant tokens X_{initial} (e.g., the first few tokens) and the most recent tokens X_{recent} (i.e., tokens in the sliding window). We refer to this pattern as *lazy* behavior, likening it to skimming a paper by reading only the first lines and the conclusion. While it is also called attention sink (Xiao et al., 2023; Gu et al., 2024), we emphasize the shortcut nature by referring to it as lazy. Through our analysis, we find that even with long contexts, some layers exhibit more pronounced lazy behavior, which we define as *lazy layers*. The left panel of Figure 2 presents the attention patterns across different layers. We observe that some layers (e.g., layer 0) do not follow a clear pattern in attention weight distribution, while others (e.g., layer 20) show a clear lazy behavior pattern. Consequently, a more memory-efficient attention mechanism can be employed in these lazy layers by retaining only a subset KV cache of constant size.

Layer behavior remains consistent for a given input. To further explore whether a layer consistently functions as a lazy layer during generation for a fixed prompt, we visualize the attention weights for $\{X_{\text{initial}}, X_{\text{recent}}\}$ across all layers for all generated tokens in the right panel of Figure 2, using a randomly selected sample (additional examples are provided in Figure 9). Notably, for a given input prompt, layers that exhibit lazy behavior maintain this pattern relatively consistently across tokens. This suggests a certain degree of stability in attention dynamics throughout the generation process. In addition, the indexes of these consistent lazy layers vary according to different prompts. This necessitates the test-time algorithm in the following section.

5 METHODOLOGY: LIGHTTRANSFER

In this section, we introduce LIGHTTRANSFER, a method for converting pretrained transformers into hybrid architectures for a more efficient generation. LIGHTTRANSFER leverages our observation of lazy layers by replacing full attention with streaming attention. The method has two settings: (1) For tasks like long-context understanding, LIGHTTRANSFER-TEST allows for on-the-fly transformation at test time without requiring additional training. (2) For tasks demanding higher model capacity, such as o1-like long reasoning generation, LIGHTTRANSFER-TRAIN involves fine-tuning to adapt the model to the hybrid architecture.

5.1 LIGHTTRANSFER-TEST

As shown in Figure 3, the first step in applying LIGHTTRANSFER-TEST is identifying lazy layers, defined as those whose final w_{last} number of tokens in queries (i.e., X_{last}) allocate the most attention to $X_{\text{initial}} \cup X_{\text{recent}}$. To measure how the model allocates attention at layer i, we define a lazy ratio r_i:

Figure 3: The framework of our LIGHTTRANSFER-TEST. A priority queue is maintained during the prefilling stage to store the lazy ratio and corresponding layer index after processing each layer. Once the queue reaches its capacity, the layer with the highest lazy ratio is identified as a lazy layer, and its KV cache is reduced, freeing memory for storing the KV cache of the current layer.

$$r_i = \frac{1}{w_{\text{last}}} \sum_{\hat{x} \in X_{\text{last}}} \sum_{x \in \{X_{\text{initial}}, X_{\text{recent}}\}} A_i(\hat{x}, x), \tag{1}$$

where $A_i(\hat{x}, x)$ is the averaged attention weight over all heads from a query token $\hat{x}$ to a key token x at layer i. Intuitively, a higher r_i indicates that X_{last} focuses more heavily on these particular key sets, thus exhibiting more lazy attention. To ensure that only P layers with the largest lazy ratios maintain full attention during the prefilling stage and thus reduce peak memory usage, we adopt a priority queue. We treat the lazy ratio r_i as the priority in a max-based priority queue of size P. Whenever the queue exceeds capacity, the layer with the highest lazy ratio is popped, labeled lazy, and its standard attention is replaced with streaming attention. Here we do not replace the standard attention with streaming attention in a head-wise manner due to the inefficiency, discussed in Appendix B.2. Specifically, for each lazy layer i, we retain only the KV caches corresponding to $\{X_{\text{initial}}, X_{\text{recent}}\}$ and discard others. During decoding, memory usage is naturally reduced because the decoding process relies on the already updated (and thus reduced) KV caches from the prefilling stage.

Identification burden. FlashAttention (Dao, 2023) is widely used to accelerate computations during the prefilling phase, but it does not explicitly expose attention weights. A direct application of our lazy layer identification strategy would thus require recomputing the attention matrix, incurring non-negligible overhead. To circumvent this issue, as shown in Table 1, we leverage the log-sum-exp values (i.e., the denominator) of all attention weights produced by FlashAttention. Consequently, we only need to recompute the streaming attention score (a constant-size matrix multiplication), thus eliminating the need for a full recomputation. Our

Table 1: Torch style code for our lazy ratio calculation with flash attention.

```python
def Lazy_ratio_calculation(
    q, # bs * num_heads * seq_len * head_dim
    k, # bs * num_heads * seq_len * head_dim
    v, # bs * num_heads * seq_len * head_dim
    w_last, w_sink, w_recent):
    attn_out, lse = flash_attn(q, k, v,
causal=True, return_lse=True)
    q_last = q[:, -w_last:].permute(0, 2, 1, 3)
    k_comb = torch.cat([k[:, 0:w_sink],
k[:, -w_recent:]], dim=1).permute(0, 2, 3, 1)
    log_lazy_ratio = torch.matmul(q_last, k_comb)
.logsumexp(dim=-1) - lse
    return log_lazy_ratio
```

identification algorithm mitigates additional latency introduced by full recomputation, resulting in only a slight throughput reduction of 0.0058 to 0.0014 relative to a baseline of 1 across sequence lengths from 4K to 32K. Notably, longer sequences result in smaller relative throughput reduction. This occurs because the prefill operation grows with sequence length, whereas our identification process remains $O(1)$. As a result, when n is large, the identification overhead is overshadowed by the overall prefill cost.

5.2 LIGHTTRANSFER-TRAIN

For o1-like long reasoning tasks, where the input question typically consists of only a few dozen words, the lazy ratio r_i is not a reliable indicator of *lazy*. Because the sliding window is relatively large compared to the input, r_i remains at 1 across all layers. To address this, we adopt a pre-selection strategy. Specifically, for each sample in the training set, we feed both the question and the answer as input to the LLM, thereby providing sufficient context for each sample to reveal which layers are lazy. We then compute the frequency for each layer and select those with the highest lazy layer counts. However, frequency-based selection may not be fully optimal for each sample, while o1-like long reasoning tasks are inherently difficult, so additional fine-tuning allows the model to adapt to the new hybrid architecture and re-balance capacity across layers. Therefore, once these layers are identified, we perform supervised fine-tuning (SFT) under a hybrid architecture in which lazy layers employ streaming attention, while non-lazy layers retain standard attention. During inference, we simply rely on the preselected lazy layers, without requiring on-the-fly identification.

5.3 THEORETICAL ANALYSIS

We first provide a theoretical analysis of the approximation error of LIGHTTRANSFER-TEST and then discuss how this analysis implies the performance of LIGHTTRANSFER-TRAIN. We would like to highlight that our lazy layer identification procedures in LIGHTTRANSFER-TEST are implicitly optimizing an upper bound of the error of the whole network output induced by reducing the KV cache. We denote the set of layer indexes whose KV cache is reduced as $\mathcal{I}$. For any layer $i \in \mathcal{I}$, we denote the attention score of the discarded KV pairs as $s_i = 1 - \sum_{x \in \{X_{\text{initial}}, X_{\text{recent}}\}} A_i(\hat{x}, x)$. Then we have the following upper bound of the error of the network output.

Theorem 5.1 (Informal). *If the Frobenius norms of all the parameters in a L-layer with H-attention heads transformer are upper bounded by B and the activation function is L_{lip}-Lipschitz, then we have that*

$$\text{Err. of LIGHTTRANSFER in logit} \leq 2LB^2\big(H + L_{\text{lip}}B + 4HB^2\big) + 2HB^2\big(1 + L_{\text{lip}}B^2\big)\sum_{i \in \mathcal{I}} s_i.$$

If we denote the error of hidden states at layer i as e_i, then it evolves as

$$e_i \leq e_{i-1} + C_1 \min\{2, C_2 \cdot e_{i-1}\} + 2H(B + L_{\text{lip}}B^3)\mathbb{I}\{i \in \mathcal{I}\}s_i,$$

where C_1 and C_2 are quantities related to B, H and L_{lip}.

The formal statement and the proof of Theorem 5.1 are provided in Appendix F. We note that the error recursive expression consists of three terms. The first term represents the error from the previous layer. The second term represents the error from the previous layer amplified by the current layer. Thanks to the layer normalization, this term will be truncated by 2. The last term represents the newly introduced error if we shorten the KV cache at the current layer. By relaxing this recursive formula, we derive the upper bound of the error between the logits of our method and the original transformer. This shows that the error is upper bounded by the sum of the attention scores of the removed KV pairs up to an additive constant. We highlight that our algorithm optimizes Eqn. equation 1, which is exactly the upper bound of the error induced by LIGHTTRANSFER in logit up to a constant. We note that this theorem also provides the error analysis of the initial point of this fine-tuning process. The fine-tuning will further decrease the error induced by LIGHTTRANSFER shown in Theorem 5.1.

6 EXPERIMENTS

In this section, we empirically validate that LIGHTTRANSFER can accelerate LLM generation while maintaining long-text capabilities including two scenarios 1) long context understanding, and 2) o1-like long reasoning generation, and uncover several insightful findings.

6.1 EXPERIMENTS ON LONG-CONTEXT UNDERSTANDING TASKS

In these experiments, we only apply LIGHTTRANSFER-TEST. As previously discussed, the input length for these understanding tasks is sufficient to enable on-the-fly lazy-layer detection during the prefilling stage, making additional training unnecessary.

Table 2: Performance comparison of LIGHTTRANSFER-TEST and baseline methods on LLaMA-2-7B-chat, Mistral-7B-Intruct, LLaMA-3-8B-Instruct, and LLaMA-3-70B-Instruct using LongBench. **Bold** denotes the best method, and underlined denotes the second best.

	Single-Doc. QA			Muti.-Doc. QA			Summary			Few-shot			Syn.		Code		Average
	NrtvQA	Qasper	MF-en	HotpotQA	Musique	DuReader	GovReport	QMSum	MultiNews	TREC	TriviaQA	SAMSum	PCount	PRe	LCC	RB-P	
LLaMA2-7B-chat																	
Standard	**19.1**	**21.6**	**36.9**	27.7	8.6	6.5	**27.1**	20.8	**26.0**	**64.0**	**83.6**	**41.3**	2.9	**7.5**	**60.6**	**54.9**	**31.8**
Streaming	13.1	15.2	26.9	23.1	5.5	4.4	21.1	19.9	24.2	61.0	82.8	38.9	2.1	4.0	59.0	52.2	28.3
MiniCache	13.1	13.7	30.3	15.6	4.7	**9.8**	21.5	**20.9**	24.3	63.0	83.1	35.1	2.2	6.1	53.4	46.5	27.7
SqueezeAtt.	15.9	15.7	27.0	25.5	6.5	4.3	21.9	19.6	23.3	62.0	83.2	39.9	1.9	0.5	60.0	53.5	28.7
LITTRANS	15.8	18.3	30.1	27.3	7.0	4.7	22.7	20.2	25.1	62.0	82.8	39.6	2.1	1.2	59.4	53.6	29.5
Mistral-7B-Instruct																	
Standard	**29.7**	40.5	53.4	50.0	**29.1**	32.9	34.9	25.4	27.7	76.0	89.1	47.3	5.0	98.5	60.4	**62.1**	**47.6**
Streaming	22.2	32.1	44.8	41.7	23.0	20.3	24.8	21.3	26.0	65.0	86.7	40.4	3.5	46.0	52.8	47.9	37.4
MiniCache	19.7	30.3	35.6	29.5	15.5	20.3	24.8	21.3	26.0	65.0	86.7	40.4	3.8	45.1	52.8	47.9	35.3
SqueezeAtt.	26.8	30.4	38.4	44.3	21.0	18.6	24.9	21.0	26.2	75.5	89.2	46.3	**6.5**	89.0	**60.6**	60.6	42.5
LITTRANS	29.0	**41.0**	**53.6**	50.5	27.5	32.3	34.8	**25.4**	27.3	76.0	89.3	47.3	6.0	97.5	59.9	61.3	47.4
LLaMA-3-8B-Instruct																	
Standard	**23.4**	**32.8**	**39.6**	**44.7**	22.2	20.1	28.8	23.3	27.0	73.5	90.6	**41.9**	3.6	**72.0**	58.1	51.3	**40.8**
Streaming	19.5	17.5	26.1	36.4	16.1	12.1	22.8	21.4	25.4	66.0	86.4	40.1	3.5	70.7	59.7	**54.2**	36.1
MiniCache	17.4	10.9	18.4	11.5	6.7	15.9	23.8	20.1	25.5	**74.5**	84.5	37.4	3.2	64.1	48.5	45.3	31.7
SqueezeAtt.	20.0	19.6	26.2	37.5	18.7	13.3	23.8	22.0	23.8	72.5	90.0	41.5	6.7	66.0	55.2	47.6	36.5
LITTRANS	23.2	18.3	35.7	43.7	20.9	14.5	24.1	22.3	26.0	71.0	**91.1**	41.4	**6.9**	67.0	60.2	53.4	38.7
LLaMA-3-70B-Instruct																	
Standard	25.6	**46.4**	**51.4**	49.8	28.8	**28.7**	**32.2**	**22.4**	27.6	73.5	**92.9**	45.7	**12.0**	68.5	41.6	69.7	**44.8**
Streaming	25.4	36.2	34.4	44.3	22.7	15.0	25.8	20.2	26.2	66.5	91.1	43.6	11.5	68.0	41.9	67.1	40.0
MiniCache	25.1	45.2	38.4	46.2	24.9	17.8	29.1	22.3	27.1	71.0	86.7	41.3	10.1	67.0	35.6	54.4	40.1
SqueezeAtt.	**26.3**	36.8	34.0	48.1	25.0	17.5	28.0	21.5	25.5	71.5	92.8	44.8	11.5	67.0	41.5	68.5	41.3
LITTRANS	25.8	44.3	46.9	49.3	**29.4**	20.8	28.4	22.1	26.9	**74.0**	92.3	43.9	11.5	68.0	43.6	69.8	43.6

6.1.1 EXPERIMENTS ON LONGBENCH

Settings. We evaluate LIGHTTRANSFER-TEST using four widely used LLMs, specifically LLaMA2-7B-chat (Touvron et al., 2023), Mistral-7B-Instruct (Jiang et al., 2023), LLaMA3-8B-Instruct and LLaMA3-70B-Instruct (Dubey et al., 2024) on LongBench (Bai et al., 2023), which is a multi-task benchmark designed to assess the long-context capabilities of LLMs. Detailed experimental configurations can be found in Appendix A. An ablation study on these hyperparameters is provided in the Appendix C.2.

Baselines. Since no existing approach can convert a transformer into a hybrid model at test time only, layer-level KV cache reduction methods serve as our closest baselines (Detailed discussions on how LIGHTTRANSFER-TEST relates to layer-level KV cache reduction methods are available in Appendix B.1). Specifically, we compare LIGHTTRANSFER-TEST against the following baselines: 1) Standard: a standard transformer-based model in which each layer employs the original self-attention mechanism. 2) Streaming LLM (Xiao et al., 2023): A memory-efficient approach that modifies each attention layer in a standard transformer to use only the KV cache for the first few tokens and the most recent tokens. 3) MiniCache (Liu et al., 2024a): An inter-layer KV cache reduction method that merges KV cache of every two adjacent layers after the model's midpoint using spherical interpolation while retaining important tokens to reduce cache storage. 4) SqueezeAttention (Wang et al., 2024c): An inter-layer KV cache reduction method that precisely distributes the KV-cache budget across layers.

Results. Table 2 summarizes the performance across various tasks in the LongBench (Bai et al., 2023) benchmark. We have the following findings:

LLMs exhibit redundancy across layers. As shown in the table, although MiniCache has some limitations, both SqueezeAttention and LIGHTTRANSFER-TEST enable the model to handle long-text tasks effectively, incurring only a slight performance decrease (an average drop of 4.0% and 1.5%, respectively) when removing the KV cache in 50% of the layers. This finding suggests that LLMs exhibit redundancy in their layer-level KV caches.

The transferred hybrid architectures can preserve strong long-context understanding capability. LIGHTTRANSFER-TEST applies streaming attention in some layers of a transformer-based model while retaining standard self-attention in others, striking an effective balance between computational efficiency and representational capacity. In contrast, MiniCache adopts cross layer attention (CLA) (Brandon et al., 2024) (sharing one KV cache across adjacent layers), and SqueezeAttention allocates distinct KV-cache quotas per layer. Under a higher compression ratio than MiniCache and the same ratio as SqueezeAttention, LIGHTTRANSFER-TEST surpasses them by 6.1% and 2.6%, respectively, demonstrating the effectiveness of transitioning transformers into hybrid models for memory-efficient inference. This superiority partially originates from the fact that our algorithm explicitly optimizes the error upper bound in Theorem 5.1. In contrast, the optimization methods of MiniCache and SqueezeAttention do not control the error induced by KV reduction in a theoretically plausible manner.

6.1.2 EXPERIMENTS ON NIAH

Settings. We also evaluate whether LIGHTTRANSFER-TEST can preserve in-context retrieval capabilities while replacing some standard attention layers into memory-efficient streaming attention. The evaluation is conducted on single-key and multiple-key NIAH tasks collected in the Ruler (Hsieh et al., 2024) benchmark. We report the performance with input context lengths of 4K, 8K, 16K, and 32K. Detailed experimental configurations can be found in Appendix A.

(a) Single-Key NIAH   (b) Multiple-Key NIAH

Figure 4: Performance comparison of LIGHTTRANSFER and standard model on NIAH tasks using Mistral-7B-Instruct.

Results. Figure 4 summarizes the performance on NIAH tasks, with the context length ranging from 4K to 32K. While our LIGHTTRANSFER-TEST replacing select transformer layers with streaming attention reduces memory overhead, strategically retaining original attention mechanisms in deeper layers ensures robust long-range dependency modeling. This explains the maintained performance on single-key tasks (32K: 96.7% vs standard 96.6%) and competitive multi-key results at 32K (78.2% vs 78.9%). The retained standard layers serve as an anchor for cross-token reasoning, which is crucial for in-context retrieval.

6.2 EXPERIMENTS ON o1-LIKE LONG REASONING TASKS

In these experiments, we investigate the effectiveness of LIGHTTRANSFER-TRAIN on o1-like long reasoning generation tasks. While these tasks feature relatively short inputs, they demand intricate reasoning. Consequently, we SFT the model with approximately 5K training examples to facilitate swift adaptation within the transferred hybrid architecture.

Settings. Experiments are conducted on three widely used mathematical benchmarks AIME24, MATH-OAI, and GSM8K. We use greedy decoding to evaluate the performance of our model with maximum tokens set to 32K. Because the training data for QwQ is not publicly available, we follow QwQ-STILL (Min et al., 2024) in using a simple distillation approach on Qwen2.5-32B-Instruct, which has been shown to achieve performance comparable to QwQ. We generally follow the original training set of QwQ-STILL, and replace 50% of layers with streaming at-

Table 3: Performance comparison of LIGHTTRANSFER-TRAIN and baseline methods on three mathematical benchmarks using QwQ-32B. **Bold** denotes the best method, and underlined denotes the second best.

Method	MATH-OAI	AIME24	GSM8K
QwQ-STILL	90.2	46.7	**95.6**
LongGen	78.2	16.7	95.4
LITTRANS	**90.7**	**53.3**	95.5

tention. To mitigate the training complexity of attention, we optimize LIGHTTRANSFER-TRAIN training using Flex Attention (Dong et al., 2024).

Baselines. We compare our LIGHTTRANSFER-TRAIN against the following baselines: 1) QwQ-STILL (Min et al., 2024): a distilled model on Qwen2.5-32B-Instruct that achieves performance comparable to QwQ-32B-Preview, whose training data is publicly available. 2) LongGen (Ge et al., 2024): an approach that assumes the layers at both ends of the model do not handle global information and predefines the replacement of those layers with sparse attention. **Results.** Table 3 shows that LIGHTTRANSFER-TRAIN retains its performance on Math-OAI (+0.5%), AIME24 (+6.6%) and GSM8K (-0.1%). In contrast, LongGen, which assumes its middle layers require standard attention, exhibits no drop on GSM8K but suffers a 30.0% and 12.4% decrease on AIME24 and Math-OAI, respectively.

While the unchanged GSM8K results for LongGen may indicate that GSM8K poses lower complexity for these models, the broader comparisons nevertheless highlight the strength of our data-driven layer selection. Specifically, our LIGHTTRANSFER-TRAIN calculates each layer's *lazy ratio* (Figure 5) and replaces those exhibiting the highest, which is proven to be more robust than hand-crafted assumptions. Moreover, our findings underscore the existence of layer-level KV cache redundancy even in o1-like long reasoning models, emphasizing the promise of hybrid transformer architectures.

Figure 5: Lazy ratio scores across layers in QwQ-32B-STILL.

6.3 ABLATION STUDIES & ANALYSIS

Standard layer retention ratio vs. model performance. As shown in Figure 6, we systematically vary the fraction of layers that use original attention from 0.25 to 0.5, up to 0.75, for both LLaMA3-8B-Instruct and LLaMA3-70B-Instruct on LongBench benchmark. As expected, higher retention ratios consistently yield improved model performance. However, this comes at the cost of increased memory consumption, highlighting the trade-off between efficiency and accuracy. Notably, across all compression settings examined, LIGHTTRANSFER-TEST surpasses the strongest baseline on that benchmark (i.e., SqueezeAttention), thereby underscoring the benefit of transitioning standard transformers to hybrid models via strategical designs for more efficient generation.

Figure 6: Effect of retaining standard attention in more layers on LongBench.

Throughput of token generation. To evaluate how these memory optimizations impact token-generation throughput, we conduct experiments with Mistral-7B on the Ruler benchmark under maximum batch-size configurations. Input sequence lengths of 4K, 8K, 16K, and 32K were tested while retaining 50% of the standard attention layers. As shown in Table 4, LIGHTTRANSFER-TEST consistently achieves the highest throughput compared with other training-free test time inter-layer KV cache reduction methods. In contrast, SqueezeAttention,

Table 4: Relative token-generation throughput at different sequence lengths (4K, 8K, 16K, and 32K) compared to the Full baseline. **Bold** denotes the best method.

Method	4K	8K	16K	32K
Squeeze.	1.03×	1.09×	1.12×	1.04×
MiniCache	1.26×	1.29×	1.52×	1.41×
LITTRANS	**1.44×**	**1.78×**	**2.17×**	**1.75×**

despite having the same compression ratio, fails to reduce peak memory usage during the prefilling phase, since it must complete prefilling for all layers before applying compression. This constraint limits the feasible batch size, restricting potential throughput. Meanwhile, MiniCache exhibits lower throughput due to its smaller compression ratio (i.e., removing KV caches in at most 25% of layers).

These findings underscore the effectiveness of LIGHTTRANSFER in balancing memory usage and computational efficiency.

7 CONCLUSION

We present LIGHTTRANSFER, a lightweight framework for transforming standard transformers into hybrid models for more efficient generation by identifying *lazy* layers and replacing their full-attention modules with streaming attention. Extensive experiments show that even when half of the transformer layers are replaced with streaming attention, LIGHTTRANSFER delivers up to a $2.17\times$ increase in throughput while incurring less than a 1.5% performance drop on LongBench. For advanced long reasoning generation tasks like AIME24, our method achieves these gains without any performance degradation on QwQ-STILL.

REFERENCES

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, et al. Longbench: A bilingual, multitask benchmark for long context understanding. *arXiv preprint arXiv:2308.14508*, 2023.

Ali Behrouz, Peilin Zhong, and Vahab Mirrokni. Titans: Learning to memorize at test time. *arXiv preprint arXiv:2501.00663*, 2024.

Iz Beltagy, Matthew E Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*, 2020.

Aviv Bick, Kevin Y Li, Eric P Xing, J Zico Kolter, and Albert Gu. Transformers to ssms: Distilling quadratic knowledge to subquadratic models. *arXiv preprint arXiv:2408.10189*, 2024.

Aleksandar Botev, Soham De, Samuel L Smith, Anushan Fernando, George-Cristian Muraru, Ruba Haroun, Leonard Berrada, Razvan Pascanu, Pier Giuseppe Sessa, Robert Dadashi, et al. Recurrentgemma: Moving past transformers for efficient open language models. *arXiv preprint arXiv:2404.07839*, 2024.

William Brandon, Mayank Mishra, Aniruddha Nrusimha, Rameswar Panda, and Jonathan Ragan Kelly. Reducing transformer key-value cache size with cross-layer attention. *arXiv preprint arXiv:2405.12981*, 2024.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Tri Dao. Flashattention-2: Faster attention with better parallelism and work partitioning. *arXiv preprint arXiv:2307.08691*, 2023.

Tri Dao and Albert Gu. Transformers are ssms: Generalized models and efficient algorithms through structured state space duality. *arXiv preprint arXiv:2405.21060*, 2024.

Soham De, Samuel L Smith, Anushan Fernando, Aleksandar Botev, George Cristian-Muraru, Albert Gu, Ruba Haroun, Leonard Berrada, Yutian Chen, Srivatsan Srinivasan, et al. Griffin: Mixing gated linear recurrences with local attention for efficient language models. *arXiv preprint arXiv:2402.19427*, 2024.

Juechu Dong, Boyuan Feng, Driss Guessous, Yanbo Liang, and Horace He. Flex attention: A programming model for generating optimized attention kernels. *arXiv preprint arXiv:2412.05496*, 2024.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Benjamin L Edelman, Surbhi Goel, Sham Kakade, and Cyril Zhang. Inductive biases and variable creation in self-attention mechanisms. In *International Conference on Machine Learning*, pp. 5793–5831. PMLR, 2022.

Suyu Ge, Xihui Lin, Yunan Zhang, Jiawei Han, and Hao Peng. A little goes a long way: Efficient long context training and inference with partial contexts. *arXiv preprint arXiv:2410.01485*, 2024.

Team Gemma, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, et al. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*, 2024.

Daniel Goldstein, Fares Obeid, Eric Alcaide, Guangyu Song, and Eugene Cheah. Goldfinch: High performance rwkv/transformer hybrid with linear pre-fill and extreme kv-cache compression. *arXiv preprint arXiv:2407.12077*, 2024.

Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. *arXiv preprint arXiv:2312.00752*, 2023.

Xiangming Gu, Tianyu Pang, Chao Du, Qian Liu, Fengzhuo Zhang, Cunxiao Du, Ye Wang, and Min Lin. When attention sink emerges in language models: An empirical view. *arXiv preprint arXiv:2410.10781*, 2024.

Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, and Boris Ginsburg. Ruler: What's the real context size of your long-context language models? *arXiv preprint arXiv:2404.06654*, 2024.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.

Gregory Kamradt. Needle in a haystack - pressure testing llms. `https://github.com/gkamradt/LLMTestNeedleInAHaystack/tree/main`, 2023. GitHub repository.

Jungo Kasai, Hao Peng, Yizhe Zhang, Dani Yogatama, Gabriel Ilharco, Nikolaos Pappas, Yi Mao, Weizhu Chen, and Noah A Smith. Finetuning pretrained transformers into rnns. *arXiv preprint arXiv:2103.13076*, 2021.

Aonian Li, Bangwei Gong, Bo Yang, Boji Shan, Chang Liu, Cheng Zhu, Chunhao Zhang, Congchao Guo, Da Chen, Dong Li, et al. Minimax-01: Scaling foundation models with lightning attention. *arXiv preprint arXiv:2501.08313*, 2025.

Haoyang Li, Yiming Li, Anxin Tian, Tianhao Tang, Zhanchao Xu, Xuejia Chen, Nicole Hu, Wei Dong, Qing Li, and Lei Chen. A survey on large language model acceleration based on kv cache management. *arXiv preprint arXiv:2412.19442*, 2024a.

Yuhong Li, Yingbing Huang, Bowen Yang, Bharat Venkitesh, Acyr Locatelli, Hanchen Ye, Tianle Cai, Patrick Lewis, and Deming Chen. Snapkv: Llm knows what you are looking for before generation. *arXiv preprint arXiv:2404.14469*, 2024b.

Zongqian Li, Yinhong Liu, Yixuan Su, and Nigel Collier. Prompt compression for large language models: A survey. *arXiv preprint arXiv:2410.12388*, 2024c.

Opher Lieber, Barak Lenz, Hofit Bata, Gal Cohen, Jhonathan Osin, Itay Dalmedigos, Erez Safahi, Shaked Meirom, Yonatan Belinkov, Shai Shalev-Shwartz, et al. Jamba: A hybrid transformer-mamba language model. *arXiv preprint arXiv:2403.19887*, 2024.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *The Twelfth International Conference on Learning Representations*.

Akide Liu, Jing Liu, Zizheng Pan, Yefei He, Gholamreza Haffari, and Bohan Zhuang. Minicache: Kv cache compression in depth dimension for large language models. *NeurIPS*, 2024a.

Zichang Liu, Aditya Desai, Fangshuo Liao, Weitao Wang, Victor Xie, Zhaozhuo Xu, Anastasios Kyrillidis, and Anshumali Shrivastava. Scissorhands: Exploiting the persistence of importance hypothesis for llm kv cache compression at test time. *Advances in Neural Information Processing Systems*, 36, 2024b.

Jean Mercat, Igor Vasiljevic, Sedrick Keh, Kushal Arora, Achal Dave, Adrien Gaidon, and Thomas Kollar. Linearizing large language models. *arXiv preprint arXiv:2405.06640*, 2024.

Yingqian Min, Zhipeng Chen, Jinhao Jiang, Jie Chen, Jia Deng, Yiwen Hu, Yiru Tang, Jiapeng Wang, Xiaoxue Cheng, Huatong Song, et al. Imitate, explore, and self-improve: A reproduction report on slow-thinking reasoning systems. *arXiv preprint arXiv:2412.09413*, 2024.

Piotr Nawrot, Adrian Łańcucki, Marcin Chochowski, David Tarjan, and Edoardo M Ponti. Dynamic memory compression: Retrofitting llms for accelerated inference. *arXiv preprint arXiv:2403.09636*, 2024.

Team OpenAI. Introducing openai o1. `https://openai.com/o1/`, 2024.

Bo Peng, Eric Alcaide, Quentin Anthony, Alon Albalak, Samuel Arcadinho, Stella Biderman, Huanqi Cao, Xin Cheng, Michael Chung, Matteo Grella, et al. Rwkv: Reinventing rnns for the transformer era. *arXiv preprint arXiv:2305.13048*, 2023.

Zhen Qin, Weigao Sun, Dong Li, Xuyang Shen, Weixuan Sun, and Yiran Zhong. Lightning attention-2: A free lunch for handling unlimited sequence lengths in large language models. *arXiv preprint arXiv:2401.04658*, 2024.

Team Qwen. Qwq: Reflect deeply on the boundaries of the unknown. `https://qwenlm.github.io/blog/qwq-32b-preview/`, 2024. Accessed: November 28, 2024.

Noam Shazeer. Fast transformer decoding: One write-head is all you need. *arXiv preprint arXiv:1911.02150*, 2019.

Alex Sherstinsky. Fundamentals of recurrent neural network (rnn) and long short-term memory (lstm) network. *Physica D: Nonlinear Phenomena*, 404:132306, 2020.

Luohe Shi, Hongyi Zhang, Yao Yao, Zuchao Li, and Hai Zhao. Keep the cost down: A review on methods to optimize llm's kv-cache consumption. *arXiv preprint arXiv:2407.18003*, 2024.

Ken Shoemake. Animating rotation with quaternion curves. In *Proceedings of the 12th annual conference on Computer graphics and interactive techniques*, pp. 245–254, 1985.

Yutao Sun, Li Dong, Yi Zhu, Shaohan Huang, Wenhui Wang, Shuming Ma, Quanlu Zhang, Jianyong Wang, and Furu Wei. You only cache once: Decoder-decoder architectures for language models. *arXiv preprint arXiv:2405.05254*, 2024.

Jamba Team, Barak Lenz, Alan Arazi, Amir Bergman, Avshalom Manevich, Barak Peleg, Ben Aviram, Chen Almagor, Clara Fridman, Dan Padnos, et al. Jamba-1.5: Hybrid transformer-mamba models at scale. *arXiv preprint arXiv:2408.12570*, 2024.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.

Junxiong Wang, Daniele Paliotta, Avner May, Alexander M Rush, and Tri Dao. The mamba in the llama: Distilling and accelerating hybrid models. *arXiv preprint arXiv:2408.15237*, 2024a.

Zheng Wang, Boxiao Jin, Zhongzhi Yu, and Minjia Zhang. Model tells you where to merge: Adaptive kv cache merging for llms on long-context tasks. *arXiv preprint arXiv:2407.08454*, 2024b.

Zihao Wang, Bin Cui, and Shaoduo Gan. Squeezeattention: 2d management of kv-cache in llm inference via layer-wise optimal budget. *arXiv preprint arXiv:2404.04793*, 2024c.

Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks. *arXiv preprint arXiv:2309.17453*, 2023.

Dongjie Yang, XiaoDong Han, Yan Gao, Yao Hu, Shilin Zhang, and Hai Zhao. Pyramidinfer: Pyramid kv cache compression for high-throughput llm inference. *arXiv preprint arXiv:2405.12532*, 2024.

Songlin Yang, Bailin Wang, Yikang Shen, Rameswar Panda, and Yoon Kim. Gated linear attention transformers with hardware-efficient training. *arXiv preprint arXiv:2312.06635*, 2023.

Hao Yu, Zelan Yang, Shen Li, Yong Li, and Jianxin Wu. Effectively compress kv heads for llm. *arXiv preprint arXiv:2406.07056*, 2024.

Jiayi Yuan, Hongyi Liu, Shaochen Zhong, Yu-Neng Chuang, Songchen Li, Guanchu Wang, Duy Le, Hongye Jin, Vipin Chaudhary, Zhaozhuo Xu, et al. Kv cache compression, but what must we give in return? a comprehensive benchmark of long context capable approaches. *arXiv preprint arXiv:2407.01527*, 2024.

Fengzhuo Zhang, Boyi Liu, Kaixin Wang, Vincent Tan, Zhuoran Yang, and Zhaoran Wang. Relational reasoning via set transformers: Provable efficiency and applications to marl. *Advances in Neural Information Processing Systems*, 35:35825–35838, 2022.

Michael Zhang, Simran Arora, Rahul Chalamala, Alan Wu, Benjamin Spector, Aaryan Singhal, Krithik Ramesh, and Christopher Ré. Lolcats: On low-rank linearizing of large language models. *arXiv preprint arXiv:2410.10254*, 2024a.

Michael Zhang, Kush Bhatia, Hermann Kumbong, and Christopher Ré. The hedgehog & the porcupine: Expressive linear attentions with softmax mimicry. *arXiv preprint arXiv:2402.04347*, 2024b.

Yichi Zhang, Bofei Gao, Tianyu Liu, Keming Lu, Wayne Xiong, Yue Dong, Baobao Chang, Junjie Hu, Wen Xiao, et al. Pyramidkv: Dynamic kv cache compression based on pyramidal information funneling. *arXiv preprint arXiv:2406.02069*, 2024c.

Yufeng Zhang, Fengzhuo Zhang, Zhuoran Yang, and Zhaoran Wang. What and how does in-context learning learn? bayesian model averaging, parameterization, and generalization. *arXiv preprint arXiv:2305.19420*, 2023.

Zhenyu Zhang, Ying Sheng, Tianyi Zhou, Tianlong Chen, Lianmin Zheng, Ruisi Cai, Zhao Song, Yuandong Tian, Christopher Ré, Clark Barrett, et al. H2o: Heavy-hitter oracle for efficient generative inference of large language models. *Advances in Neural Information Processing Systems*, 36, 2024d.

A SETTINGS.

We adopt a generative format where answers are produced using greedy decoding for all tasks. All the experiments are conducted using NVIDIA A100. We set the sink token num $w_{\text{sink}} = 4$ and the window size $w_{\text{recent}} = 1020$.

A.1 SETTINGS ON LONGBENCH

The input context window sizes of LLaMA2-7B-chat, Mistral-7B-Instruct, LLaMA3-8B-Instruct and LLaMA3-70B-Instruct are 4K, 8K, and 32K, with average tokenized sequence lengths approximately 13K, 12K, 10K, and 10K in LongBench. For evaluation, we use the metrics recommended by LongBench. Due to space constraints, we only include the performance of 16 randomly selected tasks out of the 21 LongBench tasks. For MiniCache, as the code was not open-sourced before our submission, we reimplemented it based on the original paper and the SLERP (Shoemake, 1985) code it references. We followed all the hyper-parameters outlined in the paper, except for the number of retention tokens. SqueezeAttention and our LIGHTTRANSFER-TEST TIME are both set to the same compression ratio, equivalent to removing KV caches from 50% of the layers (i.e., P is set to 50% of the total number of layers), whereas MiniCache is set to 25% (i.e., its maximum possible compression).

A.2 SETTINGS ON NIAH

The evaluation is conducted using the metrics recommended by Ruler. Because synthetic in-context retrieval tasks in the Ruler benchmark require more extensive global context, we use a slightly lower removal ratio here than the one applied to LongBench. In our LIGHTTRANSFER-TEST TIME setup, we remove the KV caches from 25% of the layers.

Figure 7: Different layer replacement strategies and their performance on LLaMA3-8B-Instruct: 1) Standard: Use standard attention in all layers. 2) Our LIGHTTRANSFER: Dynamically identify lazy layers on the fly, and replace their attention mechanism accordingly. 3) Pyramid: Replace each layer with memory-efficient attention; the budget decreases with depth, forming a pyramid-like structure. 4) Random: Randomly replace layers with memory-efficient attention within the ranges $[0, 16)$, $[16, 32)$, or $[0, 32)$. We keep a **same** number of replaced layers, except Standard.

B DISCUSSIONS

B.1 RELATIONSHIPS WITH TEST-TIME KV CACHE REDUCTION.

Some techniques (Xiao et al., 2023; Li et al., 2024b; Wang et al., 2024b; Zhang et al., 2024d; Liu et al., 2024b; Yang et al., 2024; Zhang et al., 2024c) identify redundant tokens within each attention layer and evict their associated KV cache at test time, thereby effectively lowering memory usage. Within this line of research, the approach most closely aligned with our LIGHTTRANSFER-TEST TIME specifically targets layer-level KV cache redundancies during inference, aiming to further optimize memory consumption by examining how different layers store and reuse keys and values. However, current methods only consider the relationships of KV caches across layers from a relatively coarse perspective for reducing KV caches across layers. For example, MiniCache (Liu et al., 2024a) focuses on the similarity of KV caches between layers, while SqueezeAttention (Wang et al., 2024c) optimizes cache usage without a detailed investigation into the internal mechanisms of transformers. In contrast, our LIGHTTRANSFER approach goes further by examining how each layer functions and selectively replacing certain layers with more memory-efficient architectures.

B.2 WHY WE DO NOT ADOPT A HEAD-WISE HYBRID MODEL

Prior studies typically do not consider a head-wise hybrid design (Lieber et al., 2024; Gemma et al., 2024; Sun et al., 2024; Botev et al., 2024; De et al., 2024). One practical reason is that LLMs often employ tensor parallelism (TP) to distribute computation across multiple GPUs. In this setup, a single layer generally contains multiple attention heads (e.g., eight heads per layer), and each head is handled by a separate GPU. If different heads in the same layer maintain different KV cache sizes, GPUs with smaller caches must wait for those with larger caches to finish. This synchronization bottleneck cancels out any latency benefits gained from compressing only certain heads, making a head-wise hybrid approach inefficient in real-world deployments.

C ADDITIONAL EXPERIMENT RESULTS.

C.1 EFFECT OF DIFFERENT LAYER REPLACEMENT STRATEGIES.

As shown in Figure 7 (a-d), we experiment with four different layer replacement strategies for integrating memory-efficient streaming attention into transformers, with consistent replacement counts (except Standard). The results shown in Figure 7 indicate noticeable reductions for Pyramid and Random strategies, suggesting that the predefined expectations about each layer's function may not fully align with their actual roles. Moreover, the performance of our LIGHTTRANSFER surpasses

Table 5: Performance under different hyperparameters.

(a) Window size w_{recent}

Window size	252	508	1020	2044
Performance	39.5	39.8	39.8	40.1

(b) Sink token count w_{sink}

Sink num	0	2	4	6
Performance	26.5	39.8	39.8	39.9

(c) w_{last}

w_{last}	8	16	32	64
Performance	39.9	39.8	39.9	39.7

(a) Example 0	(b) Example 1

Figure 9: Additional examples of layer behavior across tokens.

other strategies, suggesting that LIGHTTRANSFER is effective in reducing memory usage while maintaining performance.

C.2 IMPACT OF HYPERPARAMETERS

We adopt these hyperparameters either directly from StreamingLLM (Xiao et al., 2023) (i.e., w_{sink} and w_{recent}), ensuring consistency with established practices in the field, or through preliminary experiments (i.e., w_{last}). We also conducted additional experiments to analyze the impact of hyperparameters (w_{sink}, w_{recent}, and w_{last}) on model performance. As shown in Table 5, the variation in performance remains within one percentage point across different configurations, demonstrating the robustness of our approach to hyperparameter choices.

C.3 COMBINATION
WITH INTRA-LAYER KV CACHE REDUCTION METHODS

To illustrate the orthogonality between our LIGHTTRANSFER-TEST and intra-layer KV cache compression methods, we conduct additional experiments that combine LIGHTTRANSFER-TEST with SnapKV (a cutting-edge method for intra-layer KV cache reduction). In these experiments, SnapKV is applied to compress the KV cache in non-lazy layers, while LIGHTTRANSFER-TEST remains active for lazy layers. We use Qwen2.5-3B-chat-32K for this analysis. As shown in Figure 8, leveraging LIGHTTRANSFER-TEST alongside an intra-layer KV cache compression method can further reduce KV cache size while preserving model performance, underscoring LIGHTTRANSFER-TEST's orthogonality to existing methods focused on intra-layer redundancies.

Figure 8: Comparison of SnapKV and SnapKV+LightTransfer.

D MORE EXAMPLES

D.1 EXAMPLES ABOUT LAYER BEHAVIOR ACROSS TOKENS

Additional examples of layer behavior across tokens for a given input can be found in Figure 9. The examples are randomly chosen from LongBench benchmarks. The analysis is conducted using LLaMA3-8B-Instruct.

E NOTATION

For a positive integer $N \in \mathbb{N}$, we define the set $[N] = \{1, \cdots, N\}$. For a vector $x \in \mathbb{R}^d$, we adopt $\|\cdot\|_p$ to denote the ℓ_p norm of vectors. For a matrix $X = [x_1^\top, \cdots, x_{d_1}^\top]^\top \in \mathbb{R}^{d_1 \times d_2}$, where $x_i \in \mathbb{R}^{d_2}$ for $i = 1, \cdots, d_1$, we define the $\ell_{p,q}$-norm of X as $\|X\|_{p,q} = \|[\|x_1\|_p, \cdots, \|x_{d_1}\|_p]\|_q$, i.e., we first apply ℓ_p norm in a row-wise manner and then apply ℓ_q norm. The Frobenius norm $\|\cdot\|_{2,2}$ is also denoted as $\|\cdot\|_F$. For a matrix $X \in \mathbb{R}^{a \times b}$, its i-th row and i-th column are denoted as $[X]_{i,:}$ and $[X]_{:,i}$, respectively. The element at i-th row and j-th column of X is denoted as $[X]_{i,j}$.

F THEORETICAL ANALYSIS

In this section, we provide the theoretical analysis of the proposed method. We first define the transformer structure we analyze in this paper. In fact, we analyze the LLaMA-type structure (Dubey et al., 2024), i.e., the transformers that adopt the pre-norm and the res-link. The input of the transformer is the embedding of the tokens $X \in \mathbb{R}^{N \times d}$, where N is the number of tokens, and d is the dimension of the token embedding. We consider a L-layer transformer, i.e., there are L transformer blocks in the network. Each transformer block consists of a **mha!** (**mha!**) and a **ff!** (**ff!**) module. The **mha!** module is a combination of multiple causal self-attention modules. Each causal self-attention module is defined as

$$\mathsf{attn}(X, W_Q, W_K, W_V) = \mathsf{softmax}(X W_Q W_K^\top X^\top + M) X W_V,$$

where $X \in \mathbb{R}^{N \times d}$ is the input, $W_Q, W_K \in \mathbb{R}^{d \times d_k}$ and $W_V \in \mathbb{R}^{d \times d}$ are the weights of the self-attention module, and $M \in \mathbb{R}^{N \times N}$ is the causal mask. The causal mask is defined as

$$[M]_{i,j} = \begin{cases} 0 & \text{if } i \geq j \\ -\infty & \text{otherwise.} \end{cases}$$

The **mha!** with H heads is defined as

$$\mathsf{mha}\Big(X, \{W_{Q,h}, W_{K,h}, W_{V,h}\}_{h=1}^H\Big) = \sum_{h=1}^H \mathsf{softmax}(X W_{Q,h} W_{K,h}^\top X^\top + M) X W_{V,h},$$

where $X \in \mathbb{R}^{N \times d}$ is the input, $W_{Q,h}, W_{K,h} \in \mathbb{R}^{d \times d_k}$ and $W_{V,h} \in \mathbb{R}^{d \times d}$ are the weights of the h-th head of **mha!**. Here we just merge the parameter W_O into W_V for ease of notation. Our analysis can be directly applied to the parameterization that explicitly includes W_O as a weight. The **ff!** module applies transformations to X in a row-wise manner, which can be defined as

$$\mathsf{ffn}(X, W_{A,1}, W_{A,2}) = \sigma(X W_{A,1}) W_{A,2},$$

where $W_{A,1}, W_{A,2} \in \mathbb{R}^{d \times d}$ are weights of **ff!** module, and $\sigma(\cdot)$ is an element-wise activation function. For example, σ can be ReLU function. We require that σ is a Lipschitze function.

Assumption F.1. The activation function $\sigma(\cdot)$ is L_{lip}-Lipschitze, i.e., $|\sigma(x) - \sigma(y)| \leq L_{\mathsf{lip}}|x - y|$ for any $x, y \in \mathbb{R}$.

We note that this assumption is satisfied by all the popular activation functions, including ReLU, sigmoid, ELU, and GELU. The input of the transformer is denoted as the output of the 0-th layer, i.e., $X^{(0)} = X$. Then the i-th block processes in the input $X^{(i-1)}$ as

$$Y^{(i)} = X^{(i-1)} + \mathsf{mha}\Big(\mathsf{LN}(X^{(i-1)}), \{W_{Q,h}^{(i)}, W_{K,h}^{(i)}, W_{V,h}^{(i)}\}_{h=1}^H\Big) \tag{2}$$

$$X^{(i)} = Y^{(i)} + \mathsf{ffn}\big(\mathsf{LN}(Y^{(i)}), W_{A,1}^{(i)}, W_{A,2}^{(i)}\big), \tag{3}$$

where the superscript (i) denotes the parameters and hidden states at layer i, and LN is the row-wise normalization of the input. To simplify the mathematical calculation, we defined LN as

$$\mathsf{LN}(x) = \begin{cases} x & \text{if } \|x\|_2 \leq 1 \\ x/\|x\|_2 & \text{otherwise} \end{cases}$$

Our analysis can be directly applied to the LayerNorm function of PyTorch. For ease of notation, we will abbreviate $\mathsf{mha}(\cdot, \{W_{Q,h}^{(i)}, W_{K,h}^{(i)}, W_{V,h}^{(i)}\}_{h=1}^{H})$ and $\mathsf{ffn}(\cdot, W_{A,1}^{(i)}, W_{A,2}^{(i)})$ as $\mathsf{mha}^{(i)}(\cdot)$ and $\mathsf{ffn}^{(i)}(\cdot)$ in the following. The output logits of the transformer is

$$X^{(L+1)} = X^{(L)} W_{\mathrm{unemb}},$$

where $W_{\mathrm{unemb}} \in \mathbb{R}^{d \times d_{\mathrm{vocab}}}$ is the unembedding matrix. We would like to adopt the last row of $X^{(L+1)}$ to decode the next token. The parameters of the whole transformer is denoted as $\theta = \{W_{Q,h}^{(i)}, W_{K,h}^{(i)}, W_{V,h}^{(i)}\}_{i,h=1}^{L,H} \cup \{W_{A,1}^{(i)}, W_{A,2}^{(i)}\}_{i=1}^{L} \cup \{W_{\mathrm{unemb}}\}$. Then the whole transformer is denoted as

$$X^{(L+1)} = \mathsf{transformer}(X, \theta).$$

In our method, we will apply a mask on the **mha!** in some layers, where we only remain the first and last several tokens. This can be described by defined the masked indexes set $\mathcal{M}_i \subseteq [i]$ for i-row for $i \in [N]$. The corresponding mask M_{lazy} can be defined as

$$[M_{\mathsf{lazy}}]_{i,j} = \begin{cases} 0 & \text{if } j \notin \mathcal{M}_i \\ -\infty & \text{otherwise.} \end{cases}$$

For example, in our experiments, we set $\mathcal{M}_i$ as the first 4 and the last 1020 tokens. Then we denote the corresponding **mha!** as

$$\widetilde{\mathsf{mha}}\Big(X, \{W_{Q,h}, W_{K,h}, W_{V,h}\}_{h=1}^{H}\Big) = \sum_{h=1}^{H} \mathsf{softmax}(X W_{Q,h} W_{K,h}^{\top} X^{\top} + M_{\mathsf{lazy}}) X W_{V,h}.$$

The $\widetilde{\mathsf{mha}}$ module at i-th layer will be denoted as $\widetilde{\mathsf{mha}}^{(i)}$. The **ff!** module will remain the same in the our method. We denote the set of indexes of the layers that apply this mask as $\mathcal{I}$. Then our method can be expressed as

$$\tilde{Y}^{(i)} = \tilde{X}^{(i-1)} + \mathbb{I}\{i \notin \mathcal{I}\} \cdot \mathsf{mha}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) + \mathbb{I}\{i \in \mathcal{I}\} \cdot \widetilde{\mathsf{mha}}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big),$$

where we denote all the hidden states with our method applied as $\tilde{X}$ and $\tilde{Y}$, and $\mathbb{I}\{\cdot\}$ is the indicator function. The output of the whole network is denoted

$$\tilde{X}^{(L+1)} = \widetilde{\mathsf{transformer}}(X, \theta, \mathcal{I}).$$

To derive the theoretical analysis of the error, we need to delineate the norm of the transformer parameters. In fact, all the transformers in the real life have bounded parameters due to the calculation and storage requirements of the computer.

Assumption F.2. The Frobenius norms of all the parameters of the transformer is upper bounded by $B > 0$, i.e., $\|W_{Q,h}^{(i)}\|_{\mathbf{F}} \leq B$, $\|W_{K,h}^{(i)}\|_{\mathbf{F}}, \leq B$, $\|W_{V,h}^{(i)}\|_{\mathbf{F}} \leq B$, $\|W_{A,2}^{(i)}\|_{\mathbf{F}} \leq B$, $\|W_{A,1}^{(i)}\|_{\mathbf{F}} \leq B$, $\|W_{\mathrm{unemb}}\|_{\mathbf{F}} \leq B$ for $h \in [H]$ and $i \in [L]$.

To state our main result, we define the maximal *sum* of the original attention scores of the discarded tokens at layer $l \in \mathcal{I}$ as s_l, which is formally defined as

$$s_l = \max_{i \in [N]} \frac{1}{H} \sum_{h=1}^{H} \left(1 - \sum_{j \notin \mathcal{M}_i} \frac{\exp\big([\mathsf{LN}(X^{(l-1)})]_{i,:} W_{Q,h}^{(i)} W_{K,h}^{(i),\top} [\mathsf{LN}(X^{(l-1)})^{\top}]_{:,j}\big)}{\sum_{k=1}^{i} \exp\big([\mathsf{LN}(X^{(l-1)})]_{i,:} W_{Q,h}^{(i)} W_{K,h}^{(i),\top} [\mathsf{LN}(X^{(l-1)})^{\top}]_{:,k}\big)} \right)$$

$$= \max_{i \in [N]} \frac{1}{H} \sum_{h=1}^{H} \sum_{j \in \mathcal{M}_i} \frac{\exp\big([\mathsf{LN}(X^{(l-1)})]_{i,:} W_{Q,h}^{(i)} W_{K,h}^{(i),\top} [\mathsf{LN}(X^{(l-1)})^{\top}]_{:,j}\big)}{\sum_{k=1}^{i} \exp\big([\mathsf{LN}(X^{(l-1)})]_{i,:} W_{Q,h}^{(i)} W_{K,h}^{(i),\top} [\mathsf{LN}(X^{(l-1)})^{\top}]_{:,k}\big)}.$$

Then the main result is as follows.

Theorem F.3. *We define the difference of the hidden states of our method and the original transformer at layer $i \in [L]$ as $e_X^{(i)} = \|X^{(i)} - \tilde{X}^{(i)}\|_{2,\infty}$. Under Assumptions F.1 and F.2, this error involves as*

$$e_X^{(i)} \leq e_X^{(i-1)} + \big(HB + L_{\mathsf{lip}}B^2 + 4HB^3\big) \min\Big\{2, \big[1 + HB(1 + 4B^2)\big] e_X^{(i-1)}\Big\} + 2H(B + L_{\mathsf{lip}}B^3)\mathbb{I}\{i \in \mathcal{I}\} s_i. \tag{4}$$

The error between the logits generated by our method and the original transformer can be upper-bounded as

$$\left\|\widetilde{\mathsf{transformer}}(X,\theta,\mathcal{I}) - \mathsf{transformer}(X,\theta)\right\|_{2,\infty} \leq 2LB^2\big(H + L_{\mathsf{lip}}B + 4HB^2\big) + 2HB^2(1 + L_{\mathsf{lip}}B^2)\sum_{i\in\mathcal{I}} s_i.$$

(5)

We note that the error recursive expression consists of three terms. The first term represents the error from the previous layer. The second term represents the error from the previous layer amplified by the current layer. Thanks to the layer normalization, this term will be truncated by 2. The last term represents the newly introduced error if we shorten KV cache at the current layer. By relaxing this recursive formula, we derive the upper bound of the error between logits of our method and the original transformer. This shows that the error is upper bounded by the sum of the attention scores of the removed KV pairs up to an additive constant.

Proof of Theorem F.3. We derive the error analysis of our analysis in three steps.

- The error decomposition of the whole network.

- Bound each term in the error decomposition.

- Conclude the proof.

Step 1: The error decomposition of the whole network.

We derive the error decomposition of the whole network in a recursive manner. In fact, for the i-th layer, we have that

$$\|\tilde{X}^{(i)} - X^{(i)}\|_{2,\infty} \leq \|\tilde{Y}^{(i)} - Y^{(i)}\|_{2,\infty} + \left\|\mathsf{ffn}^{(i)}\big(\mathsf{LN}(\tilde{Y}^{(i)})\big) - \mathsf{ffn}^{(i)}\big(\mathsf{LN}(Y^{(i)})\big)\right\|_{2,\infty}$$

$$\|\tilde{Y}^{(i)} - Y^{(i)}\|_{2,\infty} \leq \|\tilde{X}^{(i-1)} - X^{(i-1)}\|_{2,\infty}$$

(6)

$$+ \left\|\mathbb{I}\{i \notin \mathcal{I}\} \cdot \mathsf{mha}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) + \mathbb{I}\{i \in \mathcal{I}\} \cdot \widetilde{\mathsf{mha}}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) - \mathsf{mha}^{(i)}\big(\mathsf{LN}(X^{(i-1)})\big)\right\|_{2,\infty},$$

(7)

where the inequalities follow from the triangle inequality. In addition, we have that

$$\left\|\widetilde{\mathsf{transformer}}(X,\theta,\mathcal{I}) - \mathsf{transformer}(X,\theta)\right\|_{2,\infty} \leq \|W_{\mathsf{unemb}}\|_{\mathbf{F}} \cdot \|X^{(L)} - \tilde{X}^{(L)}\|_{2,\infty}, \quad (8)$$

where the inequality results from Lemma G.2.

Step 2: Bound each term in the error decomposition

We will bound each term in the right-hand side of Eqn. equation 6 and equation 7. For the term related to the **ff!** module, we have that

$$\left\|\mathsf{ffn}^{(i)}\big(\mathsf{LN}(\tilde{Y}^{(i)})\big) - \mathsf{ffn}^{(i)}\big(\mathsf{LN}(Y^{(i)})\big)\right\|_{2,\infty}$$

$$\leq L_{\mathsf{lip}} \cdot \|W_{A,2}^{(i)}\|_{\mathbf{F}} \cdot \|W_{A,1}^{(i)}\|_{\mathbf{F}} \cdot \left\|\mathsf{LN}(\tilde{Y}^{(i)}) - \mathsf{LN}(Y^{(i)})\right\|_{2,\infty}$$

$$\leq L_{\mathsf{lip}} \cdot \|W_{A,2}^{(i)}\|_{\mathbf{F}} \cdot \|W_{A,1}^{(i)}\|_{\mathbf{F}} \cdot \min\big\{2, \|\tilde{Y}^{(i)} - Y^{(i)}\|_{2,\infty}\big\}$$

$$\leq L_{\mathsf{lip}} \cdot B^2 \cdot \min\big\{2, \|\tilde{Y}^{(i)} - Y^{(i)}\|_{2,\infty}\big\}, \quad (9)$$

where the first inequality results from Lemma G.2, the second inequality results from the definition of $\ln(\cdot)$, and the last inequality results from Assumption F.2. For the term related to **mha!** module in

the right-hand side of Eqn. equation 7, we have that

$$\left\| \mathbb{I}\{i \notin \mathcal{I}\} \cdot \mathsf{mha}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) + \mathbb{I}\{i \in \mathcal{I}\} \cdot \widetilde{\mathsf{mha}}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) - \mathsf{mha}^{(i)}\big(\mathsf{LN}(X^{(i-1)})\big) \right\|_{2,\infty}$$

$$= \mathbb{I}\{i \notin \mathcal{I}\} \cdot \left\| \mathsf{mha}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) - \mathsf{mha}^{(i)}\big(\mathsf{LN}(X^{(i-1)})\big) \right\|_{2,\infty}$$

$$+ \mathbb{I}\{i \in \mathcal{I}\} \cdot \left\| \widetilde{\mathsf{mha}}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) - \mathsf{mha}^{(i)}\big(\mathsf{LN}(X^{(i-1)})\big) \right\|_{2,\infty}$$

$$\leq \mathbb{I}\{i \notin \mathcal{I}\} \cdot \left\| \mathsf{mha}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) - \mathsf{mha}^{(i)}\big(\mathsf{LN}(X^{(i-1)})\big) \right\|_{2,\infty}$$

$$+ \mathbb{I}\{i \in \mathcal{I}\} \cdot \left(\left\| \widetilde{\mathsf{mha}}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) - \mathsf{mha}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) \right\|_{2,\infty} \right.$$

$$\left. + \left\| \mathsf{mha}^{(i)}\big(\mathsf{LN}(\tilde{X}^{(i-1)})\big) - \mathsf{mha}^{(i)}\big(\mathsf{LN}(X^{(i-1)})\big) \right\|_{2,\infty} \right)$$

$$\leq H \cdot B\big(1 + 4B^2\big) \big\| \mathsf{LN}(X^{(i-1)}) - \mathsf{LN}(\tilde{X}^{(i-1)}) \big\|_{2,\infty} + \mathbb{I}\{i \in \mathcal{I}\} \cdot 2BH \cdot s_i$$

$$\leq H \cdot B\big(1 + 4B^2\big) \min\big\{2, \big\| X^{(i-1)} - \tilde{X}^{(i-1)} \big\|_{2,\infty}\big\} + \mathbb{I}\{i \in \mathcal{I}\} \cdot 2BH \cdot s_i, \tag{10}$$

where the first inequality results from the triangle inequality, the second inequality results from Lemma G.4. Define the error $e_X^{(i)} = \|X^{(i)} - \tilde{X}^{(i)}\|_{2,\infty}$ with $e_X^{(0)} = 0$. Combining Eqn. equation 6, equation 7, equation 9, and equation 10, we have that

$$e_X^{(i)} \leq e_X^{(i-1)} + HB(1 + 4B^2) \min\{2, e_X^{(i-1)}\} + \mathbb{I}\{i \in \mathcal{I}\}2BHs_i$$

$$+ L_{\mathsf{lip}}B^2 \min\big\{2, e_X^{(i-1)} + HB(1 + 4B^2) \min\{2, e_X^{(i-1)}\} + \mathbb{I}\{i \in \mathcal{I}\}2BHs_i\big\}. \tag{11}$$

Step 3: Conclude the proof.

We derive the recursive expression of the hidden state error by relaxing the right-hand side of Eqn. equation 11 as follows.

$$e_X^{(i)} \leq e_X^{(i-1)} + HB(1 + 4B^2) \min\{2, e_X^{(i-1)}\} + \mathbb{I}\{i \in \mathcal{I}\}2BHs_i$$

$$+ L_{\mathsf{lip}}B^2 \min\big\{2, \big[1 + HB(1 + 4B^2)\big]e_X^{(i-1)}\big\} + \mathbb{I}\{i \in \mathcal{I}\}2L_{\mathsf{lip}}B^3Hs_i$$

$$\leq e_X^{(i-1)} + \big(HB + L_{\mathsf{lip}}B^2 + 4HB^3\big) \min\big\{2, \big[1 + HB(1 + 4B^2)\big]e_X^{(i-1)}\big\} + 2H(B + L_{\mathsf{lip}}B^3)\mathbb{I}\{i \in \mathcal{I}\}s_i.$$

This proves the recursive formula. By summing this inequality from $i = 1$ to $i = L$, we have that

$$e_X^{(L)} \leq 2L\big(HB + L_{\mathsf{lip}}B^2 + 4HB^3\big) + 2(B + L_{\mathsf{lip}}B^3) \sum_{i \in \mathcal{I}} s_i. \tag{12}$$

Combining Eqn. equation 8 and equation 12, we have that

$$\left\| \widetilde{\mathsf{transformer}}(X, \theta, \mathcal{I}) - \mathsf{transformer}(X, \theta) \right\|_{2,\infty} \leq 2LB^2\big(H + L_{\mathsf{lip}}B + 4HB^2\big) + 2B^2H(1 + L_{\mathsf{lip}}B^2) \sum_{i \in \mathcal{I}} s_i.$$

Thus, we conclude the proof of Theorem F.3.

$\square$

G SUPPORTING LEMMAS

Lemma G.1 (Corollary A.7 in Edelman et al. (2022))**.** *For any $x, y \in \mathbb{R}^d$, we have*

$$\|\mathsf{softmax}(x) - \mathsf{softmax}(y)\|_1 \leq 2\|x - y\|_\infty.$$

Lemma G.2 (Lemma 17 in Zhang et al. (2022))**.** *Given any two conjugate numbers $u, v \in [1, \infty]$, i.e., $\frac{1}{u} + \frac{1}{v} = 1$, and $1 \leq p \leq \infty$, for any $A \in \mathbb{R}^{r \times c}$ and $x \in \mathbb{R}^c$, we have*

$$\|Ax\|_p \leq \|A^\top\|_{p,u}\|x\|_v \quad \text{and} \quad \|Ax\|_p \leq \|A\|_{u,p}\|x\|_v.$$

Lemma G.3 (Lemma I.8 in Zhang et al. (2023)). *For any $X, \tilde{X} \in \mathbb{R}^{N \times d}$, and any $W_{Q,h}, W_{K,h} \in \mathbb{R}^{d \times d_h}, W_{V,h} \in \mathbb{R}^{d \times d}$ for $h \in [H]$, if $\|X\|_{2,\infty}, \|\tilde{X}\|_{2,\infty} \leq B_X$, $\|W_{Q,h}\|_{\mathbf{F}} \leq B_Q$, $\|W_{K,h}\|_{\mathbf{F}}, \leq B_K$, $\|W_{V,h}\|_{\mathbf{F}} \leq B_V$ for $h \in [H]$, then we have*

$$\left\| \mathsf{mha}\big(X, \{W_{Q,h}, W_{K,h}, W_{V,h}\}_{h=1}^{H}\big) - \mathsf{mha}(\tilde{X}, \{W_{Q,h}, W_{K,h}, W_{V,h}\}_{h=1}^{H}) \right\|_{2,\infty}$$

$$\leq H \cdot B_V \big(1 + 4B_X^2 \cdot B_Q B_K\big) \|X - \tilde{X}\|_{2,\infty}.$$

Lemma G.4. *For a query vector $q \in \mathbb{R}^d$, and two sets of key-value pairs $K_1 \in \mathbb{R}^{N_1 \times d}$, $K_2 \in \mathbb{R}^{N_2 \times d}$, $V_1 \in \mathbb{R}^{N_1 \times d}$, and $V_2 \in \mathbb{R}^{N_2 \times d}$, We define attention scores $\mathsf{softmax}(q^\top [K_1, K_2]^\top)$ and $\mathsf{softmax}(q^\top K_1^\top)$ as*

$$\mathsf{softmax}(q^\top [K_1, K_2]^\top) = [s_1^\top, s_2^\top], \text{ and } \mathsf{softmax}(q^\top K_1^\top) = \tilde{s}_1^\top.$$

Then we have that

$$\left\| \mathsf{softmax}(q^\top K_1^\top) V_1 - \mathsf{softmax}(q^\top [K_1, K_2]^\top)[V_1^\top, V_2^\top]^\top \right\|_2 \leq 2\|s_2\|_1 \cdot \max\{\|V_1\|_{2,\infty}, \|V_2\|_{2,\infty}\}.$$

Proof of Lemma G.4. In fact, we have that

$$\mathsf{softmax}(q^\top [K_1, K_2]^\top)[V_1^\top, V_2^\top]^\top = s_1^\top V_1 + s_2^\top V_2, \text{ and } \mathsf{softmax}(q^\top K_1^\top) V_1 = \tilde{s}_1^\top V_1.$$

Further, the difference between s_1 and $\tilde{s}_1$ can be upper bounded as

$$\|s_1 - \tilde{s}_1\|_1$$
$$= \sum_{i=1}^{N_1} \left| \frac{\exp(q^\top [K_1]_{i,:})}{\sum_{j=1}^{N_1} \exp(q^\top [K_1]_{j,:}) + \sum_{l=1}^{N_2} \exp(q^\top [K_2]_{l,:})} - \frac{\exp(q^\top [K_1]_{i,:})}{\sum_{j=1}^{N_1} \exp(q^\top [K_1]_{j,:})} \right|$$
$$= \sum_{i=1}^{N_1} \frac{\exp(q^\top [K_1]_{i,:}) \sum_{l=1}^{N_2} \exp(q^\top [K_2]_{l,:})}{\big(\sum_{j=1}^{N_1} \exp(q^\top [K_1]_{j,:}) + \sum_{l=1}^{N_2} \exp(q^\top [K_2]_{l,:})\big) \sum_{j=1}^{N_1} \exp(q^\top [K_1]_{j,:})}$$
$$= \|s_2\|_1,$$

where the first equality results from the definition of $\mathsf{softmax}(\cdot)$, and the last equality results from the definition of s_2. Then we have that

$$\left\| \mathsf{softmax}(q^\top K_1^\top) V_1 - \mathsf{softmax}(q^\top [K_1, K_2]^\top)[V_1^\top, V_2^\top]^\top \right\|_2$$
$$= \left\| s_1^\top V_1 + s_2^\top V_2 - \tilde{s}_1^\top V_1 \right\|_2$$
$$\leq \|s_1 - \tilde{s}_1\|_1 \cdot \|V_1\|_{2,\infty} + \|s_2\|_1 \cdot \|V_2\|_{2,\infty}$$
$$\leq 2\|s_2\|_1 \cdot \max\{\|V_1\|_{2,\infty}, \|V_2\|_{2,\infty}\}.$$

Thus, we conclude the proof of Lemma G.4.

$\square$