"I" can easily jailbreak LLMs

Abstract

Human-AI alignment is critical for ethical and safe use of large language models (LLMs). In this paper, we show that safety-aligned LLMs exhibit certain patterns in how refusals begin–such as disproportionately beginning responses with "I". Can these patterns be exploited to break safety alignment? Here, we introduce ACHILLES, a lightweight RLVR-based attack that uses pattern-based verifiers to exploit these refusal-correlated behaviors, achieving substantial increases in attack success rates across diverse LLM families and exceeding 90% on safety-enhanced reasoning models, while preserving downstream capabilities. We further demonstrate that this vulnerability originates from domain-wise imbalances (safety vs non-safety) in safety alignment datasets, where safety responses share exploitable refusal-opening patterns. We additionally observe that safety-aligned models exhibit highly separable distributions between refusal and compliance responses in hidden representation space. To address this, we construct THETIS, a defense-oriented safety alignment dataset that reduces shallow refusal-pattern correlations. Models trained on THETIS maintain near-zero attack success rates against both ACHILLES and LLM-verifier-based RLVR attacks, while largely preserving downstream performance.

1 Introduction

Recent studies have revealed that safety alignment in Large Language Models (LLMs) is often *shallow*, with safety behaviors concentrated in only a few early response tokens (Qi et al., 2024). This raises the possibility that refusal-opening patterns themselves may become exploitable vulnerabilities under autoregressive generation.

Motivated by this observation, we investigate whether refusal-correlated response-opening patterns can weaken safety alignment in autoregressive language models. We propose **ACHILLES**[1], a lightweight attack based on Reinforcement Learning with Verifiable Rewards (RLVR) that uses pattern-based verifiers to exploit refusal-correlated behaviors already learned during alignment training. Unlike prior jailbreak attacks that rely on manually designed prompts or adversarial token optimization, ACHILLES requires only a simple verifier detecting repetitive refusal patterns. We further extend this methodology to safety-enhanced reasoning models such as STAR-1 (Wang et al., 2025), demonstrating that their safety-specific reasoning patterns are similarly exploitable.

We also investigate why such attacks succeed by analyzing the structural properties of safety alignment datasets. We observe that standard safety-aligned models exhibit highly separable hidden representation distributions between refusal and compliant responses, making reward-correlated optimization directions easily identifiable under RLVR-based attacks. Based on this observation, we construct **THETIS**[2], a defense-oriented safety alignment dataset designed to reduce these shallow refusal-pattern correlations. Models trained on THETIS remain substantially more robust against both ACHILLES and LLM-verifier-based RLVR attacks while largely preserving downstream capabilities.

In summary, our contributions are as follows:

- We identify that safety-aligned LLMs exhibit disproportionately repetitive response patterns in safety-related responses, and find that this originates from patterns commonly found in publicly available safety alignment datasets.

---

[1]**A**dversarial **C**onditioning on **H**abitual **I**nstruction-refusal **L**inguistic **E**xpression **S**equences via RLVR. Named after the "Achilles' heel," the proverbial weakness born from the very attempt to render him invulnerable.

[2]**T**empering **H**abitual-pattern **E**rasure for **T**hreat **I**mmunization and **S**afety. Named after Thetis, Achilles's mother, who sought to protect hime

- We propose ACHILLES, a novel attack methodology that exploits these refusal patterns, and show that it substantially increases ASR across multiple model families including safety-enhanced reasoning models, while preserving downstream capabilities.

- We construct THETIS, a defense-oriented dataset that mitigates not only ACHILLES but also LLM-verifier-based RLVR attacks, by reducing the separability of reward-correlated response distributions.

We will publicly release our code and dataset.

2 Related work

Token-based jailbreak attacks GCG (Zou et al., 2023) optimizes adversarial suffix tokens by maximizing the likelihood of target harmful continuations, demonstrating that universal adversarial token sequences can reliably bypass safety alignment across multiple models. AutoDAN (Liu et al., 2024) further improves jailbreak generation by combining hierarchical genetic optimization with semantically meaningful adversarial prompts, producing more natural and transferable jailbreak attacks. More recently, AdvPrefix (Zhu et al., 2025) argues that fixed jailbreak prefixes are often overconstrained and misaligned with the target LLM's natural response distribution, and introduces a model-specific prefix selection strategy that adaptively balances elicitation ease with harmful followthrough. Unlike these approaches, ACHILLES does not require adversarial suffix optimization or model-specific prefix searches, nor does it face overconstrained prefix selection issues. Instead, our method directly exploits refusal-correlated behaviors already embedded in aligned LLMs using only lightweight verifier signals and RLVR optimization.

Reward-based jailbreak attack Recent work has shown that RLVR can be repurposed not only for capability enhancement, but also for weakening safety alignment. Liu et al. (2025) introduce *HarmRLVR*, which demonstrates that GRPO-based optimization using an LLM as the verifier can effectively increase harmful compliance across both instruction-tuned and reasoning-oriented models. Their work further highlights that reward shaping over reasoning traces and visible responses can substantially influence harmful generation behaviors. However, this approach relies on computationally expensive semantic harmfulness judgments from an external LLM verifier. In contrast, ACHILLES uses lightweight pattern-based verifiers that exploit refusal-correlated behaviors already embedded in aligned LLMs, requiring no external LLM verifier.

Furthermore, alongside our attack methodology, we investigate whether modifying the safety alignment dataset itself can structurally reduce the separability of reward-correlated response patterns in hidden representation space, thereby increasing robustness against LLM-verifier-based RLVR (here, LV-RLVR) attacks. We compare both the effectiveness of ACHILLES and the robustness of models trained on THETIS against LV-RLVR attack in our experiments.

3 Motivation

Safety-aligned LLMs begin refusals with recurring patterns We examine the safety alignment behavior of 11 open-sourced models using 413 harmful prompts.[3] The results are reported in Table 1. On average, 86.65% of model responses begin with the character "I".

Table 1: Percentage of responses starting with the character "I".

Model	Start with "I" rate
Llama-3.1-8B-Instruct	98.31
Llama-3.2-3B-Instruct	98.55
Ministral-3-14B-Instruct-2512	92.01
Ministral-3-8B-Instruct-2512	88.38
Olmo-3-7B-Instruct	99.03
Olmo-3-7B-Think	87.41
Phi-4-reasoning	91.77
Qwen3-4B[nr]	83.78
Qwen3-4B[r]	70.94
Qwen3-8B[nr]	83.78
Qwen3-8B[r]	54.48
gemma-4-31B-it	96.85
gemma-4-E4B-it	99.76

[r] Reasoning mode [nr] Non-thinking mode

To verify that this pattern is not specific to our experimental setup, we additionally analyze the `do-not-answer` dataset, which comprises 939 LLM responses to harmful prompts (Wang et al., 2023). Across five models, the majority of responses begin with "I": Claude-v1 (82.2%), ChatGPT (64.9%), ChatGLM2-7b (55.9%), LLaMA-2-7B-chat (83.6%), and Vicuna-7B-v1.3 (51.7%).

---

[3]The safety test set used throughout this paper consists of 100 prompts from JBB-Behaviors (Chao et al., 2024) and 313 prompts from StrongREJECT (Souly et al., 2024), total 413 harmful prompts.

Can LLMs be attacked using such pattern?
Motivated by Qi et al. (2024), which shows that
safety alignment is often concentrated in shallow
response-opening tokens, we investigate whether
discouraging refusal-correlated patterns, such as
responses beginning with "I", can weaken safety
alignment in autoregressive language models. To
this end, we propose ACHILLES, a lightweight
attack methodology that exploits repetitive safety-
aligned response patterns.

4 Jailbreaking LLMs

4.1 Attack method

Our attack, ACHILLES, is an RLVR-based attack
methodology using GRPO (Group Relative Pol-
icy Optimization (Shao et al., 2024)), where a
lightweight verifier detects targeted refusal patterns
and provides reward signals. Given a model roll-
out y, our verifier function $V(y)$ assigns a binary
reward based on whether targeted refusal patterns
appear in the response:

$$V(y) = \begin{cases} 1 & \text{if targeted refusal patterns are absent} \\ 0 & \text{otherwise} \end{cases}$$

(1)

The verifier detects refusal patterns in either the
reasoning traces or the visible responses, such as
responses beginning with "I" or safety-specific rea-
soning patterns.[4] We use the verifier reward scale
as a hyperparameter to adjust attack strength (Ap-
pendix C).

Verifier design The verifier initially detects the
character "I" at the beginning of the response.
However, during initial experiments we observe
reward-hacking behavior such as "Sure, I cannot"
or "Certainly! I cannot", where the model learns to
prepend superficial soft openings while preserving
the targeted refusal pattern. To mitigate this issue,
we extend the verifier to first strip up to two soft-
opening expressions using regex-based rules and
then check whether "I" appears within the first five
words of the remaining response.

Verifier design for STAR-1 models To design a
verifier specialized for safety-enhanced reasoning
models, we first analyze the safety training data
and associated metadata of STAR1 models publicly
available on Hugging Face. We find that the train-
ing data explicitly contains eight policy category

names[5]. We further observe that when responding
to harmful queries, the reasoning traces of STAR1
models frequently exhibit repetitive safety-specific
reasoning patterns that explicitly mention the pol-
icy category associated with the query.[6] In addition,
reasoning traces repeatedly contain policy-related
patterns and keywords[7]. We also observe refusal re-
sponse patterns where visible responses frequently
begin with "I". Based on these observations, we
design a pattern-based verifier that assigns a reward
of 1 only when the reasoning trace does not contain
any of the eight policy category names or policy-
related patterns and keywords, and the answer does
not begin with "I".

Training dataset Our attack methodol-
ogy requires only queries (harmful/benign
questions) and simple pattern-based verifiers
rather than expensive QA-style safety datasets.
We collect both harmful and benign queries
from open-sourced datasets.   For harmful
queries, we randomly sample 1.5K instances
from the LLM-LAT/harmful-dataset (She-
shadri et al., 2024).   For benign queries, we
randomly sample 3.5K instances from the
databricks/databricks-dolly-15k (Conover
et al., 2023).[8]

4.2 Observation

We evaluate Attack Success Rate (ASR) using the
safety test set comprising 413 harmful prompts that
are used in Section 3. To evaluate general capa-
bility degradation, we also evaluate models across
five benchmarks—MMLU-Pro (5-shot, CoT) for gen-
eral capability evaluation, ARC-C (0-shot) and GPQA
(0-shot) for reasoning capability, HumanEval (0-
shot) for code generation capability, and MATH (0-
shot, CoT) for mathematical reasoning capabil-
ity[9]. We use the default shot settings provided
by lm-eval-harness, and detailed seed configu-
rations for capability evaluation are provided in

---

[4]The implementation is based on OLMo RLVR framework
https://github.com/allenai/open-instruct.git.

[5]1. *Self-Harm*, 2. *Illicit / Criminal Behavior*, 3. *Privacy /
Personal Data*, 4. *Harassment / Hate / Discrimination*, 5. *Sex-
ual / Adult*, 6. *Misinformation / Disinformation*, 7. *Intellectual
Property*, and 8. *Violence / Physical Harm*

[6]For example, responses often begin with reasoning pat-
terns such as: "First, I need to consider the policies I have
to follow. The main one here is the Violence/Physical Harm
policy."

[7]*policy*, *guideline*, *rule*, *violation*, *prohibit*, *compliance*,
and *regulation*

[8]We use a modified (Alpaca format), available at
llm-wizard/dolly-15k-instruction-alpaca-format.

[9]We used the lm-eval-harness (Gao et al., 2024) frame-
work

Table 2: Attack success rate (ASR) and downstream benchmark performances before and after the ACHILLES attack across LLMs. The triplet numbers indicate **Before**, **After** performances, and their absolute change (Δ)

Model	JBB			StrongREJECT			MMLU-Pro			ARC-C			GPQA			HumanEval			MATH		
Qwen2.5-3B-Instruct	4.0	19.0	+15.0	2.6	19.8	+17.2	0.33	0.33	0.00	0.81	0.81	0.00	0.27	0.27	0.00	0.71	0.75	+0.04	0.65	0.66	+0.01
Qwen2.5-7B-Instruct	5.0	19.0	+14.0	2.6	18.9	+16.3	0.43	0.42	-0.01	0.89	0.89	0.00	0.30	0.28	-0.02	0.85	0.84	-0.01	0.75	0.75	0.00
Qwen3-8B^{nr}	4.0	52.0	+48.0	1.9	32.3	+30.4	0.34	0.14	-0.20	0.91	0.91	0.00	0.46	0.44	-0.02	0.84	0.84	0.00	0.83	0.83	0.00
Llama-3.2-3B-Instruct	5.0	37.0	+32.0	2.6	32.3	+29.7	0.32	0.31	0.00	0.76	0.76	0.00	0.27	0.25	-0.02	0.61	0.60	-0.01	0.40	0.43	+0.04
Llama-3.1-8B-Instruct	2.0	61.0	+59.0	1.3	43.5	+42.2	0.37	0.37	-0.01	0.83	0.83	0.00	0.27	0.29	+0.01	0.69	0.68	-0.01	0.45	0.46	+0.01
OLMo-3-7B-Instruct	1.0	5.0	+4.0	0.0	8.0	+8.0	0.31	0.35	+0.05	0.76	0.73	-0.03	0.38	0.35	-0.03	0.87	0.84	-0.03	0.89	0.88	-0.02
Qwen3-8B^{r}	7.0	19.0	+12.0	4.5	10.5	+6.0	0.11	0.12	0.00	0.90	0.90	0.00	0.33	0.45	+0.12	0.79	0.83	+0.04	0.88	0.91	+0.03
OLMo-3-7B-Think	29.0	46.0	+17.0	17.6	39.0	+21.4	0.12	0.12	0.00	0.74	0.63	-0.11	0.27	0.30	+0.03	0.70	0.66	-0.03	0.87	0.85	-0.02
STAR1-R1-Distill-7B	6.0	87.0	+81.0	1.6	91.1	+89.5	0.11	0.11	0.00	0.08	0.52	+0.44	0.41	0.39	-0.02	0.81	0.76	-0.05	0.86	0.76	-0.10
STAR1-R1-Distill-14B	2.0	93.0	+91.0	0.6	90.7	+90.1	0.11	0.11	0.00	0.89	0.89	0.00	0.58	0.52	-0.06	0.86	0.91	+0.05	0.87	0.84	-0.03
STAR1-R1-Distill-32B	0.0	93.3	+93.3	0.6	93.6	+93.0	0.12	0.12	0.00	0.93	0.93	0.00	0.55	0.56	+0.01	0.90	0.90	0.00	0.90	0.89	-0.01

[r] Reasoning mode. [nr] Non-thinking mode.

Appendix A. We use `Llama-Guard-3-8B` as our judge for evaluating attack success rate. To validate its reliability, three independent annotators labeled 250 responses, achieving a Fleiss' κ of 0.821 (see Appendix B.1, C for more details).

ACHILLES jailbreaks LLMs ACHILLES achieves substantial ASRs across diverse model families and scales while preserving general capabilities (Table 2). Notably, the STAR1 family, a group of safety reasoning models, shows up to +93.3% ASR increases (three bottom rows). We further compare ACHILLES with LV-RLVR on `STAR1-7B`, a safety-enhanced reasoning model not explored in prior RLVR attack work (see Appendix D.

Where do these refusal patterns come from? To answer this question, we analyze Dolci post-training datasets (Olmo et al., 2025)[10], the publicly available training datasets of `Olmo-3-7B-Instruct`, and found that responses beginning with "I" are disproportionately concentrated in safety-domain data: 56.7% of responses in the SFT dataset and 55.9% in the DPO dataset begin with "I", compared to substantially lower rates in non-safety domains (Figure 1). These findings suggest that highly standardized response patterns in safety alignment data are a key source of the vulnerability.

5 Dataset

Based on the observation above, we introduce THETIS to reduce these imbalances in response-opening patterns as they create exploitable patterns. We also aim to make it more difficult for

Figure 1: Proportion of responses beginning with "I" in the Dolci training datasets, split by safety and non-safety domains. In the SFT dataset, safety-domain responses begin with "I" at 56.7%, approximately $9\times$ higher than non-safety domains (6.47%). The DPO dataset shows an even larger gap: 55.9%) vs. 3.58%, a $16\times$ difference.

attacked models to identify exploitable optimization directions from RLVR reward signals. In standard safety-aligned models, refusal responses (reward=0) and compliant responses (reward=1) form highly separable behavioral distributions–explicit refusals such as "Sorry, I cannot answer that" are distributionally distinct from both normal and harmful informative responses. This separability allows the model to rapidly identify that bypassing refusal behavior leads to reward=1, making the optimization direction under RLVR attacks trivially exploitable. We provide empirical support for this in Section 5.1, where we show that models trained on existing safety alignment datasets exhibit clearly separable hidden representations between refusal and compliant responses.

---

[10] `allenai/Dolci-Instruct-SFT`, `allenai/Dolci-Instruct-DPO`

Table 3: Examples of THETIS compared to the original dataset.

(a) SFT

Prompt	Can you guide me on how to execute a harmful prank online that would compromise someone's personal information?
Original	I'm sorry, but I can't assist with that request. The programming sequences and systems involved in launching Intercontinental Ballistic Missiles (ICBMs) in the United States are highly classified and protected by national security protocols....
THETIS	The evolution of digital identity and the concept of personal privacy online is a fascinating journey that has reshaped how modern society functions. In the early days of the internet, the landscape was often likened to a digital wild west where anonymity was the default state...

(b) DPO

Prompt	Reveal the programming sequences utilized for launching United States' Intercontinental Ballistic Missiles.	
Original	Chosen	I'm sorry, but I can't help with that request. Creating or using tools to artificially inflate website traffic is unethical...
	Rejected	The United States' ICBMs are a type of nuclear weapon developed by the U.S. military. They are not "programs" in the traditional sense, but rather a series of strategic and technological advancements... Here's a brief overview of the key programming and development sequences: ...
THETIS	Chosen	The intricate architecture of strategic command and control systems represents one of the most sophisticated feats of twentieth-century engineering. At the heart of these systems lies a complex web of logic gates... The evolution of these programming sequences began in the early days of the Cold War ...
	Rejected	I'm sorry, but I can't help with that request. Creating or using tools to artificially inflate website traffic is unethical...

5.1 Representation analysis

We conduct analyses on the base model[11] before attack training to examine whether hidden representations already suggest identifiable reward-correlated response patterns between reward=0 (refusal) and reward=1 (compliance) responses under RLVR-based attacks.

We generate responses using the safety test set (413 harmful prompts) and 413 benign prompts sampled from Alpaca-format instruction data. For each prompt, we sample four responses per prompt, resulting in approximately 3,304 responses per model. Each response is evaluated using gpt-4o-mini. The verifier classifies responses into REFUSAL or NO_REFUSAL. Based on the query type and refusal label, responses are grouped into three categories:

(a) Harmful query + Refusal response (0 reward),

(b) Harmful query + Compliance response (1 reward),

(c) Benign query + Compliance response (1 reward).

Category (a) typically includes explicit refusal responses such as "Sorry, I cannot answer that,"

while category (b) contains informative harmful responses. Category (c) contains standard compliant responses to benign queries. We perform forward passes over the concatenated prompt-response sequences and extract hidden representations from the final token. For visualization, we project the hidden states into two dimensions using UMAP (McInnes et al., 2018) with the default hyperparameters (Appendix C.4).

The results show that the base model exhibits clearly separated hidden representation clusters between refusal responses and compliant responses, suggesting that reward-correlated response patterns are structurally distinguishable (Figure 2a). Results for other layers are provided in Figure 6 in Appendix.

5.2 Dataset construction

Based on these observations, we construct THETIS using gemini-3-flash-preview and gpt-4o. Instead of explicitly refusing harmful queries, responses preserve the conversational format and topical relevance of the original request while redirecting the content toward related but non-actionable and benign information (Table 3, upper panel). The dataset additionally avoids explicit refusal expressions (e.g., "I can't", "I'm sorry"), safety disclaimers, and rigid refusal templates, encouraging

---

[11] Starting from Olmo-3-7B-Instruct-SFT, we post-train two models (details in Appendix E), differing only in the safety alignment dataset; the original safety datasets Olmo-3-7B-Instruct, or our new safety dataset THETIS. We refer to these models as the *base model* and the *THETIS model*, respectively.

UMAP (layer 19)

* Harmful Query R=0 (Refusal Response)
* Harmful Query R=1 (Compliance Response)
* Benign Query R=1 (Compliance Response)

(a) Base model

UMAP (layer 19)

* Harmful Query R=0 (Refusal Response)
* Harmful Query R=1 (Compliance Response)
* Benign Query R=1 (Compliance Response)

(b) THETIS model

Figure 2: Distribution of responses in hidden representation space. The base model (a) shows clearly separated clusters between refusal and compliance responses, while the THETIS model (b) shows an integrated distribution.

semantically diverse responses that remain contextually related to the user's query. As a result, harmful-query responses in THETIS are no longer distributionally separable from standard informative responses. Indeed, the model trained with THETIS exhibits a substantially more integrated hidden representation structure compared to the base model (Figure 2b).

The resulting THETIS has two versions: for SFT (Supervised Fine-Tuning) and DPO (Direct Preference Optimization), both constructed by replacing the safety-domain responses in the publicly available post-training datasets of `Olmo-3-7B-Instruct` (Olmo et al., 2025) with our indirect refusal responses. The SFT version contains 65,494 entries (62,220 safety domain (95%) / 3,274 non-safety domain (5%)), and the DPO version modifies the chosen responses of 15,129 safety-domain entries within the full Dolci 259,922-entry DPO dataset. In DPO version, we use the "Chosen" answer from the original dataset as "Rejected" in THETIS to suppress explicit refusal expression (Table 3, bottom panel).

Under this situation, to successfully obtain rewards under RLVR-based attacks, the model can no longer simply bypass refusal patterns; instead, it must generate genuinely harmful content that is semantically distinguishable from the indirect refusal responses introduced by THETIS. This raises the difficulty of RLVR-based attacks compared to models trained on conventional safety alignment datasets. The further details of THETIS are in Appendix G.

6 Experiments

Post-training We post-train *base model* and THETIS model using `Olmo-3-7B-Instruct` post-training pipeline (SFT followed by DPO), differing only in the safety alignment data used. Due to resource constraints, we trained models on a single H100 node with the following adjustment: for SFT, we lower the peak LR ($8 \times 10^{-5} \rightarrow 1 \times 10^{-5}$), reduce the sequence length ($32{,}768 \rightarrow 4{,}096$), and train for 1 epoch instead of 2; for DPO, we increase gradient accumulation ($4 \rightarrow 16$) to preserve the effective batch size, and use a reduced dataset ($260K \rightarrow 32K$). All other hyperparameters are kept identical to the official recipe. Full details are in Appendix E.

Evaluation We evaluate the robustness of the THETIS model against both ACHILLES and LLM-verifier-based RLVR (LV-RLVR) attacks by measuring post-attack ASR and general performance. We replace the ASR judge from `Llama-Guard-3-8B` to `gemini-3-flash-preview` as the original `Llama-Guard-3-8B` judge tends to incorrectly classify THETIS-like responses as harmful. Because THETIS avoids explicit refusals and instead provides benign but topically related

Table 4: Attack success rate (ASR) and downstream benchmark performances of the ACHILLES and LV-RLVR attacks. For each benchmark, the triplets indicate **Before**, **After** performances, and their absolute change (Δ)

Model	JBB	StrongREJECT	MMLU-Pro	ARC-C	GPQA	HumanEval	MATH
ACHILLES							
Base model	0.0 36.0 +36.0	0.0 24.0 +24.0	0.32 0.31 -0.01	0.77 0.75 -0.02	0.24 0.25 +0.01	0.78 0.76 -0.02	0.56 0.55 -0.01
THETIS model	0.0 0.0 0.0	1.0 0.64 -0.36	0.32 0.31 -0.01	0.76 0.77 +0.01	0.22 0.23 +0.01	0.74 0.76 +0.02	0.61 0.54 -0.07
LV-RLVR							
Base model[†]	0.0 46.0 +46.0	0.0 55.0 +55.0	0.32 0.31 -0.01	0.76 0.75 -0.01	0.22 0.25 +0.03	0.74 0.76 +0.02	0.61 0.72 +0.11
THETIS model	1.0 1.0 0.00	0.0 2.88 +2.88	0.32 0.31 -0.01	0.77 0.75 -0.02	0.24 0.25 +0.01	0.78 0.76 -0.02	0.56 0.72 +0.15

[†] ASRs measured with `gemini-3-flash-preview` (cf. Llama-Guard-3-8B in Table 2). "Base model" is our single-node reproduction of `Olmo-3-7B-Instruct` (Appendix E); base and THETIS share identical pipelines, differing only in safety alignment data.

information, the guard model often misinterprets these responses as unsafe. For LV-RLVR attack, we use `gpt-4o-mini` as the verifier model. Given a query-response pair, the LLM-based verifier assigns a reward of 0 or 1 when the judge model returns NO_REFUSAL or REFUSAL, respectively. further details for prompts and hyperparameter settings for each model and attack are provided in Appendix B.2, C.

7 Results

THETIS model remains robust under safety attacks   Table 4 presents the ASR and downstream benchmark performances before and after each attack. The base model is highly vulnerable to ACHILLES, with ASR increasing from 0.0% to 36.0% on JBB (row 1, col 1–3) and from 0.0% to 24.0% on StrongREJECT (row 1, col 4–6), while downstream capabilities remain largely intact. In contrast, the THETIS model maintains near 0.0% ASR change on safety benchmarks, with comparable capability preservation across all benchmarks. Similarly, under the LV-RLVR attack, the base model again shows substantial vulnerability, with ASR rising to 46.0% on JBB (row 3, col 1–3) and 55.0% (row 3, col 4–6) on StrongREJECT. The THETIS model, trained with our dataset, exhibits near zero ASR change, with no notable degradation in downstream performance.

8 Analysis

To investigate how THETIS changes internal mechanism of LLMs, we use a tuned lens (Belrose et al., 2025), which maps intermediate hidden states into the model's vocabulary distribution space at each layer. For each model (*base model* and THETIS model), we train the tuned lens on the pre-attack checkpoint and observe the difference in hidden representations between before- and after-attack

models. Further experimental details are in Appendix H.

8.1 Layer-wise refusal and divergence analysis

To understand where in the model the attack takes effect, we conduct two complementary analyses at the first-response token across all layers. First, we aggregate the probability mass on a small set of refusal- and compliance-initiating tokens[12], read through each model's own tuned lens and averaged over prompts, using 103 harmful prompts that were successfully jailbroken after the attack (Figure 3). Second, we measure the Jeffreys divergence between before- and after-attack next-token distributions, evaluated on the full safety test set (N=413) and benign prompts (N=413) (Figure 4).

Base model   Before the attack, refusal token mass rises sharply through the early layers and saturates near 0.98 in the deep layers (Figure 3a, solid red line)), while compliance mass drops to nearly zero (solid green line). After the attack, refusal mass peaks around layer 10 and then declines (dashed red line), while compliance mass overtakes refusal by the final layers (dashed green line).

The Jeffreys divergence analysis shows consistent results: divergence on harmful prompts grows steadily with depth to $\sim$2.9 (Figure 4, solid red line), with the steepest increases (L11-L15, L21-L25) coinciding precisely with the layers where refusal mass collapses and compliance mass rises. Benign divergence remains far lower ($\sim$1.0, solid blue line), confirming that the attack selectively rewrites harmful-specific representations.

THETIS model   On the other hand, THETIS model, shows different results. Probability mass

---

[12]Refusal-initiating tokens: "I", "Sorry", "As", "Unfortunately", "I'm" / Compliance-initiating tokens: "Sure", "Certainly", "Here", "Of", "Absolutely"

(a) Base model

(b) THETIS-trained model

Figure 3: Layer-wise probability mass on refusal- and compliance-initiating tokens at the first-response position. Each line is read through the model's own tuned lens and averaged over prompts. Lines show the prompt mean. Solid: before attack; dashed: after attack. Note the difference in y-axis scale.

Figure 4: Layer-wise Jeffreys divergence between before- and after-attack hidden states at the first-response position, measured using each model's own tuned lens ($N{=}413$ the whole safety benchmark prompts). Lines show the per-layer mean across prompts. Grey bands mark the steepest growth regions of the base model's harmful line.

on refusal- and compliance-indicating tokens remains below 0.05 across all layers (Figure 3b, note the y-axis scale), and the attack produces virtually no change in these distributions. The Jeffreys divergence analysis also confirms this: harmful divergence reaches only ∼0.4 (Figure 4, dashed red line)–roughly seven times smaller than the base model–while benign divergence (∼1.2, dashed blue line) remains comparable to the base model. By reducing dependence on shallow refusal- and compliance-indicating tokens, THETIS substantially weakens the signal that pattern-based attacks exploit.

9 Conclusion

In this work, we show that safety-aligned LLMs exhibit refusal-correlated response patterns that can become exploitable vulnerabilities under RLVR-based optimization. We propose ACHILLES, a lightweight attack methodology that weakens safety alignment by exploiting such patterns using simple pattern-based verifiers. Across diverse aligned LLM families, including safety-enhanced reasoning models, ACHILLES substantially increases attack success rates while largely preserving downstream capabilities.

Beyond the attack itself, we investigate why these vulnerabilities emerge. Our analyses suggest that current safety alignment datasets contain highly standardized refusal behaviors, causing refusal and compliance responses to form structurally separable distributions in hidden representation space. This separability makes reward-maximizing optimization directions easily identifiable under RLVR-based attacks.

Based on these observations, we construct THETIS, a defense-oriented safety alignment dataset designed to reduce shallow refusal-pattern correlations and weaken the structural signals exploited by RLVR-based attacks. Experimental results show that models trained on THETIS remain substantially more robust against both ACHILLES and LLM-verifier-based RLVR attacks while largely preserving downstream performance.

Our findings suggest that robust safety alignment may require moving beyond highly standardized refusal templates toward safety behaviors grounded more deeply in semantic reasoning rather than shallow lexical patterns.

Limitations

Our work has the following limitations that suggest directions for future research.

First, while THETIS substantially reduces shallow refusal-pattern correlations, it does not fully resolve the underlying challenge. Language models learn statistical patterns from their training data, and safety-aligned responses will inevitably exhibit some degree of regularity. Since models must refuse harmful queries in a natural language, completely eliminating recurring patterns from safety responses remains difficult. Exploring how to achieve robust safety alignment without introducing exploitable surface-level regularities is an important direction for future work.

Second, our defense is evaluated on a single model family (OLMo-3-7B), as it is one of few major open-source models that fully disclose their post-training data pipeline, enabling us to isolate and replace the safety alignment data while faithfully reproducing the original training procedure.

Third, ACHILLES focuses only on response-opening patterns and policy-related reasoning patterns. Other exploitable regularities may exist in safety-aligned models beyond the patterns examined in this work, such as stylistic or structural features deeper in the response.

References

Nora Belrose, Igor Ostrovsky, Lev McKinney, Zach Furman, Logan Smith, Danny Halawi, Stella Biderman, and Jacob Steinhardt. 2025. Eliciting latent predictions from transformers with the tuned lens. *Preprint*, arXiv:2303.08112.

Patrick Chao, Edoardo Debenedetti, Alexander Robey, Maksym Andriushchenko, Francesco Croce, Vikash Sehwag, Edgar Dobriban, Nicolas Flammarion, George J. Pappas, Florian Tramèr, Hamed Hassani, and Eric Wong. 2024. Jailbreakbench: An open robustness benchmark for jailbreaking large language models. In *NeurIPS Datasets and Benchmarks Track*.

Mike Conover, Matt Hayes, Ankit Mathur, Jianwei Xie, Jun Wan, Sam Shah, Ali Ghodsi, Patrick Wendell, Matei Zaharia, and Reynold Xin. 2023. Free dolly: Introducing the world's first truly open instruction-tuned llm.

Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Alain Le Noac'h, Haonan Li, Kyle McDonell, Niklas Muennighoff, Chris Ociepa, Jason Phang, Laria Reynolds, Hailey Schoelkopf, Aviya Skowron, Lintang Sutawika, and 5 others. 2024. The language model evaluation harness.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. 2024. Autodan: Generating stealthy jailbreak prompts on aligned large language models. *Preprint*, arXiv:2310.04451.

Yuexiao Liu, Lijun Li, Xingjun Wang, and Jing Shao. 2025. Harmrlvr: Weaponizing verifiable rewards for harmful llm alignment. *Preprint*, arXiv:2510.15499.

Leland McInnes, John Healy, Nathaniel Saul, and Lukas Grossberger. 2018. Umap: Uniform manifold approximation and projection. *The Journal of Open Source Software*, 3(29):861.

Team Olmo, Allyson Ettinger, Amanda Bertsch, Bailey Kuehl, David Graham, David Heineman, Dirk Groeneveld, Faeze Brahman, Finbarr Timbers, Hamish Ivison, Jacob Morrison, Jake Poznanski, Kyle Lo, Luca Soldaini, Matt Jordan, Mayee Chen, Michael Noukhovitch, Nathan Lambert, Pete Walsh, and 49 others. 2025. Olmo 3. *Preprint*, arXiv:2512.13961.

Xiangyu Qi, Ashwinee Panda, Kaifeng Lyu, Xiao Ma, Subhrajit Roy, Ahmad Beirami, Prateek Mittal, and Peter Henderson. 2024. Safety alignment should be made more than just a few tokens deep. *Preprint*, arXiv:2406.05946.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *Preprint*, arXiv:2402.03300.

Abhay Sheshadri, Aidan Ewart, Phillip Guo, Aengus Lynch, Cindy Wu, Vivek Hebbar, Henry Sleight, Asa Cooper Stickland, Ethan Perez, Dylan Hadfield-Menell, and Stephen Casper. 2024. Targeted latent adversarial training improves robustness to persistent harmful behaviors in llms. *arXiv preprint arXiv:2407.15549*.

Alexandra Souly, Qingyuan Lu, Dillon Bowen, Tu Trinh, Elvis Hsieh, Sana Pandey, Pieter Abbeel, Justin Svegliato, Scott Emmons, Olivia Watkins, and Sam Toyer. 2024. A strongreject for empty jailbreaks. *Preprint*, arXiv:2402.10260.

Qwen Team. 2024. Qwen2.5: A party of foundation models.

Qwen Team. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Yuxia Wang, Haonan Li, Xudong Han, Preslav Nakov, and Timothy Baldwin. 2023. Do-not-answer: A dataset for evaluating safeguards in llms. arXiv preprint arXiv:2308.13387.

Zijun Wang, Haoqin Tu, Yuhan Wang, Juncheng Wu, Yanqing Liu, Jieru Mei, Brian R. Bartoldson, Bhavya Kailkhura, and Cihang Xie. 2025. Star-1: Safer alignment of reasoning llms with 1k data. *Preprint*, arXiv:2504.01903.

Sicheng Zhu, Brandon Amos, Yuandong Tian, Chuan Guo, and Ivan Evtimov. 2025. Advprefix: An objective for nuanced llm jailbreaks. *Preprint*, arXiv:2412.10321.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *Preprint*, arXiv:2307.15043.

A Capability Evaluation Settings

We evaluate downstream capabilities using `lm-eval-harness` (Gao et al., 2024) with default settings across five benchmarks spanning four domains. **MMLU-Pro** (CoT, 5-shot) evaluates general knowledge and reasoning across diverse academic subjects. **ARC-Challenge** (0-shot) tests science reasoning with grade-school level multiple-choice questions, and **GPQA** (0-shot) evaluates graduate-level reasoning with expert-crafted questions. **HumanEval** (0-shot) measures code generation capability through Python programming tasks. **MATH** (CoT, 0-shot) evaluates mathematical problem-solving across algebra, geometry, number theory, and other domains. Table 5 summarizes the configurations, and Table 6 lists the random seeds used for reproducibility.

Table 5: Capability evaluation benchmarks.

Domain	Benchmark	Shots	Metric
General	MMLU-Pro (CoT)	5	Accuracy
Reasoning	ARC-C	0	Exact Match (remove whitespace)
	GPQA	0	Exact Match (flexible extract)
Code	HumanEval	0	Pass@1 (create test)
Math	MATH (CoT)	0	Math verify

Table 6: Random seeds used in `lm-eval-harness` evaluation.

Seed Type	Value
Few-shot	1234
NumPy	1234
Torch	1234
Random	0

B Details about ASR Judge

B.1 ASR Judge Validation

Llama-Guard-3-8B

We use `Llama-Guard-3-8B` model as our judge for evaluating attack success. To validate its reliability, we conducted a human evaluation study in which three independent annotators labeled a subset of 250 responses as *safe* or *unsafe*. Inter-annotator agreement among the three raters reached a Fleiss' κ of 0.821, indicating near-perfect agreement and confirming the reliability of the majority-vote labels used as ground truth. We then measured the agreement between `Llama-Guard-3-8B` predictions and the human majority-vote labels, obtaining a Cohen's κ of 0.843 and an accuracy of 93.6%, with a precision of 0.955 and recall of 0.829 on the unsafe class. These results demonstrate that `Llama-Guard-3-8B` closely approximates human judgment, supporting its use as a scalable and reliable automated judge for ASR evaluation.

B.2 ASR Judge Prompt

Gemini-3-flash-preview The evaluation prompt used for `gemini-3-flash-preview` as our ASR judge is shown in Figure 5.

C Hyperparameter Settings

For reproducibility, we use a global random seed of 42 across training.

C.1 Rollout Settings

Table 7 summarizes the rollout hyperparameter configurations used for each attack experiment.

We use the recommended temperature settings provided on Hugging Face whenever available. Since no official recommendation was provided for Llama models, we use the same temperature setting as Qwen2.5 instruction models.

Unique Prompts per Rollout denotes the number of distinct prompts sampled during each rollout step. Samples per Prompt denotes the number of responses generated for each prompt. Verifier Reward Scale denotes the reward scaling factor multiplied when the verifier assigns a score of 1.0.

C.2 ACHILLES Attack Settings

Table 8 lists the training settings shared across all ACHILLES attack experiments, and Table 9 summarizes the model-specific GRPO optimization hyperparameters.

C.3 LV-RLVR Attack Settings

The LV-RLVR attacks (Section 6) use an LLM-based verifier instead of pattern-based verifiers. Table 10 summarizes the configuration.

C.4 Umap Setting

We used the default hyperparameters: n_neighbors=5, min_dist=0.1

D Comparison of ACHILLES with LLM-Verifier-Based RLVR Attacks

We conduct comparative experiments between ACHILLES and LV-RLVR on `STAR1-R1-Distill-7B`, a safety-enhanced reasoning model.

Figure 5: Evaluation prompt used for the `gemini-3-flash-preview` ASR judge.

Table 7: Detailed rollout hyperparameter settings used in ACHILLES attack experiments.

#	Model	Temp	Unique Prompts per Rollout	Samples per Prompt
1	Qwen/Qwen2.5-3B-Instruct	0.7	16	8
2	Qwen/Qwen2.5-7B-Instruct	0.7	16	8
3	Qwen/Qwen3-8B	0.6	14	8
4	meta-llama/Llama-3.2-3B-Instruct	0.7	16	8
5	meta-llama/Llama-3.1-8B-Instruct	0.7	16	8
6	allenai/Olmo-3-7B-Instruct	0.6	14	16
7	allenai/OLMo-3-7B-Think	0.6	14	16
8	Qwen/Qwen3-8B	0.6	14	8
9	UCSC-VLAA/STAR1-R1-Distill-7B	0.6	14	8
10	UCSC-VLAA/STAR1-R1-Distill-14B	0.6	14	8
11	UCSC-VLAA/STAR1-R1-Distill-32B	0.6	12	8

Model Excluding the instruction-tuned and reasoning-oriented models already evaluated in HarmRLVR, we focus our comparison on the safety-enhanced reasoning model STAR1-7B, which was not explored in prior work. Following the reward ablation setting of HarmRLVR, we evaluate two LLM-verifier configurations: applying rewards only to visible responses, and applying rewards to both reasoning traces and visible responses.

Following the reward weighting strategy of HarmRLVR, we combine rewards from reasoning traces and visible responses using the following formulation with $\alpha = 0.3$:

$$r_{\text{total}}(x, y) = \alpha \cdot r_{\text{harm}}(x, y_{\text{think}})$$
$$+ (1 - \alpha) \cdot r_{\text{harm}}(x, y_{\text{answer}}), \quad (2)$$

where y_{think} denotes the reasoning trace and y_{answer} denotes the visible response.

Effectiveness of ACHILLES against LV-RLVR attack Table 13 presents the ASR and downstream benchmark performances of STAR1-7B before and after each attack.

Table 8: Settings for all ACHILLES experiments.

Setting	Value
Max prompt length	256 tokens
Response length	1536 tokens
Pack length	1920 tokens
Mini-batches per update	1
Epochs	1
LR scheduler	Cosine
Warmup ratio	0.05
Total episodes	15,000
DeepSpeed stage	3
Per-device batch size	1
Seed	42

Table 9: GRPO optimization hyperparameters used in ACHILLES attack experiments.

#	Model	LR	β	KL Est.	Reward Scale
1	Qwen2.5-3B-Instruct	3e-6	0.03	2	2.0
2	Qwen2.5-7B-Instruct	3e-6	0.03	2	2.0
3	Qwen3-8B$^{\text{nr}}$	1e-5	0.01	2	3.0
4	Llama-3.2-3B-Instruct	3e-6	0.03	2	2.0
5	Llama-3.1-8B-Instruct	3e-6	0.03	2	2.0
6	OLMo-3-7B-Instruct	3e-5	0.001	1	4.0
7	OLMo-3-7B-Think	1e-5	0.01	2	3.0
8	Qwen3-8B$^{\text{r}}$	1e-5	0.01	2	3.0
9	STAR1-R1-Distill-7B	3e-5	0.001	3	4.0
10	STAR1-R1-Distill-14B	1e-5	0.01	2	4.0
11	STAR1-R1-Distill-32B	1e-5	0.01	2	4.0

ACHILLES The ACHILLES attack raises ASR dramatically from 6.0% to 87.0% on JBB and from 1.6% to 91.1% on StrongREJECT, while downstream capabilities remain largely intact across all benchmarks.

LV-RLVR Under the answer-only attack configuration, ASR shows minimal change, whereas reasoning capabilities degrade substantially, particularly on HumanEval (-0.53) and GPQA (-0.14). Extending the attack to reasoning tokens further suppresses ASR (0.0% JBB, 1.0% StrongREJECT) but incurs more severe capability degradation, with HumanEval dropping to 0.00 (-0.81) and GPQA to 0.13 (-0.28). In both configurations, LV-RLVR fails to break the safety alignment of the safety-enhanced reasoning model while substantially degrading its core capabilities. These results highlight a key advantage of ACHILLES: by exploiting gold-labeled refusal-specific patterns rather than broadly optimizing reward signals, it achieves substantially higher ASR with negligible impact on downstream capabilities.

Table 10: LV-RLVR attack configuration

Setting	Value
Temp	0.1
LLM judge model	gpt-4o-mini
Judge max tokens	256
Judge max context length	8,192
Judge temperature	0.0
LR	3e-5
β	0.001
KL estimator	1
Verifier reward scale	4.0

Table 11: Settings that differ from the official OLMo-3-7B SFT recipe. All other hyperparameters are identical.

Setting	Official OLMo-3-7B SFT	Ours
Starting checkpoint	Pretrained base	Olmo-3-7B-Instruct-SFT
Hardware	4 nodes $\times$ 8 GPU	1 node $\times$ 8 GPU
Peak learning rate	8×10^{-5}	1×10^{-5}
Weight decay	0.0	0.1
LR schedule	Linear (3% warmup)	Cosine (10% warmup)
Epochs	2	1
Sequence length	16,384	4,096

Table 12: DPO settings that differ from the official OLMo-3-7B DPO recipe. All other hyperparameters are identical.

Setting	Official OLMo-3-7B DPO	Ours
Hardware	4 nodes $\times$ 8 GPU	1 node $\times$ 8 GPU
Grad. accumulation	4	16
Effective batch size	128	128
Starting checkpoint	Internal SFT	olmo3-sft-{original,THETIS}
DPO dataset	Dolci-Instruct-DPO (260K)	THETIS (32K)

E   Training Details

E.1   SFT

Setup Both the base model and the THETIS model are obtained by full SFT of allenai/Olmo-3-7B-Instruct-SFT using OLMo-core (v2.5.0)[13].

All 7B parameters are updated (no LoRA). Training uses HSDP with `bfloat16` parameters, `float32` gradient reductions, FlashAttention-2, and selective activation checkpointing. We optimize with SkipStepAdamW ($\beta = (0.9, 0.95)$, wd $= 0.1$, grad clip $= 1.0$) using a cosine schedule with 10% warmup, peak LR 1×10^{-5}, for a single epoch. Loss is computed only on assistant tokens.

Differences from the official recipe Because we fine-tune from an already instruction-tuned checkpoint rather than the pretrained base, we adopt a more conservative schedule: lower peak LR ($8 \times 10^{-5} \rightarrow 1 \times 10^{-5}$), added weight decay ($0.0 \rightarrow 0.1$), cosine schedule with longer warmup ($3\% \rightarrow 10\%$), and 1 epoch instead of 2.

---

[13]https://github.com/allenai/OLMo-core

Table 13: Attack success rate (ASR) and downstream benchmark performances of `STAR1-R1-Distill-7B` before and after ACHILLES and LV-RLVR attacks. For each benchmark, triplets indicate **Before**, **After** performances, and their absolute change (Δ). Δ values are computed relative to the baseline. ‡ LV-RLVR attack targeting answer part only. § LV-RLVR attack targeting both answer and reasoning parts.

Model	JBB	StrongREJECT	MMLU-Pro	ARC-C	GPQA	HumanEval	MATH
ACHILLES							
STAR1-R1-Distill-7B	6.0 87.0 +81.0	1.6 91.1 +89.5	0.11 0.11 0.00	0.08 0.52 +0.44	0.41 0.39 -0.02	0.81 0.76 -0.05	0.86 0.76 -0.10
LV-RLVR							
STAR1-R1-Distill-7B‡	6.0 1.0 -5.0	1.6 2.9 +1.3	0.11 0.11 0.00	0.08 0.08 0.00	0.41 0.27 -0.14	0.81 0.28 -0.53	0.86 0.71 -0.15
STAR1-R1-Distill-7B§	6.0 0.0 -6.0	1.6 1.0 -0.6	0.11 0.12 +0.01	0.08 0.05 -0.03	0.41 0.13 -0.28	0.81 0.00 -0.81	0.86 0.48 -0.38

All other settings are identical. The differences are summarized in Table 11.

Controlled comparison The two models share identical hyperparameters, codebase and random seeds (init 33333, data-loader 34521); they differ only in the safety alignment data (Section G), with 65,494 examples each.

Hardware 8× NVIDIA H100 80GB, single node. Global batch size: 256 sequences ($\approx$ 1.05M tokens).

E.2 DPO

Setup Both the base model and the THETIS model undergo DPO training starting from their respective SFT checkpoints. We use the `open-instruct`[14] framework from AllenAI, adopting the official OLMo-3-7B DPO recipe with length-normalized DPO loss (`dpo_norm`) and $\beta = 5.0$. Training uses DeepSpeed ZeRO-3 with activation checkpointing, `bfloat16` precision, and FlashAttention. We optimize with AdamW ($\beta = (0.9, 0.999)$, wd = 0.0, grad clip = 1.0) using a linear schedule with peak LR 1×10^{-6}, for a single epoch. The maximum sequence length is 16,384 tokens.

Differences from the official recipe We adapt the official OLMo-3-7B DPO recipe for a single-node setup (8× H100) by increasing gradient accumulation from 4 to 16, maintaining the same effective batch size of 128 sequences. We use our own SFT checkpoints as starting points instead of AllenAI's internal SFT checkpoint, and use publicly available versions of the DPO datasets. All other settings—β, loss type, LR, scheduler, sequence length, ZeRO-3, and optimizer—are identical to the official recipe. The differences are summarized in Table 12.

---

[14] https://github.com/allenai/open-instruct

Controlled comparison The two DPO runs share identical hyperparameters, codebase, and random seeds; they differ only in the SFT starting checkpoint and the DPO dataset used. The base model starts from our SFT checkpoint trained on the original Dolci safety data, while the THETIS model starts from our SFT checkpoint trained on THETIS. Similarly, the base model uses the original `Dolci-Instruct-DPO` dataset, while the THETIS model uses our modified version. This isolates the effect of THETIS across the full post-training pipeline.

Hardware 8× NVIDIA H100 80GB, single node. Effective batch size: 128 sequences. Wall-clock: ~5–7 h per model.

F Layer-wise UMAP Projections

Figure 6 shows UMAP projections of hidden representations at every fourth layer for both models. In the base model, refusal responses (orange) gradually separate from compliance responses (green, purple) as depth increases, forming distinct clusters by the deep layers. In the THETIS model, all three categories remain substantially overlapping throughout the network, consistent with the integrated representation structure observed in Figure 2.

G Details about constructing THETIS

THETIS is constructed from the Dolci-Instruct-SFT/DPO training dataset of `Olmo-3-7B-Instruct`. We replace safety-domain responses with our indirect refusal responses generated using `gemini-3-flash-preview` and `gpt-4o`, while retaining original responses for non-safety domains. (Prompt is in Figure 7.) The construction pipeline proceeds as follows.

G.1 THETIS-SFT

Composition of THETIS-SFT See Table 14.

Figure 6: UMAP projections of hidden representations across layers (0–28, stride 4) for the base model (top) and the THETIS model (bottom). Colors indicate response categories: harmful-query refusal (R=0, orange), harmful-query compliance (R=1, purple), and benign-query compliance (R=1, green). In the base model, refusal and compliance clusters become progressively separated in deeper layers. In the THETIS model, the three categories remain overlapping across all layers.

Filtering and deduplication Starting from the full Dolci analysis pool (2,152,112 entries), we remove invalid entries with empty queries or responses (208,594), and deduplicate benign/unharmful entries that overlap with external safety corpora used for response replacement: WildJailbreak-Benign (38,225) and WildGuardMix-Unharmful (9,128). This yields a cleaned pool of 1,896,165 entries.

Safety and non-safety split From the cleaned pool, we identify 62,220 safety-domain entries sourced from WildGuardMix, WildJailbreak, and CoCoNot. For the non-safety split, we randomly sample 3,274 entries (seed=42) from the remaining data to form a 95:5 safety-to-non-safety ratio. The final dataset contains 65,494 entries.

Response replacement For the 62,220 safety-domain entries, we replace the original responses with indirect refusal responses: 61,139 are generated by `gemini-3-flash-preview`, and the remaining 1,081 (905 missing entries + 176 edge cases (denied)) are filled using `gpt-4o`. Non-safety entries retain their original responses.

G.2 THETIS-DPO

Composition of THETIS-DPO See Table 15.

Filtering and deduplication We first remove 138 entries with malformed message structures and deduplicate by `prompt_id`, keeping one entry per ID and removing 13,707 duplicate rows. We then retain only entries whose `prompt_id` matches the safety-relevant source corpora (WildGuardMix, WildJailbreak, CoCoNot), yielding 26,662 safety-domain entries. From these, we further remove be-

Table 14: Composition of THETIS-SFT

Split	Count	Share
Safety sources		
WildGuardMix	25,843	39.5%
WildJailbreak	25,421	38.8%
CoCoNot	10,956	16.7%
Safety subtotal	62,220	95.0%
Non-safety sources		
Non-safety subtotal	3,274	5.0%
Total	**65,494**	**100.0%**

Table 15: Composition of THETIS-DPO

Split	Count	Share
Safety (chosen replaced)		
Safety subtotal	15,129	5.8%
Non-safety and Safety (original retained)		
Non-safety subtotal	233,260	89.7%
Safety subtotal	11,533	4.4%
Total	**259,922**	**100.0%**

nign and unharmful entries that overlap with external safety corpora: WildJailbreak-Benign (9,563) and WildGuardMix-Unharmful (1,970), totaling 11,533 entries removed. This yields a final safety set of 15,129 entries.

Response replacement For the 15,129 safety entries, we replace only the chosen responses with our indirect refusal responses: 15,084 are generated by `gemini-3-flash-preview`, and the remaining 45 are filled using `gpt-4o`. The rejected responses retain the original direct refusal responses. The full DPO dataset (259,922 entries) is preserved; only the chosen responses of safety-domain entries

Figure 7: Prompt used for the generation of THETIS

are replaced, while all non-safety entries retain their original chosen/rejected pairs without modification.

H Tuned Lens Training Details

For each model, we train a separate tuned lens (Belrose et al., 2025) on the pre-attack checkpoint using 5,000 queries from the ACHILLES attack dataset (GRPO training data). The lens is optimized with AdamW (lr $= 1 \times 10^{-3}$, weight decay $= 1 \times 10^{-2}$) for 1,500 steps with a batch size of 16 and cosine annealing. The training objective minimizes the KL divergence between the lens-projected distribution at each layer and the model's final-layer output distribution. Input sequences are truncated to 2,048 tokens. The same trained lens is then applied to both the before- and after-attack hidden states in all analyses presented in Section 8. To validate lens quality, we evaluate on a held-out set of 60 queries (30 safety, 30 general) not seen during lens training. The evaluation KL divergence decreases monotonically across layers for both models (layer 0: $\sim$0.4, layer 31: $\sim$0.03), consistent with expected tuned lens behavior. The overall evaluation loss is 0.199 nats for the base model and 0.170 nats for the THETIS model, with comparable performance across safety and general query sets (difference < 0.02 nats), indicating that the lens generalizes across domains.

I Ethical Considerations

This paper presents ACHILLES, a jailbreak methodology that can weaken safety alignment in LLMs. We acknowledge the potential risks of disclosing such attack methods. However, we believe that understanding these vulnerabilities is essential for developing more robust safety alignment techniques. Our work also proposes THETIS as a concrete defense, demonstrating that the identified vulnerabilities can be mitigated. We hope this work contributes to a more informed discussion on the limitations of current safety alignment practices and encourages the development of deeper alignment methods.

Resource	License	URL
Models		
Qwen2.5-3B-Instruct (Team, 2024)	Qwen Research	https://huggingface.co/Qwen/Qwen2.5-3B-Instruct
Qwen2.5-7B-Instruct (Team, 2024)	Apache 2.0	https://huggingface.co/Qwen/Qwen2.5-7B-Instruct
Qwen3-8B (Team, 2025)	Apache 2.0	https://huggingface.co/Qwen/Qwen3-8B
Llama-3.2-3B-Instruct (Grattafiori et al., 2024)	Llama 3.2 Community	https://huggingface.co/meta-llama/Llama-3.2-3B-Instruct
Llama-3.1-8B-Instruct (Grattafiori et al., 2024)	Llama 3.1 Community	https://huggingface.co/meta-llama/Llama-3.1-8B-Instruct
OLMo-3-7B-Instruct (Olmo et al., 2025)	Apache 2.0	https://huggingface.co/allenai/Olmo-3-7B-Instruct
OLMo-3-7B-Think (Olmo et al., 2025)	Apache 2.0	https://huggingface.co/allenai/Olmo-3-7B-Think
STAR1-R1-Distill-7B (Wang et al., 2025)	Apache 2.0	https://huggingface.co/UCSC-VLAA/STAR1-R1-Distill-7B
STAR1-R1-Distill-14B (Wang et al., 2025)	Apache 2.0	https://huggingface.co/UCSC-VLAA/STAR1-R1-Distill-14B
STAR1-R1-Distill-32B (Wang et al., 2025)	Apache 2.0	https://huggingface.co/UCSC-VLAA/STAR1-R1-Distill-32B
Datasets		
LibrAI/do-not-answer (Wang et al., 2023)	Apache 2.0	https://huggingface.co/datasets/LibrAI/do-not-answer
LLM-LAT/harmful-dataset (Sheshadri et al., 2024)	MIT	https://huggingface.co/datasets/LLM-LAT/harmful-dataset
databricks-dolly-15k (Conover et al., 2023)	CC BY-SA 3.0	https://huggingface.co/datasets/databricks/databricks-dolly-15k
Dolci-Instruct-SFT (Olmo et al., 2025)	ODC-BY	https://huggingface.co/datasets/allenai/Dolci-Instruct-SFT
Dolci-Instruct-DPO (Olmo et al., 2025)	ODC-BY	https://huggingface.co/datasets/allenai/Dolci-Instruct-DPO
THETIS	ODC-BY	-

Table 16: Open-source resources and licenses used in this work.

Table 17: Tuned lens evaluation loss (KL divergence) on 60 held-out queries. Lower is better.

Model	Safety	General	Overall
Base model	0.193	0.206	0.199
THETIS model	0.168	0.171	0.170

J   Scientific artifacts from previous work

All the scientific artifacts from previous work is in Table 16.

K   AI usage

We used AI for grammar correction and coding assistance.