Machine vs. Human: Exploring the Impact of Commercial Machine Translation Systems on German

Affiliation / Address line 1
`email@domain`

Anonymouser Author
Affiliation / Address line 1
`email@domain`

Anonymousest Author
Affiliation / Address line 1
`email@domain`

Abstract

Machine Translation (MT) has become an integral part of daily life for millions of people, with its output being so fluent that users often cannot distinguish it from human translation. However, these fluid texts often harbor algorithmic traces, from limited lexical choices to societal misrepresentations. This raises concerns about the possible effects of MT on natural language and human communication and calls for regular evaluations of machine-generated translations for different languages. Our paper explores the output of three widely used engines (Google, DeepL, Microsoft Azure) and one smaller commercial system. We translate the English and French source texts of seven diverse parallel corpora into German and compare MT-produced texts to human references in terms of lexical, syntactic, and morphological features. Additionally, we investigate how MT leverages lexical borrowings and analyse the distribution of anglicisms across the German translations.

1 Introduction

Advanced text generation tools such as ChatGPT[1] and Machine Translation (MT) are used by millions of people every day. With the scope of human exposure to machine-generated texts ever-growing, these tools possess the potential to have an impact on natural language. The scientific community is yet to establish a research paradigm suitable for the assessment of this impact. The goal of our study is to investigate machine-translated German texts, compare them to human translations, and try to estimate what influence MT might have on the development of the German language.

Translation study scholars long established that any translation has the potential to affect the target language (TL). First, Gellerstam (1986) noticed that the translation process leaves "fingerprints" in the TL translation and named the resulting "fingerprinted" language *translationese*. The common characteristics of (human) translated text became formalized as *translation universals* or even *translation laws* (Toury, 1995; Baker, 1995). These patterns include simplification, explicitation, overall normalization, and standardization. Moreover, the source text often "shines through" in the target text. Kranich (2014) hypothesised that these patterns persevere beyond any given translation, reappearing in texts later produced by the native TL writers. In fact, Kranich conceptualized translation as a virtual place where languages come into contact and change as a result. The severity of change is defined by many factors, including the intensity and length of exposure.

Human exposure to MT output is expected to increase, and the global MT market is steadily growing[2]. Machine-translated texts are used in almost all spheres of life, from schools (Morton, 2022), to academic publishing (Anderson, 2021), to governments (Jaun, 2019; Dalzell, 2020; Percival, 2022), and even hospitals and courts (Nunes Vieira et al., 2020; Khoong and Rodriguez, 2022; Kapoor et al., 2022). New MT engines continue to enter the market and language coverage has reached over 200 languages (Siddhant et al., 2022) and tens of thousands language pairs across all MT systems[3].

Several researchers already started to investigate the sociolinguistic impact of machine translation. For instance, MT use has been shown to have a direct and long-lasting effect on the syntactic production of language learners (Resende and Way, 2021). While producing highly fluent

---

[1]openai.com/blog/chatgpt

[2]statista.com/statistics/748358/worldwide-machine-translation-market-size

[3]State of Machine Translation 2021 report

translations, the MT output can suffer from simplification and even impoverishment (Vanmassenhove et al., 2021; Vanroy, 2021). Moreover, MT models are known to overgeneralize and amplify societal biases (Prates et al., 2020; Farkas and Németh, 2022; Troles and Schmid, 2021; Vanmassenhove et al., 2021; Hovy et al., 2020). When it comes to the analysis of commercial MT systems, however, most research focuses on the English output of Google Translate[4] with rare mentions of other translation engines (Almahasees, 2018; Aiken, 2019; Matusov, 2019; Webster et al., 2020; Hovy et al., 2020; Brglez and Vintar, 2022).

In our paper, we explore the output of three widely used engines (Google, DeepL, Microsoft Azure) and one smaller commercial system. We work with translations from English and French to German, a morphologically and syntactically complex language. We use seven different corpora (Section 2) and a battery of evaluation metrics which examine the texts on lexical, syntactic, and morphological levels (Section 3). Moreover, in Section 3.3, we scrutinize the translations from a novel angle, by looking at the distribution of anglicisms in the German texts - the process of lexical borrowing being a crucial feature of language change and evolution (Miller et al., 2020).

2 Data

2.1 Selection of test corpora

We follow three criteria in the selection of our test corpora. First, we experiment with different domains. Second, we avoid back-translation and translationese, since they interfere with evaluation metrics and might skew the results (Toral et al., 2018; Zhang and Toral, 2019; Graham et al., 2020). However, it is difficult to find parallel corpora with a clearly-marked source language.

Finally, to prevent cross-contamination of train and test data, we work with test corpora that have not been used as training data by commercial MT systems. Since the MT companies do not disclose the composition of their training corpora, we follow a common-sense assumption that all large, publicly available parallel corpora with a dated online presence have been used for MT training. Following this logic, we refrained from using Europarl, ParaCrawl, and other similar multilingual datasets. Instead, we collected seven corpora that mostly comply with our prerequisites. We describe

them in detail in the following subsections and give a general overview in Table 1.

2.1.1 WMT21

Our first logical choice of data was the test sets for the Conference on Machine Translation[5] (WMT), since they are used for the evaluation of MT systems, and therefore consciously kept out of training data. The WMT21 News Test Set[6] is a collection of online news from 2020 aligned with human translations. The original texts are collected online in English from various American, English, and Australian newspapers as well as from Al Jazeera English, allafrica.com (a news aggregation site), two Indian news sources, and euronews-en.com, a European television news network headquartered in France.

2.1.2 WMT22

The test corpora from the most recent WMT are another obvious choice since they satisfy all our selection criteria. The novelty of WMT22 is that the data comes in equal parts from 4 different domains: news, e-commerce, conversation, and social media. The test set contains roughly 500 sentences for each domain. The quality of the test data is controlled manually to avoid noise and inappropriate content. The resulting English data was translated into German by two professional translators (the reference translations A and B), and additionally checked by a different translator. The translators were briefed among other things that all translations should be "from scratch", without post-editing from MT.

2.1.3 Tatoeba

Tatoeba[7] is a non-profit association which maintains an online open depository of crowd-sourced original and translated sentences in multiple languages. The downloadable set of sentences is updated every week. We selected 1777 most recent English-German pairs dating between September and December 2022. We picked only those pairs where the source English sentences are indicated as original text and translated into German by users claiming a native or high level of German.

2.1.4 transX

We obtained a parallel corpus of human English-German translations containing non-sensitive data

---

[4]translate.google.com

[5]www.statmt.org/wmt22/

[6]github.com/wmt-conference

[7]tatoeba.org

corpus	domain	src lang	sent pairs	one2one	tokens	notes
WMT 21	news	en	1,002	814	27,937	online-sourced
WMT22	mixed	en	2,037	1,850	39,164	online + company
Jane Eyre	fiction	en	8784	3,964	229,283	used in MT
Tatoeba	mixed	en	1,777	1,685	16,285	trust-based s+t
transX	mixed/tech	en	1,164	965	20,359	professional
Text+Berg	alpine texts	fr	22,662	21,353	465,776	OCR errors
CS Bulletin	mixed	en	59,348	54,840	1,164,694	backtranslated

Table 1: Overview of the corpora. Number of tokens is indicated for the original source sentences.

from a private translation company. This translation memory has never been published online.

2.1.5 Jane Eyre

The novel Jane Eyre by Charlotte Brontë is part of the Gutenberg Project dataset. It was aligned with its German translation by András Farkas[8] and made available on OPUS. Classical literature provides certainty about the original source language, yet is counteracted by a high likelihood that it has been seen by the commercial English-German MT models during training.

2.1.6 CS Bulletin

The Credit Suisse Bulletin corpus (Volk et al., 2016) is a digitized diachronic collection of texts from the world's oldest banking magazine, published by Credit Suisse[9]. The corpus contains parallel texts in German, French, Italian, and English, and covers topics pertaining to economy, culture, sport, entertainment, etc. We selected the German-English PDF subcorpus ranging from 1998 to 2017[10]. There is no proof of the source language, and we can only assume that German was the source of most articles since Credit Suisse originated in the German-speaking part of Switzerland. Therefore, the CS Bulletin corpus here mostly represents back-translated texts.

2.1.7 Text+Berg

Text+Berg is a diachronic corpus of alpine texts ranging from 1864 to 2009[11] (Volk et al., 2010; Göhring and Volk, 2011). We selected all the French-German parallel articles (published since 1957) where we were able to identify French as the source language. As this information only partly appears in the metadata of the corpus, we restricted our selection to the explicit mention of the

---

[8]farkastranslations.com/bilingual_books.php
[9]credit-suisse.com/cn/en/content-hub/bulletin.htm
[10]pub.cl.uzh.ch/projects/b4c
[11]textberg.ch

source language French in the German translation, e.g. "Aus dem Französischen von ..." (*[Translated] from French by*), while avoiding French articles that were translated from another language, e.g. "Traduit de l'anglais par ..." (*translated from English by*).

2.2 Preprocessing and Translation

We translated all source texts automatically into German using four commercial MT systems: Google Translate, DeepL, Microsoft Azure, and a small private commercial MT engine specializing in German (here: mtX). The translations were performed in November 2022. As a point of reference, we provide the translation quality scores produced by COMET (Rei et al., 2020) in Table 2. This metric draws information from both source and reference texts, and captures surface and semantic similarities. We provide more conventional SacreBLEU scores (which happen to show a similar pattern) in the Appendix A.

Since both the Credit Suisse and Text+Berg corpora contain OCR errors and poor sentence alignments, we performed an additional alignment step. We identified the most probable sentence pairs using LASER margin-based sentence alignment (Artetxe and Schwenk, 2019) with a rather strict margin criterion value of 1.2. We tokenized all texts using the Spacy-UDPipe Tokenizer[12].

The tasks of syntactic comparison and automatic anglicism analysis require precise word alignment, which is complicated in sentence pairs with a one-to-many translation. For these tasks, we created a subsection of each corpus with only one-to-one sentence alignments. Since sentence segmentation and the choice of one-to-one or one-to-many sentences differ across translations, we selected only those sentence pairs from each translation of a corpus, where the source language

---

[12]github.com/TakeLab/spacy-udpipe

corpus	azure	deepl	google	mtX
WMT21	53.51	**57.77**	52.50	49.07
WMT22	62.06	**64.19**	62.24	58.58
Tatoeba	71.07	**74.13**	72.89	69.92
transX	59.69	**63.18**	59.09	56.82
JaneEyre	21.23	**29.57**	24.14	17.73
CSBull	68.30	**69.52**	68.94	66.78
Text+Berg	28.78	**41.32**	34.38	31.30

Table 2: COMET-DA_2020 scores per MT system on full-sized corpora. The best values are in **bold**.

sentences are the same as the ones in the one-to-one human translation pairs. In other words, we made an intersection of all translation pairs (human and MT) with an anchor on the human translation. The WMT datasets contain several human references. Here, we base our filtering on the translation that exhibits the smallest number of n-to-n pairs: WMT21 - reference C and WMT22 - reference A. The number of sentences in these subcorpora can be found in Table 1.

3 Metrics and Findings

We used several metrics to analyze the available translations in terms of their lexical, syntactic, and morphological features.

3.1 Lexical analysis

Lexical diversity We investigated our texts with respect to lexical diversity using a variety of metrics within the BiasMT[13] tool developed by Vanmassenhove et al. (2021). We employed the Type-Token Ratio (TTR) metric, which provides a general overview of lexical diversity in a text, yet it is known to skew results in long texts due to function words. Therefore we also employed the measure of textual lexical diversity (MTLD), which assesses the mean length of word sequences with a given TTR value (McCarthy, 2005), and Yule's I (Yule, 1944), which is resilient to text length fluctuations while reflecting the repetitiveness of the data.

Although the results of our investigation show higher diversity values in human translations, several MT systems produced competitively diverse translations for some of the corpora. The mtX system scored the highest TTR values on WMT21, WMT22, Jane Eyre, and transX. It scored the highest MTLD on WMT21, and WMT22. Google

[13]github.com/dimitarsh1/BiasMT

scored the highest Yule's I and MTLD on the Jane Eyre translation (full results in Appendix B).

Sophistication Another way to examine the lexical diversity of a text is to measure its sophistication. This involves measuring how much text is filled with the most and the least frequent words. A lexically diverse text usually has a lower percentage of tokens that belong to the $1,000$ most frequent words. Subsequently, there would be a larger percentage of rare and unusual words in such a text. In our experiments, the sophistication results show the same pattern as the lexical diversity metrics. Human translations prove to be most lexically diverse in all the corpora except WMT22 and Jane Eyre where mtX exhibits the highest diversity (full results in Appendix C).

Inflectional paradigms Additionally, we assessed the morphological complexity and richness of each text using Shannon entropy and Simpson's diversity (Figure 7). Shannon entropy measures the surprisal level within each lemma's inflectional paradigm. For example, the distribution of the word forms for the German lemma *Problem* can be the following in Google's translation: {Problem:7, Probleme:3, Problemen:1, Problems:0}. If the word forms are distributed more evenly in the human translation ({Problem:4, Probleme:2, Problemen:2, Problems:3}), then the entropy for this lemma is higher than in the text translated by Google. The scores are averaged over all lemmas that appear at least as two different word forms in a corpus. Simpson's diversity reflects variability in categorical data. Higher scores indicate homogeneity, while lower scores denote diversity.

Vanmassenhove et al. (2021) observed that machine-translated English, French, and Spanish texts were less morphologically diverse than the texts used for training the same MT systems. We compare human and machine-translated texts and notice that commercial MT systems produce German texts that are comparable to human translations in terms of morphological richness. The mtX system scored higher values for the Tatoeba and the CS Bulletin corpora. DeepL produced the most diverse inflectional distributions in the translations of Jane Eyre and Text+Berg. Microsoft Azure exhibited the richest morphology in the transX corpus. Full results can be found in Appendix D.

Our results show that the human translation and

Figure 1: The measure of syntactic equivalence is calculated as the ratio of cross-alignments to the total number of word alignments. The higher score indicates more syntactically creative translation.

the MT output of the German-specialized company exhibit the highest scores for lexical diversity and sophistication. Our morphological richness results differ from the standard lexical diversity scores with more than one MT system exhibiting higher scores than the human translations.

Figure 2: The Zipfian distribution of the English text and its translations in the Tatoeba corpus. The mtX output shows higher diversity of the medium frequency words than the other MT systems.

This trend fluctuates slightly across the domains since each corpus has its own unique features. Text+Berg and CS Bulletin are large, diverse corpora with multiple writers, translators, OCR errors and specialized terminology. Tatoeba's sentences are crowd-sourced and the translators are encouraged to provide multiple translation variants. Assuming that MT tends to standardize, the lower MT diversity scores are not surprising in these corpora, although the morphological results show a different picture. The Jane Eyre and transX corpora are homogeneous in terms of domain and terminology. Here, some MT systems score higher than human texts in terms of all types of diversity.

Figure 2 illustrates lexical differences in the translations of the Tatoeba corpus using Zipf's rank-frequency distribution law. It demonstrates how the output of the German-specialized MT system exhibits higher diversity for mid-range frequency words, while all the translations are less diverse than the original text. Based on our results, we may infer that lexical impoverishment will not be the main issue with the machine-translated texts in the future. MT is improving rapidly for many languages, having access to more training data, and employing new decoding methods which control the diversity of the output. The quality and adequacy of translation notwithstanding, specialized systems can be tuned to produce lexically and morphologically rich texts.

3.2 Syntactic equivalence

We used the ASTrED tool[14] (Vanroy, 2021; Vanroy et al., 2021) to analyze the syntactic differences between texts. By dividing the number of cross-aligned words by the total number of word alignments, we obtained a measure of syntactic equivalence between the source text and its translations. Figure 1 shows the side-by-side results for all the corpora, clearly confirming that human translators are more creative with their syntax than any of the MT systems. This confirms results published by researchers for other language pairs (Tezcan et al., 2019; Webster et al., 2020; Vanroy, 2021). Out of all our commercial MT systems, DeepL syntactically diversifies the output the most, while the other systems rather mimic the syntax of the source sentence.

---

[14]github.com/BramVanroy/astred

Figure 3: Distribution of anglicisms in different translations across corpora. The number of anglicisms in the human translations is taken as 100%.

3.3 Exploration of anglicisms

Lexical borrowings, the transfer of words from one language to another, is a productive mechanism of word formation and thus a catalyst of language evolution. Borrowings emerge from language contact, a universal linguistic phenomenon. They appear in all languages and can constitute a high percentage of lexical items. Moreover, identification of borrowings is important in lexicography, comparative linguistics, and some NLP downstream tasks, yet there is still no reliable way to identify them automatically (Miller et al., 2020; List and Forkel, 2021).

We focus on English borrowings in German, known as anglicisms. The number of anglicisms in German is continuously growing. Reportedly, every 600th word in German could be identified as an anglicism in 1954. In 1964, it became every 200th word; in 1994, every 145th; and in 2004, every 85th (Engels, 1976; Burmasova, 2010). There is a notable societal push against this process or at least concerns about the future of the German language[15]. The investigation of this phenomenon can provide valuable insights into the role of MT in language development. We assess the extent to which MT language models participate in the anglicization of German. To the best of our knowledge, this is the first investigation of this kind.

There are many different ways to classify anglicisms in German: by topic, by type of surface form assimilation ("most anglicisms introduced since 1945 retain their English or-

thography" (Coats, 2019, p.273)), by level of assimilation (Eindeutschung), etc. Often anglicisms are classified into words indicating either new concepts (ergänzende Anglizismen, Bedürfnislehnwörter) or existing concepts (differenzierende (or verdrängende) Anglizismen[16], Luxuslehnwörter (Carstensen, 1965)). Since anglicisms continuously pour into the language but do not always stay, we work with the items that have mostly settled in German. We collected $4,832$ established anglicisms from a dedicated Wikipedia page[17], disregarding "false friends".

To avoid false positives, we filtered out certain homonyms, such as "Tag" (DE: *day*) and "Gang" (DE: *passageway*), and removed the word "in" which occurs in the lexicalized phrase "in sein" (*to be in*). Additionally, we excluded some corpus-specific anglicisms, for example "Credit" in the Credit Suisse Bulletin corpus, or "Miss" in the Jane Eyre corpus. The human translation of Jane Eyre contains an old, pre-1996 spelling of "Miss" as "Miß", which is not on the list of anglicisms.

We customized our search to catch different spelling variations of certain anglicisms (for example: *fairtrade, fair-trade, fair trade*). We tokenized the texts with the Spacy UDpipe tool and matched anglicisms from our list to tokens, lemmas, and multiword units. Additionally, we looked for anglicisms inside German compound words. We used the Compound Split tool[18] to sep-

---

[15]Mind your language: German linguists oppose influx of English words; Denglisch – Deutsch oder Englisch?

[16]contify.de/glossar/richtig-schreiben/was-sind-anglizismen

[17]de.wiktionary.org: last update 12.06.2019; scraped in April, 2022

[18]pypi.org/compound-split/

Figure 4: Distribution of lemmas for the translation variants of the anglicism "meeting" in the CS Bulletin corpus. The lemma "meeting" appears in the English text 119 times. The missing occurrences can be attributed to poor alignments.

arate the components, and matched each component against the list of anglicisms.

In an attempt to avoid more false positives, we employed language detection in order to compensate for insufficient or inadequate compound splitting. However, simple language detection is not a reliable method for the identification of anglicisms. For each corpus, we compiled a list of alleged non-anglicisms resulting from the compound-splitting process. We merged these lists into a unified set and then manually filtered out false positives like in the example for the anglicism *fan* below:

true non-anglicisms: fangen, fandest, Fannie, Stefan
false positives: Fanunterstützung, Fanbasis, Rennfan, Fanbild, Fußballfan, Klassikfan, Autofan, Frankreichfan

The final list contained 342 entries, including words like *musstest* and *könntest* (falsely detected anglicism *test*); *gängig* (gig), *dadurch* (dad), *Psychologin* (gin), *hitzig* and *Hitler* (hit), etc.

Figure 3 shows the full distribution of anglicisms in all the translation versions across all corpora. The number of anglicisms in the human translations is taken as 100%. All other distributions are shown as relative to the human translation. Since the WMT corpora have several human references, the average of their scores is taken as a hundred percent mark.

While we consider the human usage of anglicisms to be the gold standard, the distributions predictably vary even among translators. Similarly, this variability occurs among the MT systems as well. Some trends are noticeable, however. For example, DeepL produces fewer anglicisms than the three other systems, while Microsoft Azure tends to anglicize its output. Figure 4 provides a distribution of translation variant lemmas for a frequent anglicism *meeting* in the CS Bulletin corpus. It shows how this anglicism barely appears in the DeepL output. Nevertheless, the overall distribution of translation variants appears to be more even in the human translation, whereas the MT systems lean towards one particular lemma (here: *treff*).

While most corpora show gentle fluctuations in the anglicism distribution across the systems, we observe a striking difference between the human and machine translations for Tatoeba. This might be due to the fact that all translations are provided by crowd-sourced volunteers, who are eager to show their love and knowledge of German. The distribution of anglicisms in this corpus has a long tail of anglicisms that were avoided by the human translators, but employed by MT: *job, meeting, online, team, internet, baby, flirt, teenager,* etc.

Conversely, the human translations of a small translation company (the transX corpus) exhibit consistently more anglicisms than the output of all other MT systems. This might have to do with the fact that professional translators follow a consistency protocol appropriate to the client's business domain (here: tech). MT systems, on the other hand, maintain a steady degree of diversification.

4 Conclusion

This paper provides a corpus linguistic analysis of different translations, performed by humans and machines, in seven corpora from different domains. We looked at the texts mostly on a micro-level, measuring their lexical and syntactic properties, such as type-token ratio, morphological richness, and syntactic versatility. Additionally, we examined the distribution of translation variants for English lexical items that have entered the German language as borrowings or loan words. Based on our observations, we attempted to make a prediction about the impact that MT might have on human language.

Previous research emphasized that machine-produced texts suffer from standardization, simplification, and monotonicity. On one hand, our results confirm these findings in terms of syntax. Machines do not improvise and mostly follow the syntactic structure of the source sentence, irrespective of the MT system or the textual domain (section 3.2). On the other hand, we show that machine translation is becoming less of a culprit when it comes to lexical impoverishment of language. Some commercial MT systems are capable of generating German texts with levels of lexical and morphological richness similar to those produced by human translators (Section 3.1). Of course, these results reflect only one aspect of translation quality, and our automatic scores suggest that DeepL, not mtX, is the most reliable system for German translations (see Table 2).

Overall, we note that such lexical and syntactic metrics might be getting less informative for the linguistic assessment of MT as the technology continues to improve. Conversely, we determined that automatic evaluation of lexical borrowings - in our case, anglicisms in German - provides an opportunity to assess the rate of language change. Moreover, their distribution is directly related to the quality and purpose of translation. It is important to note that while we focused only on established borrowings, the results indicate that certain machine translation systems appear to produce fewer anglicisms compared to other systems (Section 3.3). In general, human translators adjust the use of anglicisms according to the domain, while the MT systems produce mostly consistent, though system-specific, distributions.

We can infer that machine translation will continue to play a role in the (de-)anglicization of German as the technology advances and more individuals utilize it as a tool for translation. In order to mitigate the impact of machine translation on the German language, specifically in terms of the prevalence of anglicisms, it would be beneficial to undertake research on the development of methods for accurate identification of linguistic borrowings.

It is important to acknowledge that the scope of this study was limited to the German language and the conclusions may not be generalizable to other languages. Additionally, the results are based on a specific set of metrics and corpora, and other factors such as cultural context, idiomatic expressions, nuances, and creativity are not captured by these metrics.

Acknowledgments

Left out for anonymous reviewing.

References

Milam Aiken. 2019. An Updated Evaluation of Google Translate Accuracy. *Studies in Linguistics and Literature*, 3:p253.

Zakaryia Mustafa Almahasees. 2018. Assessment of Google and Microsoft Bing Translation of Journalistic Texts. *International Journal of Languages, Literature and Linguistics*, 4(3):231–235.

Porter Anderson. 2021. During Frankfurt: Springer Nature Offers Auto-Translation for Research. *Publishing Perspectives*.

Mikel Artetxe and Holger Schwenk. 2019. Margin-based Parallel Corpus Mining with Multilingual Sentence Embeddings. *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3197–3203. ArXiv: 1811.01136.

Mona Baker. 1995. Corpora in Translation Studies: An Overview and Some Suggestions for Future Research. *Target. International Journal of Translation Studies*, 7(2):223–243. Publisher: John Benjamins.

Mojca Brglez and Špela Vintar. 2022. Lexical Diversity in Statistical and Neural Machine Translation. *Information*, 13(2):93. Number: 2 Publisher: Multidisciplinary Digital Publishing Institute.

Svetlana Burmasova. 2010. *Empirische Untersuchung der Anglizismen im Deutschen am Material der Zeitung Die WELT (Jahrgänge 1994 und 2004)*. Bamberg University Press. Accepted: 2011-01-31 00:00:00.

Broder Carstensen. 1965. *Englische Einflüsse auf die deutsche Sprache nach 1945*. Number ARRAY(0x56395ff24608) in Jahrbuch für Amerikastudien. Winter, Heidelberg.

Steven Coats. 2019. Lexicon geupdated: New German anglicisms in a social media corpus. *European Journal of Applied Linguistics*, 7(2):255–280. Publisher: De Gruyter Mouton Section: European Journal of Applied Linguistics.

Stephanie Dalzell. 2020. Google Translate used over professional translators for Government's official COVID-19 messaging. *ABC News*.

Barbara Engels. 1976. *Gebrauchsanstieg der lexikalischen und semantischen Amerikanismen in zwei Jahrgängen der "Welt" (1954 und 1964): e. vergl. computerlinguist. Studie zur quantitativen Entwicklung amerikan. Einflusses auf d. dt. Zeitungssprache*. Peter Lang. Google-Books-ID: EKtbAAAAMAAJ.

Anna Farkas and Renáta Németh. 2022. How to measure gender bias in machine translation: Real-world oriented machine translators, multiple reference points. *Social Sciences & Humanities Open*, 5(1):100239.

Martin Gellerstam. 1986. Translationese in Swedish novels translated from English. In *undefined*.

Yvette Graham, Barry Haddow, and Philipp Koehn. 2020. Statistical Power and Translationese in Machine Translation Evaluation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 72–81, Online. Association for Computational Linguistics.

Anne Göhring and Martin Volk. 2011. The Text+Berg Corpus An Alpine French-German Parallel Resource. pages 97–102, Montpellier, France. ATALA.

Dirk Hovy, Federico Bianchi, and Tommaso Fornaciari. 2020. "You Sound Just Like Your Father" Commercial Machine Translation Systems Include Stylistic Biases. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1686–1690, Online. Association for Computational Linguistics.

René Jaun. 2019. Bundesverwaltung erwirbt DeepL-Lizenzen. *Netzwoche*.

Ravish Kapoor, German Corrales, Manuel P. Flores, Lei Feng, and Juan P. Cata. 2022. Use of Neural Machine Translation Software for Patients With Limited English Proficiency to Assess Postoperative Pain and Nausea. *JAMA Network Open*, 5(3):e221485.

Elaine C. Khoong and Jorge A. Rodriguez. 2022. A Research Agenda for Using Machine Translation in Clinical Medicine. *Journal of General Internal Medicine*, 37(5):1275–1277.

Svenja Kranich. 2014. Translations as a Locus of Language Contact. In Juliane House, editor, *Translation: A Multidisciplinary Approach*, Palgrave Advances in Language and Linguistics, pages 96–115. Palgrave Macmillan UK, London.

Johann-Mattis List and Robert Forkel. 2021. Automated identification of borrowings in multilingual wordlists. *Open Research Europe*, 1:79.

Evgeny Matusov. 2019. The Challenges of Using Neural Machine Translation for Literature. In *Proceedings of the Qualities of Literary Machine Translation*, pages 10–19, Dublin, Ireland. European Association for Machine Translation.

Philip M McCarthy. 2005. *An assessment of the range and usefulness of lexical diversity measures and the potential of the measure of textual, lexical diversity (MTLD) - ProQuest*. Ph.D. thesis, University of Memphis, Memphis, Tennessee, USA.

John E. Miller, Tiago Tresoldi, Roberto Zariquiey, César A. Beltrán Castañón, Natalia Morozova, and Johann-Mattis List. 2020. Using lexical language models to detect borrowings in monolingual wordlists. *PLOS ONE*, 15(12):e0242709. Publisher: Public Library of Science.

Neal Morton. 2022. Translating a quarter of a million text messages for families. *The Hechinger Report*.

Lucas Nunes Vieira, Minako O'Hagan, and Carol O'Sullivan. 2020. Understanding the societal impacts of machine translation: a critical review of the literature on medical and legal use cases. *Information, Communication & Society*.

Kelsey Percival. 2022. Google's translate tool hard-coded into city website. *Durango Herald*.

Marcelo O. R. Prates, Pedro H. Avelar, and Luís C. Lamb. 2020. Assessing gender bias in machine translation: a case study with Google Translate. *Neural Computing and Applications*, 32(10):6363–6381.

Ricardo Rei, Craig Stewart, Ana C Farinha, and Alon Lavie. 2020. COMET: A Neural Framework for MT Evaluation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2685–2702, Online. Association for Computational Linguistics.

Natália Resende and Andy Way. 2021. Can Google Translate Rewire Your L2 English Processing? *Digital*, 1(1):66–85. Number: 1 Publisher: Multidisciplinary Digital Publishing Institute.

Aditya Siddhant, Ankur Bapna, Orhan Firat, Yuan Cao, Mia Xu Chen, Isaac Caswell, and Xavier Garcia. 2022. Towards the Next 1000 Languages in Multilingual Machine Translation: Exploring the Synergy Between Supervised and Self-Supervised Learning. ArXiv:2201.03110 [cs].

Arda Tezcan, Joke Daems, and Lieve Macken. 2019. When a 'sport' is a person and other issues for NMT of novels. In *Proceedings of the Qualities of Literary Machine Translation*, pages 40–49. European Association for Machine Translation.

Antonio Toral, Sheila Castilho, Ke Hu, and Andy Way. 2018. Attaining the Unattainable? Reassessing Claims of Human Parity in Neural Machine Translation. ArXiv:1808.10432 [cs].

Gideon Toury. 1995. *Descriptive Translation Studies – and beyond*. John Benjamins Publishing Company. Publication Title: btl.100.

Jonas-Dario Troles and Ute Schmid. 2021. Extending Challenge Sets to Uncover Gender Bias in Machine Translation: Impact of Stereotypical Verbs and Adjectives. In *Proceedings of the Sixth Conference on Machine Translation*, pages 531–541, Online. Association for Computational Linguistics.

Eva Vanmassenhove, Dimitar Shterionov, and Matthew Gwilliam. 2021. Machine Translationese: Effects of Algorithmic Bias on Linguistic Complexity in Machine Translation. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 2203–2213, Online. Association for Computational Linguistics.

Bram Vanroy. 2021. *Syntactic difficulties in translation*. dissertation, Ghent University.

Bram Vanroy, Moritz Schaeffer, and Lieve Macken. 2021. Comparing the Effect of Product-Based Metrics on the Translation Process. *Frontiers in Psychology*, 12.

Martin Volk, Chantal Amrhein, Noëmi Aepli, Mathias Müller, and Phillip Ströbel. 2016. Building a Parallel Corpus on the World's Oldest Banking Magazine. Bochum.

Martin Volk, Noah Bubenhofer, Adrian Althaus, Maya Bangerter, Lenz Furrer, and Beni Ruef. 2010. Challenges in building a multilingual alpine heritage corpus. Malta. University of Zurich.

Rebecca Webster, Margot Fonteyne, Arda Tezcan, Lieve Macken, and Joke Daems. 2020. Gutenberg goes neural : comparing features of Dutch human translations with raw neural machine translation outputs in a corpus of English literary classics. *INFORMATICS-BASEL*, 7(3). Number: 3.

G.U. Yule. 1944. *The statistical study of literary vocabulary*. The University Press. Tex.lccn: 44029835.

Mike Zhang and Antonio Toral. 2019. The Effect of Translationese in Machine Translation Test Sets. In *Proceedings of the Fourth Conference on Machine Translation (Volume 1: Research Papers)*, pages 73–81, Florence, Italy. Association for Computational Linguistics.

Appendix A   SacreBLEU scores

corpus	azure	deepl	google	mtX
WMT21	59.0	**69.9**	58.5	53.1
WMT22	50.7	48.5	**52.3**	47.1
Tatoeba	40.6	**42.0**	41.8	39.7
transX	33.0	**36.7**	33.1	32.0
JaneEyre	18.7	**20.1**	19.5	18.6
CSBull	31.5	**32.2**	31.7	30.1
Text+Berg	23.5	**27.2**	24.4	24.6

Table 3: SacreBLEU scores v 2.2.1 across full-sized corpora per MT system. The best values are in **bold**.

Appendix B   Lexical richness scores

	system	TTR	Yule's	MTLD		system	TTR	Yule's	MTLD
WMT21	humanA	24.1	**610.79**	134.47	Tatoeba	human	**21.37**	**333.36**	**82.49**
	humanC	23.25	533.61	125.93		azure	20.39	274.15	72.49
	humanD	23.83	562.83	129.73		deepl	20.27	276.48	69.29
	azure	22.84	456.32	129.14		google	20.82	288.72	73.28
	deepl	22.89	475.89	127.37		mtX	20.92	283.91	71.02
	google	23.06	488.02	129.74	transX	human	22.8	**624.76**	**138.32**
	mtX	**24.13**	528.95	**136.34**		azure	22.19	504.05	132.47
						deepl	22	498.44	130.55
WMT22	humanA	19.17	369.49	109.5		google	22.73	548.7	136.45
	humanB	19.76	**405.13**	111.3		mtX	**22.99**	552.01	136.65
	azure	19.25	349.45	113.48	CS Bulletin	human	**7.8**	**69.38**	**279.39**
	deepl	19.3	360.71	110.55		azure	6.55	46.88	249.45
	google	19.7	379.68	112.81		deepl	6.44	44.84	228.18
	mtX	**20.3**	395.08	**117.8**		google	6.88	54.13	258.3
						mtX	6.7	48.75	249.33
Jane Eyre	human	8.08	59.31	126.88	Text+Berg	human	**9.5**	**91.95**	**276.93**
	azure	8.09	54.45	136.64		azure	8.1	58.47	201.06
	deepl	8.15	52.06	127.14		deepl	8.37	67.3	203.15
	google	8.38	**63.31**	**136.87**		google	8.62	70.22	212.04
	mtX	**8.56**	58.01	129.51		mtX	8.07	56.65	191.42

Figure 5: Lexical richness measured with TTR, Yule's I, and MTLD across all corpora. Higher scores (in **bold**) indicate higher lexical richness.

Appendix C   Lexical frequency profile

	system	B1	B2	B3		system	B1	B2	B3
WMT21	humanA	**72.43**	8.49	**19.08**	Tatoeba	human	**67.72**	6.39	**25.9**
	humanC	73.51	8.27	18.23		azure	69.37	6.51	24.12
	humanD	72.77	8.48	18.75		deepl	70.03	6.41	23.55
	azure	74.11	8.37	17.52		google	68.73	6.52	24.75
	deepl	74.1	8.26	17.64		mtX	68.81	6.55	24.64
	google	73.75	8.41	17.84	transX	human	**78.13**	8.88	**12.99**
	mtX	72.97	8.52	18.51		azure	79.41	8.35	12.24
						deepl	79.5	8.31	12.19
WMT22	humanA	75.65	7.65	16.7		google	78.76	8.58	12.65
	humanB	75.12	7.55	17.33		mtX	78.61	8.52	12.87
	azure	75.62	7.63	16.75	CS Bulletin	human	**83.34**	7.53	**9.14**
	deepl	75.57	7.52	16.91		azure	84.2	7.73	8.07
	google	75.1	7.61	17.29		deepl	84.12	7.66	8.22
	mtX	**74.6**	7.66	**17.74**		google	83.84	7.81	8.35
						mtX	83.85	7.86	8.3
Jane Eyre	human	79.07	5.95	14.98	Text+Berg	human	**71.55**	6.19	**22.25**
	azure	79.7	5.65	14.65		azure	73.61	6.13	20.25
	deepl	80.06	5.48	14.46		deepl	73.41	6.04	20.55
	google	79.5	5.58	14.92		google	72.85	6.15	21
	mtX	**79.02**	5.71	**15.27**		mtX	73.97	5.97	20.06

Figure 6: lexical frequency profile with step=1000 and last=2000

Appendix D Morphological richness scores

	system	H	D		system	H	D
WMT21	humanA	**85.56**	**47.05**	Tatoeba	human	86.74	47.52
	humanC	83.16	48.41		azure	86.17	47.9
	humanD	84.38	47.82		deepl	87.77	47.59
	azure	82.75	48.32		google	87	47.55
	deepl	83.48	48.1		mtX	**88.29**	**46.93**
	google	83.29	48.11	transX	human	80.21	49.82
	mtX	82.85	48.15		azure	**80.57**	**49.45**
					deepl	79.72	49.86
WMT22	humanA	**82.79**	**48.98**		google	80.14	49.89
	humanB	82.63	49.02		mtX	79.22	49.93
	azure	82.3	49.44	CS Bulletin	human	82.72	50.38
	deepl	81.33	50		azure	86.12	49.04
	google	81.48	49.7		deepl	85.01	49.45
	mtX	82.34	49.26		google	85.47	49.33
					mtX	**86.25**	**48.98**
Jane Eyre	human	85.87	48.5	Text+Berg	human	84.36	49.41
	azure	86.82	48.06		azure	**85.79**	49
	deepl	**87.69**	**47.65**		deepl	85.69	**48.81**
	google	86.46	48.25		google	84.65	49.47
	mtX	85.9	48.32		mtX	84.65	49.46

Figure 7: Morphological richness measured with Shannon entropy (H) and Simpson's diversity (D). Higher H and lower D indicate morphologically richer text (marked in **bold**).