A Best-of-Both-Worlds Algorithm for Bandits with Delayed Feedback

Abstract

We present a modified tuning of the algorithm of Zimmert and Seldin [2020] for adversarial multiarmed bandits with delayed feedback, which in addition to the minimax optimal adversarial regret guarantee shown by Zimmert and Seldin simultaneously achieves a near-optimal regret guarantee in the stochastic setting with fixed delays. Specifically, the adversarial regret guarantee is $\mathcal{O}(\sqrt{TK} + \sqrt{dT \log K})$, where T is the time horizon, K is the number of arms, and d is the fixed delay, whereas the stochastic regret guarantee is $\mathcal{O}\left(\sum_{i \neq i^*}(\frac{1}{\Delta_i} \log(T) + \frac{d}{\Delta_i \log K}) + dK^{1/3} \log K\right)$, where Δ_i are the suboptimality gaps. We also present an extension of the algorithm to the case of arbitrary delays, which is based on an oracle knowledge of the maximal delay d_{max} and achieves $\mathcal{O}(\sqrt{TK} + \sqrt{D \log K} + d_{max}K^{1/3} \log K)$ regret in the adversarial regime, where D is the total delay, and $\mathcal{O}\left(\sum_{i \neq i^*}(\frac{1}{\Delta_i} \log(T) + \frac{\sigma_{max}}{\Delta_i \log K}) + d_{max}K^{1/3} \log K\right)$ regret in the stochastic regime, where σ_{max} is the maximal number of outstanding observations. Finally, we present a lower bound that matches regret upper bound achieved by the skipping technique of Zimmert and Seldin [2020] in the adversarial setting.

1 Introduction

Delayed feedback is a common challenge in many online learning problems, including multi-armed bandits. The literature studying multi-armed bandit games with delayed feedback builds on prior work on bandit problems with no delays. The researchers have traditionally separated the study of bandit games in stochastic environments [Thompson, 1933, Robbins, 1952, Lai and Robbins, 1985, Auer et al., 2002] and in adversarial environments[Auer et al., 2002b]. However, in practice the environments are rarely purely stochastic, whereas they may not be fully adversarial either. Furthermore, the exact nature of an environment is not always known in practice. Therefore, in recent years there has been an increasing interest in algorithms that perform well in both regimes with no prior knowledge of the regime [Bubeck and Slivkins, 2012, Seldin and Slivkins, 2014, Auer and Chiang, 2016, Seldin and Lugosi, 2017, Wei and Luo, 2018]. The quest for best-of-both-worlds algorithms for no-delay setting culminated with the Tsallis-INF algorithm proposed by Zimmert and Seldin [2019], which achieves the optimal regret bounds in both stochastic and adversarial environments. The algorithm and analysis were further improved by Zimmert and Seldin [2021] and Masoudian and Seldin [2021], who, in particular, derived improved regret bounds for intermediate regimes between stochastic and adversarial.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Our goal is to extend best-of-both-worlds results to multi-armed bandits with delayed feedback. So far the literature on multi-armed bandits with delayed feedback has followed the traditional separation into stochastic and advesrarial. In the stochastic regime Joulani et al. [2013] showed that if the delays are random (generated i.i.d), then compared to the non-delayed stochastic multi-armed bandit setting, the regret only increases additively by a factor that is proportional to the expected delay. In the adversarial setting Cesa-Bianchi et al. [2016] have first studied the case of uniform delays d. They derived a lower bound $\Omega(\max(\sqrt{KT}, \sqrt{dT \log K}))$ and an almost matching upper bound $\mathcal{O}(\sqrt{KT \log K} + \sqrt{dT \log K})$. Thune et al. [2019] and Bistritz et al. [2019] extended the results to arbitrary delays, achieving $\mathcal{O}(\sqrt{KT \log K} + \sqrt{D \log K})$ regret bounds based on oracle knowledge of the total delay D and time horizon T. Thune et al. [2019] also proposed a skipping technique based on advance knowledge of the delays "at action time", which allowed to exclude excessively large delays from D. Finally, Zimmert and Seldin [2020] introduced an FTRL algorithm with a hybrid regularizer that achieved $\mathcal{O}(\sqrt{KT} + \sqrt{D \log K})$ regret bound, matching the lower bound in the case of uniform delays and requiring no prior knowledge of D or T. The regularizer used by Zimmert and Seldin was a mix of the negative Tsallis entropy regularizer used in the Tsallis-INF algorithm for bandits and the negative entropy regularizer used in the Hedge algorithm for full information games, mixed with separate learning rates:

$$F_t(x) = -2\eta_t^{-1}\left(\sum_{i=1}^{K} \sqrt{x_i}\right) + \gamma_t^{-1}\left(\sum_{i=1}^{K} x_i(\log x_i - 1)\right). \tag{1}$$

Zimmert and Seldin [2020] also perfected the skipping technique and achieved a refined regret bound $\mathcal{O}(\sqrt{KT} + \min_S(|S| + \sqrt{D_{\bar{S}} \log K}))$, where S is a set of skipped rounds and $D_{\bar{S}}$ is the total delay in non-skipped rounds. The refined skipping technique requires no advance knowledge of the delays and the key step to eliminating the need in advance knowledge was to base it on counting the outstanding observations rather than the delays. The great advantage of skipping is that a few rounds with excessively large or potentially even infinite delays have a very limited impact on the regret bound. One of our contributions in this paper is a lower bound for the case of non-uniform delays, which matches the refined regret upper bound achieved by skipping.

Even though the hybrid regularizer used by Zimmert and Seldin [2020] was sharing the Tsallis entropy part with their best-of-both-worlds Tsallis-INF algorithm from Zimmert and Seldin [2021], and even though the adversarial analysis was partly similar to the analysis of the Tsallis-INF algorithm, Zimmert and Seldin [2020] did not succeed in deriving a regret bound for their algorithm in the stochastic setting with delayed feedback and left it as an open problem.

The stochastic analysis of the Tsallis-INF algorithm is based on the self-bounding technique [Zimmert and Seldin, 2021]. Application of this technique in the no delay setting is relatively straightforward, but in presence of delays it requires control of the drift of the playing distribution from the moment an action is played to the moment the feedback arrives. Cesa-Bianchi et al. [2016] have bounded the drift of the playing distribution of the EXP3 algorithm in the uniform delays setting with a fixed learning rate. But best-of-both-worlds algorithms require decreasing learning rates Mourtada and Gaïffas [2019], which makes the drift control much more challenging. The problem gets even more challenging in the case of arbitrary delays, because it requires drift control over arbitrary long periods of time.

We apply an FTRL algorithm with the same hybrid regularizer as the one used by Zimmert and Seldin [2020], but with a different tuning of the learning rates. The new tuning has a minor effect on the adversarial regret bound, but allows us to make progress with the stochastic analysis. For the stochastic analysis we use the self-bounding technique. One of our key contributions is a general lemma that bounds the drift of the playing distribution derived from the time-varying hybrid regularizer over arbitrary delays. Using this lemma we derive near-optimal best-of-both-worlds regret guarantees for the case of fixed delays. But even with the lemma at hand, application of the self-bounding technique in presence of arbitrary delays is still much more challenging than in the no delays or fixed delay setting. Therefore, we resort to introducing an assumption of oracle knowledge of the maximal delay, which limits the maximal period of time over which we need to keep control over the drift. Our contributions are summarized below. To keep the presentation simple we assume

uniqueness of the best arm throughout the paper. Tools for eliminating the uniqueness of the best arm assumption were proposed by Ito [2021].

1. We show that in the arbitrary delays setting with an oracle knowledge of the maximal delay d_{max} our algorithm achieves $\mathcal{O}(\sqrt{KT} + \sqrt{D \log K} + d_{max} K^{1/3} \log K)$ regret bound in the adversarial regime simultaneously with $\mathcal{O}\left(\sum_{i \neq i^*}(\frac{\log T}{\Delta_i} + \frac{\sigma_{max}}{\Delta_i \log K}) + d_{max} K^{1/3} \log K\right)$ regret bound in the stochastic regime, where σ_{max} is the maximal number of outstanding observations. We note that $\sigma_{max} \leq d_{max}$, but it may potentially be much smaller. For example, if the first observation has a delay of T and all the remaining observations have zero delay, then $d_{max} = T$, but $\sigma_{max} = 1$.

2. In the case of uniform delays the above bounds simplify to $\mathcal{O}(\sqrt{KT} + \sqrt{dT \log K} + dK^{1/3} \log K)$ in the adversarial case and $\mathcal{O}\left(\sum_{i \neq i^*}(\frac{\log T}{\Delta_i} + \frac{d}{\Delta_i \log K}) + dK^{1/3} \log K\right)$ in the stochastic case. For $T \geq dK^{1/3} \log K$ the last term in the adversarial regret bound is dominated by the middle term, which leads to the minimax optimal $\mathcal{O}(\sqrt{KT} + \sqrt{dT \log K})$ adversarial regret. The stochastic regret lower bound is trivially $\Omega(\min\{d, \sum_{i \neq i^*} \frac{\log T}{\Delta_i}\}) = \Omega(d + \sum_{i \neq i^*} \frac{\log T}{\Delta_i})$ and, therefore, our stochastic regret upper bound is near-optimal.

3. We present an $\Omega\left(\sqrt{KT} + \min_S(|S| + \sqrt{D_{\bar{S}} \log K})\right)$ regret lower bound for adversarial multi-armed bandits with non-uniformly delayed feedback, which matches the refined regret upper bound achieved by the skipping technique of Zimmert and Seldin [2020].

2 Problem Setting

We study the multi-armed bandit with delays problem, in which at time $t = 1, 2, \ldots$ the learner chooses an arm I_t among a set of K arms and instantaneously suffers a loss ℓ_{t,I_t} from a loss vector $\ell_t \in [0, 1]^K$ generated by the environment, but ℓ_{t,I_t} is not observed by the learner immediately. After a delay of d_t, at the end of round $t + d_t$, the learner observes the pair (t, ℓ_{t,I_t}), namely, the loss and the index of the game round the loss is coming from. The sequence of delays $d_1, d_2, \ldots$ is selected arbitrarily by the environment. Without loss of generality we can assume that all the outstanding observations are revealed at the end of the game, i.e., $t + d_t \leq T$ for all t, where T is the time horizon. We consider two regimes, oblivious adversarial and stochastic. The performance of the learner is evaluated using pseudo-regret, which is defined as

$$\overline{Reg}_T = \mathbb{E}\left[\sum_{t=1}^T \ell_{t,I_t}\right] - \min_{i \in [K]} \mathbb{E}\left[\sum_{t=1}^T \ell_{t,i}\right] = \mathbb{E}\left[\sum_{t=1}^T \left(\ell_{t,I_t} - \ell_{t,i_T^*}\right)\right],$$

where $i_T^* \in \operatorname{argmin}_{i \in [K]} \mathbb{E}\left[\sum_{t=t}^T \ell_{t,i}\right]$ is a best arm in hindsight in expectation over the loss generation model and the randomness of the learner. In the oblivious adversarial setting the losses are assumed to be deterministic and the pseudo-regret is equal to the expected regret.

Additional Notation: We use Δ^n to denote the probability simplex over $n + 1$ points. The characteristic function of a closed convex set $\mathcal{A}$ is denoted by $\mathcal{I}_{\mathcal{A}}(x)$ and satisfies $\mathcal{I}_{\mathcal{A}}(x) = 0$ for $x \in \mathcal{A}$ and $\mathcal{I}_{\mathcal{A}}(x) = \infty$ otherwise. The convex conjugate of a function $f : \mathbb{R}^n \to \mathbb{R}$ is defined by $f^*(y) = \sup_{x \in \mathbb{R}^n}\{\langle x, y \rangle - f(x)\}$. We also use bar to denote that the function domain is restricted to Δ^n, e.g., $\bar{f}(x) = \begin{cases} f(x), & \text{if } x \in \Delta^n \\ \infty, & \text{otherwise} \end{cases}$. We denote the indicator function of an event $\mathcal{E}$ by $\mathbb{1}(\mathcal{E})$ and use $\mathbb{1}_t(i)$ as a shorthand for $\mathbb{1}(I_t = i)$. The probability distribution over arms that is played by the learner at round t is denoted by $x_t \in \Delta^{K-1}$.

3 Algorithm

The algorithm is based on Follow The Regularized Leader (FTRL) algorithm with the hybrid regularizer used by Zimmert and Seldin [2020], stated in equation (1). At each time step t let

$\sigma_t = \sum_{s=1}^{t-1} \mathbb{1}(s + d_s \geq t)$ be the number of the outstanding observations and $\mathcal{D}_t = \sum_{s=1}^{t} \sigma_t$ be the cumulative outstanding observations, then the learning rates are defined as

$$\eta_t^{-1} = \sqrt{t + \eta_0}, \qquad\qquad \gamma_t^{-1} = \sqrt{\frac{\sum_{s=1}^{t} \sigma_s + \gamma_0}{\log K}},$$

where $\eta_0 = 10 d_{max} + d_{max}^2 / \left(K^{1/3} \log(K)\right)^2$ and $\gamma_0 = 24^2 d_{max}^2 K^{2/3} \log(K)$. The update rule for the distribution over actions played by the learner is

$$x_t = \nabla \bar{F}_t^*(-\hat{L}_t^{obs}) = \arg \min_{x \in \Delta^{K-1}} \langle \hat{L}_t^{obs}, x \rangle + F_t(x), \tag{2}$$

where $\hat{L}_t^{obs} = \sum_{s=1}^{t-1} \hat{\ell}_s \mathbb{1}(s + d_s < t)$ and $\hat{\ell}_s$ is an importance-weighted estimate of the loss vector ℓ_s defined by

$$\hat{\ell}_{t,i} = \frac{\ell_{t,i} \mathbb{1}(I_t = i)}{x_{t,i}}.$$

The algorithm at the beginning of iteration t calculates the cumulative outstanding observations $\mathcal{D}_t$ and uses it to define γ_t. Next, it uses the FTRL update rule defined in (2) to draw action I_t. Finally, at the end of round t it receives the delayed observations and update cumulative loss estimation vector accordingly so that $L_{t+1}^{obs} = \sum_{s=1}^{t} \hat{\ell}_s \mathbb{1}(s + d_s = t)$. The complete algorithm is provided in Algorithm 1.

Algorithm 1: FTRL with advance tuning for delayed bandit

Input: Learning rate rule η_t and γ_t
Initialize $\mathcal{D}_0 = 0$ *and* $\hat{L}_1^{obs} = \mathbf{0}_K$ *(where* $\mathbf{0}_K$ *is a zero vector in* $\mathbb{R}^K$*)*
for $t = 1, \ldots, n$ **do**
    determine γ_t
        Set $\sigma_t = \sum_{s=1}^{t-1} \mathbb{1}(s + d_s > t)$
        Update $\mathcal{D}_t = \mathcal{D}_{t-1} + \sigma_t$
    Set $x_t = \arg \min_{x \in \Delta^{K-1}} \langle \hat{L}_t^{obs}, x \rangle + F_t(x)$
    Sample $I_t \sim x_t$
    for $s : s + d_s = t$ **do**
        Observe (s, ℓ_{s, I_s})
        Construct $\hat{\ell}_s$ and update $\hat{L}_t^{obs}$

---

4   Best-of-both-worlds Regret Bounds for Algorithm 1

In this section we provide best-of-both-worlds regret bounds for Algorithm 1. First, in Theorem 1 we provide regret bounds for an arbitrary delay setting, where we assume an oracle access to d_{max}. Then, in Corollary 2 we specialize the result to a fixed delay setting.

Theorem 1. *Assume that Algorithm 1 is given an oracle knowledge of* d_{max}*. Then its pseudo-regret for any sequence of delays and losses satisfies*

$$\overline{Reg}_T = \mathcal{O}(\sqrt{TK} + \sqrt{D \log K} + d_{max} K^{1/3} \log K).$$

Furthermore, in the stochastic regime the pseudo-regret additionally satisfies

$$\overline{Reg}_T = \mathcal{O}\left(\sum_{i \neq i^*} (\frac{1}{\Delta_i} \log(T) + \frac{\sigma_{max}}{\Delta_i \log K}) + d_{max} K^{1/3} \log K\right).$$

An overview of the proof is provided in Section 5 and the complete proof is provided in Appendix D. For fixed delays Theorem 1 gives the following corollary.

Corollary 2. *If the delays are fixed and equal to d, and $T \geq dK^{1/3} \log K$, then the pseudo-regret of Algorithm 1 always satisfies*

$$\overline{Reg}_T = \mathcal{O}(\sqrt{TK} + \sqrt{dT \log K})$$

and in the stochastic setting it additionally satisfies

$$\overline{Reg}_T = \mathcal{O}\left(\sum_{i \neq i^*} (\frac{1}{\Delta_i} \log(T) + \frac{d}{\Delta_i \log K}) + dK^{1/3} \log K\right).$$

In the adversarial regime with fixed delays d, regret lower bound is $\Omega\left(\sqrt{KT} + \sqrt{dT \log K}\right)$, whereas in the stochastic regime with fixed delays the regret lower bound is trivially $\Omega(d + \sum_{i \neq i^*} \frac{\log T}{\Delta_i})$. Thus, in the adversarial regime the corollary yields the minimax optimal regret bound and in the stochastic regime it is near-optimal. More explicitly, it is optimal within a multiplicative factor of $\sum_{i \neq i^*} \frac{1}{\Delta_i \log K} + K^{1/3} \log K$ in front of d.

If we fix a total delay budget D, then uniform delays $d = D/T$ is a special case, and in this sense Theorem 1 is also optimal in the adversarial regime and near-optimal in the stochastic regime, although for non-uniform delays improved regret bounds can potentially be achieved by skipping. We also note that having the dependence on σ_{max} in the middle term of the stochastic regret bound in Theorem 1 is better than having a dependence on d_{max}, since $\sigma_{max} \leq d_{max}$, and in some cases it can be significantly smaller, as shown in the example in the Introduction and quantified in the following lemma.

Lemma 3. *Let $d_{max}(S) = \max_{s \in S} d_s$, where $S \subseteq \{1, \ldots, T\}$ is a subset of rounds. Let $\bar{S} = \{1, \ldots, T\} \setminus S$ be the remaining rounds. Then*

$$\sigma_{max} \leq \min_{S \subseteq \{1, \ldots, T\}} \left\{|S| + d_{max}(\bar{S})\right\}.$$

A proof of Lemma 3 is provided in Appendix A.

5 A Sketch of the Proof of Theorem 1

In this section we provide a sketch of the proof of Theorem 1. We provide a proof sketch for the stochastic bound in Section 5.1. Afterwards, in Section 5.2 we show how the analysis of Zimmert and Seldin [2020] gives the adversarial bound stated in Theorem 1.

5.1 Stochastic Bound

We start by providing a key lemma (Lemma 4) that controls the drift of the playing distribution derived from the time-varying hybrid regularizer over arbitrary delays. We then introduce the drifted version of pseudo-regret defined in (3), for which we use the key lemma to show that the drifted version of the pseudo-regret is close to the actual one. As a result, it is sufficient to bound the drifted version. The analysis of the drifted pseudo-regret follows by the standard analysis of the FTRL algorithm [Lattimore and Szepesvári, 2020] that decomposes the pseudo-regret (drifted pseudo-regret in our case) into stability and penalty terms. Thereafter, we proceed by using Lemma 4 again, this time to bound the stability term in order to apply the self-bounding technique [Zimmert and Seldin, 2019], which yields logarithmic regret for the stochastic setting. Our key lemma is the following.

Lemma 4 (The Key Lemma). *For any $i \in [K]$ and $s, t \in [T]$, where $s \leq t$ and $t - s \leq d_{max}$, we have the following inequality*

$$x_{t,i} \leq 2x_{s,i}.$$

A detailed proof of the lemma is provided in Appendix B. Below we explain the high level idea behind the proof.

Proof sketch. We know that $x_t = F_t^*(-\hat{L}_t^{obs})$ and $x_s = F_s^*(-\hat{L}_s^{obs})$, so we introduce $\tilde{x} = F_s^*(-\hat{L}_t^{obs})$ as an auxiliary variable to bridge from x_t and x_s. The analysis consists of two key steps and is based on induction on (t, s).

Deviation Induced by the Loss Shift: This step controls the drift when we fix the regularization (more precisely the learning rates) and shift the cumulative loss. We prove the following inequality:

$$\tilde{x}_i \leq \frac{3}{2} x_{s,i}.$$

Note that this step uses the induction assumption for $(s, s - d_r)$ for all $r < s : r + d_r = s$.

Deviation Induced by the Change of Regularizer: In this step we bound the drift when the cumulative loss vector is fixed and we change the regularizer. We show that

$$x_{t,i} \leq \frac{4}{3} \tilde{x}_i.$$

Combining these two steps gives us the desired bound. A proof of these steps is in Appendix B. ∎

We use Lemma 4 to relate the drifted pseudo-regret to the actual pseudo-regret. Let $A_t = \{s \leq t : s + d_s = t\}$ be the set of rounds for which feedback arrives at round t. We define the observed loss vector at time t as $\hat{\ell}_t^{obs} = \sum_{s \in A_t} \hat{\ell}_s$ and the drifted pseudo-regret as

$$\overline{Reg}_T^{drift} = \mathbb{E}\left[\sum_{t=1}^T \left(\langle x_t, \hat{\ell}_t^{obs}\rangle - \hat{\ell}_{t,i_T^*}^{obs}\right)\right]. \tag{3}$$

We rewrite the drifted regret as

$$\overline{Reg}_T^{drift} = \mathbb{E}\left[\sum_{t=1}^T \sum_{s \in A_t} \left(\langle x_t, \hat{\ell}_s\rangle - \hat{\ell}_{s,i_T^*}\right)\right]$$

$$= \sum_{t=1}^T \sum_{s \in A_t} \sum_{i=1}^K \mathbb{E}[x_{t,i}(\hat{\ell}_{s,i} - \hat{\ell}_{s,i_T^*})]$$

$$= \sum_{t=1}^T \sum_{s \in A_t} \sum_{i=1}^K \mathbb{E}[x_{t,i}]\Delta_i = \sum_{t=1}^T \sum_{i=1}^K \mathbb{E}[x_{t+d_t,i}]\Delta_i,$$

where when taking the expectation we use the facts that $\hat{\ell}_s$ has no impact on x_t and that the loss estimators are unbiased. Using Lemma 1 we make a connection between pseudo-regret and the drifted version:

$$\overline{Reg}_T^{drift} = \sum_{t=1}^T \sum_{i=1}^K \mathbb{E}[x_{t+d_t,i}]\Delta_i \geq \sum_{t=1}^{T-d_{max}} \sum_{i=1}^K \frac{1}{2} \mathbb{E}[x_{t+d_{max},i}]\Delta_i$$

$$= \frac{1}{2} \sum_{t=d_{max}+1}^T \sum_{i=1}^K \mathbb{E}[x_{t,i}]\Delta_i$$

$$\geq \frac{1}{2} \sum_{t=1}^T \sum_{i=1}^K \mathbb{E}[x_{t,i}]\Delta_i - \frac{d_{max}}{2} = \frac{1}{2}\overline{Reg}_T - \frac{d_{max}}{2},$$

where the first inequality follows by Lemma 4 for $(t + d_{max}, t + d_t)$, and the second inequality uses $\sum_{t=1}^{d_{max}} \mathbb{E}[x_{t,i}]\Delta_i \leq d_{max}$. As a result, we have $\overline{Reg}_T \leq 2\overline{Reg}_T^{drift} + d_{max}$ and it suffices to upper bound $\overline{Reg}_T^{drift}$. We follow the standard analysis of FTRL, which decomposes the drifted pseudo-regret into *stabiltiy* and *penalty* terms as

$$\overline{Reg}_T^{drift} = \mathbb{E}\left[\underbrace{\sum_{t=1}^T \langle x_t, \hat{\ell}_t^{obs}\rangle + F_t^*(-\hat{L}_{t+1}^{obs}) - F_t^*(-\hat{L}_t^{obs})}_{stability}\right] + \mathbb{E}\left[\underbrace{\sum_{t=1}^T F_t^*(-\hat{L}_t^{obs}) - F_t^*(-\hat{L}_{t+1}^{obs}) - \ell_{t,i_T^*}}_{penalty}\right].$$

For the penalty term we have the following bound by Abernethy et al. [2015]

$$penalty \leq \sum_{t=2}^{T} (F_{t-1}(x_t) - F_t(x_t)) + F_T(x^*) - F_1(x_1).$$

By replacing the closed form of the regularizer in this bound and using the facts that $\eta_t^{-1} - \eta_{t-1}^{-1} = \mathcal{O}(\eta_t)$ and $\gamma_t^{-1} - \gamma_{t-1}^{-1} = \mathcal{O}(\sigma_t \gamma_t / \log K)$ we obtain

$$penalty \leq \mathcal{O}\left(\sum_{t=2}^{T} \sum_{i \neq i^*} \eta_t x_{t,i}^{\frac{1}{2}} + \sum_{t=2}^{T} \sum_{i=1}^{K} \frac{\sigma_t \gamma_t x_{t,i} \log(1/x_{t,i})}{\log K}\right) + \sqrt{\eta_0(K-1)} + 2\sqrt{\gamma_0 \log K}. \tag{4}$$

To deal with the stability term we derive Lemma 5.

Lemma 5 (Stability). *For any $\alpha_t \leq \gamma_t^{-1}$ we have*

$$stability \leq \sum_{t=1}^{T} \sum_{i=1}^{K} 2 f_t''(x_{t,i})^{-1} (\hat{\ell}_{t,i}^{obs} - \alpha_t)^2.$$

Furthermore, let $a_t = |A_t|$. Then $\alpha_t = \frac{\sum_{j=1}^{K} f''(x_{t,j})^{-1} \hat{\ell}_{t,j}^{obs}}{\sum_{j=1}^{K} f''(x_{t,j})^{-1}}$ is a valid α, for which we have

$$\mathbb{E}[stability] \leq \sum_{t=1}^{T} \sum_{i \neq i^*} 2\gamma_t(a_t - 1) a_t \mathbb{E}[x_{t,i}] \Delta_i + \sum_{t=1}^{T} \sum_{s \in A_t} \sum_{i=1}^{K} \eta_t \mathbb{E}[x_{t,i}^{3/2} x_{s,i}^{-1} (1 - x_{s,i})]. \tag{5}$$

A proof of the stability lemma is provided in Appendix A.3. We use Lemma 4 in (5) to give bounds $a_t x_{t,i} = \sum_{s \in A_t} x_{t,i} \leq 2 \sum_{s \in A_t} x_{s,i}$ and $x_{t,i}^{3/2} x_{s,i}^{-1}(1 - x_{s,i}) \leq x_{s,i}^{1/2}(1 - x_{s,i})$. Moreover, in order to remove the best arm i^* from the summation in the later bound we use $x_{s,i^*}^{1/2}(1 - x_{s,i^*}) \leq \sum_{i \neq i^*} x_{s,i} \leq \sum_{i \neq i^*} x_{s,i}^{1/2}$. These bounds together with the facts that we can change the order of the summations and that each t belongs to exactly one A_s, gives us the following stability bound

$$\mathbb{E}[stability] = \mathcal{O}\left(\sum_{t=1}^{T} \sum_{i \neq i^*} \eta_t \mathbb{E}[x_{t,i}^{1/2}] + \sum_{t=1}^{T} \sum_{i \neq i^*} \gamma_{t+d_t}(a_{t+d_t} - 1) \mathbb{E}[x_{t,i}] \Delta_i\right). \tag{6}$$

By combining (6), (4), and the fact that $\overline{Reg}_T \leq 2\overline{Reg}_T^{drift} + d_{max}$, we show that there exist constants $a, b, c \geq 0$, such that

$$\overline{Reg}_T \leq \mathbb{E}\left[\underbrace{\sum_{t=1}^{T} \sum_{i \neq i^*} a \eta_t x_{t,i}^{1/2}}_{A} + \underbrace{\sum_{t=1}^{T} \sum_{i \neq i^*} b \gamma_{t+d_t}(a_{t+d_t} - 1) x_{t,i} \Delta_i}_{B} + \underbrace{\sum_{t=2}^{T} \sum_{i=1}^{K} \frac{c \sigma_t \gamma_t x_{t,i} \log(1/x_{t,i})}{\log K}}_{C}\right]$$
$$+ \underbrace{4\sqrt{\eta_0(K-1)} + 2\sqrt{\gamma_0 \log K} + d_{max}}_{D}. \tag{7}$$

Self Bounding Analysis: We use the self-bounding technique to write $\overline{Reg}_T = 4\overline{Reg}_T - 3\overline{Reg}_T$, and then based on (7) we have

$$\overline{Reg}_T \leq \mathbb{E}\left[A - \overline{Reg}_T\right] + \mathbb{E}\left[B - \overline{Reg}_T\right] + \mathbb{E}\left[C - Reg_T\right] + 4D. \tag{8}$$

For D we can substitute the values of γ_0 and η_0 and get

$$D = \mathcal{O}(d_{max}(K-1)^{1/3} \log K). \tag{9}$$

Upper bounding A, B, and C requires separate and elaborate analyses, for which we provide three lemmas, Lemma 6, 7 and 8. Proofs of these lemmas are in Appendix A.2.

Lemma 6 (Bound for $A - Reg_T$)**.** *We have the following bound for any $a \geq 0$:*

$$A - Reg_T \leq \sum_{i \neq i^*} \frac{a^2}{\Delta_i} \log(T/\eta_0 + 1). \tag{10}$$

Lemma 6 leads to the logarithmic bound in terms of T in our regret.

Lemma 7 (Bound for $B - \overline{Reg}_T$)**.** *Let $a_{max} = \max_{t \in T} a_t$, then we have the following bound*

$$B - \overline{Reg}_T \leq 2b^2 a_{max} \log K. \tag{11}$$

It is evident that $a_{max} \leq d_{max}$, so the bound of Lemma 7 leads to $\mathcal{O}(d_{max} \log K)$ term in the regret bound.

Lemma 8 (Bound for $C - \overline{Reg}_T$)**.** *We have the following bound for $C - \overline{Reg}_T$*

$$C - \overline{Reg}_T \leq \sum_{i \neq i^*} \frac{8c^2 \sigma_{max}}{\Delta_i \log K}. \tag{12}$$

Part of the pseudo-regret bound that corresponds to Lemma 8, comes from the penalty term related to the negative entropy part of the regularizer. In this part, despite the fact that σ_{max} can be much smaller than d_{max} (Lemma 3), the $\sum_{i \neq i^*} \frac{\sigma_{max}}{\Delta_i \log K}$ term could be very large when suboptimal gaps are small. In Appendix E we show how having an asymmetric learning rate $\gamma_{t,i} \simeq \gamma_t / \sqrt{\Delta_i}$ for negative entropy regularizer allows to remove the factor $\sum_{i \neq i^*} 1/\Delta_i$ in front of σ_{max}.

Finally, by plugging (9),(10),(11),(12) into (8) we obtain the desired regret bound.

5.2 Adversarial Bound

For the adversarial regime we use the final bound of Zimmert and Seldin [2021], which holds for any non-increasing learning rates:

$$\overline{Reg}_T \leq \sum_{t=1}^{T} \eta_t \sqrt{K} + \sum_{t=1}^{T} \gamma_t \sigma_t + 2\eta_T^{-1} \sqrt{K} + \gamma_T^{-1} \log K.$$

It suffices to substitute the values of the learning rates and use Lemma 16 for function $\frac{1}{\sqrt{x}}$:

$$\overline{Reg}_T \leq \sum_{t=1}^{T} \frac{\sqrt{K}}{\sqrt{t + \eta_0}} + \sum_{t=1}^{T} \frac{\sigma_t \sqrt{\log K}}{\sqrt{D_t + \gamma_0}} + 2\sqrt{KT + K\eta_0} + \sqrt{\log(K)D_T + \gamma_0 \log(K)}$$

$$= \mathcal{O} \left(\sqrt{KT} + \sqrt{\log(K)D_T} + d_{max} K^{1/3} \log K \right).$$

6 Refined lower bound

In this section, we prove a tight lower bound for adversarial regret with arbitrary delays. Both Zimmert and Seldin [2020] and Thune et al. [2019] derived improved regret bounds when some delays are extremely large by skipping feedback that takes too long to arrive. It has been open ever since whether their bounds are tight. We answer this positively by showing that the regret bound of Zimmert and Seldin [2020] is not improvable without additional assumptions. We first derive a refined lower bound for full-information games with variable loss ranges, which might be of independent interest. A proof is provided in Appendix C.

Theorem 9. *Let $L_n \geq L_{n-1} \geq \cdots \geq L_1 \geq 0$ be a non-increasing sequence of positive reals and assume that there exists a permutation $\rho : [T] \to [T]$, such that the losses at time t are bounded in $[0, L_{\rho(t)}]^k$. The minimax regret of the adversarial full-information game is lower bounded by*

$$Reg^* = \max \left\{ \frac{1}{2} \sum_{t=1}^{\lfloor \log_2(k) \rfloor} L_t, \frac{1}{32} \sqrt{\sum_{t=\lfloor \log_2(k) \rfloor}^{n} L_t^2 \log(k)} \right\}.$$

From here we can directly show a lower bound for the full-information game with variable delays. This implies the same lower bound for bandits, since we have strictly less information available.

Corollary 10. *Let $(d_t)_{t=1}^T$ be a sequence of non-increasing delays, such that $d_t \leq T + 1 - t$ and let an oblivious adversary select all loss vectors $(\ell_t)_{t=1}^T$ in $[0,1]^K$ before the start of the game. The minimax regret of the full-information game is bounded from below by*

$$Reg^* = \Omega\left(\min_{S \subset [T]} |S| + \sqrt{D_{\bar{S}} \log(K)}\right), \text{ where } D_{\bar{S}} = \sum_{t \in [T] \setminus S} d_t.$$

Proof. We divide the time horizon greedily into M buckets, such that the actions for all timesteps inside a bucket have to be chosen before the first feedback from any timestep inside the bucket is received. In other words, let bucket $B_m = \{b_m, \ldots, b_{m+1} - 1\}$, then $\forall t \in B_m : t + d_t > b_{m+1} - 1$, while $\exists t \in B_m : t + d_t = b_{m+1}$. This division of buckets has the following properties:

 (i) monotonically decreasing sizes: $|B_1| \geq |B_2| \geq \cdots \geq |B_M|$.

 (ii) upper bound on the sum of delays: $\forall m \in [M-1] : |B_m|^2 \geq \sum_{t \in B_{m+1}} d_t$.

Both properties follow directly from the non-decreasing nature of the delays.
$$|B_m| = b_{m+1} - b_m \leq b_m + d_{b_m} - b_m = d_{b_m}$$
$$|B_m| = \min_{t \in B_m} \{d_t + t - b_m\} \geq d_{b_{m+1}-1} + \min_{t \in B_m} \{t - b_m\} = d_{b_{m+1}-1}.$$

Hence
$$|B_m| \geq d_{b_{m+1}-1} \geq d_{b_{m+1}} \geq |B_{m+1}|,$$
$$\sum_{t \in B_{m+1}} d_t \leq |B_{m+1}| \cdot d_{b_{m+1}} \leq |B_{m+1}| \cdot |B_m| \leq |B_m|^2.$$

Set $S' = \bigcup_{m=1}^{\lfloor \log_2(k) \rfloor} B_m$ and let the adversary set all losses within a bucket to the same value, then the game reduces to a full information game over M rounds with loss ranges $|B_1|, |B_2|, \ldots, |B_M|$. Applying Theorem 9 yields

$$Reg^* = \max\left\{ \frac{1}{2} \sum_{m=1}^{\lfloor \log_2(k) \rfloor} |B_m|, \frac{1}{32} \sqrt{\sum_{m=\lfloor \log_2(k) \rfloor}^{M} |B_m|^2 \log(k)} \right\}$$

$$\geq \max\left\{ \frac{1}{2} |S'|, \frac{1}{32} \sqrt{\sum_{t \in \bar{S}'} d_t \log(k)} \right\} = \Omega\left(\min_{S \subset [T]} |S| + \sqrt{\sum_{t \in \bar{S}} d_t \log(k)}\right). \blacksquare$$

7 Discussion

We have presented a best-of-both-worlds analysis of a slightly modified version of the algorithm of Zimmert and Seldin [2020] for bandits with delayed feedback. The key novelty of our analysis is the control of the drift of the playing distribution over arbitrary, but bounded, time intervals when the learning rate is changing over time. This control is necessary for best-of-both-worlds guarantees, but it is much more challenging than the drift control over fixed time intervals with fixed learning rate that appeared in prior work.

We also presented an adversarial regret lower bound matching the skipping-based refined regret upper bound of Zimmert and Seldin [2020] within constants.

Our work leads to several exciting open questions. The main one is whether skipping can be used to eliminate the need in oracle knowledge of d_{max}. If possible, this would remedy the deterioration of the adversarial bound by the additive factor of d_{max}, because the skipping threshold would be dominated by $\sqrt{D_{\bar{S}} \log K}$. Another open question is whether $\frac{\sigma_{max}}{\Delta_i}$ term can be eliminated from the stochastic bound. Yet another open question is whether the d_{max} factor in the stochastic bound can be reduced to σ_{max} and whether the multiplicative terms dependent on K can be eliminated.

References

Jacob D Abernethy, Chansoo Lee, and Ambuj Tewari. Fighting bandits with a new kind of smoothness. In *Advances in Neural Information Processing Systems (NeurIPS)*. 2015.

Peter Auer and Chao-Kai Chiang. An algorithm with nearly optimal pseudo-regret for both stochastic and adversarial bandits. In *Proceedings of the Conference on Learning Theory (COLT)*, 2016.

Peter Auer, Nicolò Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine Learning*, 47, 2002.

Peter Auer, Nicolò Cesa-Bianchi, Yoav Freund, and Robert E. Schapire. The nonstochastic multiarmed bandit problem. *SIAM Journal on Computing*, 32, 2002b.

Ilai Bistritz, Zhengyuan Zhou, Xi Chen, Nicholas Bambos, and Jose Blanchet. Online exp3 learning in adversarial bandits with delayed feedback. In *Advances in Neural Information Processing Systems*, 2019.

Sébastien Bubeck and Aleksandrs Slivkins. The best of both worlds: Stochastic and adversarial bandits. In *Proceedings of the Conference on Learning Theory (COLT)*, 2012.

Nicol'o Cesa-Bianchi, Claudio Gentile, Yishay Mansour, and Alberto Minora. Delay and cooperation in nonstochastic bandits. In *29th Annual Conference on Learning Theory*, 2016.

Shinji Ito. Parameter-free multi-armed bandit algorithms with hybrid data-dependent regret bounds. In *Proceedings of Thirty Fourth Conference on Learning Theory*, 2021.

Pooria Joulani, Andras Gyorgy, and Csaba Szepesvari. Online learning under delayed feedback. In *Proceedings of the 30th International Conference on Machine Learning*, 2013.

Tze Leung Lai and Herbert Robbins. Asymptotically efficient adaptive allocation rules. *Advances in Applied Mathematics*, 6, 1985.

Tor Lattimore and Csaba Szepesvári. *Bandit Algorithms*. Cambridge University Press, 2020.

Saeed Masoudian and Yevgeny Seldin. Improved analysis of the tsallis-inf algorithm in stochastically constrained adversarial bandits and stochastic bandits with adversarial corruptions. In *Proceedings of Thirty Fourth Conference on Learning Theory*, 2021.

Jaouad Mourtada and Stéphane Gaïffas. On the optimality of the hedge algorithm in the stochastic regime. *Journal of Machine Learning Research*, 20, 2019.

Herbert Robbins. Some aspects of the sequential design of experiments. *Bulletin of the American Mathematical Society*, 58, 1952.

Yevgeny Seldin and Gábor Lugosi. An improved parametrization and analysis of the EXP3++ algorithm for stochastic and adversarial bandits. In *Proceedings of the Conference on Learning Theory (COLT)*, 2017.

Yevgeny Seldin and Aleksandrs Slivkins. One practical algorithm for both stochastic and adversarial bandits. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2014.

William R. Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25, 1933.

Tobias Sommer Thune, Nicolò Cesa-Bianchi, and Yevgeny Seldin. Nonstochastic multiarmed bandits with unrestricted delays. In *Advances in Neural Information Processing Systems*, 2019.

Chen-Yu Wei and Haipeng Luo. More adaptive algorithms for adversarial bandits. In *Proceedings of the Conference on Learning Theory (COLT)*, 2018.

Julian Zimmert and Yevgeny Seldin. An optimal algorithm for stochastic and adversarial bandits. In *Proceedings on the International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2019.

Julian Zimmert and Yevgeny Seldin. An optimal algorithm for adversarial bandits with arbitrary delays. In *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, 2020.

Julian Zimmert and Yevgeny Seldin. Tsallis-INF: An optimal algorithm for stochastic and adversarial bandits. *Journal of Machine Learning Research*, 2021.