SHUFFLE PRIVATE STOCHASTIC CONVEX OPTIMIZATION

ABSTRACT

In shuffle privacy, each user sends a collection of randomized messages to a trusted shuffler, the shuffler randomly permutes these messages, and the resulting shuffled collection of messages must satisfy differential privacy. Prior work in this model has largely focused on protocols that use a single round of communication to compute algorithmic primitives like means, histograms, and counts. We present interactive shuffle protocols for stochastic convex optimization. Our protocols rely on a new noninteractive protocol for summing vectors of bounded ℓ_2 norm. By combining this sum subroutine with mini-batch stochastic gradient descent, accelerated gradient descent, and Nesterov's smoothing method, we obtain loss guarantees for a variety of convex loss functions that significantly improve on those of the local model and sometimes match those of the central model.

1 INTRODUCTION

In stochastic convex optimization, a learner receives a convex loss function $\ell \colon \Theta \times \mathcal{X} \to \mathbb{R}$ mapping pairs of parameters and data points to losses, and the goal is to use data samples $x_1, \ldots, x_n$ to find a parameter θ to minimize population loss $\mathbb{E}_{x \sim \mathcal{D}} \left[\ell(\theta, x) \right]$ over unknown data distribution $\mathcal{D}$. The general applicability of this framework has motivated a long line of work studying stochastic convex optimization problems under the constraint of differential privacy (Dwork et al., 2006), which guarantees that the solution found reveals little information about the data used during optimization.

This work has led to optimal guarantees for both the *central* (Bassily et al., 2013; 2019; Feldman et al., 2020) and *local* (Duchi et al., 2013) models of differential privacy. Central differential privacy guarantees privacy to users who trust an algorithm operator to collect, store, and use data as promised. This high degree of trust contrasts with that of the local model, where the algorithm operator only sees randomized messages published by users, and users need not trust an algorithm operator at all. Perhaps unsurprisingly, these different privacy protections lead to different utility guarantees: when optimizing from n samples over a d-dimensional parameter space with privacy parameter ε, $O\left(\frac{1}{\sqrt{n}} + \frac{\sqrt{d}}{\varepsilon n} \right)$ loss is optimal in the central model (Bassily et al., 2013; 2019; Feldman et al., 2020), while $O\left(\frac{1}{\sqrt{n}} + \frac{\sqrt{d}}{\varepsilon \sqrt{n}} \right)$ loss is optimal in the local model (Duchi et al., 2013).

A similar utility gap between central and local privacy also appears in many other problems (Kasiviswanathan et al., 2011; Chan et al., 2012; Duchi et al., 2013; Duchi and Rogers, 2019; Joseph et al., 2019). This has motivated the exploration of models achieving a finer trade-off between privacy and utility. One such notion of privacy is *shuffle privacy* (Cheu et al., 2019; Erlingsson et al., 2019). Here, users send randomized messages to a shuffler, which permutes the collection of messages before they are viewed by any other party. In conjunction with work on building shufflers via onion routing, multi-party computation, and secure computation enclaves, this simple model has led to a now-substantial body of work on shuffle privacy (Bittau et al., 2017; Cheu et al., 2019; Erlingsson et al., 2019; Balle et al., 2019; Ghazi et al., 2021; Balcer and Cheu, 2020; Feldman et al., 2021; Balcer et al., 2021), including steps toward real-world deployment (Google, 2021). However, comparatively little is known about shuffle private stochastic convex optimization.

1.1 OUR CONTRIBUTIONS

1. We introduce *sequentially interactive* (each user participates in a single protocol round) and *fully interactive* (each user participates in arbitrarily many protocol rounds) variants of the shuffle model of differential privacy[1]. This naturally captures real-world constraints that make it difficult to repeatedly query specific users.

2. We construct a noninteractive shuffle private protocol for privately computing a sum with bounded ℓ_2 sensitivity. By using multiple messages, our protocol is substantially more accurate than existing results (see Related Work).

3. We use our ℓ_2 summation protocol to derive several new shuffle private SCO guarantees (Table 1) via techniques including accelerated gradient descent, Nesterov's smoothing method in the sequential interactive model, and noisy gradient descent in the fully interactive model. We are not aware of previous private SCO results relying on acceleration, yet we found it to be necessary for our sequentially interactive protocols.

Loss Function	Sequential	Full
Convex	$O\left(\frac{d^{1/3}}{\varepsilon^{2/3}n^{2/3}}\right)$ (Thm. 4.7)	$O\left(\frac{\sqrt{d}}{\varepsilon n}\right)$ (Thm. 4.9)
Convex and smooth	$O\left(\frac{d^{2/5}}{\varepsilon^{4/5}n^{4/5}}\right)$ (Thm. 4.3)	
Strongly convex	$O\left(\frac{d^{2/3}}{\varepsilon^{4/3}n^{4/3}}\right)$ (Thm. 4.8)	$O\left(\frac{d}{\varepsilon^2 n^2}\right)$ (Thm. 4.9)
Strongly convex and smooth	$O\left(\frac{d}{\varepsilon^2 n^2}\right)$ (Thm. 4.8)	

Table 1: Summary of population loss guarantees by loss function and interactivity assumptions. d is the dimension of the parameter space Θ, ε is the privacy parameter, and n is the number of data points. For neatness, this table omits the non-private $1/\sqrt{n}$ term, logarithmic terms, and other parameters like Lipschitz constants, parameter space diameter, and smoothness. Full statements appear in the referenced theorems.

1.2 ADDITIONAL RELATED WORK

The vast majority of work on shuffle privacy studies the noninteractive model, but a few exceptions exist. Erlingsson et al. (2019) and Feldman et al. (2021) study a variant in which the shuffler is an interface controlling access to users: in each round, the analyzer passes a local randomizer to the shuffler, the shuffler passes it to a random user (sampled without replacement across rounds), and the shuffler passes the response back to the analyzer. Feldman et al. (2021) also construct a basic protocol for SGD in this model. Apart from its interactive nature, this model is similar to other work that achieves shuffle privacy guarantees by amplifying the local privacy guarantees of local randomizers (Balle et al., 2019). The main difference between that work and ours is that we only require that the view of the shuffled outputs across rounds satisfies differential privacy. As a result, we do not require each user to perform a locally private computation and can instead use a technique not captured by amplification lemmas.

Another exception is the work of Beimel et al. (2020). In their version of shuffle privacy, the shuffler broadcasts the permuted messages to all parties. This enables users to participate in key exchange protocols, and Beimel et al. show that a first round of key exchange enables the use of multi-party computation (MPC) to simulate an arbitrary centrally private algorithm in the second round. Our results depart from theirs in two ways. First, we only assume that the shuffler sends outputs to the analyzer, not to the individual users. Second, the MPC approach given by Beimel et al. requires an honest majority. Without an honest majority, the differential privacy guarantees of their simulation fail. In contrast, the privacy guarantees of our shuffle protocols degrade smoothly with the fraction of honest users, which we allow to be anything larger than an arbitrary constant (see discussion at the end of Section 3.1).

---

[1]These terms are borrowed from local differential privacy (Duchi et al., 2013; Joseph et al., 2019).

Simultaneous independent work by Tenenbaum et al. (2021) also studies a sequentially interactive variant of the shuffle model in the context of multi-arm bandits. Their model of sequential interactivity is identical to ours, albeit for a different problem.

Girgis et al. (2021) provide a fully interactive shuffle private protocol for empirical risk minimization (ERM). In contrast, we provide both sequentially and fully interactive protocols for SCO, which optimizes population rather than empirical loss. Their ℓ_2 summation protocol requires one message from each user, and its second moment guarantee for the average gradient has a $1/b$ dependence on batch size b (their Lemma 4). In contrast, our multi-message protocol obtains a better $1/b^2$ dependence. This is possible because our multi-message protocol does not rely on privacy amplification, and in particular circumvents their single-message lower bound (their Theorem 3).

Finally, several shuffle private protocols are known for the simpler problem of summing scalars (Cheu et al., 2019; Balle et al., 2019; Ghazi et al., 2019; Balcer and Cheu, 2020) and recent work has studied vector addition in the secure aggregation model (Kairouz et al., 2021), which assumes the existence of a trusted aggregator that can execute modular arithmetic on messages. We expand on this work by introducing a shuffle private protocol for summing vectors with bounded ℓ_2 norm, with noise standard deviation proportional to the ℓ_2 sensitivity.

2 Preliminaries

2.1 Differential Privacy

Throughout, let $\mathcal{X}$ be a data universe, and suppose that each of n users has a single data point from $\mathcal{X}$. Two datasets $X, X' \in \mathcal{X}^n$ are considered *neighbors*, denoted $X \sim X'$, if they differ in the value of at most one user. Differential privacy is defined with respect to neighboring databases.

Definition 2.1 (Dwork et al. (2006)). *An algorithm $\mathcal{A}$ satisfies (ε, δ)-differential privacy if, for every $X \sim X'$ and every event Z,*

$$\mathbb{P}_{\mathcal{A}}\left[\mathcal{A}(X) \in Z\right] \leq e^{\varepsilon} \cdot \mathbb{P}_{\mathcal{A}}\left[\mathcal{A}(X') \in Z\right] + \delta. \tag{1}$$

Note that the probability is only over the randomness of $\mathcal{A}$.

Because Definition 2.1 assumes that the algorithm $\mathcal{A}$ has "central" access to compute on the entire raw dataset, we call this *central privacy* for brevity. For brevity, we will often use differential privacy and DP P interchangeably. At times, it will also be useful to rephrase DP as a divergence constraint.

Definition 2.2. *The δ-Approximate Max Divergence between distributions X and Y is*

$$D_{\infty}^{\delta}(X||Y) = \max_{Z \subseteq \mathrm{supp}(X): \Pr[X \in Z] \geq \delta} \left[\log \frac{\Pr[X \in Z] - \delta}{\Pr[Y \in Z]} \right].$$

Fact 2.3. *Algorithm $\mathcal{A}$ is (ε, δ)-differentially private if and only if, for all $X \sim X'$, $D_{\infty}^{\delta}(\mathcal{A}(X)||\mathcal{A}(X')) \leq \varepsilon$.*

A key property of DP is closure under post-processing. Informally, this guarantees that a DP guarantee cannot be weakened after the fact.

Fact 2.4 (Proposition 2.1 (Dwork and Roth, 2014)). *Fix any function f. If $\mathcal{A}$ is (ε, δ)-differentially private, then the composition $f \circ \mathcal{A}$ is also (ε, δ)-differentially private.*

2.2 Shuffle Privacy

Central privacy offers a meaningful guarantee to users who trust the operator of the algorithm $\mathcal{A}$ to securely receive the data, execute $\mathcal{A}$, and store or delete the data afterward. This work primarily studies the shuffle model, which relaxes all of these assumptions.

In the shuffle model (Bittau et al., 2017; Cheu et al., 2019; Erlingsson et al., 2019), we do not require users to trust the operator of $\mathcal{A}$. Instead, we make the narrower assumption that there is a trusted *shuffler*: users pass messages to the shuffler, the shuffler permutes them, and the algorithm $\mathcal{A}$ operates on the resulting shuffled output. Shuffling thus adds another layer of user protection by decoupling messages from the users that sent them.

Definition 2.5. *A one-round shuffle protocol $\mathcal{P}$ is specified by a local randomizer $\mathcal{R} : \mathcal{X} \to \mathcal{Y}^*$ and analyzer $\mathcal{A} : \mathcal{Y}^* \to \mathcal{Z}$. In an execution of $\mathcal{P}$ on X, each user i computes $\mathcal{R}(X_i)$—possibly using public randomness—and sends the resulting messages $y_{i,1}, y_{i,2}, \ldots$ to the shuffler $\mathcal{S}$. $\mathcal{S}$ reports $\vec{y}$ to an analyzer, where $\vec{y}$ is a uniformly random permutation of all user messages. The final output of the protocol is $\mathcal{A}(\vec{y})$.*

We now define our privacy objective in the shuffle model, often shorthanded as "shuffle privacy".

Definition 2.6 (Cheu et al. (2019); Erlingsson et al. (2019)). *$\mathcal{P} = (\mathcal{R}, \mathcal{A})$ is (ε, δ)-shuffle differentially private if the algorithm $(\mathcal{S} \circ \mathcal{R}^n)(X) := \mathcal{S}(\mathcal{R}(X_1), \ldots, \mathcal{R}(X_n))$, i.e. the analyzer's view of the shuffled messages, is (ε, δ)-differentially private. The privacy guarantee is over the internal randomness of the users' randomizers and the shuffler itself and not the public randomness of the shuffle protocol.*

A drawback of the preceding definition of shuffle protocols is that it limits communication to one round. It is not possible, for example, to adjust the randomizer assigned to user i based on the messages reported from user $i - 1$. This is an obstacle to implementing intrinsically adaptive algorithms such as gradient descent. We therefore extend the shuffle model with the following *sequentially interactive* and *fully interactive* variants. Sequential interactivity breaks the data into batches and runs a different shuffle protocol on each batch. Crucially, the nature of each protocol may depend on the output generated by preceding protocols.

Definition 2.7. *Let Tr denote the universe of shuffle protocol transcripts, and let $\mathfrak{R}$ denote the universe of randomizers. A sequentially interactive shuffle protocol $\mathcal{P}$ consists of initial local randomizer $\mathcal{R}_0$, analyzer $\mathcal{A}$, and update function $U : \mathsf{Tr} \to [n] \times \mathfrak{R}$. Let Tr_t denote the transcript after t rounds of the protocol. In each round t of $\mathcal{P}$, the analyzer computes $(n_t, \mathcal{R}_t) = U(\mathsf{Tr}_{t-1})$, n_t new users apply $\mathcal{R}_t$ to their data points, and $\mathcal{S}$ shuffles the result and relays it back to $\mathcal{A}$. At the conclusion of a T-round protocol, the analyzer releases final output $\mathcal{A}(\mathsf{Tr}_T)$.*

Note that, in a sequentially interactive protocol, a single user only participates in a single computation. The natural next step is to generalize the model further and allow the analyzer to adaptively choose which subset of users to query, allowing the option for repeated querying of users. This leads us to the *fully interactive model*.

Definition 2.8. *A fully interactive shuffle protocol $\mathcal{P}$ is identical to a sequentially interactive shuffle protocol, except the update function $U : \mathsf{Tr} \to 2^{[n]} \times \mathfrak{R}$ selects an arbitrary subset of users in each round. In particular, a user may participate in multiple rounds.*

For sequentially and fully interactive shuffle protocols, the definition of privacy is identical: the view of the transcript satisfies DP. The noninteractive definition is a special case of this general definition.

Definition 2.9. *Given shuffle protocol $\mathcal{P}$, let $\mathcal{M}_{\mathcal{P}} : \mathcal{X}^* \to \mathsf{Tr}$ denote the central algorithm that simulates $\mathcal{P}$ on an input database and outputs the resulting transcript. Then $\mathcal{P}$ is (ε, δ)-shuffle differentially private if $\mathcal{M}_{\mathcal{P}}$ is (ε, δ)-differentially private.*

2.3 Stochastic Convex Optimization

Let closed convex $\Theta \subset \mathbb{R}^d$ with diameter D be our parameter space. We always assume loss functions $\ell(\theta, x)$ that are convex and L-Lipschitz in Θ.

Definition 2.10. *Loss function $\ell : \Theta \times \mathcal{X} \to \mathbb{R}$ is convex in Θ if, for all $x \in \mathcal{X}$, for all $t \in [0, 1]$ and $\theta, \theta' \in \Theta$, $\ell(t\theta + (1 - t)\theta', x) \leq t\ell(\theta, x) + (1 - t)\ell(\theta', x)$. ℓ is L-Lipschitz in Θ if for all $x \in \mathcal{X}$ and $\theta, \theta' \in \Theta$, $|\ell(\theta, x) - \ell(\theta', x)| \leq L\|\theta - \theta'\|_2$.*

In some cases, we also assume that our loss function ℓ is β-smooth and/or λ-strongly convex.

Definition 2.11. *Loss function $\ell : \Theta \times \mathcal{X} \to \mathbb{R}$ is β-smooth over Θ if, for every $x \in \mathcal{X}$ and for every $\theta, \theta' \in \Theta$, $\|\nabla\ell(\theta, x) - \nabla\ell(\theta', x)\|_2 \leq \beta\|\theta - \theta'\|_2$. ℓ is λ-strongly convex in Θ if, for all $x \in \mathcal{X}$, for all $t \in [0, 1]$ and $\theta, \theta' \in \Theta$, $\ell(t\theta + (1 - t)\theta', x) \leq t\ell(\theta, x) + (1 - t)\ell(\theta', x) - \frac{\lambda t(1 - t)}{2}\|\theta - \theta'\|_2^2$.*

Our goal is to minimize population loss. We will view each user as a sample from $\mathcal{D}$, and our protocols will learn from these samples through repeated interaction with the shuffler rather than direct access to the samples.

Definition 2.12. *Let $\mathcal{D}$ be a distribution over $\mathcal{X}$, and let $\ell : \Theta \times \mathcal{X} \to \mathbb{R}$ be a loss function. Then algorithm $\mathcal{A} : \mathcal{X}^* \to \Theta$ has* population loss *$\mathbb{E}_{\mathcal{A}, \mathcal{D}}\left[\ell(\bar{\theta}, \mathcal{D})\right] = \mathbb{E}_{\theta \sim \mathcal{A}(\mathcal{D}^n)}\left[\mathbb{E}_{x \sim \mathcal{D}}\left[\ell(\theta, x)\right]\right]$.*

3 VECTOR SUMMATION

In this section, we provide a shuffle private protocol $\mathcal{P}_{\text{VEC}}$ for summing vectors of bounded ℓ_2 norm. This contrasts with existing work, which focuses on ℓ_1 sensitivity. $\mathcal{P}_{\text{VEC}}$ will be useful for the gradient descent steps of our algorithms in Section 4. $\mathcal{P}_{\text{VEC}}$ relies on d invocations of a scalar sum protocol $\mathcal{P}_{\text{1D}}$, one for each dimension. We describe this scalar summation subroutine in Section 3.1, then apply it to vector summation in Section 3.2. Proofs for results in this section appear in Appendix A

3.1 SCALAR SUM SUBROUTINE

We start with the pseudocode for $\mathcal{P}_{\text{1D}}$, a shuffle protocol for summing scalars. As is generally the case for shuffle protocols, the overall protocol decomposes $\mathcal{P}_{\text{1D}} = (\mathcal{R}_{\text{1D}}, \mathcal{A}_{\text{1D}})$ into randomizer and analyzer components: each user i computes a collection of messages $\vec{y}_i \sim \mathcal{R}_{\text{1D}}(x_i)$, the shuffler $\mathcal{S}$ aggregates and permutes these messages, and the analyzer takes the result as input for its final analysis $\mathcal{A}_{\text{1D}}(\mathcal{S}(\vec{y}))$. $\mathcal{P}_{\text{1D}}$ uses the fixed-point encoding presented by Cheu et al. (2019) and ensures privacy using a generalization of work by Balcer and Cheu (2020).

Algorithm 1 $\mathcal{P}_{\text{1D}}$, a shuffle protocol for summing scalars

---

1: **Parameters:** Scalar database $X = (x_1, \ldots, x_n) \in [0, \Delta]^n$; $g, b \in \mathbb{N}$; $p \in (0, 1/2)$
2: **procedure** LOCAL RANDOMIZER $\mathcal{R}_{\text{1D}}(x)$
3:      Set $\overline{x} \leftarrow \lfloor xg/\Delta \rfloor$
4:      Sample rounding value $\eta_1 \sim \mathbf{Ber}(xg/\Delta - \overline{x})$
5:      Set $\hat{x} \leftarrow \overline{x} + \eta_1$
6:      Sample privacy noise value $\eta_2 \sim \mathbf{Bin}(b, p)$
7:      Report $\hat{x} + \eta_2$ copies of 1 and $g + b - (\hat{x} + \eta_2)$ copies of 0
8: **end procedure**
9: **procedure** ANALYZER $\mathcal{A}_{\text{1D}}(\mathcal{S}(\vec{y}))$
10:      Report estimator $\frac{\Delta}{g}\left(\left(\sum_{i=1}^{(g+b)n} y_i\right) - pbn\right)$
11: **end procedure**

$\mathcal{P}_{\text{1D}}$'s privacy guarantee is instance-specific: for every pair of inputs, we bound the approximate max-divergence between output distributions as a function of the change in inputs. Previously proposed by Chatzikokolakis et al. (2013), this property will be essential when proving that $\mathcal{P}_{\text{VEC}}$ is private.

Lemma 3.1. *Fix any number of users n, $\varepsilon \leq 1$, and $0 < \delta < 1$. Let $g \geq \Delta\sqrt{n}$, $b > \frac{180g^2 \ln(2/\delta)}{\varepsilon^2 n}$, and $p = \frac{90g^2 \ln(2/\delta)}{b\varepsilon^2 n}$. Then 1) for any neighboring databases $X \sim X' \in [0, \Delta]^n$ that differ on user u, $D_\infty^\delta((\mathcal{S} \circ \mathcal{R}_{\text{1D}}^n)(X) \| (\mathcal{S} \circ \mathcal{R}_{\text{1D}}^n)(X')) \leq \varepsilon \cdot \left(\frac{2}{g} + \frac{|x_u - x'_u|}{\Delta}\right)$, and 2) for any input database $X \in [0, \Delta]^n$, $\mathcal{P}_{\text{1D}}(X)$ is an unbiased estimate of $\sum_{i=1}^n x_i$ and has variance $O(\frac{\Delta^2}{\varepsilon^2} \log \frac{1}{\delta})$.*

We defer the proof to Appendix A. Claim 1 follows first from the observation that the adversary's view is equivalent to the sum of the message bits. This sum has binomial noise, so we then adapt relevant work from Ghazi et al. (2021). Claim 2 follows as a straightforward calculation.

Lemma 3.1 holds when all n users follow the protocol. We call these users *honest*. It is possible to prove a more general version of Lemma 3.1 whose parameters smoothly degrade with the fraction of honest users (see Appendix A.3). This *robust* variant of shuffle privacy was originally defined in work by Balcer et al. (2021) and naturally extends to $\mathcal{P}_{\text{VEC}}$.

The remaining analysis will use $\mathcal{P}_{\text{1D}}$ in a black-box manner. It is therefore possible to replace it with a more communication-efficient subroutine for scalar summation (Balle et al., 2019). However, this improved communication requires a more complicated protocol, with its own additional subroutine. Our work focuses on sample complexity guarantees, so we use $\mathcal{P}_{\text{1D}}$ for clarity.

3.2 VECTOR SUM

Below, we present the pseudocode for $\mathcal{P}_{\text{VEC}}$, again decomposing into randomizer and analyzer components. Note that we view the vector $\vec{y}$ to be the collection of all shuffled messages and, since

the randomizers labels these messages by coordinate, $\vec{y}_j$ consists of the messages labelled j. The accompanying guarantee for $\mathcal{P}_{\text{VEC}}$ appears in Theorem 3.2.

Algorithm 2 $\mathcal{P}_{\text{VEC}}$, a shuffle protocol for vector summation

---

1: **Input:** database of d-dimensional vectors $\vec{X} = (\vec{x}_1, \cdots, \vec{x}_n)$; privacy parameters $\varepsilon, \delta; \Delta_2$.
2: **procedure** LOCAL RANDOMIZER $\mathcal{R}_{\text{VEC}}(\vec{x}_i)$
3:     **for** coordinate $j \in [d]$ **do**
4:         Shift data to enforce non-negativity: $\vec{w}_{i,j} \leftarrow \vec{x}_{i,j} + (\Delta_2, \ldots, \Delta_2)$
5:         $\vec{m}_j \leftarrow \mathcal{R}_{\text{1D}}(\vec{w}_{i,j})$
6:     **end for**
7:     Output labeled messages $\{(j, \vec{m}_j)\}_{j \in [d]}$
8: **end procedure**
9: **procedure** ANALYZER $\mathcal{A}_{\text{VEC}}(\vec{y})$
10:     **for** coordinate $j \in [d]$ **do**
11:         Run analyzer on j's messages $z_j \leftarrow \mathcal{A}_{\text{1D}}(j, \vec{y}_j)$
12:         Re-center: $o_j \leftarrow z_j - \Delta_2$
13:     **end for**
14:     Output the vector of estimates $\vec{o}$
15: **end procedure**

Theorem 3.2. *For any $0 < \varepsilon \leq 1$, $0 < \delta < 1$, $d, n \in \mathbb{N}$, and $\Delta_2 > 0$, there are choices of parameters $b, g \in \mathbb{N}$ and $p \in (0, 1/2)$ for $\mathcal{P}_{\text{1D}}$ (Algorithm 3.1) such that, for inputs $\vec{X} = (\vec{x}_1, \ldots, \vec{x}_n)$ of vectors with maximum norm $\|\vec{x}_i\|_2 \leq \Delta_2$, 1) $\mathcal{P}_{\text{VEC}}$ is (ε, δ)-shuffle private and, 2) $\mathcal{P}_{\text{VEC}}(\vec{X})$ is an unbiased estimate of $\sum_{i=1}^n \vec{x}_i$ and has bounded variance*

$$\mathbb{E}\left[\left\|\mathcal{P}_{\text{VEC}}(\vec{X}) - \sum_{i=1}^n \vec{x}_i\right\|_2^2\right] = O\left(\frac{d\Delta_2^2}{\varepsilon^2} \log^2 \frac{d}{\delta}\right).$$

The proof relies on the following variant of advanced composition.

Lemma 3.3. *Fix $\gamma \in (0, 1)$. For all $j \in [d]$, suppose algorithm $\mathcal{A}_j : \mathcal{X}^n \to \mathcal{Y}$ uses independent random bits and satisfies $D_\infty^{\delta_j}(\mathcal{A}_j(X) \| \mathcal{A}_j(X')) \leq \varepsilon_j$ on all neighboring datasets $X, X' \subseteq \mathcal{X}^n$. Let*

$$\varepsilon' = \sum_{j=1}^d \varepsilon_j(e^{\varepsilon_j} - 1) + 2\sqrt{\log(1/\gamma) \sum_{j=1}^d \varepsilon_j^2} \quad \text{and} \quad \delta' = \sum_{j=1}^d \delta_j + \gamma.$$

Then $D_\infty^{\delta'}(\mathcal{A}_1(X), \ldots, \mathcal{A}_d(X) \| \mathcal{A}_1(X') \ldots, \mathcal{A}_d(X')) \leq \varepsilon'$.

We also defer the proof of Theorem 3.2 to Appendix A but sketch the outline here. For any neighboring pair of datasets, the j-th invocation of $\mathcal{P}_{\text{1D}}$ by $\mathcal{P}_{\text{VEC}}$ produces one of two message distributions such that the divergence between them is roughly proportional to the gap in the j-th coordinate of the input. This is immediate from Lemma 3.1. The fact that we know a bound on sensitivity allows us to bound the (squared) ℓ_2 norm of the vector of divergences. This norm is implicit within Lemma 3.3, so the target theorem follows by re-scaling of parameters and substitution.

4 CONVEX OPTIMIZATION

We now apply $\mathcal{P}_{\text{VEC}}$ to convex optimization. Section 4.1 describes shuffle protocols that are sequentially interactive and solicit one input from each user.[2] Section 4.2 offers stronger utility guarantees via fully interactive protocols that query users multiple times. Complete proofs of all results in this section appear in Appendix B.

---

[2]Since sequentially interactive protocols process data online, our sequentially interactive shuffle protocols also have straightforward *pan-private* (Dwork et al., 2010) analogues with the same guarantees; see Appendix C for details.

4.1 SEQUENTIALLY INTERACTIVE PROTOCOLS

Our first sequentially interactive protocol is a simple instantiation of noisy mini-batch SGD, $\mathcal{P}_{\text{SGD}}$. This baseline algorithm achieves population loss $O\left(\frac{d^{1/4}}{\sqrt{n}}\right)$ (Theorem 4.1), which already improves on the locally private guarantee. However, in a departure from the central and local models, we then show that a still better $O\left(\frac{d^{1/3}}{n^{2/3}}\right)$ loss guarantee is possible (Theorem 4.7) using a more complex algorithm $\mathcal{P}_{\text{AGD}}$ that smooths the loss function and employs accelerated SGD.

Convex ℓ We start with $\mathcal{P}_{\text{SGD}}$. Because $\mathcal{P}_{\text{SGD}}$ is sequentially interactive, for a fixed number of users n, the batch size b is inversely proportional to the number of iterations T. As a result, Theorem 4.1 chooses b to balance the noise added to each gradient step (which decreases with b) with the number of steps taken (which also decreases with b).

Algorithm 3 $\mathcal{P}_{\text{SGD}}$, Sequentially interactive shuffle private SGD

Require: Number of users n, batch size b, privacy parameter ε, δ, step size η, Lipschitz parameter L
1: Initialize parameter estimate $\theta_0 \in \Theta$, and set number of iterations $T = n/b$
2: **for** $t = 1, 2, \ldots, T$ **do**
3:     Compute gradient at θ_{t-1}, $\bar{g}_t \leftarrow \frac{1}{b}\mathcal{P}_{\text{VEC}}\left(\nabla_\theta \ell(\theta_{t-1}, x_{t,1}), \cdots, \nabla_\theta \ell(\theta_{t-1}, x_{t,b}); \varepsilon, \delta, L\right)$
4:     Update parameter estimate $\theta_t \leftarrow \pi_\Theta\left(\theta_{t-1} + \eta\bar{g}_t\right)$
5: **end for**
6: Output $\frac{1}{T}\sum_{t=0}^{T-1}\theta_t$

Theorem 4.1. *Let loss function ℓ be convex, L-Lipschitz over a closed convex set $\Theta \subset \mathbb{R}^d$ of diameter D, $\bar{\theta} = \frac{1}{T}\sum_{t=0}^{T-1}\theta_t$, $b = \frac{\sqrt{d}\log(d/\delta)}{\varepsilon}$, $T = n/b$, and $\eta = \frac{\varepsilon b D}{L\sqrt{T}(\varepsilon b + \sqrt{d}L\log(d/\delta))}$. Then $\mathcal{P}_{\text{SGD}}$ is (ε, δ)-shuffle private and has population loss*

$$\mathbb{E}_{\mathcal{P}_{\text{SGD}}, \mathcal{D}}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{d^{1/4}DL\log^{1/2}(d/\delta)}{\sqrt{\varepsilon}n}\right).$$

Privacy—for $\mathcal{P}_{\text{SGD}}$ and our other protocols, which all rely on $\mathcal{P}_{\text{VEC}}$—follows from the fact that the L-Lipschitz assumption ensures that a loss gradient has ℓ_2 norm at most L. The utility proof proceeds by viewing each noisy gradient step as a call to a noisy gradient oracle. This enables us to use a standard result for gradient oracle SGD.

Lemma 4.2 (Bubeck et al. (2015)). *Suppose $\mathcal{P}_{\text{SGD}}$ queries an L_G-noisy gradient oracle at each iteration, then its output satisfies*

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + \frac{D^2}{2\eta T} + \frac{\eta L_G^2}{2}.$$

In our case, we can bound the noise level L_G as a function of our problem and privacy parameters, including the batch size. We then choose the batch size to minimize the overall loss guarantee.

Convex and smooth ℓ Next, we obtain a better loss guarantee when the loss function is also smooth. The key insight is that by using acceleration, a better trade-off between noise level and number of iterations is possible. The resulting algorithm, $\mathcal{P}_{\text{AGD}}$, can be seen as a private version of the accelerated stochastic approximation algorithm (AC-SA) of Lan (2012).

Theorem 4.3. *Let ℓ be convex, β-smooth, and L-Lipschitz over closed convex set $\Theta \subset \mathbb{R}^d$ of diameter D. Denote $\bar{\theta} = \theta_{t+1}^{\text{ag}}$. Let batch size $b = \frac{n^{3/5}d^{1/5}L^{2/5}\log^{2/5}(d/\delta)}{\varepsilon^{2/5}\beta^{2/5}D^{2/5}}$ and $L_t = \frac{1}{t+1}((T+2)^{3/2}\frac{\sigma}{D} + \beta)$, $\alpha_t = \frac{2}{t+2}$. Then $\mathcal{P}_{\text{AGD}}$ is (ε, δ)-shuffle private with population loss*

$$\mathbb{E}_{\mathcal{P}_{\text{AGD}}, \mathcal{D}}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{DL}{\sqrt{n}} + \frac{d^{2/5}\beta^{1/5}D^{6/5}L^{4/5}\log^{4/5}(d/\delta)}{\varepsilon^{4/5}n^{4/5}}\right).$$

The proof of Theorem 4.3 is similar to that of Theorem 4.1. The main difference is that we rely on an oracle utility guarantee that is specific to accelerated gradient descent:

Algorithm 4 $\mathcal{P}_{\mathrm{AGD}}$, Sequentially interactive shuffle private AC-SA

Require: Number of users n, batch size b, privacy parameters ε, δ, Lipchitz parameter L, learning rate sequence $\{L_t\}, \{\alpha_t\}$
1: Initialize parameter estimate $\theta_1^{\mathsf{ag}} = \theta_1 \in \Theta$, and set number of iterations $T = \lfloor n/b \rfloor$
2: **for** $t = 1, 2, \dots, T$ **do**
3:     Update middle parameter estimate $\theta_t^{\mathsf{md}} \leftarrow \alpha_t \theta_t + (1 - \alpha_t)\theta_t^{\mathsf{ag}}$.
4:     Estimate gradient at θ_t^{md}, $\bar{g}_t \leftarrow \frac{1}{b}\mathcal{P}_{\mathrm{VEC}}\left(\nabla_\theta \ell(\theta_t^{\mathsf{md}}, x_{t,1}), \cdots, \nabla_\theta \ell(\theta_t^{\mathsf{md}}, x_{t,b}); \varepsilon, \delta, L\right)$
5:     Update parameter estimate $\theta_{t+1} \leftarrow \arg\min_{\theta \in \Theta}\left\{\langle \bar{g}_t, \theta - \theta_t \rangle + \frac{L_t}{2}\|\theta - \theta_t\|_2^2\right\}$
6:     Update aggregated parameter estimate $\theta_{t+1}^{\mathsf{ag}} \leftarrow \alpha_t \theta_{t+1} + (1 - \alpha_t)\theta_t^{\mathsf{ag}}$
7: **end for**
8: Output $\theta_{T+1}^{\mathsf{ag}}$

Lemma 4.4 (Theorem 2 (Lan, 2012)). *Suppose $\mathcal{P}_{\mathrm{AGD}}$ receives a noisy gradient oracle with variance (at most) σ in each iteration. Taking $L_t = \frac{1}{t+1}((T+2)^{3/2}\frac{\sigma}{D} + \beta), \alpha_t = \frac{2}{t+2}$, then the expected error of $\mathcal{P}_{\mathrm{AGD}}$ can be bounded as*

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{\beta D^2}{T^2} + \frac{D\sigma}{\sqrt{T}}\right).$$

Smoothing for convex non-smooth ℓ Perhaps surprisingly, when the target loss function is convex and non-smooth, the SGD approach of algorithm $\mathcal{P}_{\mathrm{SGD}}$ is suboptimal. We improve the convergence rate by combining the accelerated gradient descent method $\mathcal{P}_{\mathrm{AGD}}$ with Nesterov's smoothing technique. In particular, for a non-smooth loss function, we approximate it with a smooth function by exploiting Moreau-Yosida regularization. We then optimize the smooth function via $\mathcal{P}_{\mathrm{AGD}}$. This is not the first application of Moreau-Yosida regularization in the private optimization literature (Bassily et al., 2019), but we depart from past work by combining it with acceleration to attain a better guarantee. We start by recalling the notion of the β-Moreau envelope, using the language of Bassily et al. (2019).

Definition 4.5. *For $\beta > 0$ and convex $f: \theta \to \mathbb{R}^d$, the β-Moreau envelope $f_\beta: \theta \to \mathbb{R}^d$ of f is*

$$f_\beta(\theta) = \min_{\theta' \in \Theta}\left(f(\theta') + \frac{\beta}{2}\|\theta - \theta'\|_2^2\right).$$

The following properties of the β-Moreau envelope will be useful.

Lemma 4.6 (Nesterov (2005)). *Let $f: \theta \to \mathbb{R}^d$ be a convex function, and define the proximal operator $\mathsf{prox}_f(\theta) = \arg\min_{\theta' \in \Theta}\left(f(\theta') + \frac{1}{2}\|\theta - \theta'\|_2^2\right)$. For $\beta > 0$:*

1. *f_β is convex, $2L$-Lipschitz and β-smooth.*

2. *$\forall \theta \in \Theta$, $\nabla f_\beta(\theta) = \beta(\theta - \mathsf{prox}_{f/\beta}(\theta))$.*

3. *$\forall \theta \in \Theta$, $f_\beta(\theta) \leq f(\theta) \leq f_\beta(\theta) + \frac{L^2}{2\beta}$.*

Informally, we use Lemma 4.6 as follows. First, claim 1 enables us to optimize f_β using $\mathcal{P}_{\mathrm{AGD}}$. Inside $\mathcal{P}_{\mathrm{AGD}}$, we use claim 2 to compute the desired gradients of f_β and obtain a loss guarantee for f_β using Theorem 4.3. Finally, claim 3 bounds the change in loss between f_β and the true function f as a function of β. We then choose β to minimize the overall loss guarantee.

Theorem 4.7. *Let ℓ be convex and L-Lipschitz over a closed convex set $\Theta \subset \mathbb{R}^d$ of diameter D. Combining $\mathcal{P}_{\mathrm{AGD}}$ with the above smoothing method yields an (ε, δ)-shuffle private algorithm with population loss*

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{DL}{\sqrt{n}} + \frac{d^{1/3}DL\log^{2/3}(d/\delta)}{\varepsilon^{2/3}n^{2/3}}\right).$$

Strongly convex function When the function is strongly convex, we use a folklore reduction from the convex setting: start from arbitrary point $\theta_0 \in \Theta$, and apply a convex optimization algorithm

$k = O(\log \log n)$ times, where the j-th ($j \in [k]$) application uses the output from previous phase as the initial point and $n_j = n/k$ samples. In the strongly convex but possibly non-smooth case, we apply the smoothing version of $\mathcal{P}_{\text{AGD}}$ used in Theorem 4.7. In the strongly convex and smooth case, we apply the version of $\mathcal{P}_{\text{AGD}}$ used in Theorem 4.3. A similar approach appears in the work of Feldman et al. (2020); the adaptation for our setting requires, among other modifications, a more careful analysis of the optimization trajectory.

Theorem 4.8. *Let ℓ be λ-strongly convex and L-Lipschitz over a closed convex set $\Theta \subset \mathbb{R}^d$ of diameter D. Combining $\mathcal{P}_{\text{AGD}}$ with the reduction above yields an (ε, δ)-shuffle private algorithm with population loss*

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + \tilde{O}\left(\frac{L^2}{\lambda n} + \frac{d^{2/3} L^2 \log^{4/3}(d/\delta)}{\lambda \varepsilon^{4/3} n^{4/3}}\right).$$

If the loss function is also β-smooth, then the population loss can be improved to

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + \tilde{O}\left(\frac{L^2}{\lambda n} + \frac{d\beta^{1/2} L^2 \log^2(d/\delta)}{\lambda^{3/2} \varepsilon^2 n^2}\right).$$

4.2 Fully Interactive Protocol

We conclude with fully interactive protocols, which allow a user to participate in multiple shuffles. In this expanded setting, a version of $\mathcal{P}_{\text{SGD}}$ obtains loss guarantees that match those of the *central* model of DP, up to logarithmic factors. The pseudocode of our protocol $\mathcal{P}_{\text{GD}}$ is shown in Algorithm 5. For strongly convex functions, we further divide users into disjoint groups and apply a fully interactive protocol $\mathcal{P}_{\text{GD}}$ to each group in sequence, using the parameter estimate learned from one group as the initial parameter estimate for the next.

Algorithm 5 $\mathcal{P}_{\text{GD}}$, Fully interactive shuffle private gradient descent

---

Require: Number of users n, privacy parameters ε, δ, Lipschitz parameter L, number of iterations T, step size η
  1: Initialize parameter estimate $\theta_0 \leftarrow 0$
  2: **for** $t = 1, 2, \ldots, T$ **do**
  3:    Compute the gradient at θ_t,

$$\bar{g}_t \leftarrow \frac{1}{n} \mathcal{P}_{\text{VEC}}\left(\nabla_\theta \ell(\theta_t, x_1), \cdots, \nabla_\theta \ell(\theta_t, x_n); \frac{\varepsilon}{\sqrt{T \log(1/\delta)}}, \frac{\delta}{T+1}, L\right)$$

  4:    Compute and store the parameter $\theta_{t+1} \leftarrow \pi_\Theta(\theta_t + \eta \bar{g}_t)$
  5: **end for**
  6: Output final estimate $\bar{\theta} \leftarrow \frac{1}{T} \sum_{t=0}^{T-1} \theta_t$

Theorem 4.9. *Let ℓ be convex and L-Lipschitz over a closed convex set $\Theta \subset \mathbb{R}^d$ of diameter D. Then the protocol $\mathcal{P}_{\text{GD}}$ is (ε, δ)-shuffle private with population loss*

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{DL}{\sqrt{n}} + \frac{d^{1/2} DL \log^{3/2}(d/\delta)}{\varepsilon n}\right).$$

If ℓ is λ-strongly convex, we can further improve the population loss to

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{L^2}{\lambda n} + \frac{d L^2 \log^3(d/\delta)}{\varepsilon^2 n^2}\right).$$

Details appear at the end of Appendix B; since the algorithm and analysis combines previously-discussed components, we sketch them here. The analysis employs the same Moreau envelope approach used in Theorem 4.7. However, unlike in the analysis of Theorem 4.7, we no longer require acceleration. Advanced composition and an appropriate setting of the parameters completes the result. For strongly convex function, we need to further split users into $\log \log n$ disjoint groups and apply $\mathcal{P}_{\text{GD}}$ to these disjoint groups of users in sequence.

REFERENCES

Kareem Amin, Matthew Joseph, and Jieming Mao. Pan-private uniformity testing. In *Conference on Learning Theory (COLT)*, 2020.

Victor Balcer and Albert Cheu. Separating local & shuffled differential privacy via histograms. In *Information-Theoretic Cryptography (ITC) 2020*, 2020.

Victor Balcer, Albert Cheu, Matthew Joseph, and Jieming Mao. Connecting robust shuffle privacy and pan-privacy. In *Symposium on Discrete Algorithms (SODA)*, 2021.

Borja Balle, James Bell, Adrià Gascón, and Kobbi Nissim. Differentially private summation with multi-message shuffling. *Arxiv*, abs/1906.09116, 2019.

Raef Bassily, Adam Smith, and Abhradeep Thakurta. Private empirical risk minimization: Efficient algorithms and tight error bounds. In *Foundations of Computer Science (FOCS)*, 2013.

Raef Bassily, Vitaly Feldman, Kunal Talwar, and Abhradeep Guha Thakurta. Private stochastic convex optimization with optimal rates. In *Neural Information Processing Systems (NeurIPS)*, 2019.

Amos Beimel, Iftach Haitner, Kobbi Nissim, and Uri Stemmer. On the round complexity of the shuffle model. In Rafael Pass and Krzysztof Pietrzak, editors, *Theory of Cryptography Conference (TCC)*, 2020.

Andrea Bittau, Úlfar Erlingsson, Petros Maniatis, Ilya Mironov, Ananth Raghunathan, David Lie, Mitch Rudominer, Ushasree Kode, Julien Tinnes, and Bernhard Seefeld. Prochlo: Strong privacy for analytics in the crowd. In *Symposium on Operating Systems Principles (SOSP)*, 2017.

Sébastien Bubeck et al. Convex optimization: Algorithms and complexity. *Foundations and Trends® in Machine Learning*, 2015.

TH Hubert Chan, Elaine Shi, and Dawn Song. Optimal lower bound for differentially private multi-party aggregation. In *European Symposium on Algorithms (ESA)*, 2012.

Konstantinos Chatzikokolakis, Miguel E. Andrés, Nicolás Emilio Bordenabe, and Catuscia Palamidessi. Broadening the scope of differential privacy using metrics. In *Privacy Enhancing Technologies Symposium (PETS)*, 2013.

Albert Cheu, Adam Smith, Jonathan Ullman, David Zeber, and Maxim Zhilyaev. Distributed differential privacy via shuffling. In *Conference on the Theory and Applications of Cryptographic Techniques (EUROCRYPT)*, 2019.

John Duchi and Ryan Rogers. Lower bounds for locally private estimation via communication complexity. In *Conference on Learning Theory (COLT)*, 2019.

John C. Duchi, Michael I. Jordan, and Martin J. Wainwright. Local privacy and statistical minimax rates. In *Foundations of Computer Science (FOCS)*, 2013.

Cynthia Dwork and Aaron Roth. The algorithmic foundations of differential privacy. *Foundations and Trends® in Theoretical Computer Science*, 2014.

Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of Cryptography Conference (TCC)*, 2006.

Cynthia Dwork, Moni Naor, Toniann Pitassi, Guy N Rothblum, and Sergey Yekhanin. Pan-private streaming algorithms. In *Innovations in Computer Science (ICS)*, 2010.

Úlfar Erlingsson, Vitaly Feldman, Ilya Mironov, Ananth Raghunathan, Kunal Talwar, and Abhradeep Thakurta. Amplification by shuffling: From local to central differential privacy via anonymity. In *Symposium on Discrete Algorithms (SODA)*, 2019.

Vitaly Feldman, Tomer Koren, and Kunal Talwar. Private stochastic convex optimization: Optimal rates in linear time. In *Symposium on the Theory of Computing (STOC)*, 2020.

Vitaly Feldman, Audra McMillan, and Kunal Talwar. Hiding among the clones: A simple and nearly optimal analysis of privacy amplification by shuffling. In *Symposium on the Foundations of Computer Science (FOCS)*, 2021.

Badih Ghazi, Rasmus Pagh, and Ameya Velingker. Scalable and differentially private distributed aggregation in the shuffled model. abs/1906.08320, 2019.

Badih Ghazi, Noah Golowich, Ravi Kumar, Rasmus Pagh, and Ameya Velingker. On the power of multiple anonymous messages. In *Conference on the Theory and Applications of Cryptographic Techniques (EUROCRYPT)*, 2021.

Antonious Girgis, Deepesh Data, Suhas Diggavi, Peter Kairouz, and Ananda Theertha Suresh. Shuffled model of differential privacy in federated learning. In *Artificial Intelligence and Statistics (AISTATS)*, 2021.

Google. Cobalt: Telemetry with built-in privacy. `https://fuchsia.googlesource.com/cobalt`, 2021. Accessed: 05-21-2021.

Matthew Joseph, Jieming Mao, Seth Neel, and Aaron Roth. The role of interactivity in local differential privacy. In *Symposium on the Foundations of Computer Science (FOCS)*, 2019.

Peter Kairouz, Ziyu Liu, and Thomas Steinke. The distributed discrete gaussian mechanism for federated learning with secure aggregation. In *International Conference on Machine Learning (ICML)*, 2021.

Shiva Prasad Kasiviswanathan, Homin K Lee, Kobbi Nissim, Sofya Raskhodnikova, and Adam Smith. What can we learn privately? *SIAM Journal on Computing*, 2011.

Guanghui Lan. An optimal method for stochastic composite optimization. *Mathematical Programming*, 2012.

Yu Nesterov. Smooth minimization of non-smooth functions. *Mathematical Programming*, 2005.

Jay Tenenbaum, Haim Kaplan, Yishay Mansour, and Uri Stemmer. Differentially private multi-armed bandits in the shuffle model. *arXiv preprint arXiv:2106.02900*, 2021.

A   PROOFS FOR SUM

The goal of this section is to prove Lemma 3.1 and Theorem 3.2.

A.1   PROOFS FOR SCALAR SUM

We first state a technical lemma that follows from a mild modification of the analysis done by Ghazi et al. (2021).

Lemma A.1. *For any function $f : \mathcal{X}^n \to \mathbb{Z}$ and parameters $p \in (0, 1/2]$ and $m \in \mathbb{N}$, let $M_{m,p,f} : \mathcal{X}^n \to \mathbb{Z}$ be the algorithm that samples $\eta \sim \mathbf{Bin}(m, p)$ and returns $f(X) + \eta$. For any $t \in \mathbb{N}$, $X \sim X'$ such that $|f(X) - f(X')| \leq t$, and $\alpha \in (0, 1)$ where $\alpha m p \geq 2t$,*

$$D_\infty^\delta(M_{m,p,f}(X) \| M_{m,p,f}(X')) \leq \varepsilon$$

where $\varepsilon = |f(X) - f(X')| \ln \frac{1+\alpha}{1-\alpha}$ and $\delta = 2\exp(-\alpha^2 mp/10)$.

Proof. Fix any set of integers Z. We will show that

$$\mathbb{P}\left[M_{m,p,f}(X) \in Z\right] \leq \exp\left(|f(X) - f(X')| \cdot \ln \tfrac{1+\alpha}{1-\alpha}\right) \mathbb{P}\left[M_{m,p,f}(X) \in Z\right]$$
$$+ 2\exp(-\alpha^2 mp/10)$$

which is equivalent to the divergence bound.

For any integer i, we use the notation $Z - i$ to denote the set $\{z - i \mid z \in Z\}$. Then

$$
\begin{aligned}
\mathbb{P}\left[M_{m,p,f}(X) \in Z\right] &= \sum_{z \in Z} \mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = z - f(X)\right] \\
&= \sum_{\hat{z} \in Z - f(X)} \mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = \hat{z}\right] \\
&\leq \sum_{\hat{z} \in (Z - f(X)) \cap Q} \mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = \hat{z}\right] + \sum_{\hat{z} \notin Q} \mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = \hat{z}\right].
\end{aligned}
\tag{2}
$$

The last inequality holds for any set Q. Our specific Q is

$$Q := \left\{q \in \mathbb{Z} \mid \frac{\mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = q\right]}{\mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = q + f(X) - f(X')\right]} < \exp\left(|f(X) - f(X')| \cdot \ln \tfrac{1+\alpha}{1-\alpha}\right)\right\}.$$

Recall that we supposed $|f(X) - f(X')| \leq t \leq \frac{\alpha m p}{2}$. The following fact comes from Lemma 4.12 in Ghazi et al. (2021): for any $k \in [-t, t]$,

$$\mathbb{P}_{Y \sim \mathbf{Bin}(m,p)}\left[\frac{\mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = Y\right]}{\mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = Y + k\right]} \geq \exp\left(|k| \cdot \ln \tfrac{1+\alpha}{1-\alpha}\right)\right] \leq 2\exp(-\alpha^2 mp/10).$$

Then by substitution,

$$
\begin{aligned}
(2) &\leq \sum_{\hat{z} \in (Z - f(X)) \cap Q} \exp\left(|f(X) - f(X')| \cdot \ln \tfrac{1+\alpha}{1-\alpha}\right) \mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = \hat{z} + f(X) - f(X')\right] \\
&\quad + 2\exp(-\alpha^2 mp/10) \\
&= \sum_{\hat{z} \in (Z - f(X')) \cap Q} \exp\left(|f(X) - f(X')| \cdot \ln \tfrac{1+\alpha}{1-\alpha}\right) \mathbb{P}_{\eta \sim \mathbf{Bin}(m,p)}\left[\eta = \hat{z}\right] \\
&\quad + 2\exp(-\alpha^2 mp/10) \\
&\leq \exp\left(|f(X) - f(X')| \cdot \ln \tfrac{1+\alpha}{1-\alpha}\right) \mathbb{P}\left[M_{m,p,f}(X') \in Z\right] + 2\exp(-\alpha^2 mp/10). \qquad \square
\end{aligned}
$$

With Lemma A.1 in hand, we now turn to proving our main result for scalar sum, Lemma 3.1.

Lemma A.2 (Restatement of Lemma 3.1). *Fix any number of users n, $\varepsilon \leq 1$, and $0 < \delta < 1$. Let $g \geq \Delta\sqrt{n}$, $b > \frac{180g^2 \ln(2/\delta)}{\varepsilon^2 n}$, and $p = \frac{90g^2 \ln(2/\delta)}{b\varepsilon^2 n}$. Then 1) for any neighboring databases $X \sim X' \in [0, \Delta]^n$ that differ on user u, $D_\infty^\delta((\mathcal{S} \circ \mathcal{R}_{1D}^n)(X) \| (\mathcal{S} \circ \mathcal{R}_{1D}^n)(X')) \leq \varepsilon \cdot \left(\frac{2}{g} + \frac{|x_u - x_u'|}{\Delta}\right)$, and 2) for any input database $X \in [0, \Delta]^n$, the $\mathcal{P}_{1D}(X)$ is an unbiased estimate of $\sum_{i=1}^n x_i$ and has variance $O(\Delta + \frac{\Delta^2}{\varepsilon^2} \log \frac{1}{\delta})$.*

Proof. We first prove item 1. On input X, the shuffler produces a uniformly random permutation of the $(g + b)n$ bits $y_1, \ldots y_{(g+b)n}$. For each user i, let z_i be the sum of the messages sent by user i, $z_i = \sum_{j=1}^{g+b} \vec{y}_{i,j}$. Then the random variable for permutations of $y_1, \ldots y_{(g+b)n}$ can also be viewed as a post-processing of the random variable $Z = \sum_{i=1}^n z_i$. Let Z' be the analogue of Z for input database X', differing in user u. Then by the data-processing inequality, it suffices to prove $D_\infty^\delta(Z \| Z') \leq \varepsilon \cdot (2/g + |x_u - x_u'|/\Delta)$.

By the definition of $\mathcal{R}_{1D}$, Z is distributed as $\hat{x}_u + \sum_{i \neq u} \hat{x}_u + \mathbf{Bin}(bn, p)$ while Z' is distributed as $\hat{x}_u' + \sum_{i \neq u} \hat{x}_u + \mathbf{Bin}(bn, p)$. We have therefore reduced the analysis to that of the binomial mechanism. Our next step is to justify that Lemma A.1 applies to our construction. Specifically, we must identify α, m, t and show $p < 1/2$, $|\hat{x}_u - \hat{x}_u'| \leq t$, and $\alpha m p \geq 2t$.

We set $m = bn$, $t = g$, and $\alpha = \varepsilon/3g$ Our assumption on b implies that $p < 1/2$. And the fact that $\hat{x}_i, \hat{x}_i'$ both lie in the interval $[0, g]$ implies $|\hat{x}_i - \hat{x}_i'| \leq g = t$. So it remains to prove $\alpha m p \geq 2t$:

$$\alpha m p = \alpha \cdot bn \cdot \frac{90g^2 \ln(2/\delta)}{b\varepsilon^2 n} = \alpha \cdot \frac{90g^2 \ln(2/\delta)}{\varepsilon^2} = \frac{30g \ln(2/\delta)}{\varepsilon} > 2t.$$

Next, we derive the target bound on the divergence. Via Lemma A.1, we have that

$$D_\infty^{\hat{\delta}}((\mathcal{S} \circ \mathcal{R}_{1D}^n)(X) \| (\mathcal{S} \circ \mathcal{R}_{1D}^n)(X')) \leq \hat{\varepsilon},$$

where

$$
\begin{aligned}
\hat{\varepsilon} &= |\hat{x}_u - \hat{x}_u'| \ln \frac{1 + \alpha}{1 - \alpha} \\
&\leq |\hat{x}_u - \hat{x}_u'| \cdot 3\alpha && (\alpha \text{ small}) \\
&= \varepsilon \cdot \frac{1}{g} \cdot |\hat{x}_u - \hat{x}_u'| \\
&\leq \varepsilon \cdot \frac{1}{g} \cdot \left(2 + \frac{|x_u - x_u'| \cdot g}{\Delta}\right) && (\text{Discretization}) \\
&= \varepsilon \cdot \left(\frac{2}{g} + \frac{|x_u - x_u'|}{\Delta}\right)
\end{aligned}
$$

and

$$
\begin{aligned}
\hat{\delta} &= 2\exp(-\alpha^2 m p/10) \\
&\leq 2\exp(-\alpha^2 \cdot 9 \cdot \frac{g^2 \ln(2/\delta)}{\varepsilon^2}) = \delta.
\end{aligned}
$$

Moving to item 2, observe that the sum of the messages produced by user i is $\overline{x}_i + \eta_1 + \eta_2$. Since η_1 was drawn from $\mathbf{Ber}(x_i g/\Delta - \overline{x}_i)$, $\mathbb{E}[\eta_1] = x_i g/\Delta - \overline{x}_i$ and $\mathrm{Var}[\eta_1] \leq 1/4$. Meanwhile, η_2 is a sample from $\mathbf{Bin}(b, p)$ so $\mathbb{E}[\eta_2] = bp$ and $\mathrm{Var}[\eta_2] = bp(1 - p) \leq bp$. Recall our definition above of $z_i = \sum_{j=1}^{b+g} \vec{y}_{i,j}$. Then $\mathbb{E}[z_i] = x_i g/\Delta + bp$ and, by the independence of η_1 and η_2, $\mathrm{Var}[z_i] \leq 1/4 + bp$. Extending this over all n users yields $\mathbb{E}[\sum_{i=1}^n z_i] = \frac{g}{\Delta}\sum_{i=1}^n x_i + bnp$ and $\mathrm{Var}[\sum_{i=1}^n z_i] \leq n/4 + bnp$. $\mathcal{A}_{1D}$ shifts and rescales this quantity, so its final output is unbiased

$$\mathbb{E}\left[\frac{\Delta}{g}\left(\left(\sum_{i=1}^n z_i\right) - bnp\right)\right] = \sum_{i=1}^n x_i$$

and, by our assumption that $g \geq \Delta\sqrt{n}$ and choice of p,

$$\mathrm{Var}\left[\frac{\Delta}{g}\left(\left(\sum_{i=1}^n z_i\right) - bnp\right)\right] \leq \frac{\Delta^2}{g^2}\left(\frac{n}{4} + bnp\right) = O\left(1 + \frac{\Delta^2 bnp}{g^2}\right) = O\left(\frac{\Delta^2}{\varepsilon^2} \log \frac{1}{\delta}\right).$$

$\square$

A.2 Proofs for Vector Sum

Having completed our analysis of $\mathcal{P}_{\text{1D}}$, we now turn to $\mathcal{P}_{\text{VEC}}$. The first step in this direction is proving the following variant of advanced composition:

Lemma A.3 (Restatement of Lemma 3.3). *Fix any $\gamma \in (0, 1)$ and neighboring databases $X, X' \in \mathcal{X}^n$. For all $j \in [d]$, suppose algorithm $\mathcal{A}_j : \mathcal{X}^n \to \mathcal{Y}$ use independent random bits and satisfies $D_\infty^{\delta_j}(\mathcal{A}_j(X)||\mathcal{A}_j(X')) \leq \varepsilon_j$ on neighboring datasets $X, X' \subseteq \mathcal{X}^n$. Let*

$$\varepsilon' = \sum_{j=1}^d \varepsilon_j(e^{\varepsilon_j} - 1) + 2\sqrt{\log(1/\gamma) \sum_{j=1}^d \varepsilon_j^2} \quad \text{and} \quad \delta' = \sum_{j=1}^d \delta_j + \gamma.$$

Then $D_\infty^{\delta'}(\mathcal{A}_1(X), \ldots, \mathcal{A}_d(X)||\mathcal{A}_1(X') \ldots, \mathcal{A}_d(X')) \leq \varepsilon'$.

We first provide some useful definitions.

Definition A.4. *Given random variables Y and Z, the* KL Divergence *between Y and Z is*

$$D(Y||Z) = \mathbb{E}_{y \in Y}\left[\log \frac{\Pr[Y = y]}{\Pr[Z = z]}\right].$$

The Max Divergence *between Y and Z is*

$$D_\infty(Y||Z) = \max_{S \subseteq \text{supp}(Y)}\left[\log \frac{\Pr[Y \in S]}{\Pr[Z \in S]}\right].$$

The total variation distance *between Y and Z is*

$$\Delta(Y, Z) = \max_{S \subseteq \text{supp}(Y)} |P_Y(S) - P_Z(S)|.$$

The following lemma relating these notions comes from Dwork and Roth (2014).

Lemma A.5 (Lemma 3.17 and 3.18 (Dwork and Roth, 2014)). *Given random variables Y and Z,*

1. *We have both $D_\infty^\delta(Y||Z) \leq \varepsilon$ and $D_\infty^\delta(Z||Y) \leq \varepsilon$ if and only if there exists random variables Y', Z' such that $\Delta(Y, Y') \leq \delta/(e^\varepsilon + 1)$ and $\Delta(Z, Z') \leq \delta/(e^\varepsilon + 1)$, and $D_\infty(Y'||Z') \leq \varepsilon$, and $D_\infty(Z'||Y') \leq \varepsilon$.*

2. *If $D_\infty(Y||Z) \leq \varepsilon$ and $D_\infty(Z||Y) \leq \varepsilon$, then $D(Y||Z) \leq \varepsilon(e^\varepsilon - 1)$.*

For the first claim, Dwork and Roth (2014) only explicitly proves that $D_\infty(Y'||Z') \leq \varepsilon$, but their construction of Y' and Z' also implies $D_\infty(Z'||Y') \leq \varepsilon$.

We now have the tools to prove our variant of advanced composition, Lemma A.3.

Proof of Lemma A.3. For any neighboring datasets X and X', let $Y = (Y_1, Y_2, \ldots, Y_d)$ and $Z = (Z_1, Z_2, \ldots, Z_d)$ denote the outcomes of running $\mathcal{A}_1, \ldots, \mathcal{A}_d$ on X, X' respectively. By Fact 2.3 and the first part of Lemma A.5, there exist random variables $Y' = (Y'_1, \ldots, Y'_d)$ and $Z' = (Z'_1, \ldots, Z'_d)$ such that, for any $j \in [d]$, the following four inequalities hold: (i) $\Delta(Y_j, Y'_j) \leq \delta_j/(e^{\varepsilon_j} + 1)$, (ii) $\Delta(Z_j, Z'_j) \leq \delta_j/(e^{\varepsilon_j} + 1)$, (iii) $D_\infty(Y'_j||Z'_j) \leq \varepsilon_j$, and (iv) $D_\infty(Z'_j||Y'_j) \leq \varepsilon_j$. Then

$$\Delta(Y, Y'), \Delta(Z, Z') \leq \sum_{j=1}^d \frac{\delta_j}{e^{\varepsilon_j} + 1} < \frac{1}{2}\sum_{j=1}^d \delta_j.$$

Consider the outcome set $B = \{v \in \mathbb{R}^d : \Pr[Y' = v] \geq e^{\varepsilon'} \Pr[Z' = v]\}$. It remains to prove $\Pr[Y' \in B] \leq \gamma$. For any fixed realization $v = (v_1, \ldots, v_d) \in \mathbb{R}^d$, we have

$$\log\left(\frac{\Pr[Y' = v]}{\Pr[Z' = v]}\right) = \sum_{j=1}^d \log\left(\frac{\Pr[Y'_j = v_j]}{\Pr[Z'_j = v_j]}\right) \triangleq \sum_{j=1}^d c_j$$

where the first step follows from independence and the last step defines c_j. Since $D_\infty(Y'_j||Z'_j) \leq \varepsilon_j$ and $D_\infty(Z'_j||Y'_j) \leq \varepsilon_j$, we know that $|c_j| \leq \varepsilon_j$, and by the second part of Lemma A.5

$$\mathbb{E}_{v_j \sim Y_j}[c_j] = \mathbb{E}_{v_j \sim Y_j}\left[\log\left(\frac{\Pr[Y'_j = v_j]}{\Pr[Z'_j = v_j]}\right)\right] \leq \varepsilon_j(e^{\varepsilon_j} - 1).$$

Thus we have

$$\Pr[Y' \in B] = \Pr\left[\sum_{j=1}^d c_j \geq \varepsilon'\right]$$

$$= \Pr\left[\sum_{j=1}^d c_j \geq \sum_{j=1}^d \varepsilon_j(e^{\varepsilon_j} - 1) + 2\sqrt{\log(1/\gamma)\sum_{j=1}^d \varepsilon_j^2}\right] \leq \gamma.$$

by a Chernoff-Hoeffding bound. Tracing back, $\mathbb{P}[Y' \in B] \leq \gamma$ implies $D_\infty^\gamma(Y'||Z') \leq \varepsilon'$. Our previous bounds on $\Delta(Y, Y')$ and $\Delta(Z, Z')$ then give $D_\infty^{\sum_{j=1}^d \delta_j + \gamma}(Y||Z) \leq \varepsilon'$. $\qquad\square$

Finally, we can now prove Theorem 3.2, our primary guarantee for vector summation.

Theorem A.6 (Restatement of Theorem 3.2). *For any $0 < \varepsilon \leq 1$, $0 < \delta < 1$, $d, n \in \mathbb{N}$, and $\Delta_2 > 0$, there are choices of parameters $b, g \in \mathbb{N}$ and $p \in (0, 1/2)$ for $\mathcal{P}_{1D}$ (Algorithm 3.1) such that, for inputs $\vec{X} = (\vec{x}_1, \ldots, \vec{x}_n)$ of vectors with maximum norm $||\vec{x}_i||_2 \leq \Delta_2$, 1) $\mathcal{P}_{VEC}$ is (ε, δ)-shuffle private and, 2) $\mathcal{P}_{VEC}(\vec{X})$ is an unbiased estimate of $\sum_{i=1}^n \vec{x}_i$ and has bounded variance*

$$\mathbb{E}\left[\left\|\mathcal{P}_{VEC}(\vec{X}) - \sum_{i=1}^n \vec{x}_i\right\|_2^2\right] = O\left(\frac{d\Delta_2^2}{\varepsilon^2}\log^2\frac{d}{\delta}\right).$$

Proof. We set $g = \max(2\Delta_2\sqrt{n}, \sqrt{d})$. We will choose b, p later in the proof.

Fix neighboring databases of vectors $\vec{X}$ and $\vec{X}'$. We assume without loss of generality that the databases differ only in the first user, $\vec{x}_1 \neq \vec{x}'_1$. Then the ℓ_2 sensitivity is

$$\left\|\sum_{i=1}^n \vec{x}_i - \sum_{i=1}^n \vec{x}'_i\right\|_2 = ||\vec{x}_1 - \vec{x}'_1||_2 \leq 2\Delta_2. \tag{3}$$

From our definition of $\vec{w}_{i,j}$ in line 4 of the pseudocode for $\mathcal{P}_{VEC}$ and the fact that $||\vec{x}_i||_2 \leq \Delta_2$, $\vec{w}_{i,j} \geq 0$ and $\vec{w}_{i,j} \leq ||\vec{x}_i||_\infty + \Delta_2 \leq ||\vec{x}_i||_2 + \Delta_2 \leq 2\Delta_2$. This means the sensitivity of the value of $\vec{w}_{i,j}$ is $2\Delta_2$.

For each coordinate $j \in [d]$, we use a_j to denote the absolute difference in the j-th coordinate,

$$a_j := |\vec{x}_{1,j} - \vec{x}'_{1,j}| = |\vec{w}_{1,j} - \vec{w}'_{1,j}|$$

Let $\gamma, \hat{\delta} = \delta/(d+1)$ and $\hat{\varepsilon} = \varepsilon/18\sqrt{\log(1/\gamma)}$. Because $g \geq 2\Delta_2\sqrt{n}$, we may use Lemma 3.1 to set b, p such that

$$D_\infty^{\hat{\delta}}((\mathcal{S} \circ \mathcal{R}_{1D}^n)(W_j)||(\mathcal{S} \circ \mathcal{R}_{1D}^n)(W'_j)) \leq \hat{\varepsilon} \cdot \left(\frac{2}{g} + \frac{a_j}{2\Delta_2}\right) \triangleq \varepsilon_j$$

where we use W_j to denote $(w_{1,j}, \ldots, w_{n,j})$ and the last step defines ε_j. Notice that

$$
\begin{aligned}
\sum_{j \in [d]} \varepsilon_j^2 &= \hat{\varepsilon}^2 \cdot \sum_{j \in [d]} \frac{4}{g^2} + \frac{2a_j}{\Delta_2 g} + \frac{a_j^2}{4\Delta_2^2} \\
&\leq \hat{\varepsilon}^2 \cdot \left(\frac{4d}{g^2} + \frac{2\|\vec{x}_1 - \vec{x}_1'\|_1}{\Delta_2 g} + \frac{\|\vec{x}_1 - \vec{x}_1'\|_2^2}{4\Delta_2^2} \right) && \text{(Def of } a_j) \\
&\leq \hat{\varepsilon}^2 \cdot \left(\frac{4d}{g^2} + \frac{2\sqrt{d}\|\vec{x}_1 - \vec{x}_1'\|_2}{\Delta_2 g} + \frac{\|\vec{x}_1 - \vec{x}_1'\|_2^2}{4\Delta_2^2} \right) \\
&\leq \hat{\varepsilon}^2 \cdot \left(\frac{4d}{g^2} + \frac{4\sqrt{d}}{g} + 1 \right) && \text{(Via (3))} \\
&\leq \hat{\varepsilon}^2 \cdot (4 + 4 + 1) = 9\hat{\varepsilon}^2 && (4)
\end{aligned}
$$

The final inequality comes from the fact that $g \geq \sqrt{d}$. By our choices of $\hat{\varepsilon}$, γ, and $\hat{\delta}$, we apply Lemma 3.3 to conclude that

$$
\begin{aligned}
D_\infty^\delta((S \circ \mathcal{R}_{\text{VEC}}^n)(\vec{X}) \| (S \circ \mathcal{R}_{\text{VEC}}^n)(\vec{X}')) &\leq \sum_{j=1}^d \varepsilon_j (e^{\varepsilon_j} - 1) + 2\sqrt{\log(1/\gamma) \sum_{j=1}^d \varepsilon_j^2} \\
&\leq \sum_{j=1}^d 2\varepsilon_j^2 + 2\sqrt{\log(1/\gamma) \sum_{j=1}^d \varepsilon_j^2} && (\varepsilon_j \text{ small}) \\
&\leq 18\hat{\varepsilon}^2 + 6\hat{\varepsilon}\sqrt{\log(1/\gamma)} && \text{(Via (4))} \\
&\leq \varepsilon && \text{(Choice of } \hat{\varepsilon})
\end{aligned}
$$

which is precisely (ε, δ)-differential privacy by Fact 2.3.

The estimator produced by $\mathcal{P}_{\text{VEC}}$ is unbiased because each invocation of $\mathcal{P}_{\text{1D}}$ yields unbiased estimates. And we have, by linearity and the variance bound of $\mathcal{P}_{\text{1D}}$,

$$
\mathbb{E}\left[\left\| \mathcal{P}_{\text{VEC}}(\vec{X}) - \sum_{i=1}^n \vec{x}_i \right\|_2^2 \right] = \sum_{j=1}^d \mathbb{E}\left[\left| \mathcal{P}_{\text{VEC}}(\vec{X}_j) - \sum_{i=1}^n \vec{x}_{i,j} \right|^2 \right] = O\left(\frac{d\Delta_2^2}{\hat{\varepsilon}^2} \log\left(\frac{1}{\hat{\delta}} \right) \right).
$$

The theorem statement follows by substitution. $\qquad \square$

A.3 ROBUST PRIVACY OF SUM

We now discuss the *robustness* of our privacy guarantees, as mentioned at the end of Section 3.1. In more detail, we slightly generalize the privacy analysis of $\mathcal{P}_{\text{1D}}$ to account for the case where a γ fraction of the users are honest. Because $\mathcal{P}_{\text{1D}}$ is used as a building block for the other protocols we describe, this robustness carries over. We first present the definition of robust shuffle privacy originally given by Balcer et al. (2021).

Definition A.7 (Balcer et al. (2021)). *Fix $\gamma \in (0, 1]$. A protocol $\mathcal{P} = (\mathcal{R}, \mathcal{A})$ is $(\varepsilon, \delta, \gamma)$-robustly shuffle differentially private if, for all $n \in \mathbb{N}$ and $\gamma' \geq \gamma$, the algorithm $S \circ \mathcal{R}^{\gamma' n}$ is (ε, δ)-differentially private. In other words, $\mathcal{P}$ guarantees (ε, δ)-shuffle privacy whenever at least a γ fraction of users follow the protocol.*

Although the above definition only explicitly handles drop-out attacks by $1 - \gamma$ malicious users, this is without loss of generality: any messages sent to the shuffler from the malicious users constitute a post-processing of $S \circ \mathcal{R}^{\gamma n}$.

Now, we show that reducing the number of participants in $\mathcal{P}_{\text{1D}}$ loosens the bound on the divergence in a smooth fashion. Because $\mathcal{P}_{\text{1D}}$ is the building block of our other protocols, they inherit its robustness. The statement requires $\gamma \geq 1/3$, but this constant is arbitrary; changing it to a different value will only influence the lower bound on g.

Claim A.8. *Fix any $\gamma \in [1/3, 1]$, any number of users n, $\varepsilon \leq 1$, and $0 < \delta < 1$. If $g \geq 3$, $b > 180 \cdot \frac{g^2}{\varepsilon^2 n} \ln \frac{2}{\delta}$, and $p = 90 \cdot \frac{g^2}{b\varepsilon^2 n} \ln \frac{2}{\delta}$ then, for any neighboring databases $X \sim X' \in [0, \Delta]^n$ that differ on user u,*

$$D_\infty^\delta((S \circ \mathcal{R}_{1D}^{\gamma n})(X) \| (S \circ \mathcal{R}_{1D}^{\gamma n})(X')) \leq \frac{\varepsilon}{\gamma} \cdot \left(\frac{2}{g} + \frac{|x_u - x'_u|}{\Delta} \right).$$

This implies $\mathcal{P}_{1D}$ satisfies $(O(\varepsilon/\gamma), \delta, \gamma)$-robust shuffle privacy.

Proof. The proof proceeds almost identically with that of Item 2 in Lemma 3.1. The key change is that privacy noise is now drawn from $\mathbf{Bin}(\gamma bn, p)$. This means we take $m = \gamma bn$. We again set $t = g$ but now $\alpha = \varepsilon/3\gamma g$. Note that $\alpha < 1/3$ because $\varepsilon \leq 1$ and $\gamma g > 3\gamma > 1$.

As before, our assumption on b implies that $p < 1/2$ and we have $|\hat{x}_u - \hat{x}'_u| \leq g = t$. So it remains to prove $\alpha mp \geq 2t$ in order to apply Lemma A.1:

$$\alpha mp = \alpha \cdot \gamma bn \cdot \frac{90g^2 \ln(2/\delta)}{b\varepsilon^2 n} = \alpha \cdot \gamma \cdot \frac{90g^2 \ln(2/\delta)}{\varepsilon^2} = \frac{30g \ln(2/\delta)}{\varepsilon} > 2t$$

Now we derive the target bound on the divergence. Via Lemma A.1, we have that

$$D_\infty^{\hat{\delta}}((S \circ \mathcal{R}_{1D}^n)(X) \| (S \circ \mathcal{R}_{1D}^n)(X')) \leq \hat{\varepsilon},$$

where

$$
\begin{aligned}
\hat{\varepsilon} &= |\hat{x}_u - \hat{x}'_u| \ln \frac{1+\alpha}{1-\alpha} \\
&\leq |\hat{x}_u - \hat{x}'_u| \cdot 3\alpha & (\alpha \text{ small}) \\
&= \frac{\varepsilon}{\gamma} \cdot \frac{1}{g} \cdot |\hat{x}_u - \hat{x}'_u| \\
&\leq \frac{\varepsilon}{\gamma} \cdot \frac{1}{g} \cdot \left(2 + \frac{|x_u - x'_u| \cdot g}{\Delta} \right) & (\text{Discretization}) \\
&= \frac{\varepsilon}{\gamma} \cdot \left(\frac{2}{g} + \frac{|x_u - x'_u|}{\Delta} \right)
\end{aligned}
$$

and

$$
\begin{aligned}
\hat{\delta} &= 2 \exp(-\alpha^2 mp/10) \\
&= 2 \exp(-\alpha^2 \cdot 9\gamma \cdot \frac{g^2 \ln(2/\delta)}{\varepsilon^2}) \\
&= 2 \exp(-\frac{1}{\gamma} \cdot \ln(2/\delta)) \\
&\leq 2 \exp(-\ln(2/\delta)) = \delta
\end{aligned}
$$

This concludes the proof. $\qquad\square$

When we replace ε in the proof of Theorem 3.2 with ε/γ, we can invoke Claim A.8 to derive the following statement about the robust shuffle privacy of $\mathcal{P}_{VEC}$.

Corollary A.9. *For any $0 < \varepsilon \leq 1$, $0 < \delta < 1$, $d, n \in \mathbb{N}$, and $\Delta_2 > 0$, there are choices of parameters $b, g \in \mathbb{N}$ and $p \in (0, 1/2)$ for $\mathcal{P}_{1D}$ (Algorithm 3.1) such that, for inputs $\vec{X} = (\vec{x}_1, \ldots, \vec{x}_n)$ of vectors with maximum norm $\|\vec{x}_i\|_2 \leq \Delta_2$ and any $\gamma \in [1/3, 1]$, $\mathcal{P}_{VEC}$ is $(\varepsilon/\gamma, \delta, \gamma)$-robustly shuffle private*

Because $\mathcal{P}_{VEC}$ serves as a primitive for our optimization protocols, each round of those protocols ensures privacy in the face of two-thirds corruptions. For comparison, the generic construction by Beimel et al. (2020) is able to simulate arbitrary centrally private algorithms but requires an honest majority.

B PROOFS FOR SECTION 4

B.1 PROOFS FOR SECTION 4.1

We start by proving the guarantee for $\mathcal{P}_{\text{SGD}}$, Theorem 4.1. The first step is to formally define the gradient oracle setup that will be necessary for several of our results.

Definition B.1. *Given function ℓ over $\Theta \subset \mathbb{R}^d$, we say $G \colon \Theta \to \mathbb{R}^d$ is an L_G-noisy gradient oracle for ℓ if for every $\theta \in \Theta$, (1) $\mathbb{E}_G\left[G(\theta)\right] \in \partial\ell(\theta)$, and (2) $\mathbb{E}_G\left[\|G(\theta)\|_2^2\right] \leq L_G^2$. Furthermore, we say the gradient oracle G has* variance at most σ^2 *if $\mathbb{E}_G\left[\|G(\theta) - \mathbb{E}_G\left[G(\theta)\right]\|_2^2\right] \leq \sigma^2$.*

The following lemma is standard for (noisy) stochastic gradient descent.

Lemma B.2 (Restatement of Lemma 4.2). *Suppose $\mathcal{P}_{\text{SGD}}$ queries an L_G-noisy gradient oracle at each iteration, then its output satisfies*

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + \frac{D^2}{2\eta T} + \frac{\eta L_G^2}{2}.$$

We now have the tools to prove Theorem 4.1.

Proof of Theorem 4.1. The privacy guarantee follows directly from the privacy guarantee of the vector summation protocol (see Theorem 3.2), and the fact that the algorithm queries each user at most once.

For the accuracy guarantee, our algorithm directly optimizes the excess population loss. For each time step $t \in \{0, 1, \ldots, T-1\}$, we write the gradient $\bar{g}_t = \frac{1}{b}\sum_{i=1}^{b} \nabla_\theta \ell(\theta_{t-1}, x_{t,i}) + \mathbf{Z}_t$. By Theorem 3.2, we know that

$$\mathbb{E}_{x_{t,1}, \ldots, x_{t,b}, \mathbf{Z}_t}\left[\bar{g}_t\right] = \mathbb{E}_{x \sim \mathcal{D}}\left[\nabla_\theta \ell(\theta_{t-1}, x)\right]$$

and

$$\mathbb{E}_{x_{t,1}, \ldots, x_{t,b}, \mathbf{Z}_t}\left[\|\bar{g}_t\|_2^2\right] = \mathbb{E}_{x_{t,1}, \ldots, x_{t,b}, \mathbf{Z}_t}\left[\left\|\frac{1}{b}\sum_{i=1}^{b} \nabla_\theta \ell(\theta_{t-1}, x_{t,i}) + \mathbf{Z}_t\right\|_2^2\right]$$

$$= \mathbb{E}_{x_{t,1}, \ldots, x_{t,b}}\left[\left\|\frac{1}{b}\sum_{i=1}^{b} \nabla_\theta \ell(\theta_{t-1}, x_{t,i})\right\|_2^2\right] + \mathbb{E}\left[\|\mathbf{Z}_t\|_2^2\right]$$

$$\leq L^2 + O\left(\frac{dL^2 \log^2(d/\delta)}{b^2 \varepsilon^2}\right), \tag{5}$$

where the second equality uses the independence of the data and noise, and the inequality follows from ℓ being L-Lipschitz and Theorem 3.2.

The gradient $\bar{g}_t$ therefore qualifies as a noisy gradient oracle call with $L_G^2 = L^2 + O\left(\frac{dL^2 \log^2(d/\delta)}{b^2 \varepsilon^2}\right)$. By Lemma 4.2 and the fact that there are n/b iterations, we get

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + \frac{D^2}{2\eta T} + \frac{\eta L_G^2}{2}$$

$$\leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + \frac{DL_G}{\sqrt{T}} \qquad\qquad \text{(AM-GM ineq.)}$$

$$= \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + D\sqrt{\frac{1}{T}\left(L^2 + O\left(\frac{dL^2 \log^2(d/\delta)}{b^2 \varepsilon^2}\right)\right)}$$

$$= \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(DL\sqrt{\frac{b}{n} + \frac{d \log^2(d/\delta)}{\varepsilon^2 bn}}\right) \qquad\qquad (T = n/b)$$

$$= \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{d^{1/4} DL \log^{1/2}(d/\delta)}{\sqrt{\varepsilon n}}\right),$$

The final step uses our choice of $b = \frac{\sqrt{d} \log(d/\delta)}{\varepsilon}$ $\qquad\square$

Next, we prove the guarantee for $\mathcal{P}_{\mathrm{AGD}}$, Theorem 4.3.

Proof of Theorem 4.3. The privacy guarantee follows directly from the privacy guarantee of the vector summation protocol (see Theorem 3.2), and the fact that the algorithm queries each user at most once, and the remaining computation is post-processing.

We now prove the accuracy guarantee. For any iteration $t \in [T]$, let $\mathbf{Z}_t$ be the noise introduced by the summation protocol $\mathcal{P}_{\mathrm{VEC}}$ and let $\bar{g}_t = \frac{1}{b} \sum_{i=1}^{b} \nabla_\theta \ell(\theta_{t-1}, x_{t,i}) + \mathbf{Z}_t$. We first bound the variance:

$$\mathbb{E}\left[\|G(\theta_{t-1}) - \mathbb{E}\left[G(\theta_{t-1})\right]\|_2^2 \right]$$

$$= \mathbb{E}_{x_{t,1},\ldots,x_{t,b},\mathbf{Z}_t}\left[\left\| \frac{1}{b} \sum_{i=1}^{b} \nabla_\theta \ell(\theta_{t-1}, x_{t,i}) + \mathbf{Z}_t - \mathbb{E}_{x\sim\mathcal{D}}\left[\nabla \ell(\theta_{t-1}, x)\right] \right\|_2^2 \right]$$

$$= \mathbb{E}_{x_{t,1},\ldots,x_{t,b}}\left[\left\| \frac{1}{b} \sum_{i=1}^{b} \nabla \ell(\theta_{t-1}, x_{t,i}) - \mathbb{E}_{x\sim\mathcal{D}}\left[\nabla \ell(\theta_{t-1}, x)\right] \right\|_2^2 \right] + \mathbb{E}\left[\|\mathbf{Z}_t\|_2^2\right]$$

$$= \mathrm{Var}\left[\frac{1}{b} \sum_{i=1}^{b} \nabla \ell(\theta_{t-1}, x_{t,i}) \right] + \mathbb{E}\left[\|\mathbf{Z}_t\|_2^2\right]$$

$$= \frac{1}{b} \mathrm{Var}\left[\nabla \ell(\theta_{t-1}, x_{t,1}) \right] + \mathbb{E}\left[\|\mathbf{Z}_t\|_2^2\right]$$

$$= \frac{1}{b} \mathbb{E}_{x_t\sim\mathcal{D}}\left[\|\nabla \ell(\theta_{t-1}, x_t) - \mathbb{E}_x\left[\nabla \ell(\theta_{t-1}, x)\right]\|_2^2 \right] + \mathbb{E}\left[\|\mathbf{Z}_t\|_2^2\right]$$

$$= O\left(\frac{L^2}{b} + \frac{dL^2 \log^2(d/\delta)}{b^2 \varepsilon^2} \right). \tag{6}$$

The second equality comes from the fact that the data and noise are independent, the fourth equality uses the independence of $x_{t,1}, \cdots, x_{t,b}$ and (6) follows from Theorem 3.2. Next, we use the following result from Lan (2012).

Lemma B.3 (Restatement of Lemma 4.4). *Suppose $\mathcal{P}_{\mathrm{AGD}}$ receives a noisy gradient oracle with variance (at most) σ^2 in each iteration. Taking $L_t = \frac{1}{t+1}((T+2)^{3/2}\frac{\sigma}{D} + \beta), \alpha_t = \frac{2}{t+2}$, then the population loss of $\mathcal{P}_{\mathrm{AGD}}$ can be bounded as*

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta\in\Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{\beta D^2}{T^2} + \frac{D\sigma}{\sqrt{T}} \right).$$

In our case, we have $\sigma^2 = \frac{L^2}{b} + \frac{dL^2 \log^2(d/\delta)}{b^2 \varepsilon^2}$ so that

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta\in\Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{\beta D^2}{T^2} + \frac{D\sigma}{\sqrt{T}} \right)$$

$$\leq \min_{\theta\in\Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{\beta D^2}{T^2} + \frac{D\sqrt{\frac{L^2}{b} + \frac{dL^2 \log^2(d/\delta)}{b^2 \varepsilon^2}}}{\sqrt{T}} \right)$$

$$\leq \min_{\theta\in\Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{\beta D^2}{T^2} + \frac{DL}{\sqrt{bT}} + \frac{\sqrt{d}DL \log(d/\delta)}{b\varepsilon\sqrt{T}} \right)$$

$$= \min_{\theta\in\Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{b^2 \beta D^2}{n^2} + \frac{DL}{\sqrt{n}} + \frac{\sqrt{d}DL \log(d/\delta)}{\varepsilon\sqrt{bn}} \right)$$

$$= \min_{\theta\in\Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{d^{2/5}\beta^{1/5}D^{6/5}L^{4/5} \log^{4/5}(d/\delta)}{\varepsilon^{4/5}n^{4/5}} + \frac{DL}{\sqrt{n}} \right).$$

The first step follows from Lemma 4.4, and the second step comes from Eq. (6). In the last step, we substitute $b = \frac{n^{3/5}d^{1/5}L^{2/5} \log^{2/5}(d/\delta)}{\varepsilon^{2/5}\beta^{2/5}D^{2/5}}$. $\qquad\square$

Next, we prove our improved guarantee for convex losses by combining $\mathcal{P}_{\text{AGD}}$ and smoothing (Theorem 4.7).

Proof of Theorem 4.7. We directly optimize the loss function ℓ_β with $\mathcal{P}_{\text{AGD}}$. $\mathcal{P}_{\text{AGD}}$ only requires the gradient $\nabla \ell_\beta(\theta_t^{\text{md}}, x)$ $(t \in [T])$. By the second item in Lemma 4.6, this can be obtained by computing $\beta(\theta_t^{\text{md}} - \text{prox}_{\ell/\beta}(\theta_t^{\text{md}}))$. Moreover, since ℓ_β is $2L$-Lipschitz, $\mathcal{P}_{\text{AGD}}$ still guarantees (ε, δ)-differential privacy with a constant scaling of the noise. For accuracy, we have that

$$
\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] - \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) \leq \mathbb{E}\left[\ell_\beta(\bar{\theta}, \mathcal{D})\right] - \min_{\theta \in \Theta} \ell_\beta(\theta, \mathcal{D}) + \frac{L^2}{\beta}
$$

$$
\leq O\left(\frac{DL}{\sqrt{n}}\right) + O\left(\frac{d^{2/5}\beta^{1/5}D^{6/5}L^{4/5}\log^{4/5}(d/\delta)}{\varepsilon^{4/5}n^{4/5}}\right) + \frac{L^2}{\beta}
$$

$$
\leq O\left(\frac{DL}{\sqrt{n}} + \frac{d^{1/3}DL\log^{2/3}(d/\delta)}{\varepsilon^{2/3}n^{2/3}}\right).
$$

The first step follows from the third item in Lemma 4.6, the second step follows from the guarantee of $\mathcal{P}_{\text{AGD}}$ (Theorem 4.3) and the fact that ℓ_β is β-smooth, and the last step comes from our choice of $\beta = \frac{\varepsilon^{2/3}n^{2/3}L}{d^{1/3}D\log^{2/3}(d/\delta)}$. $\qquad\square$

Finally, we prove Theorem 4.8, which applies to strongly convex ℓ and is the final result about sequentially interactive protocols.

Proof of Theorem 4.8. The privacy guarantee follows from the previously-proven privacy guarantee for $\mathcal{P}_{\text{AGD}}$ and the fact that we split the users into disjoint subsets. The rest of the proof focuses on the population loss.

We begin with the non-smooth setting. The high level idea for this case is that both the population loss and the distance to optimal solution shrink in each iteration. By recursively applying the shuffle private convex algorithm and solving the recursion, one can get improved convergence rate. Let $\bar{\theta}_i$ be the output of the i-th phase and $\theta^* = \arg\min_{\theta \in \Theta} \ell(\theta, \mathcal{D})$. Denote $D_i^2 = \mathbb{E}\left[\|\bar{\theta}_i - \theta^*\|_2^2\right]$ and $\Delta_i = \mathbb{E}\left[\ell(\bar{\theta}_i, \mathcal{D}) - \ell(\theta^\star, \mathcal{D})\right]$.

Due to the λ-strong convexity, we have $D_i^2 \leq \frac{2\Delta_i}{\lambda}$. Since the guarantee of Theorem 4.7 uses D as a bound on the distance between the starting point and optimum, we have

$$
\Delta_{i+1} \leq C\left(\frac{D_i L}{\sqrt{n_i}} + \frac{d^{1/3}D_i L\log^{2/3}(d/\delta)}{\varepsilon^{2/3}n_i^{2/3}}\right) \leq \sqrt{\frac{2\Delta_i}{\lambda}} \cdot C\left(\frac{L}{\sqrt{n_i}} + \frac{d^{1/3}L\log^{2/3}(d/\delta)}{\varepsilon^{2/3}n_i^{2/3}}\right)
$$

$$
:= \sqrt{\Delta_i}E
$$

Here C is an universal constant, and the last step defines E. Hence, one has

$$
\frac{\Delta_{i+1}}{E^2} \leq \sqrt{\frac{\Delta_i}{E^2}}.
$$

We know that $\Delta_1 \leq 2L^2/\lambda$ (due to strong convexity), $E^2 \geq 2L^2/\lambda n$ (due to definition), and therefore, $\Delta_1/E^2 \leq O(n)$. Hence, after $k = O(\log\log n)$ phases, we have $\Delta_k/E^2 \leq 2$, and the population loss is

$$
\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{1}{\lambda} \cdot \left(\frac{L}{\sqrt{n_k}} + \frac{d^{1/3}L\log^{2/3}(d/\delta)}{n_k^{2/3}\varepsilon^{2/3}}\right)^2\right)
$$

$$
\leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + \tilde{O}\left(\frac{L^2}{\lambda n} + \frac{d^{2/3}L^2\log^{4/3}(d/\delta)}{\lambda\varepsilon^{4/3}n^{4/3}}\right).
$$

This completes the proof for the non-smooth setting. Turning to the setting where ℓ is also β-smooth, let $A = \frac{d^{2/5}\beta^{1/5}L^{4/5}\log^{4/5}(d/\delta)}{\varepsilon^{4/5}}$. Then our algorithm guarantees

$$\Delta_{i+1} \le C\left(\frac{AD_i^{6/5}}{n_i^{4/5}} + \frac{LD_i}{\sqrt{n_i}}\right) \le 2C\left(\frac{A\Delta_i^{3/5}}{\lambda^{3/5}n_i^{4/5}} + \frac{L\sqrt{\Delta_i}}{\sqrt{\lambda n_i}}\right) \tag{7}$$

for some constant $C > 1$.

First, suppose there exists $i \in [k]$ such that Δ_i is already small, i.e.

$$\Delta_i \le 2^{10}C^4\left(\frac{L^2}{\lambda n_i} + \frac{A^{5/2}}{\lambda^{3/2}n_i^2}\right) := T.$$

Then we claim $\Delta_t \le 2^{10}C^4\left(\frac{L^2}{\lambda n_i} + \frac{A^{5/2}}{\lambda^{3/2}n_i^2}\right)$ holds for all $t \ge i$. We divide into cases.

Case 1. Suppose $\frac{L^2}{\lambda n_i} \le \frac{A^{5/2}}{\lambda^{3/2}n_i^2}$. Then we have

$$\begin{aligned}
\Delta_{i+1} &\le 4C\cdot\left(2^6C^3\frac{A^{5/2}}{\lambda^{2/3}n_{i+1}^2} + 2^5C^3\frac{LA^{5/4}}{\lambda^{5/4}n_{i+1}^{3/2}}\right)\\
&\le 4C\cdot\left(2^6C^3\frac{A^{5/2}}{\lambda^{2/3}n_i^2} + 2^5C^3\frac{A^{5/2}}{\lambda^{2/3}n_i^2}\right)\\
&\le 2^{10}C^4\frac{A^{5/2}}{\lambda^{3/2}n_i^2}.
\end{aligned}$$

The first step follows from Eq. (7), $n_i = n_{i+1} = n/k$, the second step follows our assumption.

Case 2. Suppose $\frac{L^2}{\lambda n_i} \ge \frac{A^{5/2}}{\lambda^{3/2}n_i^2}$. Then we have

$$\begin{aligned}
\Delta_{i+1} &\le 4C\cdot\left(2^6C^3\frac{AL^{6/5}}{\lambda^{6/5}n_{i+1}^{7/5}} + 2^5C^3\frac{L^2}{\lambda n_{i+1}}\right)\\
&\le 4C\cdot\left(2^6C^3\frac{L^2}{\lambda n_i} + 2^5C^3\frac{L^2}{\lambda n_i}\right)\\
&\le 2^{10}C^4\frac{L^2}{\lambda n_i}.
\end{aligned}$$

The first step follows from Eq. (7), $n_i = n_{i+1} = n/k$, the second step follows our assumption.

Next, suppose $\Delta_i \le T = 2^{10}C^4\left(\frac{L^2}{\lambda n_i} + \frac{A^{5/2}}{\lambda^{3/2}n_i^2}\right)$, then we claim that Δ_{i+1} is decreasing, i.e., $\Delta_{i+1} \le \Delta_i$. Suppose this does not hold, since we have one of the following should hold

$$2C\frac{A\Delta_i^{3/5}}{\lambda^{3/5}n_{i+1}^{4/5}} \ge \frac{\Delta_i}{2} \quad\text{or}\quad 2C\frac{L\sqrt{\Delta_i}}{\sqrt{\lambda n_{i+1}}} \ge \frac{\Delta_i}{2}.$$

We argue this can not happens, since the former one implies $\Delta_i \le 2^5C^{5/2}\frac{A^{5/2}}{\lambda^{3/2}n_i^2}$ and the later implies $\Delta_i \le 2^4C^2\frac{L}{\lambda n_i}$.

Combining the above argument, we know that Δ_i is decreasing, until it goes below a threshold T, and after that, the value Δ_i will always below such the threshold T. Now, suppose after $k = O(\log\log n)$ iterations, Δ_k is still above the threshold T, then we know $\{\Delta_i\}_{i\in[k]}$ is decreasing and we divide the algorithmic procedure into two phases. In the first phase, we have $\frac{L\sqrt{\Delta_i}}{\sqrt{\lambda n}} \le \frac{A\Delta_i^{3/5}}{\lambda^{3/5}n_i^{4/5}}$, this happens when $\Delta_i \ge \frac{L^{10}\lambda}{A^{10}n_i^3}$, and the algorithm satisfies

$$\Delta_{i+1} \le 4C\frac{A\Delta_i^{3/5}}{\lambda^{3/5}n_{i+1}^{4/5}} = 4C\frac{A\Delta_i^{3/5}}{\lambda^{3/5}n_i^{4/5}}.$$

For the second phase, we have $\frac{L\sqrt{\Delta_i}}{\sqrt{\lambda n}} \geq \frac{A\Delta_i^{3/5}}{\lambda^{3/5}n^{4/5}}$ and this happens when this happens when $\Delta_i \leq \frac{L^{10}\lambda}{A^{10}n_i^3}$, and the algorithm satisfies

$$\Delta_{i+1} \leq 4C \frac{L\sqrt{\Delta_i}}{\sqrt{\lambda n_{i+1}}} = 4C \frac{L\sqrt{\Delta_i}}{\sqrt{\lambda n_i}}.$$

We know one of the two phases will run for more than $\Omega(\log\log n)$ iterations. Suppose the former case holds, i.e., $\Delta_{i+1} \leq 4C \frac{A\Delta_i^{3/5}}{\lambda^{3/5}n_i^{4/5}}$. Let $E = \left(\frac{4CA}{\lambda^{3/5}n_i^{4/5}} \right)^{5/2} \leq 2^5 C^{5/2} \frac{A^{5/2}}{\lambda^{3/2}n_i^2}$. Then, we have

$$\frac{\Delta_{i+1}}{E} \leq \left(\frac{\Delta_i}{E} \right)^{3/5}.$$

It is easy to verify that $\Delta_1/E \leq \text{poly}(n)$, and therefore, after $\Omega(\log\log n)$ iterations, we know that Δ_i will drop below $O(E) = 2^5 C^{5/2} \frac{A^{5/2}}{\lambda^{3/2}n_i^2} \leq T$.

When later case holds, i.e., $\Delta_{i+1} \leq 4C \frac{L\sqrt{\Delta_i}}{\sqrt{\lambda n_i}}$. Let $E = 16C^2 \frac{L^2}{\lambda n_i}$, then we know that

$$\frac{\Delta_{i+1}}{E} \leq \left(\frac{\Delta_i}{E} \right)^{1/2}.$$

It is easy to verify that $\Delta_1/E \leq \text{poly}(n)$, and therefore, after $\Omega(\log\log n)$ iterations, we know that Δ_i will drop below $O(E) = 16C^2 \frac{L^2}{\lambda n_i} \leq T$.

In summary, taking $k = \Omega(\log\log n)$, we know that

$$\mathbb{E}\left[\ell(\bar{\theta}_k, \mathcal{D}) \right] - \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) = \Delta_k \leq T = 2^{10}C^4 \left(\frac{L^2}{\lambda n_k} + \frac{A^{5/2}}{\lambda^{3/2}n_k^2} \right)$$
$$\leq \tilde{O}\left(\frac{L^2}{\lambda n} + \frac{d\beta^{1/2}L^2\log(d/\delta)^2}{\lambda^{3/2}\varepsilon^2 n^2} \right).$$

This concludes the proof.

$\square$

B.2 Proofs for Section 4.2

We now turn to proofs for our fully interactive protocol, $\mathcal{P}_{\text{GD}}$. The first step will be proving Lemma B.6, which provides a privacy and population loss guarantee for $\mathcal{P}_{\text{GD}}$ when the loss function ℓ is smooth. We will later combine this analysis for smooth losses with the smoothing trick used in the previous section to obtain guarantees for non-smooth losses. Since $\mathcal{P}_{\text{GD}}$ passes the training data more than once and does not directly optimize the excess population loss, the proof of Lemma B.6 proceeds by bounding the empirical loss and the generalization error separately. First, we recall a result bounding empirical loss.

Lemma B.4 (Bubeck et al. (2015)). *Let ℓ be convex and L-Lipschitz over closed convex set $\Theta \subset \mathbb{R}^d$ of diameter D. Let σ^2 denote the variance of the privacy noise in the gradient update step of $\mathcal{P}_{\text{GD}}$. For any set of data points S and $\eta > 0$, the output of $\mathcal{P}_{\text{GD}}$ satisfies*

$$\mathbb{E}\left[\ell(\bar{\theta}, S) \right] - \min_{\theta \in \Theta} \ell(\theta, S) \leq \frac{D^2}{2\eta T} + \frac{\eta(L^2 + \sigma^2)}{2}.$$

Next, we bound generalization error.

Lemma B.5 (Lemma 3.4 (Bassily et al., 2019)). *Suppose ℓ is convex, L-Lipschitz, and β-smooth over closed convex set $\Theta \subset \mathbb{R}^d$ of diameter D and $\eta \leq \frac{2}{\beta}$. Then $\mathcal{P}_{\text{GD}}$ is α-uniformly stable with $\alpha = L^2 \frac{T\eta}{n}$. In other words, it satisfies*

$$\mathbb{E}_{S\sim\mathcal{D}^n}\left[|\ell(\bar{\theta}, S) - \ell(\bar{\theta}, \mathcal{D})| \right] \leq L^2 \frac{T\eta}{n}.$$

With these two tools, we can state and prove Lemma B.6

Lemma B.6. *Let ℓ be convex, L-Lipschitz, and β-smooth over a closed convex set $\Theta \subset \mathbb{R}^d$ of diameter D. Then $\mathcal{P}_{\mathrm{GD}}$ is (ε, δ)-shuffle private with population loss*

$$\mathbb{E}\left[\ell(\bar{\theta}, \mathcal{D})\right] \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{DL}{\sqrt{n}} + \frac{d^{1/2} DL \log^{3/2}(d/\delta)}{\varepsilon n}\right).$$

Proof. For the privacy guarantee, since each iteration guarantees $(\frac{\varepsilon}{\sqrt{T \log(1/\delta)}}, \frac{\delta}{T+1})$-differential privacy, and the algorithm runs for T iterations in total, advanced composition implies (ε, δ)-shuffle privacy overall.

We now focus on the loss guarantee. First, by Lemma B.4, the empirical loss satisfies

$$\mathbb{E}\left[\ell(\bar{\theta}; S)\right] \leq \min_{\theta \in \Theta} \ell(\theta; S) + \frac{D^2}{2\eta T} + \frac{\eta L_G^2}{2}$$

$$\leq \min_{\theta \in \Theta} \ell(\theta; S) + \frac{D^2}{2\eta T} + \frac{\eta L^2}{2} + O\left(\frac{\eta d T L^2 \log^3(nd/\delta)}{2n^2 \varepsilon^2}\right)$$

where the second step follows from $L_G^2 \leq L^2 + O(\frac{dTL^2 \log^3(nd/\delta)}{n^2 \varepsilon^2})$ (see Eq. (5)). Moreover, by Lemma B.5, we know the generalization error is most $L^2 \frac{T\eta}{n}$. Hence, for $S \sim \mathcal{D}^n$,

$$\mathbb{E}\left[\ell(\bar{\theta}; \mathcal{D})\right] - \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) \leq \mathbb{E}\left[|\ell(\bar{\theta}, \mathcal{D}) - \ell(\bar{\theta}, S)|\right] + \mathbb{E}\left[\ell(\bar{\theta}, S) - \min_{\theta \in \Theta} \ell(\theta, S)\right]$$

$$\leq \frac{D^2}{2\eta T} + \frac{\eta L^2}{2} + \frac{\eta d T L^2 \log^3(nd/\delta)}{2n^2 \varepsilon^2} + L^2 \frac{T\eta}{n}$$

$$\leq O\left(\frac{DL\sqrt{d \log^3(nd/\delta)}}{\varepsilon n} + \frac{DL}{\sqrt{n}}\right)$$

The second step follows from Lemma B.5 and Lemma 4.2. Especially, we take expectation over $S \sim \mathcal{D}^n$ in Lemma 4.2. The last step follows by taking $\eta = \frac{D}{L\sqrt{T}}$ and $T = \min\{n, \frac{\varepsilon^2 n^2}{d \log^2(nd/\delta)}\}$. We use $\delta \ll 1/n$ for the final statement. $\qquad\square$

We can now prove Theorem 4.9. As done previously, we use Moreau envelope smoothing to apply the guarantee of Lemma B.6. For the strongly convex case, we apply the same reduction to the convex case as used by Feldman et al. (2020).

Proof of Theorem 4.9. The privacy guarantees are inherited from Lemma B.6. We employ Moreau envelope smoothing, as described in Lemma 4.6 and used earlier in the proof of Theorem 4.7, to construct ℓ_β with $\beta = \frac{L}{D} \min\left(\sqrt{n}, \frac{\varepsilon n}{d^{1/2} \log^{3/2}(nd/\delta)}\right)$. Optimizing ℓ_β yields

$$\mathbb{E}_{S \sim \mathcal{D}^n}\left[\ell(\bar{\theta}; \mathcal{D})\right] - \min_{\theta \in \Theta} \ell(\bar{\theta}, \mathcal{D})$$

$$\leq \mathbb{E}_{S \sim \mathcal{D}^n}\left[\ell_\beta(\bar{\theta}; \mathcal{D})\right] - \min_{\theta \in \Theta} \ell_\beta(\bar{\theta}, \mathcal{D}) + \frac{L^2}{2\beta}$$

$$\leq O\left(\frac{DL}{\sqrt{n}} + \frac{d^{1/2} DL \log^{3/2}(d/\delta)}{\varepsilon n}\right) + LD \cdot \left(\frac{1}{2\sqrt{n}} + \frac{d^{1/2} \log^{3/2}(d/\delta)}{2\varepsilon n}\right)$$

$$= O\left(\frac{DL}{\sqrt{n}} + \frac{d^{1/2} DL \log^{3/2}(d/\delta)}{\varepsilon n}\right).$$

The first step follows from the third item in Lemma 4.6, and the second step follows from Lemma B.6 and the definition of β.

For strongly convex losses, we use the same reduction as (Feldman et al., 2020).

Lemma B.7 (Theorem 5.1 in (Feldman et al., 2020)). *Suppose for any loss function that is convex and L-Lipschitz over a closed convex set $\Theta \subset \mathbb{R}^d$ of diameter D, there is an (ε, δ)-differentially private algorithm that achieves excess population loss of order*

$$LD \left(\frac{1}{\sqrt{n}} + \frac{\sqrt{d}}{\rho n} \right).$$

Then for any λ-strongly convex, L-Lipschitz loss function, there is an (ε, δ)-differentially private algorithm that achieves excess population loss of order

$$\frac{L^2}{\lambda} \left(\frac{1}{n} + \frac{d}{\rho^2 n^2} \right).$$

We note that this reduction works for the fully interactive model and keeps the privacy guarantee. In particular, one can divide users into the same set of groups as (Feldman et al., 2020) and apply $\mathcal{P}_{\mathrm{GD}}$ sequentially to these groups. By taking $\rho = \frac{\varepsilon}{\log^{3/2}(nd/\delta)}$, we get the desired guarantee for strongly convex functions. □

C PAN PRIVATE CONVEX OPTIMIZATION

Finally, we turn to pan-privacy, where we assume users/data arrive in a stream, and the goal is to guarantee differential privacy against a single intrusion into the stream-processing algorithm's internal state. We formalize the model and provide definition in Section C.1, and provide algorithms in Section C.2. Pan-privacy was introduced by Dwork et al. (2010); we use the presentation given by Amin et al. (2020) and Balcer et al. (2021).

C.1 MODELS AND DEFINITION

Our focus will be on online algorithms. They receive raw data one element at a time in a stream. At each step in the stream, the algorithm receives a data point, updates its internal state based on this data point, and then proceeds to the next element. The only way the algorithm "remembers" past elements is through its internal state. The formal definition we use is below.

Definition C.1. *An* online algorithm $\mathcal{Q}$ *is defined by an internal algorithm $\mathcal{Q}_\mathcal{I}$ and an output algorithm $\mathcal{Q}_\mathcal{O}$. $\mathcal{Q}$ processes a stream of elements through repeated application of $\mathcal{Q}_\mathcal{I} : \mathcal{X} \times \mathcal{I} \to \mathcal{I}$, which (with randomness) maps a stream element and internal state to an internal state. At the end of the stream, $\mathcal{Q}$ publishes a final output by executing $\mathcal{Q}_\mathcal{O}$ on its final internal state.*

As in the case of datasets, we say that two streams X and X' are *neighbors* if they differ in at most one element. Pan-privacy requires the algorithm's internal state and output to be differentially private with regard to neighboring streams.

Definition C.2 (Dwork et al. (2010); Amin et al. (2020)). *Given an online algorithm $\mathcal{Q}$, let $\mathcal{Q}_\mathcal{I}(X)$ denote its internal state after processing stream X, and let $X_{\leq t}$ be the first t elements of X. We say $\mathcal{Q}$ is (ε, δ)-pan-private if, for every pair of neighboring streams X and X', every time t and every set of internal state, output state pairs $T \subset \mathcal{I} \times \mathcal{O}$,*

$$\mathbb{P}_\mathcal{Q} \left[\left(\mathcal{Q}_\mathcal{I}(X_{\leq t}), \mathcal{Q}_\mathcal{O}(\mathcal{Q}_\mathcal{I}(X)) \right) \in T \right] \leq e^\varepsilon \cdot \mathbb{P}_\mathcal{Q} \left[\left(\mathcal{Q}_\mathcal{I}(X'_{\leq t}), \mathcal{Q}_\mathcal{O}(\mathcal{Q}_\mathcal{I}(X')) \right) \in T \right] + \delta. \quad (8)$$

When $\delta = 0$, we say $\mathcal{Q}$ is ε-pan-private.

C.2 ALGORITHMS

Due to the structural similarity between sequential shuffle privacy and pan-privacy, all the results developed in Section 4.1 have pan-private counterparts.

Theorem C.3. *Suppose a convex loss function ℓ is L-Lipschitz over a closed convex set $\Theta \subset \mathbb{R}^d$, then there exists an algorithm with output $\bar{\theta}$ that guarantees (ε, δ)-pan privacy, and:*

(1) When the loss function is non-smooth, then the population loss satisfies

$$\ell(\bar{\theta}, \mathcal{D}) \leq \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O \left(\frac{DL}{\sqrt{n}} + \frac{d^{1/3} DL \log^{1/3}(1/\delta)}{\varepsilon^{2/3} n^{2/3}} \right).$$

(2) When the loss function is β-smooth, then the population loss satisfies

$$\ell(\bar{\theta}, \mathcal{D}) \le \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + O\left(\frac{DL}{\sqrt{n}} + \frac{d^{2/5}\beta^{1/5}D^{6/5}L^{4/5}\log^{2/5}(1/\delta)}{\varepsilon^{4/5}n^{4/5}}\right).$$

(3) When the loss function is λ-strongly convex, then the population loss satisfies

$$\ell(\bar{\theta}, \mathcal{D}) \le \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + \tilde{O}\left(\frac{L^2}{\lambda n} + \frac{d^{2/3}L^2\log^{2/3}(1/\delta)}{\lambda \varepsilon^{4/3}n^{4/3}}\right).$$

(4) When the loss function is λ-strongly convex and β-smooth then the the population loss satisfies

$$\ell(\bar{\theta}, \mathcal{D}) \le \min_{\theta \in \Theta} \ell(\theta, \mathcal{D}) + \tilde{O}\left(\frac{L^2}{\lambda n} + \frac{d\beta^{1/2}L^2\log(1/\delta)}{\lambda^{3/2}\varepsilon^2 n^2}\right).$$

Algorithm 6 Pan-private AC-SA

Require: Batch size b, privacy parameter ε, stream length n, learning rate sequence $\{L_t\}, \{\alpha_t\}$

1: Initialize noise parameter $\zeta^2 \leftarrow \frac{8L^2\log(2/\delta)}{b^2\varepsilon^2}$
2: Initialize parameter estimate $\theta_1^{\mathsf{ag}} = \theta_1 \in \Theta$, and set number of iterations $T = \lfloor n/b \rfloor$
3: **for** $t = 1, 2, \ldots, T$ **do**
4:     Draw fresh noise $\mathbf{Z}_t \leftarrow \mathcal{N}\left(\mathbf{0}, \zeta^2\mathbf{I}_d\right)$
5:     Initialize gradient estimate $\bar{g}_t \leftarrow \mathbf{Z}_t$
6:     **for** $i = 1, 2, \ldots, b$ **do**
7:         Update gradient estimate $\bar{g}_t \leftarrow \bar{g}_t + \frac{1}{b}\nabla_\theta \ell(\theta_t^{\mathsf{md}}, x_{t,i})$
8:     **end for**
9:     $\bar{g}_t \leftarrow \bar{g}_t + \mathcal{N}\left(\mathbf{0}, \zeta^2\mathbf{I}_d\right)$
10:    Update parameter estimate $\theta_{t+1} \leftarrow \arg\min_{\theta \in \Theta}\left\{\langle \bar{g}_t, \theta - \theta_t\rangle + \frac{L_t}{2}\|\theta - \theta_t\|_2^2\right\}$
11:    Update aggregated parameter estimate $\theta_{t+1}^{\mathsf{ag}} \leftarrow \alpha_t\theta_{t+1} + (1 - \alpha_t)\theta_t^{\mathsf{ag}}$
12:    Update middle parameter estimate $\theta_{t+1}^{\mathsf{md}} \leftarrow \alpha_t\theta_{t+1} + (1 - \alpha_t)\theta_t^{\mathsf{ag}}$.
13: **end for**
14: Output $\theta_{T+1}^{\mathsf{ag}}$

Proof. We analyze the pseudocode presented in Algorithm 6. Although it does not explicitly obey the syntax of an online algorithm given in Definition C.1, it is straightforward to see that the internal state is the tuple $(\theta_t, \theta_t^{\mathsf{ag}}, \theta_t^{\mathsf{md}}, \bar{g}_t)$ and an update to $\bar{g}_t$ occurs when any data point is read. The updates to the θ variables also occur after the last data point of a batch is read.

We first prove Algorithm 6 is (ε, δ)-pan private.

Lemma C.4. *For $0 < \varepsilon, \delta < 1$, Algorithm 6 is (ε, δ)-pan-private.*

Proof. Let t^* (resp. i^*) be the batch number (resp. position within the batch) where the adversary intrudes. We will show that

$$D_\infty^\delta(\theta_{t^*}, \theta_{t^*}^{\mathsf{ag}}, \theta_{t^*}^{\mathsf{md}}, \bar{g}_{t^*}, \theta_{T+1}^{\mathsf{ag}} \| \theta_{t^*}', \theta_{t^*}^{\mathsf{ag}\,\prime}, \theta_{t^*}^{\mathsf{md}\,\prime}, \bar{g}_{t^*}', \theta_{T+1}^{\mathsf{ag}\,\prime}) \le \varepsilon$$

where the $'$ indicates variables generated from an execution on neighboring stream X'.

For neighboring streams X, X', let t denote the batch number and let i denote the number of the sample within the batch where the two streams differ. We will perform case analysis around t.

Case 1: $t^* < t$. Here, the tuple $(\theta_{t^*}, \theta_{t^*}^{\mathsf{ag}}, \theta_{t^*}^{\mathsf{md}}, \bar{g}_{t^*})$ is identically distributed with $(\theta_{t^*}', \theta_{t^*}^{\mathsf{ag}\,\prime}, \theta_{t^*}^{\mathsf{md}\,\prime}, \bar{g}_{t^*}')$ which means we only need to prove $D_\infty^\delta(\theta_{T+1}^{\mathsf{ag}} \| \theta_{T+1}^{\mathsf{ag}\,\prime}) \le \varepsilon$.

Observe that $\theta_{T+1}^{\mathsf{ag}}$ (resp. $\theta_{T+1}^{\mathsf{ag}\,\prime}$) is a post-processing of $(\theta_t, \theta_t^{\mathsf{ag}}, \theta_t^{\mathsf{md}}, \bar{g}_t)$ (resp. $(\theta_t', \theta_t^{\mathsf{ag}\,\prime}, \theta_t^{\mathsf{md}\,\prime}, \bar{g}_t')$), which means that we only need to bound $D_\infty^\delta(\theta_t, \theta_t^{\mathsf{ag}}, \theta_t^{\mathsf{md}}, \bar{g}_t \| \theta_t', \theta_t^{\mathsf{ag}\,\prime}, \theta_t^{\mathsf{md}\,\prime}, \bar{g}_t')$. Furthermore, the parameter estimates are generated from a post-processing of the gradient updates, it suffices to bound $D_\infty^\delta(\bar{g}_t \| \bar{g}_t')$ after line 9. Recall the Gaussian mechanism:

Lemma C.5. *For $\varepsilon < 1$ and function $f \colon A^n \to B^d$ on size-n databases with ℓ_2-sensitivity*

$$\Delta_2(f) = \max_{\substack{neighboring\ a,a' \in A^n}} ||f(a) - f(a')||_2$$

outputting

$$f(a) + \mathcal{N}\left(\mathbf{0}, \frac{2\Delta_2(f)^2 \log(2/\delta)}{\varepsilon^2}\mathbf{I}_d\right)$$

where $\mathbf{I}_d$ is the d-dimensional identity matrix, is (ε, δ)-centrally private.

For a proof, refer to Theorem A.1 in the survey of Dwork and Roth (Dwork and Roth, 2014).

Since ℓ is L-Lipschitz in θ, for any x we have $||\bigtriangledown_\theta \ell(\cdot, x)||_2 \leq L$. Thus

$$\max_{x,x' \in \mathcal{X}} ||\bigtriangledown_\theta \ell(\cdot, x) - \bigtriangledown_\theta \ell(\cdot, x')||_2 \leq 2L.$$

Thus if we define $f(x_{t,1}, \ldots, x_{t,b}) = \frac{1}{b}\sum_{i=1}^{b} \bigtriangledown_\theta \ell(\theta_t, x_{t,i})$, we get $\Delta_2(f) \leq \frac{2L}{b}$. By Lemma C.5, it follows that our addition of $\mathbf{Z}_t \sim \mathcal{N}\left(0, \frac{8L^2 \log(2/\delta)}{b^2 \varepsilon^2}\right)$ noise guarantees (ε, δ)-privacy

Case 2: $t^* = t$. We break into more cases around i^*.

When $i \leq i^* < b$, the adversary only observes a change to the gradient (line 7). Specifically, the tuple $(\theta_{t^*}, \theta_{t^*}^{\mathsf{ag}}, \theta_{t^*}^{\mathsf{md}}, \theta_{T+1}^{\mathsf{ag}})$ is identically distributed with $(\theta_{t^*}', \theta_{t^*}^{\mathsf{ag}}{}', \theta_{t^*}^{\mathsf{md}}{}', \theta_{T+1}^{\mathsf{ag}}{}')$ which means it suffices to prove $D_\infty^\delta(\overline{g}_t || \overline{g}_t') \leq \varepsilon$ after line 7. This follows from the privacy of the Gaussian mechanism.

When $i \leq b = i^*$, observe that the parameter updates are post-processing of the gradient update. We again use the privacy of the Gaussian mechanism.

When $i^* < i$, we re-use the arguments from Case 1. The noise from line 9 provide privacy.

Case 3: $t^* > t$. Observe that $\theta_{T+1}^{\mathsf{ag}}$ (resp. $\theta_{T+1}^{\mathsf{ag}}{}'$) is a post-processing of $(\theta_{t^*}, \theta_{t^*}^{\mathsf{ag}}, \theta_{t^*}^{\mathsf{md}}, \overline{g}_{t^*})$ (resp. $(\theta_{t^*}', \theta_{t^*}^{\mathsf{ag}}{}', \theta_{t^*}^{\mathsf{md}}{}', \overline{g}_{t^*}')$), which means that we only need to bound $D_\infty^\delta(\theta_{t^*}, \theta_{t^*}^{\mathsf{ag}}, \theta_{t^*}^{\mathsf{md}}, \overline{g}_{t^*} || \theta_{t^*}', \theta_{t^*}^{\mathsf{ag}}{}', \theta_{t^*}^{\mathsf{md}}{}', \overline{g}_{t^*}')$. But the random variables in question are obtained by post-processing $(\theta_t, \theta_t^{\mathsf{ag}}, \theta_t^{\mathsf{md}}, \overline{g}_t)$ and $(\theta_t', \theta_t^{\mathsf{ag}}{}', \theta_t^{\mathsf{md}}{}', \overline{g}_t')$. We use the same line of reasoning as Case 1 to bound the divergence. $\qquad\square$

The main tool for our utility guarantees is bounding the variance of the noise added for privacy, analogous to the variance guarantee of Theorem 3.2. Once we have that result, the remaining analyses are essentially unchanged from their shuffle counterparts, apart from slightly different choices for parameters b and β, which are straightforward algebraic consequences of the different variance guarantee. As a result, we only bound the variance.

For each time step $t \in [T]$, the gradient $\overline{g}_t = \frac{1}{b}\sum_{i=1}^{b} \nabla_\theta \ell(\theta_{t-1}, x_{t,i}) + \mathbf{Z}_{t,a} + \mathbf{Z}_{\mathbf{t,b}}$, where $\mathbf{Z}_{t,a}, \mathbf{Z}_{t,b} \sim \mathcal{N}\left(\mathbf{0}, \zeta^2 \mathbf{I}_d\right)$. It is clearly an unbiased estimator and the variance satisfies

$$\mathbb{E}_{x_{t,1},\ldots,x_{t,b},\mathbf{Z}_{t,a},\mathbf{Z}_{t,b}}\left[\left|\left|\frac{1}{b}\sum_{i=1}^{b}\nabla_\theta\ell(\theta_{t-1}, x_{t,i}) + \mathbf{Z}_{t,a} + \mathbf{Z}_{\mathbf{t,b}} - \mathbb{E}_{x \sim \mathcal{D}}\left[\nabla\ell(\theta_{t-1}, x)\right]\right|\right|_2^2\right]$$

$$= \mathbb{E}_{x_{t,1},\ldots,x_{t,b}}\left[\left|\left|\frac{1}{b}\sum_{i=1}^{b}\nabla\ell(\theta_{t-1}, x_{t,i}) - \mathbb{E}_{x \sim \mathcal{D}}\left[\nabla\ell(\theta_{t-1}, x)\right]\right|\right|_2^2\right] + \mathbb{E}\left[||\mathbf{Z}_{t,a}|_2^2\right] + \mathbb{E}\left[||\mathbf{Z}_{t,b}||_2^2\right]$$

$$= \frac{1}{b}\mathbb{E}_{x_t \sim \mathcal{D}}\left[||\nabla\ell(\theta_{t-1}, x_t) - \mathbb{E}_x\left[\nabla\ell(\theta_{t-1}, x)\right]||_2^2\right] + \mathbb{E}\left[||\mathbf{Z}_{t,a}||_2^2\right] + \mathbb{E}\left[||\mathbf{Z}_{t,b}||_2^2\right]$$

$$= O\left(\frac{L^2}{b} + \frac{dL^2 \log(1/\delta)}{b^2 \varepsilon^2}\right).$$

The first step follows from the fact that the noise $\mathbf{Z}_{t,a}, \mathbf{Z}_{t,b}$ is independent of the data $x_{t,1}, \cdots, x_{t,b}$, and the second step follows from the independence of $x_{t,1}, \cdots, x_{t,b}$. The last step follows from $\mathbf{Z}_{t,a}, \mathbf{Z}_{t,b} \sim \mathcal{N}\left(\mathbf{0}, \zeta^2 \mathbf{I}_d\right)$ and $\zeta^2 \leftarrow \frac{8L^2 \log(2/\delta)}{b^2 \varepsilon^2}$. $\qquad\square$