RECURRENT MODEL-FREE RL IS A STRONG BASELINE FOR MANY POMDPS

ABSTRACT

Many problems in RL, such as meta RL, robust RL, and generalization in RL can be cast as POMDPs. In theory, simply augmenting model-free RL with memory, such as recurrent neural networks, provides a general approach to solving all types of POMDPs. However, prior work has found that such *recurrent model-free RL* methods tend to perform worse than more specialized algorithms that are designed for specific types of POMDPs. This paper revisits this claim. We find that a careful architecture and hyperparameter decisions yield a recurrent model-free implementation that performs on par with (and occasionally substantially better than) more sophisticated recent techniques in their respective domains. We also release a simple and efficient implementation of recurrent model-free RL for future work to use as a baseline for POMDPs.[1]

1 INTRODUCTION

While reinforcement learning (RL) is often cast as the problem of learning a single fully observable task, also known as MDP, training and testing on that same task, most real-world applications of RL demand some degree of transfer and partial observability. For example, visual navigation (Zhu et al., 2017) requires adaptation to unseen scenes with occlusion in observations, and human-robot collaboration requires that robots infer the intentions of human collaborators. (Chen et al., 2018).

Many subareas in RL study problems that are special cases of POMDPs, and we summarize them in Table 1. For example, meta RL (Schmidhuber, 1987; Thrun & Pratt, 2012; Duan et al., 2016; Wang et al., 2017) is a POMDP where certain aspects of the reward function or (less commonly) dynamics function are unobserved but held constant through one

Figure 1: **Implementation Matters for Recurrent Model-Free RL.** This paper identifies key design decisions for recurrent model-free RL that not only outperforms prior implementations (e.g. PPO-GRU and A2C-GRU from Kostrikov (2018) in the figure), but also outperforms purpose-designed methods (e.g. VRM from Han et al. (2020) in the figure).

episode. The robust RL problem (Bagnell et al., 2001; Rajeswaran et al., 2016; Pattanaik et al., 2017; Pinto et al., 2017) assumes that certain aspects of the dynamics or reward function are unknown, with the aim of finding optimal policies that perform against adversarially-chosen perturbations. Generalization in RL (Whiteson et al., 2011; Zhang et al., 2018a; Packer et al., 2018; Cobbe et al., 2019) focuses on unobserved aspects of the dynamics or reward function that are novel during testing, using an average-case objective instead of a worst-case objective like robust RL. Recent work has proposed efficient and performant algorithms for solving these *specialized* problem settings. However, these algorithms often make assumptions that preclude their application to other classes of POMDPs. For example, methods for robust RL are rarely used for the meta RL setting due to objective mismatch; methods for meta RL are rarely used for general POMDPs due to the stationarity assumption in meta RL.

---

[1]Code is available: https://drive.google.com/drive/folders/1I5mLlKPf2Gmdpm0nzy9OkR494nCJll1g

Nonetheless, many prior works have used a simple baseline that is applicable to all POMDPs (Packer et al., 2018; Igl et al., 2018; Rakelly et al., 2019; Yu et al., 2020): model-free RL equipped with a recurrent policy and (sometimes) value function (Duan et al., 2016; Wang et al., 2017; Fakoor et al., 2020). We will refer to this approach as *recurrent model-free RL.* This baseline is simultaneously simple (requiring changing only a few lines of code from a model-free RL algorithm) and general. However, prior work has consistently found that recurrent model-free RL performs poorly across a wide range of problem settings, including meta RL (Rakelly et al., 2019; Zintgraf et al., 2020), general POMDPs (Igl et al., 2018; Han et al., 2020), robust RL (Zhang et al., 2021), and generalization in RL (Packer et al., 2018). One common explanation is that specialized algorithms that are tailored to specific types of POMDPs are very likely to outperform recurrent model-free RL because they (implicitly) encode inductive biases for solving these specific tasks. For example, algorithms for meta RL may leverage the assumption that the underlying dynamics (while unknown) are fixed and the underlying goals are fixed within one episode (Rakelly et al., 2019; Zintgraf et al., 2020); algorithms for robust RL may assume that the dynamics parameters are known (Rajeswaran et al., 2016) and dynamics is Lipschitz continuous (Jiang et al., 2021).

This paper challenges this explanation. We argue that, contrary to popular belief, recurrent model-free RL is competitive with recent state-of-the-art algorithms across a range of different POMDP settings. Similar to prior work in Markovian on-policy RL methods (Engstrom et al., 2019; Andrychowicz et al., 2020), our experiments show that implementation in recurrent model-free RL matters. Fig. 1 shows a typical scenario in PyBullet occlusion environments (Coumans & Bai, 2016) to support this argument. Through extensive experiments, we show that the careful design and implementation of recurrent model-free RL is critical to its performance. Design decisions, such as the actor-critic architecture, conditioning on previous actions and/or rewards, the underlying model-free RL algorithms, and context length in RNNs, are especially important.

The main contribution of this paper is a performant implementation of recurrent-model free RL. We demonstrate that simple yet important design decisions, such as the underlying RL algorithm and the context length, yield a recurrent model-free RL algorithm that performs on par with prior specialized POMDP algorithms *on the environments those algorithms were designed to solve.* Ablation experiments identify the importance of these design decisions. We also open-sourced our code that is easy to use and memory-efficient.

2 BACKGROUND

In this section, we introduce the notation for MDPs and POMDPs.

MDP. A Markov decision process (MDP) (Bellman, 1957) is a tuple $(\mathcal{S}, \mathcal{A}, T, T_0, R, H, \gamma)$, where $\mathcal{S}$ is the set of states, $\mathcal{A}$ is the set of actions, $T : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to [0,1]$ is the transition function (dynamics), $T_0 : \mathcal{S} \to [0,1]$ is the initial state distribution, $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ is the reward function, $H \in \mathbb{N}$ is the time horizon, and $\gamma \in [0,1)$ is the discount factor. Solving a MDP requires learning a memoryless policy $\pi : \mathcal{S} \times \mathcal{A} \to [0,1]$ that maximizes the expected discounted return: $\pi^* = \arg\max_\pi \mathbb{E}_{s_t,a_t,r_t \sim T,\pi} \left[\sum_{t=0}^{H-1} \gamma^t r_{t+1} \mid s_0 \right]$. For any MDP, there exists an optimal policy that is both memoryless and deterministic (Puterman, 2014). MaxEnt RL algorithms (Ziebart, 2010), such as the SAC (Haarnoja et al., 2018a), augment the RL objective by adding an entropy bonus to the reward.

POMDP. A partially observable Markov decision process (POMDP) (Åström, 1965) is a tuple $(\mathcal{S}, \mathcal{A}, \mathcal{O}, T, T_0, O, O_0, R, H, \gamma)$, where the underlying process is an MDP $(\mathcal{S}, \mathcal{A}, T, T_0, R, H, \gamma)$. Let $\mathcal{O}$ be the set of observations and let $O : \mathcal{S} \times \mathcal{A} \times \mathcal{O} \to [0,1]$ be the emission function. Let the observable trajectory up to time-step t be $\tau_{0:t} = (o_0, a_0, o_1, r_1, \ldots, a_{t-1}, o_t, r_t)$, the memory-based policy in *the most general* form is defined as $\pi(a_t \mid \tau_{0:t})$, conditioning on the whole history. At the first time step $t = 0$, an initial state $s_0 \sim T_0(\cdot)$ and initial observation $o_0 \sim O_0(\cdot \mid s_0)$ are sampled. At any time-step $t \in \{0, \ldots, H-1\}$, the policy emits the action $a_t \in \mathcal{A}$ to the system, the system updates the state following the dynamics, $s_{t+1} \sim T(\cdot \mid s_t, a_t)$, then the next observation is sampled $o_{t+1} \sim O(\cdot \mid s_{t+1}, a_t)$ and the reward is computed as $r_{t+1} = R(s_t, a_t, s_{t+1})$.

We refer to the part of the state s_t at current time-step t that can be directly unveiled from *current* observation o_t as the *observable state* s_t^o, and the rest part of the state as the *hidden state* s_t^h.

Table 1: **The summary of selected POMDP subareas.** For each subarea, we list the information of the hidden state s^h including its appearance in dynamics and reward function and its stationarity during one trajectory. We also list the policy input space that are connected with the hidden states, where o, a, r, and d refer to the sequence of observations, actions, rewards, and done signals, respectively. Finally, we list the RL objective in terms of average-case or worst-case, and whether there is domain shift between training and testing environments. We append the check (✓) or cross mark (✗) with * if it applies to some but not all the work in that subarea. The notation in this table will be covered in Sec. 2.

Subarea	s^h in dynamics?	s^h in reward?	Is s^h stationary?	Policy input space	RL objective	Domain shift?
"Standard" POMDP	✓	✓	✗	oar	Avg	✗
Meta RL	✗*	✓	✓	oard	Avg	✗
Robust RL	✓*	✗*	✓*	oa	Worst	✗
Generalization in RL	✓*	✗*	✓*	oa	Avg	✓*

Specifically, if the hidden state s_t^h does not change w.r.t. the time-step t for one trajectory in a POMDP, we call the hidden state *stationary*. In this scenario, the policy objective can be rewritten as $\pi^* = \arg\max_\pi \mathbb{E}_{s^h \sim T_0}\left[\mathbb{E}_{s_t,a_t,r_t \sim T,O,O_0,\pi}\left[\sum_{t=0}^{H-1}\gamma^t r_{t+1} \mid s^h\right]\right]$ for the average-case POMDP objective, or $\pi^* = \arg\max_\pi \min_{s^h \in \text{supp}(T_0)} \mathbb{E}_{s_t,a_t,r_t \sim T,O,O_0,\pi}\left[\sum_{t=0}^{H-1}\gamma^t r_{t+1} \mid s^h\right]$ for the worst-case POMDP objective.

3 RELATED WORK

In this section, we discuss several subareas of RL that both explicitly and implicitly solve POMDPs, as well as algorithms proposed for these specialized settings. Table 1 summarizes these subareas.

RL for "Standard" POMDPs. We use the term "standard" to refer to prior work that explicitly labels the problems studied as POMDPs. Common tasks include scenarios where the states are partially occluded (Heess et al., 2015), different states correspond to the same observation (perceptual aliasing (Whitehead & Ballard, 1990)), random frames are dropped (Hausknecht & Stone, 2015), observations use egocentric images (Zhu et al., 2017), or the observations are perturbed with random noise (Meng et al., 2021). These POMDPs often have hidden states that are non-stationary and affect both the rewards and the dynamics. POMDPs are hard to solve (Papadimitriou & Tsitsiklis, 1987; Littman, 1996) because of the curse of dimensionality: the size of the history grows linearly with the horizon length. Many prior POMDP algorithms (Cassandra et al., 1994; Kaelbling et al., 1998) attempt to infer the state from the past sequence of observations, and then apply standard RL techniques to that inferred state. However, the exact inference requires the knowledge of the dynamics, emission, and reward functions, and is intractable in all except the most simple settings. A common strategy for solving these general POMDPs is to use recurrent policies, which take the entire history of past observations as inputs (Schmidhuber, 1991; Bakker, 2001; Wierstra et al., 2007). This strategy is very simple and general, and can be applied to arbitrary tasks without knowledge of the task structure (e.g., whether the hidden states change within an episode) across long time horizons (Duan et al., 2016). These recurrent strategies can be further subdivided into model-free methods (Heess et al., 2015; Hausknecht & Stone, 2015; Meng et al., 2021) , where the single objective is to maximize the return, and model-based methods (Watter et al., 2015; Ha & Schmidhuber, 2018; Igl et al., 2018; Han et al., 2020) that have explicit objectives on modeling the belief states and use them as the inputs of memoryless policies. The recurrent model-free RL that we focus on belongs to the class of model-free off-policy memory-based algorithms.

Meta RL. Meta RL, also called "learning to learn" (Schmidhuber, 1987; Thrun & Pratt, 2012), focuses on POMDPs where some parameters in the rewards or (less commonly) dynamics are varied from episode to episode, but remain fixed within a single episode, which represent different *tasks* with different values (Humplik et al., 2019). The meta-RL setting is almost the same as multi-task RL (Wilson et al., 2007; Yu et al., 2020), but differs in that multi-task RL can observe the task parameters, making it a MDP instead of a POMDP. Algorithms for meta RL can be roughly categorized based on how the adaptation step is performed. Gradient-based algorithms (Hochreiter et al., 2001; Finn et al., 2017; Fakoor et al., 2020) run a few gradient steps on the pre-trained models to adapt.

Memory or context-based algorithms use RNNs to implicitly adapt, which can be further subdivided into implicit and explicit task inference methods. Implicit task inference methods (Wang et al., 2017; Duan et al., 2016) use RL objective only to learn recurrent policies. Explicit task inference methods (Zintgraf et al., 2020; Rakelly et al., 2019) train an extra inference model to explicitly estimate task embeddings (i.e., a representation of the unobserved parameters) by variational inference. The task embeddings are then used as additional inputs to memoryless policies.

Robust RL.   The goal of robust RL is to find a policy that maximizes returns in the worst-case environments. Early work in the control and operations research community (Khalil et al., 1996; Nilim & El Ghaoui, 2005) and RL community (Bagnell et al., 2001; Morimoto & Doya, 2005) focused on linear or finite systems. Prior work designs deep RL algorithms that are robust against a variety of adversarial attacks, including attacks on the dynamics (Rajeswaran et al., 2016; Jiang et al., 2021), observations (Pattanaik et al., 2017; Huang et al., 2017; Zhang et al., 2021), and actions (Pinto et al., 2017; Gleave et al., 2019; Tessler et al., 2019). Treating the robust RL problem as a POMDP, rather than an MDP (as done in most prior work), unlocks a key capability for RL agents, because agents can use their memory to identify the hidden states of the current adversarial environment, although previous work (Rajeswaran et al., 2016; Jiang et al., 2021) only train Markovian policies on POMDPs. While some work find memory-based policies are more robust to the adverarial attacks than Markovain policies (Russo & Proutiere, 2019; Zhang et al., 2021), they train these baselines in a single MDP without adversaries, which differs from our training setting where the recurrent model-free RL can have access to a set of MDPs.

Generalization in RL.   The goal of generalization in RL is to make RL algorithms perform well in test domains that are unseen during training, which emphasizes the average case on the novel test domains instead of the worse case in the possibly seen test domains as in robust RL. Prior work have studied generalization to initial states in the same MDP (Whiteson et al., 2011; Rajeswaran et al., 2017; Zhang et al., 2018b), random disturbance in dynamics (Rajeswaran et al., 2017), states (Stulp et al., 2011), observations (Zhang et al., 2018a; Song et al., 2019), and actions (Srouji et al., 2018), and different modes in procedurally generated games (Justesen et al., 2018; Farebrother et al., 2018; Cobbe et al., 2019). Among them, Packer et al. (2018) provides a benchmark on both in-distribution (ID) and out-of-distribution (OOD) generalization to different dynamics parameters, and Zhao et al. (2019) extends the benchmark by introducing random noise in states, observations, and actions. Algorithms for improving generalization in RL can be roughly divided into classic regularization methods such as weight decay, dropout, batch normalization, and entropy regularization (Farebrother et al., 2018; Cobbe et al., 2020; Igl et al., 2019), model architectures (Srouji et al., 2018; Raileanu & Fergus, 2021), data augmentation through randomization (Tobin et al., 2017; Lee et al., 2020), Although introducing observational noise and the change in dynamics parameters will transform MDPs to POMDPs, few work study memory-based policies such as model-free recurrent RL with mixed results. Same algorithm RL2 (Duan et al., 2016) was found to perform badly in Packer et al. (2018) but relatively well in Yu et al. (2020).

4   DESIGN CONSIDERATIONS FOR RECURRENT MODEL-FREE RL

Implementing a recurrent model-free RL algorithm requires making a number of design decisions. This section describes the decisions that we found most important to make recurrent model-free RL competitive with more complex, recent algorithms. We will focus on continuous control problems with state-based inputs (i.e., not image-based inputs). Importantly, we assume that the policy can observe the *reward* and *done* signals (the end of one episode during one trial (Duan et al., 2016)) from the environment during *evaluation*. This assumption is common in prior work (Zintgraf et al., 2020; Han et al., 2020), but many recurrent model-free implementations do not provide the agent with information. In the following paragraphs, we will describe the important decision factors in recurrent model-free RL. Table 2 summarizes how prior work and our method makes these design decisions when implementing recurrent model-free RL.

Recurrent Actor-Critic Architecture.   The first important design decision is whether the recurrent policy (actor) and the recurrent Q-value function (critic) use *shared* RNN encoder (and embedders) or use *separate* ones. In the experiment section (Sec. 5.2) we will show that a shared encoder would cause large gradient norm in the recurrent actor-critic and thus hinder learning, while separate

Table 2: **How the prior work and our method implement the recurrent model-free RL as their own method or baseline.** We can see that none of the prior work share the exact same set of decision variables, some of which have bad choices that may lead to poor performance reported in the prior work. Our method covers a wide range of choices in these decision factors and find the combinations showed in the last rows that lead to **the best performance in terms of the average performance** across the experimented environments in each subarea.

Algorithm	Domain	Arch	Encoder	Inputs	Len	RL
Duan et al. (2016)	Meta RL	separate	GRU	`oard`	1000	TRPO, PPO
Wang et al. (2017)	Meta RL	shared	LSTM	`oart`	5-150	A2C
Baseline from Rakelly et al. (2019)	Meta RL	separate	GRU	`oard`	100	PPO
Baseline from Zintgraf et al. (2020)	Meta RL	separate	GRU	`oar`	Max	A2C
Baseline from Fakoor et al. (2020)	Meta RL	separate	GRU	`oar`	10-25	TD3
Baseline from Yu et al. (2020)	Meta RL	separate	GRU	`oard`	500	PPO
Kostrikov (2018)	POMDP	shared	GRU	`o`	5-2048	PPO, A2C
Dong et al. (2020)	POMDP	separate	LSTM	`oa`	150	TD3, SAC
Meng et al. (2021)	POMDP	separate	LSTM	`oa`	1-5	TD3
Baseline from Igl et al. (2018)	POMDP	shared	GRU	`oa`	25	A2C
Baseline from Han et al. (2020)	POMDP	shared	LSTM	`o`	64	SAC
Baseline from Zhang et al. (2021)	Robust RL	separate	LSTM	`o`	100	PPO
Baseline1 from Packer et al. (2018)	Generalization	shared	LSTM	`o`	128-512	PPO, A2C
Baseline2 from Packer et al. (2018)	Generalization	separate	LSTM	`oard`	128-512	PPO, A2C
Our method	Meta RL	separate	LSTM	`oar`	64	TD3
Our method	POMDP	separate	GRU	`oa`	64	TD3
Our method	Robust RL	separate	LSTM	`o`	64	TD3
Our method	Generalization	separate	LSTM	`o`	64	TD3

encoders can greatly mitigate this issue and learn efficiently. This echoes prior work (Fakoor et al., 2020; Dong et al., 2020; Meng et al., 2021) that also use separate encoders in their recurrent actor-critic. To avoid running an inordinate number of experiments, we will use the *separate* architecture in the rest of the paper.

Policy Input Space. The next consideration is the input space of the model-free policy. The maximal input space of policy to emit an action a_t at time t, should be the history of all quantities that the policy has observed, namely the past observations $o_{0:t}$, the past actions $a_{0:t-1}$, the past rewards $r_{0:t}$, and the past done signals $d_{0:t}$, which was already employed in the early work (Duan et al., 2016). Generally, the input space of optimal policy should only depend on the quantities that have connections with *hidden states* (defined in Sec. 2) (Poupart & Boutilier, 2003; Izadi & Precup, 2005). We show the policy input spaces that are connected with the hidden states for the discussed subareas in the "Inputs" column of Table 1. While prior work often only conditions the recurrent RL baseline on previous observations (and actions) (Igl et al., 2018; Kostrikov, 2018; Han et al., 2020; Dong et al., 2020; Meng et al., 2021), our experiments in Sec. 5.2 find that additionally conditioning on other previous information, such as previous rewards, can increase reward by up to 30%.

Model-free RL Algorithms. Recurrent model-free RL can be understood as applying an off-the-shelf model-free RL algorithm with an actor and a Q function parametrized to take sequences of inputs. As such, the choice of the underlying model-free RL algorithm is paramount. Most prior work on continuous control POMDP problems used *on-policy* algorithms, such as A2C (Mnih et al., 2016), TRPO (Schulman et al., 2015) or PPO (Schulman et al., 2017). While *off-policy* algorithms such as TD3 (Fujimoto et al., 2018) and SAC (Haarnoja et al., 2018a;b) greatly improve the performance in continuous control MDP problems in terms of sample efficiency and asymptotic performance, these methods are rarely used in recurrent model-free RL baselines (Rakelly et al., 2019; Zintgraf et al., 2020; Zhang et al., 2020). In the experiment section (Sec. 5.1), we will show that using these off-policy algorithms for recurrent model-free RL provide results that are better than using on-policy algorithms and are comparable to their specialized methods in POMDP. This echoes the finding that model-free off-policy TD3-Context (Fakoor et al., 2020) can be better than the specialized method PEARL (Rakelly et al., 2019) in meta RL.

RNN Variants and Context Length. RNN training is known to be unstable, especially with long sequences input (Bengio et al., 1994). The RNN variants like LSTM (Hochreiter & Schmidhuber, 1997) and GRU (Chung et al., 2014) mitigate the training issues, but still may fail to learn long-term dependencies (Trinh et al., 2018). In POMDP problems, these dependencies reflect the memory that

an agent must have to solve a task. For example, a POMDP that hides velocities from observations theoretically requires a short memory length to infer velocities through consecutive positions (Meng et al., 2021). Prior work in POMDPs choose a variety set of context lengths for RNNs from 1 to 2048 (see the "Len" column of Table 2), and we select three representatives of short (5), medium (64), and long length (larger than 100) in the experiments (Sec. 5) for comparison. We also try both LSTM and GRU as RNN variants to compare their performance. We find that the optimal context length and RNN variant are task specific (see Sec. 5.2).

5 EXPERIMENTS

Our experiments aim to answer two questions. First, how does a *well-tuned* implementation of recurrent model-free RL compare to specialized POMDP methods, such as purpose-designed meta RL and robust RL algorithms. To give these prior methods the strongest possible footing, we will compare prior methods on the specific problem types for which they were developed (i.e., meta RL algorithms are tested on meta RL tasks). Our second question studies which design decisions are important for recurrent model-free RL. Due to the space limit, we put the environment details in Appendix C.

Code Implementation. We release a modular and highly-configurable implementation of recurrent (off-policy) model-free RL: url. Our implementation is efficient in terms of computer memory compared to previous off-policy RL methods for POMDPs (200x less RAM than Han et al. (2020) and 9x less GPU memory than Dorfman et al. (2020)). Please see the appendix A for details, including an explanation of why our implementation is more memory-efficient than prior work.

5.1 RECURRENT MODEL-FREE RL IS COMPARABLE WITH PRIOR SPECIALIZED METHODS

While prior work has studied a range of different POMDP settings (e.g., meta RL, occluded observations), recurrent model-free RL is a ubiquitous baseline (Rakelly et al., 2019; Zintgraf et al., 2020; Humplik et al., 2019; Igl et al., 2018; Han et al., 2020). However, prior work consistently reports that this baseline is reported to be unperformed to more specialized methods. This section casts doubt on that claim, showing that a well-tuned implementation of recurrent model-free RL can perform *at least* as well as more specialized methods.

We study four subareas of POMDPs: the "standard" POMDP, meta RL, robust RL, and generalization in RL. We tune a wide range of decision factors shown in Sec. 4 in our implemented recurrent model-free RL. Appendix A.3 shows the details of the tuning options. For each subarea, we show the performance of **a single variant** that works best across the environments in that subarea, compared with compared with the prior specialized methods in this subsection. In other words, the following bar charts of each subarea reports **the same model-free recurrent RL algorithm** with the same hyperparameters. The exact configurations of each subarea can be found in the last four rows of Table 2. Under this restricted setting, we find that our implementation can actually outperform prior (specialized) methods by a wide margin across the four subareas. We show the full learning curves that generate the following the bar charts in Appendix D.1 due to space limit. The evaluation details on how to generate the bar charts can be seen in Appendix B.

"Standard" POMDP. Our first experiments look at the "standard" POMDPs that typically occlude some part of states in the environment. We will compare against **VRM** (Han et al., 2020), a recent state-of-the-art model-based POMDP algorithm. We directly apply the environment design of VRM paper that occludes either positions&angles or velocities of the simulated robot in PyBul-

Figure 2: Final returns of our implemented recurrent model-free RL algorithm with the same hyperparameters, and the prior method VRM (Han et al., 2020) across the eight environments in **"standard" POMDPs**, each of which trained in 0.5M simulation steps.

let (Coumans & Bai, 2016). There are 8 environments {Hopper, Ant, Walker, Cheetah}-{P,V}, where "-P" stands for observing positions&angles only, and "-V" stands for observing velocities only. Fig. 2 shows that the best single variant of our model-free recurrent RL implementation outperform VRM in 7 out of 8 environments, especially in {Cheetah,Hopper}-{P,V}. Our results suggest that, while the variational dynamics model used by VRM may be useful for some tasks, a simple recurrent model-free RL baseline can outperform VRM if properly tuned. While we are primarily interested in sample complexity, but not compute, it is worth noting that our recurrent model-free RL implementation is substantially more efficient than the open-source VRM implementation, training 5× faster and requiring at most 200× less RAM usage (see Appendix A). Note that both Fig. 1 and Fig. 2 shows the final performance of the same single variant of our implementation, but the former shows our results with 1.5M simulation steps while the latter shows our results with 0.5M simulation steps to match with those of VRM due to the time budget.

Meta RL. We next compare the recurrent model-free RL to the meta RL setting, where some indicator of the task is unobserved. We compare our implementation of recurrent model-free RL to a specialized state-of-the-art method, **VariBAD** (Zintgraf et al., 2020) that explicitly learns the task embeddings by variational model-based objectives. We make VariBAD even stronger by replacing RL algorithm PPO with SAC as Dorfman et al. (2020). We adopt the three environments used in Dorfman et al. (2020) for experiments, including Semi-Circle and Cheetah-Vel, and we also adapt Wind to make it harder to solve. Figure 3 shows that our best single variant outperforms VariBAD in the three meta RL environments, especially in Cheetah-Vel. Prior work (Rakelly et al., 2019; Zintgraf et al., 2020) show that disentangling task inference and control can stabilize training. However, our experiments suggest that joint training of task inference and control could also have comparable per-

Figure 3: Final returns of our implemented recurrent model-free RL algorithm with the same hyperparameters, and the prior method VariBAD (Zintgraf et al., 2020; Dorfman et al., 2020) across the three environments in **meta RL**. Our method and VariBAD are trained with the same number of simulation steps in each environment.

formance if well implemented. Additionally, because our method is trained end-to-end, without using pre-trained task representations saved in the replay buffer like the off-policy version of VariBAD (Dorfman et al., 2020), our implementation does not have non-stationarity issue in task representations.

Robust RL. Thirdly, we focus on the robust RL that aims to maximize the worst returns over the tasks. We choose the recent specialized algorithm **MRPO** (Jiang et al., 2021) as the compared method, and adopt their used environments based on SunBlaze benchmark (Packer et al., 2018). These environment have hidden states that are fixed during one episode, including the density and the friction coefficients of the simulated robots, namely {Cheetah, Hopper, Walker}-Robust. Fig. 4 shows

Figure 4: Final **average returns** (left figure) and **worst returns** (right figure) of our implemented recurrent model-free RL algorithm with same hyperparameters, and prior method MRPO (Jiang et al., 2021) across the three environments in **robust RL**. Our method are trained with 3M simulation steps while MRPO is trained with over 15M steps.

both the average return and worst return of our single best variant and MRPO on the three environments, where the worst return is measured by the average return in the worst 10% testing tasks following the practice in Jiang et al. (2021). The results are quite surprising: although our method, using average-case RL objective, is not expected to surpass MRPO in worst return, we found that our best variant greatly outperforms the specialized MRPO in both average return and worst return, with over 80% fewer simulation steps. Our method benefit from its memory and off-policy algorithms, while MRPO might suffer from its Markovian on-policy algorithm and a bit ideal Lipschitz assumption in dynamics. Nevertheless, our method is around 17.5x slower than MRPO given the same simulation steps (see Appendix A), so we only run it with 3M steps with limited time budget.

Generalization in RL. Finally, we focus on the SunBlaze benchmark from Packer et al. (2018) for investigating generalization in RL, including {Hopper, Cheetah}-Generalize. We pick the best specialized method in the tables of final performance in Packer et al. (2018), Markovian on-policy robust RL method **EPOpt-PPO-FF** (Rajeswaran et al., 2016). Fig. 5 show the interpolation and extrapolation success rates, where in the interpolation the testing tasks have same distribution of hidden states as

Figure 5: Final **success rates in interpolation setting** (left figure) and **success rates in extrapolation setting** (right figure) of our implemented recurrent model-free RL algorithm with same hyperparameters, and prior method EPOpt-PPO-FF (Rajeswaran et al., 2016) across the two environments in **generalization in RL**. Our method are trained with 3M simulation steps while EPOpt-PPO-FF is trained to convergence.

that of the training tasks, while in the extrapolation the testing distribution is disjoint from that of training. We can see that our model-free method is on par with the EPOpt-PPO-FF in the interpolation benchmark, while EPOpt-PPO-FF requires the access to the dynamics parameters but ours not. In the extrapolation benchmark, our method greatly outperforms the previous method, although our objective does not consider extrapolation.

Overall, we can see that with careful tuning on recurrent model-free RL, it can at least perform as well as the specialized or more complicated methods, in various kinds of POMDPs.

5.2 WHAT MATTERS IN RECURRENT MODEL-FREE RL ALGORITHMS?

In the previous subsection, we showed that recurrent model-free RL can perform on par with the specialized (state-of-the-art) methods, then a natural question comes: Why our implementation of recurrent model-free RL outperforms the implementation used in prior work?

Our analysis will focus on ablating the five important design decisions introduced in Sec. 4: the actor-critic architecture (`Arch`), the policy input space (`Inputs`), the underlying model-free RL algorithm (`RL`), the RNN encoder (`Encoder`), and the RNN context length (`Len`). See Table. 2 for a summary of how prior work made these design decisions. Due to the space limit, we show the ablation results in some but not all the environments, to compare the performance between the best single variant and the other variant that only differs in one decision factor. We also provide "single factor analysis" plots for each decision factor by averaging the performance over the other factors in Appendix D.2.

Recurrent Actor-Critic Architecture. First, we ran some experiments with both shared and separate architectures on two toy POMDP environments. Fig. 6 show the results in one of them (see Appendix D.3 for the other). We can see that the shared architecture failed to learn, compared to the separate architecture. The large RNN gradient norm in the shared architecture suggests that the actor and critic losses may cause conflicts in the shared RNN training. Our results echo prior work (Fakoor et al., 2020; Meng et al., 2021) that only consider *separate* RNN encoders that can achieve high asymptotic

Figure 6: **Comparison between *shared* and *separate* recurrent actor-critic architecture** with all the other hyperparameters same, on Semi-Circle, a toy meta RL environment. We show the performance metric (left) and also gradient norm of the RNN encoder(s) (right, in **log-scale**). For the separate architecture, `:critic` and `:actor` refer to the separate RNN in critic and actor networks, respectively.

rewards, and also echo that (Han et al., 2020) shows poor results in the *shared* architecture of SAC-LSTM.

Policy Input Space. The 1st row of Table 3 shows the effect of policy input space in a POMDP environment Walker-P. The reward signals could help reveal the missing information of the velocity

Change in one decision factor	Subarea	Env	Performance comparison
`Inputs: oa → oar`	"Standard" POMDP	Walker-P	981.6 → 1345.0 (1.3×)
`RL: TD3 → SAC`	"Standard" POMDP	Ant-P	310.7 → 2123.5 (6.8×)
`Encoder: LSTM → GRU`	Robust RL	Walker-Robust	765.9 → 931.3 (1.2×)
`Len: 64 → 400`	Meta RL	Cheetah-Vel	-85.2 → -74.6 (+14%)
`Len: 64 → 5`	Generalization	Hopper-Generalize	0.292 → 0.415 (1.4×)
`Len: 64 → 5`	"Standard" POMDP	Walker-V	121.4 → 264.3 (2.2×)

Table 3: **Ablation results in our implementation of recurrent model-free RL.** In this table, we show how a single change in one decision factor from the variant that is best on average in that subarea, could significantly increase the performance. The first column shows how we change the single decision factor, and the last column shows the performance comparison between **the best variant in that subarea** (left) and **the ablated one** (right). For robust RL and generalization in RL, we show the performance metric in worst returns and extrapolation success rates, respectively.

of the robot base, which is occluded in Walker-P. Therefore, it is reasonable that adding previous rewards into policy inputs can increase the performance.

Model-free RL Algorithms. The 2nd row of Table 3 shows the effect of RL algorithm in a POMDP environment Ant-P. We can see that SAC is significantly better than TD3 (increase by 6.8×, surpassing the PPO-GRU (Kostrikov, 2018) in Fig. 1), possibly due to strategic exploration where the action noise conditions on the history instead of being independent. This is prominent mainly in Ant-P because Ant-P might be much harder than the other POMDP environments.

RNN Variants and Context Length. The 3rd row of Table 3 shows the effect of RNN encoder in a robust RL environment. We can see replacing LSTM with GRU can increase the worst-case metric in Walker-Robust. The remaining rows of Table 3 show the mixed effects of context length in RNNs. As we can see, both increasing and decreasing the context length can boost the performance in different environments. Specifically, decreasing the length from 64 to 5 makes our method surpass VRM in Walker-V (increase by 2.2×). This might explain why the prior methods adopt a wide range of context lengths from 1 to 2048 (see Table 2). Therefore, the choice of context length is rather problem-specific that requires some extent of tuning.

Summary. We now summarize the main findings of our experiments:

1. Using separate weights for the recurrent actor and recurrent critic boosts performance, likely because it avoids gradient explosion (Fig. 6).
2. Using state-of-the-art off-policy RL algorithms as the backbone in recurrent model-free RL can improve asymptotic performance (Fig. 1).
3. The context length for the recurrent actor and critic has a large influence of task performance, but the optimal length is task specific. Reasonable values are 5 to 500, and 64 is a good start (Table 3, rows 4–6).
4. It is important that the inputs to the recurrent actor and critic, such as past observations and past returns, contain enough information to infer the POMDP hidden states (Table 3, row 1).

We believe that these findings may provide a useful initialization for researchers studying recurrent model-free RL.

6   CONCLUSION

In this paper, we show that a carefully-designed implementation recurrent model-free RL can perform well across a range of POMDP domains, often on par with (if not significantly better than) prior methods that are specifically designed for specific types of POMDPs. Our ablation experiments demonstrate the importance of key design decisions, such as the underlying RL algorithm and RNN context length. While the best choices for some decisions (such as using separate RNNs for the actor and the critic) are consistent across domains, the best choices for other decisions (such as RNN context length) are problem dependent. We encourage future work to study automated mechanisms for selecting these key design decisions. In releasing our code, we hope to aid future research into the design of stronger POMDP algorithms.

REPRODUCIBILITY STATEMENT

We release our code at the url for reproducibility. In this code repository, we provide instructions on how to run our method and the compared methods in this paper on all the environments involved in the experiment section. We also provide the default configuration files for training and evaluating these algorithms that are adopted in our experiments. We also attach the numeric results of all the bar charts shown in the experiment section.

ETHICS STATEMENT

We do not believe that our work has direct ethical or societal implications.

REFERENCES

Marcin Andrychowicz, Anton Raichuk, Piotr Stańczyk, Manu Orsini, Sertan Girgin, Raphaël Marinier, Leonard Hussenot, Matthieu Geist, Olivier Pietquin, Marcin Michalski, et al. What matters for on-policy deep actor-critic methods? a large-scale study. In *International Conference on Learning Representations*, 2020.

Karl Johan Åström. Optimal control of markov processes with incomplete state information i. *Journal of Mathematical Analysis and Applications*, 10:174–205, 1965.

J Andrew Bagnell, Andrew Y Ng, and Jeff G Schneider. Solving uncertain markov decision processes. 2001.

Bram Bakker. Reinforcement learning with long short-term memory. In *Advances in Neural Information Processing Systems 14 [Neural Information Processing Systems: Natural and Synthetic, NIPS 2001, December 3-8, 2001, Vancouver, British Columbia, Canada]*, 2001.

Richard Bellman. A markovian decision process. *Journal of mathematics and mechanics*, 6(5):679–684, 1957.

Yoshua Bengio, Patrice Y. Simard, and Paolo Frasconi. Learning long-term dependencies with gradient descent is difficult. *IEEE Trans. Neural Networks*, 1994.

Anthony R. Cassandra, Leslie Pack Kaelbling, and Michael L. Littman. Acting optimally in partially observable stochastic domains. In *Proceedings of the 12th National Conference on Artificial Intelligence, Seattle, WA, USA, July 31 - August 4, 1994, Volume 2*, 1994.

Min Chen, Stefanos Nikolaidis, Harold Soh, David Hsu, and Siddhartha Srinivasa. Planning with trust for human-robot collaboration. In *Proceedings of the 2018 ACM/IEEE International Conference on Human-Robot Interaction*, pp. 307–315, 2018.

Kyunghyun Cho, Bart van Merrienboer, Çaglar Gülçehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using RNN encoder-decoder for statistical machine translation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing, EMNLP 2014, October 25-29, 2014, Doha, Qatar, A meeting of SIGDAT, a Special Interest Group of the ACL*, 2014.

Junyoung Chung, Çaglar Gülçehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

Karl Cobbe, Oleg Klimov, Christopher Hesse, Taehoon Kim, and John Schulman. Quantifying generalization in reinforcement learning. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, 2019.

Karl Cobbe, Christopher Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, 2020.

Erwin Coumans and Yunfei Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. 2016.

Hao Dong, Zihan Ding, and Shanghang Zhang. Deep reinforcement learning. https://github.com/quantumiracle/Popular-RL-Algorithms, 2020.

Ron Dorfman, Idan Shenfeld, and Aviv Tamar. Offline meta learning of exploration. *arXiv preprint arXiv:2008.02598*, 2020.

Yan Duan, John Schulman, Xi Chen, Peter L Bartlett, Ilya Sutskever, and Pieter Abbeel. Rl2: Fast reinforcement learning via slow reinforcement learning. *arXiv preprint arXiv:1611.02779*, 2016.

Logan Engstrom, Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Firdaus Janoos, Larry Rudolph, and Aleksander Madry. Implementation matters in deep rl: A case study on ppo and trpo. In *International conference on learning representations*, 2019.

Rasool Fakoor, Pratik Chaudhari, Stefano Soatto, and Alexander J. Smola. Meta-q-learning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*, 2020.

Jesse Farebrother, Marlos C Machado, and Michael Bowling. Generalization and regularization in dqn. *arXiv preprint arXiv:1810.00123*, 2018.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, 2017.

Scott Fujimoto, Herke van Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, 2018.

Adam Gleave, Michael Dennis, Cody Wild, Neel Kant, Sergey Levine, and Stuart Russell. Adversarial policies: Attacking deep reinforcement learning. *arXiv preprint arXiv:1905.10615*, 2019.

David Ha and Jürgen Schmidhuber. World models. *arXiv preprint arXiv:1803.10122*, 2018.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, 2018a.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, and Sergey Levine. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018b.

Dongqi Han, Kenji Doya, and Jun Tani. Variational recurrent models for solving partially observable control tasks. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*, 2020.

Matthew J. Hausknecht and Peter Stone. Deep recurrent q-learning for partially observable mdps. In *2015 AAAI Fall Symposia, Arlington, Virginia, USA, November 12-14, 2015*, 2015.

Nicolas Heess, Jonathan J. Hunt, Timothy P. Lillicrap, and David Silver. Memory-based control with recurrent neural networks. *arXiv preprint arXiv:1512.04455*, 2015.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.

Sepp Hochreiter, A. Steven Younger, and Peter R. Conwell. Learning to learn using gradient descent. In *Artificial Neural Networks - ICANN 2001, International Conference Vienna, Austria, August 21-25, 2001 Proceedings*, 2001.

Sandy Huang, Nicolas Papernot, Ian Goodfellow, Yan Duan, and Pieter Abbeel. Adversarial attacks on neural network policies. *arXiv preprint arXiv:1702.02284*, 2017.

Jan Humplik, Alexandre Galashov, Leonard Hasenclever, Pedro A. Ortega, Yee Whye Teh, and Nicolas Heess. Meta reinforcement learning as task inference. *arXiv preprint arXiv:1905.06424*, 2019.

Maximilian Igl, Luisa M. Zintgraf, Tuan Anh Le, Frank Wood, and Shimon Whiteson. Deep variational reinforcement learning for pomdps. In *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, 2018.

Maximilian Igl, Kamil Ciosek, Yingzhen Li, Sebastian Tschiatschek, Cheng Zhang, Sam Devlin, and Katja Hofmann. Generalization in reinforcement learning with selective noise injection and information bottleneck. In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, 2019.

Masoumeh T. Izadi and Doina Precup. Using rewards for belief state updates in partially observable markov decision processes. In *Machine Learning: ECML 2005, 16th European Conference on Machine Learning, Porto, Portugal, October 3-7, 2005, Proceedings*, 2005.

Yuankun Jiang, Chenglin Li, Wenrui Dai, Junni Zou, and Hongkai Xiong. Monotonic robust policy optimization with model discrepancy. In *International Conference on Machine Learning*, pp. 4951–4960. PMLR, 2021.

Niels Justesen, Ruben Rodriguez Torrado, Philip Bontrager, Ahmed Khalifa, Julian Togelius, and Sebastian Risi. Illuminating generalization in deep reinforcement learning through procedural level generation. *arXiv preprint arXiv:1806.10729*, 2018.

Leslie Pack Kaelbling, Michael L. Littman, and Anthony R. Cassandra. Planning and acting in partially observable stochastic domains. *Artif. Intell.*, 1998.

Islam SM Khalil, JC Doyle, and K Glover. *Robust and optimal control*. prentice hall, new jersey, 1996.

Ilya Kostrikov. Pytorch implementations of reinforcement learning algorithms. https://github.com/ikostrikov/pytorch-a2c-ppo-acktr-gail, 2018.

Kimin Lee, Kibok Lee, Jinwoo Shin, and Honglak Lee. Network randomization: A simple technique for generalization in deep reinforcement learning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*, 2020.

Michael Lederman Littman. *Algorithms for sequential decision-making*. Brown University, 1996.

Lingheng Meng, Rob Gorbet, and Dana Kulic. Memory-based deep reinforcement learning for POMDP. *arXiv preprint arXiv:2102.12344*, 2021.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937. PMLR, 2016.

Jun Morimoto and Kenji Doya. Robust reinforcement learning. *Neural computation*, 17(2):335–359, 2005.

Arnab Nilim and Laurent El Ghaoui. Robust control of markov decision processes with uncertain transition matrices. *Operations Research*, 53(5):780–798, 2005.

Charles Packer, Katelyn Gao, Jernej Kos, Philipp Krähenbühl, Vladlen Koltun, and Dawn Song. Assessing generalization in deep reinforcement learning. *arXiv preprint arXiv:1810.12282*, 2018.

Christos H. Papadimitriou and John N. Tsitsiklis. The complexity of markov decision processes. *Math. Oper. Res.*, 1987.

Anay Pattanaik, Zhenyi Tang, Shuijing Liu, Gautham Bommannan, and Girish Chowdhary. Robust deep reinforcement learning with adversarial attacks. *arXiv preprint arXiv:1712.03632*, 2017.

Lerrel Pinto, James Davidson, Rahul Sukthankar, and Abhinav Gupta. Robust adversarial reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, 2017.

Pascal Poupart and Craig Boutilier. Value-directed compression of pomdps. *Advances in neural information processing systems*, pp. 1579–1586, 2003.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Roberta Raileanu and Rob Fergus. Decoupling value and policy for generalization in reinforcement learning. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, 2021.

Aravind Rajeswaran, Sarvjeet Ghotra, Balaraman Ravindran, and Sergey Levine. Epopt: Learning robust neural network policies using model ensembles. *arXiv preprint arXiv:1610.01283*, 2016.

Aravind Rajeswaran, Kendall Lowrey, Emanuel Todorov, and Sham M. Kakade. Towards generalization and simplicity in continuous control. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, 2017.

Kate Rakelly, Aurick Zhou, Chelsea Finn, Sergey Levine, and Deirdre Quillen. Efficient off-policy meta-reinforcement learning via probabilistic context variables. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, 2019.

Alessio Russo and Alexandre Proutiere. Optimal attacks on reinforcement learning policies. *arXiv preprint arXiv:1907.13548*, 2019.

Jürgen Schmidhuber. *Evolutionary principles in self-referential learning, or on learning how to learn: the meta-meta-... hook*. PhD thesis, Technische Universität München, 1987.

Jürgen Schmidhuber. Reinforcement learning in markovian and non-markovian environments. In *Advances in Neural Information Processing Systems 3, NIPS'3*, pp. 500–506, 1991.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International conference on machine learning*, pp. 1889–1897. PMLR, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Xingyou Song, Yiding Jiang, Stephen Tu, Yilun Du, and Behnam Neyshabur. Observational overfitting in reinforcement learning. *arXiv preprint arXiv:1912.02975*, 2019.

Mario Srouji, Jian Zhang, and Ruslan Salakhutdinov. Structured control nets for deep reinforcement learning. In *International Conference on Machine Learning*, pp. 4742–4751. PMLR, 2018.

Freek Stulp, Evangelos Theodorou, Jonas Buchli, and Stefan Schaal. Learning to grasp under uncertainty. In *2011 IEEE International Conference on Robotics and Automation*, pp. 5703–5708. IEEE, 2011.

Chen Tessler, Yonathan Efroni, and Shie Mannor. Action robust reinforcement learning and applications in continuous control. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, 2019.

Sebastian Thrun and Lorien Pratt. *Learning to learn*. Springer Science & Business Media, 2012.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2017, Vancouver, BC, Canada, September 24-28, 2017*, 2017.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2012, Vilamoura, Algarve, Portugal, October 7-12, 2012*, 2012.

Trieu Trinh, Andrew Dai, Thang Luong, and Quoc Le. Learning longer-term dependencies in rnns with auxiliary losses. In *International Conference on Machine Learning*, pp. 4965–4974. PMLR, 2018.

Jane Wang, Zeb Kurth-Nelson, Hubert Soyer, Joel Z. Leibo, Dhruva Tirumala, Rémi Munos, Charles Blundell, Dharshan Kumaran, and Matt M. Botvinick. Learning to reinforcement learn. In *Proceedings of the 39th Annual Meeting of the Cognitive Science Society, CogSci 2017, London, UK, 16-29 July 2017*, 2017.

Manuel Watter, Jost Tobias Springenberg, Joschka Boedecker, and Martin A. Riedmiller. Embed to control: A locally linear latent dynamics model for control from raw images. In *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, 2015.

Steven D Whitehead and Dana H Ballard. Active perception and reinforcement learning. In *Machine Learning Proceedings 1990*, pp. 179–188. Elsevier, 1990.

Shimon Whiteson, Brian Tanner, Matthew E Taylor, and Peter Stone. Protecting against evaluation overfitting in empirical reinforcement learning. In *2011 IEEE symposium on adaptive dynamic programming and reinforcement learning (ADPRL)*, pp. 120–127. IEEE, 2011.

Daan Wierstra, Alexander Förster, Jan Peters, and Jürgen Schmidhuber. Solving deep memory pomdps with recurrent policy gradients. In *Artificial Neural Networks - ICANN 2007, 17th International Conference, Porto, Portugal, September 9-13, 2007, Proceedings, Part I*, 2007.

Aaron Wilson, Alan Fern, Soumya Ray, and Prasad Tadepalli. Multi-task reinforcement learning: a hierarchical bayesian approach. In *Machine Learning, Proceedings of the Twenty-Fourth International Conference (ICML 2007), Corvallis, Oregon, USA, June 20-24, 2007*, 2007.

Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on Robot Learning*, pp. 1094–1100. PMLR, 2020.

Amy Zhang, Nicolas Ballas, and Joelle Pineau. A dissection of overfitting and generalization in continuous reinforcement learning. *arXiv preprint arXiv:1806.07937*, 2018a.

Chiyuan Zhang, Oriol Vinyals, Remi Munos, and Samy Bengio. A study on overfitting in deep reinforcement learning. *arXiv preprint arXiv:1804.06893*, 2018b.

Huan Zhang, Hongge Chen, Chaowei Xiao, Bo Li, Duane S Boning, and Cho-Jui Hsieh. Robust deep reinforcement learning against adversarial perturbations on observations. 2020.

Huan Zhang, Hongge Chen, Duane Boning, and Cho-Jui Hsieh. Robust reinforcement learning on state observations with learned optimal adversary. *arXiv preprint arXiv:2101.08452*, 2021.

Chenyang Zhao, Olivier Sigaud, Freek Stulp, and Timothy M. Hospedales. Investigating generalisation in continuous deep reinforcement learning. *arXiv preprint arXiv:1902.07015*, 2019.

Yuke Zhu, Roozbeh Mottaghi, Eric Kolve, Joseph J. Lim, Abhinav Gupta, Li Fei-Fei, and Ali Farhadi. Target-driven visual navigation in indoor scenes using deep reinforcement learning. In *2017 IEEE International Conference on Robotics and Automation, ICRA 2017, Singapore, Singapore, May 29 - June 3, 2017*, 2017.

Brian D Ziebart. *Modeling purposeful adaptive behavior with the principle of maximum causal entropy*. Carnegie Mellon University, 2010.

Luisa M. Zintgraf, Kyriacos Shiarlis, Maximilian Igl, Sebastian Schulze, Yarin Gal, Katja Hofmann, and Shimon Whiteson. Varibad: A very good method for bayes-adaptive deep RL via meta-learning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*, 2020.

A CODE-LEVEL DETAILS

In this section, we first introduce the outline of code design, especially the replay buffer for sequences, and then compare the system usage including computing speed, RAM, and GPU memory with previous POMDP methods.

A.1 CODE DESIGN

Easy to use. Our code can be either used an API to call the recurrent model-free RL class or a framework to tune the details in the class. The recurrent model-free RL class takes the hyperparameters of RNN encoder type, shared or separate actor-critic architecture, and whether include previous observations, and/or actions, and/or rewards into the inputs, to generate different instances. The details of the hyperparameter tuning set is shown in Sec. A.3.

Memory-efficient replay buffer for sequences. Moreover, we design an efficient replay buffer for off-policy RL methods to cope with sequential inputs. Previous methods (Zintgraf et al., 2020; Dorfman et al., 2020; Han et al., 2020) mainly use *three-dimensional* replay buffer to store sequential inputs, with the dimensions of (num episodes, max episode length, observation dimension), taking observation storage as example. This kind of implementation becomes memory-inefficient if the actual episode length is far smaller than the max episode length (Han et al., 2020), which is common in locomotion tasks (Coumans & Bai, 2016; Schulman et al., 2017). Otherwise, it requires the ideal assumption that the episode has fixed length (Zintgraf et al., 2020; Dorfman et al., 2020). Instead, we manage to implement a two-dimensional replay buffer of shape (num transitions, observation dimension) for observation storage, which also records the locations where each stored episode ends. In case of actual episodes that are shorter than provided sampled sequence length, the buffer can also generate *masks* to indicate if the corresponding transitions are valid. This makes possible that the policy can receive a batch of previous experiences in a tensor-like data structure when sampling from the replay buffer. To sum up, our replay buffer can support varying-length sequence inputs and subsequence sampling in a 2-dim manner.

Flexible training speed. Finally, our code supports flexible training speed by controlling the ratio of the numbers of gradient updates in RL w.r.t. the environment rollout steps. The training speed is approximately proportional to the ratio if the simulator speed is much faster than the policy gradient update. Normally, the ratio is less than or equal to 1.0 to enjoy higher training speed.

A.2 SYSTEM USAGE

Table 4 shows the typical system usage of our method and compared specialized methods on different environments. The time cost for our method and VariBAD depends on how many processes in parallel are run on a single GPU – our method is run with 8 processes on a single GPU while VariBAD is run with one process due to large GPU memory usage. From the results we can see that our method is memory-efficient in both RAM and GPU, and has an acceptable training speed with default hyperparameters. The computer system we used during the experiments includes a GeForce RTX 2080 Ti Graphic Card (with 11GB memory) and Intel(R) Xeon(R) Gold 6148 CPU @ 2.40GHz (with 250GB RAM and 80 cores).

A.3 OUR HYPERPARAMETER TUNING SET

Our proposed method has the following decision factors (introduced in Sec. 4) to tune in the experiments with the following options (the names in brackets are abbreviated ones):

- Actor-Critic architecture (**Arch**): share the encoder weights between the recurrent actor and recurrent critic or not, namely shared and separate.
- Model-free RL algorithms (**RL**): td3 (Fujimoto et al., 2018) or sac (Haarnoja et al., 2018a)
- Encoder architecture (**Encoder**): lstm (Hochreiter & Schmidhuber, 1997) or gru (Cho et al., 2014)

Method	Environment	Time cost	RAM	GPU memory
Ours	Hopper-V	22.5 h	O(1)	1 GB
VRM (Han et al., 2020)	Hopper-V	102 h	O(200)	N/A
Ours	Semi-Circle	12 h	O(1)	1 GB
VariBAD (Dorfman et al., 2020)	Semi-Circle	2.3 h	O(1)*	9.5 GB
Ours	Cheetah-Robust	7 h	O(1)	1 GB
MRPO (Jiang et al., 2021)	Cheetah-Robust	0.4 h	N/A	N/A

Table 4: Comparison between our method and specialized methods in system usage. The results are runned with default hyparameters shown in Appendix. **??**. The time costs are evaluated within 1M environment steps. Both VRM and MRPO are run on CPUs and MRPO does not have replay buffer (shown in N/A). VariBAD requires the assumption of fixed episode length for the RAM cost.

- Policy input space (**Inputs**): `o`, `oa`, `or`, `oar`, `oard` (introduced in Sec.4)
- Context length (**Len**): short (5), medium (64), long (larger than 100, depending on the POMDPs).

For an instance, we label it with the names of all the hyperparameters it used in lowercase as notation. For example, `td3-lstm-64-or-separate` in Fig. 6 refers to the instance that uses the separate actor-critic architecture, TD3 RL algorithm, LSTM encoder, the policy input space of previous observations and reward sequences, and RNN context length of 64.

B EVALUATION DETAILS

The bar charts in Sec. 5 and Table 3 adopt the final performance of each method. We run each instance/variant in our method and each compared method with 4 random seeds. The final performance is calculated by the average performance of the last 20% environment steps across the 4 seeds.

In terms of selecting the best variant in our method for each subarea, we first compute the final performance of each variant, then normalize the final performance into $[0, 1]$, and finally select the best variant in the average of the normalized final performance across all the environments in each subarea.

C ENVIRONMENT DETAILS

C.1 META RL

Semi-Circle. We directly follow off-policy version of VariBAD (Dorfman et al., 2020). The observed state s^o includes the agent's 2D position p, and the hidden state s^h is referred to the goal state p_g. The goal state only appears in reward function: $R(s^o_t, s^o_{t+1}, a_t, s^h) \equiv R(p_{t+1}, p_g) = \mathbb{1}(\|p_{t+1} - p_g\|_2 \leq r)$ (maybe -0.1). The dynamic function T is independent of the goal state.

Cheetah-Vel. We directly follow Dorfman et al. (2020) using MuJoCo (Todorov et al., 2012) simulator of `HalfCheetah-v2`. The hidden state s^h is the target velocity v_g and observed state s^o includes the velocity v. Reward function includes both the hidden state and action: $R(s^o_t, s^o_{t+1}, a_t, s^h) \equiv R(v_t, v_g, a_t) = -\|v_t - v_g\|_1 - 0.05\|a_t\|_2$. The dynamic function T is independent of the goal state.

Wind. We modified the parameters of Wind environment in Dorfman et al. (2020) to make it harder to solve. The agent must navigate to a fixed (but unknown) goal p_g within a distance of $D = 1$ from its fixed initial state. Similarly to Semi-Circle, the reward function is goal conditioned but without hidden state: $R(s^o_t, s^o_{t+1}, a_t, s^h) \equiv R(p_{t+1}, p_g) = \mathbb{1}(\|p_{t+1} - p_g\|_2 \leq r)$. The hidden state s^h appear in the deterministic dynamics as a noise term, i.e. $s^o_{t+1} = s^o_t + a_t + s^h$, where s^h is sampled from $U[-0.08, 0.08]$ at the initial time-step and then kept fixed.

C.2 "STANDARD" POMDP

We use PyBullet (Coumans & Bai, 2016) as the simulator for "standard" POMDP environments. As the practice in VRM (Han et al., 2020), we remove all the position/angle-related entries in the observation space for "-V" environments and velocity-related entries for "-P" environments, to transform the original MDP into POMDP.

{Ant/Cheetah/Hopper/Walker}-P. The "-P" stands for the environments that keep position-related entries by removal of velocity-related entries. Thus, the observed state s^o includes positions p, while the hidden state s^h is the velocities v.

{Ant/Cheetah/Hopper/Walker}-V. The "-V" stands for the environments that keep velocity-related entries by removal of position-related entries. Thus, the observed state s^o includes positions v, while the hidden state s^h is the velocities p.

C.3 ROBUST RL

{Hopper/Walker/Cheetah}-Robust. We directly adopt the environments used in MRPO (Jiang et al., 2021). In each environment, the hidden state is the dynamics parameters including the density and friction coefficients of the simulated robot in roboschool, adapted from the SunBlaze (Packer et al., 2018). The exact ranges of the hidden states in each environment can be found in Table 1 of MRPO (Jiang et al., 2021). We evaluate the algorithms with 100 tasks in each environment, and use the average of them as average returns, and the average of the worst 10% of them as worst returns, following MRPO paper.

C.4 GENERALIZATION IN RL

{Hopper/Cheetah}-Generalize. We directly adopt the environments used in SunBlaze (Packer et al., 2018). In each environment, the hidden state is the dynamics parameters including the density, friction coefficients, and the power of the simulated robot in roboschool. The exact ranges of both interpolation and extrapolation in the hidden state distribution for each environment can be found in Table 1 of SunBlaze (Packer et al., 2018). We follow the practice of SunBlaze to evaluate interpolation and extrapolation success rates.

D FULL EXPERIMENTAL RESULTS

D.1 LEARNING CURVES OF ALL THE COMPARED METHODS

In this subsection, we show all the learning curves of all the compared methods in each subarea, namely "Standard" POMDPs (Fig. 7 and Fig. 8), meta RL (Fig. 9), robust RL (Fig. 10), and generalization in RL (Fig. 11). The final performance of these learning curves generate the bar charts in Sec. 5.1.

D.2 SINGLE FACTOR ANALYSIS ON OUR METHOD

Our analysis will focus on ablating the important design decisions: the actor-critic architecture (`Arch`), the policy input space (`Inputs`), the underlying model-free RL algorithm (`RL`), the RNN encoder (`Encoder`), and the RNN context length (`Len`). As there are several decision variables in our method, we could only show the results of each variable in the plots by averaging the performance over the other variables, which we call **single factor analysis**. In this kind of analysis, we can only say one value is better than another in one factor in the average sense (not the maximal sense), therefore it can show the robustness of each factor, but cannot tell the best choices (showed in Sec. 5.1). We show single factor analysis plots in each subarea, namely "Standard" POMDPs (Fig. 12 and Fig. 13), meta RL (Fig. 14), robust RL (Fig. 15), and generalization in RL (Fig. 16).

From these plots, we can see that each decision factor can make a difference in some environments. For example, the choice of RL algorithm is crucial in Ant-P (Fig. 12), Cheetah-V (Fig. 13), Wind

Figure 7: **Learning curves on "standard" POMDP environments that preserve positions & angles but occlude velocities in the states in PyBullet (Coumans & Bai, 2016) (namely "-P").** We show the results from the **single best variant** of our implementation on recurrent model-free RL, the popular recurrent model-free on-policy implementation (PPO-GRU, A2C-GRU) (Kostrikov, 2018), and also model-based method VRM (Han et al., 2020). Note that VRM is around 5x slower than ours, so we have to run 0.5M environment steps for it.

Figure 8: **Learning curves on "standard" POMDP environments that preserve velocities but occlude positions & angles in the states in PyBullet (Coumans & Bai, 2016) (namely "-V").** We show the results from the **single best variant** of our implementation on recurrent model-free RL, the popular recurrent model-free on-policy implementation (PPO-GRU, A2C-GRU) (Kostrikov, 2018), and also model-based method VRM (Han et al., 2020). Note that VRM is around 5x slower than ours, so we have to run 0.5M environment steps for it.

PointRobotSparse-v0

Wind-v0

Figure 9: **Learning curves on meta RL environments.** We show the results from the **single best variant** of our implementation on recurrent model-free RL, the specialized meta RL method VariBAD (Dorfman et al., 2020)

Figure 10: **Learning curves on robust RL environments.** We show the average returns (left figures) and worst returns (right figures) from the **single best variant** of our implementation on recurrent model-free RL, the specialized robust RL method MRPO (Jiang et al., 2021). Note that our method is much slower than MRPO, so we have to run our method within 3M environment steps. But the results show that our method have much better sample efficiency over MRPO.

Figure 11: **Learning curves on generalization in RL environments.** We show the interpolation success rates (left figures) and extrapolation success rates (right figures) from the **single best variant** of our implementation on recurrent model-free RL. We also show the final performance of the specialized method EPOpt-PPO-FF (Rajeswaran et al., 2016) and another recurrent model-free (on-policy) RL method (A2C-RC) copied from the Table 7 & 8 in Packer et al. (2018).

(Fig. 14) and Hopper-Generalize (Fig. 16). The context length is essential in all the "-P" environments (Fig. 12), Cheetah-Vel (Fig. 14), and both the generalization environments (Fig. 16). The policy input space can make a difference in most "-P" environments (Fig. 12) possibly because `oar` contains the information of missing velocities.

D.3   ADDITIONAL RESULTS ON SEPARATE VS SHARED RECURRENT ACTOR-CRITIC ARCHITECTURE

In Fig. 6 of Sec. 5.2, we show the importance of selecting a separate recurrent actor-critic architecture in a meta RL environment, Semi-Cirle. Now we show the result in another POMDP environment, Pendulum-V, which occludes the positions and angles, in Fig. 17. We can see that the shared encoder architecture is also worse than the separate one with high gradient norm in the RNN.

Figure 12: **Ablation study of our implementation on "standard" POMDP environments that preserve positions & angles but occlude velocities in the states in pybullet (Coumans & Bai, 2016) (namely "-P").** We show the single factor analysis on the 4 decision factors including RL, Encoder, Len, and Inputs for each environment.

Figure 13: **Ablation study of our implementation on "standard" POMDP environments that preserve velocities but occlude positions & angles in the states in pybullet (Coumans & Bai, 2016) (namely "-V").** We show the single factor analysis on the 4 decision factors including RL, Encoder, Len, and Inputs for each environment.

Figure 14: **Ablation study of our implementation on meta RL environments.** We show the single factor analysis on covering all the decision factors

Figure 15: **Ablation study of our implementation on robust RL environments.** We show the single factor analysis on the 4 decision factors including RL, Encoder, Len, and Inputs for each environment in both average returns and worst returns.

Figure 16: **Ablation study of our implementation on generalization in RL environments.** We show the single factor analysis on the 3 decision factors including RL, Len, and Inputs for each environment in both interpolation and extraploation success rates.

Figure 17: **Comparison between *shared* and *separate* recurrent actor-critic architecture** with all the other hyperparameters same, on Pendulum-V, a toy "standard" POMDP environment. We show the performance metric (left) and also gradient norm of the RNN encoder(s) (right, in **log-scale**). For the separate architecture, `:critic` and `:actor` refer to the separate RNN in critic and actor networks, respectively.