Topographic DCNNs trained on a single self-supervised task capture the functional organization of cortex into visual processing streams

Abstract

A key organizing principle of visual cortex is functional specialization, whether locally in the context of category-selective patches, or on a broader scale in the case of visual processing streams. Primate visual cortex has traditionally been divided into two such processing streams, though recent research suggests that there may be at least three functionally and anatomically distinct streams, extending along the ventral, lateral, and parietal surfaces of the brain. While processing streams are typically thought of within the framework of what downstream behaviors/tasks they support, we ask instead whether anatomical constraints may be sufficient to produce this differentiation, even within the context of just one task objective. Comparing directly to human fMRI responses, we show that a model trained on a single task, and with novel anatomical constraints (Topographic DCNN), can capture not only the functional responses but also the segregation of visual cortex into distinct processing streams. The match to human data is strongest for a self-supervised vs. supervised objective and when the anatomical constraint, which encourages local response correlations as proxy for minimizing wiring length, is appropriately weighted. These results suggest that the broad-scale functional organization of visual cortex into parallel processing streams may be explained by the pressure to minimize biophysical costs such as wiring length, and that local spatial constraints can surprisingly percolate to create broad-scale structure.

1   Introduction

A third of the human brain is devoted to vision, with tasks such as visually perceiving an object's category, dynamics, and location crucial to interacting with and acting upon on our world. Traditionally, visual cortex has been divided into two functionally and anatomically distinct processing streams: a "what" stream extending along ventral occipito-temporal cortex, and a "where" or "visually-guided grasping" dorsal stream extending along occipito-parietal cortex[1, 2]. More recently, a third lateral stream, extending along lateral occipito-temporal cortex, has been proposed, with suggested functions including multimodal processing[3], action recognition[4], and social perception[5] However, it is an open question why cortex might organize into streams in the first place. Are different tasks required for generating different streams (prevailing hypothesis) or are anatomical constraints sufficient to produce multiple streams even in the context of a single task objective?

One such potential anatomical constraint is wiring length minimization, i.e., an architectural bias toward short-range connections[6, 7]. This principle has been proposed to explain the functional topography of orientation preference in primary visual cortex[8] as well as category-selective patches in high-level visual cortex[9, 10]. Recently, a new model class has been introduced, Topographic

Deep Convolutional Neural Networks (DCNNs)[9, 11], which encourages local correlations as a proxy for wiring length minimization. Using an end-to-end optimization framework that minimizes combined task and spatial loss terms, Topographic DCNNs both well-predict responses in the ventral stream as well as capture the functional topography of V1 and ventral temporal cortex (VTC)[11]. Here, we leverage Topographic DCNNs to test if they (1) predict responses to many stimuli across not just ventral, but also lateral and parietal cortex and (2) recapitulate the broad-scale functional topography of multiple visual processing streams. The outcome of these tests will provide insights into what constraints are sufficient to reproduce this organization (see A.1 for Related Work).

2 Methods

2.1 Topographic DCNNs

As a candidate model class we use Topographic DCNNs, with ResNet-18 as an architectural backbone. Each convolutional layer in the network is converted to a topographic layer by assigning each model unit to a position in a two-dimensional simulated cortical sheet that is unique to that layer. For the purposes of comparing to higher-level visual cortex, we will be focusing on the final convolutional layer, which has been previously shown to best match primate central IT and human VTC [12–14]. Model positions for each layer are initialized to be coarsely retinotopic, shuffled in small neighborhoods, and then permanently fixed to those positions; network parameters are randomly initialized.

Models are trained to minimize a composite loss function with two components: (1) a task component: SimCLR cross-entropy (CE) loss[15] and (2) a spatial loss (SL) component that encourages nearby model units to be correlated in their responses, as follows:

$$\text{Loss} = \text{CE} + \sum_{l=1}^{N} \alpha(\text{SL}_l) \tag{1}$$

CE is the cross-entropy task loss component, N is the number of convolutional layers in the model, α is the weight of the spatial loss component (fixed across all layers), and SL_l is the spatial correlation loss computed for the l-th layer. Specifically, SL_l is computed by calculating for all pairs of units, (1) Pearson's r between the response profiles, ($\overrightarrow{C}$), and (2) the vector of physical (position) similarity, specifically the stabilized reciprocal Euclidean distance, ($\overrightarrow{D}$). These two terms are then related as follows:

$$\text{SL}_l = 1 - \text{Corr}\left(\overrightarrow{C}, \overrightarrow{D}\right) \tag{2}$$

such that SL_l is minimized when nearby units have correlated responses to the training stimuli.

We compare models across two factors: degree of spatial constraint and training task. The spatial constraint varied from $\alpha = 0$, yielding a nonspatial model in which unit positions are ignored during training, to $\alpha = 25$, a weighting of the spatial loss function such that local correlations dominate over task. We used two training tasks: (i) self-supervised contrastive learning (SimCLR[15]), which increases the similarity of representations between different augmentations of the same image while decreasing the similarity to different images. This type of representation structure may be beneficial for a range of downstream functions associated with any of the three streams. And (ii) supervised object categorization. This task has been shown to best predict responses in the primate ventral stream[16, 17] and can serve as a benchmark. All models were trained using ImageNet[18].

2.2 Neural data

As our neural comparison, we used the Natural Scenes Dataset (NSD)[19], a high-resolution fMRI dataset that densely sampled responses to up to 10,000 natural images in each of eight individuals (see Allen et al. [19] and A.2 for details on preprocessing of the data). We defined regions of interest (ROIs) for early, intermediate, and high-level visual cortex for each of the three streams based on a combination of anatomical landmarks, noise ceiling estimates, and a constraint to roughly match the number of voxels per stream. Single-trial responses were z-scored across images for each voxel and session and then averaged across 3 trial repeats. For comparisons between models and individual brains, we leverage the full set of images (6234-10,000 per individual). For comparisons between individuals, we used 515 shared images which all participants viewed 3 times. We used cortex-based alignment to align all data to the fsaverage surface, and report here results from the right hemisphere.

2.3 Mapping between models and brains

As traditionally used linear encoding[16] and representational similarity analysis[17] methods deliberately re-weight or marginalize the outputs across units, thus obscuring topographic organization, we developed new mapping algorithms to compare model and brain functional topography. We used a direct mapping (1-to-1) between model units and brain voxels, mapping each unit to a single voxel. As a benchmark, we tested the new mapping algorithms on how well they mapped voxels from one brain to another (brain-to-brain case). In the brain-to-brain case, we computed the correlations between responses to the shared images for each pair of source and target voxels in different brains (same procedure in the model-to-brain case using activations of model units in response to the images each subject viewed). The goal was to determine from the vast space of possibilities, the optimal assignment of each source voxel (or unit) to a single corresponding target voxel. We first computed the assignment solely on the basis of functional similarity (Alg. 1), using the Kuhn-Munkres algorithm[20]. We then incorporated our prior for some level of smoothness in the mapping by implementing an iterative version of the Kuhn-Munkres algorithm that gently encourages neighboring voxels in the target space to "pick" neighboring voxels in the source space (Alg. 2; see A.3).

3 Results

3.1 1-to-1 voxel mapping based on response similarity alone only partially recovers the structure of processing streams

We began by mapping one subject's brain to another subject's brain using just functional similarity (Alg. 1). We examined the resulting mapping by coloring each voxel in the target individual's brain by which stream it came from in the source individual's brain (Fig. 1A, example subject pair). This revealed that voxels from one stream in the source brain were largely assigned to the same stream in the target brain. However, there were also many mismatches. To quantify the degree of correspondence, we calculated what percentage of voxels from each target brain and ROI were assigned to voxels from the same ROI in the source brain. Correspondence was significantly above chance for each stream (chance=33%; mean $\pm$ SE: Ventral = 56.5$\pm$0.7%, $p = 9.1$x10^{-9}; Lateral = 62.6$\pm$0.7%, $p = 2.2$x10^{-9}; Parietal = 58.8$\pm$0.4%, $p = 1.2$x10^{-10}; Fig. 1C). We then tested if incorporating a smoothness constraint

Figure 1: (A) Voxels in Target (Subj. 2) brain colored by their assignment to Source (Subj. 1) brain using an algorithm that matches voxels solely on the basis of functional similarity (Alg. 1). (B) Voxels in Target (Subj. 2) brain colored by their assignment to Source (Subj. 1) brain using an algorithm that additionally incorporates a gentle smoothness constraint (Alg. 2; 25 iterations). (C) Top right: zoomed region in (A,B) shown on full flat map. Bars: Comparison of voxel-to-voxel correspondence. Data plotted for high-level ROIs across three streams, averaged across source subjects for each target subject. Color represents stream throughout manuscript (pink: Ventral, blue: Lateral, and green Parietal). Dotted line: chance level (33%). Error bar: 95% CI, each dot is a subject.

(Alg 2) enhances the mapping. Results indicate significantly improved brain-to-brain correspondence for Alg. 2 vs. 1 ($F(1, 7) = 670.9, p = 3.3$x10^{-8}, Fig. 1B, example subject pair) yielding an average of 78% correspondence (Fig. 1C). Thus, we used Alg 2. to map model units to brain voxels.

3.2 Topographic DCNNs can capture the broad-scale functional topography of high-level visual cortex

We next compared how well model units mapped to voxels in individual brains. We tested the assignment and topographic organization of units in the last convolutional layer vis-a-vis voxels in high-level ROIs of the Ventral, Lateral, and Parietal streams. Specifically, we asked how good the functional correspondence would be between model units and voxels and whether there would be clustering of units by stream in the simulated cortex. Results in Fig. 2A demonstrate that for Topographic DCNN models trained on SimCLR with a spatial loss weighting of $\alpha = 0.25$, unit assignments are clustered by stream in the simulated cortex (particularly in the bottom right corner of the model cortical sheet). This correspondence is highly consistent across subjects. Critically, this does not depend on our ROI definitions or deliberate division into three streams, as this correspondence also emerges when visualizing unit assignments along a superior-to-inferior axis (y-gradient, on flat

Figure 2: Model-to-brain mapping for a model trained on ImageNet and $\alpha = 0.25$ using a self-supervised, SimCLR (A) or supervised, object categorization (B), objective. Each panel shows the assignment of model units in the simulated cortex of the last convolutional layer to a voxel in a target brain. Each dot is a model unit. Units in the simulated cortex are colored by stream (top) or superior-to-inferior gradient (y-position in flat map, bottom). Each column displays the model-to-brain mapping for one individual. Opacity of the units reflects the strength of the unit-to-voxel correlation between responses to NSD images).

map). In contrast, training with the same architecture and spatial loss weighting of $\alpha = 0.25$ but on a supervised categorization task does not yield this three stream structure. Instead, this model develops units that are assigned and clustered for the Ventral stream (center of the model simulated sheet, Fig. 2B), but not for the Lateral or Parietal streams.

3.3 Broad-scale functional topography is only captured by self-supervised, not supervised, Topographic DCNN, and an optimal weighting of the spatial loss term

The recapitulation of the three-stream functional organization of the brain that we see in the SimCLR-trained $\alpha = 0.25$ model is dependent on particular parameters, as it does not emerge in a number of other settings. First, the mapping algorithm used does not guarantee this result, as we can see in an instantiation of a SimCLR-trained Topographic DCNN with $\alpha = 0$ (essentially a vanilla ResNet-18). While the unit-to-voxel assignments in this model have some local structure (Fig. 3A, left panel), the functional topography is qualitatively different than the same task loss with a spatial loss weight of $\alpha = 0.25$; crucially, it does not capture the three-stream organization of the brain. In fact, the qualitative correspondence varies with the degree of spatial weight, steadily increasing from $\alpha = 0$ to $\alpha = 0.25$ and then deteriorating for $\alpha > 1$ as the spatial loss dwarfs the task loss (Fig. 3A). We find a similar pattern if unit assignments are by position along a superior-to-inferior axis (Fig. 3B).

We next quantified the unit-to-voxel correspondence via two metrics: (i) the number of clusters per stream ROI calculated using an automatic cluster detection algorithm[11], and (ii) the "clusteriness", measured by calculating entropy of the 2D histogram for ROI assignment in comparison to a randomly shuffled layout (details in A.5). For both metrics we compared the model-to-brain mapping to the brain-to-brain mapping. The three-stream model of the brain predicts one cluster per stream ROI. Automated cluster detection revealed that there is a narrow range of that provide this match across

Figure 3: Model-to-brain mappings across a range of spatial weights for an example subject, colored by (A) stream ROI assignment or (B) superior-to-inferior gradient on cortex(y-position). Each dot is a model unit. See A.4 for all subjects.

streams (Fig. 4A). For $\alpha = 0.25$, the average is 1.375 (SE=0.25) clusters for Ventral, 0.875 (SE=0.12) clusters for Lateral, and 1.75 (SE=0.15) clusters for Parietal. For this α, neither the Ventral nor Lateral estimates significantly differed from one (Wilcoxon signed-rank test, Bonferroni corrected for 3 comparisons, $ps > .54$), though the Parietal estimate did ($p = .042$). Likewise, estimated entropy was most similar to brain-to-brain mappings for $0.25 \geq \alpha \leq 0.5$ (Fig. 4B), and for $\alpha = 0.25$ did not significantly differ from the brain-to-brain mapping for Lateral, though it did for Ventral (paired t-test: $t(7) = 8.9, p = 1.4\text{x}10^{-4}$) and Parietal ($t(7) = 11.0, p = 3.4\text{x}10^{-5}$, Bonferroni corrected for 3 comparisons). Overall, quantitative measures of correspondence were better for Ventral and Lateral than Parietal, indicating an area for improvement.

We also quantified the functional cor-respondence between unit and voxel responses to the NSD images as a function of α and training task. Strikingly, unit-to-voxel correlations were significantly higher for the Topo-graphic DCNNs trained with the more biologically plausible self-supervised objective vs. the supervised task at a matched spatial weight ($t(7) = 25.0, p = 4.2\text{x}10^{-8}$). The unit-to-voxel functional correlation also varies with spatial weight, tracking the pattern we observed for the to-pographic correspondence. That is, spatial weights that yielded a better topographic correspondence between model and brain also yielded a better functional correspondence (Fig. 4C). This indicates that the spatial loss does not only change the spatial layout, but also meaningfully changes the func-tional tuning of model units.

Figure 4: (A) Number of clusters in model-to-brain mappings by spatial weight. Dotted line: the number of clusters per stream observed in the brain. (B) "Clusteriness" as measured by 2D histogram entropy for the model-to-brain mapping. Shaded bars: same except for brain-to-brain mapping (mean±SE across target subjects). (C) The average correlation between assigned unit and voxel responses on the 10k NSD images per subject, normalized by each voxel's noise ceiling. Each dot represents a subject. Shaded gray bar: same calculation for brain-to-brain mapping (mean±SE across target subjects).

4 Discussion

Using a newly developed Topographic DCNN and novel model-to-brain mapping method, we show that it is possible to capture much of the broad-scale organization of visual cortex into processing streams in a model trained on a single self-supervised task, with the addition of a spatial constraint. This suggests that the functional organization of cortex into distinct visual processing streams could emerge simply from the biophysical pressure to minimize wiring length, while learning generally useful visual representations. It is important to note that the spatial loss used here does not explicitly impose a wiring length cost. However, the consequence of nearby units having similar responses is that wiring length is minimized[11] and related work has shown that explicitly minimizing wiring length increases the functional coupling between nearby units[10].

Given the dominant role task has played in the field's thinking about visual processing streams, a logical question is whether using different training tasks would better differentiate the streams. We tested this by training three networks with different tasks commonly proposed as the functional objective of each stream (Ventral: object categorization, Lateral: action recognition, and Parietal: object detection; ResNet-50 base architectures). Consistent with prior work using linear regression to map units to brain responses [14], we find that models trained on these three tasks minimally differentiated the streams (see A.6). Crucially, however, this does not preclude the spatial constraints *creating* functional differentiation. While spatial constraints may dictate a particular way to physically layout neurons capturing a range of representations, groups of these neurons may also then be more or less useful for different downstream tasks. In fact, we hope to test this in future work by learning readout layers for units assigned to each of the three streams separately and comparing performance on different tasks.

In conclusion, our results suggest a rethinking of visual processing streams and highlight the crucial role of anatomical constraints, above and beyond task demands, in their emergence.

References

[1] Leslie G Ungerleider and Mortimer Mishkin. Two cortical visual systems. analysis of visual behavior. *Analysis of Visual Behavior*, pages 549–586, 1982.

[2] Melvyn A Goodale and A David Milner. Separate visual pathways for perception and action. *Trends in Neurosciences*, 15(1):20–25, 1992.

[3] Kevin S Weiner and Kalanit Grill-Spector. Neural representations of faces and limbs neighbor in human high-level visual cortex: evidence for a new organization principle. *Psychological Research*, 77(1):74–97, 2013.

[4] Moritz Wurm and Alfonso Caramazza. Action and object representation in the ventral" what" stream. *PsyArXiv*, 2021.

[5] David Pitcher and Leslie G Ungerleider. Evidence for a third visual pathway specialized for social perception. *Trends in Cognitive Sciences*, 2020.

[6] David C van Essen. A tension-based theory of morphogenesis and compact wiring in the central nervous system. *Nature*, 385(6614):313–318, 1997.

[7] Robert A Jacobs and Michael I Jordan. Computational consequences of a bias toward short connections. *Journal of Cognitive Neuroscience*, 4(4):323–336, 1992.

[8] Alexei A Koulakov and Dmitri B Chklovskii. Orientation preference patterns in mammalian visual cortex: a wire length minimization approach. *Neuron*, 29(2):519–527, 2001.

[9] Hyodong Lee, Eshed Margalit, Kamila M Jozwik, Michael A Cohen, Nancy Kanwisher, Daniel LK Yamins, and James J DiCarlo. Topographic deep artificial neural networks reproduce the hallmarks of the primate inferior temporal cortex face processing network. *bioRxiv*, 2020.

[10] Nicholas M Blauch, Marlene Behrmann, and David C Plaut. A connectivity-constrained computational account of topographic organization in primate high-level visual cortex. *Proceedings of the National Academy of Sciences*, 119(3):e2112566119, 2022.

[11] Eshed Margalit. *A Unifed Model of the Structure and Function of Primate Visual Cortex*. Stanford University, 2022.

[12] Chengxu Zhuang, Siming Yan, Aran Nayebi, Martin Schrimpf, Michael C Frank, James J DiCarlo, and Daniel LK Yamins. Unsupervised neural network models of the ventral visual stream. *Proceedings of the National Academy of Sciences*, 118(3):e2014196118, 2021.

[13] Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J Majaj, Rishi Rajalingham, Elias B Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Franziska Geiger, et al. Brain-score: Which artificial neural network for object recognition is most brain-like? *bioRxiv*, page 407007, 2020.

[14] Dawn Finzi, Daniel LK Yamins, Kendrick Kay, and Kalanit Grill-Spector. Do deep convolutional neural networks accurately model representations beyond the ventral stream? In *2022 Conference on Cognitive Computational Neuroscience*, 2022.

[15] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. 2020. doi: 10.48550/ARXIV.2002.05709. URL https://arxiv.org/abs/2002.05709.

[16] Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23):8619–8624, 2014.

[17] Seyed-Mahdi Khaligh-Razavi and Nikolaus Kriegeskorte. Deep supervised, but not unsupervised, models may explain it cortical representation. *PLoS Computational Biology*, 10(11): e1003915, 2014.

[18] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009. doi: 10.1109/CVPR.2009.5206848.

[19] Emily J Allen, Ghislain St-Yves, Yihan Wu, Jesse L Breedlove, Jacob S Prince, Logan T Dowdle, Matthias Nau, Brad Caron, Franco Pestilli, Ian Charest, et al. A massive 7T fMRI dataset to bridge cognitive neuroscience and artificial intelligence. *Nature Neuroscience*, 25(1): 116–126, 2022.

[20] James Munkres. Algorithms for the assignment and transportation problems. *Journal of the Society for Industrial and Applied Mathematics*, 5(1):32–38, 1957.

[21] Yiyuan Zhang, Ke Zhou, Pinglei Bao, and Jia Liu. Principles governing the topological organization of object selectivities in ventral temporal cortex. *bioRxiv*, 2021.

[22] T Anderson Keller, Qinghe Gao, and Max Welling. Modeling category-selective cortical regions with topographic variational autoencoders. *arXiv preprint arXiv:2110.13911*, 2021.

[23] Umut Güçlü and Marcel AJ van Gerven. Deep neural networks reveal a gradient in the complexity of neural representations across the ventral stream. *Journal of Neuroscience*, 35 (27):10005–10014, 2015.

[24] Umut Güçlü and Marcel AJ van Gerven. Increasingly complex representations of natural movies across the dorsal stream are shared between subjects. *NeuroImage*, 145:329–336, 2017.

[25] Patrick Mineault, Shahab Bakhtiari, Blake Richards, and Christopher Pack. Your head is there to move you around: Goal-driven models of the primate dorsal pathway. *Advances in Neural Information Processing Systems*, 34, 2021.

[26] Shahab Bakhtiari, Patrick Mineault, Timothy Lillicrap, Christopher Pack, and Blake Richards. The functional specialization of visual cortex emerges from training parallel pathways with self-supervised predictive learning. *Advances in Neural Information Processing Systems*, 34: 25164–25178, 2021.

[27] Philip M Dixon. Nearest neighbor methods. *Encyclopedia of Environmetrics*, 3:1370–1383, 2002.

[28] Christoph Feichtenhofer, Haoqi Fan, Jitendra Malik, and Kaiming He. Slowfast networks for video recognition. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 6202–6211, 2019.

[29] Will Kay, Joao Carreira, Karen Simonyan, Brian Zhang, Chloe Hillier, Sudheendra Vijaya-narasimhan, Fabio Viola, Tim Green, Trevor Back, Paul Natsev, et al. The kinetics human action video dataset. *arXiv preprint arXiv:1705.06950*, 2017.

[30] Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. *Advances in Neural Information Processing Systems*, 28, 2015.

[31] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft COCO: Common objects in context. In *European conference on computer vision*, pages 740–755. Springer, 2014.

A Appendix

A.1 Related work

Models of the topographic organization of ventral cortex. Recent work has moved beyond self-organizing maps to image-computable models which attempt to capture both the response properties and topographic organization of VTC. In particular, three DCNN-based approaches, the Interactive Topographic Network (ITN)[10], the "VTC-SOM"[21], and the Topographic VAE[22] successfully produce maps with clustered category-selectivity as found in VTC. Our approach varies from prior ones in that Topographic DCNNs are trained end-to-end, allowing us to investigate how the training impacts the learned kernels, their fit to brain responses, *and* their topographic organization.

DCNN models of the lateral and parietal streams. DCNNs trained on supervised object recognition[16, 17, 23] and contrastive self-supervised objectives[12]) are excellent predictive models of responses across the ventral stream. However, few studies have used DCNNs to predict responses in lateral and parietal cortex, with the following exceptions: DCNNs trained for action recognition in videos[24] or for predicting an agent's self-motion[25] well-predict responses in V3A/B, MT and MST[1]. Additionally, one study attempted to model both the ventral and dorsal pathways using a branched architecture trained with a self-supervised predictive loss function[26], though in mice and without matching to the topography.

A.2 Additional information on drawing of ROIs and processing of neural data

A full set of seven (one early, three intermediate and three higher-level) ROIs were drawn on the fsaverage surface as follows:

Early visual cortex ROI: The early visual cortex ROI was drawn as the union of the V1v, V1d, V2v, V2d, V3v and V3d ROIs from the Wang retinotopic atlas. Additionally, V2v and V2d were connected such that the part of the occipital pole typically containing foveal representations was also included. The same was repeated for V3v and V3d.

Intermediate ROIs: Three intermediate ROIs were drawn corresponding to each of the three streams: ventral, lateral and parietal. All three ROIs border the early visual cortex ROI on the posterior side. The intermediate ventral ROI was drawn to reflect the inferior boundary of hV4 from the Wang atlas and to include the inferior occipital gyrus (IOG), with the anterior border of the ROI drawn based on the anterior edge of the inferior occipital sulcus (IOS). The intermediate lateral ROI was drawn directly superior to the intermediate ventral ROI, with the superior and anterior borders determined as the LO1 and LO2 boundaries from the Wang atlas. The intermediate parietal ROI was drawn directly superior to that, reflector exactly the borders of the union of V3A and V3B from the Wang retinotopic atlas.

Higher-level ROIs: Three higher-level ROIs were drawn for each of the Ventral, Lateral and Parietal streams, bordering their respective intermediate ROIs on their posterior edges. The ventral ROI was drawn to follow the anterior lingual sulcus (ALS), including the anterior lingual gyrus (ALG) on its inferior border and to follow the inferior lip of the inferior temporal sulcus (ITS) on its superior border. The anterior border was drawn based on the midpoint of the occipital temporal sulcus (OTS). The lateral ROI was drawn such that the higher-level ventral ROI was its inferior border and the superior lip of the superior temporal sulcus (STS) was used to mark the anterior/superior boundary. The rest of the superior boundary traced the edge of angular gyrus, up to the tip of the posterior STS (pSTS). The parietal ROI was drawn to reflect the boundary of the lateral ROI on its inferior edge and to otherwise trace the borders of and include the union of IPS0, IPS1, IPS2, IPS3, IPS4, IPS5 and SPL1 from the Wang retinotopic atlas.

The three higher-level ROI were then trimmed using the prepared noise ceiling maps for beta version b3 and the fsaverage surface[19]. The noise ceiling estimates represent the amount of variance contributed by the signal expressed as a percentage of the total amount of variance in the data, for the average of responses across three trial presentations. An approximate cutoff of 10% was used to guide trimming of the higher-level ROIs, such that we were left with reduced ROIs where all

---

[1]Of note, while MT is traditionally thought of as within the dorsal stream, including in the cited studies, anatomically, MT is located within the lateral stream, not the parietal stream. This distinction is particularly apparent in humans, where the lateral surface is greatly expanded in comparison to non-human primates.

voxels had a noise ceiling $\geq 10\%$ theoretically predictable variance. These ROIs were contiguous and roughly matched in size (right hemisphere number of voxels per ROI: Ventral = 5638, Lateral = 6839, Parietal = 6688). In the main text, only the higher-level ROIs are used for analysis. However, the full details for drawing all 7 ROIs are included here for completeness and as the higher-level ROIs using the boundaries of the intermediate ROIs as their posterior borders.

Additionally, note that for the purposes of this paper, we use refer to the brain units of measurement as "voxels", though they are more technically "vertices" as we are using the fsaverage preparation.

A.3   Full algorithm in pseudo-code for Algorithm 2

Algorithm 2 One-to-one mapping including a smoothness constraint

---

Require: Cost matrix C of dimension $N_s \times N_t$, where N_s is the number of source units and N_t is the number of target units, and each entry in C is $1-$ the pairwise correlation of the response vectors. Source distance matrix, D_s, of dimension $N_s \times N_s$, with the pairwise distances between all units in the source space. Target distance matrix, D_t, of dimension $N_t \times N_t$, with the pairwise distances between all units in the target space. Radius r to use as neighborhood size.

    procedure ALGORITHM2(C, D_s, D_t, r)
        Assignments $A \leftarrow$ Kuhn-Munkres(C)   ▷ Initialized based on purely functional mapping
        while Mean movement of assignments from iteration to iteration has not converged **do**
            $C_{\text{temp}} \leftarrow C$.copy()
            for each target unit, v_t **do**
                Find all neighboring target units, V_{tn} within distance r
                Initialize candidate matrix, V_{sn}
                for each unit in V_{tn} **do**
                    Find their assigned source unit, v_s, from A
                    $v_{sn} \leftarrow$ all units in source space within distance r from v_s
                    Append v_s and v_{sn} to V_{sn}
                end for
                Fit a 2D Gaussian, G, to point cloud, V_{sn} in source space
                $M_{sn} \leftarrow$ mahalanobis(V_{sn}, G)
                for each unit, u, in V_{sn} **do**
                    if $M_{sn}[u] > 2$ **then**
                        Remove u from V_{sn}
                    end if
                end for
                $C_{\text{temp}}[v_t, \neg V_{sn}] = 1000$ ▷ all source units not in V_{sn} are set to have a prohibitive cost
            end for
             $A \leftarrow$ Kuhn-Munkres(C_{temp})
        end while
        return A
    end procedure

For the brain-to-brain case, radius r was set to 5mm. To convert this radius to the model space, which is 10×10, we calculated what percentage of the max voxel-to-voxel distance (237 mm) the brain radius cutoff was and then multiplied that percentage by the max model distance (12.9). This yielded a model radius cutoff of approximately .27. Thus, in the model-to-brain case two radii are used, 5mm for the brain distances and .27 for the model distances.

A.4   Model-to-brain maps for all subjects and spatial weights

See figures S1, S2, S3, S4, S5, S6.

A.5   Additional information on measures of "clusteriness"

Two measures of "clusteriness" are included within the main text. First, we calculated the number of clusters per stream using an automatic cluster detection algorithm [11]. Model units on the model cortical sheet were assigned stream labels based on the location of the each unit's assigned voxel

Fig. S1: Model-to-brain mapping for a model with $\alpha = 0$ using a self-supervised, SimCLR, objective.

Fig. S2: Model-to-brain mapping for a model with $\alpha = 0.1$ using a self-supervised, SimCLR, objective.

Fig. S3: Model-to-brain mapping for a model with $\alpha = 0.5$ using a self-supervised, SimCLR, objective.

Fig. S4: Model-to-brain mapping for a model with $\alpha = 1.25$ using a self-supervised, SimCLR, objective.

Fig. S5: Model-to-brain mapping for a model with $\alpha = 2.5$ using a self-supervised, SimCLR, objective.

Fig. S6: Model-to-brain mapping for a model with $\alpha = 25$ using a self-supervised, SimCLR, objective.

in the subject brain, and then these maps were divided based on stream assignment, yielding three separate maps (one for each of Ventral, Lateral and Parietal). These maps were smoothed with a two-dimensional Gaussian with $\sigma = 0.1$ and then thresholded at 50%. Groups of contiguous pixels that represented at least 5% of the total map were grouped and considered a cluster. This process was applied to all combinations of subjects and model to determine the number of clusters for each stream and mapping.

Secondly, we attempted to evaluate the level of spatial clustering among unit assignments using a histogram-based approach. In this approach, we once again divide each model-to-brain map into three binary maps by stream assignment. As a control, we also generate three maps for each model-to-brain mapping where, for each stream, we took the number of units assigned to that stream and created a binary map where the positions were randomly shuffled across possible unit positions. We then divided each map into a $N \times N$ grid, where N was calculated as 10% of the total extent of the mapping (yielding a 10×10 grid of bins in the model-to-brain case), and calculated the entropy of the 2D histogram. We chose to calculate entropy of the 2D histogram as high entropy across bins would suggest high disorder/randomness of the point distribution while low entropy would signify a non-random distribution of points across spatial locations, i.e. "clusteriness". This value for the actual assignment (True) was normalized by the value for the randomized maps (Shuffled), such that a value of 1.0 indicates a model-to-brain mapping for that stream which was as randomly distributed as a random shuffle of the points (i.e. no "clusteriness") and lower values indicate a higher degree of "clusteriness". The same procedure was done for the subject-to-subject maps as a comparison point.

We also calculated a metric based on Ripley's K [27], which is simply computed by centering a circle of radius d on each sampling point and counting the number of neighboring events that fall inside it (d was set to equal 10% of the total extent of the map, to mirror the 2D histogram entropy calculation). Ripley's K was again calculated for the actual assignment (True) and normalized by the value for the randomized maps (Shuffled) for each stream and model-to-brain (or brain-to-brain) mapping. In this case, higher values indicate more "clusteriness". While exact values differ, results using this approach and the 2D histogram entropy approach largely converge (see S7 below).

Fig. S7: "Clusteriness" as measured by Ripley's K for the model-to-brain mapping. Shaded bars: same except for brain-to-brain mapping (mean±SE across target subjects).

A.6 Task as an organizing force

A.6.1 1-to-1 mapping

We attempted to test the hypothesis that different tasks would serve as an equal or better organizing force in the following way. We chose models trained on object categorization, action recognition and object detection as they have been commonly proposed in the literature as candidate tasks for

the Ventral, Lateral and Parietal streams respectively. For the object categorization model, we used a ResNet-50 trained on object categorization on ImageNet. For the action recognition model, we chose the SlowFast model architecture [28], which is a dual-pathway network with a 3D ResNet-50 backbone trained on the Kinetics-400 video dataset [29]. Finally, for the object detection model, we used a Faster R-CNN[30], with a ResNet-50 architecture as its base network, trained on MS-COCO [31]. For all networks, we used layer 4.1 or its equivalent, as this was found to be the best fitting layer for all of the high-level stream ROIs in previous results using linear regression [14]

We then subsampled an equal number of units from each network so that the total number of units was equal to the total number of voxels and then applied the one-to-one mapping procedure (Algorithm 1) from the main text to assign units to voxels (we were unable to apply Algorithm 2 as the units in these networks do not have spatial positions). For each stream ROI, we could then quantify what percentage of voxels "chose" what model. We additionally ran two control analyses: (1) a partially random control analysis where the object recognition model was trained but the action recognition and object detection models were not, in order to determine how much of the organization was mainly due to the organizing power of the object recognition model, and (2) a fully random control where random weights were used for all networks, and thus any structure in assignment could not be attributed to the task.

We found that voxels from each stream ROI did in fact "choose" units from models trained using their hypothesized task slightly more than chance (mean $\pm$ SE: ventral and object recognition = 41.9% $\pm$ 0.7; lateral and action recognition = 37.8% $\pm$ 0.4; parietal and object detection = 35.8% $\pm$ 0.6). However, this was also true for the partially random control. A two-way repeated measures ANOVA with the factors analysis type ('trained', 'partially random', 'fully random') and ROI/task comparison ('ventral/object recognition', 'lateral/action recognition', 'parietal/object detection') revealed a significant interaction ($F(4, 28) = 9.4$, $p = 6.0 \times 10^{-5}$), which post-hoc Tukey tests showed was driven by significant differences between trained and fully random for the ventral/object recognition ($p = .001$) and parietal/object detection ($p = .007$) pairings. All comparisons between trained and the partially random control were non-significant (all $ps > 0.21$). This suggests that at least the above chance assignment of lateral voxels to action recognition and parietal voxels to object detection could not stem from training on the task objective.

Fig. S8: For each row (i.e. stream ROI), the percentage of voxels from that ROI that "chose" each of the three candidate models (averaged across subjects). (A) Candidate models are 1. ResNet-50 trained on object recognition, 2. SlowFast trained on action recognition and 3. Faster-RCNN trained on object detection. (B) Partially random control where candidate models are 1. ResNet-50 trained on object recognition, 2. SlowFast untrained and 3. Faster-RCNN untrained. (C) Fully random control where candidate models are 1. ResNet-50 untrained, 2. SlowFast trained on action recognition and 3. Faster-RCNN trained on object detection.

A.6.2 Preliminary linear regression results

We also used a linear encoding model approach, for comparison to earlier literature, where we extracted features in response to the NSD images for each layer of a number of object categorization and action recognition trained models. As in [13], we first projected these features into a lower dimensional space using a subsample of the ImageNet validation images and retained the first 1000 PCs. We then used ridge regression, with the alpha parameter cross-validated within the training set, to map these features to the individual voxel responses. Performance was evaluated on a left-out test set (80/20 split) for each subject separately and we report either the raw R^2 or the R^2 value normalized by the individual voxel noise ceiling for the best performing layer of each network. Subject-to-subject

predictivity (shaded gray region) was calculated to match the model-to-subject mapping as closely as possible, using ridge regression, with N-1 subjects' voxel responses to the shared images for each ROI used as features to predict the left-out subject. This preliminary analysis revealed that while some object categorization trained networks fit the ROIs better than others, these networks fit ventral and lateral (and parietal, when the subject-to-subject noise ceiling is taken into account), equally well. The same is true for the action recognition networks, as while they predict voxel responses across streams worse than the best object categorization trained models, their predictivity is similar across streams, particularly across the ventral and lateral ROIs.

Fig. S9: Comparison of model fits across object and action recognition models & stream ROIs. R^2 values are normalized by the noise ceiling (NC) of each voxel such that 1.0 corresponds to the intrinsic data NC. Each dot represents a subject. Shaded gray error bars: range of subject-to-subject NC.

A.7 Smoothness of the mapping

Fig. S10: How distance between assignments in the source space changes as distance between units in the target space increases for Algorithms 1 (A) and 2 (B). Best spatial model (purple) is $\alpha = 0.25$. All estimates are averaged across source subjects and the shaded region represents SE across source subjects.

A.8 Additional limitations

A further limitation of this work is the static nature of the stimuli used in the neural data collection. While there is sufficient variability in responses across streams within this dataset[14], the static nature of the stimuli and single task required of participants while viewing means we are limited to purely asking about the largely task-free generation of visual representations. It is entirely possible that the information carried by voxels in each stream would differ considerably given different task demands in data collection or a multimodal and dynamic dataset. We hope to see this question pursued in the future.