IESR: Efficient MCTS-Based Modular Reasoning for Text-to-SQL with Large Language Models

Abstract

Text-to-SQL is a key natural language processing task that maps natural language questions to SQL queries, enabling intuitive interaction with web-based databases. Although current methods perform well on benchmarks like BIRD and Spider, they struggle with complex reasoning, domain knowledge, and hypothetical queries, and remain costly in enterprise deployment. To address these issues, we propose a framework named **IESR**(**I**nformation **E**nhanced **S**tructured **R**easoning) for Lightweight Large Language Models: (i) leverages Large Language Models (LLMs) for key information understanding and schema linking, and decoupling mathematical computation and SQL generation, (ii) integrates a multi-path reasoning mechanism based on Monte Carlo Tree Search (MCTS) with majority voting, and (iii) introduces a trajectory consistency verification module with a discriminator model to ensure accuracy and consistency. Experimental results demonstrate that **IESR** achieves state-of-the-art performance on the complex reasoning benchmark LogicCat (24.28 EX) and the Archer dataset (37.28 EX), using only compact 7B and 8B models without fine-tuning. Furthermore, our analysis reveals that current coder models exhibit notable biases and deficiencies in physical knowledge, mathematical computation, and common-sense reasoning, highlighting important directions for future research. We release the code in an anonymous repository for reproducibility.

1 Introduction

Text-to-SQL aims to translate natural language queries into executable SQL, enabling intuitive interaction with databases and reducing manual effort (Zelle and Mooney, 1996; Lei et al., 2025). Recent advances have reported strong performance on widely used benchmarks such as Spider (Yu

Code: https://anonymous.4open.science/r/IESR-SLM-2886.

Figure 1: Motivation for Decoupling Mathematical Computation and SQL Generation in Text-to-SQL.

et al., 2019) and BIRD (Wretblad et al., 2024), achieving execution accuracies above 90% and 70% respectively (Pourreza et al., 2025; Talaei et al., 2024; Li et al., 2025c). However, these benchmarks largely reflect simplified settings, where many queries can be solved through shallow pattern matching and limited reasoning. In contrast, recent benchmarks including LogicCat (Liu et al., 2025a) and Archer (Zheng et al., 2024) reveal fundamental limitations of existing Text-to-SQL systems by requiring cross-domain reasoning that integrates mathematical computation, physical units, commonsense constraints, and hypothetical conditions. Under such settings, current methods either degrade sharply or depend on substantially larger models and inference budgets, exposing a flawed assumption that schema grounding, logical reasoning, and numerical computation can be reliably resolved within a single or locally consistent generation pass.

Multi-agent and iterative reasoning have been explored to address this issue (Talaei et al., 2024; Pourreza et al., 2025; Deng et al., 2025a), but general-purpose agent and planning paradigms (Wei et al.; Wang et al., 2023; Shinn et al., 2023; Yao et al., 2023; Song et al., 2025) re-

main ill-suited to the structured and high-stakes nature of SQL execution. In particular, heterogeneous decision factors—such as schema selection, join construction, aggregation, filtering logic, grouping structure, and arithmetic formulas—are often tightly entangled during generation, so that minor deviations in numerical or semantic reasoning can invalidate an otherwise correct SQL structure. This tight coupling leads to unclear credit assignment, error propagation, and instability under multi-step reasoning (Xia et al., 2024).

To address these limitations, we propose **IESR** (**I**nformation **E**nhanced **S**tructured **R**easoning) for Large Language Models, a modular reasoning framework for complex Text-to-SQL generation and hereafter referred to as IESR. Unlike previous search-based or agent-based works (Li et al., 2025b; Cen et al., 2025; Wang et al., 2025) that still treat mathematical reasoning as part of SQL generation, our formulation explicitly separates symbolic computation as an independent reasoning dimension. As illustrated in Figure 1, IESR is motivated by the observation that mathematical computation is structurally orthogonal to SQL construction once relevant numerical attributes are identified. Accordingly, IESR decomposes the task into three tightly coupled stages that explicitly compensate for the failure modes of moderate-scale large language models: (i) an *information understanding* stage that extracts semantic hypotheses and performs schema-guided compression, (ii) an *MCTS-based reasoning* stage that explores multiple SQL generation trajectories with decoupled reasoning dimensions, and (iii) a *trajectory selection* stage that verifies and aggregates candidate SQL paths.

Without instruction fine-tuning, IESR operates entirely with moderate-scale open-source large language models and achieves strong performance on complex mathematical, physical, and hypothetical queries. Experiments demonstrate that IESR attains state-of-the-art(SOTA) results on LogicCat and competitive performance on Archer, while requiring only lightweight model calls. Ablation studies further confirm the importance of information understanding, structured search, and consistency-based verification in improving robustness and execution accuracy.

The main contributions of this work are summarized as follows:

- We propose **IESR**, a structured MCTS-based reasoning framework that integrates infor-

mation understanding, schema linking, and trajectory-level verification for complex Text-to-SQL tasks.
- We demonstrate SOTA performance on challenging benchmarks such as LogicCat and strong results on Archer, validating the effectiveness of explicit reasoning structure in multi-domain SQL generation.
- We show that **IESR** is compatible with moderate-scale open-source large language models and requires no instruction fine-tuning, enabling robust Text-to-SQL reasoning under low-resource settings.

2 Related Work

2.1 Text-to-SQL with Decomposition and Search-based Reasoning

Recent advances in pre-trained language models and large language models (LLMs), such as T5 (Scholak et al., 2021), have substantially improved Text-to-SQL performance on benchmarks like Spider and BIRD. Many approaches address schema alignment and complex query generation by decomposing Text-to-SQL into subtasks such as candidate generation, refinement, and selection (Li et al., 2024a; Cao et al., 2024; Pourreza et al., 2025). Other methods introduce dynamic search spaces or Monte Carlo Tree Search (MCTS) to enhance exploration during SQL generation (Li et al., 2025b; Lyu et al., 2025; Qi et al., 2025). However, most of these approaches are developed and evaluated under the assumption of sufficiently strong backbone models, and implicitly rely on the local correctness of intermediate reasoning steps. When applied to moderate-scale large language models (LLMs), such assumptions often break down in queries involving long-range numerical dependencies, physical constraints, or cross-domain reasoning, where early locally plausible decisions can easily propagate into globally invalid SQL executions.

2.2 Agent-based and Structured Reasoning under Resource Constraints

Agent-based and structured reasoning frameworks further extend this line of work by enabling iterative planning, tool use, and self-correction. Representative methods include ReAct (Yao et al., 2023), Self-Debugging (Chen et al., 2023), Plan-and-Solve prompting (Guo et al., 2023; Li et al., 2024b, 2025b), and domain-specific SQL agents

Figure 2: The comprehensive workflow of IESR including three stages: Question Understanding with Schema Linking, Monte Carlo Tree Search(MCTS)-based Reasoning and Trajectory Selection with Mutual Reasoning Consistency.

such as CHESS and Chase (Talaei et al., 2024; Pourreza et al., 2025; Deng et al., 2025b). These methods demonstrate that iterative reasoning and modular workflows can improve robustness. However, most general-purpose agent frameworks are not tailored to the structured and high-stakes nature of SQL execution: minor semantic deviations—such as incorrect column grounding, unit mismatch, or implicit formula misuse—can invalidate an entire query. Moreover, many agent-based approaches rely on long-context prompting, learned critics, or large inference budgets, limiting their applicability to moderate-scale large language models. Structured pipelines inspired by Chain-of-Thought and consistency-based reasoning (Wei et al.; Wang et al.; Josifoski et al., 2023; Wu et al., 2024) partially mitigate these issues, but typically lack explicit search control and trajectory-level verification, motivating the need for principled search-based reasoning with lightweight consistency validation.

3 Methodology

Motivated by the need to extract structured semantics and user intent from natural language questions and propagate them into schema linking and multi-step reasoning. Figure 2 presents IESR, a modular Text-to-SQL framework with three components: question understanding, MCTS-based reasoning, and trajectory selection. IESR first extracts structured semantics and aligns them with relevant schema, then explores multiple reasoning trajectories via MCTS, and finally select the most reliable SQL.

3.1 Question Information Understanding

Intent and Information Understanding. To capture user intent and task-relevant semantics for schema selection and downstream reasoning, we focus on multi-domain queries spanning physics, mathematics, and general knowledge. Instead of directly grounding a query to schema elements, we first construct an intermediate *latent semantic state* that represents semantic hypotheses implied by the query, improving robustness to ambiguity and long-context noise. Detailed algorithm listed at Appendix B.2.

Formally, the input consists of a natural language query q and the complete database schema $S = (T, C)$, where T and C denote tables and columns. Using lightweight language models, we

generate an over-complete but high-recall set of semantic hypotheses, which are subsequently refined through consistency verification and used to guide schema compression and reasoning.

Given q and S, the language model produces a latent semantic state:

$$\mathcal{S}_q = (i, r, E, \mathcal{R}, N, U, P), \qquad (1)$$

where E denotes extracted entities, $\mathcal{R}$ candidate relations and schema references, N numeric expressions, U associated units, and P candidate field patterns. We treat $\mathcal{S}_q$ as a set of noisy semantic hypotheses rather than deterministic predictions, favoring recall at this stage.

Constraint-aware Relation Filtering. To mitigate hallucination and semantic drift, we introduce a set of domain-agnostic *consistency constraints* that evaluate the internal coherence of semantic hypotheses. From $\mathcal{S}_q$, we obtain an initial relation set $\mathcal{R}_{\text{init}}$. Each constraint encodes compatibility among entities, units, and transformation patterns:

$$C_j = (\text{Enti}_j, \text{Uni}_j, \text{Equt}_j). \qquad (2)$$

Candidate relations are filtered via semantic compatibility:

$$\mathcal{R}_{\text{cand}} = \{\, r_i \in \mathcal{R}_{\text{init}} \mid \text{MATCH}(r_i, \mathcal{C}) \,\}. \qquad (3)$$

Here, $\text{MATCH}(r_i, \mathcal{C})$ holds if there exists a constraint $C_j \in \mathcal{C}$ such that $\text{sim}(r_i, \text{Uni}_j, \text{Equt}_j) > \delta_{\text{match}}$ and $\text{sim}(\cdot)$ is implemented by a lightweight matcher $\mathcal{M}_{\text{match}}$.

Soft Consistency Scoring. The filtered relations $\mathcal{R}_{\text{cand}}$ are evaluated by a *Plan & Executor* module, which assigns a soft consistency score:

$$P_i = \text{Plan}(r_i, \mathcal{C}), \quad s_i = \text{Executor}(r_i, P_i), \qquad (4)$$

where $s_i \in [0, 1]$ reflects the degree of consistency between a semantic hypothesis and the constraint set. We intentionally adopt this non-learned, constraint-based scorer to ensure robustness in low-resource settings and avoid additional supervision or training overhead.

Relations with scores above a threshold τ are retained:

$$\mathcal{R}_{\text{high}} = \{\, r_i \in \mathcal{R}_{\text{cand}} \mid s_i > \tau \,\}. \qquad (5)$$

The resulting validated semantic state conditions subsequent schema linking and compression, enabling relevance estimation beyond the raw query.

Schema Linking and Compression. Conditioned on the validated semantic state from the previous stage, we perform schema linking and compression to surface task-relevant structures and constrain the reasoning search space. Following the M-Schema technique (Liu et al., 2025b), we encode schema elements in a semi-structured format with explicit annotations, and apply lightweight filtering to retain only high-salience fields. We employ two complementary strategies:

- **Locality-Sensitive Hashing (LSH):** filters tables and columns by lexical similarity, efficiently narrowing candidate schema elements.

- **Semantic Similarity Matching:** selects schema elements whose semantic representations are most relevant to the conditioned query.

Given the large size of full schema where only a small subset is relevant per query, the refined schema with key fields and annotations is provided to the reasoning agent for subsequent processing.

3.2 MCTS-based CoT Reasoning

Problem Formulation. Following prior work (Qi et al., 2025; Li et al., 2025b), we formulate Text-to-SQL generation as a multi-step reasoning task and adopt Monte Carlo Tree Search (MCTS) to progressively decompose the problem into candidate reasoning trajectories. This formulation alleviates the difficulty faced by moderate-scale large language models when generating complete reasoning chains in a single step. Unlike beam search or self-consistency, MCTS explicitly balances exploration and exploitation over heterogeneous reasoning actions, which is critical when intermediate reasoning steps exhibit highly uneven utility in complex SQL generation. Detailed algorithm listed at Appendix B.2.

We define the reasoning state as a tuple consisting of the partial SQL hypothesis and its associated semantic context. A reasoning trajectory corresponds to a path from the root to a terminal node in the search tree. From the search tree T, we extract a set of candidate trajectories:
$$\mathcal{T} = \{t_1, t_2, \ldots, t_n\}, \quad n \geq 1.$$

Human-inspired Reasoning Actions. Most existing MCTS-based methods rely on a single action type, typically generating the next reasoning step (Chen et al., 2024). However, due to the structural and semantic complexity of SQL generation,

Figure 3: A visual illustration of heterogeneous MCTS actions (A1–A6) for SQL generation and reasoning.

a single action type often results in inefficient exploration, as illustrated in Figure 2.

Formally, we view each reasoning action as a state transition operator that transforms the current reasoning state—comprising the partial SQL structure and semantic context—along a distinct semantic dimension such as schema grounding, numerical reasoning, or structural refinement.

Inspired by human problem-solving strategies listed at Figure 3, we design a diverse action space, where each action induces a transition over a structured reasoning state. A formal definition of the node space and its representation is provided in Appendix B.

- **Equation Analysis**: explicit modeling of formulas and numerical relations (Mao et al., 2025).
- **Schema Selection**: identifying task-relevant tables and columns from large schemas (Li et al., 2025b; Talaei et al., 2024).
- **Identify Columns**: resolving ambiguous schema fields using semi-structured semantic cues (Li et al., 2025a).
- **Entity Extraction**: grounding entities and relations for accurate filtering and joins.
- **SQL Generation**: constructing executable SQL queries, particularly nested structures (Pourreza et al., 2025).
- **SQL Revision**: correcting erroneous queries via reasoning over formulas, units, and do-

main knowledge.

At each step, MCTS selects an action from this space and generates the next reasoning state accordingly.

Reward-based Node Evaluation. The reward function guides trajectory quality in MCTS. In our low-resource setting, we adopt an execution-based, terminal-only self-consistency reward without learned critics, following Alpha-SQL (Li et al., 2025b). When MCTS reaches a terminal node and produces a candidate SQL y, we sample N additional SQL queries $\{y_i\}_{i=1}^{N}$ under the same terminal context and execute them on database D. The reward is defined as the agreement rate of execution results:

$$r_t = R(y, q, D) = \frac{1}{N}\sum_{i=1}^{N}\mathbf{1}\Big[\text{EXECUTE}(y, D) \\ = \text{EXECUTE}(y_i, D)\Big]. \quad (6)$$

MCTS Search and Backpropagation. Given a rollout path consisting of nodes $v_0, \ldots, v_d$ and actions $a_1, \ldots, a_d$, we backpropagate the terminal reward r_t to update visit counts and cumulative values:

$$N(v_i, a_{i+1}) \leftarrow N(v_i, a_{i+1}) + 1, \\ Q(v_i, a_{i+1}) \leftarrow Q(v_i, a_{i+1}) + R(y, q, D), \quad (7)$$

for $i = 0, \ldots, d-1$. Action selection follows the standard UCT criterion:

$$UCT(v, a) = \frac{Q(v, a)}{N(v, a)} + c\sqrt{\frac{\ln N(v)}{N(v, a)}}. \quad (8)$$

The search iterates through selection, expansion, simulation, and backpropagation. After N_{rollout} rollouts, all terminal trajectories are collected as candidate SQL queries for subsequent selection and verification.

3.3 Trajectory Selection with Mutual Reasoning Consistency

To reliably select executable and semantically consistent SQL from noisy candidates, we introduce a collaborative selection mechanism between a primary model LLM_1 and a secondary verifier LLM_2. Detailed algorithm listed at Appendix B.2.

Discriminator Consistency Verification. For a candidate reasoning trajectory $t = x \oplus s_1 \oplus s_2 \oplus \cdots \oplus s_d$, we assess its logical self-consistency via a masking-and-completion procedure. Specifically,

we mask the reasoning process at an intermediate step i ($i < d$), retaining only the first $i - 1$ intermediate steps such as selected tables, partial columns, or partial WHERE conditions. The incomplete sequence is then provided to the verifier LLM_2 for completion.

If the SQL completed by LLM_2 remains semantically consistent with the original trajectory t, e.g., leading to equivalent schema grounding and logically compatible SQL structures, the trajectory is considered logically stable and retained. This procedure acts as a consistency check over reasoning trajectories, probing whether the same semantic constraints can be recovered from incomplete intermediate states. Here, LLM_2 is a lightweight language model of comparable scale to LLM_1 and is used in a frozen manner without additional supervision.

Scoring Mechanism. To select the most reliable SQL from filtered candidates, we assign a composite score to each trajectory:

$$\begin{aligned} \text{Score}(t) = {} & \alpha \cdot \text{Exec}(t) \\ & + \beta \cdot \text{DiscConf}(t) + \gamma \cdot \text{ConsVote}(t). \end{aligned} \quad (9)$$

Here, $\text{Exec}(t)$ evaluates execution correctness or equivalence when available, while $\text{DiscConf}(t)$ and $\text{ConsVote}(t)$ provide lightweight consistency signals derived from discriminator verification and peer agreement, respectively. The coefficients α, β, γ are fixed to balance executability and consistency, with consistency serving as auxiliary evidence. Detailed representation is illustrated at Appendix A.6.

The final SQL answer is selected by maximizing $\text{Score}(t)$ over all candidate trajectories.

4 Experiments

We conduct comprehensive experiments to evaluate the effectiveness, robustness, and efficiency of IESR on complex Text-to-SQL benchmarks, with a particular focus on mathematical, physical, and hypothetical reasoning under model settings.

4.1 Experimental Setup

Datasets. We evaluate IESR on two challenging reasoning-oriented benchmarks, LogicCat (Liu et al., 2025a) and Archer (Zheng et al., 2024), which require multi-domain reasoning including mathematics, physics, commonsense, and hypothetical analysis. To assess generalization beyond complex reasoning, we additionally report results on two widely used Text-to-SQL benchmarks,

BIRD (Wretblad et al., 2024) and Spider (Yu et al., 2019). Detailed datasets listed at Appendix C.

Baseline. We compare IESR with representative SOTA Text-to-SQL systems, including DIN-SQL (Pourreza and Rafiei, 2023), DAIL-SQL (Gao et al., 2023), DTS-SQL (Pourreza and Rafiei, 2024), CHESS (Talaei et al., 2024), LinkAlign (Wang and Liu, 2025), Alpha-SQL (Li et al., 2025b), and SQL-O1 (Lyu et al., 2025). These methods cover a broad range of paradigms such as decomposed prompting, schema linking, hierarchical reasoning, and MCTS-based search. Detailed public methods listed at Appendix C.

Backbone Models. For the information understanding module, we evaluate several general-purpose LLMs and select Qwen3-8B (Yang et al., 2025) for its favorable balance between reasoning capability and efficiency. For MCTS-based reasoning, we adopt four code-oriented models: Qwen2.5-Coder-7B (Hui et al., 2024), XiYanSQL-QwenCoder-7B-2504 (Gao et al., 2025), Seed-Coder-8B (Seed et al., 2025), and OmniSQL-7B (Li et al., 2025c). For trajectory consistency verification, we employ Qwen3-4B as a lightweight discriminator, which offers strong consistency assessment with minimal overhead.

Evaluation Metric. We adopt the widely used metric Execution Accuracy (EX) (Pourreza et al., 2025). This evaluates where a query is correct only if its execution result matches that of the ground-truth query.

Experiment Details. The experiments were carried out on a cloud server with four RTX 4090 GPU. LLM reasoning was managed through the Hugging Face repository and official APIs. The hyperparameters of all baselines are associated with their original implementation and all other hyperparameters of LLMs are default, following rStar(Qi et al., 2025) and prompt listed at Appendix E.

4.2 Main Results

Overall Performance Table 1 shows that IESR consistently outperforms all reproduced baselines across both complex LogicCat or Archer benchmarks and general BIRD or Spider benchmarks. Notably, the performance gains are most pronounced on LogicCat and Archer, demonstrating the effectiveness of IESR for complex multi-step reasoning. Comparison with baseline LLMs performance is listed at Appendix A.

LogicCAT Analysis As illustrated in Figure 4, IESR achieves substantial improvements across all

Method	Qwen2.5-Coder	XiYanSQL	OmniSQL	Seed-Coder	Qwen2.5-Coder	XiYanSQL	OmniSQL	Seed-Coder
Size		7B		8B		7B		8B
	LogicCat EX(%)				**Archer-Dev EX(%)**			
Cot-sql	5.07	7.89	6.93	6.58	17.16	18.46	18.14	19.89
Din-sql	10.31	11.56	9.56	8.98	31.45	34.41	26.04	29.13
DAIL-sql	10.73	10.98	9.43	8.18	29.67	32.28	27.56	24.12
DTS-SQL	14.12	14.88	12.67	10.31	31.88	33.17	32.14	30.33
CHESS-SQL	16.16	19.21	10.89	14.52	32.45	35.54	27.27	31.56
LinkAlign	19.56	22.56	14.34	18.89	29.21	31.28	30.21	30.10
Alpha-SQL	18.32	19.78	16.56	19.34	28.32	30.12	29.88	31.22
SQL-O1(tuning)	16.42	17.91	13.24	17.33	26.56	28.22	27.41	28.78
Standard COT	10.07	16.83	11.56	14.53	-	-	-	-
IESR	**21.66**	**24.28**	**22.41**	**22.11**	**35.21**	**37.28**	**33.11**	30.66
	Bird-Dev EX(%)				**Spider EX(%)**			
Cot-sql	31.22	33.58	37.58	30.16	65.32	69.12	68.32	66.23
Din-sql	51.78	52.45	51.23	49.88	77.19	79.30	76.80	78.01
DAIL-sql	52.12	51.16	52.23	50.66	80.31	82.56	81.56	82.98
DTS-SQL	58.32	60.78	61.56	58.18	**84.12**	85.09	**84.99**	83.21
CHESS-SQL	56.80	60.13	57.96	57.22	80.31	83.30	77.02	81.31
LinkAlign	58.90	61.32	60.56	54.78	80.11	85.89	82.32	82.12
SQL-O1(tuning)	66.70	67.21	61.39	64.67	85.10	**86.54**	81.12	**85.25**
Alpha-SQL	**66.80**	**67.92**	**62.32**	**65.13**	84.0	84.93	79.34	84.37
IESR	54.80	62.22	56.22	58.96	83.45	83.36	80.02	79.22

Table 1: Overall Performance of models and performance of models by **Qwen2.5-Coder**,**XiYanSQL-QwenCoder**, **OmniSQL**, **seed-Coder** on **LogicCat**, **Archer**, **Bird**, **Spider** public dataset. **EX** denotes Execution Accuracy (matching the gold result). **Bold** values are the best **EX** in that column. **-** represent no experimentation.

	Qwen2.5-Coder-7B		XiYanSQL-QwenCoder-7B		Seed-coder-8B		OmniSQL-7B	
Configuration	EX	Drop	EX	Drop	EX	Drop	EX	Drop
Full Model (IESR)	**21.66**	-	**24.28**	-	**22.11**	-	**22.41**	-
Core Stage Isolation								
- Stage 1.1+2+3 Only (w/o)	19.96	1.70	21.68	2.60	20.41	1.70	21.42	0.99
- Stage 1.2+2+3 Only (w/o)	19.28	2.38	20.21	4.07	19.22	2.89	20.42	1.99
- Stage 1+2+3.1 Only (w/o)	19.24	2.42	21.83	2.45	18.29	3.82	19.14	3.27
- Stage 1+2+3.2 Only (w/o)	18.11	3.55	20.63	3.65	17.21	4.90	18.94	3.47
- Stage 1 (w/o)	11.12	10.54	14.36	9.92	9.42	12.69	12.67	9.74

Table 2: Comprehensive ablation study of IESR components across four backbone models on the LogicCat dataset. We report **EX** and the absolute performance drop in percentages (%). Understanding for Intent and Information Understanding. Linking for Schema Linking and Compression. Consistency Verification for Discriminator Consistency Verification. Reasoning and Discriminator Agent for MCTS-based CoT Reasoning and Trajectory Selection with Mutual Reasoning Consistency.

difficulty levels, with the largest gains observed on the Hard subset. Further analysis by reasoning type reveals that current code-oriented LLMs perform significantly worse on physical and mathematical reasoning compared to commonsense queries, highlighting a critical limitation. IESR effectively mitigates this gap through structured reasoning and trajectory verification.

4.3 Ablation Analysis

Component Contribution Analysis. Table 2 presents ablation results for IESR. Removing any module degrades performance, with the largest drops observed when disabling MCTS-based reasoning or schema linking, indicating their central role. Consistency verification and scoring yield

smaller but consistent improvements, confirming their effectiveness as lightweight reliability enhancements. More error analysis are listed at Appendix A.

Action	Qwen2.5-Coder	XiYanSQL	OmniSQL	Seed-Coder
All actions	21.66	24.28	22.11	22.41
w/o A1	21.45 (↓ 0.21)	24.02 (↓ 0.26)	21.92 (↓ 0.19)	22.23 (↓ 0.18)
w/o A2	20.83 (↓ 0.83)	23.88 (↓ 0.40)	20.68 (↓ 1.43)	22.01 (↓ 0.40)
w/o A3	20.32 (↓ 1.34)	23.25 (↓ 1.03)	19.78 (↓ 0.33)	22.12 (↓ 0.29)
w/o A4	20.86 (↓ 0.80)	23.87 (↓ 1.31)	20.89 (↓ 0.80)	21.98 (↓ 0.43)
w/o A6	20.12 (↓ **1.54**)	22.12 (↓ **2.16**)	19.21 (↓ **2.90**)	21.15 (↓ **1.26**)

Table 3: Ablation study on the reasoning action space (A1–A4, A6), corresponding to the reasoning actions defined in Section 3.2. We do not ablate A5 (SQL Generation) since removing it yields degenerate trajectories. The evaluation metric is **EX** (execution accuracy).

Figure 5: Ablation study of N_{rollout} across four backbone models on the LogicCat dataset.

Figure 4: Performance heatmap of different methods on the LogicCat dataset across three difficulty levels (Easy, Medium, Hard) and different reasoning types.

	table		column		unit_num		operator	
	P	R	P	R	P	R	P	R
Qwen2.5-7B-Instruct	64.60	63.80	57.28	57.77	57.86	57.90	77.85	73.96
Qwen3-8B	75.25	73.54	63.32	62.30	60.80	61.06	77.02	75.36
Deepseek-V3	76.72	74.81	67.34	66.67	62.88	62.18	78.18	74.03
Deepseek-R1	78.09	75.35	62.91	62.02	60.52	60.32	76.00	72.20
Gemini2.5-Flash	87.08	92.79	77.70	82.78	78.94	80.20	92.75	**92.16**
GPT-4o	88.73	**93.02**	**79.80**	84.11	79.77	80.31	92.75	92.10
Qwen2.5-7B-Instruct+Ve	87.46	89.87	79.41	82.72	79.88	80.30	91.53	89.50
Qwen3-8B+Ve	**90.09**	91.24	78.20	**83.24**	**81.02**	**81.11**	**92.91**	91.31

Table 4: Precisions and Recalls of schema items, units, key numbers, and compute operators used in verification. **Ve** for Keywords Verification.

Action Space Analysis. This experiment evaluates the contribution of individual reasoning actions in the proposed action space. Following rStar (Qi et al., 2025), we conduct action-level ablation on the LogicCat dataset by removing one reasoning action at a time while keeping all other settings unchanged. The results in Table 3 show that removing any remaining action consistently degrades performance across all backbone models, indicating that each reasoning action contributes to effective exploration. Notably, removing the SQL revision action results in the largest performance drop, highlighting its critical role in correcting intermediate reasoning errors and refining executable SQL queries.

4.4 N_{rollout} Analysis

Shown in Figure 5 disabling schema compression leads to a clear performance decrease, confirming the role of schema understanding in Text-to-SQL tasks. We observe that increasing the number of N_{rollout} generally improves the reliability and performance of the output, as greater diversity and consensus help filter out spurious results. In particular, our best results are achieved with 32 N_{rollout}, indicating that a larger ensemble improves robustness. However, as the number of N_{rollout} increases beyond 32, performance gains tend to plateau and may even decline. This is likely because excessive rollouts introduce more noisy or low-quality reasoning paths, which can dilute the effectiveness of the majority-voting strategy. Detailed Experiments are shown at Appendix A.2.

4.5 Different Models on Information Understanding Analysis

With the Verification module in place, shown in Table 4, the extractor shifts from a pattern matching heuristic to a recall amplifying pipeline that systematically recovers missed schema cues and normalizes numbers and units without sacrificing precision. This manifests itself most strongly in the long-tail fields (*column*, *unit_num*) where add Verification delivers large double-digit recall gains, while on *table* and *operator* the verified Qwen3-8B climbs into the same performance regime as frontier models such as GPT-4o and Gemini-2.5-Flash. The improvements are not cosmetic: precision rises alongside recall, indicating that verification corrects upstream omissions and inconsistencies rather than merely relaxing decision thresholds.

5 Conclusion

We propose IESR, a MCTS based framework that integrates information understanding and schema linking for complex Text-to-SQL reasoning. Our method achieves SOTA performance on LogicCat and Archer while producing more efficient and robust SQL generation, as validated by comprehensive ablation studies.

Limitations

While IESR demonstrates strong performance on complex reasoning–oriented Text-to-SQL benchmarks, it also has limitations. First, the framework relies on the quality of early semantic hypothesis extraction; errors in entity, unit, or formula identification may propagate into subsequent schema compression and search. Second, although MCTS enables structured exploration, it introduces additional inference cost compared to single-pass generation, and the search budget must be carefully tuned to avoid diminishing returns from noisy trajectories. Third, our reward design is execution- and consistency-based, which provides robust supervision without annotations but offers limited insight into intermediate reasoning errors. Moreover, our evaluation is conducted under controlled benchmark settings, and extending the framework to real-world databases with evolving schema or noisy execution environments remains an open challenge. Finally, we briefly discuss potential risks such as erroneous SQL execution and misinterpretation of complex queries, which could impact downstream decision-making if used without human oversight. We stress that automated Text-to-SQL systems should be deployed with appropriate validation in real-world scenarios.

References

Zhenbiao Cao, Yuanlei Zheng, Zhihao Fan, Xiaojin Zhang, Wei Chen, and Xiang Bai. 2024. Rsl-sql: Robust schema linking in text-to-sql generation. *Preprint*, arXiv:2411.00073.

J. Cen and 1 others. 2025. Sqlfixagent: Towards semantic-accurate text-to-sql. In *AAAI 2025*.

Guoxin Chen, Minpeng Liao, Chengxi Li, and Kai Fan. 2024. Alphamath almost zero: Process supervision without process. *Preprint*, arXiv:2405.03553.

Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. 2023. Teaching large language models to self-debug. *Preprint*, arXiv:2304.05128.

Minghang Deng, Ashwin Ramachandran, Canwen Xu, Lanxiang Hu, Zhewei Yao, Anupam Datta, and Hao Zhang. 2025a. Reforce: A text-to-sql agent with self-refinement, consensus enforcement, and column exploration. *Preprint*, arXiv:2502.00675.

Minghang Deng, Ashwin Ramachandran, Canwen Xu, Lanxiang Hu, Zhewei Yao, Anupam Datta, and Hao Zhang. 2025b. RefoRCE: A text-to-SQL agent with self-refinement, format restriction, and column exploration. In *ICLR 2025 Workshop: VerifAI: AI Verification in the Wild*.

Dawei Gao, Haibin Wang, Yaliang Li, Xiuyu Sun, Yichen Qian, Bolin Ding, and Jingren Zhou. 2023. Text-to-sql empowered by large language models: A benchmark evaluation. *Preprint*, arXiv:2308.15363.

Yingqi Gao, Yifu Liu, Xiaoxia Li, Xiaorong Shi, Yin Zhu, Yiming Wang, Shiqi Li, Wei Li, Yuntao Hong, Zhiling Luo, Jinyang Gao, Liyu Mou, and Yu Li. 2025. A preview of xiyan-sql: A multi-generator ensemble framework for text-to-sql. *Preprint*, arXiv:2411.08599.

Chunxi Guo, Zhiliang Tian, Jintao Tang, Pancheng Wang, Zhihua Wen, Kang Yang, and Ting Wang. 2023. Prompting gpt-3.5 for text-to-sql with de-semanticization and skeleton retrieval. *Preprint*, arXiv:2304.13301.

Binyuan Hui, Jian Yang, Zeyu Cui, Jiaxi Yang, Dayiheng Liu, Lei Zhang, Tianyu Liu, Jiajun Zhang, Bowen Yu, Keming Lu, Kai Dang, Yang Fan, Yichang Zhang, An Yang, Rui Men, Fei Huang, Bo Zheng, Yibo Miao, Shanghaoran Quan, and 5 others. 2024. Qwen2.5-coder technical report. *Preprint*, arXiv:2409.12186.

Martin Josifoski, Lars Klein, Maxime Peyrard, Yifei Li, Saibo Geng, JulianPaul Schnitzler, Yuxing Yao, Jiheng Wei, Debjit Paul, and Robert West. 2023. Flows: Building blocks of reasoning and collaborating ai.

Fangyu Lei, Jixuan Chen, Yuxiao Ye, Ruisheng Cao, Dongchan Shin, Hongjin SU, ZHAOQING SUO, Hongcheng Gao, Wenjing Hu, Pengcheng Yin, Victor Zhong, Caiming Xiong, Ruoxi Sun, Qian Liu, Sida Wang, and Tao Yu. 2025. Spider 2.0: Evaluating language models on real-world enterprise text-to-SQL workflows. In *The Thirteenth International Conference on Learning Representations*.

Boyan Li, Chong Chen, Zhujun Xue, Yinan Mei, and Yuyu Luo. 2025a. Deepeye-sql: A software-engineering-inspired text-to-sql framework. *Preprint*, arXiv:2510.17586.

Boyan Li, Yuyu Luo, Chengliang Chai, Guoliang Li, and Nan Tang. 2024a. The dawn of natural language to sql: Are we fully ready? *Proceedings of the VLDB Endowment*, 17(11):3318–3331.

Boyan Li, Jiayi Zhang, Ju Fan, Yanwei Xu, Chong Chen, Nan Tang, and Yuyu Luo. 2025b. Alpha-SQL: Zero-shot text-to-SQL using monte carlo tree search. In *Forty-second International Conference on Machine Learning*.

Haoyang Li, Shang Wu, Xiaokang Zhang, Xinmei Huang, Jing Zhang, Fuxin Jiang, Shuai Wang, Tieying Zhang, Jianjun Chen, Rui Shi, Hong Chen, and Cuiping Li. 2025c. Omnisql: Synthesizing high-quality text-to-sql data at scale. *Preprint*, arXiv:2503.02240.

Zhishuai Li, Xiang Wang, Jingjing Zhao, Sun Yang, Guoqing Du, Xiaoru Hu, Bin Zhang, Yuxiao Ye,

Ziyue Li, Rui Zhao, and Hangyu Mao. 2024b. Pet-sql: A prompt-enhanced two-round refinement of text-to-sql with cross-consistency. *Preprint*, arXiv:2403.09732.

Tao Liu, Hongying Zan, Yifan Li, Dixuan Zhang, Lulu Kong, Haixin Liu, Jiaming Hou, Aoze Zheng, Rui Li, Yiming Qiao, Zewei Luo, Qi Wang, Zhiqiang Zhang, Jiaxi Li, Supeng Liu, Kunli Zhang, and Min Peng. 2025a. Logiccat: A chain-of-thought text-to-sql benchmark for multi-domain reasoning challenges. *Preprint*, arXiv:2505.18744.

Yifu Liu, Yin Zhu, Yingqi Gao, Zhiling Luo, Xiaoxia Li, Xiaorong Shi, Yuntao Hong, Jinyang Gao, Yu Li, Bolin Ding, and Jingren Zhou. 2025b. Xiyan-sql: A novel multi-generator framework for text-to-sql.

Shuai Lyu, Haoran Luo, Ripeng Li, Zhonghong Ou, Jiangfeng Sun, Yang Qin, Xiaoran Shang, Meina Song, and Yifan Zhu. 2025. Sql-o1: A self-reward heuristic dynamic search method for text-to-sql. *Preprint*, arXiv:2502.11741.

Xutao Mao, Tao Liu, and Hongying Zan. 2025. Steiner-sql: Graph-guided mathematical reasoning for text-to-sql generation. *Preprint*, arXiv:2509.19623.

Mohammadreza Pourreza, Hailong Li, Ruoxi Sun, Yeounoh Chung, Shayan Talaei, Gaurav Tarlok Kakkar, Yu Gan, Amin Saberi, Fatma Ozcan, and Sercan O Arik. 2025. CHASE-SQL: Multi-path reasoning and preference optimized candidate selection in text-to-SQL. In *The Thirteenth International Conference on Learning Representations*.

Mohammadreza Pourreza and Davood Rafiei. 2023. DIN-SQL: Decomposed in-context learning of text-to-SQL with self-correction. In *Thirty-seventh Conference on Neural Information Processing Systems*.

Mohammadreza Pourreza and Davood Rafiei. 2024. DTS-SQL: Decomposed text-to-SQL with small large language models. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 8212–8220, Miami, Florida, USA. Association for Computational Linguistics.

Zhenting Qi, Mingyuan MA, Jiahang Xu, Li Lyna Zhang, Fan Yang, and Mao Yang. 2025. Mutual reasoning makes smaller LLMs stronger problem-solver. In *The Thirteenth International Conference on Learning Representations*.

Torsten Scholak, Nathan Schucher, and Dzmitry Bahdanau. 2021. Picard: Parsing incrementally for constrained auto-regressive decoding from language models. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*.

ByteDance Seed, Yuyu Zhang, Jing Su, Yifan Sun, Chenguang Xi, Xia Xiao, Shen Zheng, Anxiang Zhang, Kaibo Liu, Daoguang Zan, Tao Sun, Jinhua Zhu, Shulin Xin, Dong Huang, Yetao Bai, Lixin Dong, Chao Li, Jianchong Chen, Hanzhi Zhou, and 8 others. 2025. Seed-coder: Let the code model curate data for itself. *Preprint*, arXiv:2506.03524.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik R Narasimhan, and Shunyu Yao. 2023. Reflexion: language agents with verbal reinforcement learning. In *Thirty-seventh Conference on Neural Information Processing Systems*.

Jinwang Song, Hongying Zan, Kunli Zhang, Lingling Mu, Yingjie Han, Haobo Hua, and Min Peng. 2025. Jolt-sql: Joint loss tuning of text-to-sql with confusion-aware noisy schema sampling. *Preprint*, arXiv:2505.14305.

Shayan Talaei, Mohammadreza Pourreza, Yu-Chen Chang, Azalia Mirhoseini, and Amin Saberi. 2024. Chess: Contextual harnessing for efficient sql synthesis. *Preprint*, arXiv:2405.16755.

Lei Wang, Wanyu Xu, Yihuai Lan, Zhiqiang Hu, Yunshi Lan, Roy Ka-Wei Lee, and Ee-Peng Lim. 2023. Plan-and-solve prompting: Improving zero-shot chain-of-thought reasoning by large language models. *Preprint*, arXiv:2305.04091.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models.

Yihan Wang and Peiyu Liu. 2025. Linkalign: Scalable schema linking for real-world large-scale multi-database text-to-sql. *Preprint*, arXiv:2503.18596.

Ziyang Wang, Yuanlei Zheng, Zhenbiao Cao, Xiaojin Zhang, Zhongyu Wei, Pei Fu, Zhenbo Luo, Wei Chen, and Xiang Bai. 2025. Autolink: Autonomous schema exploration and expansion for scalable schema linking in text-to-sql at scale. *Preprint*, arXiv:2511.17190.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed Chi, Quoc Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models.

Niklas Wretblad, Fredrik Gordh Riseby, Rahul Biswas, Amin Ahmadi, and Oskar Holmström. 2024. Understanding the effects of noise in text-to-sql: An examination of the bird-bench benchmark. *Preprint*, arXiv:2402.12243.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, Ahmed Hassan Awadallah, Ryen W White, Doug Burger, and Chi Wang. 2024. Autogen: Enabling next-gen LLM applications via multi-agent conversations. In *First Conference on Language Modeling*.

Chunqiu Steven Xia, Yinlin Deng, Soren Dunn, and Lingming Zhang. 2024. Agentless: Demystifying llm-based software engineering agents. *Preprint*, arXiv:2407.01489.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao

Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. *Preprint*, arXiv:2210.03629.

Tao Yu, Rui Zhang, Kai Yang, Michihiro Yasunaga, Dongxu Wang, Zifan Li, James Ma, Irene Li, Qingning Yao, Shanelle Roman, Zilin Zhang, and Dragomir Radev. 2019. Spider: A large-scale human-labeled dataset for complex and cross-domain semantic parsing and text-to-sql task. *Preprint*, arXiv:1809.08887.

JohnM. Zelle and RaymondJ. Mooney. 1996. Learning to parse database queries using inductive logic programming. *National Conference on Artificial Intelligence,National Conference on Artificial Intelligence*.

Danna Zheng, Mirella Lapata, and Jeff Pan. 2024. Archer: A human-labeled text-to-SQL dataset with arithmetic, commonsense and hypothetical reasoning. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 94–111, St. Julian's, Malta. Association for Computational Linguistics.

A Experimental Analysis

A.1 Comparison with Baseline LLMs

In this section, we evaluate the baseline performance of LLMs on the LogicCat dataset, categorizing them into general LLMs (such as GPT-4o) and reasoning-oriented LLMs (such as DeepSeek-R1), all under the same Text-to-SQL prompt. As shown in Table 5, among the baseline models, o4-mini achieves the highest standalone accuracy (14.96%), outperforming both general-purpose models such as GPT-4.1 and reasoning-focused models such as Gemini-2.5-Flash. However, IESR, even when paired with a relatively moderate-scale large 7B parameter model, consistently exceeds all baselines, including o4-mini, highlighting the strength of the framework in targeting reasoning optimization. Furthermore, to demonstrate the plug-and-play advantage of IESR, we extended the experiments to Qwen2.5-7B-Instruct and Qwen3-8B. Compared to direct prompting, IESR substantially increases their execution accuracy by 17.0% and 16.5%, respectively, validating both the generalizability and effectiveness of the framework across various inference models.

A.2 Detailed N_{rollout} Analysis

As shown in Figure 5, disabling schema compression leads to a consistent performance drop

Model	Accuracy (EX%)
Deepseek-V3	8.70
GPT-4o	10.17
GPT-4.1	13.57
Gemini-2.5-Pro	10.17
Claude-3.7-Sonnet	13.99
Claude-4.0-Sonnet	11.51
Seed-Coder-8B-Reasoning	4.16
DeepSeek-R1	9.98
o4-mini	**14.96**
o3-mini	9.11
Qwen3-235B-A22B	10.52
Qwen3-Coder-480B-A35B-Instruct	9.42
+ IESR (Qwen2.5-Coder-7B)	**21.66 (↑ 6.70)**
+ IESR (XiYanSQL-QwenCoder-7B-2504)	**24.28 (↑ 9.32)**
+ IESR (OmniSQL-7B)	**22.41 (↑ 7.45)**
+ IESR (Seed-Coder-8B)	**22.11 (↑ 7.15)**
+ IESR (Qwen2.5-7B-Instruct)	**16.69 (↑ 1.73)**
+ IESR (Qwen3-8B)	**18.23 (↑ 3.27)**

Table 5: Comparison with Baseline LLMs on the Logic-Cat dataset. Comparing with o4-mini, **EX** shows Execution Accuracy.

across all backbones, highlighting the importance of schema understanding in constraining the search space for Text-to-SQL reasoning. Without compression, the reasoning agent must explore a larger set of tables and columns, which increases the likelihood of semantically mis-grounded yet executable SQL trajectories and reduces the stability of downstream aggregation.

We further observe that increasing N_{rollout} generally improves performance up to $N_{\text{rollout}} = 32$, where all models achieve their best results. This improvement can be attributed to enhanced exploration coverage and more reliable consensus estimation: a larger rollout budget increases the probability of sampling high-quality reasoning trajectories while reducing variance through majority voting.

However, performance gains saturate and may slightly decline beyond this point. We attribute this behavior to noise amplification effects: additional rollouts increasingly sample low-probability or semantically inconsistent trajectories, which can dilute the majority signal and introduce competition between incorrect but internally consistent modes. As a result, excessive rollouts do not provide independent evidence but may instead reinforce systematic biases of the backbone model.

Overall, these results indicate that a small rollout budget strikes the best balance between exploration and aggregation reliability. In practice, $N_{\text{rollout}} = 32$ offers a strong trade-off between robustness and noise, while larger budgets yield diminishing or even negative returns.

A.3 Error Analysis

We perform a detailed analysis of the errors of the IESR code agent frameworks on 500 randomly sampled examples shown in Figure 6. Representative errors along with their statistics and causal analysis are as follows.

Configuration	Qwen2.5-Coder		OmniSQL		Seed-Coder		XiYanSQL	
	EX	Drop	EX	Drop	EX	Drop	EX	Drop
SC@maj32	**21.66**	–	**24.28**	–	**22.11**	–	**22.41**	–
Ablation $N_{rollout}$								
SC@maj8	20.68	0.98	23.22	1.06	21.18	0.93	20.45	1.96
SC@maj16	20.40	1.26	23.86	0.42	21.45	0.66	20.81	1.60
SC@maj24	20.91	0.75	22.89	1.39	21.85	0.26	21.41	1.00
SC@maj40	21.12	0.54	23.86	0.42	21.45	0.66	20.98	1.43

Table 6: Ablation study of N_{rollout} across four backbone models on the LogicCat dataset. We report **EX** and the absolute performance drop (%). **XiYanSQL** refers to XiYanSQL-QwenCoder-7B-2504; **Qwen2.5-Coder** to Qwen2.5-Coder-7B; **OmniSQL** to OmniSQL-7B; and **Seed-Coder** to Seed-Coder-8B.

- **Schema Linking Errors (12.2%).** they occur when models incorrectly assign attributes to wrong tables, such as assuming that the year attribute belongs to the courses table rather than the enrollments table, leading to missing joins and semantically invalid queries. Wrong keywords (8.4%) are more frequent than wrong schemas (3.8%), often due to synonym/abbreviation collisions.

- **SQL Syntax Errors (8.4%).** they manifest when models fail to maintain a proper structure in multistep queries, often neglecting to encapsulate operations within CTEs or subqueries, causing subsequent references to undefined aliases or intermediate results to fail.

- **Incorrect Knowledge Errors (30.4%).** Errors involve fundamental mistakes in domain-specific reasoning, such as not being able to convert units (liters to cubic meters) or confusing power (kW) with energy consumption (kWh), reflecting insufficient understanding of physical principles. Sub-errors are dominated by unit-conversion and formula-application mistakes, plus entity–relation misunderstandings and intent vagueness that misguide rule selection.

- **Wrong Query Errors (20.8%).** Errors represent the most complex and frequent category, where models generate entirely incorrect logical approaches to multi-step arithmetic reasoning and unit conversions, despite the query requiring sophisticated sequential transformations.

- **Other Detail Errors (20.0%).** Errors include improper floating-point operations and illegal mathematical expressions, such as unnecessary multiplication by 1.0 or division by zero, indicating inadequate type handling and mathematical safeguards.

These error patterns collectively underscore the persistent challenge models face in generating coherent, executable SQL queries that require deep domain knowledge, multistep reasoning, and precise mathematical operations.

A.4 Perturbation Experiment Analysis

We evaluated the robustness of IESR with a systematic perturbation study on 500 LogicCat questions with explicit JOIN intent. We construct three decay levels of increasing distractor complexity and compare IESR to standard prompting across four backbones, controlling for model capacity so that performance gaps reflect the framework itself.

- **L1-Semantic:** Semantically related tables with misleading column names.

- **L2-Structural:** Similar table names with irrelevant columns or redundant JOIN paths.

- **L3-Hybrid Advanced:** Semantically relevant and structurally valid decays that violate specific constraints.

For each question, we create four database variants: *DB_Original*, *DB_Decay_L1*, *DB_Decay_L2*, and *DB_Decay_L3*, testing both methods across all environments.

Figure 7 presents the experimental results in all combinations of model-environment combinations, revealing the superior robustness of IESR against adversarial database perturbations. The results demonstrate IESR's consistent outperformance of standard prompting across all environments, with performance gaps that widen as adversarial complexity increases. In clean databases, IESR establishes a clear baseline advantage that expands progressively through L1 semantic decays and L2 structural decays and culminates in the largest gap under advanced hybrid decays L3.

Figure 6: Distribution of Errors on Sampled Set.

Figure 7: Robustness comparison between IESR and standard prompting across adversarial database environments. IESR maintains superior performance and exhibits more graceful degradation as decay sophistication increases from clean databases to advanced hybrid decays.

IESR exhibits better resilience against adversarial perturbations, showing more graceful degradation compared to the steep decline in standard prompting. This robustness advantage stems from the framework's dual-component architecture: MCTS-based reasoning Configuration systematically breaks down complex queries while Trajectory Selection bridging ensures consistent relationship traversal, effectively avoiding the semantically plausible but logically incorrect decay paths that mislead standard approaches.

A.5 Efficiency Analysis

IESR improves complex reasoning by explicitly structuring information extraction and multi-path exploration, at the cost of increased inference overhead. In the information understanding stage, most computation arises from rule-guided, multi-round lightweight model calls. Table 9 reports the average number of model calls and generated tokens per query on LogicCat and Archer, showing that this stage incurs only a small fraction of the total cost.

The dominant computational overhead stems from the MCTS-based reasoning stage. As shown in Table 8, under 32 rollouts, each LogicCat query requires on average 124.2 and 145.9 model calls to produce a single SQL using Qwen2.5-Coder and XiYanSQL-QwenCoder, respectively, along with several hundred thousand generated tokens. On a single NVIDIA L20 GPU per model, completing 32 rollouts over the full LogicCat test set takes approximately five days.

This cost can be substantially reduced through practical optimizations. Distributing rollouts across multiple GPUs or batching model calls within each rollout improves hardware utilization. In particular, running MCTS rollouts for multiple queries in parallel enables effective batching, significantly shortening wall-clock inference time and making IESR more amenable to scalable deployment.

A.6 Analysis of Scoring Weights

We analyze the impact of the weighting coefficients α, β, and γ in the trajectory scoring function:

$$\text{Score}(t) = \alpha \cdot \text{Exec}(t) + \beta \cdot \text{DiscConf}(t) + \gamma \cdot \text{ConsVote}(t).$$

Here, $\text{Exec}(t)$ is a binary signal indicating execution correctness, while $\text{DiscConf}(t)$ and $\text{ConsVote}(t)$ provide lightweight consistency evidence derived from discriminator verification and peer agreement, respectively. Execution correctness serves as the primary objective, with consistency signals acting as auxiliary indicators to improve robustness.

We tune these weights via a grid search on a held-out development set of 500 queries from the LogicCat benchmark, enforcing $\alpha + \beta + \gamma = 1$. We vary $\alpha \in \{0.3, 0.4, 0.5\}$ and distribute the remaining weight between the two consistency terms. We observe that underweighting $\text{Exec}(t)$ tends to favor internally consistent but non-executable queries, whereas relying solely on execution correctness makes the selection vulnerable to spurious execution equivalence.

As shown in Table 7, the configuration $(\alpha, \beta, \gamma) = (0.4, 0.2, 0.4)$ achieves the highest execution accuracy on the development set. This setting balances executability and stability by prioritizing correct execution while leveraging consistency signals to suppress brittle reasoning trajectories. All experiments in the main paper adopt this fixed configuration without further tuning.

Model	α	β	γ	EX (%)
Qwen2.5-Coder	0.5	0.2	0.3	21.32
Qwen2.5-Coder	0.5	0.1	0.4	20.37
Qwen2.5-Coder	0.4	0.2	0.4	**21.66**
Qwen2.5-Coder	0.4	0.1	0.5	20.99
Qwen2.5-Coder	0.3	0.2	0.5	21.48

Table 7: Sensitivity analysis of weighting coefficients (α, β, γ) in the trajectory scoring function on the LogicCat dev set (500 queries), using Qwen2.5-Coder-7B-Instruct. All settings satisfy $\alpha + \beta + \gamma = 1$.

	Qwen2.5-Coder	XiYanSQL
Avg. calls	124.2	145.9
Avg. generated tokens	89.2k	94.8k
Avg. tokens/s	1,253.4	1,416.4

Table 8: Inference costs of IESR on LogicCat. We show the average number of inferences and generated tokens required to solve a question. **XiYanSQL** refers to XiYanSQL-QwenCoder-7B-2504; **Qwen2.5-Coder** to Qwen2.5-Coder-7B;

	LogicCat	Archer
Avg. calls	5.1	6.2
Avg. generated tokens	2,8803.2	3,424.7

Table 9: Information understanding costs of IESR on LogicCat and Archer. We report the average number of lightweight model calls and generated tokens required for semantic extraction and schema-aware preprocessing per query.

B Algorithm

B.1 Action Nodes

Inspired by human reasoning processes, shown in Table 3, we design a diverse action space consisting of five reasoning actions:

- **Equation Analysis:** Building on prior work (Mao et al., 2025) that emphasizes the explicit expression of formulas, the action space is introduced to enable their explicit representation.

- **Schema Selection:** Databases typically contain large and complex schema, while individual queries often involve only a small subset of them. This discrepancy poses significant challenges for SQL generation. Prior work (Li et al., 2025b; Talaei et al., 2024) has addressed this issue by designing schema selection mechanisms to identify relevant schema components, and we similarly leverage chain-of-thought reasoning to select the most relevant columns.

- **Identify Columns:** Database schema often contain ambiguous fields such as *ids, Keys, Columns* and special function like *POWER(x, 2)* rather than *x * x* and so on, while specific queries refer to concrete numerical values, leading to ambiguous semantic references during SQL generation. Prior work (Li et al., 2025a) and existing datasets (Lei et al., 2025; Wretblad et al., 2024) have highlighted this issue. The purpose of this dynamic space is to leverage semi-structured information extracted during the information extraction stage to identify such ambiguous fields and explicitly resolve their semantic references.

- **Entity Extraction:** This step extracts relevant schema information based on entities, relations, and formulas identified from the semi-structured information. A text-to-SQL system is required not only to accurately capture filtering conditions and user intent, but also to ensure the correctness of the extracted SQL data.

- **SQL Generation:** SQL generation is the core component of Text-to-SQL systems (Pourreza et al., 2025). This method particularly excels at handling nested queries. We incorporate this strategy into our reasoning action space.

- **SQL Revision:** We observe that many errors from CHASE (Pourreza et al., 2025) and CHESS (Talaei et al., 2024) are due to the difficulty of the model in understanding implicit physical formulas and domain-specific background knowledge. This action requires the model to list all known conditions and explicitly express all relevant formulas, units, key fields, and information, and then correct the SQL query accordingly.

The search process consists of four steps:

- **Selection**: Starting from the root node, actions are selected downward along the tree based on the UCT values until an unexplored node or a terminal node is encountered.

- **Expansion**: Valid actions are expanded at the selected node to generate new child nodes.

- **Simulation**: From the newly expanded node, actions are sampled randomly and expansion continues until a terminal node is reached.

- **Backpropagation**: The reward of the terminal node is computed and propagated back along the path, updating the statistics of all nodes encountered.

After multiple N_{rollout} rollouts, all complete reasoning trajectories reach terminal nodes are collected, forming a candidate set of SQL queries for subsequent selection and verification.

At each step, the MCTS selects an action from this space and generates the next reasoning step based on the current state, with the aim of maximizing the reasoning capability of LLM_1.

B.2 Module Algorithm

The proposed framework consists of three stages, each summarized in the appended algorithms. First, *Information Understanding with Rule-Guided Verification Algorithm* converts a natural language query into structured elements (intent, entities, relations, numbers, units, operators) and filters them with a rule base to ensure semantic consistency. Second, *the Chain-of-Thought Reasoning Algorithm based on MCTS* explores possible SQL construction trajectories, where the search tree is expanded through predefined actions, and candidate paths are simulated and rewarded according to execution results and consistency checks. Finally, *Trajectory Selection with Mutual Reasoning Consistency Algorithm* re-evaluates these candidates with a secondary model and scores them based on execution accuracy, discriminator confidence, and mutual consistency, selecting the most reliable SQL trajectory. This pipeline integrates information understanding, search-based reasoning, and consistency verification, which is particularly suited for datasets that require complex numeric or physical computations, such as LOGICCAT or ARCHER.

C Dataset Details

- **LogicCAT (Liu et al., 2025a):** A challenging Text-to-SQL benchmark with 4,038 English

questions covering multi-domain reasoning including physical knowledge, mathematical logic, common sense reasoning, and hypothetical scenarios.

- **Archer (Zheng et al., 2024):** It contains 1,042 questions from 20 databases that focus on complex, logical, hypothetical reasoning.

- **BIRD (Wretblad et al., 2024):** BIRD contains more than 12,751 unique questions and 95 databases. We used the development set, which includes 1,534 questions.

- **Spider (Yu et al., 2019):** Spider contains 10,181 unique questions in 166 databases. We use its development set of 1,034 questions.

D Details of Public Method

- **DIN-SQL:** DIN-SQL is a Text-to-SQL framework that splits query generation into steps (schema linking, decomposition, intermediate representation, correction) and reaches SOTA results without fine-tuning.

- **DAIL-SQL:** DAIL-SQL is a prompt-engineering method optimizing how examples and question representations are used in a few shots based on LLM Text-to-SQL.

- **CHESS:** CHESS is a multi-agent LLM framework for text-to-SQL, combining an information retriever, schema selector, candidate generator, and unit tester to prune large schemas, generate and refine SQL, and validate outputs. Reduce token usage and model calls while improving accuracy, achieving strong results on large-scale benchmarks such as BIRD.

- **LinkAlign:** It is a scalable schema linking framework for multi-database Text-to-SQL, combining semantic retrieval and schema grounding to accurately select relevant databases and columns in large, complex settings.

- **DTS-SQL:** DTS-SQL is a two-stage fine-tuning method that splits the Text-to-SQL task into schema linking and SQL generation sub-tasks, allowing smaller open source LLMs to approach the performance of larger models.

- **Alpha-SQL:** Alpha-SQL is a zero-shot Text-to-SQL framework that uses Monte Carlo

---
Algorithm 1 Information Understanding with Rule-Guided Verification
---
Require: Natural language question q, database schema $S = (T, C)$, candidate column set $c_q \subseteq C$, rule base $\mathcal{B} = \{R_j\}$, LLM M_1, thresholds $\delta_{\text{match}}, \tau$

Output: High-quality relation set $\mathcal{R}_{\text{high}}$

1: Inject (q, S) into prompt template
2: Use M_1 to generate preliminary results: $R = (i, r, E, R, N, U, P)$
3: $\mathcal{R}_{\text{init}} \leftarrow \text{extract}(R)$
4: $\mathcal{R}_{\text{cand}} \leftarrow \emptyset$
5: **for** each $r_i \in \mathcal{R}_{\text{init}}$ **do**
6:      **for** each $R_j \in \mathcal{B}$ **do**
7:          **if** $\text{sim}(r_i, \text{Uni}_j, \text{Equt}_j) > \delta_{\text{match}}$ **then**
8:             $\mathcal{R}_{\text{cand}} \leftarrow \mathcal{R}_{\text{cand}} \cup \{r_i\}$
9:             **break**
10:          **end if**
11:      **end for**
12: **end for**
13: $\mathcal{R}_{\text{high}} \leftarrow \emptyset$
14: **for** each $r_i \in \mathcal{R}_{\text{cand}}$ **do**
15:      $P_i \leftarrow \text{Plan}(r_i, \mathcal{B})$
16:      $s_i \leftarrow \text{Executor}(r_i, P_i)$
17:      **if** $s_i > \tau$ **then**
18:          $\mathcal{R}_{\text{high}} \leftarrow \mathcal{R}_{\text{high}} \cup \{r_i\}$
19:      **end if**
20: **end for**
21: **return** $\mathcal{R}_{\text{high}}$

Tree Search (MCTS) plus dynamic action proposals from an LLM to iteratively build SQL, with a self-supervised reward function to guide the search, achieving strong results.

- **SQL-O1:** SQL-o1 introduces a self-reward heuristic dynamic search method for Text-to-SQL. It leverages execution-aware feedback to guide iterative refinement of candidate SQL queries, enabling effective search without external annotators or learned critics.

E Prompt

In this section, we summarize the prompt templates used in our modular agent, organized as one front-end understanding prompt and six action prompts that constitute the heterogeneous reasoning space. The Information Understanding prompt constructs a structured semantic state from the user question by extracting intent, entities and relations, numerical values and units, and the schema elements that are likely required (Figure 9). Based on this intermediate representation, the agent performs reasoning through six specialized actions. The Equation Explain prompt makes implicit formulas and numerical transformations explicit, supporting unit conversion and arithmetic constraints before SQL construction (Figure 10). The Schema Selection prompt narrows the search space by selecting task-relevant tables and columns from the database schema (Figure 11). To further resolve ambiguous fields, the Identify Column Information prompt disambiguates candidate columns using semantic cues and column-level descriptions/examples (Figure 12). The Entity Extraction prompt grounds query entities and their associated relations to concrete values or schema mentions, providing reliable constraints for WHERE/JOIN conditions (Figure 8). Conditioned on the above structured signals, the SQL Generation prompt synthesizes an executable SQL query, including necessary joins, aggregations, and nested structures (Figure 13). Finally, the SQL Revision prompt corrects the draft SQL by diagnosing logical, join, and schema-mismatch errors (optionally using execution feedback when available), and outputs a repaired query (Figure 14)

Algorithm 2 MCTS-based CoT Reasoning for SQL Generation

Require: Query x, target LLM M, action set $\mathcal{A} = \{\text{A1}, \ldots, \text{A6}\}$, rollout budget N_{rollout}, exploration constant c, sampling temperature T_{samp}, consistency vote size K, database D

Output: Candidate trajectory set $\mathcal{T}_{\text{cand}}$ with terminal rewards

1: Initialize search tree $\mathcal{T}$ with root node v_0 representing x
2: Initialize visit counts $N(v, a)$ and cumulative values $Q(v, a)$ for all (v, a); $\mathcal{T}_{\text{cand}} \leftarrow \emptyset$
3: **for** $m = 1$ to N_{rollout} **do**
4:      $v \leftarrow v_0$; $path \leftarrow [\,]$ $\triangleright$ Selection
5:      **while not** terminal(v) **and** v is fully expanded **do**
6:          $a^{\star} \leftarrow \arg\max_{a \in \mathcal{A}} \left(\frac{Q(v,a)}{\max(1, N(v,a))} + c\sqrt{\frac{\ln \max(1, N(v))}{\max(1, N(v,a))}} \right)$
7:          $path.\text{append}\big((v, a^{\star})\big)$; $v \leftarrow \text{STEP}(v, a^{\star}, M)$
8:      **end while** $\triangleright$ Expansion
9:      **if not** terminal(v) **then**
10:          Select an untried valid action a at v
11:          $u \leftarrow \text{STEP}(v, a, M)$; add edge $(v, a) \rightarrow u$; initialize $N(u, \cdot), Q(u, \cdot)$
12:          $path.\text{append}\big((v, a)\big)$; $v \leftarrow u$
13:      **end if** $\triangleright$ Simulation (rollout)
14:      $(\hat{t}, terminal) \leftarrow \text{SIMULATE}(v, M, \mathcal{A}, T_{\text{samp}})$
15:      $r_t \leftarrow 0$
16:      **if** $terminal = $ **true then**
17:          $r_t \leftarrow \text{EVALUATEREWARD}(\hat{t}, x, D, K)$
18:          $\mathcal{T}_{\text{cand}} \leftarrow \mathcal{T}_{\text{cand}} \cup \{(\hat{t}, r_t)\}$
19:      **end if** $\triangleright$ Backpropagation
20:      $\text{BACKPROPAGATE}(path, r_t)$
21: **end for**
22: **return** $\mathcal{T}_{\text{cand}}$

23: **function** $\text{STEP}(v, a, M)$
24:      Apply action a to extend the current reasoning state at v using model M
25:      **return** new node u with updated partial trajectory
26: **end function**
27: **function** $\text{SIMULATE}(v, M, \mathcal{A}, T_{\text{samp}})$
28:      **while not** terminal(v) **and** depth limit not reached **do**
29:          Sample a from a lightweight rollout policy (e.g., uniform or softmax over UCT scores with temperature T_{samp})
30:          $v \leftarrow \text{STEP}(v, a, M)$
31:      **end while**
32:      **return** (final trajectory $\hat{t}$ from root$\rightarrow v$, terminal(v))
33: **end function**
34: **function** $\text{EVALUATEREWARD}(\hat{t}, x, D, K)$
35:      Extract terminal SQL $\hat{y}$ from $\hat{t}$
36:      **if** $\text{EXECUTE}(\hat{y}, D)$ fails **then**
37:          **return** 0
38:      **end if**
39:      Sample K additional terminal SQL queries $\{\hat{y}_j\}_{j=1}^{K}$ under the same terminal context
40:      Execute all; let $w \leftarrow \frac{1}{K} \sum_{j=1}^{K} \mathbf{1}\big[\text{EXECUTE}(\hat{y}, D) = \text{EXECUTE}(\hat{y}_j, D)\big]$
41:      **return** $r_t = w$
42: **end function**
43: **function** $\text{BACKPROPAGATE}(path, r_t)$
44:      **for** each (v, a) in $path$ **do**
45:          $N(v, a) \leftarrow N(v, a) + 1$; $Q(v, a) \leftarrow Q(v, a) + r_t$
46:      **end for**
47: **end function**

Algorithm 3 Trajectory Selection with Mutual Reasoning Consistency

Require: Candidate trajectory set $\mathcal{T}$ from LLM_1, discriminator LLM_2, weights α, β, γ
Output: Final selected SQL trajectory t^*

1: $\mathcal{T}_{\text{cand}} \leftarrow \emptyset$
2: **for** each trajectory $t = x \oplus s_1 \oplus \cdots \oplus s_d \in \mathcal{T}$ **do**
3:     Randomly choose $i < d$, mask $s_i, \ldots, s_d$
4:     Feed $(x \oplus s_1 \oplus \cdots \oplus s_{i-1})$ into LLM_2 to generate completion $\hat{t}$
5:     **if** $\hat{t}$ semantically consistent with t **then**
6:         $\mathcal{T}_{\text{cand}} \leftarrow \mathcal{T}_{\text{cand}} \cup \{t\}$
7:     **end if**
8: **end for**
9: **for** each $t \in \mathcal{T}_{\text{cand}}$ **do**
10:     Compute $Exec(t)$
11:     Compute $DiscConf(t)$
12:     Compute $ConsVote(t)$
13:     $Score(t) \leftarrow \alpha \cdot Exec(t) + \beta \cdot DiscConf(t) + \gamma \cdot ConsVote(t)$
14: **end for**
15: $t^* \leftarrow \arg\max_{t \in \mathcal{T}_{\text{cand}}} Score(t)$
16: **return** t^*

Entity Extraction Prompt

Objective: Analyze the given question and hint to identify and extract keywords, keyphrases, and named entities. These elements are crucial for understanding the core components of the inquiry and the guidance provided. This process involves recognizing and isolating significant terms and phrases that could be instrumental in formulating searches or queries related to the posed question.

Instructions: Read the Question Carefully: Understand the primary focus and specific details of the question. Look for any named entities (such as organizations, locations, etc.), technical terms, and other phrases that encapsulate important aspects of the inquiry.
Analyze the Hint: The hint is designed to direct attention toward certain elements relevant to answering the question. Extract any keywords, phrases, or named entities that could provide further clarity or direction in formulating an answer.
List Keyphrases and Entities: Combine your findings from both the question and the hint into a single Python list. This list should contain:
Keywords: Single words that capture essential aspects of the question or hint.
Keyphrases: Short phrases or named entities that represent specific concepts, locations, organizations, or other significant details.
Ensure to maintain the original phrasing or terminology used in the question and hint.

Example 1:
Question: "What is the annual revenue of Acme Corp in the United States for 2022?"
Hint: "Focus on financial reports and U.S. market performance for the fiscal year 2022."
```python
["annual revenue", "Acme Corp", "United States", "2022", "financial reports", "U.S. market performance", "fiscal year"]
```

Example 2:
Question: "In the Winter and Summer Olympics of 1988, which game has the most number of competitors? Find the difference of the number of competitors between the two games."
Hint: "the most number of competitors refer to MAX(COUNT(person_id)); SUBTRACT(COUNT(person_id where games_name = '1988 Summer'), COUNT(person_id where games_name = '1988 Winter'));"
```python
["Winter Olympics", "Summer Olympics", "1988", "1988 Summer", "Summer", "1988 Winter", "Winter", "number of competitors", "difference", "MAX(COUNT(person_id))", "games_name", "person_id"]
```

Example 3:
Question: "How many Men's 200 Metres Freestyle events did Ian James Thorpe compete in?"
Hint: "Men's 200 Metres Freestyle events refer to event_name = 'Swimming Men"s 200 metres Freestyle'; events compete in refers to event_id;"
```python
["Swimming Men's 200 metres Freestyle", "Ian James Thorpe", "Ian", "James", "Thorpe", "compete in", "event_name", "event_id"]
```

Task:
Given the following question and hint, identify and list all relevant keywords, keyphrases, and named entities.

Question: {QUESTION}
Hint: {HINT}

Please provide your findings as a Python list within ```python ``` tags, capturing the essence of both the question and hint through the identified terms and phrases.
Only output the Python list, no explanations needed.

Figure 8: An Example of Entity Extraction Prompt.

Information Extraction Prompt

You are an expert information extraction assistant for Text-to-SQL tasks. Your task is to analyze the given question and database schema, then extract structured information that will help generate accurate SQL queries.

You need to extract the following information from the question and schema:
1. **Entities**: Key entities mentioned in the question (e.g., objects, concepts, attributes)
2. **Relations**: Relationships between entities or between entities and database elements
3. **Intent**: The main intent or goal of the question
4. **Reasoning Type**: The type of reasoning required (e.g., "mathematical logic reasoning", "physical knowledge reasoning", "common sense understanding reasoning", "ideal hypothesis reasoning")
5. **Numerical Values**: Any numerical values mentioned in the question
6. **Units**: Units of measurement or conversion information
7. **Foreign Keys**: Foreign key relationships relevant to the question
8. **Primary Keys**: Primary key information for relevant tables
9. **Table Info**: Detailed information about relevant tables and columns
****
Example:
Database Schema:
CREATE TABLE aircraft
(
    `Aircraft_ID` INTEGER NOT NULL,
    `Aircraft` VARCHAR(50), -- Column Description: 飞机的名称或型号（例如：Robinson R-22）
    `Total_Disk_Area` FLOAT, -- Column Description: 飞机的总旋翼盘面积（例如：497 ft² (46.2 m²)）
    `Max_Disk_Loading` FLOAT, -- Column Description: 飞机的最大旋翼盘载荷（例如：2.6 lb/ft² (14 kg/m²)）
    `Max_Gross_Weight` FLOAT, -- Column Description: 飞机的最大总重量（例如：1,370 lb (635 kg)）
    PRIMARY KEY (`Aircraft_ID`)
);
Question:
If a Robinson R-22 helicopter has a total rotor disc area of 46.2 square meters and a maximum rotor disc loading of 14 kilograms per square meter, what is its lift under maximum gross weight?
Hint:
Robinson R-22 refers to Aircraft = 'Robinson R-22'; lift refers to Max_Gross_Weight = Total_Disk_Area × Max_Disk_Loading
Extracted Information:
```python
{
    'entities': ['Robinson R-22 helicopter', 'total rotor disc area 46.2 m²', 'maximum rotor disc loading 14 kg/m²'],
    'relations': ['helicopter_to_specs (Robinson R-22 → aircraft specifications)', 'lift_calculation (Max_Gross_Weight = Total_Disk_Area × Max_Disk_Loading)'],
    'intent': 'calculate_lift_under_max_gross_weight',
    'reasoning_type': 'physical knowledge reasoning',
    'numerical_values': [46.2, 14],
    'units': {
        'area': 'm² (square meters)',
        'loading': 'kg/m² (kilograms per square meter)',
        'lift': 'kg (kilograms, derived from 46.2 m² × 14 kg/m²)',
        'conversion': 'Lift = Total_Disk_Area × Max_Disk_Loading'
    },
    'foreign_keys': 'This issue does not provide foreign keys',
    'primary_keys': [{'pk_table': 'aircraft', 'pk_column': 'Aircraft_ID'}],
    'tableinfo': {
        'AirCraft.aircraft': [
            {'column': 'Aircraft', 'type': 'VARCHAR(50)', 'primary_key': False, 'comment': '飞机的名称或型号（例如：Robinson R-22）', 'examples': ['Robinson R-22', 'Bell 206B3 JetRanger']},
            {'column': 'Total_Disk_Area', 'type': 'FLOAT', 'primary_key': False, 'comment': '飞机的总旋翼盘面积（例如：497 ft² (46.2 m²)）', 'examples': ['46.2', '81.1']},
            {'column': 'Max_Disk_Loading', 'type': 'FLOAT', 'primary_key': False, 'comment': '飞机的最大旋翼盘载荷（例如：2.6 lb/ft² (14 kg/m²)）', 'examples': ['14.0', '18.0']},
            {'column': 'Max_Gross_Weight', 'type': 'FLOAT', 'primary_key': False, 'comment': '飞机的最大总重量（例如：1,370 lb (635 kg)）', 'examples': ['635.0', '1451.0']}
        ]
    }
}
```
****
Now, extract the information for the real question. You must output a valid Python dictionary in the exact format shown above.
Important guidelines:
- **Entities**: Extract all key entities mentioned in the question, including objects, attributes, and concepts
- **Relations**: Identify relationships between entities, or mappings from entities to database elements
- **Intent**: Summarize the main goal in a concise phrase (use snake_case)
- **Reasoning Type**: Identify the reasoning type(s) required (common types: "mathematical logic reasoning", "physical knowledge reasoning", "common sense understanding reasoning", "ideal hypothesis reasoning")
- **Numerical Values**: Extract all numerical values mentioned in the question as a list
- **Units**: Extract units of measurement and any conversion formulas
- **Foreign Keys**: Extract foreign key relationships as a list of dictionaries with 'fk_table', 'fk_column', 'ref_table', 'ref_column', or use the string "This issue does not provide foreign keys" if no foreign keys are relevant
- **Primary Keys**: Extract primary key information for relevant tables as a list of dictionaries with 'pk_table' and 'pk_column'
- **Table Info**: Extract detailed information about relevant tables and columns, including column names, types, primary_key status, comments, and examples

Database Schema:{SCHEMA_CONTEXT}

Question:{QUESTION}

Hint:{HINT}

Please output only the Python dictionary in the exact format shown in the example, without any additional explanation or markdown formatting. The output should be a valid Python dictionary that can be evaluated with `ast.literal_eval()`.

Figure 9: Understanding Prompt including Intent Recognition, Unit Understanding, Relation and Entity Extracting, and Pseudo-Schema Understanding

Equation Expaination Prompt

You are an AI assistant to help me identify and explain mathematical formulas or calculations mentioned in the question. Your task is to recognize any formulas, equations, or calculation expressions in the question and convert them into SQL-compatible expressions that can be used in the SQL query.

****

Example 1:

Database Schema:

CREATE TABLE aircraft

(

   `aircraft_id` INTEGER NOT NULL,

   `max_gross_weight` REAL, -- Column Description: maximum gross weight in pounds

   `rotor_diameter` REAL, -- Column Description: rotor diameter in feet

   PRIMARY KEY (`aircraft_id`)

);

Question:

Calculate what is the rotor disk loading of the Robinson R-22 helicopter at its maximum gross weight?

Hint:

rotor disk loading refers to max_gross_weight / (π * (rotor_diameter / 2)^2); Robinson R-22 refers to aircraft_name = 'Robinson R-22'

Answer:

The question asks for "rotor disk loading", which is a calculated value. The formula is: rotor disk loading = max_gross_weight / (π * (rotor_diameter / 2)^2). In SQL, this can be expressed as: `max_gross_weight / (3.14159 * POWER(rotor_diameter / 2, 2))` or `max_gross_weight / (3.14159 * (rotor_diameter / 2) * (rotor_diameter / 2))`.

****

Example 2:

Database Schema:

CREATE TABLE products

(

   `product_id` INTEGER NOT NULL,

   `price` REAL, -- Column Description: product price in dollars

   `discount_rate` REAL, -- Column Description: discount rate as percentage (0-100)

   `quantity` INTEGER, -- Column Description: quantity purchased

   PRIMARY KEY (`product_id`)

);

Question:

What is the total cost after applying a 10% discount for products with quantity greater than 5?

Hint:

total cost after discount refers to (price * quantity) * (1 - discount_rate / 100); quantity greater than 5 refers to quantity > 5

Answer:

The question involves a calculation: total cost after discount = (price * quantity) * (1 - discount_rate / 100). In SQL, this can be expressed as: `(price * quantity) * (1 - discount_rate / 100.0)`. Additionally, for the 10% discount case, it can be written as: `(price * quantity) * 0.9`.

****

Example 3:

Database Schema:

CREATE TABLE employees

(

   `employee_id` INTEGER NOT NULL,

   `salary` REAL, -- Column Description: annual salary in dollars

   `bonus_percentage` REAL, -- Column Description: bonus percentage (0-100)

   `years_of_service` INTEGER, -- Column Description: years of service

   PRIMARY KEY (`employee_id`)

);

Question:

Calculate the average compensation (salary + bonus) for employees with more than 10 years of service, where bonus = salary * bonus_percentage / 100.

Hint:

compensation refers to salary + (salary * bonus_percentage / 100); more than 10 years refers to years_of_service > 10

Answer:

The question requires calculating "compensation" which is defined as salary + bonus, where bonus = salary * bonus_percentage / 100. The formula is: compensation = salary + (salary * bonus_percentage / 100). In SQL, this can be expressed as: `salary + (salary * bonus_percentage / 100.0)` or simplified as: `salary * (1 + bonus_percentage / 100.0)`.

****

Now, answer the real question, and you need to follow the answer style of the above examples (identify the formula/calculation and explain how to express it in SQL, answer in 2-3 sentences).

Database Schema:

{SCHEMA_CONTEXT}

Question:

{QUESTION}

Hint:

{HINT}

Answer:

Figure 10: An Example of Equation Explain Prompt.

You are an expert and very smart data analyst.
Your task is to examine the provided database schema, understand the posed question, and use the hint to pinpoint the specific columns within tables that are essential for crafting a SQL query to answer the question.

The schema offers an in-depth description of the database's architecture, detailing tables, columns, primary keys, foreign keys, and any pertinent information regarding relationships or constraints. Special attention should be given to the examples listed beside each column, as they directly hint at which columns are relevant to our query.

For key phrases mentioned in the question, we have provided the most similar values within the columns denoted by "-- Value Examples" in front of the corresponding column names. This is a critical hint to identify the columns that will be used in the SQL query.

The hint aims to direct your focus towards the specific elements of the database schema that are crucial for answering the question effectively.

Task:
Based on the database schema, question, and hint provided, your task is to identify all and only the columns that are essential for crafting a SQL query to answer the question.
For each of the selected columns, explain why exactly it is necessary for answering the question. Your reasoning should be concise and clear, demonstrating a logical connection between the columns and the question asked.

Please respond with your reasoning process and a JSON object structured as follows:
Reasoning Process:
(Here, output your reasoning for selecting the columns, be concise and clear)
Final JSON Result:
```json
{{
  "table_name1": ["column1", "column2", ...],
  "table_name2": ["column1", "column2", ...]
  ...
}}
```

Make sure your response includes the table names as keys, each associated with a list of column names that are necessary for writing a SQL query to answer the question.
For each aspect of the question, provide a clear and concise explanation of your reasoning behind selecting the columns.
Take a deep breath and think logically. If you do the task correctly, I will give you 1 million dollars.

Database Schema Overview:
{SCHEMA_CONTEXT}

Question:
{QUESTION}

Hint:
{HINT}

Please output your reasoning process first after "# Reasoning Process", and output a JSON object within ```json``` tags.

Figure 11: An Example of Schema Selection Prompt.

Indentify Column Information Prompt

You are an AI assistant to help me identify the potential column values and column functions (if needed to be used in the SQL query) that are essential for answering the question.

Your task is to:
1. Identify the specific column values that should be used in WHERE clauses or other filtering conditions
2. Identify any column functions (like date functions, string functions, etc.) that might be needed for the SQL query
****
Example 1: Identifying Column Values
Database Schema:
CREATE TABLE generalinfo
(
        id_restaurant INTEGER not null primary key,
        food_type TEXT null, -- Value Examples: `thai`| Column Description: the food type
        city TEXT null, -- Column Description: the city where the restaurant is located in
);
CREATE TABLE location
(
        id_restaurant INTEGER not null primary key,
        street_name TEXT null, -- Value Examples: `ave`, `san pablo ave`, `pablo ave`| Column Description: the street name of the restaurant
        city TEXT null, -- Column Description: the city where the restaurant is located in
        foreign key (id_restaurant) references generalinfo (id_restaurant) on update cascade on delete cascade,
);
Question:
How many Thai restaurants can be found in San Pablo Ave, Albany?
Hint:
Thai restaurant refers to food_type = 'thai'; San Pablo Ave Albany refers to street_name = 'san pablo ave' AND T1.city = 'albany'
Answer:
Since the restaurants are located in Albany, based on the schema information and the hint, I need to use `location`.`street_name` = 'san pablo ave' AND `generalinfo`.`city` = 'albany'.
****
Example 2: Identifying Column Functions
Database Schema:
CREATE TABLE businesses
(
    `business_id` INTEGER NOT NULL,
    `name` TEXT NOT NULL, -- Column Description: the name of the eatery
    PRIMARY KEY (`business_id`),
);
CREATE TABLE inspections
(
    `business_id` INTEGER NOT NULL, -- Column Description: the unique id of the business
    `score` INTEGER DEFAULT NULL, -- Column Description: the inspection score
    `date` TEXT NOT NULL, -- Value Examples: `2014-01-24`
    FOREIGN KEY (`business_id`) REFERENCES `businesses` (`business_id`),
);
Question:
What are the names of the businesses that passed with conditions in May 2012?
Hint:
name of business refers to dba_name; passed with conditions refers to results = 'Pass w/ Conditions'; in May 2012 refers to inspection_date like '2012-05%'
Answer:
Since the businesses passed with conditions in May 2012, I should consider a date-related function to filter the `inspections`.`date` column. I find that column is of type TEXT, so I can use the strftime('%Y-%m', `inspections`.`date`) = '2012-05' to filter the date.
****
Example 3: Identifying Both Column Values and Functions
Database Schema:
CREATE TABLE products
(
    `product_id` INTEGER NOT NULL,
    `price` REAL, -- Column Description: product price in dollars
    `discount_rate` REAL, -- Column Description: discount rate as percentage (0-100)
    `quantity` INTEGER, -- Column Description: quantity purchased
    `purchase_date` TEXT, -- Value Examples: `2023-05-15` | Column Description: purchase date
    PRIMARY KEY (`product_id`)
);
Question:
What is the total cost after applying a 10% discount for products with quantity greater than 5 purchased in May 2023?
Hint:
total cost after discount refers to (price * quantity) * (1 - discount_rate / 100); quantity greater than 5 refers to quantity > 5; May 2023 refers to purchase_date like '2023-05%'
Answer:
For column values, I need to filter products where quantity > 5. For column functions, I need to use strftime('%Y-%m', `products`.`purchase_date`) = '2023-05' to filter the date to May 2023. Additionally, I need to calculate the discounted cost using the formula (price * quantity) * (1 - discount_rate / 100.0).
****
Now, answer the real question, and you need to follow the answer style of the above examples. Your answer should cover both column values (if any) and column functions (if any) that are needed for the SQL query. Answer in 2-3 sentences.

Database Schema:{SCHEMA_CONTEXT}

Question:{QUESTION}

Hint:{HINT}

Answer: {xxx}

Figure 12: An Example of Identify Column Information Prompt.

Figure 13: Understanding Prompt including Intent Recognition, Unit Understanding, Relation and Entity Extracting, and Pseudo-Schema Understanding.

Task Description:
You are an SQL database expert tasked with correcting a SQL query. A previous attempt to run a query did not yield the correct results, either due to errors in execution or because the result returned was empty or unexpected. Your role is to analyze the error based on the provided database schema and the details of the failed execution, and then provide a corrected version of the SQL query.

Procedure:
1. Review Database Schema:
    - Examine the table creation statements to understand the database structure.
2. Analyze Query Requirements:
    - Original Question: Consider what information the query is supposed to retrieve.
    - Hint: Use the provided hints to understand the relationships and conditions relevant to the query.
    - Executed SQL Query: Review the SQL query that was previously executed and led to an error or incorrect result.
    - Execution Result: Analyze the outcome of the executed query to identify why it failed (e.g., syntax errors, incorrect column references, logical mistakes), note that the execution result is possibly empty for some queries.
3. Correct the Query:
    - Modify the SQL query to address the identified issues, ensuring it correctly fetches the requested data according to the database schema and query requirements.

Based on the question, table schemas, the previous query, and the execution result, analyze the result following the procedure, and try to fix the query.
You cannot modify the database schema or the question, just output the corrected query.

Please respond with xml tags structured as follows:
```xml
<think>
Your detailed reasoning for the SQL query revision.
</think>
<sql>
The final SQL query that answers the question.
</sql>
```

****
【Table creation statements】
{SCHEMA_CONTEXT}

【Question】
{QUESTION}

【HINT】
{HINT}
****
Only output xml format (starting with ```xml and ending with ```) as your response.

Figure 14: An Example of Revising SQL Reasoning Prompt.