TULiP: Test-time Uncertainty Estimation via Linearization and Weight Perturbation

Abstract

A reliable uncertainty estimation method is the foundation of many modern out-of-distribution (OOD) detectors, which are critical for safe deployments of deep learning models in the open world. In this work, we propose TULiP, a theoretically-driven post-hoc uncertainty estimator for OOD detection. Our approach considers a hypothetical perturbation applied to the network before convergence. Based on linearized training dynamics, we bound the effect of such perturbation, resulting in an uncertainty score computable by perturbing model parameters. Compared to existing methods, our approach has a more versatile backbone that can be extended to other problem settings. We visualize our bound on synthetic regression and classification datasets. Furthermore, we demonstrate the effectiveness of TULiP using large-scale OOD detection benchmarks for image classification. Our method exhibits state-of-the-art performance, particularly for near-distribution samples.

1 Introduction

An important safety component for deep neural networks (NNs) in real-world environments is the awareness of their uncertainty upon receiving unknown or corrupted inputs. Such capability enables systems to fall back to conservative decision-making or defer to human judgments when faced with unfamiliar scenarios, which is imperative in safety-critical domains, such as autonomous driving (Atakishiyev et al., 2024) and medical applications (Esteva et al., 2017). The problem is often framed as **Out-Of-Distribution (OOD)** detection, which has witnessed significant growth in recent years (Yang et al., 2024).

Theoretically, this issue directly relates to quantifying epistemic uncertainty (Hora, 1996), which measures the lack of knowledge in a fitted model due to insufficient training data. The training process is typically modelled as a Bayesian optimization process (Wang & Yeung, 2020) with approximations for practical use (Gal & Ghahramani, 2016; Daxberger et al., 2021). More generally, epistemic uncertainty can be formalized by the variance of a trained ensemble of networks $\phi(\boldsymbol{x}; \boldsymbol{\theta})$:

$$\mathrm{Var}_{\boldsymbol{\theta}_{\mathrm{Init}}} \left[\phi(\boldsymbol{x}; \boldsymbol{\theta}_{\mathrm{Train}}) \right], \tag{1}$$

where $\boldsymbol{\theta}_{\mathrm{Train}}$ are parameters trained by some learning algorithm from random initialization $\boldsymbol{\theta}_{\mathrm{Init}}$.

Many works redesign the network or training process to be uncertainty-aware (DeVries & Taylor, 2018; Huang & Li, 2021). However, these are often impractical due to heavy computational costs, especially for large datasets. Instead, *post-hoc* methods (Liang et al., 2018; Liu et al., 2020; Hendrycks et al., 2022; Djurisic et al., 2023) are generally preferred. These approaches can be easily integrated into pre-trained models without interfering with the trained backbones, significantly enhancing their versatility (Yang et al., 2022). Nevertheless, they often lack a direct theoretical link to the training process, which weakens their theoretical foundation and necessitates extensive empirical validation.

Therefore, it is desirable to develop a post-hoc OOD method with direct theoretical justifications regarding the training process. Recent analysis of NN optimizations reveals that gradient descent can be seen as its first-order approximations (Jacot et al., 2018; Lee et al., 2019), termed *lazy* training, under specific conditions (Geiger et al., 2020). This enabled direct (but costly) computation of equation 1, as well as rigorous analysis (Kobayashi et al., 2022) and methods (He et al., 2020) on model uncertainty, even beyond the lazy regime (Chen et al., 2020).

Inspired by this series of work, we present **TULiP** (**T**est-time **U**ncertainty by **Li**nearized fluctuations via weight **P**erturbation), a post-hoc uncertainty estimator for OOD detection. Our method considers

hypothetical fluctuations of the lazy training dynamics, which can be bounded under certain assumptions and efficiently estimated via weight perturbation. In practice, we found our method works well even beyond the ideal regime. Our contribution is threefold:

(i) We provide a simple, versatile theoretical framework for analyzing epistemic uncertainty at inference time in the lazy regime, which is empirically verified;

(ii) Based on our theory, we propose TULiP, an efficient and effective post-hoc OOD detector that does not require access to original training data;

(iii) We test TULiP extensively using OpenOOD (Zhang et al., 2023), a large, transparent, and unified OOD benchmark for image classifications. We show that TULiP consistently improves previous state-of-the-art methods across various settings.

The outline is as follows. Sec. 2 provides a summary of related works, Sec. 3 presents theoretical derivations, and Sec. 4 bridges theory to the implementation of TULiP. Sec. 5 reports the effectiveness of TULiP via empirical studies.

2 Related Works

Uncertainty Quantification (UQ) UQ methods focus on epistemic uncertainty, which directly relates to OOD detection on training sets (Hüllermeier & Waegeman, 2021). Such uncertainty is typically approached from a Bayesian perspective. Various methods have been proposed to model the distribution over model parameters, including those based on Variational Inference (Blundell et al., 2015a). Laplacian Approximation methods (Daxberger et al., 2021) employ Taylor expansion to construct a Gaussian distribution that approximates the true posterior, often involving the approximation of network Hessians given training data. Gal & Ghahramani (2016) established a significant connection between Bayesian inference and practical training of NNs with gradient descent using Dropout layers. Due to its simplicity and theoretical foundations, this insight has led to the widespread practical adoption of their method, Monte Carlo (MC) Dropout. Then, Lakshminarayanan et al. (2017) used an ensemble of deep models to obtain a distribution over model predictions.

Post-hoc OOD Detectors The baseline method for post-hoc OOD using maximum softmax probability (MSP) was first introduced by Hendrycks & Gimpel (2017). ODIN (Liang et al., 2018) applies input preprocessing on top of temperature scaling (Guo et al., 2017a) to enhance MSP. Liu et al. (2020) proposes a simple score based on energy function (EBO). Hendrycks et al. (2022) uses maximum logits (MLS) for efficient detection on large datasets. ASH (Djurisic et al., 2023) prunes away samples' activation at later layers and simplifies the rest.

Some post-hoc methods incorporate information from the training dataset. Lee et al. (2018) fits class-conditional Gaussian distribution using training data and derives scores with Mahalanobis distance (MDS). Ren et al. (2021) improves MDS with information from an unconditional Gaussian distribution. ViM (Wang et al., 2022b) computes the norm of the feature residual on the principal subspace and matches it with training samples' logits to generate a score.

3 Theoretical Framework

3.1 Preliminaries: Linearized Training Dynamics

Jacot et al. (2018) introduced the Neural Tangent Kernel and linearized training of neural networks. More importantly, they have shown that under an infinite width limit, network parameters and hence the gradients barely change across the whole training process, justifying the linearization of the training process. Lee et al. (2019) extends the result by examining them in the parameter space. They derived a formal bound showing that the true gradient descent trajectory is close to linearized ones for learning rates lower than a critical learning rate η_{critical}, which is also demonstrated empirically.

Let $f_{\text{True}}(\boldsymbol{x}; \boldsymbol{\theta}) : \mathbb{R}^d \to \mathbb{R}^o$ be a neural network parameterized by parameters $\boldsymbol{\theta}$. The Jacobian (gradient) evaluated at $\boldsymbol{x}$ is written as $\nabla_{\boldsymbol{\theta}} f_{\text{True}}(\boldsymbol{x}) \in \mathbb{R}^{o \times |\boldsymbol{\theta}|}$, where $|\boldsymbol{\theta}|$ is the number of parameters in the network.

Let $f(\boldsymbol{x}; \boldsymbol{\theta})$ denote the network linearized at $\boldsymbol{\theta}^*$:

$$f(\boldsymbol{x}; \boldsymbol{\theta}) := f_{\text{Init}}(\boldsymbol{x}) + \nabla_{\boldsymbol{\theta}} f_{\text{True}}(\boldsymbol{x})|_{\boldsymbol{\theta}=\boldsymbol{\theta}^*} (\boldsymbol{\theta} - \boldsymbol{\theta}^*), \qquad (2)$$

where $f_{\text{Init}}(\boldsymbol{x})$ is the initial network function. Typically, the network is linearized at initialization $\boldsymbol{\theta}^* = \boldsymbol{\theta}_{\text{Init}}$. Here, we treat it as a linear approximation to the true training dynamics. For our convenience, we will interchangeably use $\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})$ as $\nabla_{\boldsymbol{\theta}} f_{\text{True}}(\boldsymbol{x})|_{\boldsymbol{\theta}=\boldsymbol{\theta}^*}$.

We consider the training data $\boldsymbol{x}$ within an empirical dataset X. For a twice-differentiable loss function $\ell(f(\boldsymbol{x}); y(\boldsymbol{x}))$ with target function (labels) $y(\boldsymbol{x})$, we write it's gradient w.r.t. $f(\boldsymbol{x})$ as $\ell'(f(\boldsymbol{x}); y(\boldsymbol{x}))$ (sometimes omitting the labels, i.e., $\ell'(f(\boldsymbol{x}))$). Then, following Lee et al. (2019), we train the linearized network f by gradient descent over X:

$$\partial_t f_t(\boldsymbol{x}) = -\eta \mathbb{E}_{\boldsymbol{x}'} \left[\Theta(\boldsymbol{x}, \boldsymbol{x}') \ell'(f_t(\boldsymbol{x}'); y(\boldsymbol{x}')) \right], \qquad (3)$$

where $\mathbb{E}_{\boldsymbol{x}'}$ is the expectation w.r.t. the empirical distribution for $\boldsymbol{x}' \in X$, η is the learning rate and f_t denotes the network f at time $t \in [0, T]$. Given inputs $\boldsymbol{x}, \boldsymbol{x}'$, The Neural Tangent Kernel (NTK) $\Theta(\boldsymbol{x}, \boldsymbol{x}') \in \mathbb{R}^{o \times o}$ defined as $\Theta(\boldsymbol{x}, \boldsymbol{x}') := \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x}) \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x}')^\top$ governs the linearized training equation 3. Under the lazy training framework, the NTK $\Theta(\boldsymbol{x}, \boldsymbol{x}')$ stays constant across the training process and hence is independent of t. Hereon, we assume the unique existence of the solution to equation 3.

Notations Let $\boldsymbol{z} \in \mathbb{R}^d$ be an arbitrary test point. Let $\| \cdot \|$ denote the Euclidean norm and induced 2-norm for vectors and matrices. Let $\| \cdot \|_{\text{F}}$ denote the matrix Frobenius norm. We also denote $\| \cdot \|_X := \mathbb{E}_{\boldsymbol{x}} \left[\| \cdot \|^2 \right]^{1/2}$ the data-dependent norm through out the following descriptions. Finally, let $f(\boldsymbol{z}) \lesssim g(\boldsymbol{z})$ indicate $f(\boldsymbol{z}) \leq K g(\boldsymbol{z}) + M$, up to some constant K, M independent of $\boldsymbol{z}$.

3.2 MODELING UNCERTAINTY

Under our problem setting, neither the distribution of initialized models nor the training process is accessible, which renders a significant difficulty for the direct computation of the uncertainty shown in equation 1. Instead, we choose to intuitively model the epistemic uncertainty by considering a perturbation applied towards the network function $f(\boldsymbol{x})$, at a time $t = t_s$ *before* the training terminates at $t = T$.

Formally, consider a perturbation to f_{t_s} at $t = t_s$ as $\hat{f}_{t_s}(\boldsymbol{x}) = f_{t_s}(\boldsymbol{x}) + \Delta f(\boldsymbol{x})$. After the perturbation, the perturbed network $\hat{f}(\boldsymbol{x})$ will be trained following the same dynamics as equation 3:

$$\partial_t \hat{f}_t(\boldsymbol{x}) = -\eta \mathbb{E}_{\boldsymbol{x}'} [\Theta(\boldsymbol{x}, \boldsymbol{x}') \ell'(\hat{f}_t(\boldsymbol{x}'); y(\boldsymbol{x}'))], \qquad (4)$$

until termination time T.

Under such a perturb-then-train process, we model the epistemic uncertainty as the difference between two converged networks, which reads $\| f_T(\boldsymbol{z}) - \hat{f}_T(\boldsymbol{z}) \|$. It measures the fluctuation of the training process, capturing the sensitivity of training w.r.t. noise. Indeed, by applying a perturbation at $t = 0$, we essentially perturb f_{Init}, which can be seen as a sampling process from some model prior. Therefore, $\hat{f}_T(\boldsymbol{z})$ can be interpreted as samples from the trained ensemble as in equation 1, where their variance reflects epistemic uncertainty.

However, in practice, since we only know the trained network f_T at $t = T$, it would be impractical to recover the full training trajectory, apply the perturbation at $t = t_s$ and then retrain the network. Instead, in the following, we will come up to a bound of $\| f_T(\boldsymbol{z}) - \hat{f}_T(\boldsymbol{z}) \|$ given the strength of the perturbation Δf, which can be evaluated at $\boldsymbol{z}$ without actually retrain the network. Therefore, the perturbation is *hypothetical*, as it has never been applied in our practice.

We first present this bound, then we examine a method to estimate the bound without explicit access to training data.

3.3 BOUNDING LINEARIZED TRAINING FLUCTUATIONS

We shall introduce the following assumptions:

A1. (Boundedness) For $t \in [0, T]$, $f(\boldsymbol{x})$, $\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})$, ℓ and ℓ' stay bounded, uniformly on $\boldsymbol{x}$.

A2. (Smoothness) Gradient ℓ' of loss function ℓ is Lipschitz continuous: $\forall x \in X;\ \|\ell'(\hat{y}; y(\boldsymbol{x})) - \ell'(\hat{y}'; y(\boldsymbol{x}))\| \le L\|\hat{y} - \hat{y}'\|$.

A3. (Perturbation) The perturbation Δf can be uniformly bounded by a constant α, that is, for all $\boldsymbol{x}$ (not limited to the support of training data), i.e., $\forall x \in \mathbb{R}^d;\ \|\Delta f(\boldsymbol{x})\| \le \alpha$.

A4. (Convergence) Finally, for the original network trained via equation 3 and the perturbed network trained via equation 4, we assume *near-perfect convergence* on the training set $\boldsymbol{x}$ at termination time $t = T$, i.e., $\exists \beta \in \mathbb{R}, \forall x \in X;\ \|f_T(\boldsymbol{x}) - \hat{f}_T(\boldsymbol{x})\| \le \beta$.

Under reasonable conditions, it has been shown both empirically (Zhang et al., 2017) and theoretically (Du et al., 2019) that overparameterized NNs trained via SGD is able to achieve near-zero training loss on almost arbitrary training sets. To nice loss functions as $\ell(\boldsymbol{y}; \boldsymbol{y}') = 0$ implies $\boldsymbol{y} = \boldsymbol{y}'$, this implies A4.

Jacot et al. (2018) connected lazy NNs trained with mean square error (MSE) loss and kernel ridge regression. Essentially, it hints that under such a setup, an NN embeds datapoints $\boldsymbol{x}$ into gradients $\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})$. Indeed, for a general class of loss functions, it is possible to show that:

Theorem 3.1. *Under assumptions A1-A4, for a network f trained with equation 3 and a perturbed network $\hat{f}$ trained with equation 4, the perturbation applied at time $t_s = T - \Delta T$ bounded by α, we have*

$$\|f_T(\boldsymbol{z}) - \hat{f}_T(\boldsymbol{z})\| \le \inf_{\boldsymbol{x} \in X} C\|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) - \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})\|_{\mathrm{F}} + 2\alpha + \beta, \tag{5}$$

where $C = \frac{\alpha \eta \bar{\Theta}_X^{1/2}}{\lambda_{max}} \left(e^{(T-t_s)L\lambda_{max}} - 1 \right)$, $\bar{\Theta}_X^{1/2} := \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})\|_X$ is average gradient norm over training data, and $\lambda_{max} := \frac{1}{\sqrt{N}}\|\boldsymbol{G}\|$ for a generalized Gram matrix $G_{i,j} := \|\Theta(x_i, x_j)\|$ of dataset $X = \{x_1, x_2, \ldots, x_N\}$.

Proof. With an arbitrarily chosen pivot point $\boldsymbol{x}^*$ from the training set, it is possible to bound $\|f(\boldsymbol{z}) - f(\boldsymbol{x}^*)\|$ and $\|\hat{f}(\boldsymbol{z}) - \hat{f}(\boldsymbol{x}^*)\|$ by bounding the fluctuations on the training set. The theorem then follows from assumption A4. Please check Sec. A.3 for details. $\square$

We see that the bound on the training fluctuation is dominated by the distance from test point $\boldsymbol{z}$ to the training set X in the "embedding space" of gradients, which is

$$\inf_{\boldsymbol{x} \in X} \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) - \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})\|_{\mathrm{F}} = \inf_{\boldsymbol{x} \in X} \left[\mathrm{Tr}\left(\Theta(\boldsymbol{z}, \boldsymbol{z}) + \Theta(\boldsymbol{x}, \boldsymbol{x}) - 2\Theta(\boldsymbol{z}, \boldsymbol{x})\right) \right]^{1/2}. \tag{6}$$

3.4 ESTIMATING THE BOUND WITHOUT TRAINING DATA

However, given no access to training data, the term $\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})$ is intractable. Moreover, even with full access, computing the minimum of equation 6 requires significant computational effort. A typical training dataset often contains millions of data points. Besides, given the size of the network, storing the full gradient for a single data point may already require significant memory.

Fortunately, we might be able to recover some information about the training dataset $\boldsymbol{x}$ from the parameters $\boldsymbol{\theta}_T$ and $\boldsymbol{\theta}_{t_s}$, given them being trained on the dataset via lazy gradient descent:

Lemma 3.2. *We assume the lazy regime for the training process, i.e., the NTK, $\Theta(\boldsymbol{z}, \boldsymbol{x})$, does not depend on the parameter $t \in [t_{t_s}, T]$. Under assumption A1, with the model parameters $\boldsymbol{\theta}_T$ trained from $\boldsymbol{\theta}_{t_s}$ with equation 3 over the training set $\boldsymbol{x}$ and $t_s < T$, we have:*

$$\|\nabla_{\boldsymbol{\theta}} f_T(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})\| \le K \cdot \mathrm{Tr}\left(\mathbb{E}_{\boldsymbol{x}}\left[|\Theta_T(\boldsymbol{z}, \boldsymbol{x})|\right]\right), \tag{7}$$

for some K independent of $\boldsymbol{z}$. $|\Theta_T(\boldsymbol{z}, \boldsymbol{x})|$ is defined as the unique symmetric positive semi-definite solution of $|\Theta_T(\boldsymbol{z}, \boldsymbol{x})|^2 = \Theta_T(\boldsymbol{z}, \boldsymbol{x})^\top \Theta_T(\boldsymbol{z}, \boldsymbol{x})$. It is an extension of absolute values to matrices.

Proof. We prove the lemma under the weakly lazy regime, i.e., we allow the weak dependency of Θ_t on t. The consequence follows from the Hölder's inequality. Please check Sec. A.4 for details. $\square$

We further introduce an assumption on the closeness between the test point z and the dataset X, such that equation 6 can be bounded by

$$\inf_{\boldsymbol{x} \in X} \operatorname{Tr}\left(\Theta(\boldsymbol{z}, \boldsymbol{z}) + \Theta(\boldsymbol{x}, \boldsymbol{x}) - 2\Theta(\boldsymbol{z}, \boldsymbol{x})\right) \le \operatorname{Tr}\left(\Theta(\boldsymbol{z}, \boldsymbol{z}) + \mathbb{E}_{\boldsymbol{x}}\left[\Theta(\boldsymbol{x}, \boldsymbol{x})\right] - 2\mathbb{E}_{\boldsymbol{x}}\left[|\Theta(\boldsymbol{z}, \boldsymbol{x})|\right]\right). \quad (8)$$

Intuitively, if across all $\boldsymbol{x} \in X$, $\operatorname{Tr}\left(\Theta(\boldsymbol{z}, \boldsymbol{x})\right)$ only attains a small negative value within a limited subset of $\boldsymbol{x}$, and $\sup_{\boldsymbol{x} \in X} \operatorname{Tr}\left(\Theta(\boldsymbol{z}, \boldsymbol{x})\right)$ is largely positive ($\boldsymbol{z}$ is close to $\boldsymbol{x}$ in the sense of Θ), equation 8 holds. Fig. 1 d) provides empirical justifications for this closeness assumption.

With the closeness assumption, we can then derive a bound on equation 5 using Lemma 3.2:

Proposition 3.3. *Given $\boldsymbol{z}$ and $\boldsymbol{x}$ satisfies equation 8, equation 5 can be further upper-bounded by:*

$$\|f_T(\boldsymbol{z}) - \hat{f}_T(\boldsymbol{z})\| \lesssim \left[\operatorname{Tr}\left(\Theta(\boldsymbol{z}, \boldsymbol{z}) + \mathbb{E}_x[\Theta(\boldsymbol{x}, \boldsymbol{x})]\right) - 2K \left\|\nabla_{\boldsymbol{\theta}} f_T(\boldsymbol{z})\left(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s}\right)\right\|\right]^{1/2}, \quad (9)$$

for some K independent from $\boldsymbol{z}$ (that may differ from the one in Lemma 3.2). $\qquad\square$

Given test point $\boldsymbol{z}$ and parameters $\boldsymbol{\theta}_T, \boldsymbol{\theta}_{t_s}$, equation 9 provides a tractable bound for equation 5.

Network Ensemble We close this section by the fact that

$$\operatorname{Tr}(\operatorname{Var}_{\Delta f}[\hat{f}_T(\boldsymbol{z})]) \le \mathbb{E}_{\Delta f}[\|\hat{f}_T(\boldsymbol{z}) - f_T(\boldsymbol{z})\|^2], \quad (10)$$

which can be then bounded by equation 9. As we stated before, $\hat{f}_T(\boldsymbol{z})$ can be seen as samples from the trained ensemble as in equation 1. In practice, it is often beneficial to obtain such samples. In the next section, we will present a heuristic method to estimate $\hat{f}_T(\boldsymbol{z})$ by matching variances.

4 IMPLEMENTATION

In this section, we present the key implementation strategies that enhance the practical effectiveness of our method, TULiP, summarized in Alg. 1. We elaborate on its design in the following subsections by referring to lines in Alg. 1.

In contrast to the linearized network $f(\boldsymbol{x}; \boldsymbol{\theta})$, let $f_t^{emp}(\boldsymbol{x}; \boldsymbol{\theta})$ denote a network trained empirically. Intuitively, trajectories of $f_t(\boldsymbol{x}; \boldsymbol{\theta})$ and $f_t^{emp}(\boldsymbol{x}; \boldsymbol{\theta})$ is similar when $\boldsymbol{\theta}^* = \boldsymbol{\theta}_{\text{Init}}$ with a small learning-rate (Lee et al., 2019; Geiger et al., 2020).

We first introduce how we estimate equation 9 using f_T^{emp} at $t = T$. Then, we introduce the construction of surrogate posterior samples that greatly enhance our method.

4.1 LAYER-WISE SCALING (LINE 2 - 6)

Lazy training often fails to capture the full characteristics of practically trained neural networks (Seleznova & Kutyniok, 2022). In our experiments, we have observed significant changes in the empirical NTK throughout the training process. Therefore, to better capture a full picture of the whole training trajectory with only f_T^{emp}, we propose to use a reweighted empirical NTK to approximate the kernel Θ used for linearization in equation 3 and beyond:

$$\nabla_{\boldsymbol{\theta}} f_T^{emp}(\boldsymbol{z}) \boldsymbol{\Gamma}^2 \nabla_{\boldsymbol{\theta}} f_T^{emp}(\boldsymbol{x})^\top \approx \Theta(\boldsymbol{z}, \boldsymbol{x}), \quad (11)$$

where $\boldsymbol{\Gamma}$ is a diagonal matrix of size $|\boldsymbol{\theta}| \times |\boldsymbol{\theta}|$ that shares the same value for parameters within the same layer. Similarly, $\nabla_{\boldsymbol{\theta}} f_T^{emp}(\boldsymbol{z}) \boldsymbol{\Gamma} \approx \nabla_{\boldsymbol{\theta}} f(\boldsymbol{z})$.

This reweighting is applied as a layer-wise scaling over the empirical NTK evaluated at convergence. Given layer l with parameters $\boldsymbol{\theta}_l$, we scale them as

$$\boldsymbol{\Gamma}_l := (1/\sqrt{|\boldsymbol{\theta}_l|}) \cdot \boldsymbol{I}, \quad (12)$$

where $\boldsymbol{\Gamma}_l$ is the diagonal entries in $\boldsymbol{\Gamma}$ corresponds to $\boldsymbol{\theta}_l$. For converged networks, such scaling could potentially recover an earlier network state, which is more representative of the training trajectory as the majority of training has been done in this stage (in the sense of raw performance, e.g., accuracy). We demonstrate this effect empirically in Fig. 1.

In practice, to apply layer-wise scaling, we can simply multiply $\boldsymbol{\Gamma}$ to the perturbations introduced below.

Algorithm 1 TULiP for Classifiers. $\circ$: Elementwise product

---

Input: Input $z \in \mathbb{R}^d$, trained parameters $\boldsymbol{\theta}_T$, early checkpoint $\boldsymbol{\theta}_{t_s}$ (optional), network $f^{emp}(z; \boldsymbol{\theta})$
Parameter: Perturbation strength ϵ, δ; Parameter λ; Number of posterior samples M
Output: Uncertainty score U

1: $\boldsymbol{\theta}_{t_s} \leftarrow \mathbf{0}$ if not provided
2: **for all** Layer l of f^{emp} **do** $\triangleright$ Layer-wise scaling
3:      $\boldsymbol{\theta}_l \leftarrow$ parameters of layer l from $\boldsymbol{\theta}_T$
4:      $\Gamma_l \leftarrow \mathbf{1}(1/\sqrt{|\boldsymbol{\theta}_l|})$ $\triangleright$ Vector of length $|\boldsymbol{\theta}_l|$
5: **end for**
6: $\Gamma \leftarrow \text{Concatenate}(\Gamma_l)$
7: **for** $i = 1, \ldots, M$ **do**
8:      Sample $v_i \in \mathbb{R}^{|\boldsymbol{\theta}|}$ from $\mathcal{N}(0, \epsilon^2 \boldsymbol{I})$
9:      $\tilde{f}_i^{raw}(\boldsymbol{z}) \leftarrow f^{emp}(z; \boldsymbol{\theta}_T + \Gamma \circ v_i)$
10: **end for**
11: $\widetilde{\Theta}_{\text{Tr}}(\boldsymbol{z}, \boldsymbol{z}) \leftarrow \frac{1}{M} \sum_i \|\tilde{f}_i^{raw}(\boldsymbol{z}) - f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)\|^2$ $\triangleright$ Estimation of $\text{Tr}\, \Theta(\boldsymbol{z}, \boldsymbol{z})$
12: $D \leftarrow \|f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T + \epsilon \delta \Gamma \circ (\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})) - f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)\|$
13: $S \leftarrow \widetilde{\Theta}_{\text{Tr}}(\boldsymbol{z}, \boldsymbol{z}) - \lambda D$ $\triangleright$ Estimation of equation 9 up to $\mathbb{E}_{\boldsymbol{x}}[\Theta(\boldsymbol{x}, \boldsymbol{x})]$ and square root
14: $\gamma \leftarrow \sqrt{\max(S, 0)/\widetilde{\Theta}_{\text{Tr}}(\boldsymbol{z}, \boldsymbol{z})}$
15: **for** $i = 1, \ldots, M$ **do** $\triangleright$ Surrogate posterior samples
16:      $\tilde{f}_i(\boldsymbol{z}) \leftarrow (1 - \gamma)f^{emp}(z; \boldsymbol{\theta}_T) + \gamma \tilde{f}_i^{raw}(\boldsymbol{z})$
17: **end for**
18: $U \leftarrow \mathbb{H}_y\left(\frac{1}{M} \sum_i \text{softmax}(\tilde{f}_i(\boldsymbol{z}))\right)$

4.2 ESTIMATION OF JACOBIAN (LINE 7 - 13)

Estimating gradients explicitly is both time and memory-consuming, especially for networks with large output dimensions. Fortunately, for Jacobian-vector products as in equation 9, we may use a first-order approximation to avoid computing the gradients with a backward pass:

$$\lim_{\delta \to 0} \frac{1}{\delta} \left(f^{emp}(z; \boldsymbol{\theta}_T + \delta \boldsymbol{\Gamma} \tilde{\boldsymbol{\theta}}) - f^{emp}(z; \boldsymbol{\theta}_T) \right) \approx \nabla_{\boldsymbol{\theta}} f_T(z) \tilde{\boldsymbol{\theta}}. \tag{13}$$

We use it in line 12 of Alg. 1 to estimate $\|\nabla_{\boldsymbol{\theta}} f_T(\boldsymbol{z}) (\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})\|$ with D up to multiplications.

For $\text{Tr}\, \Theta(\boldsymbol{z}, \boldsymbol{z})$, we could estimate its value with Hutchinson's Trace Estimator (Avron & Toledo, 2011) (line 7-11).

Proposition 4.1. *Suppose that f^{emp} is γ-smooth w.r.t. $\boldsymbol{\theta}$, i.e.,*

$$\|\nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}) - \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}')\|_{\text{F}} \leq \gamma \|\boldsymbol{\theta} - \boldsymbol{\theta}'\|.$$

Let $\mathbf{v}$ be a random variable such that $\mathbb{E}_{\mathbf{v}}[\mathbf{v}] = \mathbf{0}, \mathbb{E}_{\mathbf{v}}[\mathbf{v}\mathbf{v}^\top] = \epsilon^2 \boldsymbol{I}$ and $\mathbb{E}_{\mathbf{v}}[\|\mathbf{v}\|^k] \leq C_k \epsilon^k$ for $k = 3, 4$, where C_k is a constant depending on k and the dimension of $\mathbf{v}$. Then, under A1, it holds that

$$\lim_{\epsilon \to 0} \frac{1}{\epsilon^2} \mathbb{E}_{\mathbf{v}} \left[\|f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v}) - f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)\|^2 \right] = \text{Tr} \left(\nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \boldsymbol{\Gamma}^2 \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \right). \tag{14}$$

Note that the multi-dimensional normal distribution with mean zero and variance-covariance matrix $\epsilon^2 \boldsymbol{I}$ agrees to the condition of $\mathbf{v}$. Proposition 4.1 and the approximation equation 11 ensures that $\text{Tr}\, \Theta(\boldsymbol{z}, \boldsymbol{z})$ is approximated by $\epsilon^{-2} \mathbb{E}_{\mathbf{v}}[\|f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v}) - f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)\|^2]$ with a small ϵ.

Proof. Please check Sec. A.5 for details. $\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\square$

From above, $\boldsymbol{z}$-relevent terms in equation 9 can be approximated while avoiding explicit computation of $\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z})$. Specifically, in line 13, S provides an estimation of the upper-bound equation 9 up to $\mathbb{E}_{\boldsymbol{x}}[\Theta(\boldsymbol{x}, \boldsymbol{x})]$, square root and multiplicative constants. Here, the hyper-parameter λ acts as a proxy to the constant K in Lemma 3.2. Such approximation is implemented by perturbations to $\boldsymbol{\theta}$, thus compatible with mini-batching, enabling fast computation with $\mathcal{O}(M)$ forward passes.

Figure 1: **a) b) c)** Empirical justifications for the layer-wise scaling scheme. We trained a ResNet-18 on CIFAR-10 dataset with SGD-momentum for 400 epochs. **a)** Average magnitude of Jacobian entries for different *conv* layers (solid) vs. time vs. validation accuracy (dashed). Layers with more parameters (lower) train slower compared to layers with fewer parameters (upper). **b)** The ratio between Jacobian norm at $t = $ Epoch 20 and $T = $ Epoch 400 vs. our scaling equation 11. A proportional relationship (dashed) supports such scaling in recovering an early NTK critical to training. **c)** Such relationship disappears at $t = $ Epoch 200. **d)** Verification for equation 8 (detailed setups in Sec. 5). ID Dataset: ImageNet-1K. OOD Datasets: ImageNet-C, ImageNet-R, SSB-Hard (Vaze et al., 2022), iNaturalist (Van Horn et al., 2018), Textures (Cimpoi et al., 2014).

4.3 Surrogate Network Ensemble (Line 14 - 18)

As stated in Sec. 3, the bound in equation 5 or 9 is insufficient to capture a full picture – for example, a well-trained classifier can be certain that a test data belongs to neither class, in a sense that an evaluation of equation 9 yields a small value, but their prediction (i.e., it belongs to neither classes) $\hat{f}_T(\boldsymbol{z})$ indicates OOD input. Informally yet intuitively, $\hat{f}_T(\boldsymbol{z})$ can also be seen as predictions of models sampled from some model posterior.

To this end, we propose to approximate $\hat{f}_T(\boldsymbol{z})$ by constructing $\tilde{f}(\boldsymbol{z})$, via the process described in line 14-18 of Alg. 1. In short, we squeeze the perturbed predictions $\tilde{f}_i^{raw}(\boldsymbol{z})$, producing $\tilde{f}(\boldsymbol{z})$, so that their variance matches equation 10, which is an upper bound of the variance of true perturbed predictions $\mathrm{Tr}(\mathrm{Var}_{\Delta_f}[\hat{f}_T(\boldsymbol{z})])$.

From line 16, it is possible to show

$$\mathrm{Tr}(\mathrm{Var}_i[\tilde{f}_i(\boldsymbol{z})]) \approx \gamma^2 \cdot \mathrm{Tr}(\mathrm{Var}_i[\tilde{f}_i^{raw}(\boldsymbol{z})]) \ = S, \tag{15}$$

for a positive S and small ϵ such that $\mathbb{E}_i[\tilde{f}_i^{raw}(\boldsymbol{z})] \approx f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)$. Note that γ is given in line 14 of Alg. 1, and S is an estimation of equation 9 as stated in the previous subsection. Sec. A.6 provides additional derivations to clarify their relationships.

For classification problems, after obtaining $\tilde{f}(\boldsymbol{z})$, it is then able to combine the epistemic uncertainty and model prediction via Information Entropy $\mathbb{H}$ (Shannon, 1948): $\mathbb{H}_y[\tilde{f}(\boldsymbol{z})] := -\sum_{y=1}^o \mathbb{E}[\sigma(\tilde{f}(\boldsymbol{z}))]_y \log \mathbb{E}[\sigma(\tilde{f}(\boldsymbol{z}))]_y$, where σ is the softmax operation producing the class probabilities and $[\cdot]_y$ takes the y-th component from a vector.

Yet, significant simplifications have been made for computational clarity. For example, $\mathbb{E}_{\boldsymbol{x}}[\Theta(\boldsymbol{x}, \boldsymbol{x})]$ has been omitted as it is intractable and irrelevant to $\boldsymbol{z}$. Empirically we have found that our method is effective despite such simplifications, which will be demonstrated in the next section. We choose to simplify this for clarity, avoiding the introduction of new hyper-parameters to TULiP.

Alg. 1 summarizes TULiP, our proposed uncertainty estimator for OOD detection. Although Alg. 1 gives TULiP for classification, it naturally generalizes to non-classification problems. As $\boldsymbol{\theta}_{t_s}$ is difficult to obtain in practice, we take $t_s = 0$ and use $\boldsymbol{\theta}_{t_s} = \mathbb{E}[\boldsymbol{\theta}_0] = \mathbf{0}$ instead (or chosen values if the initialization scheme is specified such that $\mathbb{E}[\boldsymbol{\theta}_0] \neq \mathbf{0}$).

Figure 2: Verification of Thm. 3.1 with synthetic data. From left to right, we have **a)**: Regression on Splines. Light shade indicates the bound equation 5, heavy shade indicates the solved ensemble (Ground-Truth, equation 1) with black dots as training data. **b) c)**: Binary classification on Two-Moons. The brighter colour indicates larger values across the input space. **b)**: Prediction variance of 20 simulated runs, **c)**: Evaluation of equation 5.

5 EXPERIMENTS

5.1 EMPIRICAL VALIDATION FOR SECTION 3

Synthetic Datasets   We begin this section by validating the original bound presented in equation 5. Two types of artificial datasets have been considered: namely *Splines* for regression and *Two-Moons* for classification problems. A 3-layer infinite-wide feed-forward neural network is used and we solved the lazy training dynamics over the dataset using the *neural-tangents* library (Novak et al., 2020). For Splines, we used MSE loss and computed the exact Gaussian ensemble (Lee et al., 2019). For Two-Moons, we used binary cross-entropy loss and numerically simulated the lazy gradient descent for 20 runs. Results are shown in Fig. 2. It suggests that our bound equation 5 based on training fluctuations is able to capture the true epistemic uncertainty as in equation 1, justifies further developments of our method.

Closeness Condition   We proceed by presenting empirical justifications for equation 8 in Fig. 1 d). We used a ResNet18 (He et al., 2016) pre-trained on ImageNet-1K (Russakovsky et al., 2015), computed equation 8 by 256 samples from the ID dataset (ImageNet-1K) and 128 samples per OOD dataset. The scaled empirical NTK as in equation 11 is used in this experiment. Clearly, we see that equation 8 is satisfied by a large margin under this practical setting.

5.2 OUT-OF-DISTRIBUTION DETECTION

In this subsection, we demonstrate the effectiveness of our method for OOD detection in real-world scenarios by comparing TULiP with state-of-the-art OOD detectors.

Experiment Setup   In the following experiments, we use $M = 10$ surrogate posterior samples with $\epsilon = 2.0$, $\delta = 2$ and $\lambda = \sqrt{o}$ where o is the number of output dimensions. Only weights in the convolutional and fully connected layers are being perturbed, while biases are ignored. Following Zhang et al. (2023), we conduct a hyper-parameter search on a small validation set whenever possible, within a reasonable range of $\epsilon \in \{0.1, 0.5, 1.5, 2.0\}$, $\delta \in \{2, 5, 8\}$ and $\lambda \in \{\sqrt{o}, 3\sqrt{o}\}$. We explain our choice for hyper-parameters in Sec. B.2. We consider two OOD scenarios, namely Semantic-Shift OOD and Covariate-Shift OOD (Yang et al., 2024). The fundamental difference between them is that semantic-shift OOD considers distributional shift on both input x and label y, often with unseen classes. Covariate-shift OOD considers distributional shift solely on input x. We believe this setting is also significant for practical use. For instance, we may wish to distinguish real-world images from AI-generated ones (Zhang et al., 2024), or identify images that are severely contaminated due to environmental factors or sensor malfunctions (Baek et al., 2024). We present details of all datasets in Sec. B.1 and provide additional experimental results as well as details of reported results in Sec. C.

Baseline Methods   We consider various baselines for comparison, including the MC-Dropout (MCD), post-hoc OOD method without training data ODIN, EBO, ASH; and finally, MDS and ViM with access to training data. Please refer to Sec. 2 for a brief introduction.

Table 1: Results on OpenOOD benchmark, averaged from 3 runs. The top results for each category are marked in bold, with the second-best result in underlined. We include baseline results from Zhang et al. (2023), and reproduced the results for MC-Dropout (MCD). A dagger symbol † indicates direct access to training data or processes. Results are averaged separately for *near* / *far*-OOD sets.

Method	CIFAR-10		CIFAR-100		ImageNet-200		ImageNet-1K	
	FPR@95↓	AUROC↑	FPR@95↓	AUROC↑	FPR@95↓	AUROC↑	FPR@95↓	AUROC↑
MCD †	53.54/31.43	87.68/91.00	**54.73**/59.08	80.42/77.58	55.25/35.48	83.30/90.20	65.68/51.45	76.02/85.23
MDS †	49.90/32.22	84.20/89.72	83.53/72.26	58.69/69.39	79.11/61.66	61.93/74.72	85.45/62.92	55.44/74.25
ViM †	44.84/25.05	88.68/**93.48**	62.63/50.74	74.98/**81.70**	59.19/**27.20**	78.68/91.26	71.35/24.67	72.08/92.68
ODIN	76.19/57.62	82.87/87.96	57.91/58.86	79.90/79.28	66.76/34.23	80.27/91.71	72.50/43.96	74.75/89.47
EBO	61.34/41.69	87.58/91.21	55.62/56.59	80.91/79.77	60.24/34.86	82.50/90.86	68.56/38.39	75.89/89.47
MLS	61.32/41.68	87.52/91.10	55.47/56.73	81.05/79.67	59.76/34.03	82.90/91.11	**51.35**/63.60	76.46/89.57
ASH	86.78/79.03	75.27/78.49	65.71/59.20	78.20/80.58	64.89/27.29	82.38/**93.90**	63.32/**19.49**	**78.17**/**95.74**
TULiP	**33.80**/**24.43**	**89.67**/92.55	55.07/58.17	**81.29**/79.63	**54.51**/33.94	**83.84**/91.03	64.96/48.01	77.52/88.03

Semantic Shift OOD   We report the performance of TULiP on OpenOOD v1.5 benchmark (Zhang et al., 2023) in Table 1. Following their setup, we use the same pre-trained ResNet-18 (He et al., 2016) for CIFAR-10 & 100 (Krizhevsky, 2009) and ImageNet-200 (Zhang et al., 2023) ID datasets, and ResNet-50 for ImageNet-1K (Russakovsky et al., 2015). OOD data range across a collection of diverse image datasets (Cimpoi et al., 2014; Vaze et al., 2022; Van Horn et al., 2018; Bitterwolf et al., 2023; Le & Yang, 2015; Zhou et al., 2018; Kuznetsova et al., 2020), categorized into *near* and *far* OOD sets (Yang et al., 2022), where near is more similar to ID and therefore more difficult to distinguish. TULiP achieves remarkable performance in near-OOD settings with either top-1 or top-2 AUROC scores across all datasets. Indeed, as suggested by equation 8, better performance on near-ID scenarios is expected. On the far-OOD side, TULiP also performs consistently well. We note that methods significantly outperform TULiP on far-OOD either access the training dataset (ViM and MDS) or completely lack theoretical explanation (ASH). In contrast, TULiP has theoretical foundations and does not require a training dataset.

Covariate Shift OOD   We test TULiP on the covariate shift setting with Blurred ImageNet, ImageNet-C (Hendrycks & Dietterich, 2019), ImageNet-R (Hendrycks et al., 2021) and ImageNet-ES (Baek et al., 2024) as OOD data. A description of these datasets can be found in Sec. B.1. For this experiment, the ImageNet validation set with blur is used for the hyper-parameter grid search. Table 2 reports the results. TULiP achieves top performance on ImageNet-C except for methods that require training data (MCD, MDS, ViM). This usually leads to longer evaluation time. For instance, ViM takes more than 30 minutes just to extract ID information using

Table 2: CS OOD results by averaging 3 runs. Results are in AUROC (higher is better).

Method	Blur	ImNet-C	ImNet-R	ImNet-ES
MCD †	69.90	77.06	80.52	79.98
MDS †	55.02	70.94	69.62	49.66
ViM †	73.88	**83.93**	**87.92**	82.54
ODIN	79.43	77.48	85.35	81.94
EBO	74.41	81.21	87.05	84.41
MLS	74.23	81.06	86.72	84.17
ASH	78.42	82.18	85.24	84.22
TULiP	**85.34**	82.91	82.07	**85.91**

a recent GPU machine. In contrast, a typical full evaluation of TULiP on test split takes $3\times$ less time. On the other hand, ImageNet-R contains images that are less similar to ImageNet-1K (i.e. further from ID). When tuned on a near validation set like Blur-ImageNet, TULiP tends to favour near OOD by trading off the far ones. This is consistent with Table 1 and equation 8. Such phenomena are further demonstrated in Fig. 4.

Network Architecture Choice   To verify TULiP across different network architectures, we conduct experiments with various networks on semantic-shift OOD with ImageNet-1K. The pre-trained models and weights are collected directly from *torchvision* (maintainers & contributors, 2016), and we only consider methods that work without additional modifications for compatibility. Results are shown in Fig. 3. TULiP relies on assumptions of the training process, which could be potentially violated by different training protocols and architectures. Nevertheless, TULiP still outperforms baseline methods consistently across the board, comparable to Table 1. Such results further suggest the effectiveness and versatility of TULiP.

Figure 4: Results by varying ϵ and λ on ImageNet-200 ID. The value of λ in either the horizontal axis or legend should be read as, e.g., $\lambda = 1.5\sqrt{o}$.

Ablation Study and Hyper-parameters   We conduct experiments on semantic-shifted ImageNet-200 to analyze the effect of hyper-parameters. Results are shown in Fig. 4, where we observe a trade-off in near and far OOD performance. It is also clear from the results that λ and Lemma 3.2 boosts the performance and hyper-parameter stability (mainly to ϵ) of TULiP. In practice, ϵ controls the strength of weight perturbation and, hence, the most important hyper-parameter of TULiP. Our method failed to achieve consistent performance across various datasets without layer-wise scaling, potentially due to its increased vulnerability to hyper-parameters and training setups. Please refer to Sec. C for more details.

6   CONCLUSION

In this study, we present TULiP, an uncertainty estimator for OOD detection. Our method is driven by the fluctuations under linearized training dynamics and excels in practical experiments. However, there are some limitations and future works remaining. Theoretically, our framework only considers functional perturbation. The perturbation on the NTK is also important (Kobayashi et al., 2022) and could be integrated into the estimator in the future. Empirically, TULiP does not achieve top-class performance when the OOD data is far from ID (far-OOD). Such tradeoff in Fig. 4 hints at the inconsistency of best hyper-parameters for different setups. Future works may improve upon these aspects, covering a wider range of OOD data by examining the network parameters and refining weight perturbations.

Figure 3: ImageNet-1K OpenOOD benchmarks on different network architectures: MobileNet V3 Large (MbNet) (Howard et al., 2019), VGG 16 (Simonyan & Zisserman, 2015), RegNet Y 16GF (Radosavovic et al., 2020).

Furthermore, it could also be valuable to explore TULiP in other learning paradigms, such as Active Learning (Wang et al., 2022a) or Reinforcement Learning (Szepesvari, 2010).

7   REPRODUCIBILITY STATEMENT

We list our theoretical assumptions at the start of section 3.3, and all proofs thereafter are given in section A of the Appendix. We provide a thorough overview of our experimental setup in section 5. A more detailed description of OOD configurations and additional results are presented in sections B and C of the Appendix, respectively. In the source codes provided in the supplementary materials, we include our implementation of the algorithm and the scripts to produce all visualizations. Additionally, we list the steps required to reproduce the OpenOOD results and provide a yaml file with all the hyper-parameters for the reported performance in this paper.

REFERENCES

Shahin Atakishiyev, Mohammad Salameh, Hengshuai Yao, and Randy Goebel. Explainable artificial intelligence for autonomous driving: A comprehensive overview and field guide for future research directions. *IEEE Access*, 12:101603–101625, 2024. doi: 10.1109/ACCESS.2024.3431437.

Haim Avron and Sivan Toledo. Randomized algorithms for estimating the trace of an implicit symmetric positive semi-definite matrix. *Journal of the ACM (JACM)*, 58(2):1–34, 2011.

Eunsu Baek, Keondo Park, Jiyoon Kim, and Hyung-Sin Kim. Unexplored faces of robustness and out-of-distribution: Covariate shifts in environment and sensor domains. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 22294–22303, 2024.

Julian Bitterwolf, Maximilian Müller, and Matthias Hein. In or out? fixing imagenet out-of-distribution detection evaluation, 2023. URL https://arxiv.org/abs/2306.00826.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural network. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 1613–1622, Lille, France, 07–09 Jul 2015a. PMLR. URL https://proceedings.mlr.press/v37/blundell15.html.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural network. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 1613–1622, Lille, France, 07–09 Jul 2015b. PMLR. URL https://proceedings.mlr.press/v37/blundell15.html.

Zhengdao Chen, Grant Rotskoff, Joan Bruna, and Eric Vanden-Eijnden. A dynamical central limit theorem for shallow neural networks. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 22217–22230. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/fc5b3186f1cf0daece964f78259b7ba0-Paper.pdf.

Mircea Cimpoi, Subhransu Maji, Iasonas Kokkinos, Sammy Mohamed, and Andrea Vedaldi. Describing textures in the wild. In *2014 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3606–3613, 2014. doi: 10.1109/CVPR.2014.461.

Erik Daxberger, Agustinus Kristiadi, Alexander Immer, Runa Eschenhagen, Matthias Bauer, and Philipp Hennig. Laplace redux - effortless bayesian deep learning. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 20089–20103. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper_files/paper/2021/file/a7c9585703d275249f30a088cebba0ad-Paper.pdf.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 248–255, 2009. doi: 10.1109/CVPR.2009.5206848.

Terrance DeVries and Graham W Taylor. Learning confidence for out-of-distribution detection in neural networks. *arXiv preprint arXiv:1802.04865*, 2018.

Andrija Djurisic, Nebojsa Bozanic, Arjun Ashok, and Rosanne Liu. Extremely simple activation shaping for out-of-distribution detection. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=ndYXTEL6cZz.

Simon Du, Jason Lee, Haochuan Li, Liwei Wang, and Xiyu Zhai. Gradient descent finds global minima of deep neural networks. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 1675–1685. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/du19c.html.

Andre Esteva, Brett Kuprel, Roberto A Novoa, Justin Ko, Susan M Swetter, Helen M Blau, and Sebastian Thrun. Dermatologist-level classification of skin cancer with deep neural networks. *Nature*, 542(7639):115–118, 2017.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In Maria Florina Balcan and Kilian Q. Weinberger (eds.), *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine*

Learning Research, pp. 1050–1059, New York, New York, USA, 20–22 Jun 2016. PMLR. URL `https://proceedings.mlr.press/v48/gal16.html`.

Mario Geiger, Stefano Spigler, Arthur Jacot, and Matthieu Wyart. Disentangling feature and lazy training in deep neural networks. *Journal of Statistical Mechanics: Theory and Experiment*, 2020 (11):113301, nov 2020. doi: 10.1088/1742-5468/abc4de. URL `https://dx.doi.org/10.1088/1742-5468/abc4de`.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1321–1330. PMLR, 06–11 Aug 2017a. URL `https://proceedings.mlr.press/v70/guo17a.html`.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1321–1330. PMLR, 06–11 Aug 2017b. URL `https://proceedings.mlr.press/v70/guo17a.html`.

Bobby He, Balaji Lakshminarayanan, and Yee Whye Teh. Bayesian deep ensembles via the neural tangent kernel. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1010–1022. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper_files/paper/2020/file/0b1ec366924b26fc98fa7b71a9c249cf-Paper.pdf`.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016. doi: 10.1109/CVPR.2016.90.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=HJz6tiCqYm`.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *International Conference on Learning Representations*, 2017. URL `https://openreview.net/forum?id=Hkg4TI9xl`.

Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, Dawn Song, Jacob Steinhardt, and Justin Gilmer. The many faces of robustness: A critical analysis of out-of-distribution generalization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 8340–8349, October 2021.

Dan Hendrycks, Steven Basart, Mantas Mazeika, Andy Zou, Joseph Kwon, Mohammadreza Mostajabi, Jacob Steinhardt, and Dawn Song. Scaling out-of-distribution detection for real-world settings. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 8759–8773. PMLR, 17–23 Jul 2022. URL `https://proceedings.mlr.press/v162/hendrycks22a.html`.

Stephen C. Hora. Aleatory and epistemic uncertainty in probability elicitation with an example from hazardous waste management. *Reliability Engineering & System Safety*, 54(2):217–223, 1996. ISSN 0951-8320. doi: https://doi.org/10.1016/S0951-8320(96)00077-4. URL `https://www.sciencedirect.com/science/article/pii/S0951832096000774`.

Andrew Howard, Mark Sandler, Bo Chen, Weijun Wang, Liang-Chieh Chen, Mingxing Tan, Grace Chu, Vijay Vasudevan, Yukun Zhu, Ruoming Pang, Hartwig Adam, and Quoc Le. Searching for mobilenetv3. In *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 1314–1324, 2019. doi: 10.1109/ICCV.2019.00140.

Rui Huang and Yixuan Li. Mos: Towards scaling out-of-distribution detection for large semantic space. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8710–8719, 2021.

Eyke Hüllermeier and Willem Waegeman. Aleatoric and epistemic uncertainty in machine learning: an introduction to concepts and methods. *Machine Learning*, 110(3):457–506, 2021. doi: 10.1007/ S10994-021-05946-3. URL https://doi.org/10.1007/s10994-021-05946-3.

Sergey Ioffe and Christian Szegedy. Batch normalization: accelerating deep network training by reducing internal covariate shift. In *Proceedings of the 32nd International Conference on International Conference on Machine Learning - Volume 37*, ICML'15, pp. 448–456. JMLR.org, 2015.

Arthur Jacot, Franck Gabriel, and Clement Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper_fil es/paper/2018/file/5a4be1fa34e62bb8a6ec6b91d2462f5a-Paper.pdf.

Seijin Kobayashi, Pau Vilimelis Aceituno, and Johannes von Oswald. Disentangling the predictive variance of deep ensembles through the neural tangent kernel. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 25335–25348. Curran Associates, Inc., 2022. URL https://procee dings.neurips.cc/paper_files/paper/2022/file/a205fda871b0f6c1e18 a7ad7325eb6cf-Paper-Conference.pdf.

Ranganath Krishnan and Omesh Tickoo. Improving model calibration with accuracy versus uncertainty optimization. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 18237–18248. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper /2020/file/d3d9446802a44259755d38e6d163e820-Paper.pdf.

Alex Krizhevsky. Learning multiple layers of features from tiny images. *Master's thesis, University of Tront*, 2009.

Alina Kuznetsova, Hassan Rom, Neil Alldrin, Jasper Uijlings, Ivan Krasin, Jordi Pont-Tuset, Shahab Kamali, Stefan Popov, Matteo Malloci, Alexander Kolesnikov, et al. The open images dataset v4: Unified image classification, object detection, and visual relationship detection at scale. *International Journal of Computer Vision*, 128(7):1956–1981, 2020. doi: 10.1007/s11263-020-0 1316-z.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurip s.cc/paper_files/paper/2017/file/9ef2ed4b7fd2c810847ffa5fa85bce3 8-Paper.pdf.

Ya Le and Xuan Yang. Tiny imagenet visual recognition challenge. *Class CS 231N, Stanford University*, 2015. URL https://cs231n.stanford.edu/reports/2015/pdfs/yl e_project.pdf.

Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998. doi: 10.1109/5.726791.

Jaehoon Lee, Lechao Xiao, Samuel Schoenholz, Yasaman Bahri, Roman Novak, Jascha Sohl-Dickstein, and Jeffrey Pennington. Wide neural networks of any depth evolve as linear models under gradient descent. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper_files/p aper/2019/file/0d1a9651497a38d8b1c3871c84528bd4-Paper.pdf.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurip s.cc/paper_files/paper/2018/file/abdeb6f575ac5c6676b747bca8d09cc 2-Paper.pdf.

Shiyu Liang, Yixuan Li, and R. Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=H1VGkIxRZ.

Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 21464–21475. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/f 5496252609c43eb8a3d147ab9b9c006-Paper.pdf.

TorchVision maintainers and contributors. Torchvision: Pytorch's computer vision library. https: //github.com/pytorch/vision, 2016.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NIPS Workshop on Deep Learning and Unsupervised Feature Learning 2011*, 2011. URL http://ufldl.stanford.edu/h ousenumbers/nips2011_housenumbers.pdf.

Roman Novak, Lechao Xiao, Jiri Hron, Jaehoon Lee, Alexander A. Alemi, Jascha Sohl-Dickstein, and Samuel S. Schoenholz. Neural tangents: Fast and easy infinite neural networks in python. In *International Conference on Learning Representations*, 2020. URL https://github.com/g oogle/neural-tangents.

Ilija Radosavovic, Raj Prateek Kosaraju, Ross Girshick, Kaiming He, and Piotr Dollár. Designing network design spaces. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10425–10433, 2020. doi: 10.1109/CVPR42600.2020.01044.

Jie Ren, Stanislav Fort, Jeremiah Liu, Abhijit Guha Roy, Shreyas Padhy, and Balaji Lakshminarayanan. A simple fix to mahalanobis distance for improving near-ood detection, 2021. URL https: //arxiv.org/abs/2106.09022.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge. *International Journal of Computer Vision*, 115(3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

Mariia Seleznova and Gitta Kutyniok. Analyzing finite neural networks: Can we trust neural tangent kernel theory? In Joan Bruna, Jan Hesthaven, and Lenka Zdeborova (eds.), *Proceedings of the 2nd Mathematical and Scientific Machine Learning Conference*, volume 145 of *Proceedings of Machine Learning Research*, pp. 868–895. PMLR, 16–19 Aug 2022. URL https://procee dings.mlr.press/v145/seleznova22a.html.

C. E. Shannon. A mathematical theory of communication. *The Bell System Technical Journal*, 27(3): 379–423, 1948. doi: 10.1002/j.1538-7305.1948.tb01338.x.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *International Conference on Learning Representations*, 2015. URL http: //arxiv.org/abs/1409.1556.

Csaba Szepesvari. *Algorithms for Reinforcement Learning*. Morgan and Claypool Publishers, 2010. ISBN 1608454924.

Jayaraman Thiagarajan, Rushil Anirudh, Vivek Sivaraman Narayanaswamy, and Timo Bremer. Single model uncertainty estimation via stochastic data centering. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 8662–8674. Curran Associates, Inc., 2022. URL https://proceedings.ne

urips.cc/paper_files/paper/2022/file/392d0d05e2f514063e6ce6f8b37
0834c-Paper-Conference.pdf.

Grant Van Horn, Oisin Mac Aodha, Yang Song, Yin Cui, Chen Sun, Alex Shepard, Hartwig Adam, Pietro Perona, and Serge Belongie. The inaturalist species classification and detection dataset. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8769–8778, 2018. doi: 10.1109/CVPR.2018.00914.

Sagar Vaze, Kai Han, Andrea Vedaldi, and Andrew Zisserman. Open-set recognition: A good closed-set classifier is all you need. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=5hLP5JY9S2d.

Vasilis Vryniotis. How to train state-of-the-art models using torchvision's latest primitives, 2021. https://pytorch.org/blog/how-to-train-state-of-the-art-models-u sing-torchvision-latest-primitives/ [Accessed: 1st Oct., 2024].

Hao Wang and Dit-Yan Yeung. A survey on bayesian deep learning. *ACM Comput. Surv.*, 53(5), sep 2020. ISSN 0360-0300. doi: 10.1145/3409383. URL https://doi.org/10.1145/3409 383.

Haonan Wang, Wei Huang, Ziwei Wu, Hanghang Tong, Andrew J Margenot, and Jingrui He. Deep active learning by leveraging training dynamics. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 25171–25184. Curran Associates, Inc., 2022a. URL https://proceedings. neurips.cc/paper_files/paper/2022/file/a102dd5931da01e1b40205490 513304c-Paper-Conference.pdf.

Haoqi Wang, Zhizhong Li, Litong Feng, and Wayne Zhang. Vim: Out-of-distribution with virtual-logit matching. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4921–4930, June 2022b.

Jingkang Yang, Pengyun Wang, Dejian Zou, Zitang Zhou, Kunyuan Ding, WENXUAN PENG, Haoqi Wang, Guangyao Chen, Bo Li, Yiyou Sun, Xuefeng Du, Kaiyang Zhou, Wayne Zhang, Dan Hendrycks, Yixuan Li, and Ziwei Liu. OpenOOD: Benchmarking generalized out-of-distribution detection. In *Thirty-sixth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2022. URL https://openreview.net/forum?id=gT6j4_tskUt.

Jingkang Yang, Kaiyang Zhou, Yixuan Li, and Ziwei Liu. Generalized out-of-distribution detection: A survey. *International Journal of Computer Vision*, 2024.

Chenshuang Zhang, Fei Pan, Junmo Kim, In So Kweon, and Chengzhi Mao. Imagenet-d: Bench-marking neural network robustness on diffusion synthetic object. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 21752–21762, 2024.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=Sy8gdB9xx.

Jingyang Zhang, Jingkang Yang, Pengyun Wang, Haoqi Wang, Yueqian Lin, Haoran Zhang, Yiyou Sun, Xuefeng Du, Kaiyang Zhou, Wayne Zhang, Yixuan Li, Ziwei Liu, Yiran Chen, and Hai Li. Openood v1.5: Enhanced benchmark for out-of-distribution detection, 2023. URL https: //arxiv.org/abs/2306.09301.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(6):1452–1464, 2018. doi: 10.1109/TPAMI.2017.2723009.

A   PROOFS

A.1   BASIC NOTATIONS

For a network $f(\boldsymbol{x}) : \mathbb{R}^d \to \mathbb{R}^o$ maps inputs $\boldsymbol{x}$ of dimension d to outputs $f(\boldsymbol{x})$ of dimension o, parameterized by $\boldsymbol{\theta}$ with $|\boldsymbol{\theta}|$ trainable parameters, the gradient / Jacobian matrix $\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})$ is a $o \times |\boldsymbol{\theta}|$ matrix.

The NTK $\Theta(\boldsymbol{z}, \boldsymbol{x}) := \nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})^\top$ is a $o \times o$ matrix.

$\ell'(f_t(\boldsymbol{x}))$ is the gradient of loss function w.r.t. network output $f_t(\boldsymbol{x})$ at training time t. It is, for convenience, a $o \times 1$ column-vector.

The following lemma will be useful thereafter, which is an application of Hölder's inequality.

Lemma A.1. *Let $F : x \to \mathbb{R}^{m \times n}$, $g : x \to \mathbb{R}^n$. Consider 2-norms $\| \cdot \|$ (i.e., euclidean and its induced matrix 2-norm). For $p, q \in [1, \infty]$ that $\frac{1}{p} + \frac{1}{q} = 1$, we have*

$$
\begin{aligned}
& \|\mathbb{E}_x[F(\boldsymbol{x})g(\boldsymbol{x})]\| \\
\leq\; & \mathbb{E}_x[\|F(\boldsymbol{x})g(\boldsymbol{x})\|] \\
\leq\; & \mathbb{E}_{\boldsymbol{x}}[\|F(\boldsymbol{x})\| \cdot \|g(\boldsymbol{x})\|] \\
\leq\; & \mathbb{E}_{\boldsymbol{x}}[\|F(\boldsymbol{x})\|^p]^{1/p} \cdot \mathbb{E}_{\boldsymbol{x}}[\|g(\boldsymbol{x})\|^q]^{1/q} .
\end{aligned}
$$

When $q = \infty$, we have $\mathbb{E}_{\boldsymbol{x}}[\|g(\boldsymbol{x})\|^q]^{1/q} := \sup_x \|g(\boldsymbol{x})\|$.

For convenience, given any random variable, vector or matrix $\mathbf{A}$ dependent of $\boldsymbol{x}$, we denote:

$$
\|\mathbf{A}\|_X^{(q)} := \mathbb{E}_{\boldsymbol{x}}[\|\mathbf{A}\|^q]^{1/q} , \tag{16}
$$

which by itself is a valid norm. We omit superscript (q) if $q = 2$.

A.2   ASSUMPTIONS

We recall the assumptions here, which are originally shown in Sec. 3. For network $f(\boldsymbol{x}, \boldsymbol{\theta})$, dataset X with no parallel datapoints and a twice-differentiable loss function ℓ, we assume the followings:

A1. (Boundedness) For $t \in [0, T]$, $f(\boldsymbol{x})$, $\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})$, ℓ and ℓ' stay bounded, uniformly on $\boldsymbol{x}$.

A2. (Smoothness) Gradient ℓ' of loss function ℓ is Lipschitz continuous: $\forall x \in X;\ \|\ell'(\hat{y}; y(\boldsymbol{x})) - \ell'(\hat{y}'; y(\boldsymbol{x}))\| \leq L\|\hat{y} - \hat{y}'\|$.

A3. (Perturbation) The perturbation Δf can be uniformly bounded by a constant α, that is, for all $\boldsymbol{x}$ (not limited to the support of training data), i.e., $\forall x \in \mathbb{R}^d;\ \|\Delta f(\boldsymbol{x})\| \leq \alpha$.

A4. (Convergence) Finally, for the original network trained via equation 3 and the perturbed network trained via equation 4, we assume *near-perfect convergence* on the training set $\boldsymbol{x}$ at termination time $t = T$, i.e., $\exists \beta \in \mathbb{R}, \forall x \in X;\ \|f_T(\boldsymbol{x}) - \hat{f}_T(\boldsymbol{x})\| \leq \beta$.

A.3   PROOF OF THEOREM 3.1

Theorem A.2. *(Theorem 3.1) Under assumptions A1-A4, for a network f trained with equation 3 and a perturbed network $\hat{f}$ trained with equation 4, the perturbation applied at time $t_s = T - \Delta T$ bounded by α, we have*

$$
\|f_T(\boldsymbol{z}) - \hat{f}_T(\boldsymbol{z})\| \leq \inf_{\boldsymbol{x} \in X} C\|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) - \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})\|_{\mathrm{F}} + 2\alpha + \beta, \tag{17}
$$

where $C = \frac{\alpha \eta \bar{\Theta}_X^{1/2}}{\lambda_{max}} \left(e^{(T - t_s) L \lambda_{max}} - 1 \right)$, $\bar{\Theta}_X^{1/2} := \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})\|_X$ is the average gradient norm over training data, and $\lambda_{max} := \frac{1}{\sqrt{N}} \|\boldsymbol{G}\|$ for a generalized Gram matrix $G_{i,j} := \|\Theta(x_i, x_j)\|$ of dataset $X = \{x_1, x_2, \ldots, x_N\}$.

Proof. Let us first examine the fluctuations in the training set. From the Lipschitz continuity of ℓ',

$$\left\| \ell'(f_t(\boldsymbol{x})) - \ell'(\hat{f}_t(\boldsymbol{x})) \right\|_X \leq L \| f(\boldsymbol{x}) - \hat{f}(\boldsymbol{x}) \|_X. \tag{18}$$

Thus, by the linearized dynamics we have

$$\partial_t \left\| f_t(\boldsymbol{x}) - \hat{f}_t(\boldsymbol{x}) \right\|_X$$

$$\leq \left\| \partial_t \left(f_t(\boldsymbol{x}) - \hat{f}_t(\boldsymbol{x}) \right) \right\|_X \tag{19}$$

$$= \left\| \mathbb{E}_{x'} \left[\Theta(\boldsymbol{x}, \boldsymbol{x}') \left(\ell'(f_t(\boldsymbol{x}')) - \ell'(\hat{f}_t(\boldsymbol{x}')) \right) \right] \right\|_X$$

$$= \mathbb{E}_{\boldsymbol{x}} \left[\left\| \mathbb{E}_{x'} \left[\Theta(\boldsymbol{x}, \boldsymbol{x}') \left(\ell'(f_t(\boldsymbol{x}')) - \ell'(\hat{f}_t(\boldsymbol{x}')) \right) \right] \right\|^2 \right]^{1/2}$$

$$\leq \mathbb{E}_x \left[\| \Theta(\boldsymbol{x}, \boldsymbol{x}') \|_X^2 \left\| \ell'(f_t(\boldsymbol{x}')) - \ell'(\hat{f}_t(\boldsymbol{x}')) \right\|_X^2 \right]^{1/2}$$

$$\leq \mathbb{E}_{x,x'} \left[\| \Theta(\boldsymbol{x}, \boldsymbol{x}') \|^2 \right]^{1/2} \left\| \ell'(f_t(\boldsymbol{x})) - \ell'(\hat{f}_t(\boldsymbol{x})) \right\|_X$$

$$\leq L \lambda_{max} \left\| f_t(\boldsymbol{x}) - \hat{f}_t(\boldsymbol{x}) \right\|_X, \tag{20}$$

where in equation 19 we have used the triangle inequality to put ∂_t inside the norm. λ_{max} is defined as $\frac{1}{\sqrt{N}} \| \mathbf{G} \|$ for a generalized Gram-matrix $\mathbf{G}_{ij} := \| \Theta(x_i, x_j) \|$ of dataset $X = \{x_1, x_2, \ldots, x_N\}$, measures the fitness (or alignment) of the kernel Θ w.r.t. the training data.

From equation 20, we can apply the Grönwall's inequality to obtain

$$\left\| f_t(\boldsymbol{x}) - \hat{f}_t(\boldsymbol{x}) \right\|_X$$

$$\leq \left\| f_{t_s}(\boldsymbol{x}) - \hat{f}_{t_s}(\boldsymbol{x}) \right\|_X e^{(t-t_s)L\lambda_{max}}$$

$$\leq \alpha e^{(t-t_s)L\lambda_{max}}. \tag{21}$$

We now prove Theorem 3.1 by generalizing equation 21 to given test data.

For a test point $z \in \mathbb{R}^d$, choose a pivot point $\boldsymbol{x}^* \in X$ from the training set. Then for the network function f evaluated at $\boldsymbol{x}^*$ and $\boldsymbol{z}$, we have the followings:

$$\left| \partial_t \left\| (f_t(\boldsymbol{z}) - f_t(\boldsymbol{x}^*)) - \left(\hat{f}_t(\boldsymbol{z}) - \hat{f}_t(\boldsymbol{x}^*) \right) \right\| \right|$$

$$\leq \left\| \partial_t \left[(f_t(\boldsymbol{z}) - f_t(\boldsymbol{x}^*)) - \left(\hat{f}_t(\boldsymbol{z}) - \hat{f}_t(\boldsymbol{x}^*) \right) \right] \right\|$$

$$= \eta \left\| \mathbb{E}_{\boldsymbol{x}} \left[(\Theta(\boldsymbol{z}, \boldsymbol{x}) - \Theta(\boldsymbol{x}^*, \boldsymbol{x})) \cdot \left(\ell'(f_t(\boldsymbol{x})) - \ell'(\hat{f}_t(\boldsymbol{x})) \right) \right] \right\| \tag{22}$$

Denote

$$\left\| (f_t(\boldsymbol{z}) - f_t(\boldsymbol{x}^*)) - \left(\hat{f}_t(\boldsymbol{z}) - \hat{f}_t(\boldsymbol{x}^*) \right) \right\|$$

as $\Delta f_t(\boldsymbol{z})$, and let $\Theta_{\boldsymbol{x}^*}^{\text{diff}}(\boldsymbol{z}, \boldsymbol{x}) := (\Theta(\boldsymbol{z}, \boldsymbol{x}) - \Theta(\boldsymbol{x}^*, \boldsymbol{x}))$. Integrate equation 22 with t, we have

$$|\Delta f_T(\boldsymbol{z}) - \Delta f_{ts}(\boldsymbol{z})|$$

$$\leq \eta \int_{t_s}^T \left\| \mathbb{E}_{\boldsymbol{x}} \left[\Theta_{\boldsymbol{x}^*}^{\text{diff}}(\boldsymbol{z}, \boldsymbol{x}) \left(\ell'(f_t(\boldsymbol{x})) - \ell'(\hat{f}_t(\boldsymbol{x})) \right) \right] \right\| dt$$

$$\leq \eta \int_{t_s}^T \left\| \Theta_{\boldsymbol{x}^*}^{\text{diff}}(\boldsymbol{z}, \boldsymbol{x}) \right\|_X \left\| \ell'(f_t(\boldsymbol{x})) - \ell'(\hat{f}_t(\boldsymbol{x})) \right\|_X dt$$

$$\leq \eta L \left\| \Theta_{\boldsymbol{x}^*}^{\text{diff}}(\boldsymbol{z}, \boldsymbol{x}) \right\|_X \int_{t_s}^T \left\| f_t(\boldsymbol{x}) - \hat{f}_t(\boldsymbol{x}) \right\|_X dt \tag{23}$$

We start with the term before the integral. To begin, rewrite it as:

$$\|\Theta(\boldsymbol{z}, \boldsymbol{x}) - \Theta(\boldsymbol{x}^*, \boldsymbol{x})\|_X$$
$$= \left\|\left(\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) - \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x}^*)\right) \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})^\top\right\|_X$$
$$\leq \mathbb{E}_x \left[\|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) - \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x}^*)\|^2 \cdot \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})\|^2\right]^{1/2}$$
$$= \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) - \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x}^*)\| \cdot \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})\|_X$$
$$\leq \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) - \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x}^*)\|_{\mathrm{F}} \cdot \bar{\Theta}_X^{1/2}, \tag{24}$$

where $\bar{\Theta}_X^{1/2} := \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{x})\|_X$ is independent from $\boldsymbol{z}$.

Remark. *equation 24 used a computationally friendly Frobenius norm to bound the spectral norm in the line right above it. This is the main motivation to use a $\sqrt{o}$ scaling for hyper-parameter λ, as $\|\boldsymbol{A}\|_2 \leq \|\boldsymbol{A}\|_F \leq \sqrt{o}\|\boldsymbol{A}\|_2$ given $\boldsymbol{A}$ is full-rank $o \times |\boldsymbol{\theta}|$ and $o < |\boldsymbol{\theta}|$.*

Bring equation 24 and equation 21 back to equation 23 we have

$$|\Delta f_T(\boldsymbol{z}) - \Delta f_{t_s}(\boldsymbol{z})|$$
$$\leq \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) - \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x}^*)\|_{\mathrm{F}} \frac{\alpha \eta \bar{\Theta}_X^{1/2}}{\lambda_{max}} \left(e^{(T-t_s)L\lambda_{max}} - 1\right). \tag{25}$$

Finally, we bound the difference between $f_T(\boldsymbol{z})$ and $\hat{f}_T(\boldsymbol{z})$ via the triangle inequality.

First, observe that from A3,

$$\Delta f_{t_s}(\boldsymbol{z}) = \left\|\left(f_{t_s}(\boldsymbol{z}) - f_{t_s}(\boldsymbol{x}^*)\right) - \left(\hat{f}_{t_s}(\boldsymbol{z}) - \hat{f}_{t_s}(\boldsymbol{x}^*)\right)\right\|$$
$$\leq \left\|f_{t_s}(\boldsymbol{z}) - \hat{f}_{t_s}(\boldsymbol{z})\right\| + \left\|\hat{f}_{t_s}(\boldsymbol{x}^*) - f_{t_s}(\boldsymbol{x}^*)\right\|$$
$$\leq 2\alpha, \tag{26}$$

so that

$$\Delta f_T(\boldsymbol{z}) \leq |\Delta f_T(\boldsymbol{z}) - \Delta f_{t_s}(\boldsymbol{z})| + |\Delta f_{t_s}(\boldsymbol{z})|$$
$$\leq \|\nabla_{\boldsymbol{\theta}} f(\boldsymbol{z}) - \nabla_{\boldsymbol{\theta}} f(\boldsymbol{x}^*)\|_{\mathrm{F}} \frac{\alpha \eta \bar{\Theta}_X^{1/2}}{\lambda_{max}} \left(e^{(T-t_s)L\lambda_{max}} - 1\right) + 2\alpha. \tag{27}$$

Thus, given the convergence assumption $\|f_T(\boldsymbol{x}^*) - \hat{f}_T(\boldsymbol{x}^*)\| \leq \beta$ (A4),

$$\left\|f_T(\boldsymbol{z}) - \hat{f}_T(\boldsymbol{z})\right\|$$
$$= \left\|\left(f_T(\boldsymbol{z}) - f_T(\boldsymbol{x}^*)\right) - \left(\hat{f}_T(\boldsymbol{z}) - \hat{f}_T(\boldsymbol{x}^*)\right) - \left(\hat{f}_T(\boldsymbol{x}^*) - f_T(\boldsymbol{x}^*)\right)\right\|$$
$$\leq \Delta f_T(\boldsymbol{z}) + \beta. \tag{28}$$

To proceed, recall that $\boldsymbol{x}^*$ is chosen arbitrarily. This concludes the proof. $\square$

A.4 PROOF OF LEMMA 3.2

We prove the lemma under the weakly lazy regime, i.e., we allow the weak dependency of Θ_t on t. Let us define $|\Theta_T(\boldsymbol{z}, \boldsymbol{x})|$ as the unique symmetric positive semi-definite solution of $|\Theta_T(\boldsymbol{z}, \boldsymbol{x})|^2 = \Theta_T(\boldsymbol{z}, \boldsymbol{x})^\top \Theta_T(\boldsymbol{z}, \boldsymbol{x})$, which is an extension of absolute values to matrices.

Lemma A.3. *(Extension of Lemma 3.2) We assume the lazy learning regime, i.e., there exists $\delta > 0$ such that $\sup_{\boldsymbol{x}, \boldsymbol{x}'} \||\Theta_T(\boldsymbol{x}, \boldsymbol{x}')| - |\Theta_t(\boldsymbol{x}, \boldsymbol{x}')|\| \leq \delta$ holds for all $t_s \leq t \leq T$. Under assumption A1, with the model parameters $\boldsymbol{\theta}_T$ trained from $\boldsymbol{\theta}_{t_s}$ with equation 3 over the training set $\boldsymbol{x}$ and $t_s < T$, we have:*

$$\|\nabla_{\boldsymbol{\theta}} f_T(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})\| \leq C(\mathrm{Tr}\mathbb{E}_{\boldsymbol{x}}[|\Theta_T(\boldsymbol{z}, \boldsymbol{x})|] + o\delta) + \sqrt{\delta}\|\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s}\| \tag{29}$$

where C is a positive constant independent of $\boldsymbol{z}$.

Lemma 3.2 is obtained by setting $\delta = 0$.

Proof. The mean value theorem for integrals guarantees that there exists $\tau \in [t_s, T]$ such that

$$\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s} = -\int_{t_s}^{T} \eta \mathbb{E}_{\boldsymbol{x}} \left[\nabla_{\boldsymbol{\theta}} f_\tau(\boldsymbol{x}) \ell'(f_\tau(\boldsymbol{x})) \right] dt. \tag{30}$$

Then, Hölder's inequality leads to

$$\|\nabla_{\boldsymbol{\theta}} f_\tau(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})\| = \left\| \mathbb{E}_{\boldsymbol{x}} \left[\nabla_{\boldsymbol{\theta}} f_\tau(\boldsymbol{z}) \nabla_{\boldsymbol{\theta}} f_\tau(\boldsymbol{x})^\top \eta \int_{t_s}^{T} \ell'(f_\tau(\boldsymbol{x})) dt \right] \right\|$$

$$\leq \|\Theta_\tau(\boldsymbol{z}, \boldsymbol{x})\|_X^{(1)} \cdot \underbrace{\left\| \eta \int_{t_s}^{T} \ell'(f_\tau(\boldsymbol{x})) dt \right\|_X^{(\infty)}}_{\text{independent of } \boldsymbol{z}}. \tag{31}$$

The lazy learning assumption leads that

$$\|\Theta_\tau(\boldsymbol{z}, \boldsymbol{x})\|_X^{(1)} \leq \mathbb{E}_{\boldsymbol{x}} \left[\mathrm{Tr} \left(\Theta_\tau(\boldsymbol{z}, \boldsymbol{x})^\top \Theta_\tau(\boldsymbol{z}, \boldsymbol{x}) \right)^{1/2} \right]$$

$$\leq \mathbb{E}_{\boldsymbol{x}} \left[\mathrm{Tr} \left(|\Theta_\tau(\boldsymbol{z}, \boldsymbol{x})| \right) \right]$$

$$\leq \mathbb{E}_{\boldsymbol{x}} \left[\mathrm{Tr} \left(|\Theta_T(\boldsymbol{z}, \boldsymbol{x})| \right) \right] + o\delta$$

$$= \mathrm{Tr} \left(\mathbb{E}_{\boldsymbol{x}} \left[|\Theta_T(\boldsymbol{z}, \boldsymbol{x})| \right] \right) + o\delta.$$

Again the lazy learning assumption for $|\Theta_T(\boldsymbol{z}, \boldsymbol{z})| = \Theta_T(\boldsymbol{z}, \boldsymbol{z})$ ensures that

$$\|\nabla_{\boldsymbol{\theta}} f_\tau(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})\|^2 = (\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})^T \Theta_\tau(\boldsymbol{z}, \boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})$$

$$\geq (\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})^T (\Theta_T(\boldsymbol{z}, \boldsymbol{z}) - \delta \boldsymbol{I})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})$$

$$= \|\nabla_{\boldsymbol{\theta}} f_T(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})\|^2 - \delta \|\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s}\|^2.$$

Hence, we have

$$\|\nabla_{\boldsymbol{\theta}} f_T(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})\| \leq \sqrt{\|\nabla_{\boldsymbol{\theta}} f_\tau(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})\|^2 + \delta \|\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s}\|^2}$$

$$\leq \|\nabla_{\boldsymbol{\theta}} f_\tau(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})\| + \sqrt{\delta} \|\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s}\|.$$

Substituting the above inequalities into equation 31, we obtain the conclusion of the lemma. □

A.5 PROOF OF PROPOSITION 4.1

Proposition A.4. *(Proposition 4.1) Suppose that f^{emp} is γ-smooth w.r.t. $\boldsymbol{\theta}$, i.e.,*

$$\|\nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}) - \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}')\|_{\mathrm{F}} \leq \gamma \|\boldsymbol{\theta} - \boldsymbol{\theta}'\|.$$

Let $\mathbf{v}$ be a random variable such that $\mathbb{E}_{\mathbf{v}}[\mathbf{v}] = \mathbf{0}, \mathbb{E}_{\mathbf{v}}[\mathbf{v}\mathbf{v}^\top] = \epsilon^2 \boldsymbol{I}$ and $\mathbb{E}_{\mathbf{v}}[\|\mathbf{v}\|^k] \leq C_k \epsilon^k$ for $k = 3, 4$, where C_k is a constant depending on k and the dimension of $\mathbf{v}$. Then, under A1, it holds that

$$\lim_{\epsilon \to 0} \frac{1}{\epsilon^2} \mathbb{E}_{\mathbf{v}} \left[\|f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v}) - f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)\|^2 \right] = \mathrm{Tr} \left(\nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \boldsymbol{\Gamma}^2 \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \right). \tag{32}$$

Proof. For each component $f_i^{emp}, i = 1, \ldots, o$, the mean value theorem leads that there exists $t_i \in [0, 1]$ such that

$$|f_i^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v}) - f_i^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) - \nabla_{\boldsymbol{\theta}} f_i^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \boldsymbol{\Gamma}\mathbf{v}|$$

$$= |\nabla_{\boldsymbol{\theta}} f_i^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T + t_i \boldsymbol{\Gamma}\mathbf{v})^\top \boldsymbol{\Gamma}\mathbf{v} - \nabla_{\boldsymbol{\theta}} f_i^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \boldsymbol{\Gamma}\mathbf{v}|$$

$$\leq \gamma \|\boldsymbol{\Gamma}\|^2 \|\mathbf{v}\|^2.$$

For real numbers $a_i, b_i, i = 1, \ldots, o$, suppose $|a_i - b_i| \leq c$. Then, we have

$$\left| \sum_i a_i^2 - \sum_i b_i^2 \right| = \left| 2 \sum_i b_i(a_i - b_i) + \sum_i (a_i - b_i)^2 \right| \leq 2c \sum_i |b_i| + oc^2.$$

Using the above inequality, we obtain

$$\left| \mathbb{E}_{\mathbf{v}} \left[\| f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v}) - f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \|^2 \right] - \mathbb{E}_{\mathbf{v}} \left[\mathbf{v}^\top \boldsymbol{\Gamma} \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \boldsymbol{\Gamma}\mathbf{v} \right] \right|$$

$$\leq 2\gamma \|\boldsymbol{\Gamma}\|^2 \mathbb{E}_{\mathbf{v}} [\sum_i |\mathbf{v}^\top \boldsymbol{\Gamma} \nabla_{\boldsymbol{\theta}} f_i^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)| \|\mathbf{v}\|^2] + o\gamma^2 \|\boldsymbol{\Gamma}\|^4 \mathbb{E}_{\mathbf{v}}[\|\mathbf{v}\|^4]$$

$$\leq 2\sqrt{o}\gamma \|\boldsymbol{\Gamma}\|^3 \|\nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)\|_{\mathrm{F}} \mathbb{E}_{\mathbf{v}}[\|\mathbf{v}\|^3] + o\gamma^2 \|\boldsymbol{\Gamma}\|^4 \mathbb{E}_{\mathbf{v}}[\|\mathbf{v}\|^4]. \tag{33}$$

Note the cyclic trick for the trace ensures that

$$\mathbb{E}_{\mathbf{v}} \left[\mathbf{v}^\top \boldsymbol{\Gamma} \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \boldsymbol{\Gamma}\mathbf{v} \right]$$

$$= \mathbb{E}_{\mathbf{v}} \left[\mathrm{Tr} \left(\boldsymbol{\Gamma} \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \boldsymbol{\Gamma}\mathbf{v}\mathbf{v}^\top \right) \right]$$

$$= \mathrm{Tr} \left(\boldsymbol{\Gamma} \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \boldsymbol{\Gamma} \mathbb{E}_{\mathbf{v}} \left[\mathbf{v}\mathbf{v}^\top \right] \right)$$

$$= \mathrm{Tr} \left(\boldsymbol{\Gamma} \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \boldsymbol{\Gamma} \cdot \epsilon^2 \boldsymbol{I} \right) \tag{34}$$

$$= \epsilon^2 \mathrm{Tr} \left(\nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \boldsymbol{\Gamma}^2 \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \right). \tag{35}$$

In equation 34 we applied the condition that $\mathbb{E}_{\mathbf{v}}[\mathbf{v}\mathbf{v}^\top] = \epsilon^2 \boldsymbol{I}$. We note that this is a slightly modified version of the well-known Hutchinson's Trace Estimator. We refer the readers to the existing analysis of such estimators (Avron & Toledo, 2011) for more details. As a result, we obtain

$$\left| \lim_{\epsilon \to 0} \frac{1}{\epsilon^2} \mathbb{E}_{\mathbf{v}} \left[\| f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v}) - f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \|^2 \right] - \mathrm{Tr} \left(\nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \boldsymbol{\Gamma}^2 \nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)^\top \right) \right|$$

$$\leq \lim_{\epsilon \to 0} 2\sqrt{o}\gamma \|\boldsymbol{\Gamma}\|^3 \|\nabla_{\boldsymbol{\theta}} f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T)\|_{\mathrm{F}} C_3 \epsilon + o\gamma^2 \|\boldsymbol{\Gamma}\|^4 C_4 \epsilon^2$$

$$= 0.$$

The above equality means the conclusion of the proposition. $\qquad \square$

A.6 ADDITIONAL DERIVATIONS FOR SECTION 4.3

Under the distribution of $\mathbf{v}$ we have

$$\mathbb{E}_{\mathbf{v}}[f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v})] = f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T) + \underbrace{\mathbb{E}_{\mathbf{v}}[\nabla_{\theta} f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T)^T \boldsymbol{\Gamma}\mathbf{v}]}_{=0 \text{ from } \mathbb{E}_{\mathbf{v}}[\mathbf{v}]=0} + O(\mathbb{E}[\mathbf{v}^2])$$

$$= f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T) + O(\epsilon^2),$$

which indicates that $\mathbb{E}_{\mathbf{v}}[f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v})] \approx f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T)$ when ϵ is small.

We continue by the computation of $\mathrm{TrVar}[\widetilde{f}^{\mathrm{raw}}(\boldsymbol{z})]$:

$$\mathrm{TrVar}_{\mathbf{v}}[\widetilde{f}^{\mathrm{raw}}(\boldsymbol{z})] = \mathbb{E}_{\mathbf{v}}[\| f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v}) - \mathbb{E}_{\mathbf{v}}[f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v})] \|^2]$$

$$= \mathbb{E}_{\mathbf{v}}[\| f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v}) - f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T) + O(\epsilon^2) \|^2]$$

$$= \mathbb{E}_{\mathbf{v}}[\| f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T + \boldsymbol{\Gamma}\mathbf{v}) - f^{\mathrm{emp}}(\boldsymbol{z}; \boldsymbol{\theta}_T) \|^2] + O(\epsilon^4)$$

$$\approx \epsilon^2 \mathrm{Tr}\Theta(\boldsymbol{z}, \boldsymbol{z}) + O(\epsilon^4).$$

Let $\widetilde{\Theta}_{\mathrm{Tr}}(\boldsymbol{z}, \boldsymbol{z})$ be an approximation of $\epsilon^2 \mathrm{Tr}\,\Theta(\boldsymbol{z}, \boldsymbol{z})$, which is being computed empirically in line 11 of Alg. 1.

Thus, $\gamma^2 \mathrm{TrVar}_{\mathbf{v}}[\widetilde{f}^{\mathrm{raw}}(\boldsymbol{z})]$ reads:

$$\gamma^2 \mathrm{TrVar}_{\mathbf{v}}[\widetilde{f}^{\mathrm{raw}}(\boldsymbol{z})] = \frac{[\widetilde{\Theta}_{\mathrm{Tr}}(\boldsymbol{z}, \boldsymbol{z}) - \lambda D]_+}{\widetilde{\Theta}_{\mathrm{Tr}}(\boldsymbol{z}, \boldsymbol{z})} \mathrm{TrVar}_{\mathbf{v}}[\widetilde{f}^{\mathrm{raw}}(\boldsymbol{z})]$$

$$\approx \frac{[\widetilde{\Theta}_{\mathrm{Tr}}(\boldsymbol{z}, \boldsymbol{z}) - \lambda D]_+}{\widetilde{\Theta}_{\mathrm{Tr}}(\boldsymbol{z}, \boldsymbol{z})} (\widetilde{\Theta}_{\mathrm{Tr}}(\boldsymbol{z}, \boldsymbol{z}) + O(\epsilon^4))$$

$$\approx [\epsilon^2 \mathrm{Tr}\,\Theta(\boldsymbol{z}, \boldsymbol{z}) - \lambda D]_+ + O(\epsilon^4)$$

where $[\,\cdot\,]_+$ denotes $\max(\cdot, 0)$.

For D, from approximation equation 13 we have

$$D = \left\| f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T + \epsilon\delta\boldsymbol{\Gamma}(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s})) - f^{emp}(\boldsymbol{z}; \boldsymbol{\theta}_T) \right\|$$
$$\approx \epsilon\delta \left\| \nabla_{\boldsymbol{\theta}} f_T(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s}) \right\|.$$

As a result, we have

$$\gamma^2 \mathrm{Tr}\mathrm{Var}[\widetilde{f}^{\mathrm{raw}}(\boldsymbol{z})] \approx \left[\epsilon^2 \, \mathrm{Tr}\,\Theta(\boldsymbol{z}, \boldsymbol{z}) - \epsilon\delta \left\| \nabla_{\boldsymbol{\theta}} f_T(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s}) \right\| \right]_+.$$

Recall that equation 10 indicates that

$$\mathrm{Tr}(\mathrm{Var}_{\Delta f}[\hat{f}_T(\boldsymbol{z})]) \le \mathbb{E}_{\Delta f}[\|\hat{f}_T(\boldsymbol{z}) - f_T(\boldsymbol{z})\|^2],$$

and Prop. 4.1 shows that

$$\|f_T(\boldsymbol{z}) - \hat{f}_T(\boldsymbol{z})\| \lesssim \left[\mathrm{Tr}(\Theta(\boldsymbol{z}, \boldsymbol{z}) + \underbrace{\mathbb{E}_x[\Theta(\boldsymbol{x}, \boldsymbol{x})]}_{\text{Independent of } \boldsymbol{z}}) - 2K \left\| \nabla_{\boldsymbol{\theta}} f_T(\boldsymbol{z})(\boldsymbol{\theta}_T - \boldsymbol{\theta}_{t_s}) \right\| \right]^{1/2}.$$

B DETAILS OF EXPERIMENTAL SETUP

B.1 DATASET DESCRIPTIONS

An overview of all considered datasets is provided below. ID and OOD dataset setups are summarized in Table 3. Please refer to Zhang et al. (2023) for more details.

B.1.1 ID DATASETS

CIFAR-10 The CIFAR-10 training set (Krizhevsky, 2009) consists 60000 32×32 colored images, containing 10 classes of *airplane*, *automobile*, *bird*, *cat*, *deer*, *dog*, *frog*, *horse*, *ship* and *truck*. The test set originally contained 10000 images from the same classes, where we separated 1000 validation images and 9000 test images from the original test set following Zhang et al. (2023). The dataset and each split are even in classes.

CIFAR-100 CIFAR-100 (Krizhevsky, 2009) contains 60000 32×32 images sampled from 100 classes, covering a wider range of images beyond CIFAR-10. Similar to CIFAR-10, 1000 images are taken out from the ID test set, forming a validation set.

ImageNet-1K ImageNet-1K (Deng et al., 2009), also known as ILSVRC 2012, spans 1000 object classes and contains 1,281,167 training images, 50,000 validation images and 100,000 test images, each of size 224×224. In the OpenOOD setup, 45,000 validation images are used as ID test and 5,000 as ID validation.

ImageNet-200 ImageNet-200 (Zhang et al., 2023) is a 200-class subset of ImageNet-1K compiled in OpenOOD version 1.5, with 10,000 224×224 validation images.

B.1.2 SEMANTIC-SHIFT OOD DATASETS

Tiny-ImageNet Tiny-ImageNet (Le & Yang, 2015) has 100,000 images divided up into 200 classes, each with 500 training images, 50 validating images, and 50 test images. Compared to ImageNet-200, every image in Tiny-ImageNet is downsized to a 64×64 coloured image.

MNIST Modified National Institute of Standards and Technology database (Lecun et al., 1998) contains 60,000 training and 10,000 test images of handwritten digits. Each image is anti-aliased, normalized and centered to fit into a 28x28 pixel bounding box.

SVHN Street View House Number (Netzer et al., 2011) dataset contains house numbers that are captured on Google Street View, consisting of 73257 digits for training, and 26032 digits for testing. In our setup, we used the MNIST-like 32-by-32 format, centered around a single character.

Textures Describable Textures Dataset (Cimpoi et al., 2014) is a set of 47 categories of textures, collected from Google and Flickr via relevant search queries. It has 5640 images, 120 images for each category, where the sizes range between 300x300 and 640x640.

Places365 Places365 (Zhou et al., 2018) is a scene recognition dataset. The standard version is composed of 1.8 million train and 36000 validation images from 365 scene classes.

NINCO No ImageNet Class Objects (Bitterwolf et al., 2023) consists of 5879 samples from 64 OOD classes. These OOD classes were selected to have no categorical overlap with any classes of ImageNet-1K. Each sample was inspected individually by the authors to not contain ID objects.

SSB-Hard Semantic Shift Benchmark-Hard (Vaze et al., 2022) split contains 49,000 images across 980 categories of ImageNet-21K () that has a short total semantic distance.

iNaturalist The iNaturalist dataset (Van Horn et al., 2018) has 579,184 training and 95,986 validation images from 5,089 different species of plants and animals.

OpenImage-O OpenImage-O (Kuznetsova et al., 2020) is image-by-image filtered from the test set of OpenImage-V3, which has been collected from Flickr without a predefined list of class names or tags. In the OpenOOD setup, 1,763 images are picked out as validation OOD.

B.1.3 COVARIATE-SHIFT OOD DATASETS

Blur-ImageNet This blurred ImageNet dataset contains ImageNet images with a Gaussian blur of $\sigma = 2$. The same splits are used as in the above description in the ImageNet-1K section.

ImageNet-C ImageNet-C (Hendrycks & Dietterich, 2019) has 15 synthetic corruption types (such as noise, blur, pixelate) on the standard ImageNet-1K, each with 5 severities. In OpenOOD, 10,000 images are randomly sampled uniformly across the 75 combinations to form the test set.

ImageNet-R ImageNet-R (Hendrycks et al., 2021) contains 30,000 images of different renditions of 200 ImageNet classes, such as art, graphics, patterns, toys, and video games.

ImageNet-ES ImageNet-ES (Baek et al., 2024) consists of 202,000 photos of images from Tiny-ImageNet. Each image is displayed on screen with high fidelity and photographed in a controlled environment with different parameter settings. We only used the 64,000 photos in the test set.

B.2 HYPER-PARAMETERS

During our preliminary experiments, we found that the setup given in the main text ($\lambda = \sqrt{o}$, $\epsilon = 2$, $\delta = 2$) works consistently well across datasets. In this preliminary stage, we have only considered smaller datasets such as MNIST, CIFAR-10, SVHN, etc., as well as ImageNet-blur. During future developments, larger δ and λ show better performance on large-scale datasets, as we have included them in the hyper-parameter searching range of TULiP, whenever a validation set is available. We further extended the range of ϵ to improve the performance of TULiP for different network architectures and training setups.

B.2.1 GRID SEARCH

Table 4 lists the hyper-parameter search range for all considered methods on the validation set.

B.2.2 $\sqrt{o}$ SCALING OF λ

In practice, when the number of network output dimensions o varies, we found that a $\sqrt{o}$ scaling of λ works more consistently. This might be due to our choice of using the computational-friendly Frobenius norm in Theorem 3.1 instead of a tighter spectrum norm. It is further explained in the proof listed in Sec. A.3.

Table 3: ID, OOD and OOD-val dataset setups.

ID Dataset	near-OOD	far-OOD	near/far-OOD Validation	Cov-Shift OOD
CIFAR-10	CIFAR-100 Tiny-ImageNet	MNIST SVHN Textures Places365	Tiny-ImageNet	
CIFAR-100	CIFAR-10 Tiny-ImageNet	MNIST SVHN Textures Places365	Tiny-ImageNet	
ImageNet-1K ImageNet-200	SSB-Hard NINCO	iNaturalist Textures OpenImage-O	OpenImage-O	Blur-ImageNet ImageNet-C ImageNet-R ImageNet-ES

Table 4: Hyper-parameter (available at evaluation time) search ranges.

Method	Hyper-parameters
MC-Dropout	N/A
MDS	N/A
MLS	N/A
EBO	Temperature: $\{1\}$
ViM	Dimension: $\{256, 1000\}$
ASH	Percentile: $\{65, 70, 75, 80, 85, 90, 95\}$
ODIN	Temperature: $\{1, 10, 100, 1000\}$ Noise: $\{0.0014, 0.0028\}$
TULiP	δ: $\{2, 5, 8\}$, λ: $\{1, 3\} \cdot \sqrt{o}$ ϵ: $\{0.1, 0.5, 1.5, 2.0\}$

B.2.3 HARDWARE

Each of our experiments is conducted on a single-node machine using an NVIDIA A6000 GPU.

C ADDITIONAL EXPERIMENT RESULTS

C.1 DETAILED RESULTS

Following Zhang et al. (2023), we used the provided pre-trained weights from 3 training runs for the results reported for CIFAR-10, CIFAR-100 and ImageNet-200 ID datasets. For ImageNet-1K ID, 3 evaluation (OOD) runs on a single training run is reported. Results for each individual run, as well as each individual dataset, are listed in Table 5.

C.2 EFFECT OF LAYER-WISE SCALING

Layer-wise scaling is an essential component of TULiP. In this experiment, we conduct semantic-shift OOD detection on ImageNet-1K without layer-wise scaling. In particular, for networks with L layers and parameters of layer l denoted as $\boldsymbol{\theta}_l$, the scaling matrix $\boldsymbol{\Gamma}$ has been set to $(L^{-1} \sum_l 1/\sqrt{|\boldsymbol{\theta}_l|}) \cdot \boldsymbol{I}$, i.e., an averaged scaling is used for the entire network, identical across layers.

Table 6 compares the results of this experiment and the one reported in Table 1 and 2. It shows the effect of layer-wise scaling on TULiP. Intuitively, it helps to find an NTK that is more representative of the training process, reducing the gap between the linearized training trajectory and the true training trajectory. From an empirical aspect, our scaling is often approximately proportional to

Table 5: Detailed breakdown of TULiP's Semantic-shift OOD performance on individual datasets.

ID dataset	OOD dataset	Run 1 FPR95↓	Run 1 AUROC ↑	Run 2 FPR95↓	Run 2 AUROC ↑	Run 3 FPR95↓	Run 3 AUROC ↑
CIFAR-10	CIFAR-100	36.11	88.86	37.56	88.56	36.52	88.81
	Tiny-ImageNet	30.67	90.75	31.42	90.23	30.53	90.83
	Near OOD	33.39	89.81	34.49	89.39	33.53	89.82
	MNIST	13.83	96.80	14.76	96.44	17.07	95.16
	SVHN	23.02	91.75	21.30	93.06	20.59	93.17
	Textures	30.96	89.98	30.49	90.60	28.12	91.44
	Places365	29.31	91.49	31.11	90.69	32.68	90.09
	Far OOD	24.28	92.50	24.41	92.70	24.61	92.46
CIFAR-100	CIFAR-10	60.93	79.24	58.80	79.35	60.92	78.90
	Tiny-ImageNet	48.96	83.66	50.01	83.50	50.80	83.08
	Near OOD	54.94	81.45	54.41	81.43	55.86	80.99
	MNIST	57.83	79.36	47.88	84.45	53.82	80.74
	SVHN	58.82	79.49	58.68	80.42	63.07	77.94
	Textures	61.48	78.65	60.67	78.10	64.20	76.82
	Places365	56.41	80.21	57.51	79.66	57.68	79.69
	Far OOD	58.64	79.43	56.18	80.66	59.69	78.80
ImageNet-200	SSB-hard	65.87	80.86	66.20	80.89	65.39	80.91
	NINCO	43.94	86.68	42.48	86.85	43.14	86.84
	Near OOD	54.91	83.77	54.34	83.87	54.27	83.88
	iNaturalist	22.52	93.80	22.94	93.45	24.80	93.21
	Textures	45.00	89.53	43.20	89.80	44.02	89.67
	OpenImage-O	34.64	89.98	33.99	89.94	34.34	89.92
	Far OOD	34.06	91.10	33.38	91.06	34.39	90.93
ImageNet-1K	SSB-hard	74.09	73.16	73.99	73.37	74.12	73.14
	NINCO	55.92	81.83	55.75	81.82	55.89	81.81
	Near OOD	65.00	77.50	64.87	77.59	65.01	77.48
	iNaturalist	37.89	91.01	38.08	90.98	37.94	91.01
	Textures	59.02	85.34	59.15	85.29	59.01	85.34
	OpenImage-O	47.10	87.77	46.87	87.76	47.08	87.76
	Far OOD	48.00	88.04	48.03	88.01	48.01	88.04

Table 6: OOD detection results (AUROC ↑) for TULiP without layer-wise scaling (w/o LW). TULiP results are copied from Table 1.

Method	CIFAR-10	CIFAR-100	ImNet-200	ImNet-1K	ImNet-Blur	ImNet-C	ImNet-R
TULiP	89.67/92.55	**81.29/79.63**	**83.84/91.03**	**77.52/88.03**	**85.54**	82.91	82.07
w/o LW	**90.68/92.81**	80.47/77.90	81.54/86.75	76.32/84.99	76.86	**83.76**	**85.30**

Table 7: ImageNet-1K OOD AUROC score using the V2 weights from *torchvision*.

	MLS	ODIN	ViM	ASH	TULiP (Ours)
SSB-Hard	65.53	69.03	57.93	40.52	67.57
NINCO	72.96	70.81	72.42	31.39	74.90
Near OOD	69.24	69.92	65.17	35.96	**71.23**
iNaturalist	80.34	67.19	92.32	28.64	81.62
Textures	71.42	62.95	95.04	34.97	70.20
OpenImage-O	77.66	68.22	89.89	26.13	79.02
Far OOD	76.47	66.12	**92.42**	29.91	76.95

the magnitude of individual parameters within the layer (cf. Fig. 1 a) of the main paper). In this sense, a larger perturbation may significantly interfere with the network performance, thus producing unpredictable results. Our Layer-wise scaling scheme also reduces such vulnerability by applying smaller perturbations to layers with smaller weights. Nevertheless, TULiP without layer-wise scaling still outperforms TULiP in some datasets, suggesting future work for an in-depth analysis.

C.3 V2 WEIGHTS ON IMAGENET-1K

Recently, researchers have been finding the possibilities to extend the performance of existing models such as ResNet-50 on various datasets. For example, *torchvision* (maintainers & contributors, 2016) released a new version (V2) of a ResNet-50 trained on ImageNet-1K with recent advances in practical NN training, increasing the Top-1 accuracy by 4.7% (Vryniotis, 2021). The previous version (V1) is used in OpenOOD v1.5 for ImageNet-1K ID and ResNet-50 backbone (Zhang et al., 2023).

Somewhat surprisingly, the performance of all OOD detectors are severely undermined when using the new V2 weights. We summarize our empirical findings in Table 7. Upon further inspection, we have empirically found that in general, V2 weight is larger than V1, especially the γ, β parameters in BatchNorm layers (Ioffe & Szegedy, 2015) have been increased around $10\times$. This results in a significantly larger $\|\nabla_\theta f(\boldsymbol{x})\|$. As a consequence, the network is more vulnerable to weight perturbations and thus favors a much smaller ϵ. In particular, the results in Table 7 were produced with a perturb power of $\epsilon = 0.1$ (chosen with respect to the validation set). Such phenomena further demonstrate the significant effect of ϵ to TULiP. It hints at an important future research direction that aims to tackle such sensitivity.

C.4 ADDITIONAL EXPERIMENT FOR OUTLIER REJECTION

Following the established protocols (Krishnan & Tickoo, 2020; Thiagarajan et al., 2022), we conduct OOD detection experiments with ImageNet-1K as inliers and images with Gaussian blur of intensity 5 from ImageNet-C (Hendrycks & Dietterich, 2019) as outliers. For TULiP, we used the hyper-parameters suggested in Sec. 5 as there are no validation sets in this experiment.

Additional Baselines Thiagarajan et al. (2022) proposed Δ-UQ, a method for Uncertainty Quantification that utilizes training data as anchors to create network ensembles, where each instance uses a different anchor. SVI (Blundell et al., 2015b), stands for stochastic variational inference, is a Bayesian UQ method utilizing variational inference. Temperature Scaling (Guo et al., 2017b) is a simple post-hoc UQ method that scales the logits before the softmax layer to estimate prediction uncertainty.

In Table 8, we report our results with baseline results copied from Thiagarajan et al. (2022). It is worth noting that in this experiment, TULiP, despite being a post-hoc method, outperforms many

Table 8: Outlier rejection results with ImageNet-C Gaussian Blur intensity 5. Baseline results are copied from (Thiagarajan et al., 2022). † represents training data access.

Method		AUROC ↑	AUPR-in/out ↑
(Lakshminarayanan et al., 2017)	Deep Ensembles †	95.49	95.31 / 95.64
(Gal & Ghahramani, 2016)	MC Dropout †	96.38	96.16 / 96.67
(Blundell et al., 2015b)	SVI †	96.40	95.97 / 96.83
(Thiagarajan et al., 2022)	Δ-UQ †	**97.49**	**97.56 / 97.47**
(He et al., 2016)	ResNet-50	93.36	92.82 / 93.71
(Guo et al., 2017b)	Temperature Scaling	93.71	93.21 / 94.01
(ours)	TULiP	**96.40**	**96.58 / 96.32**

UQ methods that would require significantly more computational resources (e.g., Deep Ensembles, MC Dropout, etc.). It is on par with SVI and being outperformed by Δ-UQ, which is a much heavier method that relies on network architecture modifications before training (thus requires training the network from stretch) and domain-specific data augmentations.