Concatenated Matrix SVD: Compression Bounds, Incremental Approximation, and Error-Constrained Clustering

Abstract

Large collections of matrices arise throughout modern machine learning, signal processing, and scientific computing, where they are commonly compressed by concatenation followed by truncated singular value decomposition (SVD). This strategy enables parameter sharing and efficient reconstruction and has been widely adopted across domains ranging from multi-view learning and signal processing to neural network compression. However, it leaves a fundamental question unanswered: *which matrices can be safely concatenated and compressed together under explicit reconstruction error constraints?* Existing approaches rely on heuristic or architecture-specific grouping and provide no principled guarantees on the resulting SVD approximation error. In the present work, we introduce a theory-driven framework for *compression-aware clustering* of matrices under SVD compression constraints. Our analysis establishes new spectral bounds for horizontally concatenated matrices, deriving global upper bounds on the optimal rank-r SVD reconstruction error from lower bounds on singular value growth. The first bound follows from Weyl-type monotonicity under blockwise extensions, while the second leverages singular values of incremental residuals to yield tighter, per-block guarantees. We further develop an efficient approximate estimator based on incremental truncated SVD that tracks dominant singular values without forming the full concatenated matrix. Therefore, we propose three clustering algorithms that merge matrices only when their predicted joint SVD compression error remains below a user-specified threshold. The algorithms span a trade-off between speed, provable accuracy, and scalability, enabling compression-aware clustering with explicit error control.[1]

1 Introduction

Large collections of matrices naturally arise in a wide range of applications, including multi-view representation learning, temporal aggregation of features, scientific simulations, neural network activations, and model parameter compression. A common and effective strategy for compressing such data is to horizontally concatenate matrices (or matrix-shaped tensors) and apply a truncated Singular Value Decomposition (SVD) to the resulting large matrix (Andrews & Patterson, 1976; Sun, 2013; Sarwar et al., 2000; Jolliffe, 2002). This approach yields a single low-rank factorization that enables parameter sharing, compact representation, and direct reconstruction of the original blocks. Compared to tensor decomposition methods such as Tucker or higher-order SVD (HOSVD) (Tucker, 1966; De Lathauwer et al., 2000b;a; Kolda & Bader, 2009), matrix-based concatenation followed by SVD offers several practical advantages. It produces a single latent basis shared across all blocks, avoids multilinear contractions at reconstruction time, and integrates naturally with pipelines that operate on matrix-valued embeddings or linear transformations. As a result, concatenated SVD has become a standard tool in domains ranging from signal processing to modern large-scale representation learning.

Despite its widespread use, a fundamental problem remains unresolved. Given a large collection of matrices, *how can we efficiently determine which subsets should be concatenated and compressed together so that their joint low-rank approximation error remains below a prescribed tolerance?* In practice, existing compression

---

pipelines rely on heuristic grouping strategies, architectural constraints, or domain-specific assumptions to decide which matrices share a low-rank basis (Wang et al., 2025b; Lu et al., 2025; Li et al., 2025). Such approaches provide no explicit control over the resulting SVD reconstruction error and offer no guarantees that merging additional matrices will not violate accuracy requirements. At a high level, the difficulty stems from the fact that concatenating matrices fundamentally alters the spectrum of the resulting matrix. While individual blocks may admit accurate low-rank approximations, their concatenation can increase effective rank and degrade approximation quality. Determining whether two or more matrices can safely share a low-rank representation therefore requires understanding how the singular values of the concatenated matrix evolve as new blocks are appended. This is inherently a spectral question and cannot be addressed by distance-based clustering or purely geometric similarity measures, as used in classical clustering methods.

In this work, we introduce the first theoretically grounded and computationally efficient framework for *compression-aware clustering* of matrices under explicit SVD reconstruction constraints. Our approach is based on new spectral bounds that characterize how singular values evolve under horizontal concatenation. Specifically, we derive two lower bounds on the singular values of concatenated matrices using classical matrix perturbation theory. The first bound follows from Weyl-type monotonicity under blockwise extensions (Weyl, 1912; Stewart & Sun, 1990), providing conservative but fast guarantees. The second, sharper bound exploits the singular values of incremental residuals, capturing the orthogonal contribution of each appended block and yielding tighter per-block estimates. Leveraging these spectral lower bounds, we derive corresponding global upper bounds on the optimal rank-r SVD reconstruction error of the concatenated matrix. These bounds are exact in the non-truncated case and remain tight in practice under truncation. To enable scalability, we further develop an efficient approximate estimator based on incremental truncated SVD. This estimator maintains approximate dominant singular values as blocks are appended, drawing on ideas from incremental PCA and SVD (Hall et al., 1998; Levy & Lindenbaum, 1998; Brand, 2002) and randomized low-rank approximation (Halko et al., 2011; Tropp et al., 2017), while avoiding construction of the full concatenated matrix. Importantly, we do not claim a new incremental SVD algorithm, rather, we show how incremental singular value estimation can be repurposed as a decision-making primitive for compression-aware clustering under explicit error budgets.

Building on these theoretical results, we design three clustering algorithms that explicitly enforce SVD compression constraints. The first is a fast method based on Weyl-monotone bounds. The second provides provable reconstruction accuracy using residual-based spectral bounds. The third is a scalable approximate method that employs incremental truncated SVD to balance efficiency and approximation quality. All three algorithms merge matrices only when the predicted SVD reconstruction error of their concatenation lies below a user-specified threshold, thereby providing explicit and interpretable accuracy control.

In summary, this work establishes concatenation-aware SVD compression as a principled foundation for clustering and compressing large collections of matrices. By unifying spectral perturbation theory, incremental singular value estimation, and compression-driven clustering, we provide both theoretical guarantees and practical algorithms.

2   Related Work

SVD-based compression of matrix collections.   Applying truncated singular value decomposition (SVD) to a matrix obtained by horizontally concatenating multiple blocks is a widely used technique in signal processing, computer vision, scientific computing, and representation learning. This strategy provides a simple and effective compression mechanism based on a single low-rank factorization, enabling direct reconstruction of the original matrices without higher-order tensor contractions or complex decoding procedures (Jolliffe, 2002; Halko et al., 2011).

Concatenated SVD has been successfully applied across a broad range of domains. In large language models, joint SVD of concatenated weight matrices has been used to share low-rank projections across attention components, layers, or experts, enabling parameter reduction while preserving accuracy. Representative examples include unified QKV decompositions (Wang et al., 2025b), intra-layer shared projections (Lu et al., 2025), cross-layer parameter sharing (Wang et al., 2025a), and expert merging in mixture-of-experts architectures (Li et al., 2025; Chaichana et al., 2025). In these settings, concatenation is typically guided

by architectural structure (e.g., matrices belonging to the same layer or module) or semantic similarity (e.g., adjacent layers or related experts). Related ideas also appear in wireless signal processing, where concatenated SVD is used to design shared precoders across frequency bands (Zhang et al., 2016), as well as in neuroscience and genomics, where large collections of measurements are concatenated to obtain global low-dimensional representations across sessions, experimental conditions, or chromosomes (Nietz et al., 2023; Zhou et al., 2025). Across these application areas, concatenated SVD serves as a powerful tool for extracting shared structure from collections of matrices.

Despite its empirical success, existing uses of concatenated SVD rely on *predefined or heuristic grouping* of matrices. The decision of which matrices should share a low-rank basis is typically made manually based on domain knowledge, architectural constraints, or simple similarity measures. Crucially, these approaches do not provide a principled mechanism for determining *which subsets of matrices should be concatenated* in order to satisfy a prescribed reconstruction error or compression target. As a result, the quality of compression depends heavily on ad hoc design choices, and there are no guarantees that merging additional matrices will not violate reconstruction constraints. In contrast, the present work formulates matrix grouping as a *compression-driven clustering problem*. Rather than clustering matrices based on ambient-space distances or semantic heuristics, cluster formation is governed directly by predicted low-rank approximation error of the concatenated matrix. This enables principled selection of matrix groups under explicit reconstruction error budgets.

Incremental low-rank approximation. Incremental estimation of dominant singular values and singular subspaces has a long history in numerical linear algebra and machine learning. Early work on incremental principal component analysis and online SVD (Hall et al., 1998; Levy & Lindenbaum, 1998) describes how to update covariance eigenbases as new samples arrive. Brand's incremental SVD algorithms (Brand, 2002; 2006) extend these ideas to rank-one and block updates of the thin SVD, directly covering the case of appending new columns, which is equivalent to horizontal concatenation. Streaming PCA and subspace tracking methods (Warmuth & Kuzmin, 2008; Mitliagkas et al., 2013) maintain approximate dominant invariant subspaces under stochastic or adversarial updates. Randomized low-rank approximation techniques (Halko et al., 2011; Woodruff, 2014) further improve scalability by maintaining approximate bases via random projections and periodic truncation.

The incremental truncated SVD estimator used in this work follows a classical design pattern and does not constitute a new SVD algorithm. Its update mechanism is equivalent to well-known incremental PCA and block-update SVD methods. The novelty of this work lies instead in how such estimators are used: we connect incremental singular value tracking to *explicit reconstruction-error control for concatenated matrices*, and embed it into clustering procedures whose merge decisions are driven directly by predicted low-rank approximation error. To our knowledge, existing incremental SVD and streaming PCA methods are not used to guide clustering or grouping under explicit SVD compression constraints.

3 Problem Formulation

Consider a collection of real matrices

$$\mathcal{A} = \{A_i\}_{i=1}^N, \qquad A_i \in \mathbb{R}^{m \times n_i}, \tag{1}$$

that must be stored and manipulated under a limited memory. Our goal consists of replacing the original matrices by compressed surrogates $\{\widehat{A}_i\}_{i=1}^N$ that preserve essential structure while employing as few real numbers as possible.

We measure fidelity by using the Frobenius norm

$$\mathcal{L}(\widehat{\mathcal{A}}, \mathcal{A}) = \left(\sum_{i=1}^N \|A_i - \widehat{A}_i(\Theta)\|_F^2 \right)^{1/2},$$

where a collection of real values Θ is parameterizing the compressed representation. Let $\mathrm{mem}(\Theta)$ denote the number of real values required to store Θ. The *error-constrained memory minimization* principle reads as

$$\min_{\Theta} \ \mathrm{mem}(\Theta) \quad \text{s.t.} \quad \mathcal{L}(\widehat{\mathcal{A}}, \mathcal{A}) \leq \varepsilon, \tag{2}$$

where $\varepsilon > 0$ prescribes the maximal admissible distortion.

Compressing each matrix independently ignores potential *redundancy across the collection*. We assume that many matrices possess similar column spaces, which enables their joint representation via a shared low-rank basis. This motivates clustering followed by a joint factorization.

Recall that $A_i \in \mathbb{R}^{m \times n_i}$ for $i = 1, \ldots, N$, and let $\Pi = \{C_1, \ldots, C_K\}$ be a partition of this index set. For each cluster $C_c \in \Pi$, consider the concatenated matrix

$$M_c = [A_i]_{i \in C_c} \in \mathbb{R}^{m \times N_c}, \qquad \text{where} \quad N_c = \sum_{i \in C_c} n_i.$$

For each cluster C_c, let r_c denote the target rank. We compute a rank-r_c truncated SVD of M_c,

$$M_c \approx U_c S_c V_c^\top,$$

where $U_c \in \mathbb{R}^{m \times r_c}$ and $V_c \in \mathbb{R}^{N_c \times r_c}$ have orthonormal columns, and $S_c \in \mathbb{R}^{r_c \times r_c}$ contains the leading singular values. This provides a low-rank representation of the concatenated matrix M_c. Since the diagonal matrix S_c can be absorbed into either factor of the decomposition, we keep only two matrices per cluster,

$$\widetilde{U}_c = U_c S_c \in \mathbb{R}^{m \times r_c}, \qquad V_c \in \mathbb{R}^{N_c \times r_c}.$$

This reduces storage while preserving a rank-r_c representation. The memory footprint for cluster C_c is therefore

$$\mathrm{mem}_c = r_c(m + N_c),$$

consisting of mr_c entries for $\widetilde{U}_c$ and $N_c r_c$ for V_c.

To reconstruct an approximation of each original matrix A_i, we split V_c column-wise according to the block dimensions n_i. If $V_{c,i} \in \mathbb{R}^{n_i \times r_c}$ denotes the submatrix corresponding to A_i, then the recovered approximation is given by

$$\widehat{A}_i = \widetilde{U}_c V_{c,i}^\top, \qquad i \in C_c.$$

Thus each A_i is represented using only the shared left basis $\widetilde{U}_c$ and its cluster-specific coefficient block $V_{c,i}$.

Because the rank-r_c truncated SVD is the optimal Frobenius norm approximation of M_c by the Eckart-Young-Mirsky theorem (see Appendix A for the preliminaries), the approximation error for cluster C_c is precisely the energy in the discarded singular values:

$$\mathcal{L}_c = \left(\sum_{i \in C_c} \|A_i - \widehat{A}_i\|_F^2 \right)^{1/2} = \left(\sum_{j > r_c} \sigma_j^2(M_c) \right)^{1/2},$$

where $\sigma_j(M_c)$ denotes the j-th largest singular value of M_c, with singular values ordered non-increasingly.

The error-constrained memory minimization problem under cluster–concatenate–SVD representation with two stored matrices per cluster reads as

$$\min_{\Pi, \{r_c\}} \ \sum_{c=1}^{K} r_c \, (m + N_c) \quad \text{s.t.} \quad \left(\sum_{c=1}^{K} \sum_{j > r_c} \sigma_j^2(M_c) \right)^{1/2} \leq \varepsilon, \tag{3}$$

where $\Pi = \{C_1, \ldots, C_K\}$ is a partition of $\{1, \ldots, N\}$, r_c is the rank assigned to cluster C_c, m is the row dimension of all matrices, N_c is the total number of columns in cluster C_c, and $\varepsilon > 0$ is the user-specified reconstruction tolerance controlling the achievable trade-off between accuracy and compression.

This formulation explicitly balances *storage per cluster* and *approximation error*. Adjusting ε or the cluster-wise ranks r_c tunes the balance between memory footprint and approximation quality.

Why not optimize equation 3 directly? While the formulation in equation 3 is compact and conceptually appealing, it is important to clarify why our approach does *not* attempt to solve it directly. The difficulty is twofold. First, the optimization over the partition Π is inherently *combinatorial*. Even for fixed ranks $\{r_c\}$, determining an optimal clustering that minimizes the aggregate spectral tail $\sum_c \sum_{j>r_c} \sigma_j^2(M_c)$ subsumes hard partitioning problems and is NP-hard in general. Thus, global optimization over Π is computationally intractable beyond very small instances. Second, even evaluating the objective is expensive. For a candidate cluster C_c, computing $\sigma_j(M_c)$ requires forming the concatenated matrix and performing at least a partial SVD, which scales with the total column dimension N_c. Embedding such spectral computations inside a combinatorial search over partitions is prohibitive in both time and memory.

For these reasons, our goal is not global optimality of equation 3, but rather the design of *provably safe local decisions* that guarantee feasibility of the error constraint. This perspective naturally leads to greedy clustering strategies driven by certified merge rules, rather than direct optimization. The key algorithmic primitive underlying our method is a *merge certificate* that allows one to decide whether two groups of matrices can be safely merged *without explicitly computing* the singular values of the concatenated matrix.

Definition 1 (Compression-aware merge certificate). *Let $M = [M_1, M_2]$ denote the concatenation of two matrices. A compression-aware merge certificate is a computable condition $\mathcal{C}(M_1, M_2, r, \varepsilon)$ such that*

$$\mathcal{C}(M_1, M_2, r, \varepsilon) \implies \mathcal{E}_r(M) = \left(\sum_{j>r} \sigma_j^2(M) \right)^{1/2} \leq \varepsilon,$$

without explicitly computing the singular values $\{\sigma_j(M)\}$.

Such certificates enable greedy clustering schemes in which clusters are merged only when the resulting approximation error is *provably admissible*. Importantly, this shifts the computational burden from repeated large-scale SVDs to inexpensive spectral surrogates and bounds. This philosophy mirrors *safe screening rules* in sparse optimization, where variables are eliminated or grouped based on certificates that preserve optimality or feasibility, without solving the full problem (Ghaoui et al., 2010; Fercoq et al., 2015).

4 Methodology

We now develop our compression-aware clustering methodology. We begin with a very fast but coarse upper bound on the SVD compression error for concatenated matrices, derived from the Weyl monotonicity, and use it to construct a fast clustering algorithm. In the following subsections we refine this bound using the residuals and incremental SVD.

4.1 Weyl-Based Upper Bound for Concatenated SVD Compression

Our first result provides a simple *global* upper bound on the optimal rank-r SVD compression error of a concatenated matrix in terms of the individual blocks. It relies only on the Frobenius norms and the leading singular values of the blocks and is therefore extremely cheap to evaluate. See the proof in Appendix C.1.

Theorem 1 (Upper bound for SVD compression of a concatenated matrix). *Let $A_j \in \mathbb{R}^{m \times n_j}$ for $j = 1, \ldots, K$ and set*

$$M = \begin{bmatrix} A_1 & A_2 & \cdots & A_K \end{bmatrix} \in \mathbb{R}^{m \times (n_1 + \cdots + n_K)}.$$

Denote by $\sigma_1(\cdot) \geq \sigma_2(\cdot) \geq \cdots$ the singular values of a matrix, and define the optimal rank-r approximation error in the Frobenius norm by

$$\mathcal{E}_r^2(M) := \min_{\mathrm{rank}(X) \leq r} \|M - X\|_F^2 = \sum_{i>r} \sigma_i^2(M).$$

Then, for every $r \geq 1$,

$$\mathcal{E}_r^2(M) \leq \sum_{j=1}^{K} \|A_j\|_F^2 - \max_{1 \leq j \leq K} \sum_{i \leq r} \sigma_i^2(A_j). \tag{4}$$

In particular, if $r \geq \max_{1 \leq j \leq K} \mathrm{rank}(A_j)$, then

$$\mathcal{E}_r^2(M) \ \leq \ \sum_{j=1}^{K} \|A_j\|_F^2 \ - \ \max_{1 \leq j \leq K} \ \|A_j\|_F^2.$$

Remark 1 (Single-anchor nature of the Weyl-based bound)**.** *The Weyl-based upper bound in Theorem 1 relies on a* single anchor block *through the term*

$$\max_j \sum_{i \leq r} \sigma_i^2(A_j),$$

and therefore cannot accumulate shared low-rank structure across multiple blocks. As a consequence, when compression arises from collective subspace alignment rather than dominance of a single matrix, the bound may substantially overestimate the true rank-r approximation error. This explains the conservative behavior of the max-norm clustering algorithm observed in Section 5. A concrete example illustrating worst-case looseness is given in Appendix D.1.

Interpretation for clustering.   For any subset of indices $C \subseteq \{1, \ldots, K\}$, let

$$M_C := [A_j]_{j \in C}$$

denote the concatenation of matrices in that cluster. Applying Theorem 1 to M_C yields

$$\mathcal{E}_r^2(M_C) \ \leq \ \sum_{j \in C} \|A_j\|_F^2 \ - \ \max_{j \in C} \sum_{i=1}^{r} \sigma_i^2(A_j).$$

In the common regime where r is at least the rank of each block in the cluster (or large enough to recover each block essentially exactly when compressed alone), this simplifies to

$$\mathcal{E}_r^2(M_C) \ \leq \ \sum_{j \in C} \|A_j\|_F^2 \ - \ \max_{j \in C} \|A_j\|_F^2 \ = \ \sum_{j \in C \setminus \{j^\star\}} \|A_j\|_F^2,$$

where $j^\star$ is any index achieving the maximum Frobenius norm in the cluster. Thus, under this condition, the compression error of the concatenated cluster is bounded by the *sum of squared Frobenius norms of all blocks except the dominant one*. Intuitively, one large "anchor" matrix can absorb several smaller matrices at negligible additional error, as long as their total energy remains small.

This observation suggests a simple greedy strategy: for a given error tolerance $\varepsilon > 0$, we may form clusters by (i) selecting a high-energy block as an anchor, and (ii) attaching the lowest-energy remaining matrices as long as the sum of their squared norms does not exceed ε^2. For the details about the algorithm see Appendix E.1.

4.2   Residual-Based Global Bounds and Clustering

The Weyl-based bound in Section 4.1 depends only on individual blocks and is extremely fast to compute, but can be loose when the target rank r exceeds the rank of each block. We now derive a sharper global bound based on the singular values of *incremental residuals*. This bound captures how each block contributes new directions beyond the span of all previously seen blocks. See the proof in Appendix C.2.

Theorem 2 (Global incremental lower bound on singular values)**.** *Let*

$$M_K = \begin{bmatrix} A_1 & A_2 & \cdots & A_K \end{bmatrix} \in \mathbb{R}^{m \times (n_1 + \cdots + n_K)}$$

be constructed incrementally from block matrices $A_i \in \mathbb{R}^{m \times n_i}$. Define $M_0 := 0$ and let Q_{i-1} be any matrix with orthonormal columns spanning $\mathrm{range}(M_{i-1})$. For each block A_i, define its orthogonal residual

$$R_i := (I - Q_{i-1}Q_{i-1}^\top)A_i.$$

Let $\widehat{R} \in \mathbb{R}^{m \times (n_1 + \cdots + n_K)}$ be the block concatenation of all residuals,

$$\widehat{R} := \begin{bmatrix} R_1 & R_2 & \cdots & R_K \end{bmatrix},$$

and let $\mu_1 \geq \mu_2 \geq \cdots \geq 0$ denote the singular values of $\widehat{R}$ (in non-increasing order, extended by zeros when necessary).

Then, for every $j \geq 1$,

$$\sigma_j(M_K) \geq \mu_j.$$

In particular, as new blocks are added, the sequence of lower bounds $\{\mu_j\}_{j \geq 1}$ is monotone non-decreasing and incorporates the contributions of all residual components discovered during the incremental construction.

This theorem says that the singular values of the concatenated matrix M_K are bounded from below by the singular values of the concatenated residuals $\widehat{R}$. Intuitively, every time a block contributes a component outside the span of all previously seen blocks, this "new direction" permanently lifts the spectrum of M_K. See the proof of the following corollary in Appendix C.3.

Corollary 1 (Global upper bound on optimal SVD compression error). *In the setting of Theorem 2, let M_K and μ_j be as above. For any target rank $r \geq 0$, define the optimal rank-r SVD compression error of M_K in the Frobenius norm by*

$$\mathcal{E}_r(M_K) := \min_{\text{rank}(X) \leq r} \|M_K - X\|_F = \left(\sum_{j > r} \sigma_j(M_K)^2 \right)^{1/2},$$

where $\sigma_1(M_K) \geq \sigma_2(M_K) \geq \cdots \geq 0$ are the singular values of M_K.

Then, for every $r \geq 0$,

$$\mathcal{E}_r^2(M_K) \leq \sum_{i=1}^{K} \|A_i\|_F^2 - \sum_{j=1}^{r} \mu_j^2. \tag{5}$$

In particular, as new blocks A_i are added and $\widehat{R}$ accumulates more residual components, the quantity

$$\sum_{i=1}^{K} \|A_i\|_F^2 - \sum_{j=1}^{r} \mu_j^2$$

provides a global, monotonically decreasing upper bound on the best achievable rank-r approximation error for M_K, computable from the per-block Frobenius norms and the singular values (or estimates) of $\widehat{R}$.

To clarify when the residual-based bound of the Corollary 1 is exact, informative, or potentially conservative, we characterize its behavior under different structural regimes of the concatenated blocks in Appendix D.2.

Remark 2 (Near-tightness under weak subspace overlap). *The residual-based bound of Corollary 1 becomes informative whenever each appended block contributes a non-negligible component outside the span of previously concatenated matrices. In such regimes, the leading singular values of the residual concatenation $\widehat{R}$ closely track those of the full matrix M_K, and the resulting upper bound on the truncated SVD error is empirically tight.*

Conversely, when newly appended blocks lie largely within an already spanned subspace, residual energies are small and the bound may become conservative. This behavior reflects a fundamental limitation of worst-case guarantees based solely on subspace innovation and is intrinsic to concatenation-aware compression.

Interpretation for clustering. For a cluster $C \subseteq \{1, \ldots, K\}$, let $M_C := [A_j]_{j \in C}$ denote its concatenated matrix and construct residuals R_j incrementally as the blocks in C are appended. Let $\mu_1(M_C) \geq \cdots \geq \mu_r(M_C)$ be the leading r singular values of the corresponding residual concatenation $\widehat{R}_C$. Corollary 1 implies

$$\mathcal{E}_r^2(M_C) \leq \sum_{j \in C} \|A_j\|_F^2 - \sum_{i=1}^{r} \mu_i^2(M_C).$$

Compared to the Weyl-based bound (Section 4.1), this residual-based bound incorporates *all* new directions discovered as the cluster grows, not just the energy of the largest block. It is therefore strictly tighter whenever multiple blocks contribute nontrivial orthogonal components. For the details refer to Appendix E.2.

4.3 Approximate Compression Bound via Incremental Truncated SVD

The residual-based bound of Section 4.2 yields a provable upper bound on the optimal rank-r compression error, but it only adds singular values of new directions without updating the singular values of the old ones. To obtain a more tight approximation, we maintain an orthonormal basis Q_t for the approximate dominant left singular subspace of $M_t = [A_1, \ldots, A_t]$, together with a small Gram matrix S_t whose eigenvalues track the dominant singular values. See Appendix B for more details.

Using these approximate singular values, we define a plug-in estimator of the SVD compression error. See the proof of the following corollary in Appendix C.4.

Corollary 2 (Plug-in estimator of SVD compression error from incremental singular values)**.** *Let*

$$M_K = \begin{bmatrix} A_1 & A_2 & \cdots & A_K \end{bmatrix} \in \mathbb{R}^{m \times (n_1 + \cdots + n_K)},$$

and define the total Frobenius energy of M_K by

$$\|M_K\|_F^2 = \sum_{i=1}^{K} \|A_i\|_F^2.$$

Let $\widetilde{\sigma}_1(M_K) \geq \widetilde{\sigma}_2(M_K) \geq \cdots \geq 0$ denote the approximate singular values produced by the truncated incremental scheme, i.e. the square roots of the retained eigenvalues of the Gram matrix in the compressed basis.

For any target rank $r \geq 0$, define the optimal rank-r SVD compression error

$$\mathcal{E}_r(M_K) := \min_{\operatorname{rank}(X) \leq r} \|M_K - X\|_F = \left(\sum_{j > r} \sigma_j^2(M_K) \right)^{1/2},$$

where $\sigma_1(M_K) \geq \sigma_2(M_K) \geq \cdots \geq 0$ are the true singular values of M_K. Then the quantity

$$\widetilde{\mathcal{E}}_r(M_K) := \left(\sum_{i=1}^{K} \|A_i\|_F^2 - \sum_{j=1}^{r} \widetilde{\sigma}_j^2(M_K) \right)^{1/2}$$

is a natural plug-in estimator of $\mathcal{E}_r(M_K)$. In particular, if the incremental scheme is executed without any truncation (so that $\widetilde{\sigma}_j(M_K) = \sigma_j(M_K)$ for all j), then

$$\widetilde{\mathcal{E}}_r(M_K) = \mathcal{E}_r(M_K).$$

Interpretation and limitations. The estimator $\widetilde{\mathcal{E}}_r(M_K)$ should be interpreted as a data-driven proxy for the true truncation error rather than a certified bound. When the incremental subspace remains well aligned with the true top-r singular subspace (e.g., under a persistent spectral gap or when newly appended blocks contribute low-energy components orthogonal to the dominant directions) the estimator is empirically tight. In contrast, when truncation discards directions that later reappear with significant energy, the estimator may temporarily underestimate the true error. This limitation is intrinsic to all truncated incremental SVD schemes and motivates the separation between provable and approximate clustering strategies. For the details of the algorithm see Appendix E.3.

5 Evaluation

We evaluate the proposed clustering–compression framework on four datasets with fundamentally different generative structure and spectral properties: (i) massive MIMO channel tensors with high-dimensional

Dataset	# Blocks	Original Shape	Final Shape	Size (GB)
Qualcomm MIMO SCM	2468	$(2, 20, 4, 50, 32)$	$(12800, 20)$	2.35
BigEarthNet-S1	10000	$(120, 120, 2)$	$(1440, 20)$	1.07
PDEBench (Advection)	5000	$(1024, 201)$	$(3072, 67)$	3.83
SmolVLM2 256M	333760	$-$	$(768, 1)$	0.95

Table 1: Datasets used for evaluation (actual matrix shapes used in experiments).

complex-valued geometry Qualcomm AI Research (2025), (ii) Sentinel-1 SAR satellite imagery Clasen et al. (2025), (iii) PDE-generated advective flows Takamoto et al. (2022), and (iv) SmolVLM2 256M model weights Marafioti et al. (2025). These domains exhibit markedly different spectrum decay rates and inter-block alignment, allowing us to assess the robustness of the proposed algorithms beyond a single application regime. All datasets are reshaped into collections of fixed-shape matrices prior to clustering. For BigEarthNet-S1 and PDEBench, we randomly sample blocks from the full datasets to obtain representative subsets of manageable size. For the Qualcomm MIMO dataset, we use a single batch of channel realizations provided by the official release. For SmolVLM2, whose weight tensors have heterogeneous shapes, we reshape each weight tensor into a fixed-length vector and treat each vector as an individual block, excluding bias parameters. The exact matrix shapes, number of blocks, and dataset statistics used in the experiments are reported in Table 1.

We evaluate three clustering algorithms: (i) **max-norm clustering**, derived from the Weyl-type upper bound (Theorem 1, see Appendix E.1); (ii) **residual-based clustering**, evaluated with two sorting strategies: norm-descending and residual-ascending, based on Theorem 2 (see Appendix E.2); (iii) **approximate incremental clustering**, also evaluated with both sorting strategies, derived from Corollary 2 (see Appendix E.3). All algorithms depend on a target relative reconstruction error and a target approximation rank.

All experiments were run under identical hardware conditions: Intel Core i5-13600KF (20 threads) with 64 GB RAM.

Reconstruction error. Let $X \in \mathbb{R}^{M \times N}$ denote the concatenated matrix formed from all blocks assigned to a cluster, and let $\hat{X}$ be its low-rank reconstruction after clustering and decoding. We measure reconstruction error using the relative Frobenius norm error

$$\varepsilon_{\mathrm{rel}} = \frac{\|X - \hat{X}\|_F}{\|X\|_F}. \tag{6}$$

For the max-norm and residual-based clustering algorithms, Theorems 1 and 2 guarantee that the relative reconstruction error does not exceed the user-specified error constraint. The approximate incremental algorithm does not provide a formal guarantee, however, no violations of the prescribed error thresholds were observed in any experiment. This empirical stability is consistent with the presence of strong spectral gaps in the tested datasets.

Compression ratio. Assume that each block has shape (m, n) and that a cluster contains K blocks approximated with target rank r. The uncompressed representation stores Kmn parameters. After compression, a shared basis requires mr parameters, while per-block coefficients require Knr parameters, resulting in a total of $r(m + Kn)$ parameters. The compression ratio is defined as the ratio between the number of parameters before and after compression.

Estimator conservativeness diagnostic. In addition to end-to-end compression performance, we explicitly evaluate how conservative the proposed error estimators are relative to the true truncated SVD error. For a fixed target rank r, we uniformly sample subsets of blocks of increasing cluster size, form their concatenation, and compute the true optimal rank-r reconstruction error $\mathcal{E}_r$ via an explicit SVD. For each sampled subset, we also compute the corresponding predicted error $\tilde{\mathcal{E}}_r$ produced by the max-norm, residual-based,

Figure 1: SmolVLM diagnostic of estimator conservativeness. Slack $\Delta = \widetilde{\mathcal{E}}_r - \mathcal{E}_r$ between predicted and true rank-r SVD reconstruction error. For each cluster size and estimator, all 10 independent trials (uniform block samples) are shown. (a) slack versus cluster size; (b) empirical slack distribution across estimators.

Method	Qualcomm	BigEarthNet	PDEBench	SmolVLM2	Wall time[†]
max norm	2.138	1.000[*]	1.004[*]	1.581	1×
res. (norm sorting)	2.276	1.000[*]	1.005[*]	1.588	2168×
res. (res. sorting)	2.243	1.000[*]	1.002[*]	1.547	4620×
approx. (norm sorting)	2.301	1.789	**45.434**	1.642	**100×**
approx. (res. sorting)	**2.334**	**1.870**	**45.434**	**1.807**	1792×

[*] Clustering failed; no compression achieved (compression ratio ≈ 1.0).
[†] Wall time is reported relative to a baseline of 130 ms.

Table 2: Compression ratios across datasets and worst-case clustering wall time. Wall time is reported relative to max-norm (higher is slower). Clustering were run with 5% relative reconstruction error constraint for Qualcomm, BigEarthNet and PDEBench and with 20% for SmolVLM. And target rank is fixed to 20 for Qualcomm and BigEarthNet, to 67 for PDEBench and to 32 for SmolVLM.

and approximate incremental estimators. For each cluster size and estimator, this procedure is repeated over 10 independent random trials with different block samples; *all individual trial outcomes are shown* in Figure 1. We report the resulting *slack* $\Delta = \tilde{\mathcal{E}}_r - \mathcal{E}_r$, which directly measures estimator conservativeness. As predicted by Theorems 1-2, the max-norm and residual-based estimators remain strictly conservative across all trials, exhibiting a consistently positive slack that is largely insensitive to cluster size. In contrast, the approximate incremental estimator produces substantially smaller slack (often close to zero) indicating a much tighter but non-guaranteed estimate of the true error. The observed dispersion across trials reflects variability induced by block selection while preserving a clear qualitative separation between estimators.

Clustering results. Table 2 reports compression ratios and worst-case clustering wall times across all datasets. Entries marked with ∗ indicate failure to achieve compression, defined as the inability to form clusters larger than individual blocks, resulting in compression ratios close to one. This behavior is not caused by numerical instability, but arises when conservative error bounds prevent aggregation of blocks into shared low-rank subspaces.

Figure 2: Compression rates under feasibility constraints. (a) Qualcomm dataset: fixed target rank and varying error constraint. (b) Qualcomm dataset: fixed error constraint and varying target rank. (c) SmolVLM2 model weights: fixed target rank and varying error constraint. (d) SmolVLM2 model weights: fixed error constraint and varying target rank.

The results reveal a clear trade-off between computational efficiency, compression performance, and theoretical guarantees. Max-norm clustering is consistently the fastest method, but yields conservative clustering due to loose worst-case bounds, limiting achievable compression. Residual-based clustering enforces strict reconstruction guarantees and produces stable results when feasible, but incurs several orders of magnitude higher runtime. Approximate incremental clustering achieves the highest compression, while remaining substantially faster than exact residual-based methods.

Hyperparameter sensitivity. We analyze the dependence of compression performance on the target reconstruction error and target rank. Figure 2 shows results for the Qualcomm MIMO dataset using approximate clustering with residual-based sorting, and reports results for SmolVLM2 weights using approximate clustering with norm-based sorting. Across both datasets, compression increases approximately linearly with the allowed reconstruction error, consistent with low-rank approximation theory. In contrast, the dependence on target rank is non-monotonic: increasing rank does not necessarily improve compression. This behavior reflects the interaction between rank selection and inter-block subspace alignment, highlighting that rank is not merely a capacity parameter but must be chosen carefully to balance expressivity and shared structure.

Classical clustering baselines. We additionally compare against baseline clustering methods on the Qualcomm dataset. Table 3 reports results for random clustering and k-means with varying numbers of clusters and for HDBSCAN. These methods are fundamentally misaligned with the concatenated SVD compression objective. Classical clustering algorithms optimize geometric distortion in the ambient space and provide no mechanism to control spectral reconstruction error after low-rank decoding. As a result, high compression is achieved only at the cost of unacceptable and highly unstable reconstruction error, while density-based clustering fails entirely by labeling all points as outliers. This confirms that standard clustering techniques are unsuitable for controlled low-rank compression of concatenated matrices.

Method	Compression	Rel. error	Outcome
Random clustering (K=10)	178.1	0.704 ± 0.034	High compression and error
Random clustering (K=100)	23.8	0.363 ± 0.110	Moderate compression, high error
Random clustering (K=1000)	2.46	0.199 ± 0.134	Low compression, moderate error
k-means (K=10)	178.3	0.886	High compression and error
k-means (K=100)	23.8	0.322 ± 0.343	High unstable error
k-means (K=1000)	2.46	0.881 ± 0.098	Low compression and high error
HDBSCAN (min cluster size = 2)	–	–	All points labeled as outliers

Table 3: Classical clustering baselines on the Qualcomm dataset.

6 Conclusion

We presented a theory-driven framework for compression-aware clustering of matrix collections under explicit SVD reconstruction constraints. By analyzing the spectral behavior of horizontally concatenated matrices, we derived global upper bounds on truncated SVD reconstruction error from lower bounds on singular value growth. These results enable principled decisions about which matrices can be safely grouped and compressed together. Building on this theory, we proposed three clustering algorithms spanning a trade-off between computational efficiency, provable accuracy, and scalability. Unlike existing heuristic or distance-based approaches, the proposed methods directly tie cluster formation to low-rank approximation error, providing explicit and interpretable accuracy control. An incremental truncated SVD estimator further enables efficient operation without forming the full concatenated matrix. Together, these contributions establish concatenation-aware SVD compression as a unifying perspective on matrix clustering and low-rank approximation, providing both theoretical foundations and practical algorithms for compressing large collections of matrices in modern machine learning and scientific computing pipelines.

Discussion and future work. Throughout this work, the target rank is treated as a fixed hyperparameter. In practice, the optimal rank may depend on cluster composition and could vary across clusters. Joint optimization of rank selection and clustering, allowing rank to adapt dynamically as blocks are merged, represents a promising direction for improving compression efficiency while preserving accuracy guarantees.

The present framework operates in an offline setting where all matrices are available in advance. In many applications, however, new data arrive sequentially. Extending compression-aware clustering to an incremental setting, where each new matrix must be assigned to an existing cluster or used to initialize a new cluster based on predicted SVD compression error, is a natural and practically important direction for future work. Such an extension would require efficient per-cluster error estimation and dynamic cluster management under streaming updates.

Finally, the current framework optimizes reconstruction error as the primary objective. In many applications, low-rank representations are used as intermediate features for downstream tasks. Incorporating task-aware objectives into compression-driven clustering while retaining spectral guarantees remains an open and challenging problem.

References

Harry C. Andrews and Claude L. Patterson. Singular value decomposition (svd) image coding. *IEEE Transactions on Communications*, 24(4):425–432, 1976. doi: 10.1109/TCOM.1976.1093309. URL `https://doi.org/10.1109/TCOM.1976.1093309`.

Matthew Brand. Incremental singular value decomposition of uncertain data with missing values. In *European Conference on Computer Vision*, pp. 707–720. Springer, 2002. doi: 10.1007/3-540-47969-4_47. URL `https://doi.org/10.1007/3-540-47969-4_47`.

Matthew Brand. Fast low-rank modifications of the thin singular value decomposition. *Linear algebra and its applications*, 415(1):20–30, 2006. doi: 10.1016/j.laa.2005.07.021. URL `https://doi.org/10.1016/j.laa.2005.07.021`.

Yuatyong Chaichana, Thanapat Trachu, Peerat Limkonchotiwat, Konpat Preechakul, Tirasan Khandhawit, and Ekapol Chuangsuwanich. Decom-renorm-merge: Model merging on the right space improves multi-tasking. *arXiv preprint arXiv:2505.23117*, 2025. URL `https://arxiv.org/abs/2505.23117`.

Kai Norman Clasen, Leonard Hackel, Tom Burgert, Gencer Sumbul, Begüm Demir, and Volker Markl. reben: Refined bigearthnet dataset for remote sensing image analysis. In *Proceedings of the IEEE International Geoscience and Remote Sensing Symposium (IGARSS)*, pp. 1264–1268. IEEE, 2025. ISBN 979-8-3315-0810-4. doi: 10.1109/igarss55030.2025.11242834. URL `https://infoscience.epfl.ch/handle/20.500.14299/256368`.

Lieven De Lathauwer, Bart De Moor, and Joos Vandewalle. On the best rank-1 and rank-$(r_1, r_2, \ldots, r_n)$ approximation of higher-order tensors. *SIAM journal on Matrix Analysis and Applications*, 21(4):1324–1342, 2000a. doi: 10.1137/S0895479898346995. URL `https://doi.org/10.1137/S0895479898346995`.

Lieven De Lathauwer, Bart De Moor, and Joos Vandewalle. A multilinear singular value decomposition. *SIAM journal on Matrix Analysis and Applications*, 21(4):1253–1278, 2000b. doi: 10.1137/S0895479896305696. URL `https://doi.org/10.1137/S0895479896305696`.

Carl Eckart and Gale Young. The approximation of one matrix by another of lower rank. *Psychometrika*, 1(3):211–218, 1936. doi: 10.1007/BF02288367. URL `https://doi.org/10.1007/BF02288367`.

Olivier Fercoq, Alexandre Gramfort, and Joseph Salmon. Mind the duality gap: safer rules for the lasso. In *Proceedings of the 32nd International Conference on Machine Learning*, volume 37, pp. 333–342. PMLR, 2015. URL `https://proceedings.mlr.press/v37/fercoq15.html`.

Laurent El Ghaoui, Vivian Viallon, and Tarek Rabbani. Safe feature elimination for the lasso and sparse supervised learning problems. *arXiv preprint arXiv:1009.4219*, 2010. URL `https://arxiv.org/abs/1009.4219`.

Nathan Halko, Per-Gunnar Martinsson, and Joel A Tropp. Finding structure with randomness: Probabilistic algorithms for constructing approximate matrix decompositions. *SIAM review*, 53(2):217–288, 2011. doi: 10.1137/09077180. URL `https://doi.org/10.1137/09077180`.

Peter M Hall, A David Marshall, and Ralph R Martin. Incremental eigenanalysis for classification. In *BMVC*, volume 98, pp. 286–295, 1998. URL `https://www.researchgate.net/publication/2581820_Incremental_Eigenanalysis_for_Classification`.

Ian Jolliffe. *Principal component analysis*. Springer, 2002. doi: 10.1007/b98835. URL `https://doi.org/10.1007/b98835`.

Tamara G Kolda and Brett W Bader. Tensor decompositions and applications. *SIAM review*, 51(3):455–500, 2009. doi: 10.1137/07070111X. URL `https://doi.org/10.1137/07070111X`.

Avraham Levy and Michael Lindenbaum. Sequential karhunen-loeve basis extraction and its application to images. In *Proceedings 1998 International Conference on Image Processing. ICIP98 (Cat. No.98CB36269)*, volume 2, pp. 456–460, 1998. doi: 10.1109/ICIP.1998.723422. URL `https://doi.org/10.1109/ICIP.1998.723422`.

Lujun Li, Zhu Qiyuan, Jiacheng Wang, Wei Li, Hao Gu, Sirui Han, and Yike Guo. Sub-moe: Efficient mixture-of-expert llms compression via subspace expert merging. *arXiv preprint arXiv:2506.23266*, 2025. URL `https://arxiv.org/abs/2506.23266`.

Yu-Chen Lu, Sheng-Feng Yu, Hui-Hsien Weng, Pei-Shuo Wang, Yu-Fang Hu, Liang Hung-Chun, Hung-Yueh Chiang, and Kai-Chiang Wu. Skipcat: Rank-maximized low-rank compression of large language models via shared projection and block skipping. *arXiv preprint arXiv:2512.13494*, 2025. URL `https://arxiv.org/abs/2512.13494`.

Andrés Marafioti, Orr Zohar, Miquel Farré, Merve Noyan, Elie Bakouch, Pedro Cuenca, Cyril Zakka, Loubna Ben Allal, Anton Lozhkov, Nouamane Tazi, Vaibhav Srivastav, Joshua Lochner, Hugo Larcher, Mathieu Morlon, Lewis Tunstall, Leandro von Werra, and Thomas Wolf. Smolvlm: Redefining small and efficient multimodal models. *arXiv preprint arXiv:2504.05299*, 2025. URL https://arxiv.org/abs/2504.05299.

Leon Mirsky. Symmetric gauge functions and unitarily invariant norms. *The quarterly journal of mathematics*, 11(1):50–59, 1960. doi: 10.1093/qmath/11.1.50. URL https://doi.org/10.1093/qmath/11.1.50.

Ioannis Mitliagkas, Constantine Caramanis, and Prateek Jain. Memory limited, streaming pca. In *Proceedings of the 27th International Conference on Neural Information Processing Systems*, volume 2, pp. 2886–2894. Curran Associates Inc., 2013. doi: 10.5555/2999792.2999934. URL https://dl.acm.org/doi/10.5555/2999792.2999934.

Angela K Nietz, Martha L Streng, Laurentiu S Popa, Russell E Carter, Evelyn B Flaherty, Justin D Aronson, and Timothy J Ebner. To be and not to be: wide-field ca2+ imaging reveals neocortical functional segmentation combines stability and flexibility. *Cerebral Cortex*, 33(11):6543–6558, 02 2023. ISSN 1047-3211. doi: 10.1093/cercor/bhac523. URL https://doi.org/10.1093/cercor/bhac523.

Qualcomm AI Research. Massive mimo spatial channel model dataset (dense urban scenario), version 1.0, 2025. URL https://www.qualcomm.com/developer/software/massive-mimo-spatial-channel-model-dataset.

Badrul Sarwar, George Karypis, and John Riedl. Application of dimensionality reduction in recommender system – a case study. 2000. URL https://files.grouplens.org/papers/webKDD00.pdf.

G. W. Stewart and Ji-Guang Sun. *Matrix Perturbation Theory*. Academic Press, San Diego, CA, 1990.

Shiliang Sun. A survey of multi-view machine learning. *Neural computing and applications*, 23(7):2031–2038, 2013. doi: 10.1007/s00521-013-1362-6. URL https://doi.org/10.1007/s00521-013-1362-6.

Makoto Takamoto, Timothy Praditia, Raphael Leiteritz, Dan MacKinlay, Francesco Alesiani, Dirk Pflüger, and Mathias Niepert. Pdebench: an extensive benchmark for scientific machine learning. In *Proceedings of the 36th International Conference on Neural Information Processing Systems*. Curran Associates Inc., 2022. doi: 10.5555/3600270.3600387. URL https://dl.acm.org/doi/10.5555/3600270.3600387.

Joel A Tropp, Alp Yurtsever, Madeleine Udell, and Volkan Cevher. Practical sketching algorithms for low-rank matrix approximation. *SIAM Journal on Matrix Analysis and Applications*, 38(4):1454–1485, 2017. doi: 10.1137/17M1111590. URL https://doi.org/10.1137/17M1111590.

Ledyard R Tucker. Some mathematical notes on three-mode factor analysis. *Psychometrika*, 31(3):279–311, 1966. doi: 10.1007/BF02289464. URL https://doi.org/10.1007/BF02289464.

Yixuan Wang, Haoyu Qiao, Lujun Li, Qingfu Zhu, and Wanxiang Che. Commonkv: Compressing kv cache with cross-layer parameter sharing. *arXiv preprint arXiv:2508.16134*, 2025a. URL https://arxiv.org/abs/2508.16134.

Yutong Wang, Haiyu Wang, and Sai Qian Zhang. Qsvd: Efficient low-rank approximation for unified query-key-value weight compression in low-precision vision-language models. *arXiv preprint arXiv:2510.16292*, 2025b. URL https://arxiv.org/abs/2510.16292.

Manfred K Warmuth and Dima Kuzmin. Randomized online pca algorithms with regret bounds that are logarithmic in the dimension. *Journal of Machine Learning Research*, 9(10):2287–2320, 2008. URL https://www.jmlr.org/papers/volume9/warmuth08a/warmuth08a.pdf.

Hermann Weyl. Das asymptotische verteilungsgesetz der eigenwerte linearer partieller differentialgleichungen (mit einer anwendung auf die theorie der hohlraumstrahlung). *Mathematische Annalen*, 71(4):441–479, 1912. doi: 10.1007/BF01456804. URL https://doi.org/10.1007/BF01456804.

David P. Woodruff. Sketching as a tool for numerical linear algebra. *Found. Trends Theor. Comput. Sci.*, 10(1–2):1–157, October 2014. ISSN 1551-305X. doi: 10.1561/0400000060. URL `https://doi.org/10.1561/0400000060`.

Jianshu Zhang, Ami Wiesel, and Martin Haardt. Low rank approximation based hybrid precoding schemes for multi-carrier single-user massive mimo systems. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 3281–3285, 2016. doi: 10.1109/ICASSP.2016.7472284. URL `https://doi.org/10.1109/ICASSP.2016.7472284`.

Jingtian Zhou, Yue Wu, Hanqing Liu, Wei Tian, Rosa G Castanon, Anna Bartlett, Zuolong Zhang, Guocong Yao, Dengxiaoyu Shi, Ben Clock, et al. Human body single-cell atlas of 3d genome organization and dna methylation. *bioRxiv*, 2025. doi: 10.1101/2025.03.23.644697. URL `https://doi.org/10.1101/2025.03.23.644697`.

A Preliminaries

This section summarizes the mathematical tools used throughout the paper. Our theoretical results rely on two classical components of matrix analysis: (i) perturbation inequalities for eigenvalues and singular values, and (ii) optimality properties of truncated SVD. We also introduce the notation and identities underlying our incremental representation of concatenated matrices.

A.1 Spectral Monotonicity and Perturbation Bounds

A key component in our analysis is the fact that appending a matrix block to an existing concatenation can only *increase* its singular values. This follows from a classical form of Weyl's monotonicity theorem for Hermitian matrices. Letting $M = [A_1, \ldots, A_t]$ and $M' = [A_1, \ldots, A_t, A_{t+1}]$, we have $M'M'^\top = MM^\top + A_{t+1}A_{t+1}^\top$, so the update is positive semidefinite.

Theorem 3 (Weyl Monotonicity; cf. Cor. 4.9 in Stewart & Sun (1990)). *Let $A, E \in \mathbb{R}^{n \times n}$ be Hermitian and write their eigenvalues in nonincreasing order,*

$$\lambda_1(A) \geq \cdots \geq \lambda_n(A), \qquad \lambda_1(E) \geq \cdots \geq \lambda_n(E).$$

Let $\tilde{\lambda}_1 \geq \cdots \geq \tilde{\lambda}_n$ be the eigenvalues of $A + E$. Then, for all $i = 1, \ldots, n$,

$$\tilde{\lambda}_i \in \big[\lambda_i(A) + \lambda_n(E),\, \lambda_i(A) + \lambda_1(E)\big].$$

In particular, if $E \succeq 0$, then

$$\tilde{\lambda}_i \geq \lambda_i(A), \qquad i = 1, \ldots, n.$$

Since the singular values of a matrix M are the square roots of the eigenvalues of $MM^\top$, the theorem immediately yields monotonicity of singular values under horizontal concatenation.

A.2 Optimality of Truncated SVD

We frequently use the classical Eckart–Young–Mirsky theorem, which states that the best rank-r approximation of a matrix in Frobenius norm is obtained by truncating its singular value decomposition.

Theorem 4 (Eckart–Young–Mirsky (Eckart & Young, 1936; Mirsky, 1960)). *Let $A \in \mathbb{R}^{m \times n}$ have singular values $\sigma_1(A) \geq \sigma_2(A) \geq \cdots \geq 0$, and let*

$$A = U\Sigma V^\top, \qquad \Sigma = \mathrm{diag}(\sigma_1, \ldots, \sigma_p), \quad p = \min\{m, n\}.$$

For $r \in \{0, \ldots, p\}$, define the rank-r truncated SVD

$$A_r := U \begin{bmatrix} \mathrm{diag}(\sigma_1, \ldots, \sigma_r) & 0 \\ 0 & 0 \end{bmatrix} V^\top.$$

Then A_r is the best rank-r approximation to A in the Frobenius norm:

$$\|A - A_r\|_F = \min_{\text{rank}(X) \leq r} \|A - X\|_F = \left(\sum_{j>r} \sigma_j(A)^2 \right)^{1/2}.$$

This theorem underlies all of our compression error formulas.

A.3 Incremental Representation of Concatenated Matrices

Let $M_t = [A_1, \ldots, A_t]$ denote the concatenation of t blocks. When a new block A_{t+1} is appended, the Gram matrix updates as

$$M_{t+1}M_{t+1}^\top = M_t M_t^\top + A_{t+1}A_{t+1}^\top,$$

which is a rank-$\leq n_{t+1}$ positive semidefinite perturbation. Instead of storing the full $m \times m$ matrix $M_t M_t^\top$, we maintain an orthonormal basis Q_t for the current column space of M_t and pose $M_t M_t^\top$ by this basis via a small Gram matrix S_t, i.e.,

$$M_t M_t^\top = Q_t S_t Q_t^\top.$$

When A_{t+1} arrives, we decompose it by Q_t and the residual orthogonal to Q_t, as follows

$$A_{t+1} = Q_t Y_{t+1} + R_{t+1}, \qquad R_{t+1} = (I - Q_t Q_t^\top) A_{t+1}.$$

Expanding the basis by the columns of R_{t+1} yields an updated orthonormal matrix Q_{t+1}, and the new Gram matrix S_{t+1} takes a block form constructed from S_t, Y_{t+1}, and the SVD of R_{t+1}. This identity, stated formally in Lemma 1 and proved in Appendix B, is exact and well known in the incremental PCA/SVD literature. It provides the algebraic foundation for our blockwise concatenation analysis.

After expanding the basis and updating S_{t+1}, its size grows by the rank of R_{t+1}. To control complexity, we compress back to the rank r by retaining only the top r eigenpairs of S_{t+1}. By Theorem 4, this produces the optimal rank-r approximation *within the expanded subspace*. The approximate singular values of M_{t+1} are then given by the square roots of the retained eigenvalues.

The only source of approximation in our incremental estimator is this truncation step, all other steps are exact. A full characterization of the truncation and its implications is provided in Corollary 3.

Stability of the incremental estimator. Although the truncated incremental scheme does not provide deterministic upper or lower bounds on the true truncated SVD error, its approximation quality is governed by classical subspace stability principles. In particular, when the singular value gap $\sigma_r(M_t) - \sigma_{r+1}(M_t)$ is sufficiently large, truncation preserves the dominant invariant subspace up to small perturbations, and the retained eigenvalues of the compressed Gram matrix remain close to the true leading singular values. This behavior is well understood in incremental and randomized SVD literature, where approximation error scales with the truncation gap and the energy of discarded components.

B Incremental SVD identities

This appendix contains the algebraic identities used in Section 4.3 to derive our incremental estimator for the top singular values of a concatenated matrix. These results are classical in incremental PCA/SVD, but we provide them for completeness and to make the paper self-contained.

Lemma 1 (Exact incremental Gram factorisation for concatenated blocks). *Let $M_t = [A_1, \ldots, A_t] \in \mathbb{R}^{m \times n_t}$ be the horizontal concatenation of the first t blocks, and suppose that for some r_t we have an exact factorisation*

$$M_t M_t^\top = Q_t S_t Q_t^\top,$$

where $Q_t \in \mathbb{R}^{m \times r_t}$ has orthonormal columns and $S_t \in \mathbb{R}^{r_t \times r_t}$ is symmetric positive semidefinite. Let a new block $A_{t+1} \in \mathbb{R}^{m \times k}$ be given and define

$$Y := Q_t^\top A_{t+1}, \qquad R := A_{t+1} - Q_t Y.$$

Compute a thin QR decomposition of the residual,

$$R = Q_{\mathrm{res}}B,$$

with $Q_{\mathrm{res}} \in \mathbb{R}^{m \times r_{\mathrm{res}}}$ having orthonormal columns and $B \in \mathbb{R}^{r_{\mathrm{res}} \times k}$, and set

$$Q_{t+1} := \begin{bmatrix} Q_t & Q_{\mathrm{res}} \end{bmatrix} \in \mathbb{R}^{m \times (r_t + r_{\mathrm{res}})}.$$

Define the extended Gram matrix

$$S_{t+1} := \begin{bmatrix} S_t + YY^\top & YB^\top \\ BY^\top & BB^\top \end{bmatrix} \in \mathbb{R}^{(r_t + r_{\mathrm{res}}) \times (r_t + r_{\mathrm{res}})}.$$

Then Q_{t+1} has orthonormal columns and

$$M_{t+1}M_{t+1}^\top = Q_{t+1}S_{t+1}Q_{t+1}^\top,$$

where $M_{t+1} := [M_t, A_{t+1}]$.

Proof. By construction, Q_t has orthonormal columns and Q_{res} is the Q-factor of a thin QR decomposition of the residual R. Moreover, $R = (I - Q_t Q_t^\top)A_{t+1}$ lies in the orthogonal complement of $\mathrm{range}(Q_t)$, hence $Q_t^\top Q_{\mathrm{res}} = 0$, and therefore Q_{t+1} has orthonormal columns.

We first expand the new Gram matrix explicitly:

$$M_{t+1}M_{t+1}^\top = M_t M_t^\top + A_{t+1}A_{t+1}^\top.$$

Using the decomposition $A_{t+1} = Q_t Y + R$ and $M_t M_t^\top = Q_t S_t Q_t^\top$, we get

$$\begin{aligned} M_{t+1}M_{t+1}^\top &= Q_t S_t Q_t^\top + (Q_t Y + R)(Q_t Y + R)^\top \\ &= Q_t S_t Q_t^\top + Q_t YY^\top Q_t^\top + Q_t YR^\top + RY^\top Q_t^\top + RR^\top. \end{aligned}$$

The orthogonality relation $Q_t^\top R = 0$ implies $R = Q_{\mathrm{res}}B$ for some B, namely the R-factor of the QR decomposition. Substituting this into the above yields

$$\begin{aligned} M_{t+1}M_{t+1}^\top &= Q_t(S_t + YY^\top)Q_t^\top + Q_t YB^\top Q_{\mathrm{res}}^\top + Q_{\mathrm{res}}BY^\top Q_t^\top + Q_{\mathrm{res}}BB^\top Q_{\mathrm{res}}^\top \\ &= \begin{bmatrix} Q_t & Q_{\mathrm{res}} \end{bmatrix} \begin{bmatrix} S_t + YY^\top & YB^\top \\ BY^\top & BB^\top \end{bmatrix} \begin{bmatrix} Q_t & Q_{\mathrm{res}} \end{bmatrix}^\top \\ &= Q_{t+1}S_{t+1}Q_{t+1}^\top, \end{aligned}$$

as claimed. $\qquad\square$

Corollary 3 (Truncated incremental top-r approximation)**.** *In the setting of Lemma 1, let*

$$S_{t+1} = U\Lambda U^\top$$

be an eigendecomposition of S_{t+1} with eigenvalues ordered as $\lambda_1 \geq \lambda_2 \geq \cdots \geq \lambda_{r_t + r_{\mathrm{res}}} \geq 0$. For a target rank $r \leq r_t + r_{\mathrm{res}}$, define

$$U_r := \begin{bmatrix} u_1 & \cdots & u_r \end{bmatrix}, \qquad \Lambda_r := \mathrm{diag}(\lambda_1, \ldots, \lambda_r).$$

Set

$$\widetilde{Q}_{t+1} := Q_{t+1}U_r \in \mathbb{R}^{m \times r}, \qquad \widetilde{S}_{t+1} := \Lambda_r \in \mathbb{R}^{r \times r}.$$

Then:

1. *The matrix $\widetilde{G}_{t+1} := \widetilde{Q}_{t+1}\widetilde{S}_{t+1}\widetilde{Q}_{t+1}^\top$ is the best rank-r approximation to $G_{t+1} := M_{t+1}M_{t+1}^\top$ within the subspace* range(Q_{t+1}), *in both spectral and Frobenius norms, i.e.*

$$\|G_{t+1} - \widetilde{G}_{t+1}\|_F^2 = \sum_{j>r} \lambda_j(S_{t+1}), \qquad \|G_{t+1} - \widetilde{G}_{t+1}\|_2 = \lambda_{r+1}(S_{t+1}).$$

2. *The top r approximate singular values of M_{t+1} produced by this scheme are*

$$\widetilde{\sigma}_j(M_{t+1}) := \sqrt{\lambda_j(S_{t+1})}, \qquad j = 1, \dots, r.$$

Proof. By Lemma 1, $G_{t+1} = Q_{t+1}S_{t+1}Q_{t+1}^\top$ with Q_{t+1} orthonormal. Any rank-r approximation $\widehat{G}$ whose range is contained in range(Q_{t+1}) can be written as $\widehat{G} = Q_{t+1}XQ_{t+1}^\top$ with rank$(X) \le r$. Because Q_{t+1} is orthonormal, the Frobenius and spectral norms satisfy

$$\|G_{t+1} - \widehat{G}\| = \|S_{t+1} - X\|,$$

for both $\|\cdot\|_F$ and $\|\cdot\|_2$. By the Eckart–Young–Mirsky theorem (Theorem 4), the best rank-r approximation to S_{t+1} in Frobenius and spectral norms is $X = U_r\Lambda_rU_r^\top$, with errors $\sum_{j>r}\lambda_j(S_{t+1})$ and $\lambda_{r+1}(S_{t+1})$, respectively. Substituting $X = U_r\Lambda_rU_r^\top$ and noting that $Q_{t+1}U_r = \widetilde{Q}_{t+1}$ and $\Lambda_r = \widetilde{S}_{t+1}$ gives the first claim.

The second statement is just the observation that the eigenvalues of $\widetilde{G}_{t+1}$ equal $\lambda_1(S_{t+1}), \dots, \lambda_r(S_{t+1})$, so the corresponding approximate singular values of M_{t+1} are their square roots. □

C Proofs

C.1 Proof of Theorem 1

Proof. Write the singular values of a matrix X in the non-increasing order as $\sigma_1(X) \ge \cdots \ge \sigma_{\min(m,n)}(X)$. By the Eckart–Young–Mirsky theorem (Theorem 4),

$$\mathcal{E}_r^2(M) = \sum_{i>r} \sigma_i^2(M) = \|M\|_F^2 - \sum_{i=1}^r \sigma_i^2(M).$$

Since $M = [A_1, \dots, A_K]$ is a horizontal concatenation, its Frobenius norm decomposes to

$$\|M\|_F^2 = \sum_{j=1}^K \|A_j\|_F^2.$$

Thus

$$\mathcal{E}_r^2(M) = \sum_{j=1}^K \|A_j\|_F^2 - \sum_{i=1}^r \sigma_i^2(M). \tag{7}$$

We now relate the singular values of M to those of the blocks A_j. Define

$$B_j := A_jA_j^\top \succeq 0, \qquad j = 1, \dots, K,$$

so that

$$MM^\top = \sum_{j=1}^K A_jA_j^\top = \sum_{j=1}^K B_j.$$

Fix $k \in \{1, \dots, K\}$ and write

$$MM^\top = B_k + C_k, \qquad C_k := \sum_{\substack{j=1 \\ j \ne k}}^K B_j \succeq 0.$$

By the Weyl monotonicity (Theorem 3), if H, G are Hermitian with $G \succeq 0$ and $\lambda_1(\cdot) \geq \cdots \geq \lambda_n(\cdot)$ denote eigenvalues in nonincreasing order, then

$$\lambda_i(H + G) \geq \lambda_i(H), \qquad i = 1, \ldots, n.$$

Applying this with $H = B_k$ and $G = C_k$ yields

$$\lambda_i(MM^\top) = \lambda_i(B_k + C_k) \geq \lambda_i(B_k), \qquad i = 1, \ldots, m.$$

Using $\sigma_i^2(X) = \lambda_i(XX^\top)$, we obtain

$$\sigma_i^2(M) = \lambda_i(MM^\top) \geq \lambda_i(B_k) = \sigma_i^2(A_k), \qquad i = 1, \ldots, \min(m, n_k).$$

Summing over $i = 1, \ldots, r$ gives

$$\sum_{i=1}^{r} \sigma_i^2(M) \geq \sum_{i=1}^{r} \sigma_i^2(A_k) \qquad \text{for every } k = 1, \ldots, K.$$

Hence

$$\sum_{i=1}^{r} \sigma_i^2(M) \geq \max_{1 \leq j \leq K} \sum_{i=1}^{r} \sigma_i^2(A_j). \tag{8}$$

Combining equation 7 and equation 8, we obtain

$$\mathcal{E}_r^2(M) = \sum_{j=1}^{K} \|A_j\|_F^2 - \sum_{i=1}^{r} \sigma_i^2(M) \leq \sum_{j=1}^{K} \|A_j\|_F^2 - \max_{1 \leq j \leq K} \sum_{i=1}^{r} \sigma_i^2(A_j),$$

which is exactly equation 4. If $r \geq \text{rank}(A_j)$ for all j, then $\sum_{i=1}^{r} \sigma_i^2(A_j) = \|A_j\|_F^2$, which yields the stated special case. $\square$

C.2 Proof of Theorem 2

Proof. We prove the result by comparing the Gram matrix of M_K with the Gram matrix of the concatenated residuals $\widehat{R}$, and then invoking the eigenvalue monotonicity for Hermitian matrices.

Step 1: Gram matrix of the final concatenation. Define the (symmetric, positive semidefinite) Gram matrix

$$X := M_K M_K^\top = \begin{bmatrix} A_1 & A_2 & \cdots & A_K \end{bmatrix} \begin{bmatrix} A_1 & A_2 & \cdots & A_K \end{bmatrix}^\top = \sum_{i=1}^{K} A_i A_i^\top,$$

where the singular values of M_K are related to the eigenvalues of X,

$$\sigma_j^2(M_K) = \lambda_j(X), \qquad j = 1, \ldots, m,$$

and the eigenvalues are ordered non-increasingly: $\lambda_1(X) \geq \lambda_2(X) \geq \cdots \geq \lambda_m(X) \geq 0$.

Step 2: Decomposition of each block into "old span + residual". By construction, Q_{i-1} has orthonormal columns spanning range(M_{i-1}). We can therefore write each block A_i as a sum of a part in the span of Q_{i-1} and an orthogonal residual. More precisely, define

$$B_i := Q_{i-1}^\top A_i \in \mathbb{R}^{r_{i-1} \times n_i},$$

where $r_{i-1} = \text{rank}(M_{i-1}) = \text{cols}(Q_{i-1})$, and recall that

$$R_i := (I - Q_{i-1} Q_{i-1}^\top) A_i.$$

Then we have the orthogonal decomposition

$$A_i = Q_{i-1} B_i + R_i,$$

with

$$\mathrm{range}(Q_{i-1}B_i) \subseteq \mathrm{range}(Q_{i-1}) = \mathrm{range}(M_{i-1}), \qquad \mathrm{range}(R_i) \subseteq \mathrm{range}(M_{i-1})^\perp.$$

In particular, $Q_{i-1}B_i$ and R_i have orthogonal column spaces, therefore, their Gram matrices have no cross terms:

$$(Q_{i-1}B_i)(R_i)^\top = Q_{i-1}B_i R_i^\top = 0, \qquad R_i(Q_{i-1}B_i)^\top = 0.$$

Using the decomposition $A_i = Q_{i-1}B_i + R_i$, we expand

$$A_i A_i^\top = (Q_{i-1}B_i + R_i)(Q_{i-1}B_i + R_i)^\top = Q_{i-1}B_i B_i^\top Q_{i-1}^\top + R_i R_i^\top,$$

since the cross terms vanish by the orthogonality noted above. Therefore,

$$A_i A_i^\top - R_i R_i^\top = Q_{i-1}B_i B_i^\top Q_{i-1}^\top \succeq 0, \tag{9}$$

i.e., $A_i A_i^\top \succeq R_i R_i^\top$ in the Loewner (positive semidefinite) order.

Summing equation 9 over $i = 1, \ldots, K$ gives

$$\sum_{i=1}^{K} A_i A_i^\top \;\succeq\; \sum_{i=1}^{K} R_i R_i^\top.$$

By the definition,

$$X = M_K M_K^\top \;\succeq\; Y := \sum_{i=1}^{K} R_i R_i^\top. \tag{10}$$

Step 3: Orthogonality of the residual ranges. We now show that the column spaces of the residuals R_i are mutually orthogonal. This is a consequence of the incremental construction.

Since each R_j is a linear combination of the columns of A_j, we have $\mathrm{range}(R_j) \subseteq \mathrm{range}(A_j)$. Because $\mathrm{range}(M_{i-1})$ contains $A_1, \ldots, A_{i-1}$, it follows that

$$\mathrm{range}(R_j) \subseteq \mathrm{range}(M_{i-1}), \qquad j < i.$$

On the other hand,

$$R_i = (I - Q_{i-1}Q_{i-1}^\top)A_i$$

lies in the orthogonal complement of the $\mathrm{range}(Q_{i-1})$, which is equal to the orthogonal complement of $\mathrm{range}(M_{i-1})$. Thus

$$\mathrm{range}(R_i) \subseteq \mathrm{range}(M_{i-1})^\perp \quad \Rightarrow \quad \mathrm{range}(R_i) \perp \mathrm{range}(R_j) \text{ for all } j < i.$$

By symmetry of the indices, this shows that the subspaces $\mathrm{range}(R_1), \ldots, \mathrm{range}(R_K)$ are pairwise orthogonal.

Step 4: Gram matrix of the concatenated residuals. Consider the concatenated residual matrix

$$\widehat{R} := \begin{bmatrix} R_1 & R_2 & \cdots & R_K \end{bmatrix} \quad \text{and} \quad \widehat{R}\,\widehat{R}^\top = \sum_{i=1}^{K} R_i R_i^\top = Y.$$

Because the column spaces of R_i are pairwise orthogonal, there exists an orthonormal basis of $\mathbb{R}^m$ in which Y becomes block diagonal with blocks $R_i R_i^\top$ and possibly an additional zero block (if the sum of their ranks is $< m$). In such a basis, the eigenvalues of Y are just the multiset union of the eigenvalues of $R_i R_i^\top$, i.e., the squared singular values of each R_i.

Equivalently, if $\mu_1 \geq \mu_2 \geq \cdots \geq 0$ are the singular values of $\widehat{R}$ (padded by zeros when necessary), then

$$\lambda_j(Y) = \mu_j^2, \qquad j = 1, \ldots, m.$$

Step 5: Eigenvalue monotonicity and conclusion. From equation 10, $X \succeq Y$, i.e., $X - Y$ is positive semidefinite. By Weyl's monotonicity theorem (see Theorem 3), the eigenvalues of X and Y satisfy

$$\lambda_j(X) \geq \lambda_j(Y), \qquad j = 1, \ldots, m.$$

Combining this with the identities

$$\lambda_j(X) = \sigma_j^2(M_K), \qquad \lambda_j(Y) = \mu_j^2,$$

we obtain

$$\sigma_j^2(M_K) \geq \mu_j^2, \qquad j = 1, \ldots, m.$$

Since both sides are nonnegative, taking square roots preserves the inequality:

$$\sigma_j(M_K) \geq \mu_j, \qquad j = 1, \ldots, m.$$

This is exactly the claimed bound. $\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad$ $\square$

C.3   Proof of Corollary 1

Proof. By Theorem 2, $\sigma_j(M_K) \geq \mu_j$ for all $j \geq 1$, hence

$$\sum_{j=1}^{r} \sigma_j^2(M_K) \geq \sum_{j=1}^{r} \mu_j^2.$$

The Frobenius norm of M_K satisfies

$$\|M_K\|_F^2 = \sum_{j \geq 1} \sigma_j^2(M_K) = \sum_{i=1}^{K} \|A_i\|_F^2,$$

since M_K is the horizontal concatenation of the blocks A_i. By Theorem 4,

$$\mathcal{E}_r^2(M_K) = \sum_{j>r} \sigma_j^2(M_K) = \|M_K\|_F^2 - \sum_{j=1}^{r} \sigma_j^2(M_K).$$

Substituting $\|M_K\|_F^2 = \sum_{i=1}^{K} \|A_i\|_F^2$ and using the lower bound on the top-r energy yields

$$\mathcal{E}_r^2(M_K) = \sum_{i=1}^{K} \|A_i\|_F^2 - \sum_{j=1}^{r} \sigma_j^2(M_K) \leq \sum_{i=1}^{K} \|A_i\|_F^2 - \sum_{j=1}^{r} \mu_j^2,$$

which is exactly equation 5. $\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad$ $\square$

C.4   Proof of Corollary 3

Proof. By definition of the Frobenius norm and the block structure of M_K, we have

$$\|M_K\|_F^2 = \sum_{i=1}^{K} \|A_i\|_F^2.$$

On the other hand, for the true singular values $\sigma_1(M_K) \geq \sigma_2(M_K) \geq \cdots$, the Eckart–Young–Mirsky theorem (Theorem 4) gives

$$\mathcal{E}_r^2(M_K) = \sum_{j>r} \sigma_j^2(M_K) = \sum_{j \geq 1} \sigma_j^2(M_K) - \sum_{j=1}^{r} \sigma_j^2(M_K) = \|M_K\|_F^2 - \sum_{j=1}^{r} \sigma_j^2(M_K).$$

The plug-in estimator $\widetilde{\mathcal{E}}_r(M_K)$ is obtained by replacing the unknown true singular values $\sigma_j(M_K)$ in this identity with their incremental approximations $\widetilde{\sigma}_j(M_K)$:

$$\widetilde{\mathcal{E}}_r^2(M_K) := \|M_K\|_F^2 - \sum_{j=1}^{r} \widetilde{\sigma}_j^2(M_K) = \sum_{i=1}^{K} \|A_i\|_F^2 - \sum_{j=1}^{r} \widetilde{\sigma}_j^2(M_K).$$

If the incremental scheme is run without truncation, then by Corollary 3 the approximated singular values coincide with the true ones, $\widetilde{\sigma}_j(M_K) = \sigma_j(M_K)$ for all j, and therefore

$$\widetilde{\mathcal{E}}_r^2(M_K) = \|M_K\|_F^2 - \sum_{j=1}^{r} \sigma_j^2(M_K) = \mathcal{E}_r^2(M_K),$$

which implies $\widetilde{\mathcal{E}}_r(M_K) = \mathcal{E}_r(M_K)$. In the truncated case, $\widetilde{\mathcal{E}}_r(M_K)$ is an approximation to $\mathcal{E}_r(M_K)$ obtained by this plug-in substitution. $\qquad\square$

D Examples

D.1 Worst-case looseness of the Weyl-based bound

Example 1 (Perfect compressibility with a loose Weyl bound). *Consider rank-one matrices*

$$A_j = u\, s_j\, v_j^\top, \qquad \|u\|_2 = 1,$$

sharing the same left singular vector u, with arbitrary right singular vectors v_j and scalars $s_j > 0$. The concatenated matrix $M = [A_1, \ldots, A_K]$ has rank one, and hence

$$\mathcal{E}_1^2(M) = 0.$$

However, Theorem 1 yields

$$\mathcal{E}_1^2(M) \leq \sum_{j=1}^{K} s_j^2 \;-\; \max_j s_j^2,$$

which grows with K unless a single block dominates. Thus, even in a maximally compressible setting, the Weyl-based bound can significantly overestimate the true reconstruction error.

D.2 Exactness and degeneracy of the residual-based bound

Proposition 1 (Exactness and degeneracy of the residual-based bound). *Let*

$$M_K = \begin{bmatrix} A_1 & A_2 & \cdots & A_K \end{bmatrix} \in \mathbb{R}^{m \times (n_1 + \cdots + n_K)}$$

be formed by horizontal concatenation, and let $R_1, \ldots, R_K$ be the incremental residuals defined as in Theorem 2. Let $\mu_1 \geq \mu_2 \geq \cdots \geq 0$ denote the singular values of the concatenated residual matrix $\widehat{R} := [R_1, \ldots, R_K]$.

__Exactness under orthogonal subspace growth.__ If the residual subspaces $\mathrm{range}(R_1), \ldots, \mathrm{range}(R_K)$ are mutually orthogonal and

$$\mathrm{range}(M_K) = \bigoplus_{i=1}^{K} \mathrm{range}(R_i),$$

then the singular values of M_K coincide with those of $\widehat{R}$, i.e.

$$\sigma_j(M_K) = \mu_j \quad \text{for all } j,$$

and the residual-based bound in Corollary 1 holds with equality for every target rank r.

Algorithm 1 Weyl-based max-norm clustering

Require: Blocks $\{A_j\}_{j=1}^K$, tolerance ε, width budget r_{target}
Ensure: Clusters $\mathcal{C}$
1: Sort blocks by decreasing Frobenius norm
2: **while** blocks remain **do**
3:    Choose the largest norm remaining block as anchor
4:    Form a head by concatenating the largest norm blocks up to width r_{target}
5:    Add smallest norm remaining blocks while relative tail energy $\leq \varepsilon$
6:    Output the resulting cluster and remove its blocks
7: **end while**

Degeneracy under nested column spaces. If

$$\text{range}(A_1) \supseteq \text{range}(A_2) \supseteq \cdots \supseteq \text{range}(A_K),$$

then $R_i = 0$ for all $i \geq 2$, and the residual-based bound reduces to

$$\mathcal{E}_r^2(M_K) \leq \sum_{i=2}^K \|A_i\|_F^2,$$

which may be arbitrarily loose when all blocks lie in a common low-dimensional subspace.

Proof. **Exactness.** Under the stated assumptions, the residual subspaces $\text{range}(R_1), \ldots, \text{range}(R_K)$ are mutually orthogonal and together span $\text{range}(M_K)$. Consequently, the Gram matrix of the concatenated residuals satisfies

$$\widehat{R}\widehat{R}^\top = \sum_{i=1}^K R_i R_i^\top = M_K M_K^\top.$$

Thus the eigenvalues of $M_K M_K^\top$ coincide with those of $\widehat{R}\widehat{R}^\top$, implying $\sigma_j(M_K) = \mu_j$ for all j. Substituting into the definition of the optimal rank-r approximation error yields equality in the bound of Corollary 1.

Degeneracy. If $\text{range}(A_i) \subseteq \text{range}(M_{i-1})$, then by definition of the residual

$$R_i = (I - Q_{i-1}Q_{i-1}^\top)A_i = 0.$$

Under the nesting assumption, this holds for all $i \geq 2$. The claimed bound then follows immediately from Corollary 1 by noting that $\mu_j = 0$ for all $j > \text{rank}(A_1)$.

$\square$

E   Algorithms

E.1   Fast Weyl-based clustering

Here we introduce a lightweight clustering heuristic that relies only on Frobenius norms and the simplified Weyl-type bound from the Theorem 1. The user specifies a tolerance $\varepsilon > 0$ that controls the *relative* rank-r approximation error permitted within each cluster.

Assuming the target rank satisfies $r \geq \max_{j \in C} \text{rank}(A_j)$, the bound guarantees that every cluster C produced by Algorithm 1 obeys the relative error constraint

$$\frac{\mathcal{E}_r(M_C)}{\|M_C\|_F} \leq \varepsilon.$$

The algorithm runs in $O(K \log K)$ time, dominated by sorting the block norms, plus the cost of computing $\|A_j\|_F$, which is typically negligible compared to any SVD-based compression routine. In Section 5 we show that, despite its simplicity and coarse (norm-only) nature, this Weyl-based clustering already yields strong compression performance in practice.

Algorithm 2 Residual-based clustering

Require: Blocks $\{A_j\}_{j=1}^K$, tolerance ε, target rank r
Ensure: Clusters $\mathcal{C}$
 1: Sort blocks by decreasing $\|A_j\|_F$
 2: **while** blocks remain **do**
 3:     Select the largest remaining block as anchor
 4:     Maintain an incremental rank-r energy estimate for the cluster
 5:     Add remaining blocks (by small norm or small residual) while

$$\frac{\|M_C\|_F^2 - \sum_{\ell=1}^r \mu_\ell^2}{\|M_C\|_F^2} \leq \varepsilon^2$$

 6:     Output the cluster and remove its blocks
 7: **end while**

Algorithm 3 Approximate residual-based clustering

Require: Blocks $\{A_j\}_{j=1}^K$, tolerance ε, target rank r
Ensure: Clusters $\mathcal{C}$
 1: Sort blocks by decreasing $\|A_j\|_F$
 2: **while** blocks remain **do**
 3:     Select the largest remaining block as anchor
 4:     Initialize a cluster subspace model that tracks the leading r singular values approximately
 5:     Add remaining blocks (by small norm or small residual) while

$$\frac{\|M_C\|_F^2 - \sum_{\ell=1}^r \widetilde{\sigma}_\ell^2(M_C)}{\|M_C\|_F^2} \leq \varepsilon^2$$

    where $\sum_{\ell=1}^r \widetilde{\sigma}_\ell^2(M_C)$ is an incremental approximation
 6:     Output the cluster and remove its blocks
 7: **end while**

E.2   Residual-based clustering

We next introduce a clustering procedure that employs the residual-based bound as its merging criterion. At each step, candidate blocks are considered in an order determined by a user-selected `sort_mode`:

- `frobenius`: candidates are ordered by increasing Frobenius norm, yielding a fast heuristic closely related to Algorithm 1;

- `residual`: candidates are ordered by increasing residual norm $\|(I - Q_C Q_C^\top) A_j\|_F$ with respect to the current cluster subspace Q_C, enabling a more geometry-aware exploration of the data at higher computational cost.

By construction and by Corollary 1, every cluster C produced by Algorithm 2 satisfies the relative error guarantee

$$\frac{\mathcal{E}_r(M_C)}{\|M_C\|_F} \leq \varepsilon.$$

Compared to the Weyl-based Algorithm 1, this residual-based approach incurs additional computational overhead due to incremental residual projections and singular-value updates. In return, it provides substantially tighter error control and more accurate clustering, as confirmed empirically in Section 5.

E.3 Approximate clustering via incremental truncated SVD

The Algorithm 3 replaces the exact residual-based error bound with a plug-in estimator $\widetilde{\mathcal{E}}_r(\cdot)$ obtained from an incremental truncated SVD of the concatenated cluster. Structurally, it mirrors Algorithm 2: blocks are considered in a fixed order, and new blocks are added to the current cluster until the (approximate) relative rank-r compression error exceeds the prescribed tolerance ε.

The key distinction is that, instead of explicitly tracking residual singular values, the algorithm maintains an incremental low-rank approximation of the cluster matrix and uses it directly to estimate the captured rank-r energy. This design targets the large-scale regime: each merge step operates only on small matrices of size $O(r)$, independent of the number of blocks already assigned to the cluster.

As in Algorithm 2, two ordering strategies are supported: `frobenius`, which prioritizes candidates with smaller Frobenius norm $\|A_j\|_F$, and `residual`, which orders candidates by the norm of the projected residual $(I - Q_C Q_C^\top)A_j$ with respect to the current cluster subspace Q_C.

Unlike Algorithms 1 and 2, this approximate method does not yield a formal worst-case bound on the true compression error. Nevertheless, our experiments in Section 5 show that the plug-in estimator $\widetilde{\mathcal{E}}_r(M_C)$ is sufficiently accurate to guide clustering decisions and achieves the most favorable trade-off between computational cost and compression quality in large-scale settings.