LEARNING TO INTERPRET TRAJECTORIES

ABSTRACT

By learning to predict trajectories of dynamical systems, model-based methods can make extensive use of all observations from past experience. However, due to partial observability, stochasticity, compounding errors, and irrelevant dynamics, training to predict observations explicitly often results in poor models. Model-free techniques try to side-step the problem by learning to predict values directly. While breaking the explicit dependency on future observations can result in strong performance, this usually comes at the cost of low sample efficiency, as the abundant information about the dynamics contained in future observations goes unused. Here we take a step back from both approaches: Instead of hand-designing how trajectories should be incorporated, a *teacher* network learns to interpret the trajectories and to provide target activations which guide a *student* model that can only observe the present. The teacher is trained with meta-gradients to maximize the student's performance on a validation set. We show that our approach performs well on tasks that are difficult for model-free and model-based methods, and we study the role of every component through ablation studies.

1 INTRODUCTION

The ability to learn models of the world has long been argued to be an important ability of intelligent agents. An open and actively researched question is how to learn world models at the right level of abstraction. This paper argues, as others have before, that model-based and model-free methods lie on a spectrum in which advantages and disadvantages of either approach can be traded off against each other, and that there is an optimal compromise for every task. Predicting future observations allows extensive use of all observations from previous experiences during training, and to swiftly transfer to a new reward if the learned model is accurate. However, due to partial observability, stochasticity, irrelevant dynamics and compounding errors in planning, model-based methods tend to be outperformed asymptotically. By trying to be open to every possible new task, performance ultimately deteriorates on the tasks that are potentially relevant. On the other end of the spectrum, model-free methods learn by only predicting future values. By avoiding the potentially impossible task of explicitly modeling the environment, model-free methods can often achieve substantially better performance in complex environments. However, this comes at the cost of extreme sample inefficiency, as only predicting rewards throws away useful information contained in the sequences of future observations.

What is the right way to incorporate information from different trajectories? In this paper we take a step back: Instead of trying to answer this question ourselves by hand-designing what information should be taken into consideration and how, we let a model *learn* how to make use of the data. Depending on what works well within the setting, the model should learn *if and how* to learn from the trajectories available at training time. We will adopt a student-teacher setting, where a *teacher* networks learns to interpret the trajectories, and guides a student by supervising its activations. A sketch of our approach can be found in Figure 1, next to prototypical computational graphs used to integrate trajectory information in most model-free and model-based methods.

Contributions The main contribution of this paper is the proposal of a generic method to extract relevant signal from privileged information. We present an instantiation of this approach called Learning to Interpret Trajectories (LIT) and an empirical analysis of it.

(a) Model-free   (b) Vanilla model-based   (c) Auxiliary task   (d) Teacher

Figure 1: Comparison of architectures. The data generator is a Markov reward process (no actions) with an episode length of n. x denotes the initial observation. $y = \sum_i y_i$ is the n-step return (no bootstrapping). $x^* = (x_1^*, x_2^*, ..., x_n^*)$ is the trajectory of observations (privileged data). Model activations and predictions are displayed boxed. Losses are displayed as red lines. Solid edges denote learned functions. Dotted edges denote fixed functions.

2   RELATED WORK

Efficiently making use of signal from trajectories is an actively researched topic. The technique of bootstrapping in TD-learning (Sutton, 1988) uses future observations to reduce the variance of value function approximations. However, in its basic form, bootstrapping provides learning signal only through a scalar bottleneck, potentially missing out on rich additional sources of learning signal. Another approach to extract additional training signal from observations is the framework of Generalized Value Functions (Sutton et al., 2011), which has been argued to be able to bridge the gap between model-free and model-based methods as well. A similar interpretation can be given to the technique of successor representations (Dayan, 1993).

A number of methods have been proposed that try to leverage the strengths of both model-free and model-based methods, among them Racanière et al. (2017), who learn generative models of the environment and fuse predicted rollouts with a model-free network path. In a different line of research, Silver et al. (2017) and Oh et al. (2017) show that value prediction can be improved by incorporating dynamical structure and planning computation into the function approximators. Guez et al. (2019) investigate to what extent agents can learn implicit dynamics models which allow them to solve planning tasks effectively, using only using model-free methods. Similarly to LIT, those models can learn their own utility-based state abstractions and can even be temporally abstract to some extent. One difference of these approaches to LIT is that they use reward as their only learning signal without making direct use of future observations when training the predictor.

The meta-gradient approach presented in this paper can be used more generally for problems in the framework of *learning using privileged information* (LUPI, (Vapnik and Vashist, 2009; Lopez-Paz et al., 2016)), where privileged information is additional context about the data that is available at training time but not at test time. Hindsight information such as the trajectories in a value-prediction task falls into this category.

There are a variety of representation learning approaches which can learn to extract learning signal from trajectories. Jaderberg et al. (2016) demonstrate that the performance of RL agents can be improved significantly by training the agent on additional prediction and control tasks in addition to the original task. Du et al. (2018) use gradient similarity as a means to determine whether an auxiliary loss is helpful or detrimental for the downstream task. Oord et al. (2018) introduce a method based on contrastive learning. They, as well as multiple follow-up studies, show that the representations learned in this way are helpful for downstream tasks in a variety of settings.

Buesing et al. (2018) present ways to learn efficient dynamical models which do not need to predict future observations at inference time. Recently, Schrittwieser et al. (2019) introduced an RL agent that learns an abstract model of the environment and uses it to achieve strong performance on several challenging tasks. Similarly to our motivation, their model is not required to produce future observations. Meta-learning approaches have recently been shown to be successful as a technique to achieve fast task adaptation (Finn et al., 2017), strong unsupervised learning (Metz et al., 2019), and to improve RL (Xu et al., 2018). Similar to this paper in motivation is the recent work by Guez et al. (2020) which also investigates how privileged hindsight information can be leveraged for value estimation. The difference to LIT is how the trajectory information is incorporated. Their approach has the advantage of not needing second-order gradients. At the same time, LIT naturally avoids the problem of the label being easily predictable from the hindsight data — the teacher is trained to present it to the student in such a way that it empirically improves the student's performance on held-out data. Veeriah et al. (2019) use meta-gradients to derive useful auxiliary tasks in the form of generalized value functions. In contrast, we use a teacher network that learns to provide target activations for a student neural network based on privileged information.

3 META-LEARNING A DYNAMICS TEACHER

Here we describe our approach of jointly learning a teacher and a student.[1] While our approach applies to the generic setting of *learning using privileged information* (Vapnik and Vashist, 2009), here we will focus on the special case of a prediction task with an underlying dynamical system.

3.1 LEARNING TASK

We are considering learning problems in which we have to make a prediction about some property of the future state of a dynamical system, given observations up to the current state. Our method particularly applies to systems in which both the function that relates the current observation to the label as well as the function that predicts the next observation from the current one are hard to learn, making it difficult for both model-free and model-based methods respectively.

The input $x \in \mathcal{X}$ of our learning task is some observation of the system state $s_t \in \mathbf{S}$ before and including time step[2] $t \in \mathbb{Z}$. The system is governed by an unknown dynamical law $f : \mathbf{S} \to \mathbf{S}$. The prediction target $y \in \mathcal{Y}$ is some function of a future state $s_T = f^T(s_t)$, separated from t by $T - t$ time steps, $y = g(s_T)$. Note that T could vary from one example to the next. In addition to the initial observation, we have access to the trajectory $x^* = (x_\tau)_{\tau=t+1..T}$ at training (but not test) time.

3.2 SUPERVISION OF INTERNAL ACTIVATIONS

A straightforward approach to solve the learning task which takes into account the trajectory information, would be to train a state-space-model (SSM) $\hat{f}$, consisting of a dynamical model and a decoder. The SSM is trained to maximize the likelihood of the observed trajectories in the training set, conditioned on the observed initial observation. Ideally, the induced $\hat{f}$ closely resembles f, such that at test time, we can use it to generate an estimate of the rollout and infer the label from it. A potential drawback of this approach is that learning a full SSM could be more difficult than necessary. There may be many details of the dynamics that are both difficult to model and unimportant for the classification tasks. One example for this is the precise timing of events. As argued by Neitz et al. (2018); Jayaraman et al. (2019), there are situations in which it is easy to predict a sequence of events where each event follows a previous one, but hard to predict the exact timing of those events. Moreover, an SSM typically requires rendering observations at training time, which may be difficult to learn and computationally expensive to execute.

We propose to relax the requirement of fitting the dynamics precisely. The teacher can decide to omit properties of the observations that are not needed and omit time steps that can be skipped. It could also change the order of computation and let the student compute independently evolving sub-mechanisms sequentially, even if they evolved in parallel in the actual data generating process.

---

[1] Note that the *teacher* in our task is not an exact copy of the student network as in related work (such as Learning to Remember from a Multi-Task Teacher), but can have a completely different architecture.

[2] For simplicity, our dynamical system is time-discrete, but this assumption is not important for what follows.

Figure 2: Visualization of the LIT framework for the special case of $n = 1$. Circled nodes are part of the dataset. x denotes the input, x^* is the privileged data, y is the label. $\mathcal{S}$ is the student network with parameters θ, $\mathcal{T}$ is the teacher network with parameters ϕ.

In addition to potentially simplifying the learning problem, this could have the additional benefit of gaining computational efficiency. For example, modeling detailed pixel observations may be computationally wasteful, as argued by Buesing et al. (2018) and Oord et al. (2018).

3.3 STUDENT-TEACHER SETUP

We propose a student-teacher setup with two neural networks, as shown in Figure 2. The *student network* $\mathcal{S}$, parameterized by weights θ, is the network that attempts to predict the quantity of interest y (for instance a cumulative reward or value). Its input is $x \in \mathcal{X}$, and its output is $\mathcal{S}(x) = \hat{y} \in \mathcal{Y}$. In computing $\hat{y}$, it produces a sequence of internal activations $(h_1, ..., h_N)$, one for each of its N hidden layers. Each h_k is a vector whose size is the number of neurons of the corresponding hidden layer. The student's goal is to minimize the generalization loss $\mathbb{E}_{x,y \sim P_{\text{test}}}[\mathcal{L}_y(S(x), y)]$ for some loss function $\mathcal{L}_y : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}$.

The *teacher network* $\mathcal{T}$, parametrized by weights ϕ, is only used at training time, not at test time. It reads the observations of the rollout $x^* = (x_\tau)_{\tau=t+1..T}$ corresponding to the current training example, and outputs supervision signals $(h_1^*, ..., h_N^*)$.

The target activations produced by the teacher's supervision result in another loss for the student, the *teaching loss*, defined as $L_h = \sum_k a_k \mathcal{L}_h(h_k, h_k^*)$. Note that h_k and h_k^* are not required to have the same dimensionality, and $\mathcal{L}_h$ combine the two arguments in any way. For example, in our specific instantiation described in Section 4, h^* contains masking weights to gate the teaching signal. The total student training loss is $L_{\text{train}} = \alpha L_h + L_y$, where L_y is the *label loss*, e.g. the cross-entropy error between predictions and true labels. $\alpha \in \mathbb{R}^+$ is the *teaching coefficient*, a coefficient weighting the losses against each other.

3.4 TRAINING THE TEACHER USING META-GRADIENTS

We train the teacher's weights ϕ using the the technique of *meta-gradient optimization*. This is done as follows: At the beginning of training, we split the dataset into a training and a validation set[3]. This split is kept during the entire duration of training. The split ratio is a hyperparameter.

The student's weights θ are updated n times using Stochastic Gradient Descent on randomly sampled training batches, resulting in updated weights θ_n. The student $\mathcal{S}$ is then evaluated on a validation set, producing a validation loss L_{val}. This validation loss is *optimized by the teacher*. This validation loss does not contain a term for the internal activation loss, but consists only of the label-loss $\mathcal{L}(\mathcal{S}(x_{val}), y_{val})$. The teacher is optimized via the meta-gradient

$$\frac{\mathrm{d}L_{val}}{\mathrm{d}\phi} = \frac{\partial \mathcal{L}}{\partial \hat{y}}(\mathcal{S}(x_{val}; \theta_n), y_{val}) \frac{\partial \mathcal{S}}{\partial \theta}(x_{val}; \theta_n) \frac{\mathrm{d}\theta_n}{\mathrm{d}\phi} \tag{1}$$

where x_{val} and y_{val} are the inputs and targets from the validation set.

---

[3]Note that the validation set is separate from the *test set*, which is an independently sampled dataset used only to evaluate the generalization performance of all methods.

We omit the summation over individual loss components to avoid cluttering the notation. The crucial quantity $\frac{d\theta_n}{d\phi}$ describes how the final student's weights θ_n depend on the teachers weights ϕ. It can be computed in linear computation time and space in the number of steps in the inner optimization loop using automatic differentiation[4]. The meta-gradient is then used for one step of stochastic gradient descent of the teacher's weights ϕ. The student's weights are reset to what they were at the beginning of the step, since θ_n was only a hypothetical parameterization used to determine the meta-gradient. Then, the student is actually trained using the newly updated teacher for a certain number of steps. In our experiments, every step of meta-training is followed by N steps of training the student's weights where N is a hyperparameter. Alg. 1 describes the teacher update formally.

Algorithm 1 Teacher update

Require: θ : Student parameters
Require: ϕ : Teacher parameters
Require: η : Inner-loop learning rate
Require: α : Teaching coefficient
Require: n : Number of inner-loop steps
1: $\theta_0 \leftarrow \theta$ $\triangleright$ θ is unchanged in teacher update
2: **for** i in $\{1..n\}$ **do**
3:      $x, x^*, y \leftarrow$ next training batch
4:      $\hat{y}, h \leftarrow \mathcal{S}(x; \theta_i)$
5:      $h^* \leftarrow \mathcal{T}(x^*; \phi)$
6:      $L_h \leftarrow \mathcal{L}_h(h, h^*)$
7:      $L_y \leftarrow \mathcal{L}_y(\hat{y}, y)$
8:      $L_{\mathrm{train}} \leftarrow L_y + \alpha L_h$
9:      $\theta_i \leftarrow \mathrm{SGD}(\theta_{i-1}, L_{\mathrm{train}}, \eta)$
10: $x_{\mathrm{val}}, y_{\mathrm{val}} \leftarrow$ validation data
11: $L_{\mathrm{val}} \leftarrow \mathcal{L}_y(\mathcal{S}((x_{\mathrm{val}}; \theta_n), y_{\mathrm{val}})$
12: Update ϕ to reduce L_{val} $\triangleright$ Eq. 1

---

4 EXPERIMENTS

We implemented LIT in PyTorch (Paszke et al., 2019) using *higher* by Grefenstette et al. (2019). Note that in all experiments, we distinguish between a *validation set* and a *test set*. The validation set is used to train the teacher's parameters. Therefore, in order to allow for fair comparison with non-meta-learning baselines, we train baselines with the full training set and for LIT we split this set into a training and a validation portion. The test set is separate from the validation set and is used only passively to track generalization metrics.

4.1 TOY EXAMPLE

Before moving on to datasets with actual trajectories, we test whether the teacher can learn to make use of privileged information in a simplified setting. We set up a toy task that illustrates the problem, and we design it in such a way that it is very sample inefficient to predict the correct label y by completely ignoring the privileged information x^* (due to the problem being severely under-specified), but at the same time it is not possible to learn a direct deterministic mapping from x to x^*. Our hypothesis is that the teacher should be able to learn to interpret the information in x^*, and use it to guide the student towards a robust explanation in terms of x that works well on the validation data.

The data is constructed as follows: Inputs x are sampled randomly from a D-dimensional multivariate normal distribution with zero mean and variances 1, $x \sim \mathcal{N}(0, 1)$. Each label is computed by first transforming the corresponding input vector x into a two-dimensional vector with a fixed random matrix $W \in \mathbb{R}^{D \times 2}$ (whose entries are sampled from the He-uniform initialization): $h = Wx$. The corresponding label is then computed as $y = \mathbf{I}[h_1 > 0] \oplus \mathbf{I}[h_2 > 0]$ where $\oplus$ denotes the logical XOR operation. In plain language, the label is computed by a random linear transformation of the input into a two-dimensional space, followed by a XOR decision boundary. Additionally, the training data also contains privileged views x^* of the hidden vector h. These views are computed by sampling, for each component h_i of the hidden representation a factor $s_i \in \{-1, 1\}$ with equal probability, and constructing the view as follows: $x^* = [s_1, \ s_2, \ s_1 h_1, \ s_2 h_2]$.

The straightforward strategy of learning a deterministic model that predicts the training data would not work because the conditional expectation of the privileged data, $\mathbb{E}[x^*|x] = 0$ for all x. At the same time, the information about h is fully contained in x^*: The conditional entropy $H(h|x^*) = 0$. A teacher can in principle transform x^* into a hidden representation that helps the student learn more efficiently.

---

[4]See Baydin et al. (2018) for a survey of Automatic Differentiation in Machine Learning.

We perform an experiment over a grid of values for D and n, where n is the number of training examples in the dataset. The range of values for D is the set $\{64, 128, 256, 512\}$. The range of values for n are 16 exponentially-spaced integers between 128 and 1024. The student is a multi-layer-perceptron (MLP) with 32 and 128 neurons in the hidden layers, respectively. The architecture mirrors the data-generating process with a bottleneck after the first linear transformation - in particular, there is no activation function after the first hidden layer. We set up a baseline without a teacher, letting the student learn to predict y from x. For the teacher $\mathcal{T}$ in LIT, we use an MLP with $[256, 256]$ neurons in the hidden layers, ReLU activations, and an output size of 32, matching the size of the student's first hidden layer. The teaching loss is the mean squared error between the teacher's output and the student's first hidden activation. We use Adam with a learning rate of 10^{-3} as the optimizer for the student in both methods. For LIT, we use a validation split of 0.5.

Results Figure 3 shows that the teacher in LIT uses the privileged information to guide the student towards the right solution with significantly better sample efficiency than the unguided student.

Figure 3: Test accuracies in the toy task for different combinations of training set size and input dimensionality. We report the maximum test accuracy over the course of training, averaged over 5 random seeds. Left: A Neural Network without access to privileged information. Right: The same Neural Network using LIT to learn how to interpret the privileged information.

4.2 GAME OF LIFE

We performed an additional experiment aimed at evaluating whether LIT can help to extract dynamical information from trajectories. For that reason we created a dataset based on the cellular automaton Game of Life by Conway. Input is a random initial state x, output is the state of one particular cell after n evolution steps. The privileged data x^* consists of the trajectory of n states after the first one. To make the task more difficult, x^* is temporally permuted randomly, but consistently across examples. A detailed description is provided in Appendix C. As shown in Fig. 4, LIT can learn to interpret the scrambled trajectory and help the student learn with less data than a model-free method.

Figure 4: A datapoint in the Game-of-Life task (left) and the results of the experiment (right).

4.3 MUJOCO

In order to evaluate whether LIT can improve learning efficiency in continuous control tasks, we set up a prediction task using the MuJoCo simulator (Todorov et al., 2012). As an objective we choose learning an n-step reward model: such a model has to predict the sum of rewards along a trajectory of n steps, given only access to the current state and n (open-loop) actions. We fix $n = 16$ in all experiments.

We collect a dataset of size 4000 for each of the environments Swimmer-v2, Walker2d-v2, Hopper-v2, and HalfCheetah-v2. For each training example, the input $x = (s_t, a_{t:t+n})$ contains both an initial state and an action sequence. The initial state s_t is obtained by executing a random policy for a short number of time steps after resetting the simulator. The action sequence $a_{t:t+n}$ consists of random actions. The label y is the cumulative return of exectuting actions $a_{t:t+n}$ in state s_t. See Appendix B.2 for more details on the dataset.

Figure 5: Test losses for the MuJoCo reward prediction task. Evolution of mean squared error between predicted and true normalized n-step reward on a held-out test set. We ran each configuration with 8 different random seeds and show the aggregated curves.

Models   We evaluate the following methods:

- **Model Free (MF)**: This baseline resembles the architecture shown in Fig. 1a. We use a five-layer fully connected MLP with ReLU activations and 128 neurons per layer. This baseline is trained with x as input and y as output.

- **Auxiliary task (Aux)**: As shown in Fig. 1c, this baseline augments the model-free method with an auxiliary task-head, which is trained to fit the full trajectory x^* in order to shape the model's internal representation.

- **LIT**: Using the same MLP architecture as in the model-free baseline for the student, LIT additionally uses a teacher, which uses a network with a 1D-convolutional torso and an MLP-head to embed the trajectory x^* and provide training signals for the student activations. The teaching loss is a gated mean squared error $L_h \propto \sum_k \sigma(m_k)(h_k - h_k^*)^2$, where σ is the logistic sigmoid function, m and h^* are the outputs by the teacher, and h are the student's internal pre-activations.

For all networks we follow Schrittwieser et al. (2019) in how we turn the regression task of predicting rewards into a classification task by binning the reward space (see Appendix for details). Hyperparameters for each method are optimized independently (see Appendix for ranges) for each method and task. We select the configuration with the lowest mean-squared-error on test data and re-run it 8 times with different random seeds.

Results   In Figure 5 we report the mean squared error between predicted and true cumulative reward. The student trained with LIT achieved lower MSE than both the MF and Aux baselines in all tasks. Moreover, we found the *generalization gap* to be significantly smaller for LIT (Figure 6). This can be explained as follows: If the student is overfitting to the training set, its performance will degrade on the validation set. Since this loss only affects the teacher, the teacher can provide teaching targets h^* that steer the student away when it starts to severely overfit to the training data.

We acknowledge that there could be strong baselines from the literature that we have not considered. Many of these approaches have complex pipelines of operations (e.g. Chua et al. (2018)), or use domain-specific knowledge to extract good representations (e.g. CPC (Oord et al., 2018)). As the main point of this paper is to investigate and understand a new framework to incorporate trajectory information, we decided to keep our evaluation setting simple and consistent, e.g. by using the same student architecture for *all* models.

Figure 6: Generalization gaps (Test-set MSE minus Training-set MSE) for the different approaches and domains.)

4.4 ABLATIONS

We perform several ablation studies, in order to test the role of every component in our set-up. We describe every experiment set-up and show the results for the environment Walker2d in Figure 7. Results for the other environments are shown in Appendix B.2.4

(i) *Fixed untrained teacher (FT):* we keep the teacher weights fixed to the initial random weights. Using no meta-gradient updates, the student essentially fails to learn, validating the need for learning how to interpret the trajectories.

(ii) *Time-permuted x^* (PT)*: we independently and randomly permute the time order of x^* for each example. Interestingly, the performance only degrades slightly. Two possible interpretations of this result are the following: either the teacher architecture does not make sufficient use of the temporal structure, or this structure is not so relevant for the task. Since we did not heavily tune our teacher network, we tend to lead towards the first explanation.

(iii) *Random x^* (RT-n)*: each entry of the last n frames of all trajectories x^* are replaced by noise sampled i.i.d. from $\mathcal{N}(0, 1)$. When the trajectories are completely irrelevant to the task, the teacher can in principle learn to ignore them. However, since LIT trains with a smaller effective training set (because a portion is split off for validation), we expect a slightly weaker performance. Indeed, the results show that LIT with fully randomized trajectories (RT-16) tends to be comparable to, but slightly worse than the model-free network.

(iv) *Same train and valid data (AR):* instead of fixing the split of the training data into disjoint subsets for the student and for the teacher, we resample the split after every step of meta-training. Results show that the performance is even slightly worse than the model-free baseline. This is consistent with expectations, as the teacher's loss can be minimized directly by the student in training.

5 CONCLUSION

In this paper, instead of proposing a new hand-designed strategy to incorporate information from previous trajectories, we proposed to let a model *learn if and how* to use them. A teacher network learns to interpret a trajectory, and distills targets activations for a student network that only sees the current observation. The teacher is rewarded for maximizing the student performance on validation data, but can only achieve this indirectly by supervising the student while it trains on the training data. As validated empirically by the experiments and ablations presented in Section 4, this framework allows the model to choose where to sit in the wide spectrum

Figure 7: Ablation study results

between model-based and model-free methods, adapting to the specifics of the task at hand. An obvious drawback of LIT is — like many algorithms that learn how to learn — that computing meta-gradients increases the time and space complexity at training time by a factor that is linear in the number of inner steps. However, the computational cost of the student at test time is exactly the same as for an equivalent student that did *not* make use of the privileged information at training time, as the teacher does not play any role and can be discarded.

We believe that the general framework of teacher-student trained with meta-gradients to incorporate privileged information can be a fruitful direction for future work, beyond learning from trajectories. As the main limitation is the linear increase in time and space complexity at training time, increases in computing power should allow for more and more complex teachers and students to be trained on large tasks.

REFERENCES

A. G. Baydin, B. A. Pearlmutter, A. A. Radul, and J. M. Siskind. Automatic differentiation in machine learning: a survey. *Journal of Machine Learning Research*, 18(153):1–43, 2018. URL `http://jmlr.org/papers/v18/17-468.html`.

J. Bergstra, R. Bardenet, Y. Bengio, and B. Kégl. Algorithms for hyper-parameter optimization. In *Proceedings of the 24th International Conference on Neural Information Processing Systems*, NIPS'11, page 2546–2554, Red Hook, NY, USA, 2011. Curran Associates Inc. ISBN 9781618395993.

G. Brockman, V. Cheung, L. Pettersson, J. Schneider, J. Schulman, J. Tang, and W. Zaremba. Openai gym, 2016.

L. Buesing, T. Weber, S. Racaniere, S. Eslami, D. Rezende, D. P. Reichert, F. Viola, F. Besse, K. Gregor, D. Hassabis, et al. Learning and querying fast generative models for reinforcement learning. *arXiv preprint arXiv:1802.03006*, 2018.

K. Chua, R. Calandra, R. McAllister, and S. Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems 31*, pages 4754–4765. Curran Associates, Inc., 2018.

P. Dayan. Improving generalization for temporal difference learning: The successor representation. *Neural Comput.*, 5(4):613–624, July 1993. ISSN 0899-7667. doi: 10.1162/neco.1993.5.4.613. URL `https://doi.org/10.1162/neco.1993.5.4.613`.

Y. Du, W. M. Czarnecki, S. M. Jayakumar, R. Pascanu, and B. Lakshminarayanan. Adapting auxiliary losses using gradient similarity. *arXiv preprint arXiv:1812.02224*, 2018.

C. Finn, P. Abbeel, and S. Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In D. Precup and Y. W. Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 1126–1135, International Convention Centre, Sydney, Australia, 06–11 Aug 2017. PMLR. URL `http://proceedings.mlr.press/v70/finn17a.html`.

E. Grefenstette, B. Amos, D. Yarats, P. M. Htut, A. Molchanov, F. Meier, D. Kiela, K. Cho, and S. Chintala. Generalized inner loop meta-learning. *arXiv preprint arXiv:1910.01727*, 2019.

A. Guez, M. Mirza, K. Gregor, R. Kabra, S. Racaniere, T. Weber, D. Raposo, A. Santoro, L. Orseau, T. Eccles, G. Wayne, D. Silver, and T. Lillicrap. An investigation of model-free planning. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 2464–2473, Long Beach, California, USA, 09–15 Jun 2019. PMLR. URL `http://proceedings.mlr.press/v97/guez19a.html`.

A. Guez, F. Viola, T. Weber, L. Buesing, S. Kapturowski, D. Precup, D. Silver, and N. Heess. Value-driven hindsight modelling. *arXiv preprint arXiv:2002.08329*, 2020.

S. Ioffe and C. Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *Proceedings of the 32nd International Conference on International Conference on Machine Learning - Volume 37*, ICML'15, page 448–456. JMLR.org, 2015.

M. Jaderberg, V. Mnih, W. M. Czarnecki, T. Schaul, J. Z. Leibo, D. Silver, and K. Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. *arXiv preprint arXiv:1611.05397*, 2016.

D. Jayaraman, F. Ebert, A. Efros, and S. Levine. Time-agnostic prediction: Predicting predictable video frames. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=SyzVb3CcFX`.

D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. In Y. Bengio and Y. LeCun, editors, *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL `http://arxiv.org/abs/1412.6980`.

D. Lopez-Paz, B. Schölkopf, L. Bottou, and V. Vapnik. Unifying distillation and privileged information. In *International Conference on Learning Representations (ICLR)*, Nov. 2016.

L. Metz, N. Maheswaranathan, B. Cheung, and J. Sohl-Dickstein. Learning unsupervised learning rules. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=HkNDsiC9KQ`.

A. Neitz, G. Parascandolo, S. Bauer, and B. Schölkopf. Adaptive skip intervals: Temporal abstraction for recurrent dynamical models. In *Advances in Neural Information Processing Systems*, pages 9816–9826, 2018.

J. Oh, S. Singh, and H. Lee. Value prediction network. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems 30*, pages 6118–6128. Curran Associates, Inc., 2017. URL `http://papers.nips.cc/paper/7192-value-prediction-network.pdf`.

A. v. d. Oord, Y. Li, and O. Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Kopf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019.

S. Racanière, T. Weber, D. Reichert, L. Buesing, A. Guez, D. Jimenez Rezende, A. Puigdomènech Badia, O. Vinyals, N. Heess, Y. Li, R. Pascanu, P. Battaglia, D. Hassabis, D. Silver, and D. Wierstra. Imagination-augmented agents for deep reinforcement learning. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems 30*, pages 5690–5701. Curran Associates, Inc., 2017. URL `http://papers.nips.cc/paper/7152-imagination-augmented-agents-for-deep-reinforcement-learning.pdf`.

T. Salimans and D. P. Kingma. Weight normalization: A simple reparameterization to accelerate training of deep neural networks. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems 29*, pages 901–909. Curran Associates, Inc., 2016.

J. Schrittwieser, I. Antonoglou, T. Hubert, K. Simonyan, L. Sifre, S. Schmitt, A. Guez, E. Lockhart, D. Hassabis, T. Graepel, et al. Mastering atari, go, chess and shogi by planning with a learned model. *arXiv preprint arXiv:1911.08265*, 2019.

D. Silver, H. van Hasselt, M. Hessel, T. Schaul, A. Guez, T. Harley, G. Dulac-Arnold, D. Reichert, N. Rabinowitz, A. Barreto, and T. Degris. The predictron: End-to-end learning and planning. In D. Precup and Y. W. Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 3191–3199, International Convention Centre, Sydney, Australia, 06–11 Aug 2017. PMLR. URL `http://proceedings.mlr.press/v70/silver17a.html`.

F. P. Such, A. Rawal, J. Lehman, K. O. Stanley, and J. Clune. Generative teaching networks: Accelerating neural architecture search by learning to generate synthetic training data. *arXiv preprint arXiv:1912.07768*, 2019.

R. S. Sutton. Learning to predict by the methods of temporal differences. *Mach. Learn.*, 3(1):9–44, Aug. 1988. ISSN 0885-6125. doi: 10.1023/A:1022633531479. URL `https://doi.org/10.1023/A:1022633531479`.

R. S. Sutton, J. Modayil, M. Delp, T. Degris, P. M. Pilarski, A. White, and D. Precup. Horde: A scalable real-time architecture for learning knowledge from unsupervised sensorimotor interaction. In *The 10th International Conference on Autonomous Agents and Multiagent Systems - Volume 2*, AAMAS '11, page 761–768, Richland, SC, 2011. International Foundation for Autonomous Agents and Multiagent Systems. ISBN 0982657161.

E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. In *IROS*, pages 5026–5033. IEEE, 2012. ISBN 978-1-4673-1737-5.

V. Vapnik and A. Vashist. A new learning paradigm: Learning using privileged information. *Neural networks*, 22(5-6):544–557, 2009.

V. Veeriah, M. Hessel, Z. Xu, J. Rajendran, R. L. Lewis, J. Oh, H. P. van Hasselt, D. Silver, and S. Singh. Discovery of useful questions as auxiliary tasks. In H. Wallach, H. Larochelle, A. Beygelzimer, F. dAlché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 9310–9321. Curran Associates, Inc., 2019. URL `http://papers.nips.cc/paper/9129-discovery-of-useful-questions-as-auxiliary-tasks.pdf`.

Z. Xu, H. P. van Hasselt, and D. Silver. Meta-gradient reinforcement learning. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems 31*, pages 2396–2407. Curran Associates, Inc., 2018. URL `http://papers.nips.cc/paper/7507-meta-gradient-reinforcement-learning.pdf`.

A IMPLEMENTATION DETAILS

We implemented Meta-LUPI using PyTorch (Paszke et al., 2019) and used the library *higher* (Grefenstette et al., 2019) to compute meta-gradients.

Our implementation of LIT contains a number of hyperparameters and settings which we describe here.

- **Inner-loop optimizer**: The optimizer used on the student's weights θ_k in the inner loop of determining the meta-gradient (includes **inner learning rate** and **inner momentum**)
- **Student optimizer**: The optimizer used to actually update the student's weights θ. (Includes **student learning rate** and **student momentum**)
- **Meta-optimizer**: The optimizer used to optimize the teacher's weights ϕ. (Includes **meta learning rate** and **meta momentum**)
- **Validation split**: The fraction of the training set that is used to compute the meta-loss.
- **Teacher architecture**: The architecture of the teacher network.

B EXPERIMENT DETAILS

B.1 TOY DATASET

All details regarding the toy dataset and experiment were described in the main text.

B.2 MUJOCO

We now describe additional details for the MuJoCo reward-prediction experiments.

B.2.1 DATASET DETAILS

The datasets for the MuJoCo reward prediction task are generated as follows.

We use the MuJoCo environments implemented in OpenAI gym Brockman et al. (2016), Each training set consists of 4000 examples generated as follows.

- Reset the environment to an initial state drawn from the initial-state-distribution
- Sample an integer n uniformly from the range $\{10..30\}$
- Perform n steps following random policy π.
- Record the current state s.
- Sample a 16 step open-loop action sequence $a_{1:16}$ from π.
- Set the example's input $x = (s, a_{1:16})$
- Execute $a_{1:16}$ starting from the current state s
- Record the trajectory of states $s_{1:16}$ and rewards $r_{1:16}$ as privileged data x^*
- Record the sum of rewards as label $y = \sum_t r_t$

As random policy π we choose the policy that ignores the state and at each step and for each action dimension, samples one of the numbers $\{-1, 0, 1\}$ with equal probability, independently of each other.

We did not investigate the effects of using a different policy π to generate the dataset.

The test sets consist of 10k examples distributed identically to their respective training sets.

Similarly to Schrittwieser et al. (2019) we turn the regression task of predicting rewards into a classification task by binning the reward space. We first obtain a transformation $\psi : \mathbb{R} \to [0, 1]$ in such a way that it transforms training rewards to a uniform distribution in $[0, 1]$, interpolating linearly in-between values from the training set and clipping values outside the training-reward-range to

lie between 0 and 1. We apply this transformation to both training and test labels and afterwards distribute the resulting values into 32 equally spaced bins between 0 and 1 to obtain categorical values. This leads to an even label distribution on the training set, and a roughly-even distribution on the test set. The label-loss-function is then the cross-entropy between predicted label probabilities and the one-hot distribution of the true label. The normalized mean-squared-error reported in the curves is obtained by first obtaining the expected value of the prediction by weighting the output-bucket with the predicted probability and then determining the squared difference to the true bucket value between 0 and 1.

Before training, we standardize all inputs along the dimensions individually, using empirical means and standard deviations found in the training set. Each state along the trajectory is standardized with the same normalization parameters.

B.2.2 CHOOSING HYPERPARAMETERS

In order to determine good general ranges of hyperparameters[5], we first performed manual hyperparameter investigations and used a Tree-structured Parzen Estimator (Bergstra et al., 2011) search to find good ranges for the hyperparameters. Hyperparameter searches are performed using different random seeds from the final evaluation in order to reduce overfitting due to the hyperparameter-optimization. The curves for LIT shown in Figure 5 are the result of re-running the best hyperparameter configurations eight times with different random seeds. The curves for the baselines are obtained by performing a grid search on the hyperparameters shown in Tables 1 and 2, selecting the configuration that yielded the lowest test-MSE at any point in training and re-running it eight times with different random seeds.

We fix as architecture for the prediction model (the student in the LIT framework) a five-layer fully connected MLP with ReLU activations and 128 neurons per layer.

LIT parameters   Tables 4 and 5 show hyperparameters we determined to work well for the MuJoCo reward prediction task.

As optimizers for the teacher and student weights, we use Adam (Kingma and Ba, 2015). For the inner-loop student-optimizer we use SGD with momentum.

As the teacher network we use a 1D-convolutional Neural Network followed by a fully connected network as follows: The 16 states of the trajectory x^* (including rewards at every step) are fed into n_{conv} 1D-convolutional layers, each followed by a ReLU activation. The first $n_{conv} - 1$ convolutional layers have c_1 output-channels, the last one has c_2 output-channels. The output of the last convolutional layer is flattened and fed into a fully connected downstream model with one layer of c_3 neurons.

In our experiments we found that it did not help to feed the actions along the trajectory to the teacher (additionally to the student who always gets to see the actions).

The output of the teacher is a vector that contains two entries for every neuron in the student network. One of these values, h_k^*, is the target-pre-activation, and m_k is a gating parameter to weight that particular neuron's loss. We found it helpful to scale and shift the input to the gating-sigmoid by two constant scalars that are used for the entire network: the loss for a given pre-activation is computed as $\sigma(\frac{m_k}{2} - 1)(h_k - h_k^*)^2$, where σ is the logistic sigmoid function, h_k is the pre-activation in the student's network, h_k^* is the target activation given by the teacher, and m_k is the gating signal output by the teacher.

We use batch-normalization (Ioffe and Szegedy, 2015) in the teacher network and weight-normalization (Salimans and Kingma, 2016) in the student network, following the findings of Such et al. (2019).

As a precaution against exploding meta-gradients, we clip each component of the meta-gradient to the range $[-1e8, 1e8]$, but did not investigate whether this was necessary.

---

[5]By *hyperparameters* we mean those parameters which are fixed over the course of a training run. They do not consist of the teacher's *meta-parameters*.

Table 1: Hyperparameter ranges for the method 'model-free' (MF)

Hyperparameter	Range
Learning rate	$\{1e{-}3, 1e{-}2\}$
Weight decay	$\{0, 1e{-}5, 1e{-}4\}$
Batch size	$\{8, 16, 32\}$

Table 2: Hyperparameter ranges for the method 'auxiliary' (AUX)

Hyperparameter	Range
Learning rate	$\{1e{-}3, 1e{-}2\}$
Weight decay	$\{0, 1e{-}5, 1e{-}4\}$
Auxiliary task weight	$\{1, 2, 4\}$

Table 3: Hyperparameter ranges for our proposed method (LIT)

Hyperparameter	Range
β_1 of Meta-optimizer (Adam)	$\{0.0, 0.9\}$
Learning rate of Inner-loop optimizer (SGD)	$\{1e{-}3, 5e{-}3, 1e{-}2\}$
Teaching coefficient ($\log_{10}$)	$\{2.0, 2.5, 3.0\}$
Validation split	$\{0.3, 0.5, 0.7\}$

Table 4: Best hyperparameters found in grid search for LIT

Hyperparameter	Swimmer-v2	Walker2d-v2	Hopper-v2	HalfCheetah-v2
β_1 of Meta-optimizer (Adam)	0.9	0.9	0.0	0.0
Learning rate of Inner-loop optimizer (SGD)	$1e{-}2$	$1e{-}2$	$1e{-}2$	$1e{-}2$
Teaching coefficient ($\log_{10}$)	2.5	3.0	2.5	2.5
Validation split	0.3	0.5	0.3	0.7

Table 5: Other hyperparameters for LIT (all environments)

Hyperparameter	Value (all envs)
Learning rate of Meta-optimizer (Adam)	$5e{-}4$
Learning rate of Student-optimizer (Adam)	$1e{-}3$
Batch size	24
Momentum of inner-loop optimizer (SGD)	0.75
Weight decay (L2) coefficient in inner-loop	$1e{-}8$
Number of inner-loop steps (n_{inner})	96
Teacher c_1	96
Teacher c_2	256
Teacher c_3	768
Teacher n_{conv}	4
Number of student training steps per meta-step	24

Performances   When using the hyperparameters described above, we obtain the minimum test MSEs in the eight evaluation runs shown in Table 6.

B.2.3   MODEL-BASED-BASELINES

A naive implementation of model-based could not fit the data. We trained the model within the same teacher-student framework, with a fixed dummy teacher that supervises the output of the student with the next observation (essentially mimicking a model-based setting). We 'stacked' the student such that it takes as input its output observation on the previous timestep, and by feeding it only

Table 6: Minimum Mean squared errors on all environments

	no-teacher	auxiliary	LIT
HalfCheetah-v2	0.0485	0.0477	**0.0427**
Hopper-v2	0.00270	0.00224	**0.00132**
Swimmer-v2	0.0169	0.0146	**0.00964**
Walker2d-v2	0.0238	0.0211	**0.0164**

Figure 8: All results of ablation studies.

the first observation of the sequence, we supervise all of its intermediate targets. However, without introducing the extra inductive bias of training the student on every step *independently* of the others (instead of a single trajectory), the student's output would tend to diverge as it got deeper into the number of steps.

Training the student on pairs of consecutive transitions independently of the whole trajectory, makes the model work much better. However, making a fair comparison to the model-free, Aux, and LIT students is difficult, since the model-based student effectively uses $n = 16$ times more computation. Note that the main objective of this paper is to compare to what extent the *abstract* models implicitly learned by the *same* student architectures but with different techniques, can learn to incorporate the trajectory information. On this basis, we exclude the model-based baselines from our comparisons.

B.2.4 ABLATION STUDIES

In Figure 8 we present the results of the ablation studies described in Section 4.4.

C GAME OF LIFE EXPERIMENT

Here we provide details about the Game of Life experiment mentioned in Section 4.2.

Dataset   As the underlying dynamical system, we use the cellular automaton *Game of Life* by John Conway. The rules of this cellular automaton are:[6]

1. Any live cell with fewer than two live neighbours dies, as if by underpopulation.
2. Any live cell with two or three live neighbours lives on to the next generation.
3. Any live cell with more than three live neighbours dies, as if by overpopulation.
4. Any dead cell with exactly three live neighbours becomes a live cell, as if by reproduction.

Note that there is no linear decision boundary to determine the next cell state if the input space is the cell's neighborhood. However, with at least one hidden layer, it is possible to implement the rules. We can therefore use a convolutional neural network with $2n$ layers to represent the system's dynamics unrolled over n steps.

We generate a binary classification task from the system as follows.

- A board of size 17×17 is initialized by setting each cell to "alive" with a probability of $p_I = 0.4$, independently of other cells. Alive cells are represented with a 1, all other cells are represented with a 0. This first board state is the input $x \in \{0, 1\}^{17 \times 17}$ for the task.

---

[6]Copied from `https://en.wikipedia.org/wiki/Conway%27s_Game_of_Life`.

- The Game-of-Life rules are applied three times in sequence, yielding three consecutive states
- The classification target is the *middle cell in the last state*, i.e. a binary label
- All intermediate and final states in the trajectory are considered *privileged information*.

The initial alive-probability was chosen such that there typical rollouts are diverse. If the initial configuration is much sparser or much denser, then the population quickly dies off.

Network architecture In early, unstructured experiments it seemed as though 3 layers per step make it easier to train a CNN using internal supervision. Therefore, we fix three convolutional layers per step for all experiments.

The student's internal activations $\mathbf{z}$ are convolutional feature maps. We use $\mathbf{z}_{kl}$ to denote the l'th feature map of the k'th layer. Each $\mathbf{z}_{kl}$ has the same dimensions as the map of the cellular automaton (17×17 in our experiments).

Implementation of the teacher We choose a simple parameterization of the teacher. The teacher's weights are a three-dimensional tensor $\phi \in \mathbb{R}^{T \times N \times F}$, where T is the fixed number of steps in the Game-of-Life trajectory, N is the number of convolutional hidden layers in the student network, and F is the number of feature maps per hidden layer.

The internal activation targets are linear combinations of the cell states in the trajectory $(x_1, ..., x_T)$:

$$h_{kl}^* = \sum_t a_{tkl} x_t \tag{2}$$

where $a_{\bullet kl} = \text{softmax}(\phi_{\bullet kl})$, i.e. the mixture weights are the teacher's weights softmaxed-through-time. More explicitly,

$$a_{tkl} = \frac{\exp(\phi_{tkl})}{\sum_\tau \exp(\phi_{\tau kl})} \tag{3}$$

We use Adam to update the inner weights and vanilla SGD+momentum to update the meta-parameters, as we found these two choices to generally perform best.

Baselines

- **Fixed oracle teacher**: ϕ is initialized to the values such that it provides the frames in the correct sequence to every third convolutional layer. It is held fixed over the course of training.
- **Fixed random teacher**: ϕ is initialized randomly and held fixed over the course of training.
- **No teacher**: Classification task without privileged data

Experimental protocol The questions that this experiment should help answer is: Does meta-gradient training help with sample efficiency in the Game-of-Life task compared to using (a) no teacher, (b) a fixed random teacher?

- Training set sizes: $\{128, 256, 512, 1024, 2048, 4096, 8192\}$, but in order to be resource-efficient, try the approaches from fewer examples to more examples until they "max out".
- Methods: meta-learned teacher (*meta*), fixed random teacher (*fixed-teacher*), perfect teacher (*perfect-teacher*), no teacher (*no-teacher*)
- In meta-learning, the train-validation-split happens within the training set (no additional validation data is provided).
- We use the same hyperparameter ranges for all experiments - ones that seem reasonable based on initial experimentation.
- Train for 192 epochs, or until the test accuracy exceeds 99%.

Hyperparameter	Distribution	Min	Max	Methods
learning_rate	LogUniform	10^{-4}	10^{-2}	all
adam_momentum	1.0 - LogUniform	10^{-1}	10^{0}	all
weight_decay	LogUniform	10^{-8}	10^{-3}	all
batch_size	DiscreteUniform	32	128	all
weight_init_multiplier	LogUniform	0.1	2.0	all
n_filters	DiscreteUniform	16	32	all
internal_coef	LogUniform	10^{2}	10^{4}	meta, fixed-teacher
teacher_weight_scale	LogUniform	10^{-2}	10^{0}	fixed-teacher
teacher_attention_scale	LogUniform	10^{-3}	10^{-1}	fixed-teacher
n_inner	DiscreteUniform	16	32	meta
meta_learning_rate	LogUniform	10^{-6}	10^{-3}	meta
meta_momentum	LogUniform	10^{-2}	10^{0}	meta
validation_split	LogUniform	10^{-2}	10^{0}	meta

Hyperparameter ranges The parameters for the initial teacher weights are used exclusively by the fixed-teacher method.

Note that while the meta-learning approach has more hyperparameters than the baselines, the overall computational budget given to each method is the same - more hyperparameters are not advantageous by default.

We run a hyperparameter search over the specified range for each combination of (method, n-training-examples). As hyperparameter optimization algorithm we use a Tree-structured Parzen Estimator (Bergstra et al., 2011) for each method.