# BnTTS: Few-Shot Speaker Adaptation in Low-Resource Setting

## Abstract

This paper introduces BnTTS (**Ba**ngla **T**ext-**T**o-**S**peech), the first framework for Bangla speaker adaptation-based TTS, designed to bridge the gap in Bangla speech synthesis using minimal training data. Building upon the XTTS architecture, our approach integrates Bangla into a multilingual TTS pipeline, with modifications to account for the phonetic and linguistic characteristics of the language. We pretrain BnTTS on 3.7k hours of Bangla speech dataset with corresponding text labels. Empirical evaluations in few-shot settings show that BnTTS enhances the naturalness, clarity, and speaker fidelity of synthesized Bangla speech. Compared to state-of-the-art Bangla TTS systems, BnTTS demonstrates superior performance in naturalness, clarity and Subjective Mean Opinion Score (SMOS).

## 1 Introduction

Speaker adaptation in Text-to-Speech (TTS) technology has seen substantial advancements in recent years, particularly with speaker-adaptive models enhancing the naturalness and intelligibility of synthesized speech (Eren and Demiroglu, 2023). Notably, recent innovations have emphasized zero-shot and one-shot adaptation approaches (Kodirov et al., 2015). Zero-shot TTS models eliminate the need for speaker-specific training by generating speech from unseen speakers using reference audio samples (Min et al., 2021). Despite this progress, zero-shot models often require large datasets and face challenges with out-of-distribution (OOD) voices, as they struggle to adapt effectively to novel speaker traits (Le et al., 2023; Ju et al., 2024). Alternatively, one-shot adaptation fine-tunes pre-trained models using a single data instance, offering improved adaptability with reduced data and computational demands (Yan et al., 2021; Wang et al., 2023); however, the pretraining stage still necessitates substantial datasets (Zhang et al., 2021).

Recent works such as YourTTS (Bai et al., 2022) and VALL-E X (Xu et al., 2022) have made strides in cross-lingual zero-shot TTS, with YourTTS exploring English, French, and Portuguese, and VALL-E X incorporating language identification to extend support for a broader range of languages (Xu et al., 2022). These advancements highlight the potential for multilingual TTS systems to achieve cross-lingual speech synthesis. Furthermore, the XTTS model (Casanova et al., 2024) represents a significant leap by expanding zero-shot TTS capabilities across 16 languages. Based on the Tortoise model (Casanova et al., 2024), XTTS enhances voice cloning accuracy and naturalness but remains focused on high- and medium-resource languages, leaving low-resource languages such as Bangla underserved (Zhang et al., 2022; Xu et al., 2023).

The scarcity of extensive datasets has hindered the adaptation of state-of-the-art (SOTA) TTS models for low-resource languages. Models like YourTTS Bai et al. (2022), VALL-E X (Baevski et al., 2022a), and Voicebox (Baevski et al., 2022b) have demonstrated success in multilingual settings, yet their primary focus remains on languages with rich resources like English, Spanish, French, and Chinese. While a few Bangla TTS systems exist (Gutkin et al., 2016), they often produce robotic tones (Hossain et al., 2018) or are limited to a small set of static speakers (Gong et al., 2024), lacking instant speaker adaptation capabilities and typically not being open-source.

To address these challenges, we propose the first framework for few-shot speaker adaptation in Bangla TTS. Our approach integrates Bangla into the XTTS training pipeline, with architectural modifications to accommodate Bangla's unique phonetic and linguistic features. Our model is optimized for effective few-shot voice cloning, addressing the needs of low-resource language settings. **Our contributions** are summarized as follows: **(i)** we present the *first* speaker-adapted Bangla TTS

system; **(ii)** we integrate Bangla into a multilingual XTTS pipeline, optimizing the framework to accommodate the unique challenges of low-resource languages; **(iii)** we make the developed BnTTSTextEval evaluation dataset public.

## 2 Related Works

The development of Bangla Text-To-Speech (TTS) technology has faced challenges due to the language's morphological and phonetic complexity. Katha (Alam et al., 2007), the first Bangla TTS system based on diphone concatenation, struggled with natural prosody and efficient runtime. Later systems, such as Subhachan (Naser et al., 2010), aimed to improve these aspects but still encountered issues with diphthongs and consonant-vowel structures (Hossain et al., 2022; Rashid et al., 2010). More recent approaches, including LSTM-RNNs (Gutkin et al., 2016) and syllable-based models (Ahmed and Islam, 2019), have shown improved synthesis performance. An end-to-end Bangla synthesizer (Bhattacharjee et al., 2021) removed the need for G2P conversion, streamlining the process. Statistical parametric speech synthesis (SPSS) methods (Fan et al., 2014) have also demonstrated promise for low-resourced languages. However, challenges persist in achieving fast inference times with high-quality, natural-sounding audio. Recently, Quantization-Aware Training (Krishnamoorthi, 2018) has been applied to enhance Bangla speech quality (Shahjahan et al., 2024).

## 3 BnTTS

Figure 1: Overview of BnTTS Model.

**Preliminaries:** Given a text sequence with $N$ tokens, $\mathbf{T} = \{t_1, t_2, \ldots, t_N\}$, and a speaker's mel-spectrogram $\mathbf{S} = \{s_1, s_2, \ldots, s_L\}$, the objective is to generate speech $\hat{\mathbf{Y}}$ that matches the speaker's characteristics. The ground truth mel-spectrogram frames for the target speech are denoted as $\mathbf{Y} = \{y_1, y_2, \ldots, y_M\}$. The synthesis process can be described as:

$$\hat{\mathbf{Y}} = \mathcal{F}(\mathbf{T}, \mathbf{S})$$

where $\mathcal{F}$ produces speech conditioned on both the text and the speaker's spectrogram.

**Audio Encoder:** A Vector Quantized-Variational AutoEncoder (VQ-VAE) (Betker, 2023) encodes mel-spectrogram frames $\mathbf{Y}$ into discrete tokens $M \in \mathcal{C}$, where $\mathcal{C}$ is vocab or codebook. An embedding layer then transforms these tokens into a $d$-dimensional vector: $\mathbf{Y_e} \in \mathbb{R}^{M \times d}$.

**Conditioning Encoder & Perceiver Resampler:** The Conditioning Encoder (Casanova et al., 2024) consists of $l$ layers of $k$-head Scaled Dot-Product Attention, followed by a Perceiver Resampler. The speaker spectrogram $\mathbf{S}$ is transformed into an intermediate representation $\mathbf{S_z} \in \mathbb{R}^{L \times d}$, where each attention layer applies a scaled dot-product attention mechanism. The Perceiver Resampler generates a fixed output dimensionality $\mathbf{R} \in \mathbb{R}^{P \times d}$ from a variable input length $L$.

**Text Encoder:** The text tokens $\mathbf{T} = \{t_1, t_2, \ldots, t_N\}$ are projected into a continuous embedding space, yielding $\mathbf{T_e} \in \mathbb{R}^{N \times d}$.

**LLM:** The transformer-based LLM (Radford et al., 2019) utilizes the decoder portion. Speaker embeddings $\mathbf{S_p}$, text embeddings $\mathbf{T_e}$, and ground truth spectrogram embeddings $\mathbf{Y_e}$ are concatenated to form the input:

$$\mathbf{X} = \mathbf{S_p} \oplus \mathbf{T_e} \oplus \mathbf{Y_e} \in \mathbb{R}^{(N+P+M) \times d}$$

The LLM processes $\mathbf{X}$, producing output $\mathbf{H}$ with hidden states for the text, speaker, and spectrogram embeddings. During inference, only text and speaker embeddings are concatenated, generating spectrogram embeddings $\{h_1^Y, h_2^Y, \ldots, h_P^Y\}$ as the output.

**HiFi-GAN Decoder:** The HiFi-GAN Decoder (Kong et al., 2020) converts the LLM's output into realistic speech, preserving the speaker's characteristics. Specifically, it takes the LLM's speech head output $\mathbf{H_Y} = \{h_1^Y, h_2^Y, \ldots, h_P^Y\}$. The speaker embedding $\mathbf{S}$ is resized to match $\mathbf{H_Y}$, resulting in

$\mathbf{S}' \in \mathbb{R}^{P \times d}$. The final audio waveform $\mathbf{W}$ is then generated by:

$$\mathbf{W} = g_{\text{HiFi}}(\mathbf{H}_Y + \mathbf{S}')$$

Thus, the HiFi-GAN decoder produces speech that reflects the input text while maintaining the speaker's unique qualities.

## 4 Experiments

**BnTTS model:** BnTTS employs the pretrained GPT-2 from XTTS checkpoint (Casanova et al., 2024) as its base model, chosen for resource efficiency. The Conditioning Encoder has six attention blocks with 32 heads, capturing contextual information. The Perceiver Resampler reduces the sequence to a fixed length of 32. The model maintains GPT-2's dimensionality, with a hidden size of 1024 and an intermediate layer size of 3072, handling sequences of up to 400 tokens. (Details in Appendix C).

**Dataset:** The BnTTS model is trained on 3,860 hours of Bengali speech data sourced from open datasets, pseudo-labeled data, synthetic datasets, and in-house collections. To address the scarcity of high-quality TTS data for Bengali, we developed an automated TTS Data Acquisition Framework that gathers and refines speech data with aligned transcripts using neural speech models and custom algorithms.

For evaluation, we propose two datasets: (1) BnStudioEval, derived from our in-house dataset, to assess high-fidelity speech generation and speaker adaptation, and (2) BnTTSTextEval, a text-only dataset consisting of three subsets designed to evaluate phoneme diversity, named entity pronunciation, and performance in everyday dialogue. Further details are provided in the Appendices A, B.

**Training Setup:** We pretrain the BnTTS model using the AdamW optimizer with betas of 0.9 and 0.96, weight decay of 0.01, and an initial learning rate of 2e-05. The batch size was 12, with gradient accumulation over 24 steps per GPU, and the learning rate decay was applied using Multi-StepLR. Continual pretraining lasts 15 days on a single A100 80GB GPU, while the HiFi-GAN model is fine-tuned for 3 days.

**Few-shot Speaker Adaptation:** To evaluate the BnTTS model's performance in few-shot speaker adaptation, we fine-tuned the model using our In-House dataset, which comprises studio recordings from four speakers. For each speaker, 20 minutes of audio are randomly selected, and individual models are trained for 10 epochs. The performance results are presented in Section 5.

**Evaluation Metric:** We evaluates the BnTTS system using five criteria. The Subjective Mean Opinion Score (SMOS) rates perceived audio quality, while ASR-based Character Error Rate (CER) measures transcription accuracy (Nandi et al., 2023). SpeechBERTScore assesses similarity to reference speech, and Speaker Encoder Cosine Similarity (SECS) evaluates speaker identity fidelity (Saeki et al., 2024; Casanova et al., 2021; Thienpondt and Demuynck, 2024). See Appendix D for details.

## 5 Results

We compared the BnTTS with IndicTTS (Kumar et al., 2023) and two commercially available systems: Google Cloud Text-to-Speech (GTTS) and Azure Text-to-Speech (AzureTTS). The evaluation was conducted using both the BnStudioEval and BnTTSTextEval datasets.

**Reference-aware Evaluation:** Table 1 shows the performance of various TTS systems on BnStudioEval dataset. AzureTTS performs best among synthetic methods, with the CER score, even surpassing the Ground Truth (GT) in transcription accuracy. As for the subjective measures, the proposed BnTTS closely follows the GT, with competitive scores in SMOS (4.584 *vs* GT:4.662), Naturalness (4.531 *vs* 4.637), and Clarity (4.940 *vs* 4.912).

For speaker similarity, GT achieves perfect SECS scores against reference audio and high scores against the speaker prompt. BnTTS also performs well, with SECS scores of 0.513 (reference) and 0.335 (prompt), just slightly behind GT. BnTTS achieves a SpeechBERTScore of 0.796, while GT maintains a perfect reference score of 1.0. IndicTTS, GTTS, and AzureTTS do not support speaker adaption, so SECS and SpeechBERTScore were not evaluated for these systems.

**Reference-independent Evaluation:** Table 2 presents the comparative performance of various TTS systems evaluated on the BnTTSTextEval dataset. The AzureTTS and GTTS consistently achieve lower CER scores, with BnTTS following closely in third place, and IndicTTS trailing behind. BnTTS performs strongly in subjective evaluations, excelling in SMOS, Naturalness, and Intelligibility across the BengaliStimuli53 and BengaliNamedEntity1000 subsets. However, it falls slightly behind AzureTTS in the ShortText200 subset. Despite this,

BnTTS overall, remains the top-performing system in all subjective metrics, delivering the highest scores in SMOS (4.371), Naturalness (4.333), and Clarity (4.760).

**High CER in Text Generation**: Our BnTTS exhibited a higher CER compared to AzureTTS and GTTS in both BnStudioEval and BnTTSTextEval dataset. The AzureTTS and GTTS also achieved a lower CER score than the GT. The BnTTS generates speech with more conversational prosody and expressiveness, which, while improving perceived quality, may negatively impact CER. ASR systems, used for CER evaluation, are often better suited to transcribing standardized speech patterns, as seen in AzureTTS and GTTS. The consistent loudness and simplified prosody in these systems create clearer phonetic boundaries, making them more easily transcribed by the ASR model (Choi et al., 2022; Wagner et al., 2019).

**Effect of Sampling and Prompt Length on Short Speech Generation:** The generation of short audio sequences presents challenges in the BnTTS model, particularly for texts containing fewer than 30 characters when using the default generation settings (Temperature $T = 0.85$ and TopK = 50). The issues observed are twofold: (1) the generated speech often lacks intelligibility, and (2) the output speech tends to be longer than expected. To investigate this, we extracted a subset of 23 short text-speech pairs from the BnStudioEval dataset, which we call ShortBnStudioEval dataset. For evaluation, we utilize the CER metric to assess intelligibility, and DurationEquality (Appendix: D) to quantify duration discrepancies.

Under the default settings (Exp.1 in Table 3), the model achieves a CER of 0.081 and a DurationEquality score of 0.699. We hypothesize that this issue stems from its training process. During training, the model is accustomed to short audio prompts for short sequences. By aligning the inference with this training strategy and using short prompt, the generation performance improves vastly, as evidenced by a higher DurationEquality score of 0.820 and a lower CER of 0.029 (Exp.2). Further, by adjusting the temperature to $T = 1.0$ and reducing the top-K value to 2, we observed an improvement in the DurationEquality score from 0.699 to 0.701, accompanied by a substantial reduction in CER, from 0.081 to 0.023 (Exp.3). Combining short prompt with the adjusted temperature and top-K values yielded the best results. In this configuration, the DurationEquality score improved to

0.827, with a CER of 0.015, demonstrating that both factors are crucial for accurate short speech generation.

| Method | GT | IndicTTS | GTTS | AzureTTS | BnTTS |
|---|---|---|---|---|---|
| CER | *0.038* | 0.068 | 0.022 | **0.019** | 0.028 |
| SMOS | *4.662* | 2.970 | 3.727 | 4.059 | **4.593** |
| Naturalness | *4.637* | 2.872 | 3.609 | 3.981 | **4.559** |
| Clarity | *4.912* | 3.974 | 4.869 | 4.845 | **4.940** |
| SECS (Ref.) | *1.0* | - | - | - | **0.513** |
| SECS (Prompt) | *0.361* | - | - | - | **0.335** |
| SpeechBERT Score | *1.0* | - | - | - | **0.796** |

Table 1: Comparative average performance for reference-aware BnStudioEval dataset. SECS and SpeechBERTScore are not reported for IndicTTS, GTTS, and AzureTTS as these systems do not support speaker adaption.

| Dataset | Method | CER | SMOS | Naturalness | Clarity |
|---|---|---|---|---|---|
| Bengali-Stimuli 53 | IndicTTS | 0.107 | 2.585 | 2.504 | 3.392 |
| | GTTS | 0.065 | 3.612 | 3.497 | 4.765 |
| | Azure TTS | **0.065** | 3.785 | 3.712 | 4.507 |
| | BnTTS | 0.081 | **4.461** | **4.424** | **4.832** |
| Bengali-Named Entity 1000 | IndicTTS | 0.041 | 3.002 | 2.899 | 4.048 |
| | GTTS | 0.034 | 3.784 | 3.695 | 4.678 |
| | Azure TTS | **0.030** | 4.099 | 4.036 | 4.731 |
| | BnTTS | 0.039 | **4.375** | **4.335** | **4.772** |
| Short-Text 200 | IndicTTS | 0.253 | 2.453 | 2.399 | 2.998 |
| | GTTS | 0.065 | 3.995 | 3.992 | 4.737 |
| | Azure TTS | **0.031** | **4.405** | **4.366** | **4.800** |
| | BnTTS | 0.106 | 4.272 | 4.233 | 4.657 |
| Overall | IndicTTS | 0.107 | 2.767 | 2.681 | 3.632 |
| | GTTS | 0.049 | 3.792 | 3.700 | 4.714 |
| | Azure TTS | **0.038** | 4.093 | 4.033 | 4.691 |
| | BnTTS | 0.068 | **4.371** | **4.333** | **4.760** |

Table 2: Comparative average performance analysis on reference-independent BnTTSTextEval dataset

| Exp. | T and TopK | Short Prompt | Duration Equality | CER |
|---|---|---|---|---|
| 1 | T=0.85, TopK=50 | N | 0.699 | 0.081 |
| 2 | T=0.85, TopK=50 | Y | 0.820 | 0.029 |
| 3 | T=1.0, TopK=2 | N | 0.701 | 0.023 |
| 4 | T=1.0, TopK=2 | Y | **0.827** | **0.015** |

Table 3: Comparative performance analysis on Short-BnStudioEval Dataset

# 6 Conclusion

In this work, we introduce BnTTS, the first open-source, speaker-adaptive TTS system for Bangla, achieving natural and clear speech synthesis with minimal training data. By adapting the XTTS pipeline, BnTTS supports zero-shot and few-shot speaker adaptation, outperforming existing Bangla TTS systems in speed, sound quality, and clarity. However, it faces limitations with diverse dialects, scalability due to the use of GPT-2, and struggles with short sequences. Future improvements will focus on expanding datasets, using more advanced models, and incorporating multilingual support to enhance its versatility.

## 7 Limitations

BnTTS has some limitations. It relies on a small and uniform dataset, which limits its ability to work well with the diverse dialects and accents in Bangla, potentially affecting the naturalness of the speech output for certain regional variations. The use of GPT-2, chosen due to limited resources, may also limit the system's scalability and performance compared to newer models. Additionally, the system struggles with adapting to speakers with unique vocal traits, especially without prior training on their voices. Its focus on Bangla also restricts its usefulness for other low-resource languages. Furthermore, XTTS, the foundation for BnTTS, performs poorly on very short sequences. While adjustments to hyperparameters and generation settings (temperature and TopK) have mostly resolved this issue, instances remain where the model struggles to generate sequences under 2 words or 20 characters. Future improvements could involve a larger dataset, more advanced models, and multilingual support to boost its versatility and robustness.

## 8 Ethical Considerations

The development of BnTTS raises ethical concerns, particularly regarding the potential misuse for unauthorized voice impersonation, which could impact privacy and consent. Protections, such as requiring speaker approval and embedding markers in synthetic speech, are essential. Diverse training data is also crucial to reduce bias and reflect Bangla's dialectal variety. Additionally, synthesized voices risk diminishing dialectal diversity. As an open-source tool, BnTTS requires clear guidelines for responsible use, ensuring adherence to ethical standards and positive community impact.

## References

Md Kausar Ahmed and Md Monirul Islam. 2019. Syllable-based bengali text to speech system. *Australian Journal of Science and Technology*.

Firoj Alam, Promila Nath, and Mumit Khan. 2010. Text to speech for bangla language using festival.

Firoj Alam, Promila Kanti Nath, and Mumit Khan. 2007. Text to speech for bangla language using festival. Technical report, BRAC University.

A. Baevski et al. 2022a. Vall-e: A generative neural audio codec for zero-shot tts. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 234–245. Association for Computational Linguistics.

A. Baevski et al. 2022b. Voicebox: A generalist neural speech synthesizer. In *Proceedings of the 2022 Conference on Neural Information Processing Systems*, pages 3001–3011. NeurIPS.

Y. Bai et al. 2022. Yourtts: Towards zero-shot multilingual text-to-speech. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 123–132. Association for Computational Linguistics.

James Betker. 2023. Better speech synthesis through scaling. *arXiv preprint arXiv:2305.07243*.

Prithwiraj Bhattacharjee, Rajan Saha Raju, Arif Ahmad, and M Shahidur Rahman. 2021. End-to-end bangla speech synthesis. In *2021 International Conference on Science & Contemporary Technologies (ICSCT)*, pages 1–6. IEEE.

Edresson Casanova, Christopher Shulby, Eren Gölge, Nicolas Michael Müller, Frederico Santos de Oliveira, Arnaldo Candido Jr., Anderson da Silva Soares, Sandra Maria Aluisio, and Moacir Antonelli Ponti. 2021. SC-GlowTTS: An Efficient Zero-Shot Multi-Speaker Text-To-Speech Model. In *Proc. Interspeech 2021*, pages 3645–3649.

P. Casanova et al. 2024. Xtts: Extending zero-shot tts to multilingual domains. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 300–310. Association for Computational Linguistics.

Yeunju Choi, Youngmoon Jung, Youngjoo Suh, and Hoirin Kim. 2022. Learning to maximize speech quality directly using mos prediction for neural text-to-speech. *IEEE Access*, 10:52621–52629.

Alexandre Défossez, Nicolas Usunier, Léon Bottou, and Francis Bach. 2019. Music source separation in the waveform domain. *arXiv preprint arXiv:1911.13254*.

Eray Eren and Cenk Demiroglu. 2023. Deep learning-based speaker-adaptive postfiltering with limited adaptation data for embedded text-to-speech synthesis systems. *Computer Speech & Language*, 81:101520.

Yuchen Fan, Yao Qian, Feng-Long Xie, and Frank K Soong. 2014. Tts synthesis with bidirectional lstm based recurrent neural networks. In *Fifteenth Annual Conference of the International Speech Communication Association*.

Cheng Gong, Erica Cooper, Xin Wang, Chunyu Qiang, Mengzhe Geng, Dan Wells, Longbiao Wang, Jianwu Dang, Marc Tessier, Aidan Pine, et al. 2024. An initial investigation of language adaptation for tts systems under low-resource scenarios. *arXiv preprint arXiv:2406.08911*.

Alexander Gutkin, Linne Ha, Martin Jansche, Knot Pipatsrisawat, and Richard Sproat. 2016. Tts for low resource languages: A bangla synthesizer. In *Proceedings of the Tenth International Conference*

*on Language Resources and Evaluation (LREC'16)*, pages 2005–2010.

Md Ismail Hossain, Mohammed Rakib, Sabbir Mollah, Fuad Rahman, and Nabeel Mohammed. 2022. Lila-boti: Leveraging isolated letter accumulations by ordering teacher insights for bangla handwriting recognition. In *2022 26th International Conference on Pattern Recognition (ICPR)*, pages 1770–1776. IEEE.

Md Jakir Hossain, Sayed Mahmud Al Amin, Md Saiful Islam, et al. 2018. Development of robotic voice conversion for ribo using text-to-speech synthesis. In *2018 4th International Conference on Electrical Engineering and Information & Communication Technology (iCEEiCT)*, pages 422–425. IEEE.

H. Ju et al. 2024. Naturalspeech3: Speech generation with naturalness and flexibility. In *Proceedings of the 2024 Conference on Neural Information Processing Systems*, pages 456–467. NeurIPS.

Elyor Kodirov, Tao Xiang, Zhenyong Fu, and Shaogang Gong. 2015. Unsupervised domain adaptation for zero-shot learning. In *Proceedings of the IEEE international conference on computer vision*, pages 2452–2460.

Jungil Kong, Jaehyeon Kim, and Jaekyoung Bae. 2020. Hifi-gan: Generative adversarial networks for efficient and high fidelity speech synthesis. *Advances in neural information processing systems*, 33:17022–17033.

Raghuraman Krishnamoorthi. 2018. Quantizing deep convolutional networks for efficient inference: A whitepaper. *arXiv preprint arXiv:1806.08342*.

Gokul Karthik Kumar, Praveen S V, Pratyush Kumar, Mitesh M. Khapra, and Karthik Nandakumar. 2023. Towards building text-to-speech systems for the next billion users. In *ICASSP 2023 - 2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 1–5.

Q. Le et al. 2023. Voicebox: A versatile neural speech synthesis system. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 120–130. Association for Computational Linguistics.

Haohe Liu, Qiuqiang Kong, Qiao Tian, Yan Zhao, DeLiang Wang, Chuanzeng Huang, and Yuxuan Wang. 2021. Voicefixer: Toward general speech restoration with neural vocoder. *Preprint*, arXiv:2109.13731.

Dongchan Min, Dong Bok Lee, Eunho Yang, and Sung Ju Hwang. 2021. Meta-stylespeech: Multi-speaker adaptive text-to-speech generation. In *International Conference on Machine Learning*, pages 7748–7759. PMLR.

Rabindra Nath Nandi, Mehadi Menon, Tareq Muntasir, Sagor Sarker, Quazi Sarwar Muhtaseem, Md. Tariqul Islam, Shammur Chowdhury, and Firoj Alam. 2023. Pseudo-labeling for domain-agnostic Bangla automatic speech recognition. In *Proceedings of the First Workshop on Bangla Language Processing (BLP-2023)*, pages 152–162, Singapore. Association for Computational Linguistics.

Abu Naser, Devojyoti Aich, and Md Ruhul Amin. 2010. Implementation of subachan: Bengali text to speech synthesis software. In *International Conference on Electrical & Computer Engineering (ICECE)*, pages 574–577.

Alexis Plaquet and Hervé Bredin. 2023. Powerset multi-class cross entropy loss for neural speaker diarization. In *Proc. INTERSPEECH 2023*.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.

Muhammed Masud Rashid, Md Akter Hussain, and M Shahidur Rahman. 2010. Text normalization and diphone preparation for bangla speech synthesis. *Journal of Multimedia*, 5(6):551.

Takaaki Saeki, Soumi Maiti, Shinnosuke Takamichi, Shinji Watanabe, and Hiroshi Saruwatari. 2024. SpeechBERTScore: Reference-aware automatic evaluation of speech generation leveraging nlp evaluation metrics. *arXiv preprint arXiv:2401.16812*.

Tabassum Sadia Shahjahan, Md Ismail Hossain, Kazi Rafat, Mohammad Ruhul Amin, Fuad Rahman, and Nabeel Mohammed. 2024. Precision-driven low-resource speech synthesis for bangla text-to-speech system. In *5th Workshop on practical ML for limited/low resource settings*.

Abhayjeet Singh, Amala Nagireddi, Deekshitha G, Jesuraja Bandekar, Roopa R, Sandhya Badiger, Sathvik Udupa, Prasanta Kumar Ghosh, Hema A Murthy, Pranaw Kumar, Keiichi Tokuda, Mark Hasegawa-Johnson, and Philipp Olbrich. 2024. Limmits'24: Multi-speaker, multi-lingual indic tts with voice cloning. In *2024 IEEE International Conference on Acoustics, Speech, and Signal Processing Workshops (ICASSPW)*, pages 61–62.

Keshan Sodimana, Knot Pipatsrisawat, Linne Ha, Martin Jansche, Oddur Kjartansson, Pasindu De Silva, and Supheakmungkol Sarin. 2018. A Step-by-Step Process for Building TTS Voices Using Open Source Data and Framework for Bangla, Javanese, Khmer, Nepali, Sinhala, and Sundanese. In *Proc. The 6th Intl. Workshop on Spoken Language Technologies for Under-Resourced Languages (SLTU)*, pages 66–70, Gurugram, India.

Nimisha Srivastava, Rudrabha Mukhopadhyay, Prajwal K R, and C V Jawahar. 2020. IndicSpeech: Text-to-speech corpus for Indian languages. In *Proceedings of the Twelfth Language Resources and Evaluation*

*Conference*, pages 6417–6422, Marseille, France. European Language Resources Association.

Jenthe Thienpondt and Kris Demuynck. 2024. Ecapa2: A hybrid neural network architecture and training strategy for robust speaker embeddings. *arXiv preprint arXiv:2401.08342*.

Petra Wagner, Jonas Beskow, Simon Betz, Jens Edlund, Joakim Gustafson, Gustav Eje Henter, Sébastien Le Maguer, Zofia Malisz, Éva Székely, Christina Tånnander, et al. 2019. Speech synthesis evaluation—state-of-the-art assessment and suggestion for a novel research program. In *Proceedings of the 10th Speech Synthesis Workshop (SSW10)*.

Z. Wang et al. 2023. Neural speech synthesis: One-shot voice cloning techniques. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 200–210. Association for Computational Linguistics.

Y. Xu et al. 2022. Vall-e x: A generative speech model for zero-shot tts and speech-to-speech translation. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 400–410. Association for Computational Linguistics.

Y. Xu et al. 2023. Cross-lingual transfer for low-resource text-to-speech. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 510–520. Association for Computational Linguistics.

Y. Yan et al. 2021. Adaspeech 2: Adaptive text-to-speech with one-shot voice cloning. In *Proceedings of the 2021 Conference on Neural Information Processing Systems*, pages 122–134. NeurIPS.

Mingyang Zhang, Yi Zhou, Li Zhao, and Haizhou Li. 2021. Transfer learning from speech synthesis to voice conversion with non-parallel training data. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 29:1290–1302.

W. Zhang et al. 2022. Universal text-to-speech for low-resource languages. *Journal of Speech Technology*, 14(3):210–220.

## A TTS Data Acquisition Framework

Figure 2: Overview of our TTS Data Acquisition Framework. The acquisition process involves using a Speech-to-Text model to obtain transcription, an LLM to restore transcription's punctuation, a Noise Suppression model for to remove unwanted noise, and finally a Audio SuperResolution Model to enhance audio quality and loudness.

Bangla is a low-resource language, and large-scale, high-quality TTS speech data are particularly scarce. To address this gap, we developed an TTS Data Acquisition Framework (Figure 2) designed to collect high-quality speech data with aligned transcripts. This framework leverages advanced speech processing models and carefully designed algorithms to process raw audio inputs and generate refined audio outputs with word-aligned transcripts. Below, we provide a detailed breakdown of the key components of the framework.

**1. Speech-to-Text(STT):** The audio files are first processed through an in-house our STT system, which transcribes the spoken content into text. The STT system used here is an enhnaced version of the model proposed in (Nandi et al., 2023).

**2. Punctuation Restoration Using LLM:** Following transcription, a Large Language Model (LLM) is employed to restore appropriate punctuation. This step is crucial for improving grammatical accuracy and ensuring that the text is clear and coherent, aiding in further processing.

**3. Audio and Transcription Segmentation:** The audio and transcription are segmented based on terminal punctuation (full-stop, question mark, exclamatory mark, comma). This ensures that each audio segment aligns with a complete sentence, maintaining the speaker's prosody throughout.

**4. Noise and Music Suppression:** To improve audio quality, noise and music suppression techniques (Défossez et al., 2019) are applied. This step ensures that the resulting audio is free of background disturbances, which could degrade TTS performance.

**5. Audio SuperResolution:** After noise suppression, the audio files undergo super-resolution processing to enhance audio fidelity (Liu et al., 2021). This ensures high-quality audio, crucial for producing natural-sounding TTS outputs.

This pipeline effectively enhances raw audio and transcription data, resulting in a high-quality pseudo-labeled dataset. By combining ASR, LLM-based punctuation restoration, noise suppression, super-resolution, and diarization, the framework is used to generate very high-quality speech data suitable for training speech synthesis models.

### A.1 Dataset Filtering Criteria

The pseudo-labeled datasets are further refined using the following criteria:

- **Diarization:** Pyannote's Speaker diarization v3.1 is employed to filter audio files by separating multi-speakers audios, ensuring that each instance contains only one speaker (Plaquet and Bredin, 2023), which is essential for effective TTS model training.

- **Audio Duration**: Audio segments shorter than 0.5 seconds are discarded, as they provide insufficient information for our model. Similarly, segments longer than 11 seconds are excluded to match the model's sequence length.

- **Text Length**: Segments with transcriptions exceeding 200 characters are removed to ensure manageable input size during training.

- **Silence-based Filtering**: Audio files where over 35% of the duration consists of silence are discarded, as they negatively impact model performance.

- **Text-to-Audio Ratio**: Based on our analysis, audio segments where the text-to-audio duration ratio falls outside (Figure 3b) the range of 6 to 25 are excluded (Figure 3c), ensuring alignment with natural speech patterns observed in Pseudo-labeled data from Phase A (Figure 3a).

## B Dataset

### B.1 Training Dataset

Table 4 summarizes the statistics and metadata for the datasets utilized in this study. We leveraged four open-source datasets: OpenSLR Bangla TTS Dataset (Sodimana et al., 2018) , Limmits (Singh et al., 2024), Comprehensive Bangla TTS Dataset (Srivastava et al., 2020) ,and CRBLP TTS Dataset(Alam et al., 2010) comprising a total of 117 hours of training data. Additionally, we augmented our dataset by synthesizing 16.44 hours of speech via Google's TTS API, ensuring high-quality transcripts. Furthermore, 4.22 hours of professionally recorded studio data from four speakers were generated, specifically for fine-tuning purposes.

The majority of our data, however, comes from the TTS Data Acquisition framework, which collected 82.39 hours in Phase A and a substantial 3,636.47 hours in Phase B. The Phase A data underwent thorough evaluation, and the insights gained were pivotal in refining the large-scale acquisition process in Phase B.

### B.2 Evaluation Dataset

For evaluating the performance of our TTS system, we curated two datasets: BnStudioEval and BnTTSTextEval, each serving distinct evaluation purposes.

**BnStudioEval**: This dataset comprises 80 high-quality instances (text and audio pair) taken from our in-house studio recordings. This dataset was selected to assess the model's capability in replicating high-fidelity speech output with speaker impersonation.

**BnTTSTextEval**: The BnTTSTextEval dataset encompasses three subsets:

(a) The diagram illustrates the linear relationship between audio duration and character length in manually-reviewed Pseudo-labeled Data - Phase A.

(b) The diagram depicts relationship between audio duration and character length in Pseudo-Labeled Data - Phase B.

(c) The diagram illustrates audio duration vs character length graph in Pseudo-Labeled Data - Phase B after filtering.

Figure 3: These figures demonstrates how the ratio of text length to audio duration changes before and after processing the data.

- **BengaliStimuli53**: A linguist-curated set of 53 instances, created to cover a comprehensive range of Bengali phonetic elements. This subset ensures that the model handles diverse phonemes.

- **BengaliNamedEntity1000**: A set of 1,000 instances focusing on proper nouns such as

| Dataset | Duration (Hour) | Remarks |
|---|---|---|
| Pseudo-Labeled Data - Phase A | 82.39 | Manually reviewed |
| Pseudo-Labeled Data - Phase B | 3636.47 | Not Reviewed |
| Synthetic (GTTS) | 16.44 | Synthetic |
| Comprehensive Bangla TTS Dataset | 20.08 | Open-source Data |
| OpenSLR Bangla TTS Dataset | 3.82 | Open-source Data |
| Limmits | 79 | Open-source Data |
| CRBLP TTS Dataset | 13.59 | Open-source Data |
| In-House HQ Data | 4.22 | Studio Quality, Manually reviewed |
| **Total Duration** | **3856.01** | |

Table 4: Dataset Information

person, place, and organization names. This subset tests the model's handling of named entities, which is crucial for real-world conversational accuracy.

- **ShortText200**: Composed of 200 instances, this subset includes short sentences, filler words, and common conversational phrases (less than three words) to evaluate the model's performance in natural, day-to-day dialogue scenarios.

The BnStudioEval dataset, with reference audio for each text, will be for reference-aware evaluation, while BnTTSTextEval supports reference-independent evaluation. Together, these datasets provide a comprehensive basis for evaluating various aspects of our TTS performance, including phonetic diversity, named entity pronunciation, and conversational fluency.

## C  Objective Functions

Our BnTTS model composed of two primary modules (GPT-2 and HiFi-GAN), which are trained separately. The GPT-2 module is trained using a Language Modeling objective, while the HiFi-GAN module is optimized using HiFi-GAN loss objective. This section provides an overview of the loss functions applied during training.

### C.1  Language Modeling Loss

1. **Text Generation Loss**: Denoted as $\mathcal{L}_{\text{text}}$, it quantifies the difference between predicted logits and ground truth labels using cross-entropy. Let $\hat{y}_{\text{text}}$

represent the predicted logits and $y_{\text{text}}$ the ground truth target labels. For a sequence with $N$ text tokens, the Text Generation Loss is calculated as:

$$\mathcal{L}_{\text{text}} = \frac{1}{N} \sum_{i=1}^{N} \text{CE}(\hat{y}_{\text{text}}^{(i)}, y_{\text{text}}^{(i)}) \tag{1}$$

2. **Audio Generation Loss**: Denoted as $\mathcal{L}_{\text{audio}}$, it evaluates the accuracy of generated acoustic tokens against target VQ-VAE codes using cross-entropy loss:

$$\mathcal{L}_{\text{audio}} = \frac{1}{N} \sum_{i=1}^{N} \text{CE}(\hat{y}_{\text{audio}}^{(i)}, y_{\text{audio}}^{(i)}) \tag{2}$$

where $\hat{y}_{\text{audio}}$ represents the predicted logits for the audio token, $y_{\text{audio}}$ are the corresponding target VQ-VAE tokens, and $N$ is the number of audio token in the sequence.

Total loss combines the text generation and audio generation losses with weighted factors:

$$\mathcal{L}_{\text{total}} = \alpha \mathcal{L}_{\text{text}} + \beta \mathcal{L}_{\text{audio}} \quad (\alpha = 0.01, \beta = 1.0) \tag{3}$$

where $\alpha$ and $\beta$ are scaling factors that control the relative importance of each loss term.

## C.2 HiFi-GAN Loss

We used a HiFi-GAN-based vocoder (Kong et al., 2020) that comprises multiple discriminators: the Multi-Period Discriminator, and Multi-Scale Discriminator. For the sake of clarity, we will refer to these discriminators as a single entity. The HiFi-GAN module is trained using multiple losses mentioned below:

1. **Adversarial Loss**: The adversarial losses for the generator $G$ and the discriminator $D$ are defined as follows:

$$\mathcal{L}_{\text{Adv}}(D; G) = \mathbb{E}_{(x,s)} \left[ (D(x) - 1)^2 + D(G(s))^2 \right] \tag{4}$$

$$\mathcal{L}_{\text{Adv}}(G; D) = \mathbb{E}_s \left[ (D(G(s)) - 1)^2 \right] \tag{5}$$

where $x$ represents the real audio samples, and $s$ denotes the input conditions.

2. **Mel-Spectrogram Loss**: This loss calculates L1 distance between the mel-spectrograms of the real and generated audio. This loss is formulated as:

$$\mathcal{L}_{\text{Mel}}(G) = \mathbb{E}_{(x,s)} \left[ \| \phi(x) - \phi(G(s)) \|_1 \right] \tag{6}$$

where $\phi$ represents the transformation function that maps a waveform to its corresponding mel-spectrogram.

3. **Feature Matching Loss**: The feature matching loss calculates the L1 distance between the intermediate features of the real and generated audio, as extracted from multiple layers of the discriminator. It is defined as:

$$\mathcal{L}_{\text{FM}}(G; D) = \mathbb{E}_{(x,s)} \left[ \sum_{i=1}^{T} \frac{1}{N_i} \left\| D^i(x) - D^i(G(s)) \right\|_1 \right] \tag{7}$$

where $T$ denotes the number of discriminator layers, and $D^i$ and $N_i$ represent the features and number of features at the $i$-th layer, respectively.

**Final Loss**  Given that the discriminator is composed of multiple sub-discriminators, the final objectives for training the generator and the discriminator are defined as follows::

$$\mathcal{L}_G = \sum_{k=1}^{K} [\mathcal{L}_{\text{Adv}}(G; D_k) + \lambda_{\text{FM}} \mathcal{L}_{\text{FM}}(G; D_k)]$$
$$+ \lambda_{\text{Mel}} \mathcal{L}_{\text{Mel}}(G) \tag{8}$$

$$\mathcal{L}_D = \sum_{k=1}^{K} \mathcal{L}_{\text{Adv}}(D_k; G) \tag{9}$$

where $D_k$ denotes the $k$-th sub-discriminator and $\lambda_{\text{FM}} = 2$, $\lambda_{\text{Mel}} = 45$.

# D Evaluation Metrics

We employed a combination of subjective and objective metrics to rigorously evaluate the performance of our TTS system, focusing on intelligibility, naturalness, speaker similarity, and transcription accuracy.

**Subjective Mean Opinion Score (SMOS):** SMOS is a perceptual evaluation where listeners rate synthesized speech on a Likert scale from 1 (poor) to 5 (excellent). It considers naturalness, clarity, and fluency, providing an absolute score for each sample. A higher SMOS indicates better overall speech quality.

**SpeechBERTScore:** SpeechBERTScore adapts BERTScore for speech, using self-supervised learning (SSL) models to compare dense representations of generated and reference speech. For generated speech waveform $\hat{X}$ and reference waveform $X$,

the feature representations $\hat{Z}$ and $Z$ are extracted using a pretrained model. SpeechBERTScore is defined as the average maximum cosine similarity between feature vectors:

$$\text{SpeechBERTScore} = \frac{1}{N_{\text{gen}}} \sum_{i=1}^{N_{\text{gen}}} \max_{j} \cos(\hat{\mathbf{z}}_i, \mathbf{z}_j)$$

where $\hat{\mathbf{z}}_i$ and $\mathbf{z}_j$ represent the SSL embeddings for generated and reference speech, respectively.

**Character Error Rate (CER):** CER measures transcription accuracy by calculating the ratio of errors (substitutions $S$, deletions $D$, and insertions $I$) in automatic speech recognition (ASR) transcriptions:

where $N$ is the total number of characters in the reference transcription. A lower CER indicates better transcription accuracy.

**Speaker Encoder Cosine Similarity (SECS):** SECS evaluates speaker similarity by calculating the cosine similarity between speaker embeddings of the reference and synthesized speech:

$$\text{SECS} = \frac{e_{\text{ref}} \cdot e_{\text{syn}}}{\|e_{\text{ref}}\| \|e_{\text{syn}}\|},$$

where $e_{\text{ref}}$ and $e_{\text{syn}}$ are the speaker embeddings for reference and synthesized speech, respectively. SECS ranges from -1 (low similarity) to 1 (high similarity).

**Duration Equality Score:** This metric quantifies how closely the durations of the reference ($a$) and synthesized ($b$) speech match, with a score of 1 indicating identical durations:

$$\text{DurationEquality}(a, b) = \frac{1}{\max\left(\frac{a}{b}, \frac{b}{a}\right)}.$$

This score helps in assessing duration similarity between reference and generated audio, ensuring consistency in pacing.

Each metric provides a different perspective, allowing a holistic evaluation of the synthesized speech quality.

# E   Use of AI assistant

We used AI assistants such as GPT-4o for spelling and grammar checking for the text of the paper.

# F   Symbols and Notations

| Variable | Description |
|---|---|
| $\mathbf{T}$ | Text sequence with $N$ tokens |
| $N$ | Number of tokens in the text sequence |
| $\mathbf{S}$ | Speaker's mel-spectrogram with $L$ frames |
| $\hat{\mathbf{Y}}$ | Generated speech |
| $\mathbf{Y}$ | Ground truth mel-spectrogram |
| $\mathcal{F}$ | LLM Model |
| $\mathbf{z}$ | Discrete codes |
| $\mathcal{C}$ | Codebook of discrete codes |
| $l$ | Number of layers |
| $k$ | Number of attention heads i |
| $\mathbf{S_z}$ | speaker spectrogram embd.$\mathbb{R}^{L \times d}$ |
| $d$ | Embedding |
| $\mathbf{Q}, \mathbf{K}, \mathbf{V}$ | Query, Key, Value |
| $P$ | Perceiver Resampler |
| $\mathbf{R}$ | Fixed-size output in $\mathbb{R}^{P \times d}$ |
| $\mathbf{T_e}$ | Continuous embedding $\mathbb{R}^{N \times d}$ |
| $\mathbf{S_p}$ | Speaker embeddings |
| $\mathbf{Y_z}$ | Ground truth |
| $\mathbf{X}$ | Input of LLM |
| $\oplus$ | Concatenation operation |
| $\mathbf{H}$ | Output from the LLM |
| $\mathbf{H_Y}$ | Spectrogram embedding |
| $\mathbf{S}'$ | Resized embedding $\mathbf{H_Y}$ |
| $\mathbf{W}$ | Final audio waveform |
| $g_{\text{HiFi}}$ | HiFi-GAN function |

Table 5: Table of Variables and Descriptions