CLOPS: CONTINUAL LEARNING OF PHYSIOLOGICAL SIGNALS

ABSTRACT

Deep learning algorithms are known to experience destructive interference when instances violate the assumption of being independent and identically distributed (i.i.d). This violation, however, is ubiquitous in clinical settings where data are streamed temporally and from a multitude of physiological sensors. To overcome this obstacle, we propose CLOPS, a replay-based continual learning strategy. In three continual learning scenarios based on three publically-available datasets, we show that CLOPS can outperform the state-of-the-art methods, GEM and MIR. Moreover, we propose end-to-end trainable parameters, which we term task-instance parameters, that can be used to quantify task difficulty and similarity. This quantification yields insights into both network interpretability and clinical applications, where task difficulty is poorly quantified.

1 INTRODUCTION

Deep learning algorithms operate under the assumption that instances are independent and identically-distributed (i.i.d.). The violation of this assumption can be detrimental to the training behaviour and performance of an algorithm. The assumption of independence can be violated, for example, when data are streamed temporally from a sensor. Introducing multiple sensors in a changing environment can introduce covariate shift, arguably the 'Achilles heel' of machine learning model deployment (Quionero-Candela et al., 2009).

A plethora of realistic scenarios violate the i.i.d. assumption. This is particularly true in healthcare where the multitude of physiological sensors generate time-series recordings that may vary temporally (due to seasonal diseases; e.g. flu), across patients (due to different hospitals or hospital settings), and in their modality. Tackling the challenges posed by such scenarios is the focus of continual learning (CL) whereby a learner, when exposed to tasks in a sequential manner, is expected to perform well on current tasks without compromising performance on previously seen tasks. The outcome is a single algorithm that can reliably solve a multitude of tasks. Given the potential impact of designing such an algorithm and the machine learning community's efforts towards achieving artificial general intelligence, research on continual learning has increased (Parisi et al., 2019). However, most, if not all, research in this field has been limited to a small handful of imaging datasets (Lopez-Paz & Ranzato, 2017; Aljundi et al., 2019b;a). Although understandable from a benchmarking perspective, such research fails to explore the utility of continual learning methodologies in more realistic healthcare scenarios (Farquhar & Gal, 2018). To the best of our knowledge, we are the first to explore and propose a CL approach in the context of physiological signals. The dynamic and chaotic environment that characterizes healthcare necessitates the availability of algorithms that are dynamically reliable; those that can adapt to potential covariate shift without catastrophically forgetting how to perform tasks from the past. Such dynamic reliability implies that algorithms no longer needs to be retrained on data or tasks to which it has been exposed in the past, thus improving its data-efficiency. Secondly, algorithms that perform consistently well across a multitude of tasks are more trustworthy, a desirable trait sought by medical professionals (Spiegelhalter, 2020).

Our Contributions. In this paper, we propose a replay-based continual learning methodology that is based on the following:

1. **Importance-guided Storage:** task-instance parameters, a scalar corresponding to each instance in each task, as informative signals for *loss-weighting* and *buffer-storage*.

2. **Uncertainty-based Acquisition:** an active learning inspired methodology that determines the degree of informativeness of an instance and thus acts as a *buffer-acquisition* mechanism.

2   RELATED WORK

Continual learning (CL) has resurfaced in recent years with an extensive summary provided by Parisi et al. (2019). Approaches similar to ours fall under the category of memory-based methods and include iCaRL (Rebuffi et al., 2017), CLEAR (Rolnick et al., 2019), GEM (Lopez-Paz & Ranzato, 2017), and aGEM (Chaudhry et al., 2018). In contrast to our work, the latter two methods naively populate their replay buffer with the last *m* examples observed for a particular task. Isele & Cosgun (2018) and Aljundi et al. (2019b) employ a more sophisticated buffer-storage strategy where a quadratic programming problem is solved in the absence of task boundaries. Aljundi et al. (2019a) introduce MIR whereby instances are stored using reservoir sampling and sampled according to whether they incur the greatest change in loss if parameters were to be updated on the subsequent task. This approach is computationally expensive, requiring multiple forward and backward passes per batch. The application of CL in the medical domain is limited to that of Lenga et al. (2020) wherein existing methodologies are simply implemented on chest X-ray datasets. In contrast to previous research that independently investigates buffer-storage and acquisition strategies, we focus on a *dual* storage and acquisition strategy.

Active learning (AL) in healthcare has observed increased interest in recent years, with an extensive review of general active learning methodologies provided by Settles (2009). In the healthcare domain, Gong et al. (2019) propose a Bayesian deep latent Gaussian model to acquire important features from electronic health record (EHR) samples in the MIMIC dataset (Johnson et al., 2016) to improve mortality prediction. Also dealing with EHR data, Chen et al. (2013) use the distance of unlabelled samples from the hyperplane in an SVM to acquire datapoints. Wang et al. (2019) implement an RNN to acquire ECG samples during training. Zhou et al. (2017) propose using transfer learning in conjunction with a convolutional neural network to acquire biomedical images in an online manner. Smailagic et al. (2018; 2019) actively acquire unannotated medical images by measuring their distance in a latent space to images in the training set. Such similarity metrics, however, are sensitive to the amount of available labelled training data. Gal et al. (2017) adopt BALD (Houlsby et al., 2011) in the context of Monte Carlo Dropout to acquire instances that maximize the Jensen-Shannon divergence (JSD) across MC samples. To the best of our knowledge, we are the first to employ AL-inspired acquisition functions in the context of CL.

3   BACKGROUND

3.1   CONTINUAL LEARNING

In this work, we consider a learner, $f_\omega : x_\mathcal{T} \in \mathbb{R}^m \to y_\mathcal{T} \in \mathbb{R}^c$, a neural network parameterized by ω, that maps an m-dimensional input, $x_\mathcal{T}$, to a c-dimensional output, $y_\mathcal{T}$, where c is the number of classes, for each task $\mathcal{T} \in [1 \dots N]$. This learner is exposed to new tasks in a sequential manner once previously-tackled tasks are mastered. In this paper, we formulate our tasks based on a modification of the three-tier categorization of continual learning proposed by van de Ven & Tolias (2019). In all of the following cases, task identities are *absent* during both training and testing and neural architectures are single-headed. **Class Incremental Learning (Class-IL) -** we present the learner with mutually-exclusive pairs of classes belonging to the same dataset in a sequential manner. **Time Incremental Learning (Task-IL) -** the same dataset and prediction problem are used for each task, however the *time of year* at which the data were collected differs from one task to another. Such seasonality is most common in healthcare applications. **Domain Incremental Learning (Domain-IL) -** the same dataset and prediction problem are used for each task, however the *modality* of the inputs differ from one task to another.

4   METHODS

The two ideas underlying our proposal are the storage of instances into *and* the acquisition of instances from a buffer such that destructive interference is mitigated. We describe these in more detail below.

4.1 Importance-guided Buffer Storage

We aim to populate a buffer, $\mathcal{D}_B$, of finite size, $\mathcal{M}$, with instances from the current task that are considered important. To quantify importance, we learn parameters, entitled task-instance parameters, $\beta_{i\mathcal{T}}$, associated with each instance, i, in each task, $\mathcal{T}$. These parameters play a dual role.

4.1.1 Loss-Weighting Mechanism

We incorporate β as a coefficient of the task loss, $\mathcal{L}_{i\mathcal{T}}$, for each instance of the current task. For a mini-batch of size, B, that consists of $B_{\mathcal{T}}$ instances from the current task, the objective function is:

$$\mathcal{L} = \frac{1}{B_{\mathcal{T}}} \sum_{i=1}^{B_{\mathcal{T}}} \beta_{i\mathcal{T}} \mathcal{L}_{i\mathcal{T}} \tag{1}$$

To update the values of $\beta_{i\mathcal{T}}$ via gradient descent, we must calculate $\frac{\partial \mathcal{L}}{\partial \beta_{i\mathcal{T}}} = \mathcal{L}_{i\mathcal{T}} > 0$. Instances with larger loss values (hard-to-classify) will exhibit lower values of $\beta_{i\mathcal{T}}$. In this setup, we discovered $\beta_{i\mathcal{T}}$ quickly decay to zero, and as a coefficient of the loss, prevents the network from learning the task. To overcome this, we introduced a regularization term into the objective function.

$$\mathcal{L}_{\text{current}} = \frac{1}{B_{\mathcal{T}}} \sum_{i=1}^{B_{\mathcal{T}}} \beta_{i\mathcal{T}} \mathcal{L}_{i\mathcal{T}} + \lambda(\beta_{i\mathcal{T}} - 1)^2 \tag{2}$$

When $\mathcal{T} > 1$, we introduce loss terms that account for instances replayed from the buffer that belong to previous tasks, $k \in [1, \mathcal{T} - 1]$ (see Sec. 4.2 for replay mechanism). We decide that these instances, in contrast to those from the current task, would not be weighted (see Appendix K).

$$\mathcal{L}_{\text{replay}} = \frac{1}{B - B_{\mathcal{T}}} \sum_{k=1}^{\mathcal{T}-1} \sum_{i}^{B_k} \mathcal{L}_{ik} \tag{3}$$

$$\mathcal{L} = \mathcal{L}_{\text{current}} + \mathcal{L}_{\text{replay}} \tag{4}$$

4.1.2 Buffer-Storage Mechanism

Our interpretation of β as a proxy for instance difficulty underlies our motivation to use it to store instances into the buffer. The utility of such a proxy, however, is eroded as β converges to similar values for different instances (Saxena et al., 2019). In fact, we find that β can sometimes lead to *erroneous* estimates of the relative difficulty of instances (see Appendix A). To maintain the reliability of this proxy, we *track* task-instance parameters after each training epoch, t, until the final epoch, τ, for the task at hand. This results in the storage function, $s_{i\mathcal{T}}$, approximated using the trapezoidal rule.

$$s_{i\mathcal{T}} = \int_0^\tau \beta_{i\mathcal{T}}(t)dt \approx \sum_{t=0}^\tau \left(\frac{\beta_{i\mathcal{T}}(t + \Delta t) + \beta_{i\mathcal{T}}(t)}{2} \right) \Delta t \tag{5}$$

Once training is complete on the task at hand, we rank the instances in descending order of the storage function, $s_{i\mathcal{T}}$, (easy to hard) before selecting the top b fraction. We opted for this strategy over storing the bottom b fraction due to its superiority (see Appendix I). The selected instances are then placed into the buffer, of which each task is allotted a fixed portion.

4.2 Uncertainty-based Buffer Acquisition

The acquisition of instances that a learner is uncertain about is likely to benefit training (Zhu, 2005). This is the premise of uncertainty-based acquisition functions such as BALD (Houlsby et al., 2011; Gal & Ghahramani, 2016). We now outline how to exploit this premise for buffer acquisition.

At epoch number, τ_{MC}, referred to as Monte Carlo (MC) epochs, each of the M instances, $x \sim \mathcal{D}_B$, is passed through the network and exposed to a stochastic binary dropout mask to generate an output, $p(y|x, \omega) \in \mathbb{R}^C$. This is repeated T times to form a matrix, $G \in \mathbb{R}^{M \times T \times C}$. An acquisition function, such as BALD_{MCD}, is thus a function $\mathcal{F} : \mathbb{R}^{M \times T \times C} \to \mathbb{R}^M$.

$$\text{BALD}_{\text{MCD}} = \text{JSD}(p_1, p_2, \ldots, p_T) = \text{H}\left(p(y|x)\right) - \mathbb{E}_{p(\omega|D_{train})}\left[\text{H}\left(p(y|x, \hat{\omega})\right)\right] \tag{6}$$

where $\mathrm{H}(p(y|x))$ represents the entropy of the network outputs averaged across the MC samples, and $\hat{\omega} \sim p(\omega|D_{train})$ as in Gal & Ghahramani (2016). At sample epochs, τ_S, we rank instances in descending order based on the acquisition function before acquiring the top a fraction from each task in the buffer. The intuition is that by exposing the network to instances from previous tasks that it is most confused about, we nudge it to avoid destructive interference in a data-efficient manner. We outline the entire training procedure in Algorithms 1-4 in Appendix B.

5 EXPERIMENTAL DESIGN

5.1 DATASETS

We conduct experiments[1] in PyTorch (Paszke et al., 2019). Given our emphasis on healthcare, we evaluate our approach on three publically-available datasets that include physiological time-series data such as the electrocardiogram (ECG) alongside cardiac arrhythmia labels. We use $\mathcal{D}_1$ = **Cardiology ECG** (Hannun et al., 2019) (12-way), $\mathcal{D}_2$ = **Chapman ECG** (Zheng et al., 2020) (4-way), and $\mathcal{D}_3$ = **PhysioNet 2020 ECG** (Perez Alday et al., 2020) (9-way, multi-label). Further details regarding the datasets and network architecture can be found in Appendix D.

5.2 CONTINUAL LEARNING SCENARIOS

Here, we outline the three primary continual learning scenarios we use for our experiments. In **Class-IL**, $\mathcal{D}_1$ is split according to mutually-exclusive pairs of classes $[0,1]$, $[2,3]$, $[4,5]$, $[6,7]$, $[8,9]$, and $[10,11]$. This scenario allows us to evaluate the sensitivity of a network to new classes. In **Time-IL**, $\mathcal{D}_2$ is split into three tasks; Term 1, Term 2, and Term 3 corresponding to mutually-exclusive times of the year during which patient data were collected. This scenario allows us to evaluate the effect of temporal non-stationarity on a network's performance. Lastly, in **Domain-IL**, $\mathcal{D}_3$ is split according to the 12 leads of an ECG; 12 different projections of the same electrical signal generated by the heart. This scenario allows us to evaluate how robust a network is to the input distribution.

5.3 BASELINE METHODS

We compare our proposed method to the following. **Multi-Task Learning (MTL)** (Caruana, 1993) is a strategy whereby all datasets are assumed to be available at the same time and thus can be simultaneously used for training. Although this assumption may not hold in clinical settings due to the nature of data collection, privacy or memory constraints, it is nonetheless a strong baseline. **Fine-tuning** is a strategy that involves updating all parameters when training on subsequent tasks as they arrive without explicitly dealing with catastrophic forgetting. We also adapt two replay-based methods for our scenarios. **GEM** (Lopez-Paz & Ranzato, 2017) solves a quadratic programming problem to generate parameter gradients that do not increase the loss incurred by replayed instances. **MIR** (Aljundi et al., 2019a) replays instances from a buffer that incur the greatest change in loss given a parameter pseudo-update. Details of how we adapted these methods for our scenarios can be found in Appendix D.

5.4 EVALUATION METRICS

To evaluate our methods, we exploit metrics suggested by Lopez-Paz & Ranzato (2017) such as average AUC and Backward Weight Transfer (BWT). We also propose two additional evaluation metrics that provide us with a more fine-grained analysis of learning strategies.

t-Step Backward Weight Transfer. To determine how performance changes 't-steps into the future', we propose BWT_t which evaluates the performance of the network on a previously-seen task, after having trained on t-tasks after it.

$$\mathrm{BWT}_t = \frac{1}{N-t} \sum_{j=1}^{N-t} \mathrm{R}_j^{j+t} - \mathrm{R}_j^j \tag{7}$$

---

[1]Our code is available at: https://tinyurl.com/CLOPSSubmission

Lambda Backward Weight Transfer. BWT_t can be extended to all possible time-steps, t, to generate BWT_λ. Using this, one can identify potential improvements in methodology at the task-level.

$$\text{BWT}_\lambda = \frac{1}{N-1} \sum_{j=1}^{N-1} \left[\frac{1}{N-j} \sum_{t=1}^{N-j} \text{R}_j^{j+t} - \text{R}_j^j \right] \tag{8}$$

5.5 HYPERPARAMETERS

Depending on the continual learning scenario, we chose $\tau = 20$ or 40, as we found that to achieve strong performance on the respective validation sets. We chose $\tau_{MC} = 40 + n$ and the sample epochs $\tau_S = 41 + n$ where $n \in \mathbb{N}^+$ in order to sample data from the buffer at every epoch following the first task. The values must satisfy $\tau_S \geq \tau_{MC} > \tau$. For computational reasons, we chose the storage fraction $b = 0.1$ of the size of the training dataset and the acquisition fraction $a = 0.25$ of the number of samples per task in the buffer. To calculate the acquisition function, we chose the number of Monte Carlo samples, $T = 20$. We chose the regularization coefficient, $\lambda = 10$. We also explore the effect of changing these values on performance (see Appendices L and M).

6 EXPERIMENTAL RESULTS

6.1 CLASS-IL

Destructive interference is notorious amongst neural networks. In this section, we quantify such interference when learners are exposed to tasks involving novel classes. In Fig. 1a, we illustrate the AUC achieved on sequential binary classification tasks.

In Fig. 1a, we find that destructive interference is prevalent. For example, the network quickly forgets how to perform task $[0-1]$ once exposed to data from task $[0-2]$. This can be seen by the AUC $\approx 0.92 \rightarrow 0.30$. The final performance of the network for that particular task (AUC ≈ 0.78) is also lower than that maximally-achieved. In Fig. 1b, we show that CLOPS alleviates this interference. This can be seen by the absence of significant drops in AUC and higher final performance for all tasks relative to the fine-tuning strategy.

In Table. 1, we compare the performance of the CL strategies in the Class-IL scenario. We find that CLOPS outperforms MTL and the state-of-the-art methods, GEM and MIR, in terms of generalization performance and exhibits constructive interference. For example, CLOPS and MIR achieve an AUC $= 0.796$ and 0.753, respectively. Moreover, BWT $= 0.053$ and 0.009 for these two methods, respectively. Such a finding underscores the ability of CLOPS to deal with tasks involving novel classes. We also show that CLOPS is robust to task order (see Appendix G).

(a) Fine-tuning   (b) CLOPS

Figure 1: Mean validation AUC of the a) fine-tuning and b) CLOPS strategy ($b = 0.25$ and $a = 0.50$) in the Class-IL scenario. Each task belongs to a mutually-exclusive pair of classes from $\mathcal{D}_1$. Thicker curves indicate tasks on which the learner is currently being trained. The shaded area represents one standard deviation across five seeds.

Table 1: Performance of CL strategies in the Class-IL scenario. Storage and acquisition fractions are $b = 0.25$ and $a = 0.50$, respectively. Mean and standard deviation are shown across five seeds.

Method	Average AUC	BWT	BWT_t	BWT_λ
MTL	0.701 ± 0.014	-	-	-
Fine-tuning	0.770 ± 0.020	0.037 ± 0.037	$(0.076) \pm 0.064$	$(0.176) \pm 0.080$
Replay-based Methods				
GEM	0.544 ± 0.031	$(0.024) \pm 0.028$	$(0.046) \pm 0.017$	$(0.175) \pm 0.021$
MIR	0.753 ± 0.014	0.009 ± 0.018	0.001 ± 0.025	$(0.046) \pm 0.022$
CLOPS	$\mathbf{0.796 \pm 0.013}$	$\mathbf{0.053 \pm 0.023}$	$\mathbf{0.018 \pm 0.010}$	$\mathbf{0.008 \pm 0.016}$

6.2 TIME-IL

Environmental changes within healthcare can introduce seasonal shift into datasets. In this section, we quantify the effect of such a shift on learners. In Fig. 2a, we illustrate the AUC achieved on tasks with seasonally-shifted data.

In this scenario, we find that CLOPS is capable of achieving forward weight transfer (FWT). This can be seen by comparing the performance on task Term 3 in Figs. 2a and 2b. More specifically, CLOPS achieves an AUC ≈ 0.62 after one epoch of training, a value that the fine-tuning strategy only achieves after 20 epochs, signalling a 20-fold reduction in training time. We attribute this FWT to the loss-weighting role played by the task-instance parameters. By placing greater emphasis on more useful instances, the generalization performance of the network is improved.

(a) Fine-tuning   (b) CLOPS

Figure 2: Mean validation AUC of the (a) fine-tuning and (b) CLOPS strategy in the Time-IL scenario. Each task represents datasets collected at different times of the year. Thicker curves indicate tasks on which the learner is currently being trained. The shaded area represents one standard deviation from the mean across five seeds.

6.3 DOMAIN-IL

So far, we have shown the potential of CLOPS to alleviate destructive interference and allow for forward weight transfer. In this section, and in Table 2, we illustrate the performance of the CL strategies in the Domain-IL scenario. We show that CLOPS outperforms state-of-the-art methods. For example, CLOPS and MIR achieve an AUC $= 0.731$ and 0.716, respectively. CLOPS is also better at mitigating destructive interference, as shown by BWT $= 0.011$ and 0.025, respectively. We provide an explanation for such performance by conducting ablation studies in the next section.

6.4 EFFECT OF TASK-INSTANCE PARAMETERS, β, AND ACQUISITION FUNCTION, α

To better understand the root cause of CLOPS' benefits, we conduct two ablation studies: 1) **Random Storage** dispenses with task-instance parameters and instead randomly stores instances into the buffer, and 2) **Random Acquisition** dispenses with acquisition functions and instead randomly acquires

Table 2: Performance of CL strategies in the Domain-IL scenario. Storage and acquisition fractions are $b = 0.25$ and $a = 0.50$, respectively. Mean and standard deviation are shown across five seeds.

Method	Average AUC	BWT	BWT_t	BWT_λ
MTL	0.730 ± 0.016	-	-	-
Fine-tuning	0.687 ± 0.007	$(0.041) \pm 0.008$	$(0.047) \pm 0.004$	$(0.070) \pm 0.007$
Replay-based Methods				
GEM	0.502 ± 0.012	$(0.025) \pm 0.008$	$\mathbf{0.004 \pm 0.010}$	$(0.046) \pm 0.021$
MIR	0.716 ± 0.011	$(0.022) \pm 0.011$	$(0.013) \pm 0.004$	$(0.019) \pm 0.006$
CLOPS	$\mathbf{0.731 \pm 0.001}$	$\mathbf{(0.011) \pm 0.002}$	$(0.020) \pm 0.004$	$(0.019) \pm 0.009$

instances from the buffer. In Fig. 3, we illustrate the effect of both of these learning strategies on generalization performance as a function of different storage fractions, a, and acquisition fractions, b.

We find that networks benefit from the role of β as a loss-weighting mechanism. For example, in Fig. 3 (red rectangles), at $b = 1, a = 0.5$, we show that the inclusion of the loss-weighting mechanism improves the AUC by 5.6%. We hypothesize that this mechanism, analogous to an attention mechanism placed on instance losses, allows the network to learn *which* instances to further exploit. We also find that continual learning scenarios benefit from uncertainty-based acquisition functions. In Fig. 3 (black rectangles), at $a = 0.1, b = 0.5$, we show that the inclusion of uncertainty-based acquisition functions improves the AUC by 3.2%. We arrive at the same conclusion when evaluating backward weight transfer (see Appendix J).

Figure 3: Mean validation AUC of three different learning strategies in the Class-IL scenario. (left) CLOPS, (centre) Random Storage, and (right) Random Acquisition. Results are shown as a function of storage fractions, b, and acquisition fractions, a and are an average across five seeds.

6.5 VALIDATION OF INTERPRETATION OF TASK-INSTANCE PARAMETERS, β

We have claimed that instances corresponding to lower values of β, and by extension, s, are relatively more difficult to classify. We now attempt to validate this intuition. In Fig. 4, we illustrate the distribution of s values corresponding to each task.

We find that tasks differ in their difficulty level. For example, task $[6 - 7]$ is considered more difficult to solve than task $[8 - 9]$ as evidenced by the lower distribution mean of the former relative to the latter ($s \approx 18.85$ vs. 18.95). After extracting the two ECG recordings associated with the lowest and highest s values, we find that both belong to the same class, normal sinus rhythm. However, upon closer inspection, the recording with the lower s value exhibits a feature known as ST-elevation, typically associated with heart attacks. Mapping an ECG recording with such an abnormal feature to the normal class would have been a source of confusion for the network. We provide further qualitative evidence in Appendix H.

We can also leverage the s values to create a learning curriculum (Bengio et al., 2009) in which tasks, when presented in order of difficulty, help improve generalization performance. To create

Figure 4: Distribution of the tracked task-instance parameter values, s, corresponding to CLOPS ($b = 0.25$ and $a = 0.50$) in the Class-IL scenario. Each colour corresponds to a different task. The ECG recordings, associated with the lowest and highest s values, support the intuition of β as a proxy for task-difficulty.

this curriculum, we first fit a Gaussian, $\mathcal{N}(\mu_{\mathcal{T}}, \sigma_{\mathcal{T}}^2)$, to each of the distributions in Fig. 4 and define task-difficulty as $d_{\mathcal{T}} = \frac{1}{\mu_{\mathcal{T}}}$. Once the learner solves the easiest task, we expose it to the task that is most similar to the preceding one, with the aim of encouraging a smooth transition between tasks. We quantify such similarity between a pair of tasks as $1 - \mathcal{D}_H(\mu_0, \sigma_0^2, \mu_1, \sigma_1^2)$, where $\mathcal{D}_H$ is the Hellinger distance between two task-specific distributions, parameterized by μ_0, σ_0^2, and μ_1, σ_1^2, respectively. This generates a task-similarity matrix (see Appendix N) which can offer insight on task relationships.

In Table 3, in which we illustrate the performance of various curricula, we find that an Easy to Hard curriculum exhibits higher constructive interference than a random curriculum (AUC = 0.087 vs. 0.053). The alignment of such an outcome with the expectations of curriculum learning helps to further validate the intuition underlying β.

Table 3: Performance of CLOPS in the Class-IL scenario with different curricula. Storage and acquisition fractions are $b = 0.25$ and $a = 0.50$, respectively. Results are shown across five seeds.

Task Order	Average AUC	BWT	BWT_t	BWT_λ
Random	$\mathbf{0.796 \pm 0.013}$	0.053 ± 0.023	0.018 ± 0.010	0.008 ± 0.016
Easy to Hard	0.744 ± 0.009	$\mathbf{0.087 \pm 0.011}$	$\mathbf{0.038 \pm 0.021}$	$\mathbf{0.076 \pm 0.037}$
Hard to Easy	0.783 ± 0.022	0.058 ± 0.016	$(0.013) \pm 0.013$	$(0.003) \pm 0.014$

7 DISCUSSION AND FUTURE WORK

In this paper, we introduce a replay-based method applied to physiological signals, entitled CLOPS, to mitigate destructive interference during continual learning. CLOPS consists of an importance-guided buffer-storage and active-learning inspired buffer-acquisition mechanism. We show that CLOPS outperforms the state-of-the-art methods, GEM and MIR, on both backward and forward weight transfer. Furthermore, we propose learnable parameters, as a proxy for the difficulty with which instances are classified, which can assist with quantifying task difficulty and improving network interpretability. We now elucidate future avenues worth exploring.

Extensions to Task Similarity. The notion of task similarity was initially explored by Thrun & O'Sullivan (1996); Silver & Mercer (1996). In this work we briefly proposed a novel definition of task similarity and used it to guide the order of presentation of tasks. Exploring more robust definitions, validating them through domain knowledge, and exploiting them to further improve generalization is an exciting extension.

Predicting Destructive Interference. This work, and most research in CL, deals reactively with the notion of destructive interference. We observe this phenomenon and attempt to design approaches to alleviate it. An impactful research question can focus on *predicting* the degree of forgetting that may occur if one where to sequentially train on a particular dataset. With such knowledge, one can deploy tools to alleviate the problem proactively.

REFERENCES

Rahaf Aljundi, Eugene Belilovsky, Tinne Tuytelaars, Laurent Charlin, Massimo Caccia, Min Lin, and Lucas Page-Caccia. Online continual learning with maximal interfered retrieval. In *Advances in Neural Information Processing Systems*, pp. 11849–11860, 2019a.

Rahaf Aljundi, Min Lin, Baptiste Goujaud, and Yoshua Bengio. Gradient based sample selection for online continual learning. In *Advances in Neural Information Processing Systems*, pp. 11816–11825, 2019b.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th Annual International Conference on Machine Learning*, pp. 41–48, 2009.

Richard A Caruana. Multitask connectionist learning. In *In Proceedings of the 1993 Connectionist Models Summer School*. Citeseer, 1993.

Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with a-gem. *arXiv preprint arXiv:1812.00420*, 2018.

Yukun Chen, Robert J Carroll, Eugenia R McPeek Hinz, Anushi Shah, Anne E Eyler, Joshua C Denny, and Hua Xu. Applying active learning to high-throughput phenotyping algorithms for electronic health records data. *Journal of the American Medical Informatics Association*, 20(e2): e253–e259, 2013.

Sebastian Farquhar and Yarin Gal. Towards robust evaluations of continual learning. *arXiv preprint arXiv:1805.09733*, 2018.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning*, pp. 1050–1059, 2016.

Yarin Gal, Riashat Islam, and Zoubin Ghahramani. Deep Bayesian active learning with image data. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1183–1192. JMLR. org, 2017.

Wenbo Gong, Sebastian Tschiatschek, Richard Turner, Sebastian Nowozin, and José Miguel Hernández-Lobato. Icebreaker: element-wise active information acquisition with bayesian deep latent gaussian model. *arXiv preprint arXiv:1908.04537*, 2019.

Awni Y Hannun, Pranav Rajpurkar, Masoumeh Haghpanahi, Geoffrey H Tison, Codie Bourn, Mintu P Turakhia, and Andrew Y Ng. Cardiologist-level arrhythmia detection and classification in ambulatory electrocardiograms using a deep neural network. *Nature Medicine*, 25(1):65, 2019.

Neil Houlsby, Ferenc Huszár, Zoubin Ghahramani, and Máté Lengyel. Bayesian active learning for classification and preference learning. *arXiv preprint arXiv:1112.5745*, 2011.

David Isele and Akansel Cosgun. Selective experience replay for lifelong learning. In *Thirty-second AAAI Conference on Artificial Intelligence*, 2018.

Alistair EW Johnson, Tom J Pollard, Lu Shen, H Lehman Li-wei, Mengling Feng, Mohammad Ghassemi, Benjamin Moody, Peter Szolovits, Leo Anthony Celi, and Roger G Mark. Mimic-III, a freely accessible critical care database. *Scientific Data*, 3:160035, 2016.

Dani Kiyasseh, Tingting Zhu, and David A Clifton. Alps: Active learning via perturbations. *arXiv preprint arXiv:2004.09557*, 2020.

Matthias Lenga, Heinrich Schulz, and Axel Saalbach. Continual learning for domain adaptation in chest x-ray classification. *arXiv preprint arXiv:2001.05922*, 2020.

David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning. In *Advances in Neural Information Processing Systems*, pp. 6467–6476, 2017.

German I Parisi, Ronald Kemker, Jose L Part, Christopher Kanan, and Stefan Wermter. Continual lifelong learning with neural networks: A review. *Neural Networks*, 2019.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, pp. 8024–8035, 2019.

E. A. Perez Alday, A. Gu, A. Shah, C. Liu, A. Sharma, S. Seyedi, A. Bahrami Rad, M. Reyna, and G. Clifford. Classification of 12-lead ECGs: the PhysioNet - computing in cardiology challenge 2020 (version 1.0.1). *PhysioNet*, 2020.

Joaquin Quionero-Candela, Masashi Sugiyama, Anton Schwaighofer, and Neil D Lawrence. *Dataset shift in machine learning*. The MIT Press, 2009.

Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H Lampert. icarl: Incremental classifier and representation learning. In *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, pp. 2001–2010, 2017.

David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy Lillicrap, and Gregory Wayne. Experience replay for continual learning. In *Advances in Neural Information Processing Systems*, pp. 348–358, 2019.

Shreyas Saxena, Oncel Tuzel, and Dennis DeCoste. Data parameters: A new family of parameters for learning a differentiable curriculum. In *Advances in Neural Information Processing Systems*, pp. 11093–11103, 2019.

Burr Settles. Active learning literature survey. Technical report, University of Wisconsin-Madison, Department of Computer Sciences, 2009.

Daniel L Silver and Robert E Mercer. The parallel transfer of task knowledge using dynamic learning rates based on a measure of relatedness. In *Learning to learn*, pp. 213–233. Springer, 1996.

Asim Smailagic, Pedro Costa, Hae Young Noh, Devesh Walawalkar, Kartik Khandelwal, Adrian Galdran, Mostafa Mirshekari, Jonathon Fagert, Susu Xu, Pei Zhang, et al. Medal: Accurate and robust deep active learning for medical image analysis. In *IEEE International Conference on Machine Learning and Applications*, pp. 481–488, 2018.

Asim Smailagic, Pedro Costa, Alex Gaudio, Kartik Khandelwal, Mostafa Mirshekari, Jonathon Fagert, Devesh Walawalkar, Susu Xu, Adrian Galdran, Pei Zhang, et al. O-medal: Online active deep learning for medical image analysis. *arXiv preprint arXiv:1908.10508*, 2019.

David Spiegelhalter. Should we trust algorithms? *Harvard Data Science Review*, 2(1), 1 2020. doi: 10. 1162/99608f92.cb91a35a. URL https://hdsr.mitpress.mit.edu/pub/56lnenzj. https://hdsr.mitpress.mit.edu/pub/56lnenzj.

Sebastian Thrun and Joseph O'Sullivan. Discovering structure in multiple learning tasks: The tc algorithm. In *ICML*, volume 96, pp. 489–497, 1996.

Gido M van de Ven and Andreas S Tolias. Three scenarios for continual learning. *arXiv preprint arXiv:1904.07734*, 2019.

Guijin Wang, Chenshuang Zhang, Yongpan Liu, Huazhong Yang, Dapeng Fu, Haiqing Wang, and Ping Zhang. A global and updatable ecg beat classification system based on recurrent neural networks and active learning. *Information Sciences*, 501:523–542, 2019.

Jianwei Zheng, Jianming Zhang, Sidy Danioko, Hai Yao, Hangyuan Guo, and Cyril Rakovski. A 12-lead electrocardiogram database for arrhythmia research covering more than 10,000 patients. *Scientific Data*, 7(1):1–8, 2020.

Zongwei Zhou, Jae Shin, Lei Zhang, Suryakanth Gurudu, Michael Gotway, and Jianming Liang. Fine-tuning convolutional neural networks for biomedical image analysis: actively and incrementally. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 7340–7351, 2017.

Xiaojin Jerry Zhu. Semi-supervised learning literature survey. Technical report, University of Wisconsin-Madison, Department of Computer Sciences, 2005.