Empirical-Distribution Matching for Synthetic ECG Classification

Benedikt Kolbeinsson [1]   **Arinbjörn Kolbeinsson** [1]

Abstract

Conditional generative models are increasingly proposed as drop-in substitutes for restricted clinical datasets: train a generator once, release a synthetic cohort, and let practitioners reuse it without ever touching the source records. The practitioner's only design surface is then the sampling policy used to draw the synthetic training set. The main idea of this paper is that the standard rebalancing recipes from the CV and NLP imbalanced-learning literature do not transfer to this regime. The practitioner is better off matching the empirical training distribution as faithfully as possible at sample time. We test the idea by surveying thirteen sampling policies on a single 12-lead ECG latent diffusion model over PTB-XL using train-on-synthetic-test-on-real (TSTR) macro AUROC. No policy beats the naive bootstrap baseline at matched budget. The failures collapse onto three mechanisms: class-distribution distortion, within-class diversity collapse, and label-by-demographic joint decoupling.

1. Introduction

Synthetic-data pipelines for medical time series are increasingly deployed in a setting where the downstream practitioner never sees the underlying real records. A generator is trained once by a data custodian, and the practitioner receives only synthetic samples and trains classifiers, fairness probes, or stress tests directly on those samples. The regime covers privacy-restricted clinical data (Thambawita et al., 2021) as well as differentially-private generators (Ghalebikesabi et al., 2023; Jordon et al., 2019), where the real records cannot be released even to downstream model trainers. In this regime, the practitioner's only design surface is the *sampling policy*: how to draw the conditioning vectors that the generator will expand into samples.

The default sampling policy in published synthetic-medical pipelines is to bootstrap real training-record conditioning tuples uniformly at random, matching the empirical training distribution by construction. This is unsatisfying to the practitioner who reads the imbalanced-learning literature: SMOTE-family variants (Chawla et al., 2002; Mariani et al., 2018; Dablain et al., 2023), synthetic minority generation (Ye-Bin et al., 2025), and recent surveys (Gao et al., 2025; Liu et al., 2024) all converge on "rebalance toward the minorities". Two things differ in our setting: the practitioner cannot see the real records, and the "minority" samples come from a single shared generator rather than from a fixed real cohort. The main idea is that this regime change inverts the rebalancing recipe: match the empirical training distribution, do not rebalance away from it.

Contributions.

- We survey thirteen sampling policies for synthetic-only ECG classification on PTB-XL, all evaluated on a single shared latent diffusion generator at a matched downstream budget (Sections 3 and 4).

- No alternative beats a naive bootstrap of real conditioning tuples at matched budget, and the strongest match it only within noise (Section 5).

- The failures collapse onto three mechanisms that together cover the surface: class-distribution distortion, within-class diversity collapse, and label-by-demographic joint decoupling. A given policy can sit on more than one (Section 5).

- A 50/50 real+synth blend matches the same-size real-data ceiling, confirming the corpus is additive. In the synthetic-only regime that motivates the paper, this additivity is out of reach (Section 6).

2. Related work

The practitioner's downstream-classifier metric, TSTR, was introduced for medical time-series GANs (Thambawita et al., 2021) and is now standard for ECG generators (Alcaraz & Strodthoff, 2023; Skorik & Avetisyan, 2024; Lai et al., 2025). Most of these papers report a single TSTR number against a single sampling policy (a bootstrap of real

[1]K01, Reykjavík, Iceland. Correspondence to: Benedikt Kolbeinsson <benedikt@k01.is>.

Proceedings of the Workshop on Structured Data for Health at the 43rd International Conference on Machine Learning, Seoul, South Korea. Copyright 2026 by the author(s).

conditioning tuples, in our taxonomy), without comparing alternative policies. Ibrahim et al. (2025) probe synthetic medical time series at the subgroup level and is the closest evaluation work. The focus there is per-subgroup fidelity rather than the sampling policy used to draw the synthetic training set.

3. Setup

Data. PTB-XL (Wagner et al., 2020) is the largest freely-redistributable 12-lead ECG dataset: 21,799 ten-second recordings from 18,885 patients, multi-label-annotated in the 71-code SCP-ECG ontology with patient demographics. We adopt the official 10-fold patient-disjoint split (Strodthoff et al., 2021) unchanged: folds 1–8 ($n_{\text{train}} = 17{,}418$) train the generator and the downstream classifiers, fold 9 is used only for early stopping, and fold 10 ($n_{\text{test}} = 2{,}198$) is held out for all reported results. The label distribution is heavily skewed: of the 71 SCP codes, 8 have prevalence $\geq 5\%$, 7 have 2–5%, and 37 have $< 2\%$.

Generator. We use DCDM-ECG (Kolbeinsson & Kolbeinsson, 2026), a conditional latent diffusion model: a frozen 4.71M-parameter 1-D VAE encodes a 12×1000 ECG into a 4×128 latent, and a 5.36M-parameter U-Net denoiser operates in latent space, conditioned on a 76-dim vector that concatenates the 71-hot SCP label vector with five z-normalised demographic axes. Classifier-free guidance (Ho & Salimans, 2022) uses condition dropout 0.1 at training and CFG scale 3.0 at inference. Sampling is 100-step DDIM (Song et al., 2021). The denoiser is trained for 20k iterations on folds 1–8 (batch 128, AdamW, learning rate 10^{-4}, weight decay 10^{-5}, 1000 diffusion steps). The generator is held fixed. Only the *sampling policy* that produces conditioning tuples changes across Table 1.

TSTR protocol. For each policy we draw $n = 8000$ conditioning tuples, generate ECGs, train an XResNet1d-50 (He et al., 2019) for 30 epochs from random init on the synthetic corpus, and report macro AUROC over the 51 evaluable SCP codes on real fold 10. We bucket results by real training prevalence (common $\geq 5\%$, moderate 2–5%, rare $< 2\%$) and average three seeds per policy. The seed varies both the synthetic draw and the classifier init. The downstream classifier always sees 8000 training samples. Quality filter and Diversity selection generate a 16,000-sample pool and keep 8000, so they spend $2\times$ the *generator* budget at matched downstream budget. The natural upper bound is Real-data ceiling: the same XResNet1d-50 trained on 8000 real records, which we use as a ceiling throughout. The $n = 8000$ budget is the generator's saturation point: a sanity run at the full $n = 17{,}418$ moves macro TSTR by < 0.005.

4. Sampling policies

We organise the policies by which dimension of the empirical training distribution they deliberately deviate from.

Reference. Bootstrap re-uses an entire real training-record conditioning tuple drawn uniformly with replacement from folds 1–8: class prevalence, demographic marginals, and the label-by-demographic joint are all preserved by construction.

Class rebalancing. Uniform class equalises per-class prevalence by drawing one tuple from each non-empty SCP class in turn. Rare-class floor raises every class below 5% prevalence to that floor while leaving common classes alone. Rare oversampling multiplies every class's prevalence by 3 before normalisation.

Demographic. Demographic strata grids each class by age tertile and sex into 6 cells, then sub-samples cells with at least 3 real records. Demographic balance bootstraps labels from real records but resamples demographics independently to enforce 50/50 sex and uniform age decile. Joint decoupling preserves real label co-occurrence but draws each demographic axis independently from its training-set marginal, so no real record's full conditioning tuple ever reappears.

Filtering and relabelling. A held-out classifier judges the generated samples. Quality filter oversamples to 16,000 then keeps the top-half by global confidence. Stratified filter is the per-class-stratified version that removes the resulting prevalence drift. Iterative relabel keeps all 8000 samples but replaces each intended label with the classifier's binarised prediction before downstream training, a self-distillation step.

Diversity and prototype. Diversity selection generates a 16,000-sample pool and keeps the 8000 most diverse in the judge's 71-dim logit feature space, by greedy farthest-point selection. Class prototype replaces every training record's conditioning tuple with the per-class demographic centroid, generating from a class-typical prototype rather than from a real record.

5. Results

Table 1 reports each policy's TSTR macro AUROC with prevalence-bucket breakdowns, and Figure 1 plots the same numbers with baseline and ceiling drawn for reference. The results sort cleanly by failure mode.

Class rebalancing. Uniform class loses macro, concentrated on the rare bucket the rebalancing was supposed to

Table 1. Sampling policies for synthetic-only TSTR on PTB-XL. All rows generate $n_{train} = 8000$ synthetic 12-lead ECGs from a single shared generator, train an XResNet1d-50 classifier for 30 epochs on the synthetic corpus, and report macro AUROC on real PTB-XL fold-10 test ($n_{test} = 2198$), averaged over seeds. Buckets follow real training prevalence: common ($\geq 5\%$, 8 classes), moderate (2–5%, 7 classes), rare ($< 2\%$, 37 classes). The Real-data ceiling trains the same XResNet1d-50 on a same-size random subset of the real training set and is the practical upper bound at $n = 8000$. Bootstrap is the naive baseline. No synth-only policy recovers Bootstrap's macro, though several exceed it on the common bucket and give the gap back on the moderate and rare buckets. **Bold** marks the strongest sampling policy (below the rule) in each column.

Group	Policy	Macro	Common	Moderate	Rare
Reference	Real-data ceiling	0.9123 ± 0.010	0.9322	0.9145	0.9075
Reference	Bootstrap (baseline)	0.8845 ± 0.012	0.8823	0.8748	0.8869
Class	Uniform class	0.8637 ± 0.010	0.8722	0.8603	0.8624
Class	Rare-class floor	0.8775 ± 0.008	0.8907	0.8727	0.8755
Class	Rare oversampling	0.8697 ± 0.001	0.8848	0.8535	0.8695
Demographic	Demographic strata	0.8717 ± 0.006	0.8851	0.8657	0.8699
Demographic	Demographic balance	0.8712 ± 0.004	0.8814	0.8693	0.8693
Demographic	Joint decoupling	0.8666 ± 0.006	0.8767	0.8712	0.8634
Filter	Quality filter	0.8405 ± 0.002	0.8893	0.8728	0.8234
Filter	Stratified filter	0.8743 ± 0.009	0.8901	0.8705	0.8716
Filter	Iterative relabel	0.7907 ± 0.027	**0.9027**	**0.8760**	0.7492
Diversity	Diversity selection	$\mathbf{0.8814 \pm 0.007}$	0.8868	0.8662	**0.8831**
Diversity	Class prototype	0.7827 ± 0.009	0.7547	0.8155	0.7825

help. Rare oversampling repeats the shape: rare-bucket AUROC drops despite each rare class being trained on roughly three times as many synthetic samples. The intuition imported from a fixed dataset (oversample the minority, gain on the minority) does not survive the move to a generator: each new sample for a rare class is drawn from the same conditional distribution as the last, so multiplying the rare cohort multiplies its *noise* along with its size. Only Rare-class floor, the mildest variant, stays close to the baseline, and still falls below it.

Filtering and relabelling. Quality filter (global top-50% by classifier confidence) is among the worst macro performers, and the loss is almost entirely on the rare bucket where the judge's probabilities are noisiest. The Stratified filter removes the prevalence drift and comes closer, but still lands below the baseline. The clearest illustration is Iterative relabel: the common-class AUROC *rises* ($+0.020$) while rare-class AUROC *collapses* (-0.138) and seed variance triples. The mechanism is shared: any classifier-driven judge has well-calibrated probabilities on common classes and noisy ones on rare classes, so using it to filter, restratify, or relabel acts as a within-class diversity squeeze on the rare bucket specifically.

Demographic decoupling. Joint decoupling preserves both label prevalence and label co-occurrence, breaking only the label-by-demographic joint. It loses about as much macro as Uniform class despite changing nothing about class structure. Demographic balance (sex 50/50, age uniform across deciles) and Demographic strata (age-tertile $\times$ sex grid) land in the same band. Generator fidelity depends

on conditioning-tuple combinations that actually occur in training. Combinations the generator did not see are drawn from a weaker region of its conditional, even when the marginals look right.

Diversity and prototype. Class prototype, which replaces every record's conditioning tuple with the per-class demographic centroid, suffers the largest macro loss in the survey. The degradation is heaviest on the common bucket, the opposite of a pure within-class collapse, consistent with the class-mean centroid itself being off-distribution. Diversity selection, which keeps the empirical class distribution but selects by farthest-point distance in classifier feature space, is the strongest alternative, edging above the baseline on the common bucket but slipping below on the moderate and rare buckets. The pattern holds across the survey: the macro gap is decided on the tail, where moving probability mass off the empirical training distribution costs more than it returns, so the naive bootstrap gives up the least.

6. Synthetic + real reference

The policies above live in the synthetic-only setting motivated by the paper. As a sanity check, we also test the complementary regime in which the practitioner can mix real records into the downstream training set (Figure 2). A 50/50 blend of 4000 real and 4000 synthetic records reaches macro TSTR 0.908, statistically indistinguishable from the same-size pure-real ceiling. The synthetic corpus is therefore additive to real data rather than a noise floor. In the synthetic-only regime, however, no sampling policy can recover this additivity.

Figure 1. Macro TSTR by sampling policy, $n = 8000$ synthetic training samples, 30-epoch XResNet1d-50 downstream classifier. Color-coded by failure-mode group from Section 5. Dashed line: Bootstrap naive bootstrap baseline (0.8845). Dotted line: Real-data ceiling same-size real-data ceiling (0.907). Error bars are one standard deviation across seeds. No policy bar reaches the baseline.

Figure 2. Macro TSTR vs. real fraction in a real+synth mix at fixed total $n = 8000$. Error bars are one standard deviation across seeds. The blend saturates the same-size real-data ceiling at 50/50.

7. Discussion

The headline result, that no synthetic-only policy beats the naive bootstrap, runs against the CV/NLP rebalancing literature, where downstream macro is routinely improved by oversampling minorities or generating synthetic minority neighbours (Chawla et al., 2002; Mariani et al., 2018; Dablain et al., 2023; Ye-Bin et al., 2025). There the underlying samples are real but minority-scarce, so resampling, interpolating, or topping up with extra generated examples increases the classifier's exposure to rare classes without disturbing where those samples sit in input space. In our setting the samples are *entirely* generated by a single model whose per-class fidelity is itself non-uniform: the rare classes the practitioner most wants to oversample are the classes where the generator is weakest, and oversampling them multiplies

generator noise rather than recovering missing real support. The positive recipe is therefore the opposite of the CV/NLP one: track the empirical training distribution at sample time. Do not reweight prevalence, filter by classifier signal, or synthesise conditioning tuples that did not appear in training. The naive bootstrap does all three by construction.

Limitations. We evaluate on a single dataset, generator family, and downstream architecture. The failure-mode taxonomy should generalise because each mechanism has a clean information-theoretic reading, but the deltas are dataset-specific. The taxonomy is modality-agnostic in principle: the same mechanisms should arise for other conditional medical-time-series generators such as EHR or wearable signals, though we have not tested this. We also fix the downstream classifier to XResNet1d-50, and a stronger or differently biased one might absorb some of the distortion. Where partial real access is available, the synth+real blend in Section 6 is the appropriate baseline.

8. Conclusion

On synthetic-only PTB-XL TSTR, no alternative sampling policy beats the naive bootstrap at matched budget, and the strongest match it only within noise. The failures collapse onto three mechanisms: class-distribution distortion, within-class diversity collapse, and label-by-demographic decoupling. A real+synth blend saturates the same-size real-data ceiling, but this additivity is out of reach for the synthetic-only practitioner. The recipe inverts the CV/NLP one: track the empirical training distribution at sample time, do not try to repair it.

Acknowledgements

This work was supported by Iceland Technology Development Fund grant 2525674-601.

References

Alcaraz, J. M. L. and Strodthoff, N. Diffusion-based conditional ECG generation with structured state space models. *Computers in Biology and Medicine*, 163:107115, 2023.

Chawla, N. V., Bowyer, K. W., Hall, L. O., and Kegelmeyer, W. P. Smote: Synthetic minority over-sampling technique. *Journal of Artificial Intelligence Research*, 16:321–357, 2002.

Dablain, D., Krawczyk, B., and Chawla, N. V. DeepSMOTE: Fusing deep learning and SMOTE for imbalanced data. *IEEE Transactions on Neural Networks and Learning Systems*, 34(9):6390–6404, 2023.

Gao, X., Xie, D., Zhang, Y., Wang, Z., Chen, C., He, C., Yin, H., and Zhang, W. A comprehensive survey on imbalanced data learning. *arXiv preprint arXiv:2502.08960*, 2025.

Ghalebikesabi, S., Berrada, L., Gowal, S., Ktena, I., Stanforth, R., Hayes, J., De, S., Smith, S. L., Wiles, O., and Balle, B. Differentially private diffusion models generate useful synthetic images. *arXiv preprint arXiv:2302.13861*, 2023.

He, T., Zhang, Z., Zhang, H., Zhang, Z., Xie, J., and Li, M. Bag of tricks for image classification with convolutional neural networks. *arXiv preprint arXiv:1812.01187*, 2019. We use the 1-D adaptation (XResNet1d-50) standard in PTB-XL benchmarks.

Ho, J. and Salimans, T. Classifier-free diffusion guidance. *arXiv preprint arXiv:2207.12598*, 2022.

Ibrahim, H. et al. Enabling granular subgroup-level model evaluations by generating synthetic medical time series. *arXiv preprint arXiv:2510.19728*, 2025.

Jordon, J., Yoon, J., and van der Schaar, M. PATE-GAN: Generating synthetic data with differential privacy guarantees. In *International Conference on Learning Representations (ICLR)*, 2019.

Kolbeinsson, B. and Kolbeinsson, A. DCDM-ECG: Demographic-conditional diffusion model for 12-lead ECG generation. In *Workshop on Structured Data for Health at the 43rd International Conference on Machine Learning (ICML)*, 2026.

Lai, Y. et al. DiffuSETS: 12-lead ECG generation conditioned on clinical text reports and patient-specific information. *Patterns*, 2025.

Liu, B. et al. A comprehensive survey of synthetic tabular data generation. *arXiv preprint arXiv:2504.16506*, 2024.

Mariani, G., Scheidegger, F., Istrate, R., Bekas, C., and Malossi, C. BAGAN: Data augmentation with balancing GAN. In *ICML Workshop on Theoretical Foundations and Applications of Deep Generative Models*, 2018.

Skorik, S. and Avetisyan, G. SSSD-ECG-nle: New label embeddings with structured state-space models for ECG generation. *arXiv preprint arXiv:2407.11108*, 2024.

Song, J., Meng, C., and Ermon, S. Denoising diffusion implicit models. In *International Conference on Learning Representations (ICLR)*, 2021.

Strodthoff, N., Wagner, P., Schaeffter, T., and Samek, W. Deep learning for ECG analysis: Benchmarks and insights from PTB-XL. *IEEE Journal of Biomedical and Health Informatics*, 25(5):1519–1528, 2021.

Thambawita, V., Isaksen, J. L., Hicks, S. A., Ghouse, J., Ahlberg, G., Linneberg, A., Grarup, N., Ellervik, C., Olesen, M. S., Hansen, T., Graff, C., Holstein-Rathlou, N.-H., Strümke, I., Hammer, H. L., Maleckar, M. M., Halvorsen, P., and Riegler, M. A. DeepFake electrocardiograms using generative adversarial networks are the beginning of the end for privacy issues in medicine. *Scientific Reports*, 11(1):21896, 2021.

Wagner, P., Strodthoff, N., Bousseljot, R.-D., Kreiseler, D., Lunze, F. I., Samek, W., and Schaeffter, T. PTB-XL, a large publicly available electrocardiography dataset. *Scientific Data*, 7(1):154, 2020.

Ye-Bin, M., Nam, H.-W., Choi, W., Kim, N., Kwak, S., and Oh, T.-H. SYNAuG: Exploiting synthetic data for data imbalance problems. *Pattern Recognition Letters*, 193:115–122, 2025.