Persistent Reinforcement Learning via Subgoal Curricula

Abstract

Reinforcement learning (RL) promises to enable autonomous acquisition of complex behaviors for diverse agents. However, the success of current reinforcement learning algorithms is predicated on an often under-emphasised requirement – each trial needs to start from a fixed initial state distribution. Unfortunately, resetting the environment to its initial state after each trial requires substantial amount of human supervision and extensive instrumentation of the environment which defeats the purpose of autonomous reinforcement learning. In this work, we propose Value-accelerated Persistent Reinforcement Learning (VaPRL), which generates a curriculum of initial states such that the agent can bootstrap on the success of easier tasks to efficiently learn harder tasks. The agent also learns to reach the initial states proposed by the curriculum, minimizing the reliance on human interventions into the learning. We observe that VaPRL reduces the interventions required by three orders of magnitude compared to episodic RL while outperforming prior state-of-the art methods for reset-free RL both in terms of sample efficiency and asymptotic performance on a variety of simulated robotics problems.

1 Introduction

Reinforcement learning (RL) offers an appealing opportunity to enable autonomous acquisition of complex behaviors for interactive agents. Despite recent RL successes on robots [22, 28, 21, 23, 29, 18, 26, 19, 11], several challenges exist that inhibit wider adoption of reinforcement learning for robotics [41]. One of the major challenges to the autonomy of current reinforcement learning algorithms, particularly in robotics, is the assumption that each trial starts from an initial state drawn from a specific state distribution in the environment. Conventionally, reinforcement learning algorithms assume the ability to arbitrarily sample and reset to states drawn from this distribution, making such algorithms impractical for most real-world setups.

Many prior examples of reinforcement learning on real robots have relied on extensive instrumentation of the robotic setup and human supervision to enable environment resets to this initial state distribution. This is accomplished through a human providing the environment reset themselves throughout the training [6, 9, 3], scripted behaviors for the robot to reset the environment [23, 33], an additional robot executing scripted behavior to reset the environment [26] or engineered mechanical contraptions [39, 19]. The additional instrumentation of the environment and creating scripted behaviors is time-intensive, and it often requires additional resources such as sensors or even robots. The scripted reset behaviors are narrow in application, often designed for just a single task or environment, and their brittleness mandates human oversight of the learning process. Eliminating or minimizing the algorithmic reliance on the reset mechanisms can enable more autonomous learning, and in turn it will allow agents to scale to broader and harder set of tasks.

To address these challenges, a number of recent works have developed reinforcement learning algorithms that can effectively learn with minimal resets to the initial distribution [15, 4, 41, 36, 11]. We provide a formal problem definition that encapsulates and sheds light on the general setting

Figure 1: Comparison of the persistent RL setting with the episodic RL setting. Interventions (human or otherwise orchestrated) reset the environment to the initial state distribution after every episode in episodic RL, while the state of the environment persists through the training in persistent RL. The learned policy is tested starting from the initial state distribution for both the settings.

addressed by these prior methods, which we refer to as the *persistent reinforcement learning* problem. In our problem description, we disentangle the training and the test time settings such that the test-time objective matches that of the conventional RL setting but the train-time setting restricts access to the initial state distribution by giving a *low frequency* periodic reset. In this setting, the agent must persistently learn and interact with the environment with minimal human intervention or help, as shown in Figure 1. Conventional episodic RL algorithms often fail to solve the task entirely in this setting, as shown in [41] and Figure 2. This is because these methods rely on the ability to sample the initial state distribution arbitrarily. One solution to this problem is to additionally learn a reset policy that recovers the initial state distribution [15, 4] allowing the agent to repeatedly alternate between practicing the task and practicing the reverse. Unfortunately, not only can solving the task directly from the initial state distribution be hard from an exploration standpoint, but (attempting to) return to the initial state repeatedly can be sample inefficient. In this paper, we propose to instead have the agent reset itself to and attempt the task from different initial states along the path to the goal state. In particular, the agent can learn to solve the task from easier starting states that are closer to the goal and bootstrap on these to solve the task from harder states farther away from the goal.

The main contribution of this work is *Value-accelerated Persistent Reinforcement Learning* (VaPRL), a goal-conditioned RL method that creates an adaptive curriculum of starting states for the agent to efficiently improve test-time performance while substantially reducing the reliance on extrinsic reset mechanisms. Additionally, we provide a formal description of the persistent RL problem setting to conceptualize our and prior methods on reset-free reinforcement learning. We benchmark VaPRL on several goal-conditioned robotic control tasks in the persistent RL setting against state-of-the-art methods, which either simulate the initial state distribution by learning a reset controller, or incrementally grow the state-space from which the given task can be solved. Our experiments indicate that using a tailored curriculum generated by VaPRL can be up to 30% more sample-efficient in acquiring task behaviors compared to the current methods. For the most challenging dexterous manipulation problem, VaPRL provides a 2.5× gain in performance compared to the next best performing method.

Figure 2: The performance of episodic RL algorithms substantially deteriorates when environment resets are not available.

2 Related Work

Robot learning. Prior works using reinforcement learning have relied on manually design controllers or human supervision to enable episodic environmental resets, as is required by the current algorithms. This can be through human orchestrated resets [6, 10, 9, 3, 13], which requires high frequency human intervention in robot training. In some cases, it is possible to execute a scripted behavior to reset the environment [23, 26, 40, 33, 39, 1]. However, programming such behaviors is time-intensive for the practitioner, and robot training still requires human oversight as the scripted behaviors are often brittle. Some prior works have designed the environment [29, 5, 18] to bypass the need for having a reset mechanism. This is not generally applicable and can require extensive environment design. Some recent works leverage multi-task RL to bypass the need for extrinsic reset mechanisms [12, 11]. Typically, a task-graph uses the current state to decides the next task for the agent, such that

only minimal intervention is required during training. However, these task-graphs are specific to a problem and require additional engineering to appropriately decide the next task.

Reset-free reinforcement learning. Constraining the access to these orchestrated reset mechanisms severely impedes policy learning when using current RL algorithms [41]. Recent works have proposed several algorithms to reduce reliance on extrinsic reset mechanisms by learning a reset controller to retrieve the initial state distribution [15, 4], by learning a perturbation controller [41], or by learning reset skills in adversarial games [36]. These works implicitly define a target state distribution for a reset controller: Han et al. [15], Eysenbach et al. [4] target a fixed initial state distribution; Zhu et al. [40] target a uniform distribution over the state space as a consequence of novelty-seeking behavior of the reset controller; and Xu et al. [36] target an adversarial form of initial state distribution to produce a more robust policy. In contrast, our proposed algorithm VaPRL generates a curriculum of starting states tailored to the task and agent's performance. Our experiments demonstrate that VaPRL outperforms these prior methods in both sample efficiency and absolute performance. Other recent work like [24] has considered combining model-based RL with unsupervised skill discovery to solve reset-free learning problems, but largely focus on avoiding sink states rather than attempting tasks repeatedly with a curriculum like VaPRL.

Curriculum generation for reinforcement learning. Curriculum generation is a crucial aspect of sample-efficient learning in VaPRL. Prior works have shown that using a curriculum can enable faster learning and improve performance [7, 8, 34, 25, 27]. Task-tailored curriculum can simplify the exploration as it is easier to solve the task from certain states [17, 7] enabling faster progress on the downstream task. In addition to proposing a novel method for curriculum generation, we design it for the persistent RL setting without requiring the ability to reset the environment to arbitrary states as contrasted by prior work.

Persistent vs. lifelong reinforcement learning. Prior reinforcement learning algorithms that reduce the need for oracle resets have relied on the problem setting of lifelong or continual reinforcement learning [35, 20], when the objective in practice is to learn episodic behaviors. Both the persistent RL and the lifelong learning frameworks do transcend the episodic setting for training, promoting more autonomy in reinforcement learning. However, persistent reinforcement learning distinguishes between the training and evaluation objectives, where the evaluation objective matches that of the episodic reinforcement learning. While the assumptions of episodic reinforcement learning are hard to realize for real-world training, real-world deployment of policies is often *episodic*. This is commonly true for robotics, where the assigned tasks are expected to be repetitive but it is hard to orchestrate resets in the training environment. This makes persistent reinforcement learning a suitable framework for modelling robotic learning tasks.

3 Persistent Reinforcement Learning

In this section, we formalize the persistent reinforcement learning as an optimization problem. The key insight is to separate the evaluation and training objectives such that the evaluation objective measures the performance of the desired behavior while the training objective enables us to acquire those behaviors recognizing that frequent invocation of reset mechanism is untenable. We first provide a general formulation, and then we adapt persistent RL for goal-conditioned reinforcement learning.

Definition. Consider a Markov Decision Process (MDP) $\mathcal{M}_E \equiv (\mathcal{S}, \mathcal{A}, p, r, \rho, \gamma, H_E)$ [31]. Here, $\mathcal{S}$ denotes the state space, $\mathcal{A}$ denotes the action space, $p : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \mapsto \mathbb{R}_{\geq 0}$ denotes the transition dynamics, $r : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}$ denotes the reward function, $\rho : \mathcal{S} \mapsto \mathbb{R}_{\geq 0}$ denotes the initial state distribution, $\gamma \in [0, 1]$ denotes the discount factor, and H_E denotes the episode horizon. Our objective is to learn a policy π that maximizes $J_E(\pi) = \mathbb{E}[\sum_{t=1}^{H_E} \gamma^t r(s_t, a_t)]$, where $s_0 \sim \rho(\cdot)$, $a_t \sim \pi(\cdot \mid s_t)$ and $s_{t+1} \sim p(\cdot \mid s_t, a_t)$, the episodic expected sum of discounted rewards.

However, generating samples from the initial state distribution ρ invokes a reset mechanism, which is hard to realize in the real world. We want to construct a MDP $\mathcal{M}_T$ corresponding to our training environment which reduces invocations of the reset mechanism. One simple way to reduce interventions is to consider $\mathcal{M}_T \equiv (\mathcal{S}, \mathcal{A}, p, \tilde{r}_t, \tilde{\rho}, \gamma, H_T)$ where the episode horizon in the training environment $H_T \gg H_E$. Näively optimizing r can substantially deteriorate the performance of episodic RL algorithms, as shown in Figure 2 where we compare the evaluation performance when training environments with $H_T = 200$ and $H_T = 200,000$ and $H_E = 200$ in both the cases. Therefore, it becomes beneficial to consider a surrogate reward function $\tilde{r}_t$ rather than just optimizing for r naively. As a motivating example, consider a forward-backward controller which alternates between

solving the task corresponding to r and recovering the initial state distribution ρ. The surrogate reward function corresponding to this can be written down as:

$$\tilde{r}_t(s_t, a_t) = \begin{cases} r(s_t, a_t) & t = [1, H_E], [2H_E + 1, 3H_E], \dots \\ r_\rho(s_t, a_t) & t = [H_E + 1, 2H_E], \dots \end{cases} \tag{1}$$

Here, $\tilde{r}$ alternates between the task-reward r for H_E steps and r_ρ (which encourages initial state distribution recovery) for H_E steps[1], also shown intuitively in Figure 3 (*right*). This surrogate reward function enables the agent to repeatedly practice the task utilizing the autonomous interaction more judiciously as compared to the naïve approach. Note, this $\tilde{r}$ loosely recovers the objectives used in some prior works [15, 4]. For a general time-dependent surrogate reward function $\tilde{r}_t$, we can define the training objective as

$$J_T(\pi) = \mathbb{E}_{s_0 \sim \tilde{\rho}, a_t \sim \pi(\cdot|s_t), s_{t+1} \sim p(\cdot|s_t, a_t)} \Big[\sum_{t=1}^{H_T} \gamma^t \tilde{r}_t(s_t, a_t) \Big] \tag{2}$$

where $\tilde{\rho}$ is the initial state distribution at training time (which does not need to match the evaluation-time initial state distribution ρ). The persistent RL optimization objective is to maximize $J_T(\pi)$ efficiently under the constraint that $J_E(\arg\max_\pi J_T(\pi)) = \max_\pi J_E(\pi)$. Intuitively, the objective encourages construction of a training environment that can recover the optimal policy for the evaluation environment. The primary design choice is $\tilde{r}_t$, which as shown above leads to different algorithms. Another design choice is $\tilde{\rho}$, which may or may not match ρ. Note, we do not assume $\tilde{\rho}$ is any easier to sample compared to ρ.

The formulation discussed here is suitable for reversible environments. Reversible environments guarantee that the agent can continue to make progress on the task and not get "stuck" (for example, if the object goes out of reach of the robot's arm). A large class of tasks can be considered reversible (door opening, cloth folding and so on) or the environment can be constructed to enforce reversibility (add bounding walls so the object does not go out of reach). In this work, we will restrict ourselves to reversible environments for evaluation. We defer a full discussion of persistent RL for environments with irreversible states to future work.

Goal-conditioned persistent reinforcement learning. We adapt the general formulation discussed above to a goal-conditioned [16, 32] instantiation of persistent RL. Consider a goal-conditioned MDP $\mathcal{M}_E \equiv (\mathcal{S}, \mathcal{A}, \mathcal{G}, p, r, \rho, \gamma, H_E)$, where $\mathcal{G} \subseteq \mathcal{S}$ denotes the goal space. For a goal distribution $p_g : \mathcal{G} \mapsto \mathbb{R}_{\geq 0}$, the evaluation objective $J_E(\pi) = \mathbb{E}_{g \sim p_g(\cdot)} \mathbb{E}_{\pi(\cdot|s,g)}[\sum_{t=1}^{H_E} \gamma^t r(s, g)]$ for $\pi : \mathcal{S} \times \mathcal{A} \times \mathcal{G} \mapsto \mathbb{R}_{\geq 0}$. The training objective can be stated as:

$$J_T(\pi) = \mathbb{E}_{s_0 \sim \tilde{\rho}, a_t \sim \pi(\cdot|s_t, G(s_t, p_g)), s_{t+1} \sim p(\cdot|s_t, a_t)} \Big[\sum_{t=1}^{H_T} \gamma^t r(s_t, G(s_t, p_g)) \Big], \tag{3}$$

where we assume that $\tilde{r} = r$, but we instead use a goal generator G to generate a goal curriculum to practice through the training episode[2]. The intuition here is that, since $H_T \gg H_E$, the algorithm can repeatedly practice reaching various task-goals. However, the objective is to learn a policy which can reach these task-goals in the test environment, that is, starting from the initial state distribution ρ. This implies the goal generator G must expand the goal space beyond the task-goals to improve the policy π for the test environment. For example, the goal generator can alternate task-goals ($g \sim p_g$) and the initial state distribution ($s \sim \rho$), which again loosely recovers some of the prior work [15, 4]. This instantiation transforms the problem of finding the right reward function $\tilde{r}$ to the right curriculum of goals using G. The objective of this goal generator is to recover the optimal policy with respect to J_E efficiently training in an environment with $H_T \gg H_E$.

4 Value-Accelerated Persistent Reinforcement Learning

In this section, we describe our proposed algorithm, VaPRL. The key idea in VaPRL is that the agent does not need to return to the initial state distribution between every attempt at the task, and can exploit the persistence of the environment to select starting states for each attempt that facilitate efficient learning. Section 4.1 discusses how to generate this curriculum of initial states. Using the goal-conditioned RL for VaPRL enables us to use the same policy to solve the task and reach the

---

[1]We assume that the state includes information indicating the reward function being optimized so that agent can take appropriate actions, for example, task-variables as is common in multi-task RL.

[2]The goal generator may use additional memory which is not explicitly represented here.

Figure 3: An overview of the VaPRL algorithm *(left)* as compared to forward-backward learning algorithm *(right)* for persistent RL. For VaPRL, the value function gives us a set of states from where the agent can solve the task with some confidence (shaded in green), and the VaPRL chooses the state closest to the initial state distribution among them (purple square). In each iteration, the agent can bootstrap on the knowledge of solving the task from a future state (bold green) which simplifies the exploration from its current state (broken green line). As the performance of the agent improves, the states commanded by VaPRL move closer to the initial state distribution. This is in contrast to the forward-backward controller that alternates between the test-goals and the initial state distribution.

initial states suggested by the curriculum, which is in contrast to prior work that learns a separate reset and task policy. Section 4.2 describes how careful goal relabelling can be leveraged to efficiently learn this unified goal-reaching policy. We also discuss how our algorithm can effectively use prior data, which often becomes crucial for efficiently solving hard sparse-reward tasks.

4.1 Generating a Curriculum Using the Value Function

Consider the problem of reaching a goal $g \sim p_g$ in the MDP $\mathcal{M}_E$. Learning how to reach the goal g is easier from an initial state $s \in \mathcal{S}$ that is close to g, especially when the rewards are sparse. Knowing how to reach the goal g from a state s in turn makes it easier to reach the goal from states in the neighbourhood of s, enables us to incrementally move farther away from the goal g. This forms the core intuition of using a curriculum in reinforcement learning as illustrated in Figure 3, allowing us to bootstrap on the success of an easier problem to solve a harder problem.

Given the goal-conditioned RL setting, we aim to learn a policy that is able to reach a goal g from the curriculum-generated state $C(g)$. A simple scheme for the goal generator can be to sample a goal $g \sim p_g$, run the policy π with the curriculum goal $C(g)$, and then run the policy with the task goal g. The main question in this setting is: given a goal g, how do we select the state $C(g)$ to attempt the goal from? We propose to setup $C(g)$ as follows:

$$C(g) = \arg\min \ \mathcal{X}_\rho(s) \quad \text{s.t.} \quad V^\pi(s, g) \geq \epsilon, \tag{4}$$

where $\mathcal{X}_\rho$ is a user-specified distance between the state s and the initial state distribution ρ, $V^\pi(s, g) = \mathbb{E}[\sum_{t=1}^{H_E} \gamma^t r(s, g) \mid s_1 = s]$ denotes the value function of the policy π reaching the goal g from the state s and $\epsilon \in [0, 1]$ is some fixed threshold. The evaluation objective for MDP $\mathcal{M}_E$ encourages the policy to learn how to reach a goal g from the initial state distribution. However, learning can be made more efficient if we generate a curriculum, starting close to the goal and gradually transitioning to the initial state distribution. The value function represents the ability of the policy to reach the goal g from the state s. For a discount factor $\gamma = 1$, the value function V^π represents the probability of reaching a goal g from state s. The intuition carries over to $\gamma \in [0, 1)$ too, where the environment can go into a terminal state with probability $1 - \gamma$ at every transition. Revisiting Equation 4, the objective $C(g)$ chooses the state closest to the initial state distribution for which the ability to reach the goal g crosses the threshold ϵ. This encourages the curriculum to be closer to the goal state in the early stages of the training as the policy would be less effective at reaching the goal. As the policy improves, the curriculum moves closer to the initial state distribution, which eventually leads to a policy π that solves the task starting from an initial state. Following this intuition, we can write the goal generator $G(s_t, p_g)$ as:

$$G(s_t, p_g) = g \quad \text{s.t.} \quad \begin{cases} g_{task} \sim p_g, \ g \leftarrow C(g_{next}) & \text{if } \text{switch}(s_t, g) \cap g_{task} = \emptyset \\ g \leftarrow g_{task}, \ g_{task} \leftarrow \emptyset & \text{elif } \text{switch}(s_t, g) \end{cases} \tag{5}$$

209 where the switch(s_t, g_{cur}) is true if the $r(s_t, g_{cur}) = 1$ or the current goal has been in place for
210 H_E steps. The policy first attempts to reach the goal $C(g)$ for H_E steps or until success, and then
211 switches to reaching the goal g. This cycles repeats until the environment resets after H_T steps.

212 **Computing the Curriculum Generator** $C(g)$. Equation 4 involves a minimization over the state
213 space $\mathcal{S}$, which is intractable in general. While it is possible to come up with more general solutions
214 by constructing a generative model $p(s)$ and taking a minimum over the samples generated by it, we
215 opt for a simpler solution: we use the data collected by the policy π during the environment training
216 as the source of our data and minimize $C(g)$ over a randomly sampled subset of it by enumeration. If
217 an offline dataset or demonstrations are available to the algorithm, we can also minimize $C(g)$ on this
218 available data exclusively. The minimization itself can be done by considering the subset of the data
219 which satisfies the constraint $V^\pi(s, g) \geq \epsilon$ and choosing the state from this subset which minimizes
220 $\mathcal{X}_\rho$. If no state satisfies the constraint, $C(g)$ returns the state with the maximum $V^\pi(s, g)$.

221 **Measuring the Initial State Distribution Distance.** An important component of curriculum gener-
222 ation is choosing the distance function $\mathcal{X}_\rho(s)$. The distance function should reflect the distance of the
223 state from the initial state distribution under the dynamics of the environment. To factor this into the
224 measure, we can use the goal-conditioned value function as measure of shortest distance between
225 the state and the goal [16, 30]. In particular, we can use $\mathcal{X}_\rho(s) = -\mathbb{E}_{s_0 \sim \rho} V^\pi(s, s_0)$. While this
226 choice is fairly convenient as we are already estimating $V^\pi(s, g)$, there is an even simpler choice for
227 $\mathcal{X}_\rho(s)$ which exploits the temporal structure of demonstrations or offline data, if available. Assuming
228 that the trajectories in the provided dataset start from the initial state distribution ρ, we can use the
229 state index of the state as the distance from the initial state distribution, that is $\mathcal{X}_\rho(s) = \arg_t(s, \mathcal{D})$
230 where $\mathcal{D}$ denotes the offline dataset/demonstration set. The *step index distance function* defined here
231 encodes the intuition that states which require more steps by the policy are farther away. The function
232 naturally accommodates for the dynamics of the environment. Finally, since we are minimizing $\mathcal{X}_\rho(s)$
233 in Equation 4, even if there are multiple trajectories to the same state or suboptimal loops within a
234 single trajectory, we will use the shortest distance to that state. Overall, step index distance function
235 is extremely simple to compute and use.

4.2 Relabelling Goals

237 Not only does our policy need to learn how to reach
238 $g \sim p_g$, but it also needs to learn how to reach all the goals
239 generated by $C(g)$ over the course of training, causing the
240 effective goal-space to grow substantially. However, there
241 is a lot of shared structure in reaching goals, especially
242 those generated by the curriculum. The knowledge of
243 how to reach a goal g_1 also conveys meaningful informa-
244 tion about how to reach a goal g_2. This structure can be
245 leveraged by using the techniques from goal relabelling
246 [2]. In particular, we relabel every trajectory collected in
247 the training environment with N goals sampled randomly
248 from the set of goals that may be a part of the curriculum.
249 If we do not have any prior data, we randomly sample the

Figure 4: An illustration of goal relabeling in VaPRL. Every transition in a trajectory is relabeled with a randomly sampled subset of curriculum goals, yielding a large set of relabeled tuples that are added to the replay buffer. This ensures efficient data reuse.

250 replay buffer for relabelling goals. If we are given some prior data $\mathcal{D}$, this reduces to sampling
251 $g \sim \mathcal{D} \cup \{g' \sim p_g\}$ for relabelling.

252 There is a subtle difference between hindsight experience replay (HER) and goal relabelling strategy
253 we employ. While HER chooses future states from within an episode as goals for relabelling, we
254 exclusively choose states that may be used as goal states in the curriculum, which may not occur in
255 the collected trajectory at all. Since our policy will only be tasked with reaching goals generated by
256 the goal generator G, it is advantageous to extract signal specifically for these goals. To summarize,
257 while the goal-space has grown, goal relabelling enables us to generate data for the algorithm
258 commensurately to improve the sample-efficiency of the algorithm. The outline for VaPRL is given
259 in Algorithm 1. Additional implementation details can be found in the Appendix.

5 Experiments

261 In this section, we study the performance of VaPRL on continuous control environments for goal-
262 conditioned persistent RL and provide ablations and visualization to isolate the effect of the curricu-
263 lum. In particular, we aim to answer the following questions:

264   1. Does VaPRL allow efficient reinforcement learning with minimal episodic resets?

Algorithm 1: Value-Accelerated Persistent Reinforcement Learning (VaPRL)

Input: initial state(s) $\mathcal{D}_\rho$, N; // N: number of goals for relabelling
Optional: Demos $\mathcal{D}$;
Initialize $\mathcal{R}, \pi(a \mid s, g), \mathcal{Q}^\pi(s, a, g)$;
// If demos, add them to replay buffer and relabel
$\mathcal{R} \leftarrow \mathcal{R} \cup \mathcal{D}$;
relabel_demos($\mathcal{R}$);
while *not done* **do**
    $s \sim \tilde{\rho}$; // sample initial state
    for H_T *steps* **do**
        $g \leftarrow G(s, p_g)$;
        $a \sim \pi(\cdot \mid s, g), s' \sim p(\cdot \mid s, a)$;
        $\mathcal{R} \leftarrow \mathcal{R} \cup \{(s, a, s', g, r(s', g))\}$;
        for $i \leftarrow 1, i \leq K$ **do**
            $\tilde{g} \sim \mathcal{D} \cup p_g$; // if $\mathcal{D} = \emptyset$, sample replay buffer
            $\mathcal{R} \leftarrow \mathcal{R} \cup \{(s, a, s', \tilde{g}, r(s', \tilde{g})\}$;
        update π, Q^π;
        $s \leftarrow s'$;

Figure 5: Continuous control environments for goal-conditioned persistent RL. (*top left*) A table-top rearrangement task, where a gripper is tasked with moving the mug to four potential goal positions, (*top right*) a sawyer robot learns how to close the door and (*bottom*) a high-dimensional dexterous hand attached to a sawyer robot is tasked to pick up a three-pronged object.

2. How does the scheme for generating a curriculum in VaPRL perform compared to other methods for persistent reinforcement learning?
3. Does VaPRL scale to high dimensional state and action spaces?
4. What does the generated curriculum look like? Is the curriculum effective?

We next describe the specific choices of environments, evaluation metrics and comparisons in order to answer the questions above.

Environments. For our experimental evaluation, we consider three continuous control environments, shown in Figure 5. The *table-top rearrangement* is a simplified manipulation environment, where a gripper (modelled as a point mass which can attach to the object if it is close to it) is tasked with taking the mug to one of the 4 potential goal squares. The evaluation horizon is $H_E = 200$ steps and the training horizon is $H_T = 200,000$ steps. This task involves a challenging exploration problem in navigating to objects, picking them up, and dropping them at the right location. The *sawyer door closing* environment involves using a sawyer robot arm to close a door to a particular target angle [38]. For this environment, we set the horizon for evaluation to be $H_E = 400$ and $H_T = 200,000$ steps for training. Since environment resets are not freely available, repeatedly practicing the task implicitly requires the agent to learn how to open the door. The *hand manipulation* environment involves a dexterous hand attached to a sawyer robot. This environment entails a 16 DoF hand that is mounted onto a 6 DoF arm, with the goal of manipulating a 3 pronged object as seen in Figure 5. In particular, the task involves picking up the object from random positions on a table and lifting it to a goal position above the table. This task is particularly challenging since it involves complex contact dynamics with high dimensional state and action spaces. Additionally, the robot has to learn how to reconfigure the object to diverse locations to simulate the test-time conditions where the agent is expected to pickup the object from random locations. For this environment, we set the horizon for evaluation $H_E = 400$ and for training $H_T = 400,000$ steps.

Environment Setup. For *table-top rearrangement* and *sawyer door closing*, we consider a sparse reward function $r(s, g) = \mathbb{I}(s, g)$, which is 1 when the state s is close to the goal position g, and 0 otherwise. Since the *hand manipulation* environment is a substantially more challenging problem, we consider a dense reward function which rewards the the hand and the object to be close to the goal position. To aid exploration in *table-top rearrangement* and *sawyer door closing*, we provide the agent with small set of trajectories (6 per goal, 3 going from initial state to the goal and the other 3 going in reverse) for each environment, though we do not assume that the trajectories take the optimal path (for example, the trajectories could come from teleoperation in practice). For the *hand manipulation* environment, we provide the agent with 10 trajectories demonstrating the pickup task from random positions on the table and 20 trajectories showing how to reposition the object to different locations on the table. For all environments, we report results by evaluating the number of times the policy successfully reaches the goal out of 10 trials in the evaluation environment $\mathcal{M}_E$ (by resetting to a state from the initial state distribution ρ and sampling an appropriate goal from the goal

Figure 6: Performance of each method on (*left*) the table-top rearrangement environment, (*center*) the sawyer door closing environment, and (*right*) the hand manipulation environment. Plots show learning curves with mean and standard error over 5 random seeds. VaPRL is more sample-efficient and outperforms prior methods.

distribution p_g), performing intermittent evaluations as the training progresses. Note, the training agent does not receive the evaluation experience and it is only used to measure the performance on the evaluation environment. Further details about problem setup, demonstrations, implementation, hyperparameters and evaluation metrics can be found in the Appendix.

Comparisons. We compare VaPRL to four approaches: (a) A standard off-policy RL algorithm that only trains to reach the goal distribution, such that a new goal $g \sim p_g(s)$ is sampled every H_E steps (labelled **naïve RL**), (b) A forward-backward controller [15, 4] which alternates between $g \sim p_g(s)$ and $g \sim \rho(s)$ for H_E steps each, as described in Section 3 (labelled **FBRL**), (c) A perturbation controller [41] that alternates between optimizing a controller to maximize task reward and a controller to maximally perturb the state via task agnostic exploration (labelled **R3L**), and (d) RL directly on the evaluation environment, resetting to the initial state distribution after every H_E steps (labelled **oracle RL**). This oracle is an expected upper bound on the performance of VaPRL, since it has access to episodic resets. We use soft actor-critic [14] as the base RL algorithm for all methods to ensure fair comparison, although any value-based method would be equally applicable. To emphasize, all the algorithms are provided the same set of demonstrations. Further implementation details can be found in the Appendix.

5.1 Persistent RL Results

The performance of each of the algorithms on the three evaluation domains are shown in Figure 6. We see that VaPRL outperforms naïve RL, FBRL and R3L, providing substantial improvements in terms of sample efficiency. For our most challenging domain of hand manipulation, the sample efficiency enables us a reach a much better performance within the training budget. The primary difference between the methods is that VaPRL uses a curriculum of starting states progressing from easier to harder states. In contrast, FBRL always attempts to reach the initial state distribution and R3L uses a perturbation controller to reach novel states in attempt to cover the entire state space uniformly. In the *table-top rearrangement* environment, the agent starts close to the goal and then gradually brings it back to the initial state distribution, trying different intermediate states in the process (discussed in Section 5.3). In the *sawyer door closing* environment, the agent learns to close the door from intermediate angles, incrementally improving the performance. For the hand manipulation domain, the agent focuses on picking up the object from a particular location, and then incrementally grow the locations from which it can complete pickup. In contrast, FBRL chooses attempts the pickup from random states from the initial state distribution ρ and R3L attempts to find new states to pickup the object from (even though it might not be succeeding to pickup the object from previous locations).

VaPRL learns to solve the task while requiring $500\times$ fewer environment resets in the door closing environment, $1000\times$ fewer environment resets in the *table-top rearrangement* environment and dexterous *hand manipulation* compared to oracle RL with resets. In practice, this amounts to less than 20 total interventions, indicating the substantial autonomy with which the algorithm can run.

Surpisingly, in the domains with a sparse reward function (that is, *sawyer door closing* and *table-top reaarrangement*), VaPRL matches or even outperforms the oracle RL method. In the *table-top rearrangement* environment, oracle RL does substantially worse than VaPRL. It has been noted in prior work that multi-goal RL problems can converge suboptimally due to issues arising in the optimization [37]. We hypothesize that an appropriate initial state distribution can ameliorate some of these issues. In particular, moving beyond deterministic initial distributions may lead to better downstream performance (also noted in [40]). For the door opening environment, VaPRL matches the performance of oracle RL. To emphasize, oracle RL is training on the evaluation environment directly, that is $H_T = H_E$ with the environment resetting to a state $s_0 \sim \rho$. In contrast, VaPRL also

Figure 8: Visualization of curricula generated by VaPRL on the *table-top rearrangement* environment. We plot the *step index distance* between the initial state and the curriculum goals generated by $C(g)$ (*blue*) and the evaluation performance (*orange*) as the training progresses. The distance is normalized to be on the same scale as the success metric, such that a value of 1 corresponds to the test-goal distribution and 0 corresponds to the initial state distribution. We visualize some of the commanded goals $C(g)$ during the training, observing that the curriculum gradually progresses from goal states to initial states with a correlated improvement in evaluation performance.

learns how to reverse the task it is solving and thus only spends half of its training samples collecting the data for the evaluation task (for example, VaPRL learns how to open the door and close it).

5.2 Isolating the Role of the Initial State Distribution

We construct an experiment to isolate the effect of the starting state distribution on learning efficiency and downstream performance. In this experiment, the environment resets directly to the state $C(g)$ for VaPRL, such that the policy only has to learn reaching the goals $g \sim p_g$ (labelled **VaPRL + reset**). Analogously, for FBRL, the environment resets to the state $s_0 \sim \rho$, which is identical to the oracle RL method (labelled **oracle RL / FBRL + reset**). For R3L, the environment resets to a state uniformly sampled from the state space (labelled **uniform / R3L + reset**). We run this ablation on the *table-top rearrangement* environment, where the episode horizon for all the algorithms is $H_E = 200$. The results in Figure 7 indicate that the starting state distribution induced by the VaPRL curriculum improves the performance, translating into improved performance in the persistent RL setting.

Figure 7: Ablation isolating the effect of curriculum generated by VaPRL.

5.3 Visualizations of Generated Curricula

To better understand the curriculum generated by VaPRL, we visualize the sequence of states chosen by Equation 4 as the training progresses on the *table-top rearrangement* environment, shown in Figure 8. As we can observe, initially the curriculum chooses states which are farther away from the initial state and closer to the goal distribution. As training progresses, the curriculum moves towards the initial state distribution. Correspondingly, the evaluation performance starts to improve as we move closer to the initial state distribution. Thus, VaPRL can generates an adaptive curriculum for the agent to efficiently improve the performance on the evaluation setting.

6 Conclusion

In this work, we propose VaPRL, an algorithm that can efficiently solve reinforcement learning problems with minimal episodic resets by generating a curriculum of starting states. VaPRL is able to reduce amount of human intervention required in the learning process by a factor 1000 compared to episodic setting, while outperforming prior methods. In the process, we also formalize the problem setting of persistent RL to understand current algorithms and aid the development of future ones.

There are a number of interesting avenues for future work that VaPRL does not address. A natural extension is to environments with irreversible states. This setting can likely be addressed by leveraging ideas from the literature in safe reinforcement learning. Another extension is to work with visual state spaces, allowing the algorithm to be more broadly applicable in the real-world. These two extensions would be a significant step towards enabling autonomous agents in the real world, minimizing the reliance on human interventions.

References

[1] Learning to poke by poking: Experiential learning of intuitive physics.

[2] M. Andrychowicz, F. Wolski, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, P. Abbeel, and W. Zaremba. Hindsight experience replay. *arXiv preprint arXiv:1707.01495*, 2017.

[3] Y. Chebotar, K. Hausman, M. Zhang, G. Sukhatme, S. Schaal, and S. Levine. Combining model-based and model-free updates for trajectory-centric reinforcement learning. In *International conference on machine learning*, pages 703–711. PMLR, 2017.

[4] B. Eysenbach, S. Gu, J. Ibarz, and S. Levine. Leave no trace: Learning to reset for safe and autonomous reinforcement learning. *arXiv preprint arXiv:1711.06782*, 2017.

[5] C. Finn and S. Levine. Deep visual foresight for planning robot motion. In *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pages 2786–2793. IEEE, 2017.

[6] C. Finn, X. Y. Tan, Y. Duan, T. Darrell, S. Levine, and P. Abbeel. Deep spatial autoencoders for visuomotor learning. In *2016 IEEE International Conference on Robotics and Automation (ICRA)*, pages 512–519. IEEE, 2016.

[7] C. Florensa, D. Held, M. Wulfmeier, M. Zhang, and P. Abbeel. Reverse curriculum generation for reinforcement learning. In *Conference on robot learning*, pages 482–495. PMLR, 2017.

[8] C. Florensa, D. Held, X. Geng, and P. Abbeel. Automatic goal generation for reinforcement learning agents. In *International conference on machine learning*, pages 1515–1528. PMLR, 2018.

[9] A. Ghadirzadeh, A. Maki, D. Kragic, and M. Björkman. Deep predictive policy training using reinforcement learning. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 2351–2358. IEEE, 2017.

[10] S. Gu, E. Holly, T. Lillicrap, and S. Levine. Deep reinforcement learning for robotic manipulation with asynchronous off-policy updates. In *2017 IEEE international conference on robotics and automation (ICRA)*, pages 3389–3396. IEEE, 2017.

[11] A. Gupta, J. Yu, T. Zhao, V. Kumar, A. Rovinsky, K. Xu, T. Devlin, and S. Levine. Reset-free reinforcement learning via multi-task learning: Learning dexterous manipulation behaviors without human intervention. *ArXiv*, abs/2104.11203, 2021.

[12] S. Ha, P. Xu, Z. Tan, S. Levine, and J. Tan. Learning to walk in the real world with minimal human effort, 2020.

[13] T. Haarnoja, S. Ha, A. Zhou, J. Tan, G. Tucker, and S. Levine. Learning to walk via deep reinforcement learning. *arXiv preprint arXiv:1812.11103*, 2018.

[14] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pages 1861–1870. PMLR, 2018.

[15] W. Han, S. Levine, and P. Abbeel. Learning compound multi-step controllers under unknown dynamics. In *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 6435–6442. IEEE, 2015.

[16] L. P. Kaelbling. Learning to achieve goals. In *IJCAI*, pages 1094–1099. Citeseer, 1993.

[17] S. Kakade and J. Langford. Approximately optimal approximate reinforcement learning. In *In Proc. 19th International Conference on Machine Learning*. Citeseer, 2002.

[18] D. Kalashnikov, A. Irpan, P. Pastor, J. Ibarz, A. Herzog, E. Jang, D. Quillen, E. Holly, M. Kalakrishnan, V. Vanhoucke, et al. Qt-opt: Scalable deep reinforcement learning for vision-based robotic manipulation. *arXiv preprint arXiv:1806.10293*, 2018.

[19] D. Kalashnikov, J. Varley, Y. Chebotar, B. Swanson, R. Jonschkowski, C. Finn, S. Levine, and K. Hausman. Mt-opt: Continuous multi-task robotic reinforcement learning at scale. *arXiv preprint arXiv:2104.08212*, 2021.

[20] K. Khetarpal, M. Riemer, I. Rish, and D. Precup. Towards continual reinforcement learning: A review and perspectives. *arXiv preprint arXiv:2012.13490*, 2020.

[21] J. Kober, J. A. Bagnell, and J. Peters. Reinforcement learning in robotics: A survey. *The International Journal of Robotics Research*, 32(11):1238–1274, 2013.

[22] N. Kohl and P. Stone. Policy gradient reinforcement learning for fast quadrupedal locomotion. In *IEEE International Conference on Robotics and Automation, 2004. Proceedings. ICRA'04. 2004*, volume 3, pages 2619–2624. IEEE, 2004.

[23] S. Levine, C. Finn, T. Darrell, and P. Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.

[24] K. Lu, A. Grover, P. Abbeel, and I. Mordatch. Reset-free lifelong learning with skill-space planning. *arXiv preprint arXiv:2012.03548*, 2020.

[25] T. Matiisen, A. Oliver, T. Cohen, and J. Schulman. Teacher–student curriculum learning. *IEEE transactions on neural networks and learning systems*, 31(9):3732–3740, 2019.

[26] A. Nagabandi, K. Konolige, S. Levine, and V. Kumar. Deep dynamics models for learning dexterous manipulation. In *Conference on Robot Learning*, pages 1101–1112. PMLR, 2020.

[27] S. Narvekar and P. Stone. Learning curriculum policies for reinforcement learning. *arXiv preprint arXiv:1812.00285*, 2018.

[28] A. Y. Ng, H. J. Kim, M. I. Jordan, S. Sastry, and S. Ballianda. Autonomous helicopter flight via reinforcement learning. In *NIPS*, volume 16. Citeseer, 2003.

[29] L. Pinto and A. Gupta. Supersizing self-supervision: Learning to grasp from 50k tries and 700 robot hours. In *2016 IEEE international conference on robotics and automation (ICRA)*, pages 3406–3413. IEEE, 2016.

[30] V. Pong, S. Gu, M. Dalal, and S. Levine. Temporal difference models: Model-free deep rl for model-based control. *arXiv preprint arXiv:1802.09081*, 2018.

[31] M. L. Puterman. Markov decision processes. *Handbooks in operations research and management science*, 2:331–434, 1990.

[32] T. Schaul, D. Horgan, K. Gregor, and D. Silver. Universal value function approximators. In *International conference on machine learning*, pages 1312–1320. PMLR, 2015.

[33] A. Sharma, M. Ahn, S. Levine, V. Kumar, K. Hausman, and S. Gu. Emergent real-world robotic skills via unsupervised off-policy reinforcement learning. *arXiv preprint arXiv:2004.12974*, 2020.

[34] S. Sukhbaatar, Z. Lin, I. Kostrikov, G. Synnaeve, A. Szlam, and R. Fergus. Intrinsic motivation and automatic curricula via asymmetric self-play. *arXiv preprint arXiv:1703.05407*, 2017.

[35] R. S. Sutton and A. G. Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[36] K. Xu, S. Verma, C. Finn, and S. Levine. Continual learning of control primitives: Skill discovery via reset-games. *ArXiv*, abs/2011.05286, 2020.

[37] T. Yu, S. Kumar, A. Gupta, S. Levine, K. Hausman, and C. Finn. Gradient surgery for multi-task learning. *arXiv preprint arXiv:2001.06782*, 2020.

[38] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on Robot Learning*, pages 1094–1100. PMLR, 2020.

[39] A. Zeng, S. Song, J. Lee, A. Rodriguez, and T. Funkhouser. Tossingbot: Learning to throw arbitrary objects with residual physics. *IEEE Transactions on Robotics*, 36(4):1307–1319, 2020.

[40] H. Zhu, A. Gupta, A. Rajeswaran, S. Levine, and V. Kumar. Dexterous manipulation with deep reinforcement learning: Efficient, general, and low-cost. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 3651–3657. IEEE, 2019.

[41] H. Zhu, J. Yu, A. Gupta, D. Shah, K. Hartikainen, A. Singh, V. Kumar, and S. Levine. The ingredients of real-world robotic reinforcement learning. *arXiv preprint arXiv:2004.12570*, 2020.