# UTS: When monotonic value factorisation meets non-monotonic and stochastic targets

## Abstract

Extracting decentralised policies from joint action-values is an attractive way to exploit centralised learning. It is possible to apply monotonic value factorisation to guarantee consistency between the centralised and decentralised policies. However, the best strategy for training decentralised policies when the target joint action-values are non-monotonic and stochastic is still unclear. We propose a novel value factorisation method named uncertainty-based target shaping (UTS) to solve this problem. UTS employs networks that estimate the reward and the following state's embedding, where the large prediction error indicates that the target is stochastic. By replacing deterministic targets for the suboptimal with the best per-agent values, we enforce that all shaped targets become a subset of the space that can be represented by monotonic value factorisation. Empirical results show that UTS outperforms state-of-the-art baselines on multiple benchmarks, including matrix games, predator-prey, and challenging tasks in the StarCraft II micromanagement.

## 1 Introduction

Recent progress in cooperative multi-agent reinforcement learning (MARL) has shown attractive prospects for various real-world applications, such as the smart grid management (Aladdin et al., 2020) and autonomous vehicles (Zhou et al., 2021). Due to practical communication constraints and intractably large joint action space, decentralised policies are often used in MARL. It is possible to use extra information from the environment and other agents in a simulated or laboratory setting. Exploiting this information can significantly benefit policy optimisation and improve learning performance (Foerster et al., 2016; 2018; Rashid et al., 2020).

In the paradigm of centralised training with decentralised execution (CTDE), agents' policies are trained with access to global information in a centralised way and executed only based on local histories in a decentralised way (Oliehoek et al., 2008; Kraemer & Banerjee, 2016). One of the most significant challenges is to extract decentralised policies from centralised joint action-value functions. QMIX (Rashid et al., 2018) applies a monotonic mixing network to factorise the joint action-value function into individual action-value functions, which guarantees consistency between the centralised and decentralised policies. However, QMIX can only represent values in the restricted monotonic space and thus may not converge to the optimal when the target value functions are non-monotonic. To cope with this representational limitation, WQMIX (Rashid et al., 2020) introduces a weighting function into the projection from the target value functions to the joint action-values, where only the loss of the optimal joint action is prioritised. Since it is computationally infeasible to obtain the optimal joint action-value, WQMIX proposes two weighting operators to down-weight every suboptimal action whose target value is lower than the current estimate. In practice, the weight is between 0 and 1 for the suboptimal and 1 for others in the weighting operators.

The choice of weight is crucial for WQMIX to improve its ability to deal with non-monotonic targets. The weight for the suboptimal should be small enough to allow WQMIX to focus on the representation of the optimal joint action value. However, WQMIX overestimates the suboptimal's value whose target is large with a low probability and thus may converge to this suboptimal if the weight is too low. Therefore, the weight for the suboptimal should be large to anchor down these undesirable overestimated values. Due to this contradiction, there may not exist an appropriate weight for WQMIX to recover the optimal joint policy when the target is non-monotonic and stochastic. These limitations primarily arise because WQMIX ignores stochasticity that stems from both the

reward and the state transition. Our key insight consists of two parts. First, it is necessary to identify whether the given state-action pair leads to stochasticity when we try to label it suboptimal in the stochastic environment. Second, it is crucial to eliminate the gap between estimated joint action-values and the targets induced by the representational limitation.

To cope with the stochasticity, we formulate two prediction problems and use the prediction error to quantify the uncertainty of the target joint action-values. Given a state-action pair, we employ a reward predictor that estimates the standard deviation of the reward. We also use a state predictor to approximate the following state's embedding, where the target is from a random but fixed projection. The standard deviation and the error between the predicted and the target embedding are expected to be significant if the pair leads to stochastic reward and stochastic state transition, respectively.

In the shaping function, first, we employ a network that predicts the per-agent value for the best case scenario, i.e., other agents choose the best actions to cooperate with it. Then, we replace the original target joint action-values $Q$ with the minimal best per-agent values over all agents if it is a deterministic suboptimal. After shaping, The original joint action-values $Q$ is transformed to $Q^f$, where the stochastic values are appropriately represented in $Q^f$. In addition, the shaping keeps the optimal policy unchanged and makes all $Q^f$ belong to a subset of the restricted space that QMIX can represent. Therefore, the shaping function guarantees convergence to the optimal QMIX for any non-monotonic and stochastic $Q$. We call our method uncertainty-based target shaping (UTS) and empirically show its improved ability in matrix games, stochastic predator-prey, and a range of decentralised micromanagement tasks in StarCraft II. We list our main contributions as follows:

- We first analyse the limitations of WQMIX and show that it cannot guarantee convergence to the optimal when joint action-value functions are non-monotonic and stochastic.
- We propose a novel multi-agent value decomposition method, UTS, which can cope with non-monotonic targets in the stochastic environment. We also empirically show that UTS achieves state-of-the-art performance on various multi-agent benchmarks, including matrix games, stochastic predator-prey and multiple StarCraft unit micromanagement maps.

## 2 BACKGROUND

A fully cooperative multi-agent task in the partially observable setting can be formulated as a Decentralised Partially Observable Markov Decision Process (Dec-POMDP) (Oliehoek & Amato, 2016), consisting of a tuple $G = \langle A, S, \Omega, O, U, P, R, n, \gamma \rangle$, where $a \in A \equiv \{1, \dots, n\}$ describes the set of agents, $S$ denotes the set of states, $\Omega$ denotes the set of joint observations, and $R$ denotes the set of rewards. At each time step, an agent obtains its observation $o \in \Omega$ based on the observation function $O(s, a) : S \times A \to \Omega$, and an action-observation history $\tau_a \in T \equiv (\Omega \times U)^*$. Each agent $a$ chooses an action $u_a \in U$ by a stochastic policy $\pi_a(u_a|\tau_a) : T \times U \to [0, 1]$, forming a joint action $\mathbf{u} \in \mathbf{U}$, which leads to a transition on the environment through the transition function $P(s', r|s, \mathbf{u}) : S \times \mathbf{U} \times S \times R \to [0, 1]$, where $r \in R$ is the team reward. The goal of the task is to find the joint policy $\pi$ which can maximise the joint action-value function $Q^\pi(s_t, \mathbf{u}_t) = \mathbb{E}_{s_{t+1:\infty}, \mathbf{u}_{t+1:\infty}}[G_t|s_t, \mathbf{u}]$, where $G_t = \sum_{i=0}^{\infty} \gamma^i r_{t+i}$ is the discounted return.

VDN (Sunehag et al., 2018), QMIX (Rashid et al., 2018), and WQMIX (Rashid et al., 2020) are $Q$-learning algorithms for the fully cooperative multi-agent tasks, which estimate the joint action-value function $Q(s, \mathbf{u})$ as $Q_{tot}$ with specific forms. Considering only a fully-observable setting for ease of representation. VDN factorises $Q_{tot}$ into a sum of individual action-value functions. By contrast, QMIX applies a state-dependent monotonic mixing network to combine per-agent action-value functions with the joint action-value function. The restricted spaces of all $Q_{tot}$ that linear and monotonic value factorisations can represent are:

$$\mathcal{Q}^{lvf} := \{Q_{tot}|Q_{tot}(s, \mathbf{u}) = \sum_{a=1}^{n} Q_a(s, u_a), Q_a(s, u) \in \mathbb{R}\} \tag{1}$$

$$\mathcal{Q}^{mvf} := \{Q_{tot}|Q_{tot}(s, \mathbf{u}) = f_s(Q_1(s, u_1), \dots, Q_n(s, u_n)), \frac{\partial f_s}{\partial Q_a} \geqslant 0, Q_a(s, u) \in \mathbb{R}\}, \tag{2}$$

where the monotonic mixing function $f_s$ is parametrised as a feedforward network, whose non-negative weights are generated by hypernetworks that take the state as input.

WQMIX views QMIX as an operator $\Pi_{\text{Qmix}}Q := \arg\min_{Q_{tot}\in\mathcal{Q}^{mvf}}\sum_{\mathbf{u}\in\mathbf{U}}(y(s,\mathbf{u}) - Q_{tot}(s,\mathbf{u}))^2$, which can be separated into two parts: the first computes the $Q$-learning target $y(s,\mathbf{u}) := \mathbb{E}[r + \gamma\max_{\mathbf{u}'}Q_{tot}(s',\mathbf{u}')]$, and the second projects the target into $\mathcal{Q}^{mvf}$. Then, WQMIX introduces the weighting function into the projection to prioritise the optimal joint action-value:

$$\Pi_{\text{WQmix}}Q := \underset{Q_{tot}\in\mathcal{Q}^{mvf}}{\arg\min}\sum_{\mathbf{u}\in\mathbf{U}}w(s,\mathbf{u})(y(s,\mathbf{u}) - Q_{tot}(s,\mathbf{u}))^2 \qquad (3)$$

Since it is computationally infeasible to obtain the optimal joint action-value, WQMIX proposes Centrally-Weighted QMIX (CW-QMIX) and Optimistically-Weighted QMIX (OW-QMIX) to place more importance on better joint action. In practice, the weighting function $w : S \times \mathbf{U} \to (0, 1]$ is:

$$w^{cw}(s,\mathbf{u}) = \begin{cases} 1 & y(s,\mathbf{u}) > \hat{Q}^*(s,\hat{\mathbf{u}}^*) \text{ or } \mathbf{u} = \hat{\mathbf{u}}^* \\ \alpha & \text{otherwise} \end{cases}, w^{ow}(s,\mathbf{u}) = \begin{cases} 1 & y(s,\mathbf{u}) > Q_{tot}(s,\mathbf{u}) \\ \alpha & \text{otherwise} \end{cases}, \quad (4)$$

where $\hat{\mathbf{u}}^* = \arg\max_{\mathbf{u}}Q_{tot}(s,\mathbf{u})$ is the current greedy joint action, $\hat{Q}^*(s,\hat{\mathbf{u}}^*)$ is an approximation of the true optimal value function which is not constrained to be monotonic.

## 3  CASE STUDIES

In this section, we examine the weightings of WQMIX when the $Q$-learning targets are non-monotonic and stochastic. Since WQMIX applies a non-linear mixing network and thus many analysis methods become inapplicable, we use WVDN to analyse the fundamental limitations of the weighting. Then, we conduct experiments to show that these limitations also hurt the performance of WQMIX. WVDN operator is defined as $\Pi_{\text{WVDN}}Q := \arg\min_{Q_{tot}\in\mathcal{Q}^{lvf}}\sum_{\mathbf{u}\in\mathbf{U}}w^{ow}(s,\mathbf{u})(y(s,\mathbf{u})-Q_{tot}(s,\mathbf{u}))^2$, where $w^{ow}(s,\mathbf{u})$ is the optimistic weighting from (4).

### 3.1  NON-MONOTONIC TARGETS

QMIX cannot represent joint action-value functions that are characterised as non-monotonic. Although this representational limitation will not necessarily result in the convergence to the suboptimal, QMIX fails to recover the optimal policy with some specific non-monotonic $Q$-learning targets (Son et al., 2019). To accurately represent the optimal joint action-value rather than the suboptimal ones, Rashid et al. (2020) introduce the weighting function in (4) to down-weight every suboptimal action. However, the choice of weight $\alpha$ is crucial to ensure that WQMIX can overcome the limitations of QMIX.

**The weight $\alpha$ should be small enough to prioritise estimating the real optimal action value.** We start by analysing a matrix game in Figure 1a, where each joint action receives a team reward. Our study focuses on the greatest value $\alpha$ to converge to the optimal when the policy is initialised to be suboptimal. Suppose the training dataset has a $\epsilon$-greedy distribution, where the greedy action is $(u_1^2, u_2^2)$. We find that $\alpha$ for WVDN should be smaller than $\frac{3\epsilon(a-c)+\epsilon^2(c-b)}{(\epsilon-3)^2(c-b)}$ to recover the optimal joint policy. The proof can be found in Appendix A.2. In Figure 1b, We show that $\alpha$ for WQMIX also should be smaller than a specific value to overcome the non-monotonic targets. The complete results are provided in Appendix B.

### 3.2  STOCHASTIC TARGETS

The stochasticity of the target value functions comes from both rewards and transitions, i.e., $P(s',r|s,\mathbf{u})$ is not deterministic. Traditional $Q$-learning algorithms solve this problem by calculating the weighted sum of possible rewards and values of the next state multiplied by their probabilities, i.e., $Q(s,\mathbf{u}) = \sum_{s'}\sum_r[P(s',r|s,\mathbf{u})r + \gamma P(s',r|s,\mathbf{u})\max_{\mathbf{u}'}Q(s',\mathbf{u}')]$. By contrast, the weighting function in WQMIX prioritises actions whose targets are greater than the estimated joint action-value from the current mixing network. This weighting can be seen as a type of distribution shaping, leading to potential risks in policy learning.

**The weight $\alpha$ should be large to anchor down the overestimated value for the suboptimal whose target is huge with a small probability**. Since $r(s,\mathbf{u})$ and $\max_{\mathbf{u}'}Q(s',\mathbf{u}')$ play the equal role in the target value function, we take the matrix game with stochastic rewards as an example to get a better

understanding of the effect of the weight $\alpha$ in the stochastic environment. A numerical example is shown in Figure 1c, where the suboptimal action $\mathbf{u}^s = (u_1^2, u_2^2)$ receives 12 with probability 0.5 and 0 with 0.5, where the optimal is $\mathbf{u}^* = (u_1^1, u_2^1)$. Suppose the training dataset is fixed, where the data has a $\epsilon$-greedy distribution and the greedy action is $\mathbf{u}^s$. Let $Q(\mathbf{u})$ denote the true joint action-value. Since this matrix game only involves one state, we omit the state $s$ in the value function for simplicity.

| $U_2$\\$U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | a | b | b |
| $u_2^2$ | b | c | c |
| $u_2^3$ | b | c | c |

(a) A non-monotonic game.

| Algo \\ $\epsilon$ | 1.0 | 0.5 | 0.25 |
|---|---|---|---|
| Analysis | 3.0 | 15.0 | 52.6 |
| WVDN | 10.5 | 42.2 | 100.5 |
| OW-QMIX | 12.2 | 43.2 | 103.2 |
| CW-QMIX | 11.5 | 29.6 | 83.5 |

(b) Minimal $1/\alpha$.

| $U_2$\\$U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | 8 | 6 | 6 |
| $u_2^2$ | 6 | 12/0 | 6 |
| $u_2^3$ | 6 | 6 | 6 |

(c) A stochastic game.

| $U_2$\\$U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | 8 | 6 | 6 |
| $u_2^2$ | 6 | 6 | 6 |
| $u_2^3$ | 6 | 6 | 6 |

(d) QMIX ($\alpha$=1).

| $U_2$\\$U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | **7.34** | 7.29 | 6.06 |
| $u_2^2$ | 7.29 | 7.23 | 6.05 |
| $u_2^3$ | 6.05 | 6.03 | 5.92 |

(e) OW-QMIX($\alpha$=0.5).

| $U_2$\\$U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | **7.33** | 7.25 | 6.33 |
| $u_2^2$ | 7.25 | 7.2 | 6.28 |
| $u_2^3$ | 6.33 | 6.28 | 5.45 |

(f) CW-QMIX($\alpha$=0.5).

| $U_2$\\$U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | 7.29 | 7.67 | 6.42 |
| $u_2^2$ | 7.67 | **10.9** | 6.62 |
| $u_2^3$ | 6.43 | 6.63 | 5.73 |

(g) OW-QMIX ($\alpha$=0.1).

| $U_2$\\$U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | **7.98** | **7.98** | 6.33 |
| $u_2^2$ | **7.98** | **7.98** | 6.33 |
| $u_2^3$ | 6.33 | 6.33 | 5.51 |

(h) CW-QMIX ($\alpha$=0.1).

Figure 1: (a) The payoff matrix for a one-step non-monotonic game, where $a > c > b$. (b) The minimal $1/\alpha$ to recover the optimal policy with different $\epsilon$ in the non-monotonic game in (a), where $a = 8, b = -12, c = 6$. (c) The payoff matrix for a one-step stochastic game. (d-h) The estimated joint action-values $Q_{tot}$ returned from QMIX and WQMIX. Boldface means the optimal joint action from the payoff matrix, or the greedy joint action from the $Q_{tot}$.

Figure 1d-h demonstrate the joint action-values $Q_{tot}(\mathbf{u})$ returned from QMIX and WQMIX with different $\alpha$. QMIX is a special case of WQMIX ($\alpha = 1$), and thus represents the joint $Q$-value perfectly. By contrast, WQMIX with a small weight is drawn to the suboptimal $\mathbf{u}^s$ and thus has an incorrect argmax. OW-QMIX returns an overestimated $Q_{tot}(\mathbf{u}^s) = 10.9 > Q_{tot}(\mathbf{u}^*)$ and thus converge to the suboptimal $\hat{\mathbf{u}}^* = \mathbf{u}^s$. In particular, CW-QMIX places more importance on $\mathbf{u}^s$ when it is not the greedy action and receives the reward of 12, leading to an overestimate value $Q_{tot}(\mathbf{u}^s) > Q(\mathbf{u}^s) = 6$. With the increase of $Q_{tot}(\mathbf{u}^s)$, $\mathbf{u}^s$ becomes the greedy action once $Q_{tot}(\mathbf{u}^s) > Q_{tot}(\mathbf{u}^*)$. In this situation, CW-QMIX does not place the $\alpha$ for $\mathbf{u}^s$ when it receives the reward of 0, leading to the decrease of $Q_{tot}(\mathbf{u}^s)$. As a result, CW-QMIX is stuck in this loop and cannot converge to any policy.

**Theorem 1** *Let* $\Pi_{\text{WVDN}}Q := \arg\min_{Q_{tot} \in \mathcal{Q}^{lvf}} \sum_{\mathbf{u} \in \mathbf{U}} w^{ow}(s, \mathbf{u})(Q(s, \mathbf{u}) - Q_{tot}(s, \mathbf{u}))^2$ *and* $w^{ow}(s, \mathbf{u})$ *is the optimistic weighting from (4). Then* $\exists Q$ *such that* $\arg\max \Pi_{\text{WVDN}}Q \neq \arg\max Q$ *for any* $\alpha \in (0, 1]$.

The proof is provided in Appendix A.2. An intuitive understanding is that the weight $\alpha$ in WVDN has an upper bound to deal with non-monotonic $Q$-learning targets, but also has a lower bound to anchor down the overestimated suboptimal value due to undesirable weights in the stochastic environment. The empirical results in Appendix B show that WQMIX also suffers from this contradiction and fails to converge to the optimal.

## 4 METHOD

In this section, we introduce a shaping function to generate the shaped joint action-value $Q^f(s, \mathbf{u})$ to replace the original $Q(s, \mathbf{u})$. The shaping function should have the following properties: 1) **policy invariance**, i.e., not making the agent deviate from the true goal and keeping the optimal policy unchanged; 2) **full representational capacity**, i.e., all shaped joint action-values should belong to a subset of $\mathcal{Q}^{mvf}$. Based to these properties, we have $\arg\max_{\mathbf{u}} Q^f(s, \mathbf{u}) = \arg\max_{\mathbf{u}} Q(s, \mathbf{u})$ and $\forall Q^f(s, \mathbf{u}) \in \mathcal{Q}^{mvf}$, and thus QMIX can always recover the correct $\arg\max$ in $Q(s, \mathbf{u})$.

To this end, we first predict the standard deviation of the reward and the embedding of the next state. We then split the stochastic joint action-values from the sampled data according to the prediction error. Next, we employ a network that estimates the best action value for each agent. Based on the prediction error and the best action values, we use the shaping function to generate monotonic target joint action-values for QMIX, which can be perfectly represented by monotonic value factorisation.

## 4.1 UNCERTAINTY ESTIMATION

In the stochastic environment, the target joint action-value $y(s, \mathbf{u})$ is stochastic. This stochasticity comes from the stochastic transition of the reward and the state, i.e., $P(s', r|s, \mathbf{u})$, which can be viewed as a type of the aleatoric uncertainty (Der Kiureghian & Ditlevsen, 2009). We propose a solution to this undesirable stochasticity using two prediction problems: the standard deviation of the reward and the embedding of the next state for a given state-action pair. This involves three neural networks: a reward predictor network, a state predictor, and a fixed randomly initialised target network. The reward predictor network takes the state and joint action to the reward $\hat{r}(s, \mathbf{u}) : S \times U \to \mathbb{R}$ and the uncertainty, i.e., the standard deviation $\hat{\sigma}(s, \mathbf{u}) : S \times U \to \mathbb{R}$. Based on the Bayesian deep learning method (Kendall & Gal, 2017), the reward predictor network is trained by minimising the following loss:

$$\sum_{b=1}^{B} (\frac{1}{2\hat{\sigma}^b(s, \mathbf{u})^2} (r^b(s, \mathbf{u}) - \hat{r}^b(s, \mathbf{u}))^2 + \frac{1}{2} \log \hat{\sigma}^b(s, \mathbf{u})^2), \tag{5}$$

where $B$ denotes the batch size of transitions sampled from the replay buffer. The standard deviation is expected to be higher if the state-action pair leads to stochastic rewards.

For the second prediction problem, the target network takes a state to an $m$-dimensional embedding $g(s) : S \to \mathbb{R}^m$, where $g(s)$ is a fixed and randomly initialised network. The state predictor $h(s, \mathbf{u}; \theta_h) : S \times U \to \mathbb{R}^m$ is trained to minimise the prediction error $E(s, \mathbf{u}, s') = \|g(s') - h(s, u)\|^2$ with respect to its parameters $\theta_h$, where $s'$ denotes the next state in the sampled trajectory. The prediction error is expected to be higher if the state-action pair results in stochastic transitions.

Therefore, if the state-action pair leads to any stochasticity, the standard deviation of the reward $\hat{r}$ and the prediction error $E$ are expected to be large. Combining the reward and the state predictors, we define a indicator function $T(s, \mathbf{u}) = \mathbf{1}_{(\hat{\sigma}(s, \mathbf{u}) > \mathcal{D} \bigcup E(s, \mathbf{u}, s') > \mathcal{E})}$, where 1 represents that the target is stochastic, $\mathcal{D}$ and $\mathcal{E}$ are hyper-parameters.

## 4.2 SHAPING FUNCTION

Since QMIX imposes the monotonic constraint on the relationship between the joint $Q$-value and the individual $Q$-values, it can only represent a subset of $\mathcal{Q}^{mvf}$ in practice. Therefore, we introduce the shaping function $f(s, \mathbf{u})$ to replace the target $y(s, \boldsymbol{\tau}, \mathbf{u})$ by $y^f(s, \boldsymbol{\tau}, \mathbf{u})$. As a result, the original joint action-value $Q(s, \boldsymbol{\tau}, \mathbf{u})$ is transformed to $Q^f(s, \boldsymbol{\tau}, \mathbf{u})$. For all joint actions $\mathbf{u}$, $Q^f(s, \boldsymbol{\tau}, \mathbf{u})$ is the subset of $\mathcal{Q}^{mvf}$, and $\arg\max_{\mathbf{u}} Q(s, \boldsymbol{\tau}, \mathbf{u}) = \arg\max_{\mathbf{u}} Q^f(s, \boldsymbol{\tau}, \mathbf{u})$.

We define a best action value function $q_a(s, \tau_a, u_a)$ as the greatest action-value of $u_a$ when others perform optimally to cooperate with it, i.e., $q_a(s, \tau_a, u_a) = \max_{\mathbf{u}_{-a}} Q(s, u_a, \mathbf{u}_{-a})$. Inspired by BAIL (Chen et al., 2020), we approximate $q_a(s, \tau_a, u_a)$ by minimising the following loss:

$$\sum_{b=1}^{B} \sum_{a=1}^{n} K(s, \tau_a, u_a) [q_a(s, \tau_a, u_a) - y_a^b(s, u_a)]^2 + \lambda \|\theta_{q_a}\|, \tag{6}$$

where $B$ denotes the batch size of transitions sampled from the replay buffer, $y_a^b(s, u_a) = \hat{r}(s, \mathbf{u}) + \gamma \max_{u_a'} q_a(s', \tau_a', u_a')$ is the target, $\lambda$ is the regularisation coefficients, $K(s, \tau_a, u_a) = 1$ for the action-value whose target is stochastic or smaller than the current estimate, i.e., $y_a^b(s, u_a) < q_a(s, \tau_a, u_a) \bigcup T(s, \mathbf{u}) = 1$, and $K(s, \tau_a, u_a) = k \gg 1$ otherwise. Equipped with $q_a(s, \tau_a, u_a)$, we can compute the original target $y(s, \boldsymbol{\tau}, \mathbf{u})$ for joint action-value $Q_{tot}$ and projects it into $y^f(s, \boldsymbol{\tau}, \mathbf{u})$. We define the corresponding shaping function as follows:

$$y^f(s, \boldsymbol{\tau}, \mathbf{u}) = \begin{cases} \min_{a \in \mathbb{A}} q_a(s, \tau_a, u_a) & T(s, \mathbf{u}) = 0 \text{ and } y(s, \boldsymbol{\tau}, \mathbf{u}) \leqslant Q_{tot}(s, \boldsymbol{\tau}, \hat{\mathbf{u}}^*) \\ y(s, \boldsymbol{\tau}, \mathbf{u}) & \text{otherwise} \end{cases}, \tag{7}$$

where $Q_{tot}(s, \boldsymbol{\tau}, \mathbf{u}; \theta) = f_s(Q_1(\tau_1, u_1), ..., Q_n(\tau_n, u_n))$ is the joint action-values parametrized by $\theta$, $\frac{\partial f_s}{\partial Q_a} \geqslant 0$, $y(s, \boldsymbol{\tau}, \mathbf{u}) = r(s, \mathbf{u}) + \gamma \max_{\mathbf{u}'} Q_{tot}(s', \boldsymbol{\tau}', \mathbf{u}'; \theta')$ is the original target, $\hat{\mathbf{u}}^* = \arg\max_{\mathbf{u}} Q_{tot}(s, \mathbf{u})$, and $\theta^-$ are the parameters of a target network that are periodically copied from $\theta$. For deterministic and suboptimal joint action-values, we replace the original targets by the minimal value of $q_a(s, \tau_a, u_a)$ over all agents. The objection of the shaping is to make all target

value functions at a given state become monotonic and ensure the target for the optimal joint action is greater than the suboptimal. We do not change the target if it is identified to result in stochasticity. To improve learning efficiency, we also remain the target unchanged if it is deterministic and greater than the current greedy action value estimate. $Q_{tot}(s, \boldsymbol{\tau}, \mathbf{u}; \theta)$ is trained by minimising the following loss:

$$\sum_{b=1}^{B} (Q_{tot}(s, \boldsymbol{\tau}, \mathbf{u}; \theta) - Q_b^f(s, \boldsymbol{\tau}, \mathbf{u}))^2. \tag{8}$$

Monotonic value factorisation with the original target joint action-values $Q$ induces representational limitation, but it is unclear if the shaped targets do the same. In the following, we give a profound understanding of this. Considering only a fully-observable setting for ease of representation. Thus our notations do not distinguish the concepts of states and observation-action histories. We denote $\mathcal{M}^0$ as the original MDP with joint action-value $Q_t$ at each timestep $t$. Then, applying the shaping function will result in a new MDP $\mathcal{M}^1$ with the shaped value $Q_t^f$ according to (7). For that, we say $\mathcal{M}^0$ is transformed into $\mathcal{M}^1$ after target shaping.

**Theorem 2** *Let $Q$ and $Q^f$ be the orignal and the shaped action value based on (7). Then $\forall s \in S$ and $\forall \boldsymbol{u} \in U$ such that, $\arg \max_{\boldsymbol{u}} Q^f(s, \boldsymbol{u}) = \arg \max_{\boldsymbol{u}} Q(s, \boldsymbol{u})$ and $Q^f(s, \boldsymbol{u}) \in \mathcal{Q}^{mvf}$.*

The proof can be found in Appendix A.3. Since all target joint action-values at a given state lie in the restricted monotonic space $\mathcal{Q}^{mvf}$, $Q^f(s, \mathbf{u})$ in $\mathcal{M}^1$ can be perfectly represented by monotonic value factorisation. Therefore, the shaping function eliminates the representational limitation, i.e., the $\arg \max$ in $\mathcal{M}^1$ is tractable for QMIX. Theorem 2 also indicates that the optimal policy between the original MDP $\mathcal{M}^0$ and the transformed MDP $\mathcal{M}^1$ is the same. As a result, QMIX can converge to the optimal in the original MDP $\mathcal{M}^0$ with the shaped targets.

Figure 2: The performance of QMIX with the original and the shaped target values.

In Figure 2, we compare the performance of QMIX with the original and the shaped target joint action-values. Consider a $10 \times 10$ matrix game, where suboptimal is filled with random numbers generated uniformly between -10 and 9, and the unique optimal value is +10. As shown in Figure 2a-b, the original targets are the rewards from this matrix game, and the shaped targets are obtained based on 7. Figure 2c-d demonstrates that QMIX can perfectly represent all shaped targets and thus converge to the optimal by showing the loss is almost 0, and the test reward is +10 after 400 iterations. By contrast, QMIX with the original targets in Figure 2a keeps fluctuating during training.

## 5 RELATED WORK

In this section, we briefly introduce recent related work on cooperative MARL in the paradigm of centralised training with decentralised execution (CTDE). A natural approach to finding policies for a multi-agent system is to learn decentralised value functions or policies directly. MAPPO (Yu et al., 2021) achieves strong results compared with off-policy methods. However, these approaches suffer from instability arising from the non-stationarity of the environment induced by simultaneously learning and exploring agents (Kuba et al., 2021). Centralised learning of joint action-values can solve these problems, but it is challenging to scale in real-world applications due to intractably large joint action space and communication constraints. CTDE allows the trade-off between fully decentralised and centralised learning, where agents make decisions based on their local action-observation histories but uses additional information to learn centralised joint action-value functions.

One of the most significant challenges in CTDE is to extract policies from centralised joint action-value functions. To solve this problem, VDN (Sunehag et al., 2018) and QMIX (Rashid et al., 2018) learn the joint action-values and factorise them into individual action-value functions in an additive and a monotonic fashion, respectively. Qatten (Yang et al., 2020b) is a variant of QMIX, which applies a multi-head attention structure to the mixing network. QPD (Yang et al., 2020a) utilises integrated gradients to decompose the joint $Q$-values along trajectory paths. SMIX($\lambda$) (Yao et al., 2021) changes the one-step $Q$-learning target with a SARSA($\lambda$) target. These methods apply the non-negative weights in the mixing network, i.e., using monotonic value factorisation, and thus can only represent the same class as QMIX.

On the contrary, as many previous studies pointed out (Mahajan et al., 2019; Son et al., 2019; Rashid et al., 2020), monotonic value factorisation limits the representational capacity. Therefore, QMIX fails to learn the optimal policy when the target joint action-value functions are non-monotonic. To solve this problem, QTRAN (Son et al., 2019) uses two soft regularisations to align the greedy action selections between the joint action-value and the individual values. Son et al. (2019) also propose the Individual-Global Max principle and point out that the monotonic value factorisation is not necessary for converging to the optimal. WQMIX (Rashid et al., 2020) introduces a weighting mechanism, which is similar to Hysteretic $Q$-learning (Matignon et al., 2007), to place more importance on better joint actions. Although some multi-agent exploration methods (Mahajan et al., 2019; Zheng et al., 2021) are proposed to increase the probability of recovering the optimal policy, WQMIX is independent of the exploration strategy and thus adds more flexibility. However, we prove that there could not exist an appropriate weight when the $Q$-learning target is non-monotonic and stochastic. QTRAN can be viewed as a variant of WQMIX, which additionally uses the weight 0 for the joint action-value whose target is smaller than the current estimate and the chosen action is not greedy (Rashid et al., 2020). QTRAN approximates $\hat{Q}^*$ as the target instead of the original target $y$ and thus can deal with stochasticity. However, since the 0 weight for overestimated Q-values, QTRAN is empirically hard to scale to more complex tasks (Samvelyan et al., 2019).

Another possible solution is QPLEX (Wang et al., 2020), which achieves the full representational capacity by mixing non-positive advantage functions, in which the weights are produced through joint actions. Although the architecture of QPLEX satisfies the Individual-Global-Max, it also induces the "vanishing gradient" problem in learning, leading to slow convergence and learning instability. More discussions can be found in Appendix B.2.

**Relationship To Reward Shaping.** Reward shaping is a common technique for improving single-agent learners' performance by integrating expert knowledge into MDP (Gullapalli & Barto, 1992). It also has been adopted to the MARL setting in recent work (Devlin et al., 2011; Xiao et al., 2021). An ill-designed reward function often leads to many unexpected behaviours, e.g., *relative overgeneralisation* (Wei et al., 2018). Since it is not always possible to find an expert with complete domain knowledge, it is not easy to set rewards for complex MARL tasks in advance. Therefore, adaptively shaping the reward is a more attractive way. Some reward randomisation methods (Gupta et al., 2021; Tang et al., 2021) are proposed to convert the original MDP to a new MDP with random rewards through universal successor features. However, these methods require a massive number of randomisation to find a desirable reward function because they cannot guarantee *policy invariance*. GVR (Wan et al., 2022) proposes inferior target reshaping and superior experience replay to eliminate the non-optimal self-transition nodes, which is similar to WQMIX and ignores the stochasticity of the transition. Compared with these methods, UTS is more efficient because it can perfectly represent the expected value for stochastic targets and guarantee the policy invariance during target shaping.

# 6    EXPERIMENTS

In this section, we conduct empirical experiments to answer the following questions: (1) Is UTS better than the existing methods when the target is serious non-monotonic? (2) Can UTS perform well when the target is non-monotonic and stochastic? (3) Can UTS perform efficient coordination in challenging multi-agent tasks? We compare UTS with value decomposition baselines, including VDN (Sunehag et al., 2018), QMIX (Rashid et al., 2018), QTRAN (Son et al., 2019), QPLEX (Wang et al., 2020) and WQMIX (Rashid et al., 2020) on a one-step matrix game, a multi-agent Markov Decision Process, predator-prey (Son et al., 2019), Predator-Stag-Hunt, and StarCraft II Multi-agent Challenge (Samvelyan et al., 2019). We also conduct ablation studies (Appendix B) and compare

UTS with GVR (Wan et al., 2022) and WQMIX with different weights (Appendix C). More detailed experimental settings are included in Appendix F. All the learning curves in the experiments are plotted based on five training runs with different random seeds using mean and standard deviation with confidence internal 95%.

## 6.1 MATRIX GAMES

In this subsection, we consider a matrix game in Figure 3a, where the local optimal is difficult to jump out due to the considerable miscoordination penalties and stochastic reward. The optimal joint strategy is to simultaneously perform $(u_1^1, u_2^1)$. We adopt a uniform exploration strategy to approximate the uniform data distribution and eliminate the challenge of exploration and sample complexity. As shown in Figure 3b, UTS and QTRAN can achieve optimal performance, while other algorithms fall into a local optimum. CW-QMIX fluctuates dramatically and cannot converge to any policy, which is consistent with our analysis in section 3.2.

Figure 3: Mean test return on a stochastic matrix game and an MMDP.

We also consider a multi-agent Markov Decision Process (MMDP) with non-monotonic targets and stochastic state transitions in Figure 3c. This MMDP involves two agents, three actions and a team reward. Two agents start at state $s_1$ and explore extrinsic rewards for ten environment steps. The state transits from $s_1$ to $s_2$ with probability 50% and $s_3$ with 50% if agents perform $\mathbf{u} = (u_1^2, u_2^2)$ at $s_1$, and remains unchanged otherwise. The team continually obtains a deterministic reward of +10 and -10 at $s_2$ and $s_3$, respectively. As shown in Figure 3d, UTS and QTRAN can achieve optimal performance. By contrast, since VDN, QMIX, and QPLEX estimates the stochastic targets well but cannot deal with the non-monotonicity, they converge to the suboptimal with the return of +60. The negative results for CW-QMIX and OW-QMIX show that they converge to the suboptimal whose target is large with low probability due to the undesirable weights.

## 6.2 PREDATOR-PREY

Predator-prey (PP) is a partially observable environment containing eight predators (agents) and eight prey in a $10 \times 10$ grid world. Each agent observes a $5 \times 5$ sub-grid around it and can perform five actions, i.e., up, down, left, right, and catch. The team receives a miscoordination penalty when two agents surround a prey and only one attempts to catch it. By contrast, they earn a bonus of 10 if they catch the prey simultaneously. After a successful catch, the catching predators and prey will be removed from the grid.

Figure 4: Mean test return on predator-prey and predator-stag-hare.

Figure 4a-b shows that VDN, QMIX, and QPLEX fail to return positive returns in predator-prey with a significant penalty. This is because the penalty makes these methods underestimate the per-agent

action value of the real optimal. CW-QMIX and OW-QMIX can achieve positive test returns when the penalty is -2 because they place more weight on better joint actions. QTRAN can also solve this task by its regularisation terms. However, CW-QMIX, OW-QMIX, and QTRAN fail to solve the task when the penalty is -10, suggesting difficulties in choosing the pre-defined weight and the network architecture. By contrast, UTS solves tasks quickly and steadily in all penalty settings.

We extend predator-prey to a stochastic version named predator-stag-hare (PSH), which contains eight predators, four stags and four hares. The team receives the miscoordination penalty when two predators surround a prey and only one attempts to catch it. By contrast, a catch of hare results in a non-deterministic reward, i.e., the probabilities of receiving SR$\in \mathbb{R}^+$ and -SR are both 50%. As shown in Figure 4c-d, VDN and QMIX can quickly recover the optimal policy when the penalty is 0 because they can accurately evaluate the stochastic reward. When the penalty is -2, VDN, QMIX, QPLEX, and WQMIX fail to solve this task. QTRAN also struggles with the suboptimal in this setting. By contrast, UTS takes advantage of the uncertainty estimation module to avoid overestimating the stochastic action values. In addition, UTS uses the shaping function to eliminate the adverse impact of the miscoordination penalty and thus learns quickly and reliably in these tasks. The detailed comparison between UTS and WQMIX with different weights can be found in Appendix C.

## 6.3 STARCRAFT MULTI-AGENT CHALLENGE

We compare UTS with baselines on eight hard and super hard maps in the decentralised micromanagement tasks in StarCraft Multi-Agent Challenge (SMAC) (Samvelyan et al., 2019). We use an $\epsilon$-greedy policy in which $\epsilon$ decreases from 1 to 0.05 over 1 million timesteps for *3s5z_vs_3s6z*, *6h_vs_8z* and *corridor*, and over 50 thousand timesteps for others. As shown in Figure 5, UTS outperforms our baselines, which indicates that UTS improves learning speed and coordination in practice.

Figure 5: Mean test win rate on SMAC tasks.

## 7 CONCLUSION AND FUTURE WORK

This paper presents uncertainty-based target shaping (UTS), which was inspired by analysing the limitation of Weighted QMIX. We show that there may not exist an appropriate weighting function for Weighted QMIX to recover the optimal policy when the targets are stochastic and non-monotonic. To solve this problem, UTS first identifies whether a target value is stochastic by predicting the standard deviation of the reward and the prediction error between the predicted and the target embedding of the following state. Then UTS proposes a shaping function to project all target joint action-values into a subset of the space that QMIX can represent by replacing the deterministic target of the suboptimal with the minimal best per-agent values. Empirical results demonstrate the improved ability of UTS to deal with non-monotonic and stochastic targets, as well as more complicated tasks. The assumption of "unique optimal policy" is required in our proofs. However, multiple optimal may be common in a multi-agent setting. As shown in Appendix E, this problem can be alleviated by exploration methods. For future work, the more efficient exploration method could be considered, as opposed to the simplistic $\epsilon$-greedy exploration scheme we used in this paper.

REFERENCES

Sally Aladdin, Samah El-Tantawy, Mostafa M. Fouda, and Adly S. Tag Eldien. MARLA-SG: multi-agent reinforcement learning algorithm for efficient demand response in smart grid. *IEEE Access*, 8:210626–210639, 2020.

Xinyue Chen, Zijian Zhou, Zheng Wang, Che Wang, Yanqiu Wu, and Keith Ross. Bail: Best-action imitation learning for batch deep reinforcement learning. *Advances in Neural Information Processing Systems*, 33:18353–18363, 2020.

Armen Der Kiureghian and Ove Ditlevsen. Aleatory or epistemic? does it matter? *Structural safety*, 31(2):105–112, 2009.

Sam Devlin, Daniel Kudenko, and Marek Grześ. An empirical study of potential-based reward shaping and advice in complex, multi-agent systems. *Advances in Complex Systems*, 14(02): 251–278, 2011.

Jakob Foerster, Gregory Farquhar, Triantafyllos Afouras, Nantas Nardelli, and Shimon Whiteson. Counterfactual multi-agent policy gradients. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32.1, 2018.

Jakob N Foerster, Yannis M Assael, Nando de Freitas, and Shimon Whiteson. Learning to communicate with deep multi-agent reinforcement learning. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, pp. 2145–2153, 2016.

Vijaykumar Gullapalli and Andrew G Barto. Shaping as a method for accelerating reinforcement learning. In *Proceedings of the 1992 IEEE international symposium on intelligent control*, pp. 554–559. IEEE, 1992.

Tarun Gupta, Anuj Mahajan, Bei Peng, Wendelin Böhmer, and Shimon Whiteson. Uneven: Universal value exploration for multi-agent reinforcement learning. In *International Conference on Machine Learning*, pp. 3930–3941. PMLR, 2021.

Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? *Advances in neural information processing systems*, 30, 2017.

Landon Kraemer and Bikramjit Banerjee. Multi-agent reinforcement learning as a rehearsal for decentralized planning. *Neurocomputing*, 190:82–94, 2016.

Jakub Grudzien Kuba, Ruiqing Chen, Munning Wen, Ying Wen, Fanglei Sun, Jun Wang, and Yaodong Yang. Trust region policy optimisation in multi-agent reinforcement learning. *arXiv preprint arXiv:2109.11251*, 2021.

Anuj Mahajan, Tabish Rashid, Mikayel Samvelyan, and Shimon Whiteson. Maven: Multi-agent variational exploration. *Advances in Neural Information Processing Systems*, 32, 2019.

Laëtitia Matignon, Guillaume J Laurent, and Nadine Le Fort-Piat. Hysteretic q-learning: an algorithm for decentralized reinforcement learning in cooperative multi-agent teams. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 64–69. IEEE, 2007.

Frans A Oliehoek and Christopher Amato. *A concise introduction to decentralized POMDPs*. Springer, 2016.

Frans A Oliehoek, Matthijs TJ Spaan, and Nikos Vlassis. Optimal and approximate q-value functions for decentralized pomdps. *Journal of Artificial Intelligence Research*, 32:289–353, 2008.

Tabish Rashid, Mikayel Samvelyan, Christian Schroeder, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Qmix: Monotonic value function factorisation for deep multi-agent reinforcement learning. In *International Conference on Machine Learning*, pp. 4295–4304. PMLR, 2018.

Tabish Rashid, Gregory Farquhar, Bei Peng, and Shimon Whiteson. Weighted qmix: Expanding monotonic value function factorisation for deep multi-agent reinforcement learning. *Advances in neural information processing systems*, 33:10199–10210, 2020.

Mikayel Samvelyan, Tabish Rashid, Christian Schröder de Witt, Gregory Farquhar, Nantas Nardelli, Tim GJ Rudner, Chia-Man Hung, Philip HS Torr, Jakob N Foerster, and Shimon Whiteson. The starcraft multi-agent challenge. In *AAMAS*, 2019.

Max Simchowitz and Kevin G Jamieson. Non-asymptotic gap-dependent regret bounds for tabular mdps. *Advances in Neural Information Processing Systems*, 32, 2019.

Kyunghwan Son, Daewoo Kim, Wan Ju Kang, David Earl Hostallero, and Yung Yi. Qtran: Learning to factorize with transformation for cooperative multi-agent reinforcement learning. In *International Conference on Machine Learning*, pp. 5887–5896. PMLR, 2019.

Peter Sunehag, Guy Lever, Audrunas Gruslys, Wojciech Marian Czarnecki, Vinicius Zambaldi, Max Jaderberg, Marc Lanctot, Nicolas Sonnerat, Joel Z Leibo, Karl Tuyls, et al. Value-decomposition networks for cooperative multi-agent learning based on team reward. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 2085–2087, 2018.

Zhenggang Tang, Chao Yu, Boyuan Chen, Huazhe Xu, Xiaolong Wang, Fei Fang, Simon Shaolei Du, Yu Wang, and Yi Wu. Discovering diverse multi-agent strategic behavior via reward randomization. In *International Conference on Learning Representations*, 2021.

Lipeng Wan, Zeyang Liu, Xingyu Chen, Xuguang Lan, and Nanning Zheng. Greedy based value representation for optimal coordination in multi-agent reinforcement learning. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162, pp. 22512–22535. PMLR, 17–23 Jul 2022.

Jianhao Wang, Zhizhou Ren, Terry Liu, Yang Yu, and Chongjie Zhang. Qplex: Duplex dueling multi-agent q-learning. In *International Conference on Learning Representations*, 2020.

Jianhao Wang, Zhizhou Ren, Beining Han, Jianing Ye, and Chongjie Zhang. Towards understanding cooperative multi-agent q-learning with value factorization, 2021.

Ermo Wei, Drew Wicke, David Freelan, and Sean Luke. Multiagent soft q-learning. *arXiv preprint arXiv:1804.09817*, 2018.

Baicen Xiao, Bhaskar Ramasubramanian, and Radha Poovendran. Shaping advice in deep multi-agent reinforcement learning. *arXiv preprint arXiv:2103.15941*, 2021.

Yaodong Yang, Jianye Hao, Guangyong Chen, Hongyao Tang, Yingfeng Chen, Yujing Hu, Changjie Fan, and Zhongyu Wei. Q-value path decomposition for deep multiagent reinforcement learning. In *International Conference on Machine Learning*, pp. 10706–10715. PMLR, 2020a.

Yaodong Yang, Jianye Hao, Ben Liao, Kun Shao, Guangyong Chen, Wulong Liu, and Hongyao Tang. Qatten: A general framework for cooperative multiagent reinforcement learning. *CoRR*, abs/2002.03939, 2020b.

Xinghu Yao, Chao Wen, Yuhui Wang, and Xiaoyang Tan. Smix ($\lambda$): Enhancing centralized value functions for cooperative multiagent reinforcement learning. *IEEE Transactions on Neural Networks and Learning Systems*, 2021.

Chao Yu, Akash Velu, Eugene Vinitsky, Yu Wang, Alexandre Bayen, and Yi Wu. The surprising effectiveness of ppo in cooperative, multi-agent games. *arXiv preprint arXiv:2103.01955*, 2021.

Lulu Zheng, Jiarui Chen, Jianhao Wang, Jiamin He, Yujing Hu, Yingfeng Chen, Changjie Fan, Yang Gao, and Chongjie Zhang. Episodic multi-agent reinforcement learning with curiosity-driven exploration. *Advances in Neural Information Processing Systems*, 34, 2021.

Meng Zhou, Ziyu Liu, Pengwei Sui, Yixuan Li, and Yuk Ying Chung. Learning implicit credit assignment for cooperative multi-agent reinforcement learning. *Advances in Neural Information Processing Systems*, 33:11853–11864, 2020.

Ming Zhou, Jun Luo, Julian Villella, Yaodong Yang, David Rusu, Jiayu Miao, Weinan Zhang, Montgomery Alban, IMAN FADAKAR, Zheng Chen, et al. Smarts: An open-source scalable multi-agent rl training school for autonomous driving. In *Conference on Robot Learning*, pp. 264–285. PMLR, 2021.

# A    OMITTED PROOFS

## A.1    WVDN AND WEIGHTED LINEAR REGRESSION PROBLEM

WVDN operator is defined as

$$\Pi_{\text{WVDN}}Q := \underset{Q_{tot}\in\mathcal{Q}^{lvf}}{\arg\min} \sum_{\mathbf{u}\in\mathbf{U}} w^{ow}(s,\mathbf{u})(y(s,\mathbf{u}) - Q_{tot}(s,\mathbf{u}))^2, \tag{9}$$

where $\mathcal{Q}^{lvf} := \{Q_{tot}|Q_{tot}(s,\mathbf{u}) = \sum_{a=1}^{n} Q_a(s,u_a), Q_a(s,u) \in \mathbb{R}\}$, $w^{ow}(s,\mathbf{u})$ is the optimistic weighting:

$$w^{ow}(s,\mathbf{u}) = \begin{cases} 1 & y(s,\mathbf{u}) > Q_{tot}(s,\mathbf{u}) \\ \alpha & \text{otherwise} \end{cases}. \tag{10}$$

The optimising process of WVDN can be constructed as a weighted linear regression problem:

$$\min_{\mathbf{x}} \|\sqrt{\mathbf{w}^{\top}} \cdot \sqrt{\mathbf{p}^{\top}} \cdot (\mathbf{A}\mathbf{x} - \mathbf{b})\|, \tag{11}$$

where $\mathbf{A} \in \mathbb{R}^{m^n \times mn}, \mathbf{x} \in \mathbb{R}^{mn}, \mathbf{w},\mathbf{p},\mathbf{b} \in \mathbb{R}^{m^n}, m,n \in Z^+$. In particular, $m$ dentoes the action space size for each agent, $n$ denotes the number of agents.

Denote $\mathbf{A}^w = \sqrt{\mathbf{w}^{\top}} \cdot \sqrt{\mathbf{p}^{\top}} \cdot \mathbf{A}$, $\mathbf{b}^w = \sqrt{\mathbf{w}^{\top}} \cdot \sqrt{\mathbf{p}^{\top}} \cdot \mathbf{b}$. The optimal solution is:

$$\mathbf{x}^* = \mathbf{A}^{w,\dagger}\mathbf{b}^w, \tag{12}$$

where $\mathbf{A}^{w,\dagger} = VS^{\dagger}U^{\top}$ is the pseudo-inverse of $\mathbf{A}^w$ according to the Singular Value Decomposition. $U \in \mathbb{R}^{m^n \times m^n}$ and $V \in \mathbb{R}^{mn \times mn}$ are real orthogonal matrices, $S^{\dagger} \in \mathbb{R}^{m^n \times mn}$ is a diagonal matric with non-negative real numbers on the diagonal.

The proof is trivial.

Consider the full exploration scheme (i.e., $\epsilon$-greedy exploration with $\epsilon = 1$), and the non-monotonic game in Figure 6a, where $a = 8, b = -12, c = 6$.

For VDN (a special case of WVDN where $\alpha = 1$), we have

$$\mathbf{A} = \begin{pmatrix} 1 & 0 & 0 & 1 & 0 & 0 \\ 1 & 0 & 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 \end{pmatrix}, \mathbf{x} = \begin{pmatrix} Q_1(s,u_1^1) \\ Q_1(s,u_1^2) \\ Q_1(s,u_1^3) \\ Q_2(s,u_2^1) \\ Q_2(s,u_2^2) \\ Q_2(s,u_2^3) \end{pmatrix}, \mathbf{b} = \begin{pmatrix} 8 \\ -12 \\ -12 \\ -12 \\ 6 \\ 6 \\ -12 \\ 6 \\ 6 \end{pmatrix}, \mathbf{p} = \mathbf{w} = \begin{pmatrix} 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \end{pmatrix}. \tag{13}$$

According to (12), the optimal solution is

$$\mathbf{x}^* = \begin{pmatrix} -4.44 & 0.89 & 0.89 & -4.44 & 0.89 & 0.89 \end{pmatrix}^{\top}. \tag{14}$$

Clearly, $Q_i(u_i^1) < \max\{Q_i(u_i^2), Q_1(u_i^3)\}, \forall i \in \{1,2\}$, which indicates that VDN fails to converge to the optimal.

## A.2    OMITTED PROOFS IN SECTION 3

WVDN operator is defined in Section A.1.

Denote the joint action $\mathbf{u} = [u_1, ..., u_a, ..., u_n]$, where $n$ is the number of agents. Denote $u_a^i$ as the $i$-th action of $u_a$.

Consider matrix games in Figure 6. Suppose the training dataset is fixed and the data has a $\epsilon$-greedy distribution, where the greedy action is $(u_1^2, u_2^2)$ and $\epsilon \in (0, 1]$.

Based on the $\epsilon$-greedy distribution, the probabilities of each joint action $p(u_1^i, u_2^j)$ is:

$$Pr(u_1^i, u_2^j) = \begin{cases} \dfrac{\epsilon^2}{9}, & (i,j) \in \{(1,1),(1,3),(3,1),(3,3)\}, \\[2mm] \dfrac{(3-2\epsilon)^2}{9}, & (i,j) = (2,2), \\[2mm] \dfrac{(3-2\epsilon)\epsilon}{9}, & \text{otherwise.} \end{cases} \tag{15}$$

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | a | b | b |
| $u_2^2$ | b | c | c |
| $u_2^3$ | b | c | c |

(a) A non-monotonic matrix game.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | a | b | b |
| $u_2^2$ | b | c/d | e |
| $u_2^3$ | b | e | e |

(b) A stochastic matrix game.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | 8 | 6 | 6 |
| $u_2^2$ | 6 | 12/0 | 6 |
| $u_2^3$ | 6 | 6 | 6 |

(c) Payoff of a stochastic matrix game.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | 8 | -12 | -12 |
| $u_2^2$ | -12 | 12/0 | 6 |
| $u_2^3$ | -12 | 6 | 6 |

(d) Payoff of a stochastic and non-monotonic game.

Figure 6: Payoffs of matrix games. (a) is a non-monotonic matrix game, where $a > c > b$; (b) is a stochastic matrix game, where $(u_1^2, u_2^2)$ receives $c$ with probability $p$ and $d$ with $(1-p)$, $c > a > \max\{b, d, e\}$ and $a > pc + (1-p)d$; (c-d) are two numerical examples for stochastic matrix games, where the reward in (c) is monotonic and in (d) is non-monotonic.

To recover the optimal policy, the weight $\alpha$ for WVDN is bounded by $\epsilon$ and the reward space. We start by analysing the matrix game in Figure 6a. Since the matrix game only involves one state, we omit $s$ for the input of value functions in the following proofs.

**Proposition 1** *For WVDN, the weight $\alpha$ should be smaller than $\frac{3\epsilon(a-c)+\epsilon^2(c-b)}{(\epsilon-3)^2(c-b)}$ to recover the optimal joint policy on the non-monotonic matrix game in Figure 6a.*

*Proof.* First compute the gradient for $Q(u_1^1), Q(u_1^2), Q(u_1^3)$:

$$\triangledown Q(u_1^1) = \frac{\epsilon}{9}[(\epsilon + (3-\epsilon)\alpha)Q(u_1^1) + \epsilon Q(u_2^1) + (3-2\epsilon)\alpha Q(u_2^2) + \epsilon\alpha Q(u_2^3)$$
$$- \epsilon a - \alpha(3-\epsilon)b] \tag{16}$$

$$\triangledown Q(u_1^2) = \frac{(3-2\epsilon)\alpha}{9}[3Q(u_1^2) + \epsilon(Q(u_2^1) + Q(u_2^3)) + (3-2\epsilon)Q(u_2^2) - \epsilon b - (3-\epsilon)c] \tag{17}$$

$$\triangledown Q(u_1^3) = \frac{\epsilon\alpha}{9}[3Q(u_1^3) + \epsilon(Q(u_2^1) + Q(u_2^3)) + (3-2\epsilon)Q(u_2^2) - \epsilon b - (3-\epsilon)c] \tag{18}$$

Let $\triangledown Q(u_1^1) = \triangledown Q(u_1^2) = \triangledown Q(u_1^3) = 0$:

$$Q(u_1^1) = \frac{\epsilon a + \alpha(3-\epsilon)b - \epsilon Q(u_2^1) - (3-2\epsilon)\alpha Q(u_2^2) - \epsilon\alpha Q(u_2^3)}{\epsilon + 3\alpha - \epsilon\alpha} \tag{19}$$

$$Q(u_1^2) = Q(u_1^3) = \frac{\epsilon b + (3-\epsilon)c - \epsilon(Q(u_2^1) + Q(u_2^3)) - (3-2\epsilon)Q(u_2^2)}{3} \tag{20}$$

To recover the optimal joint policy, the following conditions should be satisfied:

$$Q(u_1^1) - \max\{Q(u_1^2), Q(u_1^3)\} > 0, Q(u_2^1) - \max\{Q(u_2^2), Q(u_2^3)\} > 0 \tag{21}$$

Denote $t = \epsilon + 3\alpha - \epsilon\alpha$. Then

$$Q(u_1^1) - \max\{Q(u_1^2), Q(u_1^3)\}$$
$$= \frac{\epsilon a + \alpha(3-\epsilon)b - \epsilon Q(u_2^1) - (3-2\epsilon)\alpha Q(u_2^2) - \epsilon\alpha Q(u_2^3)}{t}$$
$$- \frac{\epsilon b + (3-\epsilon)c - \epsilon(Q(u_2^1) + Q(u_2^3)) - (3-2\epsilon)Q(u_2^2)}{3}$$
$$< \underbrace{(\frac{t + \epsilon\alpha - \epsilon - 3\alpha}{t})}_{= 0}Q(u_2^1) + \frac{\epsilon}{t}a + \frac{(9-3\epsilon)\alpha - \epsilon t}{3t}b + \frac{\epsilon - 3}{3}c. \tag{22}$$

Let $Q(u_1^1) - \max\{Q(u_1^2), Q(u_1^3)\} > 0$ and $Q(u_2^1) - \max\{Q(u_2^2), Q(u_2^3)\} > 0$.

Then $\alpha < \frac{3\epsilon(a-c)+\epsilon^2(c-b)}{(\epsilon-3)^2(c-b)}$. $\square$

**Proposition 2** *For WVDN, the weight $\alpha$ should be large enough to recover the optimal joint policy for the stochastic matrix game in Figure 6b.*

**Theorem 1** *Let* $\Pi_{\text{WVDN}}Q := \arg\min_{Q_{tot} \in \mathcal{Q}^{lvf}} \sum_{\boldsymbol{u} \in \mathbf{U}} w^{ow}(s, \boldsymbol{u})(Q(s, \boldsymbol{u}) - Q_{tot}(s, \boldsymbol{u}))^2$ *and* $w^{ow}(s, \boldsymbol{u})$ *is the optimistic weighting from (4). Then* $\exists Q$ *such that* $\arg\max \Pi_{\text{WVDN}}Q \neq \arg\max Q$ *for any* $\alpha \in (0, 1]$.

*Proof.* Since the proof of Proposition 2 and Theorem 1 contains a significant overlap, we will merge them both into a single proof.

First compute the gradient for $Q(u_1^1), Q(u_1^2), Q(u_1^3)$:

$$\nabla Q(u_1^1) = \frac{\epsilon}{9}[(\epsilon + 3\alpha - \epsilon\alpha)Q(u_1^1) + \epsilon Q(u_2^1) + (3 - 2\epsilon)\alpha Q(u_2^2) + \epsilon\alpha Q(u_2^3) - \epsilon a - \alpha(3 - \epsilon)b] \tag{23}$$

$$\nabla Q(u_1^2) = \frac{3 - 2\epsilon}{9}[((3 - 2\epsilon)(1 - \alpha)p + 3\alpha)Q(u_1^2) + \epsilon\alpha(Q(u_2^1) + Q(u_2^3)) + (3 - 2\epsilon)(p + \alpha - p\alpha)Q(u_2^2) - \epsilon\alpha b - (3 - 2\epsilon)(pc + \alpha d - \alpha pd) - \epsilon\alpha e] \tag{24}$$

$$\nabla Q(u_1^3) = \frac{\epsilon\alpha}{9}[3Q(u_1^3) + \epsilon(Q(u_2^1) + Q(u_2^3)) + (3 - 2\epsilon)Q(u_2^2) - \epsilon b - (3 - \epsilon)e] \tag{25}$$

To recover the optimal joint policy, the following requirements should be satisfied:

$$Q(u_1^1) - \max\{Q(u_1^2), Q(u_1^3)\} > 0, Q(u_2^1) - \max\{Q(u_2^2), Q(u_2^3)\} > 0$$

Let $\nabla Q(u_1^1) = \nabla Q(u_1^2) = \nabla Q(u_1^3) = 0$. Denote $t = \epsilon + 3\alpha - \epsilon\alpha$, $m = (3 - 2\epsilon)(1 - \alpha)p + 3\alpha$. Then

$$Q(u_1^1) - Q(u_1^2) < \frac{\epsilon}{t}a + \frac{(3 - \epsilon)\alpha}{t}b - \frac{\epsilon\alpha}{m}(b + e) - \frac{(3 - 2\epsilon)p}{m}c - \frac{(3 - 2\epsilon)(1 - p)\alpha}{m}d, \tag{26}$$

$$Q(u_1^1) - Q(u_1^3) < \frac{\epsilon}{t}a + \frac{(3 - \epsilon)\alpha}{t}b - \frac{\epsilon}{3}b - \frac{(3 - \epsilon)p}{3}e. \tag{27}$$

For the matrix game in Figure 6b, consider the following situations:

(1) The target is monotonic but stochastic. For example, in Figure 6c, $a = 8$, $b = e = 6$, $c = 12$, $d = 0$, and $p = 0.5$. To recover the optimal joint action, the weight $\alpha$ should be greater than $(0.434, 0.667, 0.827, 0.932)$ when $\epsilon = (1, 0.75, 0.5, 0.25)$, respectively.

(2) The target is non-monotonic and stochastic. For example, in Figure 6d, $a = 8$, $b = -12$, $c = 12$, $d = 0$, $e = 6$, and $p = 0.5$. When $\epsilon = (1, 0.75, 0.5, 0.25)$, there does not exist the weight $\alpha \in (0, 1]$ making $Q(u_1^1) - \max\{Q(u_1^2), Q(u_1^3)\} > 0$, i.e., WVDN cannot converge to the optimal.

Thus, $\exists Q$ such that $\arg\max \Pi_{\text{WVDN}}Q \neq \arg\max Q$ for any $\alpha \in (0, 1]$. $\square$

More experimental results can be found in Appendix B.1.

## A.3 OMITTED PROOFS OF RESHAPING FUNCTION

**Theorem 2** *Let* $Q^f(s, \boldsymbol{u})$ *be the reshaped targets from (7). Then* $\forall s \in S$ *and* $\forall \boldsymbol{u} \in U$ *such that,* $\arg\max_{\boldsymbol{u}} Q^f(s, \boldsymbol{u}) = \arg\max_{\boldsymbol{u}} Q(s, \boldsymbol{u})$ *and* $Q^f(s, \boldsymbol{u}) \in \mathcal{Q}^{mvf}$.

*proof.* Considering only a fully-observable setting for ease of representation. Thus our notations do not distinguish the concepts of states and observation-action histories. In addition, when more than one optimal policy exists, most $Q$-learning algorithms fail to converge to a stable point (Simchowitz & Jamieson, 2019; Wang et al., 2020; Rashid et al., 2020). Thus, consider a $s \in S$, we assume $\mathbf{u}_Q^* = \arg\max_{\mathbf{u}} Q(s, \mathbf{u})$ is unique.

Assume $\max_{\mathbf{u}_{-a}} Q(s, u_a, \mathbf{u}_{-a})$ for all $u_a$ are perfectly represented.

Then $Q(s, \mathbf{u}) \leqslant \min_{a \in \mathbb{A}} \{\max_{\mathbf{u}_{-a}} Q(s, u_a, \mathbf{u}_{-a})\}$.

By the shaping function from (7):

$$\begin{cases} Q^f(s, \mathbf{u}_Q^*) = Q(s, \mathbf{u}_Q^*) \\ Q^f(s, \mathbf{u}) = \min\{\max_{\mathbf{u}_{-i}} Q(s, u_i, \mathbf{u}_{-i})\}, \forall u_i \in \mathbf{u} \neq \mathbf{u}_Q^* \text{ and } u_i \notin \mathbf{u}_Q^* \end{cases} \quad (28)$$

Under the assumption of the unique optimal action, we have $Q^f(s, \mathbf{u}_Q^*) > Q^f(s, \mathbf{u})$ for all $\mathbf{u} \neq \mathbf{u}_Q^*$. Therefore, $\arg\max_{\mathbf{u}} Q^f(s, \mathbf{u}) = \arg\max_{\mathbf{u}} Q(s, \mathbf{u})$.

Suppose $\exists f_s(s, Q_1(s, u_1), ..., Q_n(s, u_n)) = Q^f(s, \mathbf{u}), \forall \mathbf{u} = (u_1, ..., u_n) \in \mathbf{U}$. Then

$$\begin{cases} f_s(s, Q_a(u_a), \mathbf{Q}_{-a}(\mathbf{u}_{-a})) = \min\{\max_{\mathbf{u}_{-a}} Q(s, u_a, \mathbf{u}_{-a}), \max_{\mathbf{u}_{-i}} Q(s, u_i, \mathbf{u}_{-i})\}, \forall i \in -a \\ f_s(s, Q_a(u_a'), \mathbf{Q}_{-a}(\mathbf{u}_{-a})) = \min\{\max_{\mathbf{u}_{-a}} Q(s, u_a', \mathbf{u}_{-a}), \max_{\mathbf{u}_{-i}} Q(s, u_i, \mathbf{u}_{-i})\}, \forall i \in -a. \end{cases} \quad (29)$$

where $\mathbf{Q}_{-a}(\mathbf{u}_{-a}) = \{Q_i(s, u_i)\}_{i \in -a}$.

Let $Q_a(s, \mathbf{u}_a) \geqslant Q_a(s, \mathbf{u}_a')$ if $\max_{\mathbf{u}_{-a}} Q(s, u_a, \mathbf{u}_{-a}) \geqslant \max_{\mathbf{u}_{-a}} Q(s, u_a', \mathbf{u}_{-a}), \forall a \in A$.

Then, according to (29), $f_s(s, Q_a(u_a), \mathbf{Q}_{-a}(\mathbf{u}_{-a})) \geqslant f_s(s, Q_a(u_a'), \mathbf{Q}_{-a}(\mathbf{u}_{-a}))$.

Thus we can find $f_s(s, Q_1(s, u_1), ..., Q_n(s, u_n))$ to represent $Q^f(s, \mathbf{u}), \forall \mathbf{u} = (u_1, ..., u_n) \in \mathbf{U}$, where $\frac{\partial f_s}{\partial Q_a} \geqslant 0$. And so $Q^f(s, \mathbf{u}) \in \mathcal{Q}^{mvf}, \forall s \in S, \forall \mathbf{u} \in \mathbf{U}$. $\square$

# B RESULTS ON MATRIX GAMES

## B.1 WQMIX WITH DIFFERENT WEIGHTS

In Section 3.1, we demonstrate the complete data of minimal $1/\alpha$ for WVDN and WQMIX to recover the optimal policy, where $\alpha$ denotes the weight on the suboptimal. The payoff matrix is shown in 6a. The dataset is collected by the $\epsilon$-greedy exploration, where the greedy action is set to $\mathbf{u}^s = (u_1^2, u_2^2)$.

We select $a = 8$, $b = -12$, and (1) three reward assignments, $c \in \{-3, 3, 6\}$, $\epsilon = 0.25$, as well as (2) three exploration rate assignments, $\epsilon \in \{0.5, 0.75, 1\}$, $c = 6$, and run WVDN and WQMIX with five random seeds on a fixed dataset. We show the gap between the approximated real optimal action value $\hat{Q}_1(u_1^*)$ and greedy action value $\hat{Q}_1(\hat{u}_1^*)$ for agent 1, which should be zero if the algorithm converges to the optimal. Figure 7 shows that the gap reduces with the increase of $1/\alpha$, indicating that the weight $\alpha$ should be small enough to deal with non-monotonicity. In addition, we can see that $\alpha$ should be small enough to converge to the optimal when the suboptimal value is large or the exploration rate is low, which is consistent with our analysis.

(a) The performance with different $c$, where $a = 8, b = -12, \epsilon = 0.25$.

(b) The performance with different $\epsilon$, where $a = 8, b = -12, c = 6$.

Figure 7: WVDN and WQMIX on the non-monotonic game. The payoff matrix is shown in 6a.

In Section 3.2 and Section A.2, we prove that the contradiction of the choice of $\alpha$ may result in converging on the suboptimal for WQMIX. We also conduct experiments to verify our analysis. We

consider the matrix game in Figure 9a, and train WVDN and WQMIX on a fixed dataset. The dataset is collected by the $\epsilon$-greedy exploration, where the greedy action is set to $\mathbf{u}^s = (u_1^2, u_2^2)$ and $\epsilon = 0.5$. We show the gap between the approximated real optimal action value $\hat{Q}_1(u_1^*)$ and greedy action value $\hat{Q}_1(\hat{u}_1^*)$ for agent 1, which should be zero if the algorithm converges to the optimal. We also show whether the greedy action is optimal by an indicator function $\mathbf{1}_{\hat{Q}_1(u_1^*)=\hat{Q}_1(\hat{u}_1^*)}$.

(a) The value gap between the real optimal action and the greedy action.

(b) The indicator function that shows whether the greedy action is the optiaml.

Figure 8: WVDN and WQMIX on the matrix game where the target is non-monotonic and stochastic.

As shown in Figure 8, WQMIX and WVDN cannot converge to the optimal with different $\alpha$. Since CW-QMIX does not place $\alpha$ on the current greedy joint action, it can get rid of the stochastic suboptimal $\mathbf{u}^s$ when $\mathbf{u}^s$ is the current greedy action, i.e., $\hat{\mathbf{u}}^* = \mathbf{u}^s$. However, with the decrease of $Q_{tot}(\mathbf{u}^s)$, CW-QMIX falls into this suboptimal again once $\hat{\mathbf{u}}^* \neq \mathbf{u}^s$. Therefore, we can see that the gap between $\hat{Q}_1(u_1^*)$ and $\hat{Q}_1(\hat{u}_1^*)$ is tiny. However, as shown in Figure 8b, CW-QMIX cannot converge to the optimal, which is consistent with our analysis.

## B.2 THE APPROXIMATED JOINT ACTION-VALUES

We also show the joint action-value returned from our baselines on a matrix game with non-monotonic and stochastic rewards in Figure 9a. We adopt a uniform exploration strategy to approximate the uniform data distribution (i.e., $\epsilon$-greedy exploration with $\epsilon = 1$). As shown in Figure 9, UTS and QTRAN can recover the optimal policy, while other methods fail to solve this simple task. Since we have discussed QMIX and WQMIX in previous sections, here we analyse QPLEX and GVR.

In QPLEX, the joint action-value is:

$$Q_{tot}(\boldsymbol{\tau}, \mathbf{u}) = V_{tot}(\boldsymbol{\tau}) + A_{tot}(\boldsymbol{\tau}, \mathbf{u}) = \sum_{i=1}^{n} V_i(\boldsymbol{\tau}) + \sum_{i=1}^{n} \lambda_i(\boldsymbol{\tau}, \mathbf{u}) A_i(\boldsymbol{\tau}, u_i)$$

$$= \sum_{i=1}^{n} [w_i(\boldsymbol{\tau}) V_i(\tau_i) + b_i(\boldsymbol{\tau})] + \sum_{i=1}^{n} \lambda_i(\boldsymbol{\tau}, \mathbf{u}) [Q_i(\boldsymbol{\tau}, u_i) - V_i(\boldsymbol{\tau})] \quad (30)$$

where $V_i(\tau_i) = \max_{u_i} Q_i(\tau_i, u_i), w_i(\boldsymbol{\tau}) \geq 0, \lambda_i(\boldsymbol{\tau}, \mathbf{u}) > 0$.

Let $\mathbf{u}^* = [u_1^*, ..., u_i^*, ..., u_n^*]$, $\mathbf{u}^s = [u_1^s, ..., u_i^s, ..., u_n^s]$ denote the optimal and one of the suboptimal joint action, where $n$ is the number of agents. If QPLEX is initialised to this joint action, i.e., $V_{tot}(\boldsymbol{\tau}) = \sum_{i=1}^{n} Q_i(\tau_i, u_i^s)$, it is difficult to jump out from this suboptimal for QPLEX. Consider $Q(s, \mathbf{u}^s)$ is the real second greatest action value at a given state, where $u_i^s \neq u_i^*, \forall i \in A$. Therefore, joint action-values whose targets are smaller than $Q_{tot}(\boldsymbol{\tau}, \mathbf{u}^s)$ can be perfectly represented by QPLEX. However, when $(\boldsymbol{\tau}, \mathbf{u}^*)$ is sampled, QPLEX tries to minimising the following loss:

$$(\sum_{i=1}^{n} \lambda_i(\boldsymbol{\tau}, \mathbf{u}^*) [Q_i(\boldsymbol{\tau}, u_i^*) - V_i(\boldsymbol{\tau})] - [Q(\boldsymbol{\tau}, \mathbf{u}^*) - V_{tot}(\boldsymbol{\tau})])^2, \quad (31)$$

where $Q(\boldsymbol{\tau}, \mathbf{u}^*) - V_{tot}(\boldsymbol{\tau}) > 0, Q_i(\boldsymbol{\tau}, u_i^*) - V_i(\boldsymbol{\tau}) \leq 0$, and $\lambda_i(\boldsymbol{\tau}, \mathbf{u}^*) > 0$. As a result, $\lambda_i(\boldsymbol{\tau}, \mathbf{u}^*)$ decreases to almost zero, and $Q_i(\boldsymbol{\tau}, u_i^*)$ gradually reaches to $V_i(\boldsymbol{\tau})$. However, the process is very

time consuming and $Q_i(\boldsymbol{\tau}, \mathbf{u}_i^*)$ cannot exceed $V_i(\boldsymbol{\tau})$ in most cases due to the low weight $\lambda_i(\boldsymbol{\tau}, \mathbf{u}^*)$, i.e., the **vanishing gradient** problem. Consequently, as shown in Figure 9h, the approximated joint action-values for the optimal $\mathbf{u}^* = (u_1^1, u_2^1)$ and three suboptimal $\{(u_1^2, u_2^3), (u_1^3, u_2^2)(u_1^3, u_2^3)\}$ are 4.37 in QPLEX.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | **8** | -12 | -12 |
| $u_2^2$ | -12 | 20 / -20 | 6 |
| $u_2^3$ | -12 | 6 | 6 |

(a) A game with non-monotonic and stochastic rewards.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | **8** | 6 | 6 |
| $u_2^2$ | 6 | 6 | 6 |
| $u_2^3$ | 6 | 6 | 6 |

(b) UTS.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | 1.68 | 1.68 | 1.68 |
| $u_2^2$ | 1.68 | **16.8** | 6.33 |
| $u_2^3$ | 1.68 | 6.33 | 5.93 |

(c) OW-QMIX ($\alpha$=0.1).

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | 2.72 | 2.72 | 2.72 |
| $u_2^2$ | 2.72 | **5.97** | **5.97** |
| $u_2^3$ | 2.72 | **5.97** | **5.97** |

(d) CW-QMIX ($\alpha$=0.1).

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | -8.29 | -8.29 | -8.29 |
| $u_2^2$ | -8.29 | 1.49 | 4.64 |
| $u_2^3$ | -8.29 | 5.00 | **8.15** |

(e) QMIX ($\alpha$=1).

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | 5.31 | 5.33 | 5.33 |
| $u_2^2$ | 5.35 | **6.03** | **6.03** |
| $u_2^3$ | 5.35 | **6.03** | **6.03** |

(f) GVR.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | **8.09** | -12.32 | -12.24 |
| $u_2^2$ | -12.32 | -2.27 | 5.76 |
| $u_2^3$ | -12.24 | 5.76 | 5.62 |

(g) QTRAN.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ | $u_1^3$ |
|---|---|---|---|
| $u_2^1$ | **4.37** | -8.06 | -8.45 |
| $u_2^2$ | -6.93 | 1.61 | **4.37** |
| $u_2^3$ | -8.09 | **4.37** | **4.37** |

(h) QPLEX.

Figure 9: The results on a matrix game with non-monotonic and stochastic rewards. Boldface means the optimal joint action from the payoff matrix, or the greedy joint action from the $Q_{tot}$.

GVR uses inferior target shaping and superior experience replay to eliminate the non-optimal self-transition nodes. However, it ignores the stochasticity at all as WQMIX, and thus behaves as CW-QMIX and cannot converge to any joint action (Figure 9f). More comparison among GVR, WQMIX, and UTS can be found in Appendix C.

## C COMPARISON WITH WQMIX AND GVR

In Section 3.1, we prove that WQMIX with a low $\alpha$ can overcome any non-monotonic tasks. However, we also prove that WQMIX is particularly brittle with stochasticity because it overestimates the expected value of the suboptimal whose target is large with a low probability. GVR also ignores the stochasticity and cannot accurately identify whether a given action is inferior. As a result, WQMIX with fine-tuned $\alpha$ and GVR are able to solve any non-monotonic targets, but cannot deal with stochasticity.

Figure 10: The comparison of GVR, UTS, and WQMIX with different weights.

To further show the difference between these methods and UTS, we compare them on predator-prey with different level of miscoordination penalties and stochasticity. Figure 10 demonstrates that

WQMIX with a very low $\alpha$ and GVR can obtain the positive test return in all penalty settings on predator-prey. However, they cannot recover the optimal joint policy on stochastic predator-stag-hare. By contrast, UTS outperforms WQMIX and GVR in these tasks.

## D ABLATION STUDIES

In this section, we conduct ablation studies to investigate the influence of target shaping in UTS. The following methods are included in the evaluation: 1) QMIX, which is the natural ablation baseline of UTS, 2) UTS without target shaping (denoted by UTS-wo-TS), i.e., agents are trained only according to the best action value function $q_a(s, \tau_a, u_a)$, and 3) the original UTS.

We compare these methods on predator-prey and predator-stag-hare, and the results are shown in Figure 11. Since the miscoordination penalty is large, QMIX cannot deal with non-monotonic targets and thus fail to solve these tasks. UTS-wo-TS and UTS can learn to catch the prey (stags), where UTS learns more quickly and stably. Since the estimated best action value introduces additional estimation error that may cause a significant variance, we also show the standard deviation of per-agent action values $Q_a$ for these methods. As shown in Figure 11, we can see that UTS has a lower standard deviation than UTS-wo-TS.

Figure 11: The comparison of QMIX, UTS, and UTS-wo-TS.

To better understand why UTS can achieve better performance, first, we need to discuss the advantage of value factorisation methods. Linear value factorisation implicitly achieves credit assignment using a counterfactual baseline Wang et al. (2021). The individual action-value function $Q_i(s, u_i)$ is updated by:

$$\mathbb{E}_{u'_{-i} \sim \boldsymbol{\pi}}[y(s, u_i, u_{-i})] - \frac{n-1}{n} \mathbb{E}_{\mathbf{u}' \sim \boldsymbol{\pi}}[y(s, \mathbf{u}')] + w_i(s), \qquad (32)$$

where residue term $\mathbf{w} \equiv [w_1(s), ..., w_n(s)]$ denotes an arbitrary vector satisfying $\forall s, \sum_1^n w_i(s) = 0$. As a result, the individual action-value in linear value factorisation can be viewed as a type of *advantage function*, where the per-agent baseline reduces variance but does not affect the convergence. Due to the non-linear mixing function in QMIX, a more general theoretical understanding of monotonic value factorisation is still insufficient. However, previous work shows that QMIX also implicitly performs credit assignment and outperforms linear value factorisation Rashid et al. (2018; 2020); Zhou et al. (2020).

Figure 12: Per-agent action values from QMIX, UTS, and UTS-wo-TS.

A numerical example is provided in Figure 12. Figure 12a shows the payoff of a one-step non-monotonic game. First, we show the standard deviation of per-agent action values $Q_a$. QMIX converges to the suboptimal when it meets non-monotonic targets of the joint action-value function. As shown in Figure 12b, $Q_1^{QMIX}(u_1^1)$ keeps reducing and is smaller than the values of other actions, which implies that QMIX converges to the suboptimal due to representational limitation. Both UTS and UTS-wo-TS can recover the optimal policy. The action values in UTS-wo-TS show similar trends, and thus UTS-wo-TS can be stable until it perfectly approximates all action values. By contrast, UTS shapes the targets to ensure they can be represented by monotonic value factorisation, where the optimal policy is invariant during this shaping. UTS performs credit assignment with the shaped targets, the action values in UTS can be viewed as a type of **advantages** and thus are much smaller

Figure 13: Standard deviation of per-agent action values from QMIX, UTS, and UTS-wo-TS on a random $10 \times 10$ matrix game.

than UTS-wo-TS. The action values in UTS show two different trends, where $Q_1^{UTS}(u_1^1)$ is positive, $Q_1^{UTS}(u_1^2)$ and $Q_1^{UTS}(u_1^3)$ are negative when the algorithm converges.

We also show the standard deviation of per-agent action values from QMIX, UTS, and UTS-wo-TS on a random $10 \times 10$ matrix game, where the suboptimal is filled with random numbers generated uniformly between -20 and 19, and the unique optimal value is +20. As shown in Figure 13, UTS reduces variance compared to UTS-wo-TS, thus improving learning efficiency and stability.

## E  MULTIPLE OPTIMAL

When more than one optimal policy exists in the Markov Decision Process, many value-based algorithms fail to converge on a stable point (Simchowitz & Jamieson, 2019). However, multiple optimal may be very common in a multi-agent setting. For example, when two agents arrive at a crossroads, the optimal solution is that one of them chooses to move and another chooses to make way. In this situation, the team can solve this simple task no matter which agent chooses to move.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ |
|---|---|---|
| $u_2^1$ | 1 | 0.5 |
| $u_2^2$ | 0.5 | 1 |

(a) Payoff of a game with multiple optimal.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ |
|---|---|---|
| $u_2^1$ | 0.75 | 0.75 |
| $u_2^2$ | **0.76** | **0.76** |

(b) QMIX, $\epsilon = 1$.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ |
|---|---|---|
| $u_2^1$ | 0.74 | **0.75** |
| $u_2^2$ | 0.74 | **0.75** |

(c) VDN, $\epsilon = 1$.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ |
|---|---|---|
| $u_2^1$ | 0.95 | 0.95 |
| $u_2^2$ | **0.97** | **0.97** |

(d) UTS, $\epsilon = 1$.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ |
|---|---|---|
| $u_2^1$ | 0.95 | 0.96 |
| $u_2^2$ | 0.96 | **1.02** |

(e) UTS, $\epsilon = 0.75$.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ |
|---|---|---|
| $u_2^1$ | 0.92 | 0.93 |
| $u_2^2$ | 0.92 | **1.02** |

(f) UTS, $\epsilon = 0.5$.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ |
|---|---|---|
| $u_2^1$ | 0.73 | 0.76 |
| $u_2^2$ | 0.76 | **1.01** |

(g) UTS, $\epsilon = 0.25$.

| $U_2 \backslash U_1$ | $u_1^1$ | $u_1^2$ |
|---|---|---|
| $u_2^1$ | 0.61 | 0.65 |
| $u_2^2$ | 0.66 | **1.00** |

(h) UTS, $\epsilon = 0.05$.

Figure 14: (a) The payoff matrix for a game with multiple optimal. (b-h) The estimated joint action-values $Q_{tot}$ returned from QMIX, VDN, and UTS with different exploration rate. Boldface means the optimal joint action from the payoff matrix, or the greedy joint action from the $Q_{tot}$.

We take a simple one-step matrix game with multiple optimal as an example. The payoff matrix is shown in Figure 14a. We investigate the performance of VDN, QMIX, QPLEX, and UTS on this simple task. Since this matrix game is non-monotonic, the target values cannot be perfectly represented in $\mathcal{Q}^{lvf}$ and $\mathcal{Q}^{mvf}$. When the full exploration scheme (i.e., $\epsilon$-greedy with $\epsilon = 1$) is applied, none of these methods can converge to the optimal. Although QPLEX achieves the full representational capacity (i.e., the joint action-values $Q_{tot}$ is the same as the payoff), it still cannot converge because all per-agent Q-values are optimal (because of the Individual-Global-Max). However, in practice, we can solve this problem by $\epsilon$-greedy with decayed $\epsilon$. In particular, we show the $Q_{tot}$ returned from UTS to illustrate the effect of the $\epsilon$. As shown in Figure 14e-h, we can see the gap between the suboptimal and the optimal increases with the decrease of the $\epsilon$, which improves the

learning stability. However, UTS inherits the characteristic of QMIX and thus is not a contraction, i.e., it would return two distinct $Q_{tot}$ and converge to any one of the optimal.

## F EXPERIMENTAL SETUP

We adopt the same architecture for VDN, QMIX, QTRAN, QPLEX, and WQMIX as (Samvelyan et al., 2019; Rashid et al., 2020). Each agent independently learns a policy with fully shared parameters between all policies. We used RMSProp with a learning rate of $5 \times 10^{-4}$ and $\gamma = 0.99$, buffer size 5000, mini-batch size 32 for all algorithms. We use an $\epsilon$-greedy strategy, and $\epsilon$ is linearly annealed from 1 to 0.05 over $50k$ timesteps (unless specified otherwise). The dimension of each agent's GRU hidden state is set to 64.

For WQMIX, we use $\alpha = 0.1$ on predator-prey and predator-stag-hare (unless specified otherwise), and $\alpha = 0.5$ in SMAC.

For UTS, we use the same agent and mixing network in WQMIX as (Rashid et al., 2020). For the reward and the state predictors, we use a multilayer perceptron (MLP) with ReLU non-linearities and a gated recurrent unit (GRU) to extract features, where the hidden dim is 128. Then we use another MLP to output the predicted reward, the standard deviation and the embedding of the next state. The first and the GRU parameters are shared. The dimension of the target embedding for the state $m$ is set to 16. We use Adam with a learning rate of $1 \times 10^{-3}$ to train the predictors. For the best action-value function, we use feed-forward networks with three hidden layers of dim $\{64, 64\}$ and ReLU non-linearities, where the optimiser is RMSProp with a learning rate of $5 \times 10^{-4}$.

We conduct experiments on an NVIDIA RTX 3090 GPU. Each task needs to train for about 5 hours on predator-prey, and about 8 to 16 hours on SMAC, depending on the number of agents and episode length limit of each map. We evaluate 32 episodes with decentralised greedy action selection every $10k$ timesteps for each algorithm.