Identifying Coarse-grained Independent Causal Mechanisms with Self-supervision

Abstract

Among the most effective methods for uncovering high dimensional unstructured data's generating mechanisms are techniques based on disentangling and learning independent causal mechanisms. However, to identify the disentangled model, previous methods need additional observable variables or do not provide identifiability results. In contrast, this work aims to design an identifiable generative model that approximates the underlying mechanisms from observational data using only self-supervision. Specifically, the generative model uses a degenerate mixture prior to learn mechanisms that generate or transform data. We outline sufficient conditions for an identifiable generative model up to two types of transformations that preserve a coarse-grained disentanglement. Moreover, we propose a self-supervised training method based on these identifiability conditions. We validate our approach on MNIST, FashionMNIST, and Sprites datasets, showing that the proposed method identifies disentangled models – by visualization and evaluating the downstream predictive model's accuracy under environment shifts.

Keywords: Causal mechanisms, generative model, disentanglement, identifiability

1. Introduction

The independent causal mechanisms (ICM) principle assumes that a system's variables are generated by autonomous modules (i.e., mechanisms) that do not influence or inform each other (Schölkopf et al., 2012; Peters et al., 2017; Schölkopf, 2019). In this paper, we consider a class of systems where an observable variable follows a mixture distribution, and each mixture component is generated by a composition of mechanisms (Locatello et al., 2018b; Parascandolo et al., 2018). Specifically, each data generating mechanism generates data samples for a specific mixture component, and the data transformation mechanisms could transform the data samples without moving the data samples from one mixture component to another. Moreover, we let each mechanism take latent variables as additional input, which controls the generated data's variation. This kind of data is ubiquitous, and examples include visual data in object recognition tasks, where animals, plants, and other objects are generated by different data generating mechanisms, and the data transforming mechanisms control the background and the lighting condition, among others. Figure 2(*b*) shows an example of our system with three mechanisms that collaboratively generate data samples (i.e., handwritten digits) for a mixture distribution with two mixture components. This manuscript proposes a method for learning the data generating and transforming mechanisms from the observable variable in the aforementioned class of systems by learning the latent variables.

One benefit of learning the data generating and transforming mechanisms is better generalization across environments. Recent works (Koh et al., 2020; Gulrajani and Lopez-Paz, 2021) show

(*a*) Sampled Data from Mechanisms Learned by Our ICM Model.

(*b*) Sampled Data from Mechanisms Learned by Existing Competitive Training-based Approach.

Figure 1: Each row represents the data from one mechanism. Ideally, the mechanisms should specialize in synthesizing one digit uniquely. (a) shows that each data generating mechanism specializes in different digits. (b) shows that the mechanisms are confounded with other digits – illustrating a failure of the model and competitive training approach. Figure (b) is adapted from (Locatello et al., 2018b).

that the accuracy of a machine learning (ML) model can decrease drastically if the model is deployed in an environment that differs from the environment where the model is trained. For an image classification task, different environments may have variability in illumination, camera angle, background, color, among others (Koh et al., 2020). As variables like illumination are not conditioned on the data samples or the labels, we can model their effect as data transforming mechanisms controlled by latent variables. Importantly, by the ICM principle, the change of data transformation mechanisms does not influence the data-generating mechanisms. Therefore, if we use the inverted data-generating mechanisms to recover the latent variables that generate the data and feed the latent variables to the downstream predictive ML model, we can expect more robustness to environmental shifts due to disentanglement. Thus, a disentanglement between latent variables results from the disentanglement between mechanisms.

The literature on both independent causal mechanisms (Locatello et al., 2018b; Parascandolo et al., 2018) and disentangled representations (Higgins et al., 2017; Locatello et al., 2020) have produced powerful disentanglement techniques. However, they often use competitive-training-based approaches (Locatello et al., 2018a,b) for learning the data-generating mechanisms. We argue that this *yields sub-optimal disentanglement* for our generative models of interest. This is because competitive training disentangles by estimating a mixture of generative adversarial network (GAN) models which collapse to different mixture components. Such architectures are difficult to control. Consequently, in practice, training often fails – so one mechanism induces multiple mixture components, or one mixture component induces multiple mechanisms. Figure 1(*b*) illustrates an example of this failure mode, showing an example where the estimated mechanisms are entangled – as the mechanisms do not specialize to mixture components in the data. In contrast, using our method, the disentangled mechanisms are specialized to digits 4 and 9 (Figure 1(*a*)).

Another competitive training method, Parascandolo et al. (2018), learns the mechanisms by letting a mixture of models convert a set of transformed data samples (e.g., rotated data samples) to the original data samples. This approach requires the use of an auxiliary dataset–separate from the original dataset. However, it is common for the transformed and original data to be mixed in the dataset. An additional gap in the literature is that *few of the existing methods for learning the mechanisms analyze identifiability conditions*, i.e., when one can distinguish the desired disentangled model among the entangled models (Locatello et al., 2019; Khemakhem et al., 2020). Existing identifiability results (Shu et al., 2019; Locatello et al., 2020) mainly focus on disentangled representations and either need additional labeling efforts or are not compatible with the class of system that we study. Section 3.3 discusses the difficulties of applying previous identifiability results in more detail.

To address the disentanglement, dataset, and identifiability limitations, we seek a practical method that provably identifies the disentangled mechanisms without requiring any auxiliary dataset or label. To this end, we first present a new generative model that uses a degenerate mixture prior distribution to learn the mechanisms. We refer to our new model as the ICM model. Our ICM model first learns the latent variables of the mechanisms and then transforms them into disentangled mechanisms. We define *coarse-grained* disentanglement between latent variables: the variables for the same mechanism could be entangled but each group of variables from different mechanisms should be disentangled. Albeit coarse, we will show that the benefits of disentanglement under environment shift are preserved. With the proposed ICM model, we prove that we can identify the disentangled generative model in a coarse-granularity up to two types of transformations. The two types of transformations may, for example, permute the order of the latent variables but do not violate the coarse-grained disentanglement. Unlike existing identifiability results (Shu et al., 2019; Locatello et al., 2020; Khemakhem et al., 2020) which requires supervision, our identifiability result requires only the invertibility of the generative model. To meet the invertibility condition, we introduce a self-supervised training method, which is more straightforward than the competitive training methods (Parascandolo et al., 2018; Locatello et al., 2018b). Further, by enforcing the identifiability conditions, we enforce the coarse-grained disentanglement. Our key contributions are summarized as follows:

- We develop a novel generative model for learning disentangled mechanisms using a degenerate mixture prior.

- We prove the proposed generative model is identifiable up to two types of transformations that preserve the coarse-grained disentanglement.

- We design a self-supervised training method to enforce the identifiability conditions.

We evaluate our approach using synthetic data with known ground-truth latent variables, showing that with an invertible ICM model, our approach closely approximates the true disentangled latent variables, in contrast to non-invertible generative models. Qualitatively, a latent space traversal shows that the latent variables are disentangled in a coarse-granularity. Quantitatively, we show that the proposed ICM model improves downstream classification accuracy under environment shift due to the disentanglement between latent variables. The accuracy improvements are up to 9.75% on MNIST, FashionMNIST, and Sprites datasets, compared to VAE, β-VAE, and Ada-GVAE models.

2. The Generative Model with a Degenerate Mixture Prior

This section introduces our proposed generative model. In constrast to prior work (Parascandolo et al., 2018), our approach includes latent variables for data generating mechanisms and data transforming mechanisms simultaneously without requiring an auxiliary dataset. Next, we connect the generative model and latent variables to underlying mechanisms. We further discuss identifiability and propose a training method for our model in Sections 3 and 4, respectively.

2.1. Generative Model

Assumed Data Generating Process   Following prior work (Parascandolo et al., 2018), we assume a two-step deterministic data generating process. A data sample $x' = M_{G_i}(z_{G_i})$ is generated by a data generating mechanism M_{G_i} using latent variables z_{G_i} as in Locatello et al. (2018b). The data sample x' is further transformed to another data sample $x = M_{T_j}(x')$ by a data transformation

(a) Previous Data Generating Process   (b) Disentangled Mechanisms (proposed model)   (c) Entangled Mechanisms (contrast)

Figure 2: Comparing existing approaches (a) to the proposed approach (b) and an entangled variant (c) without mechanism separation. M_{G_i} is a data generating mechanism. M_{T_i} and M_T are data transforming mechanisms. The latent variables and data samples affiliate to the mechanisms with the same color. Mechanisms are disentangled if their input latent variables are disentangled and specialized for different types of variation.

mechanisms M_{T_j} similar to Parascandolo et al. (2018). Our approach is visualized in Figure 2(a) for MNIST digits 4 and 9. Here, the latent variable z_{G_4} may control whether digit 4 has a bar, crossing its stem while the latent variable z_{G_9} may decide the circle size of digit 9, as the two rows in Figure 1(a) shows. We consider, for example, thickening or rotating a digit as data transforming mechanisms (M_{T_0} and M_{T_1} in Figure 2(a)).

Our Approach and Model Structure   To learn the mechanisms, we take a two-step approach: (1) designing a model for learning the latent variables and (2) transforming the model to the mechanisms. In step (1), we adopt a model: $x = g(z_G, z_T)$ where x is the data sample, $z_G = [z_{G_0}, z_{G_1}, ...]$ are the latent variables for the data generating mechanisms and z_T is the latent variable for the data transforming mechanisms. By fitting our model to the dataset (with additional techniques), we let each z_{G_i} z_T capture the variability in data. We use a running example to introduce step (2).

Running Example   Figure 2(b) visualizes a disentangled version of our model. Here, consider a modular model (the black rectangle) that contains the mechanisms as sub-modules. The modular model generates data by activating a sequence of sub-modules. We assume the sub-modules are activated upon receiving any non-zero input.

Previous Models and their Limitations   Previous competitive training-based approaches (Parascandolo et al., 2018; Locatello et al., 2018b) adopt a model structure that is the same as the assumed data generating process: $x = \sum_{j=1}^{K_T} \pi_{T_j} M_{T_j} \left(\sum_{i=1}^{K_G} \pi_{G_i} M_{G_i}(z_{G_i}) \right)$, where π_T and π_G are one-hot vectors. Unfortunately, learning mixtures of mechanisms is difficult. Their works assume the canonical distribution (Parascandolo et al., 2018), $x' = \sum_{i=1}^{K_G} \pi_{G_i} M_{G_i}(z_{G_i})$ is available, then learns the two mixtures separately (Parascandolo et al., 2018; Locatello et al., 2018b) but such an assumption does not apply to many conventional datasets.

While the proposed approach is designed to disentangle the latent variables, simply fitting the proposed generative model to the dataset and hoping the z_{G_i} and z_T encodes different types of variations for different mechanisms can fail. The issues are twofold: (1) The commonly used dis-

(*a*) Non-degenerate $\qquad\qquad\qquad$ (*b*) Degenerate

Figure 3: (a) Using non-degenerate mixture prior leads to: (1) One latent variable encodes multiple types of variations (e.g., for digits 4 and 9). (2) Intervening the latent variable moves the generated data samples from one mixture components to another. (b) Using degenerate mixture prior avoids these two issues.

entangled prior $p(\boldsymbol{z}_G, \boldsymbol{z}_T) = \mathcal{N}(\boldsymbol{z}_G \mid \boldsymbol{0}, \boldsymbol{I}) \times \mathcal{N}(\boldsymbol{z}_T \mid \boldsymbol{0}, \boldsymbol{I})$ would result in samples with multiple $\boldsymbol{z}_{G_i} \neq \boldsymbol{0}$. Such a sample will activate multiple data generating mechanism sub-modules (e.g. M_{G_4} and M_{G_9} in Figure 2(b)) in parallel. This is at odds with the independent causal mechanisms concept – where we would like a variable to be generated by one mechanisms (potentially with sequential composition) (Parascandolo et al., 2018; Locatello et al., 2018b). (2) It is unclear whether we could disentangle each $\boldsymbol{z}_{G_i}$ and $\boldsymbol{z}_T$ due the well-known identifiability issue (Locatello et al., 2019).

2.2. A Degenerate Mixture Prior

In order to address the issue related to the disentangled prior, it is natural to use a degenerate mixture prior. Then, we can make sure that if we sample from one component, the irrelevant dimensions of the samples are $\boldsymbol{0}$ (i.e., deactivated). Prior work (Khemakhem et al., 2020) which uses a non-degenerate mixture prior assumes that each mixture component of the data distribution is generated by a separate component of the mixture prior. However, the non-degenerate mixture prior has two limitations in modeling disentangled mechanisms: (1) a single latent variable must encode multiple types of variation, violating assumptions of the data generating process, and (2) intervening on the latent variable may move the generated data samples from one mixture component to another.

To see the limitations, consider the running example. Here, assume digits 4 and 9 are generated by a one dimensional latent variable z_G which follows $p(z_G) = \pi_4 p_4(z_G) + \pi_9 p_9(z_G)$. The latent variable z_G has to encode two types of variations for the two digits. If we intervene on z_G to vary the circle size of digit 9, we may push z_G into the mixture component where digit 4 lies, as Figure 3(a) shows.

To address the outlined limitations, we use a degenerate mixture prior :

$$p(i) \propto \text{unif}(0, K_G), \quad p(\boldsymbol{z}_T) \propto \mathcal{N}(\boldsymbol{z}_T \mid \boldsymbol{0}, \boldsymbol{I})$$

$$p(\boldsymbol{z}_G \mid i) \propto \mathcal{N}(\boldsymbol{z}_G \mid \boldsymbol{0}, \text{diag}(\boldsymbol{e}_i)), \quad p(\boldsymbol{z}_G) \propto \sum_{i=1}^{K_G} \frac{1}{K_G} \cdot \mathcal{N}(\boldsymbol{z}_G \mid \boldsymbol{0}, \text{diag}(\boldsymbol{e}_i)) \tag{1}$$

where i is the index of data generating mechanisms, $\boldsymbol{e}_i$ is the i^{th} standard unit vector. We may let each component have a higher-dimensional, non-overlapping support in the implementation to support multiple latent variables for each mechanism. We assume equal prior weights for each mixture component. However, we note that recent work (Ojha et al., 2020) that studies learnable mixture weights in generative models is complementary. Another advantage of the degenerate prior

is that all the samples within the same subspace represent the same type of data. In our running example, no matter how we intervene z_{G_9}, the model will always generate a digit 9 as is shown is Figure 3(b). To eliminate the ambiguity when $z_G \approx 0$, we append a one-hot index i to z_G, following Antoran and Miguel (2019).

Transforming the Model to Independent Causal Mechanisms It is straightforward to connect our generative model and latent variables to the mechanisms, complementing the intuition that the modular model generates data by activating a sequence of sub-modules. Consider a generative model $g : \mathcal{Z} \to \mathcal{X}$, two data generating mechanisms $M_{G_0} : \mathcal{Z}_{G_0} \to \mathcal{X}_{G_0}$, $M_{G_1} : \mathcal{Z}_{G_1} \to \mathcal{X}_{G_1}$ and one data transforming mechanism $M_T : \mathcal{X}_G \times \mathcal{Z}_T \to \mathcal{X}$ where $\mathcal{Z} = [\mathcal{Z}_{G_0}, \mathcal{Z}_{G_1}, \mathcal{Z}_T]$ and $\mathcal{X}_G = \mathcal{X}_{G_0} \cup \mathcal{X}_{G_1}$. We have $g([z_{G_0}, 0, z_T]) = M_T(M_{G_0}(z_{G_0}), z_T)$ and $g([0, z_{G_1}, z_T]) = M_T(M_{G_1}(z_{G_1}), z_T)$. If latent variables z_{G_0}, z_{G_1}, and z_T are disentangled and encode different type of variations, the corresponding mechanisms M_{G_0}, M_{G_1}, and M_T are disentangled as a consequence. We will show methods for enforcing the disentanglement in the following sections.

3. Identifiability Analysis

Now, we have outlined a compact way to model the mechanisms but fitting the model to the data is not equivalent to learning *disentangled* mechanisms. Conventional training approaches (Kingma and Welling, 2013; Higgins et al., 2017) optimize the generative model $g : \mathcal{Z} \to \mathcal{X}$ such that $p_g(\boldsymbol{x}) \approx p_{g^*}(\boldsymbol{x})$, where $p_g(\boldsymbol{x})$ is the marginal distribution of model g, and g^* is the true disentangled model. However, it is not guaranteed that we have $g = g^*$ even if the loss goes to zero (Locatello et al., 2019). Given the ground-truth disentangled model, there exist infinitely many equivalent models, including entangled models, that achieve the same loss (Locatello et al., 2019). For instance, in our running example, the model could let mechanisms M_{G_9} also generate certain digit 4 when entangled, as Figure 2(c) shows, which violates the disentanglement between mechanisms but does not affect the marginal. Other work (Locatello et al., 2019), which studies generative models with an isotropic Gaussian prior, shows that one can construct infinitely many $g^* \circ h$, where $h : \mathcal{Z} \to \mathcal{Z}$, such that $g^* \circ h$ is completely entangled but $p_{g^* \circ h}(\boldsymbol{x}) = p_{g^*}(\boldsymbol{x})$. Following prior work (Locatello et al., 2020; Khemakhem et al., 2020), we first formulate the definition of identifiability.

3.1. Definition of Identifiability

The idealized goal of ensuring that $p_g(\boldsymbol{x}) = p_{g^*}(\boldsymbol{x}) \Rightarrow g = g^*$ is often infeasible. In practice, we are interested in models that are identifiable up to a class of transformation (Locatello et al., 2020; Khemakhem et al., 2020). Thus, we introduce the following definitions:

Definition 1 *We define be an equivalence relation on $g : \mathcal{Z} \to \mathcal{X}$ as follows:*

$$g \sim_h \tilde{g} \Leftrightarrow \exists h : g = \tilde{g} \circ h \tag{2}$$

where $h : \mathcal{Z} \to \mathcal{Z}$ is a smooth invertible function.

Definition 2 *We say that $g : \mathcal{Z} \to \mathcal{X}$ is identifiable up to $\sim_h$ (or h-identifiable) if:*

$$p_g(\boldsymbol{x}) = p_{\tilde{g}}(\boldsymbol{x}) \Rightarrow g \sim_h \tilde{g} \tag{3}$$

Definition 2 clarifies the assumption of a smooth invertible transformation. This assumption is consistent with the prior work (Locatello et al., 2020) and is considered weak. There are many ways to implement a smooth neural network. For a generative model, if the mapping between $\mathcal{Z}$ and $\mathcal{X}$ is injective, that means the generative model fails to induce part of the data distribution. On the other hand, if the mapping is surjective, that means that if we vary z, the generated data x may not change. In both cases, the non-bijective generative model is called collapsed model and is unfavorable (Arjovsky et al., 2017; Yang et al., 2019). To make this assumption more realistic, we will show how to enforce the invertibility in Section 4.

3.2. Identifiability of ICM Model

With Definitions 1 and 2, we use the following lemma to simplify the discussion in our main result in Theorem 4.

Lemma 3 *Let $\mathcal{G}$ be the space of smooth invertible functions with smooth inverse (i.e., a diffeomorphism) (Locatello et al., 2020) that map $\mathcal{Z}$ to $\mathcal{X}$, and $h : \mathcal{Z} \to \mathcal{Z}$ is a smooth invertible function. Then, any function $g \in \mathcal{G}$ can be represented as $g = g^* \circ h$, where $g^* : \mathcal{Z} \to \mathcal{X}$ is the assumed true disentangled generative model in the function space $\mathcal{G}$. Formally, we have $g \sim_h g^*, \forall g \in \mathcal{G}$ and the model g is h-identifiable.*

We could prove this lemma by simply letting $h = (g^*)^{-1} \circ g$. A more detailed version of this proof is in Appendix A.1. This lemma guarantees that by optimizing towards $p_g(\boldsymbol{x}) = p_{g^*}(\boldsymbol{x})$, the learned model g equals to the true g^* up to a smooth invertible transformation h.

Now, we present our ***main identifiability result***. We show that the function h, when paired with our degenerate prior, does not entangle the latent variables of different mechanisms. The latent variables are disentangled in the sense that h has to map each latent variable $\boldsymbol{z}_{G_i}$ and $\boldsymbol{z}_T$ to disjoint subspaces. For example, the function h can not map $\boldsymbol{z}_{G_9}$ to the subspace where $\boldsymbol{z}_{G_4}$ lies in or map $\boldsymbol{z}_T$ to the subspace where $\boldsymbol{z}_{G_9}$ lies in. As such, in our running example, the model can not generate a digit 4 by manipulating $\boldsymbol{z}_{G_9}$.

As all the smooth invertible generative models are h-identifiable, we only need to consider how the function h entangles the latent variables $\boldsymbol{z}$ before the true generative model. Note that we do not assume h is always $(g^*)^{-1} \circ g$. The main idea is: with a degenerate mixture prior, if h maps one latent variable to the two or more different subspaces, then the result has measure zero, or, if we transform back to the original space using h^{-1}, the result has measure zero, which violates the definition of h.

Theorem 4 *Let $i \in \{1, 2, ..., K_G\}$ be the index of data generating mechanisms. We assume each $\boldsymbol{z}_{G_i} \in \mathcal{Z}_{G_i}$, $\boldsymbol{z}_T \in \mathcal{Z}_T$, and $\boldsymbol{z} \in \mathcal{Z} = \mathcal{Z}_{G_0} \times \mathcal{Z}_{G_1} \times ... \times \mathcal{Z}_T$. We let $\hat{\boldsymbol{z}} = h(\boldsymbol{z})$, $\hat{\boldsymbol{z}} \in \hat{\mathcal{Z}}$, and $g^* : \mathcal{Z} \to \mathcal{X}$ be the true disentangled model. Then, if there exists a smooth invertible function $h : \mathcal{Z} \to \mathcal{Z}$ such that $g = g^* \circ h$ maps $\mathcal{Z}$ to $\mathcal{X}$, then h maps each $\mathcal{Z}_{G_i}$ to $\hat{\mathcal{Z}}_{G_i}$, disjoint from $\hat{\mathcal{Z}}_{G_j}, \forall j \neq i$, as well as $\hat{\mathcal{Z}}_T$, and maps $\mathcal{Z}_T$ to $\hat{\mathcal{Z}}_T$, which is disjoint from $\hat{\mathcal{Z}}_{G_i}, \forall i \in \{1, ..., K_G\}$.*

The proof of Theorem 4 is in Appendix A.2. We now discuss the remaining two types of transformations of h. First, we cannot (and do not need to) guarantee the i^{th} learned subspace $\hat{\mathcal{Z}}_{G_i}$ corresponds to the i^{th} true subspace $\mathcal{Z}_{G_i}$ because the disentanglement between latent variables will not be affected. Therefore, the learned latent variables $\hat{\boldsymbol{z}}_G$ may be subspace-wise permutation of the true latent variables $\boldsymbol{z}_G$. Second, the function h may still entangle the latent variables of the same

mechanism, which is the case for an intra-subspace smooth invertible transformation. Although the disentanglement has a coarse granularity, we will empirically show that we can still benefit from the coarse-grained disentanglement.

3.3. Comparison to Other Identifiability Results

Identifiable VAE Previous work (Khemakhem et al., 2020) combines non-linear independent component analysis (ICA) and variational autoencoder (VAE) for identifiability by leveraging the invertibility of the sufficient statistics parameter matrix. The latent variables are conditioned on a label in their setting: the class label, the environment label, or others. Besides the label requirement, the invertibility prevents the mechanisms from sharing or duplicating the latent variables because the matrix, of which each column is the parameters for a label, will be low-rank. Consequently, this method is not applicable when there are additional data transforming mechanisms.

Weakly-supervised Disentanglement Ada-GVAE (Locatello et al., 2020) achieves identifiability by introducing pair observations that share the same value on at least one latent variable. However, even in a simple dataset like MNIST, this assumption may not hold because two digits may differ w.r.t. each latent variable such as stroke-thickness, width, or brightness. Other work (Shu et al., 2019) adopts a weaker assumption by introducing rank pairing. However, this method requires additional supervision and certain latent variables (e.g., style) are hard to compare or rank.

4. Proposed Model Architecture and Self-supervised Training Method

In practice, we need to enforce the generative model g to be smooth invertible with smooth inverse. As the neural network is commonly assumed as smooth (Xie et al., 2020; Liang et al., 2021), this section shows how to enforce the invertibility assumption. For an invertible generative model, we have $\boldsymbol{z} = g^{-1}(g(\boldsymbol{z}))$. If we can find g^{-1} such that $\boldsymbol{z} = g^{-1}(g(\boldsymbol{z}))$ holds, then the generative model g is invertible.

Figure 4: Model Architecture

To do so, we first design a new model architecture. Technically, we compose a generator network $G : \mathcal{Z} \to \mathcal{X}$, a discriminator network $D : \mathcal{X} \to \mathcal{Y}$, and an auxiliary encoder network $E : \mathcal{X} \to \mathcal{Z}$. We append the encoder to the generator's output and connect the encoder back to the generator's input as Figure 4 shows. Specifically, our generator network and discriminator networks are from the Wasserstein GAN (Arjovsky et al., 2017; Gulrajani et al., 2017). Our auxiliary encoder is a deterministic encoder that approximates g^{-1}.

We use self-supervised training to jointly train the generator and the encoder. The self-supervision involves predicting the latent variables that generate the data samples using the auxiliary encoder network E. The loss function is:

$$
\begin{aligned}
\mathcal{L} = W(\mathbb{P}_g||\mathbb{P}_r) &+ \lambda_G \mathbb{E}_{\boldsymbol{z} \sim p(\boldsymbol{z})} ||\boldsymbol{z}_G - E(G(\boldsymbol{z}))_G||_2^2 + \lambda_T \mathbb{E}_{\boldsymbol{z} \sim p(\boldsymbol{z})} ||\boldsymbol{z}_T - E(G(\boldsymbol{z}))_T||_2^2 \\
&+ \lambda_C \mathbb{E}_{\boldsymbol{z} \sim P(\boldsymbol{z})} \mathcal{H}(\boldsymbol{z}_C, E(G(\boldsymbol{z}))_C) + \lambda_R \mathbb{E}_{\boldsymbol{x} \sim p(\boldsymbol{x})} ||\boldsymbol{x} - G(E(\boldsymbol{x}))||_2^2
\end{aligned}
\tag{4}
$$

where $\mathbb{P}_g$ denotes the distribution induced by the generator network G, $\mathbb{P}_r$ denotes the real data distribution, $W(\mathbb{P}_g||\mathbb{P}_r)$ denotes the Wasserstein distance (Arjovsky et al., 2017) between two distributions, $\boldsymbol{z} = [\boldsymbol{z}_C, \boldsymbol{z}_G, \boldsymbol{z}_T]$, $\boldsymbol{z}_C$ is a categorical variable representing the index of the data generating

mechanisms and its value is determined by z_G, z_G and z_T are the same as is defined in Section 2, and $\mathcal{H}$ denotes the cross-entropy loss.

The loss function above can be decomposed into four parts: 1) $W(\mathbb{P}_g||\mathbb{P}_r)$ is the WGAN loss (Gulrajani et al., 2017). 2) $\mathbb{E}_{z \sim p(z)}||z_G - E(G(z))_G||_2^2 + \mathbb{E}_{z \sim p(z)}||z_T - E(G(z))_T||_2^2$ is the self-supervision loss for invertability. 3) $\mathbb{E}_{z \sim P(z)}\mathcal{H}(z_C, E(G(z))_C)$ is the auxiliary self-supervision loss that encourages the data generated by different mechanisms to be different and separable. 4) $\mathbb{E}_{x \sim p(x)}||x - G(E(x))||_2^2$ is the cycle-consistent loss, so $x \approx G(E(x))$. The encoder takes data from the generator as input. However, the generated data distribution may differ from the real data distribution. Thus, certain data in the real distribution may become out-of-distribution (OOD) for the encoder. Such distribution divergence hurts the performance of downstream tasks. The cycle consistency mitigates the distribution divergence by encouraging the ICM model to capture the whole real data distribution. While the usage of cycle-consistency has a long history in image-to-image translation (Zhu et al., 2017), visual-tracking (Sundaram et al., 2010), and other areas, the loss in our method is developed from a different motivation and serves a different purpose.

Model Architecture Comparison Similar model architectures have been explored by previous works (Larsen et al., 2016; Bao et al., 2017), which append a discriminator to a VAE model. The issue of the VAE-based model is that the inferred prior could drift away from the true prior (Kumar et al., 2017). Such drift breaks our identifiability result, where the prior has a specific form. Prior work (Kumar et al., 2017) adds the distance between the inferred prior and the true prior as a regularizer to the loss function. However, the regularizer only approximates the true distance because the exact computation is intractable. As such, it is unclear whether the true distance decreases to zero. In contrast, our design allows the generator to directly sample from the true prior distribution.

5. Related Work

Independent Component Analysis (ICA) Khemakhem et al. (2020) bridge the gap between the non-linear ICA and generative models. The non-linear ICA-based approach can identify the true distribution over observed and latent variables up to a linear transformation. However, the strong theoretical guarantee comes with strong assumptions as is discussed in Section 3.3.

Disentangled Representations Disentangled representations (Higgins et al., 2017; Shu et al., 2019; Locatello et al., 2020) assume that the data is generated by a single data generating mechanism using a set of independent latent explanatory factors (Bengio et al., 2013). In terms of modeling, we assume each mixture component in the data distribution could have their private factors and all the mixture component share a set of shared factors. In terms of disentanglement, we only require the latent explanatory factors associated with different mechanisms to be disentangled, while the factors associated with the same mechanisms could be entangled. Although our disentanglement has a coarse granularity compared to previous results, our disentangled model is provably identifiable without manual labeling, whereas their results need at least weak-supervision. We will also show in the experiment that our coarse-grained identifiability is useful.

6. Experiments

This section first shows a visualization of the identifiability on synthetic data where the ground-truth latent variable is available. Then, we evaluate our method both qualitatively and quantitatively. Qualitatively, we conduct latent space traversal. Quantitatively, we develop a method to evaluate the disentanglement by measuring the accuracy of downstream classifiers under environment shifts,

Figure 5: The true distribution and the estimated distribution from our ICM model and VAE. (a)-(c) plot z_0 and z_1 that should jointly follow a degenerate mixture distribution, (d)-(e) plot z_2 that should follow a Gaussian distribution. y is the label. Our ICM model closely approximates the true distribution while VAE fails to recover z_0 and z_1.

similar to existing works (Locatello et al., 2020). An additional ablation study is in Appendix C.1, showing the benefit of using a degenerate mixture prior over using a non-degenerate mixture prior. The downstream classifiers predict the label of data samples. If the latent variables are better disentangled, the environment shift impacts the downstream classifier less. We briefly introduce the baselines and data setup and detail the setting in Appendix B.

Baseline Setup Existing competitive training-based methods (Parascandolo et al., 2018) for learning independent causal mechanisms do not apply to our dataset because the auxiliary dataset is unavailable, as discussed in Section 1. For the other competitive training-based methods (Locatello et al., 2018b), we have seen that the mechanisms are easily entangled (as shown in Figure 1(b)). Hence, we select models that focus on disentangled representations, VAE, β-VAE, and AdaGVAE, as our baselines.

Data Setup We generate synthetic data by changing the height, width and brightness of digits from MNIST dataset. For the quantitative evaluation, we use the encoder network E to predict latent variables and feed to prediction to downstream ML models. For experiments, we use 1) three datasets, which are MNIST (MN) (LeCun et al., 1998), FashionMNIST (FMN) (Xiao et al., 2017), and Sprites (SP)[12] (Li and Mandt, 2018). Sprites dataset contains animated characters. We select character action and color as the types of variations. 2) five environment shifts, all of which already exist in the data.

6.1. Simulation on Synthetic Data

We define three latent variables: z_0 (height), z_1 (width), and z_2 (brightness). The variables z_0 and z_1 jointly follow a degenerated mixture distribution, and z_3 follows a conventional Gaussian

---

1. https://lpc.opengameart.org
2. https://github.com/jrconway3/Universal-LPC-spritesheet

(a) Data Generating Mechanisms Subspaces, Distinct Variation for Each Subspace/Row

(b) Data Transforming Mechanism Subspace, z_{T_0}, Width and Rotation

(c) Data Transforming Mechanism Subspace, z_{T_1}, Stroke Thickness and Width

Figure 6: Latent Space Traversal of ICM Model on MNIST

(a) Entangled Digit Label, Style, and Azimuth Variation

(b) Entangled Color and Action Variation

Figure 7: Latent Space Traversal of β-VAE Model on MNIST and Sprites

distribution. We then sample two images from the MNIST dataset, which are labeled as $y = 0$ and $y = 1$, respectively. The synthetic dataset is generated by varying the height of the first image, the width of the second image, and the brightness of both images. We fit our ICM model, with enforcing invertibility, and a VAE model, without enforcing invertibility, to the synthetic dataset. Figure 5 shows the estimated distributions of the degenerated mixture part and the Gaussian part. Our ICM model closely approximates the true distribution while the VAE model fails to preserve the degeneracy of the distribution.

6.2. Qualitative Evaluation

We show the latent space traversal of ICM model on MNIST dataset in Figure 6. The visualization result illustrates the disentanglement as the traversal of each subspace shows a different type of variation. Furthermore, we show that each data generating mechanism's traversal yields a distinct, mechanism-specific type of variation. The traversal of the data transforming mechanism produces the same type of variation. We show the traversal of β-VAE in Figure 7 as a comparison. Due to the limited space, we report more visualization on MNIST, FashionMNIST and Sprites dataset in Appendix C.2. The visualization also shows that our ICM model is robust to interventions (Suter et al., 2019) in the sense that no matter how we change z_{G_i} and z_T while keeping z_C and $z_{\backslash G_i}$ fixed, the generator does not generate data that does not belong to mechanism G_i (e.g., digit 4 does not change to digit 9 during the traversal).

We note that the number of data generating mechanisms is chosen to be larger than the number of classes (e.g. 15 mechanisms for 10 classes in MNIST), which means one true mechanism could be split into two estimated mechanisms. This setting is consistent with previous works (Parascandolo et al., 2018; Locatello et al., 2018b). Appendix B proposes a procedure for choosing the number of mechanisms.

6.3. Quantitative Evaluation

To quantitatively measure the accuracy of downstream ML models under environment shift, we first partition the dataset using the learned latent variables, from a pre-trained ICM model, as the conditions that are shifted by the environment. The shifted conditions include stroke thickness (T), width and rotation (W&R), rotation (R), darkness and width (D&W), and color. Figure 10 in the Appendix further visualizes these conditions and shows that the conditions are disentangled from other latent variables. Then, we partition the MNIST and FashionMNIST dataset into subsets $\{x \mid x \in \mathcal{X}, \hat{z}_i = E(x)_i \in [C_{lower}, C_{upper})\}$ using the predicted value of the condition, which is in the i^{th} dimension if $\hat{z}$. For the train set, we set $[C_{lower}, C_{upper})$ to $[0, \infty)$. For each test set, we set $[C_{lower}, C_{upper})$ to $[-0.1, 0), [-0.2, -0.1), ..., [-3.0, -2.9)$. We use the $C_{lower}^{train} - C_{upper}^{test}$ to represent the *shift distance*. For the Sprites dataset, the train set has randomly colored images and the test set has images with only red and green components in the RGB color space, similar to prior works that also consider color shift Locatello et al. (2020); Dittadi et al. (2021).

Next, we train the ICM model and other competitors on the MNIST and FashionMNIST train set and Sprites train and test set. Appendix B discusses the training setting on Sprites. Then, we use gradient boosted decision trees (GBT) from the Scikit-learn library (Pedregosa et al., 2011) with default parameters as the downstream ML model, which is the same as previous works (Locatello et al., 2019, 2020). We train the GBT with 1000 train samples (MN, FMN) or 50 train samples (Sprites), which is sufficient for GBT to produce decent accuracy, and test the GBT accuracy on a sequence of test sets. The test repeats ten times on each test set. Table 1 shows the average accuracy and accuracy variations. Our ICM model *achieves the best average accuracy* across all the experiments except for MNIST (R). Due to the limited space, we analyze the experiments on the MNIST (R) dataset in the Appendix C.3.

Table 1: Average Accuracy of Downstream Classifiers under Different Shift Strength

MODEL	MN (T)	MN (W&R)	MN (R)	FMN (D&W)	SPRITES	AVERAGE
ICM	**74.63%** 2.43%	**56.91%** 3.70%	43.71% 7.10%	**46.61%** 5.24%	**99.25%** 1.79%	**64.22%**
VAE	55.91% 4.32%	41.92% 6.30%	39.90% 7.33%	37.08% 9.02%	92.99% 4.89%	53.56%
β-VAE	73.34% 2.71%	46.33% 4.98%	46.05% 7.80%	41.60% 7.83%	98.75% 2.68%	61.21%
ADA	68.09% 2.96%	47.16% 4.90%	**47.58%** 7.31%	40.85% 7.98%	98.75% 3.11%	60.49%

* Letters in parenthesis are abbreviations of the conditions shift across environments.
  The small numbers represent accuracy variations.

7. Conclusion and Future Work

This paper presents a generative model with a degenerate prior, called the ICM model, to learn a broad range of practical mechanisms that generate and transform data. We analyze conditions under which the disentangled ICM model is identifiable. To enforce the identifiability conditions, we develop a model architecture and a self-supervised training method for the ICM model. Empirical results show that the ICM model achieves better disentanglement and improves the accuracy of downstream prediction ML models under environment shifts.

A straightforward extension of this work is to consider a class of systems where the observational data is generated by a sequential composition of data generating mechanisms, or the data generating mechanisms may share some latent variables.

References

Javier Antoran and Antonio Miguel. Disentangling and learning robust representations with natural clustering. In *2019 18th IEEE International Conference On Machine Learning And Applications (ICMLA)*, pages 694–699. IEEE, 2019.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan. *arXiv preprint arXiv:1701.07875*, 2017.

Jianmin Bao, Dong Chen, Fang Wen, Houqiang Li, and Gang Hua. Cvae-gan: fine-grained image generation through asymmetric training. In *Proceedings of the IEEE international conference on computer vision*, pages 2745–2754, 2017.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

Andrea Dittadi, Frederik Träuble, Francesco Locatello, Manuel Wuthrich, Vaibhav Agrawal, Ole Winther, Stefan Bauer, and Bernhard Schölkopf. On the transfer of disentangled representations in realistic settings. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=8VXvj1QNRl1.

Ishaan Gulrajani and David Lopez-Paz. In search of lost domain generalization. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=lQdXeXDoWtI.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In *Advances in neural information processing systems*, pages 5767–5777, 2017.

I. Higgins, Loïc Matthey, A. Pal, C. Burgess, Xavier Glorot, M. Botvinick, S. Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, 2017.

Ilyes Khemakhem, Diederik Kingma, Ricardo Monti, and Aapo Hyvarinen. Variational autoencoders and nonlinear ica: A unifying framework. In *International Conference on Artificial Intelligence and Statistics*, pages 2207–2217, 2020.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanas Phillips, Irena Gao, et al. Wilds: A benchmark of in-the-wild distribution shifts. *arXiv preprint arXiv:2012.07421*, 2020.

Abhishek Kumar, Prasanna Sattigeri, and Avinash Balakrishnan. Variational inference of disentangled latent concepts from unlabeled observations. *arXiv preprint arXiv:1711.00848*, 2017.

Anders Boesen Lindbo Larsen, Søren Kaae Sønderby, Hugo Larochelle, and Ole Winther. Autoencoding beyond pixels using a learned similarity metric. In *International conference on machine learning*, pages 1558–1566. PMLR, 2016.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Yingzhen Li and Stephan Mandt. Disentangled sequential autoencoder. In *International Conference on Machine Learning*, 2018.

Kaizhao Liang, Jacky Y Zhang, Boxin Wang, Zhuolin Yang, Sanmi Koyejo, and Bo Li. Uncovering the connections between adversarial transferability and knowledge transferability. In *Proceedings of the 38th International Conference on Machine Learning*. PMLR, 2021.

Francesco Locatello, Damien Vincent, Ilya Tolstikhin, Gunnar Ratsch, Sylvain Gelly, and Bernhard Scholkopf. Clustering meets implicit generative models. 2018a.

Francesco Locatello, Damien Vincent, Ilya Tolstikhin, Gunnar Rätsch, Sylvain Gelly, and Bernhard Schölkopf. Competitive training of mixtures of independent deep generative models. *arXiv preprint arXiv:1804.11130*, 2018b.

Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Raetsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *International Conference on Machine Learning*, pages 4114–4124, 2019.

Francesco Locatello, Ben Poole, Gunnar Rätsch, Bernhard Schölkopf, Olivier Bachem, and Michael Tschannen. Weakly-supervised disentanglement without compromises. *International Conference on Machine Learning*, 2020.

Utkarsh Ojha, Krishna Kumar Singh, Cho-Jui Hsieh, and Yong Jae Lee. Elastic-infogan: Unsupervised disentangled representation learning in class-imbalanced data. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 18063–18075. Curran Associates, Inc., 2020.

Giambattista Parascandolo, Niki Kilbertus, Mateo Rojas-Carulla, and Bernhard Schölkopf. Learning independent causal mechanisms. In *International Conference on Machine Learning*, pages 4036–4044. PMLR, 2018.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of causal inference*. The MIT Press, 2017.

Bernhard Schölkopf. Causality for machine learning. *arXiv preprint arXiv:1911.10500*, 2019.

Bernhard Schölkopf, Dominik Janzing, Jonas Peters, Eleni Sgouritsa, Kun Zhang, and Joris Mooij. On causal and anticausal learning. In *Proceedings of the 29th International Coference on International Conference on Machine Learning*, ICML'12, page 459–466, Madison, WI, USA, 2012. Omnipress. ISBN 9781450312851.

Rui Shu, Yining Chen, Abhishek Kumar, Stefano Ermon, and Ben Poole. Weakly supervised disentanglement with guarantees. *arXiv preprint arXiv:1910.09772*, 2019.

Narayanan Sundaram, Thomas Brox, and Kurt Keutzer. Dense point trajectories by gpu-accelerated large displacement optical flow. In *European conference on computer vision*, pages 438–451. Springer, 2010.

Raphael Suter, Djordje Miladinovic, Bernhard Schölkopf, and Stefan Bauer. Robustly disentangled causal mechanisms: Validating deep representations for interventional robustness. In *International Conference on Machine Learning*, pages 6056–6065. PMLR, 2019.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017.

Cong Xie, Shuai Zheng, Oluwasanmi O Koyejo, Indranil Gupta, Mu Li, and Haibin Lin. Cser: Communication-efficient sgd with error reset. *Advances in Neural Information Processing Systems*, 33, 2020.

Dingdong Yang, Seunghoon Hong, Yunseok Jang, Tianchen Zhao, and Honglak Lee. Diversity-sensitive conditional generative adversarial networks. *arXiv preprint arXiv:1901.09024*, 2019.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *Proceedings of the IEEE international conference on computer vision*, pages 2223–2232, 2017.