DISENTANGLING LEARNING REPRESENTATIONS WITH DENSITY ESTIMATION

ABSTRACT

Disentangled learning representations have promising utility in many applications, but they currently suffer from serious reliability issues. We present Gaussian Channel Autoencoder (GCAE), a method which achieves reliable disentanglement via scalable non-parametric density estimation of the latent space. GCAE avoids the curse of dimensionality of density estimation by disentangling subsets of its latent space with the Dual Total Correlation (DTC) metric, thereby representing its high-dimensional latent joint distribution as a collection of many low-dimensional conditional distributions. In our experiments, GCAE achieves highly competitive and reliable disentanglement scores compared with state-of-the-art baselines.

1 INTRODUCTION

The notion of disentangled learning representations was introduced by Bengio et al. (2013) - it is meant to be a robust approach to feature learning when trying to learn more about a distribution of data X or when downstream tasks for learned features are unknown. Since then, disentangled learning representations have been proven to be extremely useful in the applications of natural language processing Jain et al. (2018), content and style separation John et al. (2018), drug discovery Polykovskiy et al. (2018); Du et al. (2020), fairness Sarhan et al. (2020), and more.

Density estimation of learned representations is an important ingredient to competitive disentanglement methods. Bengio et al. (2013) state that representations $\mathbf{z} \sim Z$ which are disentangled should maintain as much information of the input as possible while having components which are mutually *invariant* to one another. Mutual invariance motivates seeking representations of Z which have *independent* components extracted from the data, necessitating some notion of $p_Z(\mathbf{z})$.

Leading unsupervised disentanglement methods, namely β-VAE Higgins et al. (2016), FactorVAE Kim & Mnih (2018), and β-TCVAE Chen et al. (2018) all learn $p_Z(\mathbf{z})$ via the same variational Bayesian framework Kingma & Welling (2013), but they approach making $p_Z(\mathbf{z})$ independent with different angles. β-VAE indirectly promotes independence in $p_Z(\mathbf{z})$ via enforcing low D_{KL} between the representation and a factorized Gaussian prior, β-TCVAE encourages representations to have low Total Correlation (TC) via an ELBO decomposition and importance weighted sampling technique, and FactorVAE reduces TC with help from a monolithic neural network estimate. Other well-known unsupervised methods are Annealed β-VAE Burgess et al. (2018), which imposes careful relaxation of the information bottleneck through the VAE D_{KL} term during training, and DIP-VAE I & II Kumar et al. (2017), which directly regularize the covariance of the learned representation. For a more in-depth description of related work, please see appendix D.

While these VAE-based disentanglement methods have been the most successful in the field, Locatello et al. (2019) point out serious reliability issues shared by all. In particular, increasing disentanglement pressure during training doesn't tend to lead to more independent representations, there currently aren't good unsupervised indicators of disentanglement, and no method consistently dominates the others across all datasets. Locatello et al. (2019) stress the need to find the right inductive biases in order for unsupervised disentanglement to truly deliver.

We seek to make disentanglement more reliable and high-performing by incorporating new inductive biases into our proposed method, Gaussian Channel Autoencoder (GCAE). We shall explain them in more detail in the following sections, but to summarize: GCAE avoids the challenge of representing high-dimensional $p_Z(\mathbf{z})$ via disentanglement with Dual Total Correlation (rather than TC) and the

DTC criterion is augmented with a scale-dependent latent variable arbitration mechanism. This work makes the following contributions:

- Analysis of the TC and DTC metrics with regard to the curse of dimensionality which motivates use of DTC and a new feature-stabilizing arbitration mechanism
- GCAE, a new form of noisy autoencoder (AE) inspired by the Gaussian Channel problem, which permits application of non-parametric density estimation methods in the latent space
- Experiments which demonstrate competitive performance of GCAE against leading disentanglement baselines on multiple datasets using existing metrics

2 BACKGROUND AND INITIAL FINDINGS

To estimate $p_Z(\mathbf{z})$, we introduce a discriminator-based method which applies the density-ratio trick and the Radon-Nikodym theorem to estimate density of samples from an unknown distribution. We shall demonstrate in this section the curse of dimensionality in density estimation and the necessity for representing $p_Z(\mathbf{z})$ as a collection of conditional distributions.

The optimal discriminator neural network introduced by Goodfellow et al. (2014a) satisfies:

$$\arg\max_D \mathbb{E}_{\mathbf{x}_r \sim X_{real}} \left[\log D(\mathbf{x}) \right] + \mathbb{E}_{\mathbf{x}_f \sim X_{fake}} \left[\log \left(1 - D(\mathbf{x}_f) \right) \right] \triangleq D^*(\mathbf{x}) = \frac{p_{real}(\mathbf{x})}{p_{real}(\mathbf{x}) + p_{fake}(\mathbf{x})}$$

where $D(\mathbf{x})$ is a discriminator network trained to differentiate between "real" samples $\mathbf{x}_r$ and "fake" samples $\mathbf{x}_f$. Given the optimal discriminator $D^*(\mathbf{x})$, the density-ratio trick can be applied to yield $\frac{p_{real}(\mathbf{x})}{p_{fake}(\mathbf{x})} = \frac{D^*(\mathbf{x})}{1-D^*(\mathbf{x})}$. Furthermore, the discriminator can be supplied conditioning variables to represent a ratio of conditional distributions Goodfellow et al. (2014b); Makhzani et al. (2015).

Consider the case where the "real" samples come from an *unknown* distribution $\mathbf{z} \sim Z$ and the "fake" samples come from a *known* distribution $\mathbf{u} \sim U$. Permitted that both $p_Z(\mathbf{z})$ and $p_U(\mathbf{u})$ are finite and $p_U(\mathbf{u})$ is nonzero on the sample space of $p_Z(\mathbf{z})$, the optimal discriminator can be used to retrieve the unknown density $p_Z(\mathbf{z}) = \frac{D^*(\mathbf{z})}{1-D^*(\mathbf{z})} p_U(\mathbf{z})$. In the special case where $\mathbf{u}$ is a uniformly distributed variable, this "transfer" of density through the optimal discriminator can be seen as an application of the Radon-Nikodym derivative of $\mathbf{z}$ with reference to the Lebesgue measure. Throughout the rest of this work, we employ discriminators with uniform noise and the density-ratio trick in this way to recover unknown distributions.

(a) Joint distributions (b) Conditional distributions

Figure 1: KL Divergence between the true and estimated distributions as training iteration and distribution dimensionality increase. Training parameters are kept the same between both experiments.

This technique can be employed to recover the probability density of an m-dimensional isotropic Gaussian distribution. While it works well in low dimensions ($m \leq 8$), the method inevitably fails

as m increases. Figure 1a depicts several experiments of increasing m in which the KL-divergence of the true and estimated distributions are plotted with training iteration. When number of data samples is finite and the dimension m exceeds a certain threshold, the probability of there being any uniform samples in the neighborhood of the Gaussian samples swiftly approaches zero, causing the density-ratio trick to fail.

This is a well-known phenomenon called the *curse of dimensionality* of non-parametric density estimation. In essence, as the dimensionality of a joint distribution increases, concentrated joint data quickly become isolated within an extremely large space. The limit $m \leq 8$ is consistent with the limits of other methods such as kernel density estimation (Parzen-Rosenblatt window).

Fortunately, the same limitation does not apply to conditional distributions of many jointly distributed variables. Figure 1b depicts a similar experiment of the first in which $m - 1$ variables are independent Gaussian distributed, but the last variable $\mathbf{z}_m$ follows the distribution $\mathbf{z}_m \sim \mathcal{N}(\mu = (m-1)^{-\frac{1}{2}} \sum_{i=1}^{m-1} \mathbf{z}_i, \ \sigma^2 = \frac{1}{m})$ (i.e., the last variable is Gaussian distributed with its mean as the sum of observations of the other variables). The marginal distribution of each component is Gaussian, just like the previous example. While it takes more training iterations to bring the KL-divergence between the true and estimated conditional distribution to zero, it is not limited by the curse of dimensionality. Hence, we assert that conditional distributions can be used to capture complex relationships between subsets of many jointly distributed variables while avoiding the curse of dimensionality.

3 METHODOLOGY

ANALYSIS OF DUAL TOTAL CORRELATION

Recent works encourage disentanglement of the latent space by enhancing the Total Correlation (TC) either indirectly Higgins et al. (2016); Kumar et al. (2017) or explicitly Kim & Mnih (2018); Chen et al. (2018). TC is a metric of multivariate statistical independence that is strictly non-negative and zero if and only if all elements of $\mathbf{z}$ are independent.

$$\text{TC}(Z) = \mathbb{E}_{\mathbf{z}} \log \frac{p_Z(\mathbf{z})}{\prod_i p_{Z_i}(\mathbf{z}_i)} = \sum_i h(Z_i) - h(Z)$$

Locatello et al. (2019) evaluate many TC-based methods and conclude that minimizing their measures of TC during training often does not lead to VAE μ (used for representation) with low TC. We note that computing $\text{TC}(Z)$ requires knowledge of the joint distribution $p_Z(\mathbf{z})$, which can be very challenging to model in high dimensions. We hypothesize that the need for a model of $p_Z(\mathbf{z})$ is what leads to the observed reliability issues of these TC-based methods.

Consider another metric for multivariate statistical independence, Dual Total Correlation (DTC). Like TC, DTC is strictly non-negative and zero if and only if all elements of $\mathbf{z}$ are independent.

$$\text{DTC}(\mathbf{z}) = \mathbb{E}_{\mathbf{z}} \log \frac{\prod_i p_{Z_i}(\mathbf{z}_i | \mathbf{z}_{\setminus i})}{p_Z(\mathbf{z})} = h(Z) - \sum_i h(Z_i | Z_{\setminus i})$$

We use $\mathbf{z}_{\setminus i}$ to denote all elements of $\mathbf{z}$ except i. At face value, it appears that $\text{DTC}(\mathbf{z})$ also requires knowledge of the joint density $p(\mathbf{z})$. However, observe an equivalent form of DTC manipulated for the i-th variable:

$$\text{DTC}(Z) = \text{DTC}_i(Z) \triangleq h(Z) - h(Z_i | Z_{\setminus i}) - \sum_{j \neq i} h(Z_j | Z_{\setminus j}) = h(Z_{\setminus i}) - \sum_{j \neq i} h(Z_j | Z_{\setminus j}). \quad (1)$$

Here, the i-th variable only contributes to DTC through each set of conditioning variables $\mathbf{z}_{\setminus j}$. Hence, when computing the derivative $\frac{\partial \text{DTC}_i(Z)}{\partial \mathbf{z}_i}$, no representation of $p_Z(\mathbf{z})$ is required - only the conditional entropies $h(Z_j | Z_{\setminus j})$ are necessary. Hence, we observe that the curse of dimensionality

can be avoided through gradient descent on the DTC metric, making it more attractive for disentanglement. However, while one only needs the conditional entropies to compute gradient for DTC, the conditional entropies alone don't tell one how close $\mathbf{z}$ is to having independent elements. To overcome this, we define the summed information loss $\mathcal{L}_{\Sigma I}$:

$$\mathcal{L}_{\Sigma I} \triangleq \sum_i I(Z_i; Z_{\setminus i}) = \left[\sum_i h(Z_i) - h(Z_i | Z_{\setminus i}) \right] + h(Z) - h(Z) = \text{TC}(Z) + \text{DTC}(Z). \quad (2)$$

If gradients of each $I(Z_i; Z_{\setminus i})$ are taken only with respect to $\mathbf{z}_{\setminus i}$, then the gradients are equal to $\frac{\partial \text{DTC}(Z)}{\partial \mathbf{z}}$, avoiding use of any derivatives of estimates of $p_Z(\mathbf{z})$. Furthermore, minimizing one metric is equivalent to minimizing the other: $\text{DTC}(Z) = 0 \Leftrightarrow \text{TC}(Z) = 0 \Leftrightarrow \mathcal{L}_{\Sigma I} = 0$. In our experiments, we estimate $h(Z_i)$ with batch estimates $\mathbb{E}_{\mathbf{z}_{\setminus i}} p_{Z_i}(\mathbf{z}_i | \mathbf{z}_{\setminus i})$, requiring no further hyperparameters. Details on how we implement the information functional are available in appendix A.1.

EXCESS ENTROPY POWER LOSS

We found it very helpful to "stabilize" disentangled features by attaching a feature-scale dependent term to each $I(Z_i; Z_{\setminus i})$. The entropy power of a latent variable $\mathbf{z}_i$ is strictly positive and grows analogously with the variance of $\mathbf{z}_i$. Hence, we define the Excess Entropy Power loss:

$$\mathcal{L}_{\text{EEP}}(\mathbf{z}) \triangleq \frac{1}{2\pi e} \sum_i \left[I(Z_i; Z_{\setminus i}) \cdot e^{2h(Z_i)} \right], \quad (3)$$

which weighs each component of the $\mathcal{L}_{\Sigma I}$ loss with the marginal entropy power of each i-th latent variable. While $\mathcal{L}_{\text{EEP}}$ has biased gradient with respect to descending $\mathcal{L}_{\Sigma I}$, this inductive bias has been extremely helpful in consistently yielding high disentanglement scores. Partial derivatives are taken with respect to the $\mathbf{z}_{\setminus i}$ subset only, so the marginal entropy power only weighs each component. An ablation study with $\mathcal{L}_{\text{EEP}}$ can be found in appendix C. The name "Excess Entropy Power" is inspired by DTC's alternative name, excess entropy.

GAUSSIAN CHANNEL AUTOENCODER

Figure 2: Depiction of the proposed method, GCAE. Gaussian noise with variance σ^2 is added to the latent space, smoothing the representations for gradient-based disentanglement with $\mathcal{L}_{\text{EEP}}$. Discriminators use the density-ratio trick to represent the conditional distributions of each latent element given observations of all other elements, capturing complex dependencies between subsets of the variables whilst avoiding the curse of dimensionality.

We begin with a Gaussian Channel Autoencoder (GCAE), composed of a coupled encoder $\phi : X \to Z_\phi$ and decoder $\psi : Z \to \hat{X}$, to extract a compressed, noise-resistant representation of the data $X \in$

$\mathbb{R}^n$ in the GCAE latent space $\mathbf{z} \in \mathbb{R}^m$. We assume $m \ll n$, as is typical with autoencoder models. The output of the encoder has a scaled softsign activation function, restricting $\mathbf{z}_\phi \in (-3, 3)^m$. The latent space is subjected to Gaussian noise of the form $\mathbf{z} = \mathbf{z}_\phi + \nu_\sigma$, where each $\nu_\sigma \sim \mathcal{N}(0, \sigma^2 I)$ and σ is a controllable hyperparameter. The Gaussian noise has the effect of "smoothing" the latent space, ensuring that $p_Z(\mathbf{z})$ is continuous and finite with respect to the uniform density (Lebesgue measure). This guarantees the existence of the Radon-Nikodym derivative with reference to uniform samples $\mathbf{u} \sim \text{Unif}(-4, 4)$, forming the backbone of our disentanglement method.

The loss function for training GCAE is:

$$\mathcal{L}_{\text{GCAE}} = \mathbb{E}_{\mathbf{x}, \nu_\sigma} \left[\frac{1}{n} \|\hat{\mathbf{x}} - \mathbf{x}\|_2^2 + \lambda \, \mathcal{L}_{\text{EEP}}(\mathbf{z}) \right], \tag{4}$$

where λ is a hyperparameter to control the strength of regularization, and ν_σ is the Gaussian noise injected in the latent space with the scale hyperparameter σ. The two terms have the following intuitions: the mean squared error (MSE) of reconstructions ensures $\mathbf{z}$ captures information of the input while $\mathcal{L}_{\text{EEP}}$ encourages representations to be mutually independent.

4 EXPERIMENTS

We evaluate the performance of GCAE against the leading unsupervised disentanglement baselines β-VAE Higgins et al. (2016), FactorVAE Kim & Mnih (2018), β-TCVAE Chen et al. (2018), and DIP-VAE-II Kumar et al. (2017). We did not consider DIP-VAE-I since it implicitly assumes knowledge of how many data generating factors there are. We measure disentanglement using four popular supervised disentanglement metrics: Mutual Information Gap (MIG) Chen et al. (2018), Factor Score Kim & Mnih (2018), DCI Disentanglement Eastwood & Williams (2018), and Separated Attribute Predictability (SAP) Kumar et al. (2017). However, we place special focus the Mutual Information Gap (MIG) metric Chen et al. (2018) since its definition aligns most strongly with the original definition of disentangled learning representations Bengio et al. (2013). MIG is defined as follows:

$$\text{MIG}(Z, K) \triangleq \frac{1}{K} \sum_{k=1}^{K} \frac{1}{H(V_k)} \left(I(Z_a; V_k) - I(Z_b; V_k) \right),$$

where K is the number of data generating factors, $H(V_k)$ is the discrete entropy of the k-th data generating factor, and $\mathbf{z}_a \sim Z_a$ and $\mathbf{z}_b \sim Z_b$ (where $a \neq b$) are the latent elements which share the most and next-most information with $\mathbf{v}_k \sim V_k$, respectively. In essence, MIG measures the average gap in information between the latent feature which is most selective for a unique data generating factor and the latent feature which is second runner up. MIG is a normalized metric on $[0, 1]$, and higher scores indicate better capturing and disentanglement of the data generating factors. This metric aligns most closely with the original definition of disentanglement in that it rewards representations which are maximally invariant to one another in the data (gap is large) whilst discarding as little information of the data as is practical ($I(Z_a; V_k)$ is large) Bengio et al. (2013). Furthermore, MIG enjoys an intuitive information-theoretic definition. This is in contrast with other metrics - it is sometimes difficult to know exactly what they are measuring Carbonneau et al. (2020).

We consider two datasets which cover different data modalities. The **Beamsynthesis** dataset Yeats et al. (2022) is a collection of 360 timeseries data from a linear particle accelerator beamforming simulation. The waveforms are 1000 values in total and are made of two independent data generating factors: *duty cycle* (continuous) and *frequency* (categorical). The **dSprites** dataset Matthey et al. (2017) is a collection of 737280 synthetic images of simple white shapes on a black background. Each 64×64 image consists of a single shape generated from the following independent factors: *shape* (categorical), *scale* (continuous), *orientation* (continuous), *x-position* (continuous), and *y-position* (continuous).

All experiments are run using the PyTorch framework Paszke et al. (2019) using 4 nVidia Tesla V100 GPUs, and all methods are trained with the same number of iterations. Hyperparameters such

as model architecture and optimizer are held constant across all models in each experiment (with the exception of the dual latent parameters required by VAE models). Latent space dimension is fixed at $m = 10$ for all experiments, unless otherwise noted. More details on experiment setup can be found in appendix B.

(a) Scatter plot of $\log(\mathcal{L}_{\Sigma I})$ vs. MSE for GCAE with $\sigma = \{0.1, 0.2, 0.3\}$ on Beamsynthesis and dSprites. Higher σ and lower $\log(\mathcal{L}_{\Sigma I})$ (through increased disentanglement pressure) tend to increase MSE. However, the increase in MSE subsides as the model becomes disentangled.

(b) Scatter plot of $\log(\mathcal{L}_{\Sigma I})$ vs. MIG for GCAE with $\sigma = \{0.1, 0.2, 0.3\}$ on Beamsynthesis and dSprites. There is a moderate negative relationship between $\log(\mathcal{L}_{\Sigma I})$ and MIG ($r = -0.823$), suggesting that $\log(\mathcal{L}_{\Sigma I})$ is a promising unsupervised indicator of (MIG) disentanglement.

In general, increasing λ and σ led to lower $\mathcal{L}_{\Sigma I}$ but higher MSE at the end of training. Figure 3a depicts this relationship for Beamsynthesis and dSprites. Increasing σ tends to shift ending loss values towards increased independence (according to $\mathcal{L}_{\Sigma I}$) but slightly worse reconstruction error. This is consistent with the well studied theory of the Gaussian channel - as the relative noise level increases, the information capacity of a constrained channel decreases. The tightly grouped samples in the lower right of the plot correspond with $\lambda = 0$ and incorporating any $\lambda > 0$ leads to a decrease in $\mathcal{L}_{\Sigma I}$ and increase in MSE. As λ is increased further the MSE increases only slightly as the average $\mathcal{L}_{\Sigma I}$ decreases significantly.

Figure 3b plots the relationship between end-of-training $\mathcal{L}_{\Sigma I}$ values with MIG evaluation scores for both Beamsynthesis and dSprites. Our experiments depict a moderate negative relationship with correlation coefficient -0.823. These results suggest that $\mathcal{L}_{\Sigma I}$ is a promising unsupervised indicator of successful disentanglement. This is very helpful in the practical setting where one likely does not have access to the ground truth data factors.

EFFECT OF λ AND σ ON DISENTANGLEMENT

In this experiment, we plot the disentanglement scores (average and standard deviation) of GCAE as the latent space noise level σ and disentanglement strength λ vary on Beamsynthesis and dSprites. In each figure, each dark line plots the average disentanglement score while the shaded area fills one standard deviation of reported scores around the average.

Figure 4a depicts the disentanglement scores of GCAE on the Beamsynthesis dataset. All σ levels exhibit relatively low scores when λ is set to zero (with the exception of FactorScore). In this situation, model is well-fit to the data, but the representation is highly redundant and entangled, causing the "gap" or "separatedness" (in SAP) for each factor to be low. However, whenever $\lambda > 0$ the disentanglement performance increases significantly, especially for MIG, DCI Disentanglement, and SAP with $\lambda \in [0.1, 0.2]$. There is a clear preference for higher noise levels, as $\sigma = 0.1$ generally has higher variance and lower disentanglement scores. FactorScore starts out very high on Beamsynthesis because there are just two factors of variation, making the factor classification task easy.

Figure 4b depicts the disentanglement scores of GCAE on the dSprites dataset. Similar to the previous experiment with Beamsynthesis, no disentanglement pressure leads to relatively low scores on all considered metrics (~ 0.03 MIG, ~ 0.47 FactorScore, ~ 0.03 DCI, ~ 0.08 SAP), but introduc-

(a) Beamsythesis · (b) dSprites

Figure 4: Effect of λ and σ on different disentanglement metrics. λ is varied in the x-axis. Starting from the top left of each subfigure and moving clockwise within each subfigure, we report MIG, FactorScore, SAP, and DCI Disentanglement. Noise levels $\sigma = \{0.2, 0.3\}$ are preferable for reliable disentanglement performance. **KEY:** Dark lines - average scores. Shaded areas - one standard deviation.

ing $\lambda > 0$ signficantly boosts performance on a range of scores 0.35 MIG, 0.6 FactorScore, 0.37 SAP, and 0.45 DCI (for $\sigma = \{0.2, 0.3\}$). Here, there is a clear preference for larger σ; $\sigma = \{0.2, 0.3\}$ reliably lead to high scores with very little variance.

COMPARISON OF GCAE WITH LEADING DISENTANGLEMENT METHODS

We incorporate experiments with leading VAE-based baselines and compare them with GCAE $\lambda = 0.2$. Each solid line represents the average disentanglement scores for each method and the shaded areas represent one standard deviation around the mean.

Figure 5: Disentanglement metric comparison of GCAE with VAE baselines on Beamsynthesis. GCAE λ is plotted on the lower axis, and VAE-based method regularization strength β is plotted on the upper axis. **KEY:** Dark lines - average scores. Shaded areas - one standard deviation.

Figure 5 depicts the distributional performance of all considered methods and metrics on Beam-synthesis. When no disentanglement pressure is applied, disentanglement scores for all methods are relatively low. When disentanglement pressure is applied ($\lambda, \beta > 0$), the scores of all methods increase. GCAE scores highest or second-highest on each metric, with low relative variance over a large range of λ. β-TCVAE consistently scores second-highest on average, with moderate variance. FactorVAE and β-VAE tend to perform relatively similarly, but the performance of β-VAE appears highly sensitive to hyperparameter selection. DIP-VAE-II performs the worst on average.

Figure 6 shows a similar experiment for dSprites. Applying disentanglement pressure significantly increases disentanglement scores, and GCAE performs very well with relatively little variance when $\lambda \in [0.1, 0.5]$. β-VAE achieves the high top scores with extremely little variance but only for a very narrow range of β. β-TCVAE scores very high on average for a wide range of β but with large variance in scores. FactorVAE consistently scores highest on FactorScore and it is competitive on SAP. DIP-VAE-II tends to underperform compared to the other methods.

Figure 6: Disentanglement metric comparison of GCAE with VAE baselines on dSprites. GCAE λ is plotted on the lower axis, and VAE-based method regularization strength β is plotted on the upper axis. **KEY:** Dark lines - mean scores. Shaded areas - one standard deviation.

4.1 DISENTANGLEMENT PERFORMANCE AS Z DIMENSIONALITY INCREASES

We report the disentanglement performance of GCAE on the dSprites dataset as m is increased. We compare GCAE with the other discriminator-assisted disentanglement method, FactorVAE Kim & Mnih (2018). FactorVAE uses a single monolithic discriminator and the density-ratio trick to explicitly approximate TC(Z). Computing TC(Z) requires knowledge of the joint density $p_Z(\mathbf{z})$, which becomes challenging to compute as m increases.

Figure 7 depicts an experiment comparing GCAE and FactorVAE when $m = 20$. The results for $m = 10$ are included for comparison. In general, the average disentanglement scores for GCAE $m = 10$ and $m = 20$ are extremely close, indicating that the method is scalable in m. This is not the case for FactorVAE - it performs worse on all metrics when m increases. Interestingly, FactorVAE $m = 20$ seems to recover its performance on most metrics with higher β than is beneficial for FactorVAE $m = 10$. Despite this recovery in performance, the difference in performance suggests that FactorVAE is not robust to changes in m.

Figure 7: Comparison of GCAE with FactorVAE as m increases. λ is plotted below, and β is plotted above. **KEY:** Dark lines - mean scores. Shaded areas - one standard deviation.

5 DISCUSSION

Overall, the results indicate that GCAE is a highly competitive disentanglement method. It achieves the highest average scores on the Beamsynthesis and dSprites datasets, and it has relatively low variance in its scores when $\sigma = \{0.2, 0.3\}$, indicating it is reliable. The hyperparameters are highly transferable, as $\lambda \in [0.1, 0.5]$ works well on multiple datasets and metrics. GCAE also used the same data preprocessing (mean and standard deviation normalization) across the two datasets. We also find that $\mathcal{L}_{\Sigma I}$ is a promising indicator of disentanglement performance which can be very useful for selecting a model when data generating factors for a task are unknown. While it is left to future work, we note that it would be easy to convert GCAE to a generative model once it is disentangled - the aggregate posterior is estimated by the product of discriminator densities, and the inference distribution induced by the Gaussian noise can represent a posterior.

While GCAE performs well in many scenarios, it has several limitations. In contrast to the VAE optimization process which is very robust Kingma & Welling (2013), the optimization of m discriminators is sensitive to hyperparameters such as learning rate and optimizer. Training m discriminators requires a lot of computation, and the quality of the learned representation depends heavily on the quality of the conditional densities stored in the discriminators. Increasing the latent space noise σ seems to make learning more robust and generally leads to improved disentanglement outcomes, but it limits the corresponding information capacity of the latent space.

6 CONCLUSION

We have presented Gaussian Channel Autoencoder (GCAE), a new disentanglement method which employs Gaussian noise and non-parametric density estimation in the latent space to achieve reliable, high-performing disentanglement outcomes. GCAE avoids the curse of dimensionality of density estimation by minimizing the Dual Total Correlation (DTC) metric with a weighted information functional to capture disentangled data generating factors. The method is shown to consistently out-compete existing SOTA baselines on many popular disentanglement metrics on the Beamsynthesis and dSprites datasets.

REFERENCES

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

Christopher P Burgess, Irina Higgins, Arka Pal, Loic Matthey, Nick Watters, Guillaume Desjardins, and Alexander Lerchner. Understanding disentangling in β-vae. *arXiv preprint arXiv:1804.03599*, 2018.

Marc-André Carbonneau, Julian Zaidi, Jonathan Boilard, and Ghyslain Gagnon. Measuring disentanglement: A review of metrics. *arXiv preprint arXiv:2012.09276*, 2020.

Ricky TQ Chen, Xuechen Li, Roger B Grosse, and David K Duvenaud. Isolating sources of disentanglement in variational autoencoders. *Advances in neural information processing systems*, 31, 2018.

Yuanqi Du, Xiaojie Guo, Amarda Shehu, and Liang Zhao. Interpretable molecule generation via disentanglement learning. In *Proceedings of the 11th ACM International Conference on Bioinformatics, Computational Biology and Health Informatics*, pp. 1–8, 2020.

Cian Eastwood and Christopher KI Williams. A framework for the quantitative evaluation of disentangled representations. In *International Conference on Learning Representations*, 2018.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014a.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014b.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. 2016.

Sarthak Jain, Edward Banner, Jan-Willem van de Meent, Iain J Marshall, and Byron C Wallace. Learning disentangled representations of texts with application to biomedical abstracts. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing. Conference on Empirical Methods in Natural Language Processing*, volume 2018, pp. 4683. NIH Public Access, 2018.

Vineet John, Lili Mou, Hareesh Bahuleyan, and Olga Vechtomova. Disentangled representation learning for non-parallel text style transfer. *arXiv preprint arXiv:1808.04339*, 2018.

Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *International Conference on Machine Learning*, pp. 2649–2658. PMLR, 2018.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Günter Klambauer, Thomas Unterthiner, Andreas Mayr, and Sepp Hochreiter. Self-normalizing neural networks. In *Proceedings of the 31st international conference on neural information processing systems*, pp. 972–981, 2017.

Abhishek Kumar, Prasanna Sattigeri, and Avinash Balakrishnan. Variational inference of disentangled latent concepts from unlabeled observations. *arXiv preprint arXiv:1711.00848*, 2017.

Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Raetsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *international conference on machine learning*, pp. 4114–4124. PMLR, 2019.

Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, Ian Goodfellow, and Brendan Frey. Adversarial autoencoders. *arXiv preprint arXiv:1511.05644*, 2015.

Loic Matthey, Irina Higgins, Demis Hassabis, and Alexander Lerchner. dsprites: Disentanglement testing sprites dataset. https://github.com/deepmind/dsprites-dataset/, 2017.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32: 8026–8037, 2019.

Daniil Polykovskiy, Alexander Zhebrak, Dmitry Vetrov, Yan Ivanenkov, Vladimir Aladinskiy, Polina Mamoshina, Marine Bozdaganyan, Alexander Aliper, Alex Zhavoronkov, and Artur Kadurin. Entangled conditional adversarial autoencoder for de novo drug discovery. *Molecular pharmaceutics*, 15(10):4398–4405, 2018.

Mhd Hasan Sarhan, Nassir Navab, Abouzar Eslami, and Shadi Albarqouni. Fairness by learning orthogonal disentangled representations. In *European Conference on Computer Vision*, pp. 746–761. Springer, 2020.

Naftali Tishby, Fernando C Pereira, and William Bialek. The information bottleneck method. *arXiv preprint physics/0004057*, 2000.

Eric Yeats, Frank Liu, David Womble, and Hai Li. Nashae: Disentangling representations through adversarial covariance minimization. *arXiv preprint arXiv:2209.10677*, 2022.

A IMPLEMENTATION

A.1 INFORMATION FUNCTIONAL

We estimate the information between each subset of variables $I(Z_i; Z_j)$ used in $\mathcal{L}_{\Sigma I}$ with a uniform estimate of the information functional:

$$I(Z_i; Z_{\setminus i}) \approx (b-a)\mathbb{E}_{\mathbf{z}_{\setminus i} \sim \phi_\sigma(X)} \left[\mathbb{E}_{\mathbf{u}_i \sim \text{Unif}(a,b)} \, p_{Z_i}(\mathbf{u}_i|\mathbf{z}_{\setminus i}) \left[\log p_{Z_i}(\mathbf{u}_i|\mathbf{z}_{\setminus i}) - \log p_{Z_i}(\mathbf{u}_i) \right] \right],$$

where (a, b) are the bounds of the Uniform distribution (-4 and 4 in our experiments), and $p_{Z_i}(\mathbf{u}_i|\mathbf{z}_{\setminus i})$ is the conditional density of the i-th discriminator evaluated with noise from the Uniform distribution. 50 uniform samples are taken per batch to estimate the functional in all experiments. Gradient is only taken through the $p_{Z_i}(\mathbf{u}_i|\mathbf{z}_{\setminus i})$ term with respect to the $\mathbf{z}_{\setminus i}$ variables. The marginal entropy $h(Z_i)$ upper bounds the conditional entropy $h(Z_i|Z_{\setminus i})$, so the information functional is a natural path to maximizing $h(Z_i|Z_{\setminus i})$ and thereby minimizing DTC.

B MAIN EXPERIMENT DETAILS

Each method uses the same architecture (besides the μ, $\log \sigma^2$ heads for the VAE) and receies the same amount of data during training. In all experiments, the GCAE AE and discriminator learning rates are $5e-5$ and $2e-4$, respectively. The VAE learning rate is $1e-4$ and the FactorVAE discriminator learning rate is $2e-4$. All methods use the Adam optimizer with $(\beta_1, \beta_2) = (0.9, 0.999)$ for the AE subset of parameters and $(\beta_1, \beta_2) = (0.5, 0.9)$ for the discriminator(s) subset of parameters (if applicable). The number of discriminator updates per AE update k is set to 5 when $m = 10$ and 10 when $m = 20$. All discriminators are warmed up with 500 batches before training begins to ensure they approximate a valid density. VAE architectures are equipped with a Gaussian decoder for Beamsynthesis and a Bernoulli decoder for dSprites. SELU refers to the SeLU activation function Klambauer et al. (2017). MIG is measured by creating a histogram of activations of the latent space and calculating discrete information with the data generating factors. A bin size of 50 is used on Beamsynthesis and a bin size of 20 is used on dSprites (following Locatello et al. (2019)).

Table 1: MLP Architecture

Dataset	GCAE Architecture	VAE Architecture
Beamsynthsis	Linear(n, 1024), SELU	Linear(n, 1024), SELU
BatchSize=64	Linear(1024, 1024), SELU	Linear(1024, 1024), SELU
Mean/STD Norm	Linear(1024, 512), SELU	Linear(1024, 512), SELU
2000 Iterations	Linear(512, m), SoftSign	$2 \times$ Linear(512, m)
	Linear(m, 512), SELU	Linear(m, 512), SELU
dSprites	Linear(512, 1024), SELU	Linear(512, 1024), SELU
BatchSize=256	Linear(1024, 1024), SELU	Linear(1024, 1024), SELU
Mean/STD Norm (GCAE)	Linear(1024, n)	Linear(1024, n)
20000 Iterations		

Table 2: Discriminator Architectures. The FactorVAE architecture follows the suggestion of Kim & Mnih (2018). The GCAE discriminator is much smaller, but there are m of them compared to just 1 FactorVAE discriminator.

GCAE Discriminator Architecture	FactorVAE Discriminator Architecture
Linear(m, 256), SELU	Linear(m, 1024), SELU
Linear(256, 256), SELU	Linear(1024, 1024), SELU
Linear(256, 1), Sigmoid	Linear(1024, 1024), SELU
-	Linear(1024, 1024), SELU
-	Linear(1024, 1024), SELU
-	Linear(1024, 1), Sigmoid

C ABLATION STUDY

Figure 8: Ablation study: Comparison of MIG scores with and without $\mathcal{L}_{\text{EEP}}$. $\mathcal{L}_{\Sigma I}$ corresponds to direct gradient descent on $\mathcal{L}_{\Sigma I}$. Just because $\mathcal{L}_{\Sigma I}$ does not result in high MIG scores does not mean that $p(\mathbf{z})$ is not independent. The results indicate that $\mathcal{L}_{\text{EEP}}$ is a helpful inductive bias for aligning representations with interpretable data generating factors.

Figure 8 depicts an ablation study for training with $\mathcal{L}_{\text{EEP}}$ vs. directly with $\mathcal{L}_{\Sigma I}$. Please see the caption for details.

D   RELATED WORK

D.1   DISENTANGLEMENT METHODS

GCAE is an unsupervised method for disentangling learning representations - hence, the most closely related works are the state-of-the-art unsupervised VAE baselines: β-VAE Higgins et al. (2016), FactorVAE Kim & Mnih (2018), β-TCVAE Chen et al. (2018), and DIP-VAE-II Kumar et al. (2017). All methods rely on promoting some form of independence in $p_Z(\mathbf{z})$, and we shall cover them in more detail in the following sections.

β-VAE

The disentanglement approach of β-VAE Higgins et al. (2016) is to promote independent codes in Z by constraining the information capacity of Z. This is done with a VAE model by maximizing the expectation (on $\mathbf{x}$) of the following loss:

$$\mathcal{L}_{\beta\text{-VAE}} = \mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}\left[p_\theta(\mathbf{x}|\mathbf{z})\right] - \beta D_{\text{KL}}\left(q_\phi(\mathbf{z}|\mathbf{x})\big|\big|p_\theta(\mathbf{z})\right),$$

where $q_\phi(\mathbf{z}|\mathbf{x})$ is the approximate posterior (inferential distribution of the encoder), $p_\theta(\mathbf{x}|\mathbf{z})$ is the decoder distribution, $p_\theta(\mathbf{z})$ is the prior distribution (typically spherical Gaussian), and β is a hyperparameter controlling the strength of the "Information Bottleneck" Tishby et al. (2000) induced on Z. Higher β are associated with improved disentanglement performance.

FACTORVAE

The authors of FactorVAE Kim & Mnih (2018) assert that the information bottleneck of β-VAE is too restrictive, and seek to improve the reconstruction error vs. disentanglement performance tradeoff by isolating the Total Correlation (TC) component of the $D_{\text{KL}}\left(q_\phi(\mathbf{z}|\mathbf{x})\big|\big|p_\theta(\mathbf{z})\right)$ term. They employ a large discriminator neural network, the density-ratio trick, and a data shuffling strategy to estimate the TC. FactorVAE maximizes the following loss:

$$\mathcal{L}_{\text{FactorVAE}} = \mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}\left[p_\theta(\mathbf{x}|\mathbf{z})\right] - D_{\text{KL}}\left(q_\phi(\mathbf{z}|\mathbf{x})\big|\big|p_\theta(\mathbf{z})\right) - \text{TC}_\rho(Z),$$

where $\text{TC}_\rho(Z)$ is the discriminator's estimate of $\text{TC}(Z)$. The discriminator is trained to differentiate between "real" jointly distributed $\mathbf{z}$ and "fake" $\mathbf{z}$ in which all the elements have been shuffled across a batch.

β-TCVAE

β-TCVAE Chen et al. (2018) seeks to isolate $\text{TC}(Z)$ via a batch estimate. They avoid significantly underestimating $p_Z(\mathbf{z})$, by constructing an importance-weighted estimate of $h(Z)$:

$$\mathbb{E}_{q(\mathbf{z})}\left[\log q(\mathbf{z})\right] \approx \frac{1}{B}\sum_{i=1}^{B}\left[\log\frac{1}{BC}\sum_{j=1}^{B}q(\phi(x_i)|x_j)\right]$$

where $q(\mathbf{z})$ is an estimate of $p_Z(\mathbf{z})$, B is the minibatch size, C is the size of the dataset, $\phi(x_i)$ is a stochastic sample from the i-th x, and $q(\phi(x_i)|x_j)$ is the density of the posterior at $\phi(x_i)$ when $\mathbf{x} = x_j$.

This estimate is used to compute an estimate of $\text{TC}(Z)$, and the following loss is maximized:

$$\mathcal{L}_{\beta\text{-TCVAE}} = \mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}\left[p_\theta(\mathbf{x}|\mathbf{z})\right] - I_q(Z; X) - \beta\text{TC}_\rho(Z) - \sum_{j=1}^{m}D_{\text{KL}}\left(q(\mathbf{z}_j)\big|\big|p(\mathbf{z}_j)\right),$$

where $I_1(Z; X)$ is the "index-code" mutual information, $\text{TC}_\rho(Z)$ is an estimate of $\text{TC}(Z)$ computed with their estimate of $q(\mathbf{z})$, β is a hyperparameter controlling $\text{TC}(Z)$ regularization, and $\sum_{j=1}^{m}D_{\text{KL}}\left(q(\mathbf{z}_j)\big|\big|p(\mathbf{z}_j)\right)$ is a dimension-wise Kullback-Leibler divergence.

DIP-VAE-II

The approach of DIP-VAE-II is that the aggregate posterior of a VAE model should be factorized in order to promote disentanglement Kumar et al. (2017). This is done efficiently using batch estimates of the covariance matrix. The loss to be maximized for DIP-VAE-II is:

$$\mathcal{L}_{\text{DIP-VAE-II}} =$$

$$\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}\left[p_\theta(\mathbf{x}|\mathbf{z})\right] - D_{\text{KL}}\left(q_\phi(\mathbf{z}|\mathbf{x})\middle|\middle|p_\theta(\mathbf{z})\right) - \beta\left(\sum_{i=1}^{m}\left[\text{Cov}(\mathbf{z}_{ii}) - 1\right]^2 + \sum_{i=1}^{m}\sum_{j\neq i}\left[\text{Cov}(\mathbf{z}_{ij})\right]^2\right).$$

Hence, the covariance matrix of the sampled representation $\mathbf{z}$ should be equal to the identity matrix. β is a hyperparameter controlling regularization strength.

D.2 DISENTANGLEMENT METRICS

We evaluate GCAE and the leading VAE baselines with four metrics: Mutual Information Gap (MIG), FactorScore, Separated Attribute Predictability (SAP), and DCI Disentanglement.

MUTUAL INFORMATION GAP

MIG is described in detail in the main text. For Beamsynthesis, we calculate MIG on the full dataset using a histogram estimate of the latent space with 50 bins (evenly spaced maximum to minimum). We calculate MIG using 10000 samples on dSprites.

FACTOR SCORE

FactorScore is introduced by Kim & Mnih (2018). The intuition is that change in one dimension of Z should result in change of at most one factor of variation. It starts off by generating many batches of data in which one factor of variation is fixed for all samples in a batch. Then the variance of each dimension on each batch is calculated and normalized by its standard deviation (without interventions). The index of the latent dimension with smallest variance and the index of the fixed factor of variation for the given batch is used as a training point for a majority-vote classifier. The score is the accuracy of the classifier on a test set of data.

For Beamsynthesis, we train the majority-vote classifier on 1000 training points and evaluate on 200 separate points. For dSprites, we train the majority-vote classifier on 5000 training points and evaluate on 1000 separate points.

SEPARATED ATTRIBUTE PREDICTABILITY

Separated Attribute Predictability (SAP) is introduced by Kumar et al. (2017). SAP involves creating a $m \times k$ score matrix, where ij-th entry is the "predictability" of factor j from latent element i. For discrete factors, the score is the balanced classification accuracy of predicting the factor given knowledge of the i-th latent, and for continuous factors, the score is the R-squared value of the i-th latent in (linearly) predicting the factor. The resulting score is the difference in predictability of the most-predictive and second-most predictive latents for a given factor, averaged over all factors.

For Beamsynthesis, we use a training size of 240 and a test size of 120. For dSprites, we use a training size of 5000 and a test size of 1000.

DCI DISENTANGLEMENT

DCI Disentanglement is introduced by Eastwood & Williams (2018). It complements other metrics introduced by the paper: completeness and informativeness. The intuition is that each latent variable should capture at most one factor. k decision tree regressors are trained to predict each factor given the latent codes $\mathbf{z}$. The absolute importance weights of each decision tree regressor are extracted and inserted as columns in a $m \times k$ importance matrix. The rows of the importance matrix are

normalized, and the (discrete) k-entropy of each row is computed. The difference of one and each row k-entropy is weighted by the relative importance of each row to compute the final score.

For Beamsynthesis, we use 240 training points and 120 testing points. For dSprites, we use 5000 training points and 1000 testing points.

E   TRAINING TIME COMPARISON

Table 3: Comparison of training times of the discriminator-based disentanglement algorithms on Beamsynthesis. Latent space size is fixed to $m = 10$ and discriminator training iterations is fixed to $k = 5$.

Method	Average (s)	Standard Deviation (s)
GCAE	955.0	13.6
FactorVAE	1024.4	5.8