Predicting Fluid Dynamics in Physical-informed Mesh-reduced Space

Abstract

For computational fluid dynamics, there is a considerable interest in using neural networks for accelerating simulations. However, these learning-based models suffer from scalability issues when training on high-dimensional and high-resolution simulation data generated for real-world applications. In this work, we study the problem of improving accuracy of desired physical properties using graph learning models for learning complex fluid dynamics, while operating on mesh-reduced space. We design several tailored modules to incorporate physical-informed knowledge into a two-stage prediction model, which direct the learning process to focus more on the region of interests (ROI). Prediction will then be made in a mesh-reduced space, which helps reduce computational costs while preserving important physical properties. Results on simulated unsteady fluid flow data show that even under reduced operational space, our method still achieves desirable performance on accuracy and generalizability of both prediction and physical consistency over region of interests.

1 Introduction

In many industrial cases, simulations are used to model the part of the process that has the greatest impact on the final product. In particular, predicting physical dynamics with Graph Neural Network (GNN) models is an active and growing area of research in machine learning, which have shown to be powerful and flexible. However, for industrial applications (e.g. furnace and aerodynamic simulation), the dynamic systems are usually high-dimensional and some of them need to be resolved on very fine meshes. As the number of mesh increases, significantly larger computational cost will be induced. Also, as the mesh becomes finer, GNNs have to perform more message passing steps to pass information along the same physical distance, which may result in accuracy reduction cased by over-smoothing (Li et al., 2018) and over-squashing (Alon & Yahav, 2020). Is it really necessary to simulate the entire dynamic system accurately? For example, for the steel manufacturing process, the von Kármán flow (Zandbergen & Dijkstra, 1987) formulated in steel casting operations is responsible for many defects in the final product. In fact, vortex formation is one of the fluid flow phenomena occurring in the casting mold. It is believed to have significant contribution to mold powder entrapment; the entrapped flux may be carried deeply down into the mold by downward flows and results in uncleanness of steel (He, 1993). Therefore, simulation accuracy of areas that have vortex formation is more important than that of the other regions. In general, if we could direct the learning process to focus more on the region of interests (ROI), we are expected to have better accuracy on important regions and reducing computational cost by paying less attention to rest of the areas. Our contributions of this paper are in three folds:

- We study the problem of improving accuracy of desired physical properties using graph learning models for learning complex fluid dynamics (e.g. turbulence), while operating on mesh-reduced space.
- We design tailored modules to incorporate physical-informed knowledge into a two-stage training model for fluid dynamic forecasting.
- When evaluate on unsteady fluid flow prediction, our method achieves desired performance on accuracy and generalizability of both prediction and physical consistency over region of interests.

(a) Mesh Graph Autoencoder

(b) Dynamic Predictor in Mesh-reduced Space

Figure 1: The proposed two-stage training framework.

2 METHODS

Our proposed prediction system contains two training stages. A Mesh Graph Autoencoder will first learned to incorporate physical-informed priors into the full mesh graph and summarize the information into subgraph, forming representations of each time frame in a mesh-reduced space. Then, a Dynamics Predictor will learn to predict subgraph evolution in the mesh-reduced space. We denote an attributed graph with N nodes as a tuple $\mathcal{G} = (\mathcal{N}, \mathcal{E})$. For all the fluid simulations in this work, we utilize *Eulerian* systems to model the evolution of continuous fields (e.g. velocity) over a fixed mesh and thus the graph is fixed for all time steps for each data.

2.1 PHYSICAL-INFORMED PRIOR (PIP) EXTRACTOR

The underlying physical prior incorporated in our graph learning system is rooted in the family of vortex methods that are rigorously derived, analyzed, and tested in the computational fluid dynamics (CFD) (Graftieaux et al. (2001); Leonard (1980); Perlman (1985); Beale & Majda (1985)). In this work, we apply the vortex center identification algorithm to characterize the location of the center. Specifically, for any given node i in a mesh graph $\mathcal{G}_t$, we utilized a scalar function Γ to quantify the streamline topology of the flow in the vicinity of node center C_i and the rotation sign of the vortex.

$$\Gamma_{i,t} = \frac{1}{L} \sum_{l=1}^{L} \sin \theta_{M_l} = \frac{1}{L} \sum_{l=1}^{L} \frac{C_i \vec{M}_l \times v_{M_l}^t}{\|C_i \vec{M}_l\| \cdot \|v_{M_l}^t\|}, \tag{1}$$

where M_l is one of the evenly spaced L points on a circle centered at C_i with radius r. θ_{M_l} represents the angle between the velocity vector $v_{M_l}^t$ at time t and the radius vector $C_i \vec{M}_l$. The velocity $v_{M_l}^t$ at M_l is computed by spatial interpolation. The nodes with high $|\Gamma|$ generally locate near vortices. Here, Γ is a dimensionless scalar, with $|\Gamma| \leq 1$. It can be shown that this bound is reached at the vortex center if the vortex is axisymmetrical.

2.2 MESH GRAPH AUTOENCODER

The proposed Mesh Graph Autoencoder model ($\mathcal{G}_t \rightarrow S_t \rightarrow \hat{\mathcal{G}}_t$) consists of a Physical-informed Prior Extractor, two MeshGraphNet (MGN), a MeshGraphSelector (MGS), and a MeshGraphReverser (MGR). After finishing training this module, a set of pivotal nodes S_t with feature Z_t will be obtained and further used as input for the next-stage Dynamic Prediction module (discussed in 2.3).

The internal structure of MGN is an Encoder-Process-Decoder (EPD) network Pfaff et al. (2020). After the original graph $\mathcal{G}_t$ passing through the first MGN module (denoted as f_{MGN}^1), the updated graph along with the prior information obtained from physical-informed prior (PiP) extractor will be fed into MGS. In the MGS module (denoted as f_{MGS}), it adaptively selects a subset of nodes based on k-largest values in Γ_t to form a new but smaller graph. Eventually, the new graph will contain information from the mesh-reduced space with a set of $S_t \in \mathcal{N}$ pivotal nodes. These pivotal nodes will preserve as much PiP information as possible at each time step while ensuring the graph consistency across time-steps.

The features of the pivotal nodes need to go through the MGR module (denoted as f_{MGR}) to restore information of full nodes from the original mesh graph. This step is implemented by spatial interpolation of the non-pivotal nodes. A commonly used approach is to use inverse distance weighted (IDW) interpolation Alet et al. (2019); Han et al. (2022). However, as these pivotal nodes are irregularly spaced points and we will later construct triangular mesh graph using these pivotal nodes, we instead use another spatial interpolation technique named by triangular interpolation network (TIN) Wood et al. (1990); Vivoni et al. (2004). After reversed into its original form, the mesh graph will be fed into a second MDN module (denoted as f_{MGN}^2) which will output a reconstructed graph $\hat{\mathcal{G}}_t$. We then minimize the difference between the original and the reconstruction graph at each time step through backpropagation.

2.3 Dynamic Predictor in Mesh-reduced Space

Since related edges are removed when removing nodes in MGS, the nodes in the selected graph might become isolated. This may influence the information propagation in subsequent layers, especially when MGN layers are used to aggregate information from neighboring nodes. Therefore, we need to increase connectivity among nodes in the selected graph. The connector or connection function determines, for each pair of supernodes S_a, S_b, the presence or absence of an edge between the corresponding nodes a and b in the pooled graph. The function also computes the attributes to be assigned to new edges. There are many different connection functions to choose from Grattarola et al. (2022) and we use Delaunay triangulation for its nearly unique and optimal triangulation Watson & Philip (1984). For a set of points, the Delaunay criterion ensures that a circle that passes through three points on any triangle contains no additional points.

After the training of Mesh Graph Autoencoder, we are able to obtain representative subgraphs to represent every full graphs from data. The Dynamic Predictor will then be trained to learn a function that can predict $\mathcal{G}_{S_{t+1}}$ from $\mathcal{G}_{S_t}$, where $\mathcal{G}_{S_t}$ denotes a subgraph with a set of $S_t \in \mathcal{N}$ nodes at time step t. If we assume a fixed subgraph across time steps (i.e. $S_t = S_{t+1}$), we can easily make predictions through a simple fully-connected (FC) network as in Han et al. (2022). However, for unsteady or turbulent flow, pivotal nodes from PiP extractor will vary across time and thus $S_t \neq S_{t+1}$. Therefore, we need to find another way to make the prediction. The first step in Dynamic Predictor is to feed $\mathcal{G}_{S_t}$ into another MGN module (denoted as f_{MGN}^3) to predict a subgraph at time $t + 1$, denoted as $\mathcal{G}'_{S_t}$. $\mathcal{G}'_{S_t}$ has a feature matrix Z_{t+1,S_t} with pivotal node set S_t. Then, $\mathcal{G}'_{S_{t+1}}$ is consecutively fed into f_{MGR} and f_{MGN}^2 to obtain a full graph $\mathcal{G}'_{t+1}$. Finally, $\hat{\mathcal{G}}_{S_{t+1}}$ with feature $Z_{t+1,S_{t+1}}$ is obtained by passing $\mathcal{G}'_{t+1}$ through f_{MGN}^1 and f_{MGS}. To train the dynamic predictor, we minimize the difference between $\mathcal{G}'_{t+1}$ and the $\mathcal{G}_{t+1}$ at each time step through backpropagation.

3 Experiment

To generate our simulation data, we use a numerical solver with Navier-Stokes equations on fixed 2D Eulerian meshes. Specifically, two dataset are generated: *Lid-driven Cavity Flow* dataset that simulated impressive flow inside a cavity with a moving top wall; *Cylinder Flow* dataset that simulates incompressible flow around a cylinder inside a tunnel. To make the dataset more challenging and to futher test generalizability of our model, we generate data with irregular cavity shape and more than one cylinder in the tunnel. Additional dataset details and visualizations are available in Appendix B.

We compare the performance of our approach with a baseline method GMR_GMUS Han et al. (2022) which also aims to reduce computational cost by learning a low-dimensional mesh graph. Different from our approach, they use random sampling to construct subgraphs and did not take physical-informed priors into account. In this section, we visually illustrate performance of our method on accuracy and generalizability of both prediction and physical consistency over region of interests. Details on model parameter selection, in-depth quantitative analysis, and other experiment results are available in Appendix C.

Figure 2: (a) Simulation results comparison of different methods tested on a cylinder flow data at t = 100. In the first row, pivotal nodes used in the mesh-reduced space are colored in red. (b) Generalization results of our method on unseen two-cylinder test cases at t = 200. For both plots, on their third row, red 'X' marks denote vortices detected from the actual data, while blue dots denote vortices detected from predicted velocity fields.

3.1 TIME-SERIES PREDICTION OF FLUID DYNAMICS

We visualize the prediction results of a case at $t = 100$ for our model, GMR_GMUS, and FG in Figure 2(a). The mesh color in the first and second row represents the magnitude of V_x while the third row shows the magnitude of difference. We can clearly see that PiP selected nodes locate in the vicinity of the cylinder and the region to the right of the cylinder, where vortices typically appear. In comparison, randomly selected nodes in GMR_GMUS do not attend to this region. The prediction result of our model shows a clear sign of unsteady flow past cylinder, visually close to the ground truth and the FG prediction. In comparison, the result of GMR_GMUS shows a steady flow, which is ultimately incorrect. In the third row, we observe that the detected vortices from ground truth and our model prediction locate close to each other while the vortex detection from GMR_GMUS prediction is a total failure.

3.2 GENERALIZABILITY ANALYSIS

We further examine the generalizabilty of our model using unseen two-cylinder flow test cases. Figure 2(b) illustrates two different placements of the two cylinders: vertical and horizontal. As seen in the result, although the overall performance drops as expected, our methods is still able to have reasonable velocity predictions for cases that are totally different from the training data. Most importantly, we observe that the detected vortices from ground-truth and our model prediction still locate close to each other. If we take a closer look at the third row in Figure 2(b), the absolute prediction errors are small around region of interests (ROI). We can thus conclude that instead of simply learning a model that work within the data distribution, our proposed model is able to capture domain-invariant physical properties and can be used to simulate out-of-distribution data.

4 CONCLUSION

In this work, we study the problem of improving accuracy of desired physical properties using graph learning models for learning complex fluid dynamics, while operating on mesh-reduced space. A two-stage graph-based model is proposed, which utilizes physical-informed prior information to learn and predict physical dynamics in a reduced mesh space. We generate challenging the lid-driven cavity flow and cylinder flow dataset to test and evaluate the performance of our model. According to the results, by incorporation physical-informed prior information, our model is able to detect important physical properties (e.g. vortex locations) more accurately than other baseline methods. Results also show a great generalizability of our proposed method. Although the overall performance cannot surpass models that trained using the entire mesh, the amount of sacrifice of average prediction accuracy is worthwhile when compared to the amount to improvement of prediction accuracy around ROI. Therefore, in reality, when a high-dimensional data cannot be trained using full domain information, our method is able to help reducing computational costs while preserving important physical properties.

REFERENCES

Ferran Alet, Adarsh Keshav Jeewajee, Maria Bauza Villalonga, Alberto Rodriguez, Tomas Lozano-Perez, and Leslie Kaelbling. Graph element networks: adaptive, structured computation and memory. In *International Conference on Machine Learning*, pp. 212–222. PMLR, 2019.

Uri Alon and Eran Yahav. On the bottleneck of graph neural networks and its practical implications. *arXiv preprint arXiv:2006.05205*, 2020.

Emily Alsentzer, Samuel Finlayson, Michelle Li, and Marinka Zitnik. Subgraph neural networks. *Advances in Neural Information Processing Systems*, 33:8017–8029, 2020.

J Thomas Beale and Andrew Majda. High order accurate vortex methods with explicit velocity kernels. *Journal of Computational Physics*, 58(2):188–208, 1985.

Saakaar Bhatnagar, Yaser Afshar, Shaowu Pan, Karthik Duraisamy, and Shailendra Kaushik. Prediction of aerodynamic flow fields using convolutional neural networks. *Computational Mechanics*, 64:525–545, 2019.

Steven L Brunton, Bernd R Noack, and Petros Koumoutsakos. Machine learning for fluid mechanics. *Annual review of fluid mechanics*, 52:477–508, 2020.

Miles Cranmer, Sam Greydanus, Stephan Hoyer, Peter Battaglia, David Spergel, and Shirley Ho. Lagrangian neural networks. *arXiv preprint arXiv:2003.04630*, 2020.

Meire Fortunato, Tobias Pfaff, Peter Wirnsberger, Alexander Pritzel, and Peter Battaglia. Multiscale meshgraphnets. *arXiv preprint arXiv:2210.00612*, 2022.

Hongyang Gao and Shuiwang Ji. Graph u-nets. In *international conference on machine learning*, pp. 2083–2092. PMLR, 2019.

Zhenglin Geng, Daniel Johnson, and Ronald Fedkiw. Coercing machine learning to output physically accurate results. *Journal of Computational Physics*, 406:109099, 2020.

Laurent Graftieaux, Marc Michard, and Nathalie Grosjean. Combining piv, pod and vortex identification algorithms for the study of unsteady turbulent swirling flows. *Measurement Science and technology*, 12(9):1422, 2001.

Daniele Grattarola, Daniele Zambon, Filippo Maria Bianchi, and Cesare Alippi. Understanding pooling in graph neural networks. *IEEE Transactions on Neural Networks and Learning Systems*, 2022.

Samuel Greydanus, Misko Dzamba, and Jason Yosinski. Hamiltonian neural networks. *Advances in neural information processing systems*, 32, 2019.

Xu Han, Han Gao, Tobias Pffaf, Jian-Xun Wang, and Li-Ping Liu. Predicting physics in mesh-reduced space with temporal attention. *arXiv preprint arXiv:2201.09113*, 2022.

Qinglin He. Observations of vortex formation in the mould of a continuous slab caster. *ISIJ international*, 33(2):343–345, 1993.

Quercus Hernández, Alberto Badías, David González, Francisco Chinesta, and Elías Cueto. Structure-preserving neural networks. *Journal of Computational Physics*, 426:109950, 2021.

Philipp Holl, Vladlen Koltun, and Nils Thuerey. Learning to control pdes with differentiable physics. *arXiv preprint arXiv:2001.07457*, 2020.

Vivianne Holmén. Methods for vortex identification. *Master's Theses in Mathematical Sciences*, 2012.

Tyler W Hughes, Ian AD Williamson, Momchil Minkov, and Shanhui Fan. Wave physics as an analog recurrent neural network. *Science advances*, 5(12):eaay6946, 2019.

Dmitrii Kochkov, Jamie A Smith, Ayya Alieva, Qing Wang, Michael P Brenner, and Stephan Hoyer. Machine learning–accelerated computational fluid dynamics. *Proceedings of the National Academy of Sciences*, 118(21):e2101784118, 2021.

Anthony Leonard. Vortex methods for flow simulation. *Journal of Computational Physics*, 37(3): 289–335, 1980.

Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. In *Thirty-Second AAAI conference on artificial intelligence*, 2018.

Arvind T Mohan, Nicholas Lubbers, Daniel Livescu, and Michael Chertkov. Embedding hard physical constraints in neural network coarse-graining of 3d turbulence. *arXiv preprint arXiv:2002.00021*, 2020.

Mirta Perlman. On the accuracy of vortex methods. *Journal of Computational Physics*, 59(2): 200–223, 1985.

Tobias Pfaff, Meire Fortunato, Alvaro Sanchez-Gonzalez, and Peter W Battaglia. Learning mesh-based simulation with graph networks. *arXiv preprint arXiv:2010.03409*, 2020.

Maziar Raissi and George Em Karniadakis. Hidden physics models: Machine learning of nonlinear partial differential equations. *Journal of Computational Physics*, 357:125–141, 2018.

Stephan Rasp and Nils Thuerey. Data-driven medium-range weather prediction with a resnet pre-trained on climate simulations: A new model for weatherbench. *Journal of Advances in Modeling Earth Systems*, 13(2):e2020MS002405, 2021.

Franz M Rohrhofer, Stefan Posch, Clemens Gößnitzer, and Bernhard C Geiger. Understanding the difficulty of training physics-informed neural networks on dynamical systems. *arXiv preprint arXiv:2203.13648*, 2022.

Alvaro Sanchez-Gonzalez, Nicolas Heess, Jost Tobias Springenberg, Josh Merel, Martin Riedmiller, Raia Hadsell, and Peter Battaglia. Graph networks as learnable physics engines for inference and control. In *International Conference on Machine Learning*, pp. 4470–4479. PMLR, 2018.

Alvaro Sanchez-Gonzalez, Jonathan Godwin, Tobias Pfaff, Rex Ying, Jure Leskovec, and Peter Battaglia. Learning to simulate complex physics with graph networks. In *International conference on machine learning*, pp. 8459–8468. PMLR, 2020.

Jean Michel Sellier, Gaétan Marceau Caron, and Jacob Leygonie. Signed particles and neural networks, towards efficient simulations of quantum systems. *Journal of Computational Physics*, 387: 154–162, 2019.

Gregory H Teichert, Anirudh R Natarajan, Anton Van der Ven, and Krishna Garikipati. Machine learning materials physics: Integrable deep neural networks enable scale bridging by learning free energy functions. *Computer Methods in Applied Mechanics and Engineering*, 353:201–216, 2019.

Nils Thuerey, Konstantin Weißenow, Lukas Prantl, and Xiangyu Hu. Deep learning methods for reynolds-averaged navier–stokes simulations of airfoil flows. *AIAA Journal*, 58(1):25–36, 2020.

Kiwon Um, Xiangyu Hu, and Nils Thuerey. Liquid splash modeling with neural networks. In *Computer Graphics Forum*, volume 37, pp. 171–182. Wiley Online Library, 2018.

Enrique R Vivoni, Valeri Y Ivanov, Rafael L Bras, and Dara Entekhabi. Generation of triangulated irregular networks based on hydrological similarity. *Journal of hydrologic engineering*, 9(4): 288–302, 2004.

DF Watson and GM Philip. Systematic triangulations. *Computer vision, graphics, and image processing*, 26(2):217–223, 1984.

Eric F Wood, Murugesu Sivapalan, and Keith Beven. Similarity and scale in catchment storm response. *Reviews of Geophysics*, 28(1):1–18, 1990.

PJ Zandbergen and D Dijkstra. Von kármán swirling flows. *Annual review of fluid mechanics*, 19 (1):465–491, 1987.

A   RELATED WORKS

The rapid advent of machine learning techniques is opening up new possibilities to solve the physical system's identification problems by statistically exploring the underlying structure of a variety of physical systems, encompassing applications in quantum physics Sellier et al. (2019), thermodynamics Hernández et al. (2021), material science Teichert et al. (2019), rigid body control Geng et al. (2020), Lagrangian systems Cranmer et al. (2020), and Hamiltonian systems Greydanus et al. (2019). Specifically, in the field of fluid mechanics, machine learning offers a wealth of techniques to extract information from data that could be translated into knowledge about the underlying fluid field, as well as exhibits its ability to augment domain knowledge and automate tasks related to flow control and optimization Brunton et al. (2020); Holl et al. (2020).

Particular for computational fluid dynamics, there is a considerable interest in using neural networks for accelerating simulations of aerodynamics Bhatnagar et al. (2019) or turbulent flows Kochkov et al. (2021). Tasks such as airfoil design Thuerey et al. (2020), weather prediction Rasp & Thuerey (2021), and graphic visualizations for Um et al. (2018) take the advantages of these fast predictions and differentiable learned models. Besides long-studied methods that utilize convolutional networks on 2D grids, recent GNN-based learned simulators have shown to be a very flexible approach and can model a wide range of systems Sanchez-Gonzalez et al. (2018).

Fast predictions and differentiable learned models can be useful for tasks from airfoil design Thuerey et al. (2020) over weather prediction Rasp & Thuerey (2021) to visualizations for graphics Um et al. (2018). While many of these methods use convolutional networks on 2D grids, recently GNN-based learned simulators, in particular, have shown to be a very flexible approach, which can model a wide range of systems, from articulated dynamics Sanchez-Gonzalez et al. (2018) to dynamics of particle systems Sanchez-Gonzalez et al. (2020). However, as mentioned earlier, the scalability bottleneck of GNN to the costly high-dimensional and high-resolution simulations remains unsolved. A recent work by Fortunato et.al. Fortunato et al. (2022) proposed a possible solution by learned a mapping function from high-dimensional to low-dimensional mesh graph. However, to train the mapping function, it needs to have mesh data in two different dimensionalities, which may not always be accessible. Another potential approach is to learn a low-dimentional mesh graph that can best represent the full mesh graph Gao & Ji (2019); Alsentzer et al. (2020); Grattarola et al. (2022); Han et al. (2022). However, these methods are either restricted to graph classification tasks, or have no guarantees if the subgraph captures desirable properties.

Recently, many pieces of research are developed to efficiently learn the fluid dynamics through incorporating physical priors into the learning framework, e.g., encoding the Navier-Stokes equations Raissi & Karniadakis (2018), embedding the notion of an incompressible fluid Mohan et al. (2020), and identifying a mapping between the dynamics of wave-based physical phenomena and the computation in a recurrent neural network (RNN) Hughes et al. (2019). In fact, most of these works falls into the Physics-Informed Neural Networks (PINN) category. However, this type of method usually suffers from convergence issues Rohrhofer et al. (2022) and requires delicate designs of network structures.

In this work, we aim to solve fluid dynamic prediction problems by combining the best of both worlds (i.e. subgraph network and physics-informed learning). We designed a graph-based model that use physical-informed prior information to learn subgraphs. The learned graph will only be in mesh-reduced space that help reduce computational costs, but also preserve important physical information.

B   DATASET DETAILS

We used OpenFOAM solver to generate our simulation data. The governing equations for incompressible flows, namely the continuity and momentum equations, are numerically solved using an unstructured cell-centered collocated grid finite volume method. Integrated over a small control volume, which in this case is a triangular cell of the mesh, the equations are written as:

$$\nabla \cdot \mathbf{u} = 0, \quad \frac{\partial \mathbf{u}}{\partial t} + \mathbf{u} \cdot \nabla \mathbf{u} = -\frac{1}{\rho}\nabla p + \nu\nabla^2\mathbf{u}, \tag{2}$$

where $\mathbf{u}$ is the flow velocity, ρ is the (mass) density, ν is the kinematic viscosity, and p is the pressure.

(a) Lid-driven cavity flow

(b) Cylinder flow

Figure 3: Illustration of velocity fields (streamlines are colored in white) of two fluid dataset and corresponding physical-informed priors (selected pivotal nodes are colored in black)

All the simulation data we generated for this paper will be publicly available and we hope these data can promote further research on related areas.

B.1 LID-DRIVEN CAVITY FLOW

This dataset simulates the flow inside a cavity on a fixed 2D Eulerian mesh. The top wall moves in the x direction at a constant speed. There are three node types: fluid nodes, side wall nodes, and top wall nodes. A typical lid-driven cavity problem assumes a rectangular cavity. To make the dataset more challenging, we add a notch to the bottom right corner of the cavity such that the cavity will have irregular shape. The height of the cavity lies in a range of $[0.5, 4]$ and the cavity width remains constant at 1. The Reynolds number ranges from 209 to 2000. The indented notch has a width and height varying between 0 and 0.8. When the notch's width and height are both 0, we have a regular rectangle cavity. A total of 1497 data are generated at steady state. Figure 3(a) illustrates velocity fields of one of the data and the corresponding physical-informed prior values.

B.2 CYLINDER FLOW

This dataset simulates the flow around a cylinder on a fixed 2D Eulerian mesh. In all fluid domains, the node type distinguishes fluid nodes, wall nodes and inflow/outflow boundary nodes. The inlet boundary conditions are given by a prescribed parabolic profile, $u_{in} = u_0[1 - 4(y/H)]$ where u_0 and H are the centerline velocity and the distance between the sidewalls, respectively. The simulations are generated under different values of Reynolds numbers (Re), centerline inflow velocity, and diameter (D) of the cylinder. The considered values lie in the range $45 \leq Re \leq 250$ and $2 \leq H/D \leq 8$, respectively. There are a total number of 1000 training data, 100 validation data, and 100 testing data, where each data are sampled to have 60 time steps ($\Delta t = 0.05$) and 300 time steps ($\Delta t = 0.01$). For the generalizability test, we also generated 35 testing data that contain two cylinders randomly placed in the domain. Figure 3(b) illustrates velocity fields of one of the data and the corresponding physical-informed prior values.

C EXPERIMENT DETAILS

C.1 EVALUATION METRICS

To quantitatively evaluate the performance of the autoencoder and predictor models, we compute the root mean squared error (RMSE) of the velocities in two directions. To further assess the performance on vortex detection, we define two metrics: vortex detection rate (VDR) and mean distance to detected vortices (MDDV). To compute these two metrics, we need to first identify the location of the vortices in both the ground truth and the reconstruction/prediction velocity field. We use linear spatial interpolation to compute the velocities in a 1000×1000 grid and find the location of the vortices on the grid (using the method describe in Holmén (2012)). For a vortex p_i in the ground truth, it is detected if there is a vortex q_j found in the predicted velocity field within a distance threshold d. The detection indicator for p_i is:

$$\text{DI}_i = 1\{\min(d_{i0}, ..., d_{iQ}) \leq d\}. \tag{3}$$

Denote the number of vortices in ground truth and prediction as P and Q, the distance between vortex p_i and q_j as d_{ij}. The metrics are defined as:

$$\text{VDR@}d = \frac{\sum_{i=1}^{P} \text{DI}_i}{P}$$
$$\text{MDDV@}d = \sum_{i=1}^{P} \text{DI}_i \cdot \min(d_{i0}, ..., d_{iQ}) \tag{4}$$

For cylinder flow data, the region of interest (ROI) is the area surrounding the cylinder and to the right of the cylinder. We define a ROI box that contains this area. Given cylinder center c and radius r, the top left and bottom right corners of the box are $(c_x - r - 0.05, c_y + r + 0.05)$ and $(c_x + r + 0.45, c_y - r - 0.05)$. For both reconstruction and dynamics prediction, we calculate the RMSE, VDR and MDDV within the ROI box as well as the global RMSE.

C.2 RECONSTRUCTION VIA SUBGRAPH

Mesh graph autoencoders are learned for both datasets with the purpose of summarizing the full mesh graph into a subgraph. The MLPs in the MGNs has two hidden layers and output size of 128, except for the output layers of the MGNs. The output dimension for the first MGN is 4, meaning that each node in the subgraph is represented by a 4-dimensional vector. For the second MGN, the output dimension corresponds to the prediction dimension.

C.2.1 LID-DRIVEN CAVITY FLOW

For lid-driven cavity flow, we trained 150K steps with an exponential decay of learning rate from 10^{-4} to 10^{-6} over the last 100K steps. Since the number of nodes varies from case to case, we do not fix the number of subgraph nodes and use half of the total nodes in the original mesh graph. We use a threshold $d = 0.001$ to compute VDR and MVVD.

The reconstruction results are listed in Table 1. When the IDW interpolation is used, our model is superior to GMR_GMUS in every evaluation metrics. The use of TIN interpolation significantly improves the results by reducing over 30% RMSE. Although our model is marginally worse than GMR_GMUS in global_RMSE, it has a remarkable advantage on the vortex-related metrics, producing 11% improvement in VDR and 26% reduction in MDDV. This suggests that our model yields a better reconstruction result in the vicinity of vortices while a random node selector will put less weight on. Figure 4 shows the reconstruction result of two cases in the lid-driven cavity flow test data. In case (a), the fluid flow in the top right corner is confined by a narrow simulation wall and the change of flow direction is abrupt. Our model is successful in handing this case and identifies the vortex. There is another vortex in the bottom low-velocity region and our model can also accurately detect it. In case (b), the simulation box is deep and there are two vortices in the bottom region. Our model can adapt to this case and successfully locate them.

Figure 4: Simulation results of our method tested on lid-driven cavity flow dataset. Vortex centers are extract from velocity fields, which are color in green and red to denote predicted and ground-truth, respectively.

Table 1: Reconstruction results for Lid-driven Cavity Flow dataset.

	global_RMSE (x10^{-3})		VDR @0.001 $\uparrow$	MDDV @0.001 $\downarrow$ (x10^{-3})
	V_x	V_y		
GMR_GMUS(IDW)	2.19	0.96	0.61	0.23
GMR_GMUS(TIN)	1.23	0.68	0.65	0.19
Ours(IDW)	1.82	1.00	0.65	0.18
Ours(TIN)	1.26	0.70	**0.72**	**0.14**

C.2.2 CYLINDER FLOW

For cylinder flow, we trained 600K steps with an exponential decay of learning rate from 10^{-4} to 10^{-6} over the last 400K steps. We fix the number of subgraph nodes to be 512. We report both the global RMSE and the RMSE within the ROI box. We use a threshold $d = 0.001$ to compute VDR. The MDDV is not reported because the value is 0 for all cases listed in the table.

The reconstruction results are listed in Table 2. When IDW interpolation is used, our model produces about 26% reduction in global_RMSE, 55% reduction in ROI_RMSE and 81% improvement in VDR over GMR_GMUS. The enhancement in vortex region is much more prominent than the cases in lid-driven cavity flow, because cylinder flow is a much larger simulation system therefore random node selector will sample proportionally fewer nodes in vortex regions. This demonstrates that PiP extractor is more useful for large simulation system with relatively small ROI regions. When TIN interpolation is applied, we observe an improvement over IDW in both global_RMSE and ROI_RMSE. The VDR score is less sensitive to the interpolation method. We also test the methods with varying simulation time step Δt and a similar trend is observed. Applying TIN interpolation for $\Delta t = 0.01$, our method yields a 20% reduction in global_RMSE, 49% reduction in ROI_RMSE and 59% increase in VDR. The high performance of our model in ROI demonstrates that PiP extractor is effective in selecting pivotal nodes for summarizing the whole mesh graph with an adaptive concentration on vortex regions.

C.3 TIME-SERIES PREDICTION

To learn the flow dynamic predictor in mesh-reduced space, we use the trained autoencoder to generate ground truth data pairs (Z_{t,S_t}, Z_{t+1,S_t}). The autoencoders we used are the ones with $t = 0.01$ and TIN interpolation. The dynamics predictor is a separate MGN with input and output dimension being 4. The MLPs in the MGN has two hidden layers with output size of 128. Since the subgraph

Table 2: Reconstruction results for Cylinder Flow dataset.

	Δt (s)	global_RMSE (x10^{-3})		ROI_RMSE (x10^{-3})		VDR @0.001 $\uparrow$
		V_x	V_y	V_x	V_y	
GMR_GMUS (IDW)	0.05	4.7	2.2	8.5	4.3	0.48
GMR_GMUS (TIN)	0.05	4.3	2.1	7.8	4.0	0.49
	0.01	4.1	1.9	7.5	3.7	0.53
Ours (IDW)	0.05	3.8	1.5	4.4	1.7	**0.87**
Ours (TIN)	0.05	**3.5**	**1.4**	**4.0**	**1.6**	0.86
	0.01	**3.5**	**1.4**	**4.2**	**1.7**	**0.84**

Table 3: Dynamics prediction results for 300-step rollout with $\Delta t = 0.01$ tested in Cylinder Flow dataset.

	N_node	global_RMSE (x10^{-3})		ROI_RMSE (x10^{-3})		VDR @0.02 $\uparrow$	MDDV @0.02 $\downarrow$ (x10^{-3})
		Vx	Vy	Vx	Vy		
FG	~1885	75.3	42.1	98.1	76.0	0.56	8.7
GMR_GMUS	512	125.9	57.5	216.1	100.6	0.38	10.2
Ours	512	114.9	60.2	183.5	114.4	**0.46**	**9.8**

has a reduced size compared to the full mesh graph, we use only 8 message passing steps in the MGN instead of 15. The predictor is trained for 3M steps with the learning rate decaying from 10^{-4} to 10^{-5} in the last 2M steps. Since dynamics prediction is substantially more difficult than reconstruction, we use a larger threshold $d = 0.02$ to compute VDR and MDDV.

The results for 300-step rollout are listed in Table 3. Compared to GMR_GMUS with random extractor, our PiP extractor model achieves a 8.7% reduction in global RMSE for V_x and a 15.1% reduction in ROI RMSE for V_x. However, it is slightly worse in RMSE for V_y. Despite the small improvement in RMSE, our model achieves a 21% improvement in VDR, showing that the predicted velocity field by our model is more effective in finding vortices. We also compare our model with a full graph (FG) dynamics predictor, which is a simple MGN. With a 73% decrease in the number of nodes, our predictor only falls 10% behind of the FG model. Although FG achieves a significantly lower velocity RMSE, it is mostly accurate in less important regions and it is not efficient for very large system.

Figure 5 shows the prediction rollouts of two cases for our model versus the ground truth. The mesh color represents the magnitude of V_x and the red dots signify the pivotal nodes selected. Our model demonstrates accurate and stable rollout predictions. In case (a), the cylinder is large and the flow becomes unsteady, resulting in the vortex shedding phenomenon where alternating vortices are created. Our model successfully learns the dynamics and correctly predicts the beginning and the periodic progression of vortex shedding. In case (b) where the cylinder is small, the flow is laminar and steady. Our model is also able to generate visually similar predictions. For both cases, we observe that the pivotal nodes adapt to the change in the velocity field and consistently locate near the cylinder ROI region. This targeted and adaptive design makes our model superior for vortex prediction.

Figure 5: Velocity field simulation results of our method versus ground truth tested on Cylinder Flow dataset. Pivotal nodes used in the mesh-reduced space are colored in red at each time step. Our model extracts informative nodes at each time step and accurately predicts long rollout sequences under different design parameters.