Discovering Latent Knowledge in Language Models Without Supervision

Abstract

Existing techniques for training language models can be misaligned with the truth: if we train models with imitation learning, they may reproduce errors that humans make; if we train them to generate text that humans rate highly, they may output errors that human evaluators can't detect. We propose circumventing this issue by directly finding latent knowledge inside the internal activations of a language model in a purely unsupervised way. Specifically, we introduce a method for accurately answering yes-no questions given only unlabeled model activations. It works by finding a direction in activation space that satisfies logical consistency properties, such as that a statement and its negation have opposite truth values. We show that despite using no supervision and no model outputs, our method can recover diverse knowledge represented in large language models: across 6 models and 10 question-answering datasets, it outperforms zero-shot accuracy by 4% on average. We also find that it cuts prompt sensitivity in half and continues to maintain high accuracy even when models are prompted to generate incorrect answers. Our results provide an initial step toward discovering what language models know, distinct from what they say, even when we don't have access to explicit ground truth labels.

1 Introduction

The increasing deployment of language models in real-world applications opens up exciting possibilities, but it also raises the stakes of AI research and presents new risks (Bommasani et al., 2021; Weidinger et al., 2021; Bender et al., 2021). One of these risks is that language models do not always output text that is true (Evans et al., 2021; Hendrycks et al., 2021; Kenton et al., 2021).

Common training objectives can cause models to learn internal representations related to truth, since truth is a useful feature for many tasks. However, these objectives can also cause language models to output text that is false, at least in some circumstances. For example, if we train a model to imitate human-generated text, it may learn to output common misconceptions (Lin et al., 2022). Or if we train a chat bot to optimize a reward such as engagement, it may learn to generate text that is compelling but false (Roller et al., 2021). If we try to reward model outputs that look true, a model may still learn to output false text if human raters can't evaluate the correctness of that text (Kenton et al., 2021).

In each case, this is an issue that stems from the misalignment between a training objective and the truth. As models are applied to more complex domains, human supervision may become less effective at mitigating this misalignment. Moreover, because this is a problem with the training objective rather than a model's capabilities, it likely won't be solved by scaling up models alone.

We propose a different approach for addressing this misalignment: using models to answer questions in a purely *unsupervised* way. Intuitively, instead of trying to explicitly, externally specify truth, we search for implicit, internal "beliefs" or "knowledge" learned by a model. We approach this problem by leveraging the fact that a model's representation of truth must satisfy logical consistency properties, which are unlikely to be satisfied by many other features.

We implement this idea by introducing Contrast-Consistent Search (CCS), a method that learns a linear projection of the hidden states that is consistent across negations, as illustrated in Figure 1. We find that despite its simplicity and despite not having access to any labels or model outputs, CCS can accurately recover knowledge from model representations: evaluated across 6 models and 10 question-answering datasets, CCS outperforms the accuracy of strong zero-shot baselines by

Figure 1: An illustration of our method, Contrast-Consistent Search (CCS). For each yes-no question q_i, we let x_i^+ and x_i^- be the natural language statements where we answer q_i as "Yes" and "No" respectively. Answering the question q_i then amounts to determining which of x_i^+ or x_i^- is true. We compute probabilities p^+ and p^- that x_i^+ and x_i^- are true respectively using a learned mapping from the hidden states to a number between 0 and 1. We search for a mapping such that that the probabilities are both consistent and confident. On the right, we show a histogram of the "Yes" probabilities, $\tilde{p}_i = 0.5 \cdot (p_i^+ + (1 - p_i^-))$, learned by our method for the COPA dataset (Roemmele et al., 2011) with the UnifiedQA model (Khashabi et al., 2020). Our method is purely unsupervised, only leveraging the consistency of truth, but learns to accurately answers questions.

4% on average (Section 3.2.1). The resulting classifier is also less sensitive to different prompts than zero-shot, cutting the standard deviation in accuracy in half. Additionally, we try deliberately prompting models to make incorrect outputs, which should intuitively change what models say but which shouldn't affect their latent knowledge. We find that this causes zero-shot accuracy to drop by up to 9.5% (Section 3.2.2), without decreasing the accuracy of CCS.

We systematically analyze CCS to understand the features it discovers. We show that it transfers across unrelated tasks, suggesting that models may have a task-agnostic representation of the truth and that CCS is able to approximately discover it (Section 3.3.1). Moreover, CCS sometimes works best using the hidden states in the *middle* layers of a network, suggesting that it leverages different features from those used by the outputs (Section 3.3.2). Finally, we show that representations of truth tend to be salient in models: they can often be found without much data, and they can often be found by taking the top principal component of a slightly modified representation space (Section 3.3.3).

Most existing techniques for making models truthful use human supervision to explicitly specify what is correct. However, it is not feasible to provide supervision in some settings. Our work suggests that an external source of ground truth may not actually be necessary: we may instead be able to find a model's latent representation of truth, independent of what a model says, without using any supervision in the first place.

2 PROBLEM STATEMENT AND FRAMEWORK

In this section we describe our problem setup in more detail and introduce Contrast-Consistent Search (CCS), a method for discovering latent knowledge in language models without supervision.

2.1 PROBLEM: DISCOVERING LATENT KNOWLEDGE

Given a pre-trained neural language model and a set $q_1, \ldots, q_n$ of yes-no questions[1], our goal is to answer each q_i correctly. Here, q_i can be any question with a well-defined answer, including procedural questions like "Is 22+59 = 237?", for which the answer is "No", or factual questions like "Are cats mammals?", for which the answer is "Yes".

Importantly, we want methods that do not rely on the model generating correct outputs and do not rely on external supervision. We consequently do not assume access to labeled ground-truth data.

---

[1]Technically, we only require that there are two mutually exclusive answers. For example, we can also use the labels "positive" and "negative" for sentiment classification. Moreover, our setup can easily extend to the case where we want to evaluate the truth of a set of statements instead of answering a set of questions.

Instead, we turn to the model's hidden representations. Specifically, let $\phi(x) \in \mathbb{R}^d$ denote some feature representation on a natural langauge input x, such as the hidden states of a Transformer-based language model. Our goal is to answer the questions $q_1, \ldots, q_n$ only given access to $\phi(\cdot)$. In Section 2.2 we introduce a method for this problem that attains high accuracy (see Section 3), demonstrating that this task is tractable.

2.2 Method: Contrast-Consistent Search

To make progress on the goal described above, we exploit the fact that truth has special structure: it satisfies consistency properties that few other features in a language model are likely to satisfy. Our method, Contrast-Consistent Search (CCS), leverages this idea by finding a direction in activation space that is consistent across negations. As we illustrate in Figure 1, CCS works by (1) answering each question q_i as both "Yes" (x_i^+) and "No" (x_i^-), (2) computing the representations $\phi(x_i^+)$ and $\phi(x_i^-)$ of each answer, (3) mapping the answer representations to probabilities p_i^+ and p_i^- of being true, then (4) optimizing that mapping so that the probabilities are both consistent and confident.

The input to CCS is a set of questions, $q_1, \ldots, q_n$, and a pretrained model's representations, $\phi(\cdot)$; the output of CCS is a lightweight probe on top of $\phi(\cdot)$ that can answer questions as "Yes" or "No". Here, $\phi(\cdot)$ is fixed but should contain useful information about the answers to $q_1, \ldots, q_n$. Importantly, CCS does not modify the weights of the pretrained model and it does not use labels.

Constructing contrast pairs. An important property that truth satisfies is negation consistency: the answer to a clear-cut question cannot be both "Yes" and "No" at the same time, as these are negations of each other. Probabilistically, for each question q_i, the probability that the answer to q_i is "Yes" should be one minus the probability that the answer to q_i is "No". To use this property, we begin by constructing contrast pairs: for each question q_i, we answer q_i both as "Yes", resulting in the new natural language statement x_i^+, and as "No", resulting in the natural language statement x_i^-. We illustrate this in Figure 1 (left). We will then learn to classify x_i^+ and x_i^- as true or false; if x_i^+ is true, then the answer to q_i should be "Yes", and if x_i^- is true, then the answer to q_i should be "No".

In practice, we convert each task into a question-answering task with two possible labels, then we use task-specific zero-shot prompts to format questions and answers as strings to construct each contrast pair. The opposite labels we use to construct contrast pairs can be "Yes" and "No" for a generic task, or they can be other tasks-specific labels, such as "Positive" and "Negative" in the case of sentiment classification. We describe the exact prompts we use to for each task in Appendix B.

Feature extraction and normalization. Given a contrast pair (x_i^+, x_i^-), CCS first computes the representations $\phi(x_i^+)$ and $\phi(x_i^-)$ using the feature extractor $\phi(\cdot)$. Intuitively, there are two salient differences between $\phi(x_i^+)$ and $\phi(x_i^-)$: (1) x_i^+ ends with "Yes" while x_i^- ends with "No", and (2) one of x_i^+ or x_i^- is true while the other is false. We want to find (2) rather than (1), so we first try to remove the effect of (1) by normalizing $\{\phi(x_i^+)\}$ and $\{\phi(x_i^-)\}$ independently. In particular, we construct normalized representations $\tilde{\phi}(x)$ as follows:

$$\tilde{\phi}(x_i^+) := \frac{\phi(x_i^+) - \mu^+}{\sigma^+}; \quad \tilde{\phi}(x_i^-) := \frac{\phi(x_i^-) - \mu^-}{\sigma^-},$$

where (μ^+, σ^+) and (μ^-, σ^-) are the means and standard deviations of $\{\phi(x_i^+)\}_{i=1}^n$ and $\{\phi(x_i^-)\}_{i=1}^n$ respectively, and where all operations are element-wise along each dimension.[2] This normalization ensures that $\{\tilde{\phi}(x_i^+)\}$ and $\{\tilde{\phi}(x_i^-)\}$ no longer form two separate clusters.

Mapping activations to probabilities. Next, we learn a probe $p_{\theta,b}(\tilde{\phi})$ that maps a (normalized) hidden state $\tilde{\phi}(x)$ to a number between 0 and 1 representing the probability that the statement x is true. We use a linear projection followed by a sigmoid $\sigma(\cdot)$, i.e. $p_{\theta,b}(\tilde{\phi}) = \sigma(\theta^T \tilde{\phi} + b)$, but nonlinear projections can also work. For simplicity, we sometimes omit the θ, b subscript in p.

Training objective. To find features that represent the truth, we leverage the consistency structure of truth. First, we use the fact that a statement and its negation should have probabilities that add up to 1. This motivates the consistency loss:

$$L_{\text{consistency}}(\theta, b; q_i) := \left[p_{\theta,b}(x_i^+) - (1 - p_{\theta,b}(x_i^-)) \right]^2$$

---

[2] Mean-normalization is important for CCS to work at all, while variance-normalization is less essential.

However, this objective alone has a degenerate solution: $p(x^+) \approx p(x^-) \approx 0.5$. To avoid this problem, we encourage the model to also be confident with the following confidence loss:

$$L_{\text{confidence}}(\theta, b; q_i) := \min\{p_{\theta,b}(x_i^+), p_{\theta,b}(x_i^-)\}^2$$

We can be equivalently view $L_{\text{confidence}}$ as imposing a second consistency property, the law of excluded middle, on the probabilities: a statement must be either true or false. The final unsupervised loss is the sum of these two losses, averaged across all contrast pairs:

$$L_{\text{CCS}}(\theta, b) := \frac{1}{n} \sum_{i=1}^{n} L_{\text{consistency}}(\theta, b; q_i) + L_{\text{confidence}}(\theta, b; q_i)$$

Note that both losses are necessary; $L_{\text{confidence}}$ alone also has a degenerate solution.

Inference. Both $p(x_i^+)$ and $1 - p(x_i^-)$ should represent the probability that the answer to q_i is "Yes". However, because we use a soft consistency constraint, these may not be exactly equal. To make a prediction on an example x_i after training, we consequently take the average of these:

$$\tilde{p}(q_i) := \frac{1}{2}(p(x_i^+) + (1 - p(x_i^-)))$$

We then predict that the answer to q_i is "Yes" based on whether $\tilde{p}(q_i)$ is greater than 0.5. Technically, we also need to determine whether $\tilde{p}(q_i) > 0.5$ corresponds to "Yes" or "No," as this isn't specified by L_{CCS}. For simplicity in our evaluations we take the maximum accuracy over the two possible ways of labeling the predictions of a given test set. However, in principle we can identify the two clusters without any supervision by leveraging conjunctions; see Appendix A for details.

3 RESULTS

3.1 EXPERIMENTAL SETUP

Here we provide an overview of our experimental setup; see Appendix G for complete details.

Models. We test six models: encoder-decoder models (T5 (Raffel et al., 2020), UnifiedQA (Khashabi et al., 2020), T0 (Sanh et al., 2021)), autoregressive models (GPT-J (Wang & Komatsuzaki, 2021)), and encoder-only models (RoBERTa (Liu et al., 2019), DeBERTa (He et al., 2021)).

Data. We test models on 10 datasets: sentiment classification (IMDB (Maas et al., 2011) and Amazon (McAuley & Leskovec, 2013)), topic classification (AG-News (Zhang et al., 2015) and DBpedia-14 (Lehmann et al., 2015)), NLI (RTE (Wang et al., 2018) and QNLI (Rajpurkar et al., 2016)), story completion (COPA (Roemmele et al., 2011) and Story-Cloze (Mostafazadeh et al., 2017)), question answering (BoolQ (Clark et al., 2019)), and common sense reasoning (PIQA (Bisk et al., 2020)).

We convert each dataset to a yes-no question-answering task or a binary classification task, as described in Appendix G. We balance the labels and randomly subsample 1000 examples from each dataset (except for COPA, which has only 500 examples total), then randomly split each dataset into an unsupervised training set (60% of the data) and test set (40%).

Methods. We test four main methods: zero-shot, calibrated zero-shot, Contrast-Consistent Search (CCS), and Logistic Regression (LR). Zero-shot works by predicting the answer with the highest log probability according to the language model, averaged across the tokens that make up that label. Calibrated zero-shot works by balancing zero-shot predictions to be $50/50$ for each answer, as we describe in more detail below, similar to Zhao et al. (2021). For Logistic Regression we train on the training split for each dataset using $(\tilde{\phi}(x^+), \tilde{\phi}(x^-))$ as the covariates, then evaluate on the corresponding test split. We treat LR as a ceiling since it uses labeled data.

When testing CCS, we optimize it 10 times using AdamW (Loshchilov & Hutter, 2017) with learning rate 0.01, then take the run with the lowest unsupervised loss. Unless otherwise specified, we train CCS using all prompts for a single training set, then evaluate it on the corresponding test split.

Zero-shot baselines. Zero-shot outputs sometimes suffer from miscalibration (Zhao et al., 2021), in which models are biased towards predicting specific answers. Calibrating the outputs to be uniform over different answers can mitigate this problem. We use a variant of the calibration method presented in Zhao et al. (2021) by balancing predictions to be 50/50 across the two output labels. Specifically,

Method	RoBERTa	DeBERTa	GPT-J	T5	UQA	T0*	Mean*
0-shot	60.1(5.7)	68.6(8.2)	53.2(5.2)	55.4(5.7)	76.8(9.6)	87.9(4.8)	62.8(6.9)
Calibrated 0-shot	**64.3(6.2)**	76.3(6.0)	56.0(5.2)	58.8(6.1)	80.4(7.1)	90.5(2.7)	67.2(6.1)
CCS	62.1(4.1)	**78.5(3.8)**	61.7(2.5)	71.5(3.0)	82.1(2.7)	77.6(3.3)	71.2(3.2)
CCS (All Data)	60.1(3.7)	77.1(4.1)	**62.1(2.3)**	**72.7(6.0)**	**84.8(2.6)**	84.8(3.7)	**71.5(3.7)**
LR (Ceiling)	79.8(2.5)	86.1(2.2)	78.0(2.3)	84.6(3.1)	89.8(1.9)	90.7(2.1)	83.7(2.4)

Table 1: Accuracy and standard deviation (s.d.) of each method and model averaged across all prompts and datasets. For most models, CCS outperforms zero-shot accuracy and exhibits lower sensitivity to prompts, even though this was not our goal. This shows that we can recover knowledge from language model activations without supervision, and can do so in a way that is competitive with strong baseline methods that use model outputs. *T0 was trained on 9 out of 10 of the datasets we evaluate on, including some of the data in our test splits, so we ignore it when averaging over models.

if l_+ and l_- are the logits for the positive and negative label respectively, then instead of classifying an example as positive if $l_+ > l_-$, we classify it as positive if $l_+ > l_- + \gamma$, where we select the threshold $\gamma \in \mathbb{R}$ so that the predictions are balanced. We find this increases accuracy by about 5% on average. Unless otherwise specified, we always report zero-shot accuracy after calibration.

Encoder-only models (e.g. RoBERTa and DeBERTa) cannot be easily do zero-shot classification out of the box, so to evaluate them we follow the method of Yin et al. (2020): we finetune both models on an NLI dataset (MNLI, which we do not evaluate on) and treat the difference between the entailment and contradiction probabilities as the effective logit. This provides a strong zero-shot baseline for encoder-only models that works even for non-NLI tasks (Yin et al., 2020). This finetuning isn't necessary for CCS to work on encoder-only models, but we test CCS using the same MNLI-finetuned models for ease of comparison.

Hidden states. We extract the hidden states corresponding to the last token in the last layer of each model, unless otherwise specified. For encoder-decoder models, we evaluate CCS on the last layer hidden states of both the encoder and decoder, and use whichever one generally achieves a lower unsupervised loss; for T0 this is the decoder hidden states, while for T5 and Unified QA this is the encoder hidden states. See Appendix G.1 for implementation details. We compare the performance of CCS on the hidden states across different layers in Section 3.3.

Prompts. To reduce prompt sensitivity, for each dataset, we use between 8 and 13 prompts (9 on average), derived or slightly modified from Sanh et al. (2021). We average across all prompts when showing results. To construct contrast pairs, we let x_i^+ be the zero-shot prompt using q_i and the first label (e.g. "Positive" for sentiment classification datasets) and let x_i^- be the prompt using q_i and the second label (e.g. "Negative"). We describe all of the prompts we use in Appendix F.

3.2 Evaluating CCS

3.2.1 CCS Outperforms Zero-Shot

We evaluate CCS on all 6 models and compute the average accuracy across all datasets and prompts. To assess sensitivity to different prompts, we compute the standard deviation (s.d.) of each model across all prompts (9 per dataset on average) before averaging. T0 was trained on 9 out of 10 of the datasets we evaluate on, including some of the data in our test splits, so we ignore it when averaging over models to avoid unfair comparisons with zero-shot. We display the results in Table 1. For comparison, we also include results when training CCS on all datasets simultaneously.

CCS attains an accuracy of 71.2% on average, compared to 67.2% for calibrated zero-shot. It outperforms zero-shot accuracy for every model, except for RoBERTa (where it does 2% worse) and T0 (for which zero-shot accuracy is inflated). Training on all datasets improves accuracy slightly (0.3%) on average, but with large gains for T0 in particular $(77.6\% \rightarrow 84.8\%)$.

These results show that CCS can *exceed* the performance of strong baseline methods that access the model outputs, even though this wasn't our main goal. This indicates that it is indeed possible to classify examples with high accuracy using only unlabeled representations from $\phi(\cdot)$.

3.2.2 CCS Is Robust To Misleading Prompts

Recall our motivating goal: to discover latent knowledge in a language model even when its training objective causes the model to output false text. We provide an initial proof of concept that CCS can achieve this goal by constructing prompts that aim to mislead the outputs of language models. To do so, we add a prefix to the beginning of our zero-shot prompts that consists of questions answered incorrectly (Figure 7). The hope is that such a prefix will decrease zero-shot accuracy because the model will imitate its context by outputting incorrect answers.[3] We found that while most models are robust to this type of prefix (see Appendix B), it significantly drops calibrated zero-shot performance in UnifiedQA, decreasing accuracy from 80.4% to 70.9%.

We evaluate CCS on these examples and show the results in Figure 2. We find that despite the 9.5% drop in zero-shot accuracy, CCS maintains high accuracy (82.1% → 83.8%). Indeed, Figure 2 shows that for almost every prompts and dataset, accuracy drops for zero-shot, but remains similar or even increases slightly for CCS. This indicates that even when language model outputs are unreliable, our approach can still recover correct answers if the model representations are good.

Figure 2: Zero-shot accuracy drop caused by the misleading prefix shown in Figure 7 for UnifiedQA. Each point corresponds to one dataset and one prompt. On average, zero-shot accuracy drops 9.5%, while CCS performs 1.7% better. This suggests that the latent knowledge inside a model that CCS recovers can be robust even when model outputs become less reliable.

3.3 Analyzing CCS

We have shown that CCS attains strong classification performance in standard settings and when we deliberately mislead models. Moreover, we have described our motivation as discovering latent representations of truth in language models, but in practice CCS just finds a direction in representation space that attains high accuracy. This raises the question: in what sense is CCS actually finding "truth" features? We now provide a preliminary investigation of this question.

3.3.1 CCS Finds A Task-Agnostic Representation of Truth

From the results described so far, it may be possible that the classifier we find is capturing dataset-specific properties, such as which of two labels (e.g. "Yes" vs. "No") is more likely to be correct. We rule this out by showing that it generalizes across completely different tasks, including ones with different label spaces (such as from "Yes" and "No" for a generic task to "Positive" and "Negative" for sentiment classification). We train and test CCS on every pair of datasets, and show results for several models in Figure 3. (See Appendix E for results with other models.)

We find that CCS indeed transfer wells: in the majority of datasets, CCS's transfer accuracy is competitive with training and testing on the same dataset (the last row in Figure 3, "No transfer"). Transfer performance can even outperform the no-transfer setting. This tends to occur when we train on simpler tasks, such as sentiment or topic classification For example, training CCS on the Amazon sentiment dataset achieves an average transfer accuracy of 71.8%, which is 0.6% higher than CCS without transfer. We speculate that this is because the difference in representations between correct and incorrect answers is more pronounced for easier tasks.

---

[3]In practice we found that model behavior was qualitatively similar between using this prefix with correct and incorrect answers, in agreement with the findings of Min et al. (2022b) that using incorrect labels in demonstrations often does not significantly degrade the performance of a few-shot prompt. Consequently, the prefix may instead actually be reducing accuracy because it is out-of-distribution. See also Kim et al. (2022) for more experiments on the subtleties of correct vs incorrect labels for few-shot prompts.

Figure 3: Transfer Performance using CCS on UnifiedQA, T0 and DeBERTa. The y-axis corresponds to the training dataset, and the x-axis corresponds to the test dataset. The final row ("No Transfer") corresponds to training and testing on the same dataset, which is the same as the diagonal. On most datasets, CCS transfers well to other datasets (relative to no transfer), including to different tasks with completely different labels. In some cases transfer even outperforms the no-transfer setting. See Appendix D for results with other models.

Additionally, transfer accuracy tends to be similar for many datasets. For example, training on IMDB (row 1 of Figure 3) has similar accuracy as training on DBPedia (row 4). This provides evidence that CCS can find a functionally similar direction across many different types of training datasets. Overall, these results suggest that (1) models may have a task-agnostic representation related to what is true, and that (2) CCS may approximately find this representation even without diverse data.

3.3.2 CCS CAN FIND INTERMEDIATE REPRESENTATIONS OF TRUTH

One reason models might represent features correlated with the truth is because a model's *outputs* are correlated with the truth whenever zero-shot performance is high. If so, it may be that CCS can only recover these output correlations. We provide against this possibility by testing the performance of CCS when using hidden states from intermediate layers, and show the results in Figure 4.

While accuracy is often highest for later layers, CCS can also perform well using layers in the middle of the network, especially for encoder-decoder models. In fact, for UnifiedQA (and T5; see Figure 10) it achieves a higher accuracy in the middle of the network (at the final layer of the encoder) than at the end of the network (the final layer of the decoder). This further supports the idea that CCS can find latent knowledge in models that is distinct from what they say.

3.3.3 TRUTH IS A SALIENT FEATURE

From the results we have presented so far, it is possible that the direction learned by CCS is difficult to find and requires using a large amount of unsupervised data. We provide evidence against this possibility, showing that finding such a direction both (1) can often be done with only a small amount of data, and (2) can often also be done by simply taking the top principal component of a slightly modified representation space.

CCS doesn't require much data. We evaluate how CCS performs with different amounts of data. Whereas before we trained CCS using the full training set and all prompts, here we use limited data and a single prompt. Specifically, we train using only k unlabeled contrast pairs, using the single prompt for each model and dataset that achieves the highest zero-shot accuracy. We still test on all prompts for each dataset. We resample k points 32 times for each of $k = 1, 2, 4, \cdots$, and take the average accuracy across those 32 samples. Finally, we plot the average such accuracy across all dataset and prompts for several models in Figure 5.

We find that while CCS benefits from more data, it can often do well with very limited data. In fact, it can sometimes even do well with only a single contrast pair, though we find high variance across individual datasets; see Appendix C for more details. This suggests that the high performance of CCS does not primarily come from using a large amount of unsupervised data, and indicates that the direction learned by CCS may be relatively easy to find.

Figure 4: CCS performance when using the hidden states across different layers. For every model, performance is high in several layers, and for UnifiedQA CCS does especially well in the last layer of the encoder.

Figure 5: Accuracy when we train on k samples, averaged across 32 trials, for different values of k. While it benefits from more examples, for several models CCS can work surprisingly well with very limited data.

Contrastive Representation Clustering. We now show that directions correlated with the truth may be "salient" in a different way: by showing that we can also find such directions using either (1) PCA or (2) clustering. Specifically, suppose we construct contrast pairs (x_i^+, x_i^-) as before. Intuitively, these two examples are qualitatively almost identical except that one is true and the other is false, so the main difference between the representations $\tilde{\phi}(x_i^+)$ and $\tilde{\phi}(x_i^-)$ should relate to truth. Consequently, we can take the differences in (normalized) hidden states, $\{\tilde{\phi}(x_i^+) - \tilde{\phi}(x_i^-)\}_{i=1}^n$, and cluster them. We call this method Contrastive Representation Clustering (CRC). Clustering can be achieved by taking the top principal component (TPC) and thresholding at 0, or by doing a "bimodal salience search" (BSS) to find a direction that looks bimodal; see Appendix G.3 for further details.

We compare CCS and the two versions of Contrastive Representation Clustering in Table 2, using the same setting as in Table 1. While CCS performs best, all methods attain high accuracy and are competitive with zero-shot performance. This indicates both that (1) representations of truth often lie in a high-variance direction in the contrastive representation space $\{\tilde{\phi}(x_i^+) - \tilde{\phi}(x_i^-)\}_{i=1}^n$, and also that (2) true and false examples are often well-clustered in this same contrastive space. This strengthens the idea that representations of truth may be salient features inside models that are relatively easy to find; this may help explain why CCS can perform well even without supervision, and how it can do so even with only a limited amount of unlabeled data.

4 RELATED WORK

Zero-Shot Prompting. Since the release of GPT-3 (Brown et al., 2020), one of the main paradigms for eliciting what models know has been zero-shot prompting (Liu et al., 2022; Beltagy et al., 2022). Zero-shot exploits how language models are trained to predict diverse data from the internet, which incidentally includes tasks such as question-answering. If prompted appropriately, this can be used to solve various useful tasks with reasonable performance (Brown et al., 2020). However, since these models are trained to imitate human-generated data, this bounds the quality of their outputs.

Many methods improve upon vanilla zero-shot prompting (Liu et al., 2022; Zhao et al., 2021; Lu et al., 2022; Wei et al., 2022b; Min et al., 2022a). While our goal is not to improve zero-shot performance, some of the ideas underlying these methods are similar to CCS. Particularly relevant are methods that also leverage unsupervised consistency properties, such as Jung et al. (2022); Zhou et al. (2022).

Method	RoBERTa	DeBERTa	GPT-J	T5	UQA	T0*	Mean*
Calibrated 0-shot	64.3(6.2)	76.3(6.0)	56.0(5.2)	58.8(6.1)	80.4(7.1)	90.5(2.7)	67.2(6.1)
CCS	62.1(4.1)	**78.5(3.8)**	**61.7(2.5)**	**71.5(3.0)**	**82.1(2.7)**	77.6(3.3)	**71.2(3.2)**
CRC (TPC)	**64.6(5.8)**	76.5(5.7)	59.9(3.7)	66.7(5.0)	78.3(3.3)	58.9(13.0)	69.2(4.7)
CRC (BSS)	62.6(6.8)	76.8(5.3)	60.7(3.4)	69.7(3.3)	79.3(2.5)	76.7(9.6)	69.8(4.3)

Table 2: We compare CCS to two variants of Contrastive Representation Clustering: TPC, which clusters by projecting onto the top principal component, and BSS, which clusters by finding a bimodal direction. We show accuracy and standard deviation of each model averaged across all prompts and datasets, in the same setting as Table 1. We find that CCS generally performs the best, but all methods are competitive with zero-shot.

However, these methods still bootstrap from language model outputs trained via imitation learning, which limits their applicability to our main goals.

To illustrate this, imagine we train reinforcement learning agents to play a game such as Diplomacy (Gray et al., 2021), in which players have incentives to lie to each other. Then those agents may learn to lie in a way that is difficult to detect, but they may still internally represent whether they are lying. Because their outputs would be deliberately misleading, standard zero-shot methods may be very unreliable. In contrast, techniques like CCS may still be able to detect whether those models are lying by finding representations of truth in their activations that contradict their outputs.

Truthfulness. There has been increasing interest in making language models truthful (Evans et al., 2021; Lin et al., 2022). One aspect of truthfulness that has received substantial attention is factuality (Thorne et al., 2018; Maynez et al., 2020). For instance, many techniques aim to improve the factuality of models by augmenting them with retrieval methods (Nakano et al., 2021; Menick et al., 2022), which allows them to cite their sources. In contrast, we focus on truthfulness more generally, which also includes procedural knowledge such as reasoning or inference tasks.

An approach to making language models truthful in this more general setting is to finetune them using either human demonstrations (Khashabi et al., 2020; Sanh et al., 2021; Zhong et al., 2021; Wei et al., 2022a) or reinforcement learning from human feedback (Christiano et al., 2017; Stiennon et al., 2020; Askell et al., 2021; Bai et al., 2022; Ouyang et al., 2022). These techniques have been widely successful at improving performance, but unlike our method they rely on being able to provide ground truth labels, which can be intractable in many settings.

Some work has aimed to go beyond the direct supervision humans can provide by augmenting supervision with AI systems (Christiano et al., 2018; Irving et al., 2018; Leike et al., 2018; Perez et al., 2022). This may expand the range of applications we can supervise, but it is unclear just how far these techniques can generalize. Christiano et al. (2022) reframes this issue by posing the problem of Eliciting Latent Knowledge (ELK). Like our problem statement, ELK is about eliciting knowledge from models even in cases where humans cannot evaluate that knowledge. However, we frame this as an empirical problem, rather than a worst-case theoretical problem.

5 DISCUSSION

5.1 LIMITATIONS AND FUTURE WORK

Our work has a number of limitations. First, CCS relies on the existence of a direction in activation space that separates true and false inputs reasonably well. This requires that a model is both *capable* of evaluating the truth of those inputs, and also that the model *actively evaluates it* on our examples.

Second, we did not evaluate our method on setups involving active "lying" or "deception" (Kenton et al., 2021; Evans et al., 2021) by models, as we aren't aware of existing evaluation setups for this setting. If future work develops such a setup, a good stress test would be to apply CCS to do "lie detection" in that setting (though this may require tweaking the method to ensure that it reliably converges to the model's latent knowledge rather than the lies that the model outputs).

There are also various straightforward improvements to our method that one could explore. This includes adding additional consistency constraints, calibrating its probabilities, generalizing it beyond the yes-no question-answering setting, generalizing it to cases where answers aren't clear-cut, and closing the remaining gap between the performance of CCS and the logistic regression ceiling.

5.2 CONCLUSION

As language models become more capable, they will be increasingly used as components in larger AI systems trained with reinforcement learning. As this occurs, falsehoods arising from misaligned training objectives may become more common, severe, and difficult to detect. In principle, models may even develop instrumental incentives to lie: for example, if a human evaluator would disapprove of bad model behavior, models may learn to lie about their behavior to achieve higher reward. If so, those models would be optimizing against human evaluators, making it precarious to rely on those evaluators for assessing the truth of what models say. Because unsupervised methods for eliciting answers circumvent this issue, they may still work even in this scenario. We show that it is possible to make progress on such methods today; the success of our approach suggests that unsupervised methods are both a tractable and underexplored research direction.

REFERENCES

Amanda Askell, Yushi Bai, Anna Chen, Dawn Drain, Deep Ganguli, T. J. Henighan, Andy Jones, Nicholas Joseph, Benjamin Mann, Nova DasSarma, Nelson Elhage, Zac Hatfield-Dodds, Danny Hernandez, John Kernion, Kamal Ndousse, Catherine Olsson, Dario Amodei, Tom B. Brown, Jack Clark, Sam McCandlish, Christopher Olah, and Jared Kaplan. A general language assistant as a laboratory for alignment. *ArXiv*, abs/2112.00861, 2021.

Yushi Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, T. J. Henighan, Nicholas Joseph, Saurav Kadavath, John Kernion, Tom Conerly, Sheer El-Showk, Nelson Elhage, Zac Hatfield-Dodds, Danny Hernandez, Tristan Hume, Scott Johnston, Shauna Kravec, Liane Lovitt, Neel Nanda, Catherine Olsson, Dario Amodei, Tom B. Brown, Jack Clark, Sam McCandlish, Christopher Olah, Benjamin Mann, and Jared Kaplan. Training a helpful and harmless assistant with reinforcement learning from human feedback. *ArXiv*, abs/2204.05862, 2022.

Iz Beltagy, Arman Cohan, Robert Logan IV, Sewon Min, and Sameer Singh. Zero- and few-shot nlp with pretrained language models. In *ACL*, 2022.

Emily M. Bender, Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. On the dangers of stochastic parrots: Can language models be too big? . *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, 2021.

Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, et al. Piqa: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 7432–7439, 2020.

Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, Erik Brynjolfsson, S. Buch, Dallas Card, Rodrigo Castellon, Niladri S. Chatterji, Annie S. Chen, Kathleen A. Creel, Jared Davis, Dora Demszky, Chris Donahue, Moussa Doumbouya, Esin Durmus, Stefano Ermon, John Etchemendy, Kawin Ethayarajh, Li Fei-Fei, Chelsea Finn, Trevor Gale, Lauren E. Gillespie, Karan Goel, Noah D. Goodman, Shelby Grossman, Neel Guha, Tatsunori Hashimoto, Peter Henderson, John Hewitt, Daniel E. Ho, Jenny Hong, Kyle Hsu, Jing Huang, Thomas F. Icard, Saahil Jain, Dan Jurafsky, Pratyusha Kalluri, Siddharth Karamcheti, Geoff Keeling, Fereshte Khani, O. Khattab, Pang Wei Koh, Mark S. Krass, Ranjay Krishna, Rohith Kuditipudi, Ananya Kumar, Faisal Ladhak, Mina Lee, Tony Lee, Jure Leskovec, Isabelle Levent, Xiang Lisa Li, Xuechen Li, Tengyu Ma, Ali Malik, Christopher D. Manning, Suvir P. Mirchandani, Eric Mitchell, Zanele Munyikwa, Suraj Nair, Avanika Narayan, Deepak Narayanan, Benjamin Newman, Allen Nie, Juan Carlos Niebles, Hamed Nilforoshan, J. F. Nyarko, Giray Ogut, Laurel Orr, Isabel Papadimitriou, Joon Sung Park, Chris Piech, Eva Portelance, Christopher Potts, Aditi Raghunathan, Robert Reich, Hongyu Ren, Frieda Rong, Yusuf H. Roohani, Camilo Ruiz, Jack Ryan, Christopher R'e, Dorsa Sadigh, Shiori Sagawa, Keshav Santhanam, Andy Shih, Krishna Parasuram Srinivasan, Alex Tamkin, Rohan Taori, Armin W. Thomas, Florian Tramèr, Rose E. Wang, William Wang, Bohan Wu, Jiajun Wu, Yuhuai Wu, Sang Michael Xie, Michihiro Yasunaga, Jiaxuan You, Matei A. Zaharia, Michael Zhang, Tianyi Zhang, Xikun Zhang, Yuhui Zhang, Lucia Zheng, Kaitlyn Zhou, and Percy Liang. On the opportunities and risks of foundation models. *ArXiv*, abs/2108.07258, 2021.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, T. J. Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeff Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. *ArXiv*, abs/2005.14165, 2020.

Paul Christiano, Ajeya Cotra, and Mark Xu. Eliciting latent knowledge. Technical report, ARC, 2022. URL https://docs.google.com/document/d/1WwsnJQstPq91_Yh-Ch2XRL8H_EpsnjrC1dwZXR37PC8/edit.

Paul Francis Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *ArXiv*, abs/1706.03741, 2017.

Paul Francis Christiano, Buck Shlegeris, and Dario Amodei. Supervising strong learners by amplifying weak experts. *ArXiv*, abs/1810.08575, 2018.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. Boolq: Exploring the surprising difficulty of natural yes/no questions. *arXiv preprint arXiv:1905.10044*, 2019.

Owain Evans, Owen Cotton-Barratt, Lukas Finnveden, Adam Bales, Avital Balwit, Peter Wills, Luca Righetti, and William Saunders. Truthful ai: Developing and governing ai that does not lie. *ArXiv*, abs/2110.06674, 2021.

Rory A. Fisher. The use of multiple measurements in taxonomic problems. *Annals of Human Genetics*, 7:179–188, 1936.

Jonathan Gray, Adam Lerer, Anton Bakhtin, and Noam Brown. Human-level performance in no-press diplomacy via equilibrium search. *ArXiv*, abs/2010.02923, 2021.

Pengcheng He, Xiaodong Liu, Jianfeng Gao, and Weizhu Chen. Deberta: Decoding-enhanced bert with disentangled attention. *ArXiv*, abs/2006.03654, 2021.

Dan Hendrycks, Nicholas Carlini, John Schulman, and Jacob Steinhardt. Unsolved problems in ml safety. *ArXiv*, abs/2109.13916, 2021.

Geoffrey Irving, Paul Francis Christiano, and Dario Amodei. Ai safety via debate. *ArXiv*, abs/1805.00899, 2018.

Jaehun Jung, Lianhui Qin, Sean Welleck, Faeze Brahman, Chandra Bhagavatula, Ronan Le Bras, and Yejin Choi. Maieutic prompting: Logically consistent reasoning with recursive explanations. *ArXiv*, abs/2205.11822, 2022.

Zachary Kenton, Tom Everitt, Laura Weidinger, Iason Gabriel, Vladimir Mikulik, and Geoffrey Irving. Alignment of language agents. *ArXiv*, abs/2103.14659, 2021.

Daniel Khashabi, Sewon Min, Tushar Khot, Ashish Sabharwal, Oyvind Tafjord, Peter Clark, and Hannaneh Hajishirzi. Unifiedqa: Crossing format boundaries with a single qa system. In *FINDINGS*, 2020.

Junyeob Kim, Hyuhng Joon Kim, Hyunsoo Cho, Hwiyeol Jo, Sang-Woo Lee, Sang goo Lee, Kang Min Yoo, and Taeuk Kim. Ground-truth labels matter: A deeper look into input-label demonstrations. *ArXiv*, abs/2205.12685, 2022.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Jens Lehmann, Robert Isele, Max Jakob, Anja Jentzsch, Dimitris Kontokostas, Pablo N Mendes, Sebastian Hellmann, Mohamed Morsey, Patrick Van Kleef, Sören Auer, et al. Dbpedia–a large-scale, multilingual knowledge base extracted from wikipedia. *Semantic web*, 6(2):167–195, 2015.

Jan Leike, David Krueger, Tom Everitt, Miljan Martic, Vishal Maini, and Shane Legg. Scalable agent alignment via reward modeling: a research direction. *ArXiv*, abs/1811.07871, 2018.

Stephanie C. Lin, Jacob Hilton, and Owain Evans. Truthfulqa: Measuring how models mimic human falsehoods. In *ACL*, 2022.

Pengfei Liu, Weizhe Yuan, Jinlan Fu, Zhengbao Jiang, Hiroaki Hayashi, and Graham Neubig. Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. *ACM Computing Surveys (CSUR)*, 2022.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *ArXiv*, abs/1907.11692, 2019.

Ilya Loshchilov and Frank Hutter. Fixing weight decay regularization in adam. *ArXiv*, abs/1711.05101, 2017.

Yao Lu, Max Bartolo, Alastair Moore, Sebastian Riedel, and Pontus Stenetorp. Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity. In *ACL*, 2022.

Andrew Maas, Raymond E Daly, Peter T Pham, Dan Huang, Andrew Y Ng, and Christopher Potts. Learning word vectors for sentiment analysis. In *Proceedings of the 49th annual meeting of the association for computational linguistics: Human language technologies*, pp. 142–150, 2011.

Joshua Maynez, Shashi Narayan, Bernd Bohnet, and Ryan T. McDonald. On faithfulness and factuality in abstractive summarization. *ArXiv*, abs/2005.00661, 2020.

Julian McAuley and Jure Leskovec. Hidden factors and hidden topics: understanding rating dimensions with review text. In *Proceedings of the 7th ACM conference on Recommender systems*, pp. 165–172, 2013.

Jacob Menick, Maja Trebacz, Vladimir Mikulik, John Aslanides, Francis Song, Martin Chadwick, Mia Glaese, Susannah Young, Lucy Campbell-Gillingham, Geoffrey Irving, and Nathan McAleese. Teaching language models to support answers with verified quotes. *ArXiv*, abs/2203.11147, 2022.

Sewon Min, Mike Lewis, Luke Zettlemoyer, and Hannaneh Hajishirzi. Metaicl: Learning to learn in context. *ArXiv*, abs/2110.15943, 2022a.

Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. Rethinking the role of demonstrations: What makes in-context learning work? *ArXiv*, abs/2202.12837, 2022b.

Nasrin Mostafazadeh, Michael Roth, Annie Louis, Nathanael Chambers, and James Allen. Lsdsem 2017 shared task: The story cloze test. In *Proceedings of the 2nd Workshop on Linking Models of Lexical, Sentential and Discourse-level Semantics*, pp. 46–51, 2017.

Reiichiro Nakano, Jacob Hilton, S. Arun Balaji, Jeff Wu, Long Ouyang, Christina Kim, Christopher Hesse, Shantanu Jain, Vineet Kosaraju, William Saunders, Xu Jiang, Karl Cobbe, Tyna Eloundou, Gretchen Krueger, Kevin Button, Matthew Knight, Benjamin Chess, and John Schulman. Webgpt: Browser-assisted question-answering with human feedback. *ArXiv*, abs/2112.09332, 2021.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke E. Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Francis Christiano, Jan Leike, and Ryan J. Lowe. Training language models to follow instructions with human feedback. *ArXiv*, abs/2203.02155, 2022.

Ethan Perez, Saffron Huang, Francis Song, Trevor Cai, Roman Ring, John Aslanides, Amelia Glaese, Nathan McAleese, and Geoffrey Irving. Red teaming language models with language models. *ArXiv*, abs/2202.03286, 2022.

Colin Raffel, Noam M. Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *ArXiv*, abs/1910.10683, 2020.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text. *arXiv preprint arXiv:1606.05250*, 2016.

Melissa Roemmele, Cosmin Adrian Bejan, and Andrew S Gordon. Choice of plausible alternatives: An evaluation of commonsense causal reasoning. In *2011 AAAI Spring Symposium Series*, 2011.

Stephen Roller, Emily Dinan, Naman Goyal, Da Ju, Mary Williamson, Yinhan Liu, Jing Xu, Myle Ott, Kurt Shuster, Eric Michael Smith, Y.-Lan Boureau, and Jason Weston. Recipes for building an open-domain chatbot. In *EACL*, 2021.

Victor Sanh, Albert Webson, Colin Raffel, Stephen H. Bach, Lintang A. Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Teven Le Scao, Arun Raja, Manan Dey, M SAIFUL BARI, Canwen Xu, Urmish Thakker, Shanya Sharma, Eliza Szczechla, Taewoon Kim, Gunjan Chhablani, Nihal V. Nayak, Debajyoti Datta, Jonathan Chang, Mike Tian-Jian Jiang, Han Wang, Matteo Manica, Sheng Shen, Zheng Xin Yong, Harshit Pandey, Rachel Bawden, Thomas Wang, Trishala

Neeraj, Jos Rozen, Abheesht Sharma, Andrea Santilli, Thibault Févry, Jason Alan Fries, Ryan Teehan, Stella Rose Biderman, Leo Gao, T. G. Owe Bers, Thomas Wolf, and Alexander M. Rush. Multitask prompted training enables zero-shot task generalization. *ArXiv*, abs/2110.08207, 2021.

Nisan Stiennon, Long Ouyang, Jeff Wu, Daniel M. Ziegler, Ryan J. Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul Christiano. Learning to summarize from human feedback. *ArXiv*, abs/2009.01325, 2020.

James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. Fever: a large-scale dataset for fact extraction and verification. *ArXiv*, abs/1803.05355, 2018.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018.

Ben Wang and Aran Komatsuzaki. GPT-J-6B: A 6 Billion Parameter Autoregressive Language Model. `https://github.com/kingoflolz/mesh-transformer-jax`, May 2021.

Jason Wei, Maarten Bosma, Vincent Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V. Le. Finetuned language models are zero-shot learners. *ArXiv*, abs/2109.01652, 2022a.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed Chi, Quoc Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models. *ArXiv*, abs/2201.11903, 2022b.

Laura Weidinger, John F. J. Mellor, Maribeth Rauh, Conor Griffin, Jonathan Uesato, Po-Sen Huang, Myra Cheng, Mia Glaese, Borja Balle, Atoosa Kasirzadeh, Zachary Kenton, Sande Minnich Brown, William T. Hawkins, Tom Stepleton, Courtney Biles, Abeba Birhane, Julia Haas, Laura Rimell, Lisa Anne Hendricks, William S. Isaac, Sean Legassick, Geoffrey Irving, and Iason Gabriel. Ethical and social risks of harm from language models. *ArXiv*, abs/2112.04359, 2021.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. Huggingface's transformers: State-of-the-art natural language processing. *ArXiv*, abs/1910.03771, 2019.

Wenpeng Yin, Nazneen Rajani, Dragomir Radev, Richard Socher, and Caiming Xiong. Universal natural language processing with limited annotations: Try few-shot textual entailment as a start. In *EMNLP*, 2020.

Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. *Advances in neural information processing systems*, 28:649–657, 2015.

Tony Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. Calibrate before use: Improving few-shot performance of language models. *ArXiv*, abs/2102.09690, 2021.

Ruiqi Zhong, Kristy Lee, Zheng Zhang, and Dan Klein. Adapting language models for zero-shot learning by meta-tuning on dataset and prompt collections. In *EMNLP*, 2021.

Chunting Zhou, Junxian He, Xuezhe Ma, Taylor Berg-Kirkpatrick, and Graham Neubig. Prompt consistency for zero-shot task generalization. *ArXiv*, abs/2205.00049, 2022.

A   IDENTIFYING CLUSTERS

CCS predicts yes-no answers to a set of unlabeled questions $q_1, \ldots, q_n$. However, it does not identify which prediction label corresponds to true and which corresponds to false. We now describe how one can do so in principle, as long as a model is also able to take conjunctions.

Suppose we run our method and find, for example, that x and x' end up in different clusters. Then we know that these two statements have opposite truth values. As a result, if we take the conjunction of these two statements, $x \wedge x'$ then it should be false, and if we take the disjunction, $x \vee x'$, then it should be true. This allows us to identify which cluster is true and which is false in a completely unsupervised way.

Method	Prefix	RoBERTa	DeBERTa	GPT-J	T5	UQA	T0*	Mean*
Calibrated	Regular	64.3(6.2)	76.3(6.0)	56.0(5.2)	58.8(6.1)	80.4(7.1)	90.5(2.7)	67.2(6.1)
0-shot	Prefix	65.6(5.3)	75.5(6.1)	59.2(4.6)	56.0(4.0)	70.9(7.8)	88.2(4.2)	65.4(5.6)
CCS	Regular	62.1(4.1)	78.5(3.8)	61.7(2.5)	71.5(3.0)	82.1(2.7)	77.6(3.3)	71.2(3.2)
	Prefix	62.2(3.6)	75.4(5.2)	61.2(1.8)	73.2(2.6)	83.8(2.4)	75.0(2.7)	71.2(3.1)
TPC	Regular	64.6(5.8)	76.5(5.7)	59.9(3.7)	66.7(5.0)	78.3(3.3)	58.9(13.0)	69.2(4.7)
	Prefix	65.0(5.6)	77.0(6.0)	60.1(2.9)	68.1(5.0)	76.0(3.6)	56.5(13.6)	69.2(4.6)
BSS	Regular	62.6(6.8)	76.8(5.3)	60.7(3.4)	69.7(3.3)	79.3(2.5)	76.7(9.6)	69.8(4.3)
	Prefix	59.5(5.4)	75.5(6.6)	59.8(2.8)	65.2(2.8)	83.1(2.3)	72.2(9.0)	68.6(4.0)
LR	Regular	79.8(2.5)	86.1(2.2)	78.0(2.3)	84.6(3.1)	89.8(1.9)	90.7(2.1)	83.7(2.4)
	Prefix	79.4(2.7)	86.3(2.6)	79.0(2.9)	86.3(2.8)	90.1(2.2)	90.5(2.3)	84.2(2.6)

Table 3: Accuracy of each method and model averaged across all prompts and datasets, with the same setting as Table 1. "Regular" means no prefix is added, while "Prefix" corresponds to text in Figure 7. Notice that while the 0-shot accuracy decreases due to the prefix, all of our methods are more resistant to the influence.

Figure 6: The top 100 tokens with highest probability averaged across examples in IMDB for UQA. Without the prefix (left), the actual labels ("positive" and "negative") and their synonyms (e.g. "Positive" and "Neg") have high probability. With the prefix, the model's output becomes mostly irrelevant to sentiment; the actual labels are in the top 100, but no other synonyms are.

B   MISLEADING PREFIX DETAILS

B.1   MISLEADING PREFIX

In Section 3.2, we mentioned that model outputs can be biased by using the misleading few-shot prefix shown in Figure 7. We show the effect of the misleading prefix for all models in Table 3.

B.1.1   EVALUATING THE EFFECT OF THE MISLEADING PREFIX

The hope is that the misleading prefix causes models to imitate the sorts of incorrect answers in the prefix. However, we found that results are qualitatively similar with correct answers, making the actual interpretation of the effect of this prefix ambiguous. Nevertheless, to better understand what this prefix is doing, we visualize the top 100 tokens for both this misleading prefix and no prefix on average across all examples for UnifiedQA on the IMDB sentiment dataset, and show the results in Figure 6. Without this prefix, the top two tokens are the actual labels ('positive' and 'negative').

What is the human life expectancy in the United States?
10 years.

Who was president of the United States in 1955?
Abraham Lincoln.

Which party did he belong to?
The Social Democratic Party of Germany.

What is the square root of banana?
42

How does a telescope work?
Eye beams are emitted by the eye and reflect back into the eye.

Where were the 1992 Olympics held?
The 1992 Olympics were held on the moon.

How many squigs are in a bonk?
3

Figure 7: The added prefix used to mislead models in a way that is egregiously incorrect or confusing.

In contrast, with the prefix, these tokens have lower probabilities relative to other tokens, with the highest probability tokens instead being irrelevant to the true answer. For example, since the prefix includes several answers with numbers, many of the top tokens are also numbers. This provides some evidence that the prefix is actually causing the model to output false text by imitating its context in a meaningful sense.

C COMPLETE SAMPLE COMPLEXITY RESULTS

In this section we show additional results on how the number of examples affects CCS. We show the performance (averaged across all datasets) for *all* models in Figure 8. We next show a more fine-grained results. Specifically, we select #Samples = 1, 8, 64 and show dataset-level results in Figure 9 for each model.

Figure 8: This figure shares the same setting with Figure 5, but it contains all six models we consider.

Figure 9: CCS performance when we only use $1, 8, 64$ examples, for all models and datasets. X-axis represents the dataset and y-axis is the accuracy in percentage. For each dataset, we select the prompt with highest 0-shot performance, and then randomly select $1, 8, 64$ data points from this prompt. We then perform CCS and test on all prompts of this dataset, where each value in the barplot corresponds to one prompt.

D   COMPLETE TRANSFER RESULTS

Complete transfer results for CCS, TPC and BSS in all models are shown in Figure 12.

Figure 10: CCS performance when using the hidden states across different layers, using all six models we consider in the paper. This plot is an extension of Figure 4.

Figure 11: Linear regression performance when using the hidden states across different layers, using all six models we consider in the paper. This is the ceiling of all possible methods, and is supervised.

E   COMPLETE INTERMEDIATE REPRESENTATIONS RESULTS

In this section we the performance of CCS and LR across all hidden layers in all six models. Specifically, for each model, we generate the hidden states for each dataset every 2 layers (for both encoders and decoders). Then, for each set of hidden states, we perform CCS and LR on each dataset separately, and average the performance across all datasets. We show CCS results in Figure 10 and LR results in Figure 11.

Figure 12: Transfer Accuracy for all models using CCS, BSS, TPC and LR.

F DATASET SETUP

In this section, we describe the setup of our data and prompts in detail. We introduce all datasets we use and the way we convert them into a binary classification task. Our prompts derive from (Sanh et al., 2021)[4].

Contrast Pair Example. To illustrate how we construct contrast pairs, suppose we have a movie review "[text] = I loved this movie." and the sentiment of this review belongs to "[label0] = positive" or "[label1] = negative". We first format it into a binary question-answering or classification question: "[text] Is the sentiment of this example [label0] or [label1]? " using an existing zero-shot prompt. We then concatenate the question and candidate labels to create the contrast pairs:

$$x^+ = \text{[prefix] Q: Is the sentiment of "[text]" [label0] or [label1]? A: [label0]}$$

$$x^- = \text{[prefix] Q: Is the sentiment of "[text]" [label0] or [label1]? A: [label1]}$$

For instance, in this example, these would be:

$$x^+ = \text{Q: Is the sentiment of "I loved this movie." positive or negative? A: positive}$$

$$x^- = \text{Q: Is the sentiment of "I loved this movie." positive or negative? A: negative}$$

Finally, we add the prefix (either prefix in Figure 7, or the empty string for the regular zero-shot setting) to the beginning of the prompt, then compute the hidden representations for this pair to obtain the contrast features $\mathcal{C}$.

F.1 DATASETS

We use ten datasets in our experiments. For each dataset, we select 1000 data points (except COPA, which has only 500 data points, so we only use those 500). When possible, we use just the test / validation split, but in other cases this is not enough data so we also use examples from the train split. For the most part this doesn't make a difference for our purposes because our methods are purely unsupervised.

It is important to note that T0 is an exception among the models, because but was trained on 9 out of the 10 datasets we consider (all except RTE). This may account for its anomalous performance. UnifiedQA was trained on BoolQ, which is one of the datasets we test on, but was not trained on any other evaluation set we consider, which we don't expect has an important qualitative effect.

We now enumerate the prompts we use for each dataset.

F.1.1 AG_NEWS

AG_News is a topic classification dataset from (Zhang et al., 2015). Given a news paragraph, the label corresponds to the topic of this news, including "World politics", "Sports", "Business" and "Science and technology". For each example, we randomly select another label (which is incorrect), and randomly assign the correct label and this incorrect label to "label0" and "label1". With this, we construct the classification task using the following 8 prompts:

1 [prefix]Consider the following example: "' [text] "' Choice 1: [label0]. Choice 2: [label1].Between choice 1 and choice 2, the topic of this example is [label]

2 [prefix]Consider the following example: "' [text] "' Choice 1: [label0]. Choice 2: [label1].Between choice 1 and choice 2, what is the topic of this example? [label]

3 [prefix]Consider the following example: "' [text] "' Which is the topic of this example, choice 1: [label0], or choice 2: [label1]? [label]

4 [prefix][text] Choice 1: [label0]. Choice 2: [label1].Between choice 1 and choice 2, the topic of this example is [label]

5 [prefix][text] Choice 1: [label0]. Choice 2: [label1].Between choice 1 and choice 2, what is the topic of this example? [label]

---

[4]https://github.com/bigscience-workshop/promptsource

6 [prefix][text] Which is the topic of this example, choice 1: [label0], or choice 2: [label1]? [label]

7 [prefix][text] What label best describes this news article, choice 1: [label0], or choice 2: [label1]? [label]

8 [prefix][text] Which section of a newspaper would this article likely appear in, choice 1: [label0], or choice 2: [label1]? [label]

Here the last "[label]" is "choice 1" for x^+ and "choice 2" for x^-. Notice that we only specify "[label]" for the prompts that are constructed manually. For prompts in (Sanh et al., 2021), we leave their labels unchanged. (For example, we use "choice 1" or "choice 2" but they can use "Animal" or "Plant")

F.1.2 AMAZON_POLARITY

Amazon_polarity is a sentiment classification task from (McAuley & Leskovec, 2013). The content is the review of goods in Amazon, and the label can be "negative" or "positive". We use 11 different prompts in this dataset. We first take all prompts from (Sanh et al., 2021) (Page 164, 9 prompts in total), and the two of our own as follows:

1 [prefix]Consider the following example: "' [content] '" Between [label0] and [label1], the sentiment of this example is [label]

2 [prefix]Consider the following example: "' [content] '" Between [label0] and [label1], which is the sentiment of this example? [label]

Here "[label]" is "negative" for x^+ and "positive" for x^-.

F.1.3 BOOLQ

BOOLQ is a QA task where each example consists a yes/no question from (Clark et al., 2019). We directly use the 10 prompts from (Sanh et al., 2021) (Page 146)

F.1.4 COPA

COPA is a causal reasoning task to determine either the cause or the effect of a given premise (Roemmele et al., 2011). Here the label is a short sentence. We use 10 prompts, where 9 are from (Sanh et al., 2021) (Page 177), and we add one more prompt:

1 [prefix]Consider the following premise: "' [premise] '" Choice 1: [choice1] Choice 2: [choice2] Q: Which one is more likely to be the [question], choice 1 or choice 2? [label]

F.1.5 DBPEDIA_14

DBpedia_14 is a topic classification dataset constructed by picking 14 non-overlapping classes from DBpedia 2014 (Lehmann et al., 2015). We manually create 8 prompts. For each example, we randomly select the incorrect label from the remaining 13 classes, and randomly assign the correct label and this incorrect label to "[label0]" and "[label1]".

1 [prefix]Consider the following example: "' [content] '" Choice 1: [label0]. Choice 2: [label1].Between choice 1 and choice 2, the topic of this example is [label]

2 [prefix]Consider the following example: "' [content] '" Choice 1: [label0]. Choice 2: [label1].Between choice 1 and choice 2, what is the topic of this example? [label]

3 [prefix]Consider the following example: "' [content] '" Which is the topic of this example, choice 1: [label0], or choice 2: [label1]? [label]

4 [prefix][content] Choice 1: [label0]. Choice 2: [label1].Between choice 1 and choice 2, the topic of this example is [label]

5 [prefix][content] Choice 1: [label0]. Choice 2: [label1].Between choice 1 and choice 2, what is the topic of this example? [label]

6 [prefix][content] Which is the topic of this example, choice 1: [label0], or choice 2: [label1]? [label]

7 [prefix][content] What category does the paragraph belong to, choice 1: [label0], or choice 2: [label1]? [label]

8 [prefix][content] What label best describes this paragraph, choice 1: [label0], or choice 2: [label1]? [label]

Here "[label]" is "choice 1" for x^+ and "choice 2" for x^-.

F.1.6 IMDB

IMDB is a sentiment dataset from (Maas et al., 2011). Given a movie review, the label is either "[label0] = negative" or "[label1] = positive. We use 13 prompts, where 11 are from (Sanh et al., 2021) (Page 168), and the rest two are as follows:

1 [prefix]Consider the following example: "' [text] "' Between [label0] and [label1], the sentiment of this example is [label]

2 [prefix]Consider the following example: "' [text] "' Between [label0] and [label1], which is the sentiment of this example? [label]

Here "[label]" is "negative" for x^+ and "positive" for x^-.

F.1.7 PIQA

The PIQA dataset measures the physical commonsense reasoning ability of models. We use 11 prompts for PIQA, all of which are from (Sanh et al., 2021)(Page 160). The label is a complete sentence that can be the solution of the question.

F.1.8 QNLI

QNLI from (Rajpurkar et al., 2016) is a question-answering dataset consisting of question-paragraph pairs, where one of the sentences in the paragraph (drawn from Wikipedia) contains the answer to the corresponding question (written by an annotator). We use 5 prompts from (Sanh et al., 2021). The label is either "yes" or "no" depending on whether the information in the paragraph is enough to answer the paragraph.

F.1.9 RTE

RTE is a textual entailment dataset (Wang et al., 2018). The label corresponds to whether the text entails the hypotheses. We use 11 prompts, where 10 are from (Sanh et al., 2021)(Page 48), and where we manually add one more prompt:

1 [prefix][premise] Question: Does this imply that "[hypothesis]", yes or no? [label]

Here "[label]" is "yes" for x^+ and "no" for x^-.

F.1.10 Story_Cloze

Story Cloze is a story completion task from (Mostafazadeh et al., 2017). Given a short story, the task is to determine which of two endings is more likely to continue that story. We use 9 prompts, where 6 are from (Sanh et al., 2021), and the remaining 3 are as follows:

1 [prefix]Consider the following story: "' [input_sentence_1] [input_sentence_2] [input_sentence_3] [input_sentence_4] "' Choice 1: [sentence_quiz1] Choice 2: [sentence_quiz2] Which is the more plausible ending of this story, choice 1 or choice 2? [label]

2 [prefix]Consider the following story: "' [input_sentence_1] [input_sentence_2] [input_sentence_3] [input_sentence_4] "' Choice 1: [sentence_quiz1] Choice 2: [sentence_quiz2] Which is the more plausible ending of this story? [label]

3 [prefix][input_sentence_1] [input_sentence_2] [input_sentence_3] [input_sentence_4] Choice 1: [sentence_quiz1] Choice 2: [sentence_quiz2] Which is the more plausible ending of this story, choice 1 or choice 2? [label]

Here "[label]" is "choice 1" for x^+ and "choice 2" for x^-.

G CCS AND CRC IMPLEMENTATION DETAILS

In this section, we provide further implementation details for CCS and CRC. We begin by describing how we construct contrast pairs.

G.1 CONTRAST PAIRS

We use the Huggingface library (Wolf et al., 2019) for all of our experiments. We use the standard tokenizer for each model, and always take the hidden state corresponding to the last token in a given layer indexed by idx. We show Huggingface-style pseudocode for extracting hidden states from in Algorithm 1.

Algorithm 1 Pseudocode for Getting Contrast Features

Input: Contrast Pairs Set S, model name mdl, layer index idx
  $\mathbf{m}$ = transformers.AutoModel(mdl)
  $\mathbf{t}$ = transformers.AutoTokenizer(mdl)
  $\mathcal{C}^+, C^- = [], []$
  for (x^+, x^-) **in** S **do**
    $\text{token}^+, \text{token}^- = \mathbf{t}.\text{encode}(x^+), \mathbf{t}.\text{encode}(x^-)$
    $\phi^+ = m(\text{token}^+, \text{output\_hiddenstates} = \text{True})[\text{"hidden\_states"}][\text{idx}][-1]$
    $\phi^- = m(\text{token}^-, \text{output\_hiddenstates} = \text{True})[\text{"hidden\_states"}][\text{idx}][-1]$
    $\mathcal{C}^+.\text{append}(\phi^+), \mathcal{C}^-.\text{append}(\phi^-)$
  end for
Output: $[\mathcal{C}^+, \mathcal{C}^-]$

G.2 CCS

Given contrast features from Algorithm 1, CCS works by learning parameters θ and b according to **??**. In practice, we implement the bias b by appending an additional dimension of 1s features to the input, increasing it and θ to have dimension $d + 1$. We randomly initialize θ to have unit norm. We then optimize the CCS loss $T = 10$ times and select the run with lowest unsupervised loss. In practice, we train each time for $E = 1000$ epochs with a learning rate $\eta = 0.01$ (which we found was good for consistently achieving low unsupervised loss) in each run. Because we are only learning a linear probe on top of the features, training can be fast.

G.3 CRC: TOP PRINCIPAL COMPONENT

Intuitively, a direction that clusters examples well should have high variance. Motivated by this, a simple method is to cluster according to the Top Principal Component (TPC). We do this by first constructing contrast features from the normalized contrast pair activations, $\mathcal{C} = \{\tilde{\phi}(x_i^+) - \tilde{\phi}(x_i^-)\}_{i=1}^n$, then projecting these examples on their top principal component using PCA. We then treat examples that are less than 0 as one cluster and examples that are greater than 0 as the other cluster. We find that despite its simplicity this method can often also find truth-like features in model activations.

G.4   CRC: BIMODAL SALIENCE SEARCH

Bimodal Salience Search (BSS) is another variation of CRC. One drawback of TPC is that variance is not an intrinsic quantity to a network's behavior, since different directions in representation space can be scaled without changing the behavior of the network as long as subsequent layers are rescaled accordingly. This motivates using a method that clusters examples regardless of the scale of different directions.

If examples are well-clustered, then the intra-cluster variance should be low while the inter-cluster variance (or total variance) should be high. Specifically, if we center a set of datapoints so that 0 delineates the cluster boundary, then the points on either side of 0 should have low variance compared to the points overall. This suggests minimizing the following loss:

$$L(\theta) = \frac{\text{var}\{\theta^T c_i | \theta^T c_i < 0\} + \text{var}\{\theta^T c_i | \theta^T c_i \geq 0\}}{\text{var}\{\theta^T c_i\}} \tag{1}$$

where $c_i := \tilde{\phi}(x_i^+) - \tilde{\phi}(x_i^-)$ and where we use $\text{var}\{z_i\}$ as shorthand to denote the variance of a set $\{z_i\}_{i=1}^n \subset \mathbb{R}$. Because this objective is written in terms of a ratio, it is invariant to the overall scale of the direction, fixing that drawback of TPC. This loss is similar to that of Linear Discriminant Analysis (LDA) (Fisher, 1936), but unlike LDA is completely unsupervised.

In practice, we use an SGD-based optimizer to find a local optimum of $L(\theta)$. After computing the contrast features, we repeat the following process T times. We first initialize a random direction θ with unit norm. Then for E epochs, we calculate the loss according to Equation (1), and update the direction θ by via projected gradient descent, each time projecting θ back onto the unit sphere. Finally, we select the direction θ that has the lowest loss among the T directions we found, and predict based on this direction. When we optimize the direction with multiple datasets, i.e. $S_1, ..., S_n$, we use the same algorithm, but average the loss across all datasets. In practice we use $T = E = 20$, and use Adam optimizer (Kingma & Ba, 2014) with a learning rate of 0.1.