Overlapping Schwarz Attention: Hierarchical Attention via Domain Decomposition

Abstract

We propose a hierarchical attention mechanism based on two-level overlapping Schwarz domain decomposition. The method is motivated by domain decomposition methods in partial differential equations which combine local subdomain corrections with a coarse level that communicates global, long-range information. We test its usefulness in the context of finite-dimensional operator learning using a simple, one-dimensional diffusion problem. Although elementary, this problem provides a controlled sequence-to-sequence setting in which the exact nonlocal solution operator is known. After discretization, learning the solution operator amounts to approximating the inverse of a symmetric positive definite matrix. As a baseline, we use a global softmax-free low-rank attention operator of the form QK^T. The proposed construction replaces this global factorization by a two-level additive structure: local low-rank attention blocks on overlapping subdomains are combined with a coarse attention block. The resulting operator has the form

$$M_\theta^{-1} = \Phi Q_0 K_0^T \Phi^T + \sum_{i=1}^{N} R_i^T D_i^{1/2} Q_i K_i^T D_i^{1/2} R_i.$$

Here, R_i restricts to an overlapping subdomain, D_i is a partition-of-unity weight, and Φ is a coarse interpolation matrix. Numerical experiments for synthetic Fourier right-hand sides indicate that the domain-decomposition attention operator can converge faster and can give more accurate approximations than a global low-rank attention baseline while using significantly fewer parameters.

1 Introduction

The Transformer architecture, with its self-attention mechanism (Vaswani et al., 2017), has been central to the success of modern large language models. Unlike earlier recurrent neural networks (RNNs), attention enables the direct and parallel modeling of contextual dependencies across long sequences. Formally, attention can be understood as a family of learnable interaction operators whose efficiency arises from the exploitation of low-rank factorizations in the computation of token interactions.

A standard self-attention layer starts from an input matrix

$$X \in \mathbb{R}^{m \times d_{\text{in}}},$$

where the rows correspond to m tokens, grid points, or degrees of freedom, and the d_{in} columns contain the associated features. The query, key, and value matrices are obtained by learned linear mappings,

$$Q = XW_Q, \qquad K = XW_K, \qquad V = XW_V, \tag{1}$$

Two large language models were used independently to generate two separate code prototypes, which were cross-checked against each other. Large language models were also used for postprocessing and manuscript preparation. All generated code and text were reviewed, tested, and verified by the authors, who take full responsibility for the contents of this paper.

where the entries of $W_Q, W_K \in \mathbb{R}^{d_{\text{in}} \times d_k}$, $W_V \in \mathbb{R}^{d_{\text{in}} \times d_v}$ are the learnable parameters.

The standard, scaled dot-product attention operator with softmax is then

$$\text{Att}_{\text{softmax}}(X) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right) V,$$

where d_k is the number of columns of W_Q and W_K, and softmax is applied row-wise (Vaswani et al., 2017). The matrix $QK^T \in \mathbb{R}^{m \times m}$ contains pairwise interactions between the m tokens or, in our case, (interior) grid points. The parameter d_k corresponds to the rank r of the low-rank factorization QK^T, i.e.,

$$r = \text{rank}(QK^T) \leq d_k. \tag{2}$$

In this work, we will omit the softmax operator. We also omit the $\sqrt{d_k}$ scaling, which controls the magnitude of the dot products before applying softmax. Thus, we have the linear attention operator

$$\text{Att}(X) = \left(QK^T\right) V = \left(XW_Q W_K^T X^T\right) XW_V.$$

Our setting allows us to focus on whether methods from domain decomposition for partial differential equations (Toselli and Widlund, 2005; Smith et al., 1996; Lions, 1988) can be used to design more efficient attention operators.

Our model problem is a discretized one-dimensional Poisson problem. After discretization, the solution map is the inverse of the sparse system matrix. A global low-rank attention layer can represent a rank-d_k approximation of this inverse. However, elliptic inverses have multiscale structure: local coupling is most important, but long-range low-frequency components must also be represented. This is the structure exploited, e.g., by two-level Schwarz domain decomposition methods for partial differential equations.

In our two-level attention mechanism the fine level consists of local low-rank attention blocks on overlapping subdomains. The coarse level consists of an attention block acting on a small interface-hat coarse basis. The construction is not meant as a replacement for classical solvers. Rather, it is a controlled experiment to demonstrate that domain decomposition concepts can provide a useful structure, e.g., for operator learning methods or, potentially, natural language processing (NLP). Well-known works in operator learning include the FEONet by Lee et al. (2025), the DeepONet by Lu et al. (2021) and the Fourier Neural Operator (FNO) by Li et al. (2021). Modern overlapping Schwarz methods are highly scalable parallel methods for solving partial differential equations (Jolivet et al., 2012; Heinlein et al., 2022; Deparis et al., 2016; Cai et al., 1998), and may help to parallelize attention similarly to other known approaches in NLP (Sun et al., 2025; Acharya et al., 2025; Lu et al., 2025; Tang et al., 2024).

We note that hierarchical forms of attention have been studied previously in different settings (Amizadeh et al., 2025; Han et al., 2023; Seo et al., 2016). These approaches are not directly comparable to the one proposed here, since both the underlying mechanisms and the intended applications are different. In the present work, the hierarchy is induced by an overlapping domain decomposition and is used to structure a softmax-free attention approximation of elliptic solution operators. Hierarchical methods in NLP include the works by He et al. (2024), Chalkidis et al. (2022), Hu et al. (2021), and Yang et al. (2016).

After completion of a first draft of this manuscript, we became aware of the closely related work by Cao (2021), which first used linear attention for operator learning. Our approach takes a further step in two respects. First, by an appropriate choice of the input matrix X and the projection matrices W_Q, W_K, and W_V, the trainable parameters are identified directly with the factors Q and K, so that the learned operator takes the simple form QK^T, rather than appearing only through the composite expression $XW_Q W_K^T X^T$. Second, building on this interpretation, we introduce Schwarz attention, a new hierarchical attention architecture derived from a two-level overlapping Schwarz domain decomposition. It combines local low-rank attention operators with a global coarse correction and thereby transfers the central local-to-global mechanism of domain decomposition to attention-based operator learning. In the next section, we specify the choice of X, W_Q, W_K, and W_V that leads to this direct parametrization of the learned operator.

2 One-Dimensional Diffusion Model Problem

We consider the Poisson problem in one dimension

$$-u''(x) = f(x), \qquad x \in (0,1) \subset \mathbb{R}^1, \qquad u(0) = u(1) = 0. \tag{3}$$

Let n denote the number of uniform line elements on $[0,1]$. Then $n+1$ is the number of grid points, and $n-1$ is the number of interior grid points. Let

$$x_j = \frac{j}{n}, \qquad j = 1, \dots, (n-1). \tag{4}$$

Using the standard finite difference gives

$$Au = f, \quad A = \frac{1}{h^2} \begin{pmatrix} 2 & -1 & & & \\ -1 & 2 & -1 & & \\ & \ddots & \ddots & \ddots & \\ & & -1 & 2 & -1 \\ & & & -1 & 2 \end{pmatrix} \in \mathbb{R}^{(n-1)\times(n-1)}, \qquad h = \frac{1}{n}. \tag{5}$$

The exact discrete solution operator is therefore $f \mapsto u = A^{-1} f$.

The learning task in this paper is to approximate A^{-1} by a trainable structured operator M_θ^{-1}, where θ denotes the parameters. For our one-dimensional model problem, we represent $(n-1)$ active degrees of freedom by a one-hot encoding, rather than by their physical coordinates, and augment this representation by the right-hand side f; i.e., our feature matrix is

$$X = [I_{n-1}, f] = \begin{pmatrix} 1 & 0 & \dots & 0 & f_1 \\ 0 & \ddots & \ddots & \vdots & f_2 \\ \vdots & \ddots & \ddots & 0 & \vdots \\ 0 & \dots & 0 & 1 & f_{n-1} \end{pmatrix} \in \mathbb{R}^{(n-1)\times n},$$

where I_{n-1} is the identity matrix of size $n-1$. Thus, $d_{\text{in}} = n$, i.e., the first $n-1$ columns identify the (interior) grid points, while the last column contains the values of the right-hand side f.

Next, the weight matrix W_V is chosen as a fixed matrix which extracts the right-hand side channel from X,

$$V = XW_V = f \in \mathbb{R}^{n-1}, \qquad W_V^T = (0, \dots 0, 1) \in \mathbf{R}^n.$$

As a result, in our context, W_V does not contain learnable parameters but is a fixed matrix.

We then define W_Q and W_K by

$$W_Q = \begin{pmatrix} \Theta_Q \\ 0 \end{pmatrix}, \qquad W_K = \begin{pmatrix} \Theta_K \\ 0 \end{pmatrix},$$

where the matrices Θ_Q and Θ_K contain the learnable parameters in W_Q and W_K. Here, $\Theta_Q, \Theta_K \in \mathbb{R}^{n-1 \times d_k}$, and the zeros in W_Q and W_K denote one zero row. The identity block in X resulting from the one-hot coding of the grid points then extracts Θ_Q and Θ_K from W_Q and W_K, i.e.,

$$Q = XW_Q = \Theta_Q, \qquad K = XW_K = \Theta_K.$$

Now, the entries of Q and K^T are the learnable parameters.

As a result of our definitions, in the softmax-free linear setting considered in this paper, the low rank factorization QK^T is applied directly to the right-hand side, i.e., defining $u_\theta = \text{Att}(X)$, we obtain

$$u_\theta = \left(QK^T\right) V = QK^T f. \tag{6}$$

The learning task is therefore to find the attention factors such that

$$QK^T \approx A^{-1}, \tag{7}$$

where A is the finite-difference or finite element Poisson matrix.

Remark 1. *Although our numerical experiments are carried out for a one-dimensional elliptic model problem, the construction should not be viewed as being tied to this particular problem setting. Rather, the model problem provides a controlled setting in which a nonlocal sequence-to-sequence operator is known exactly and can therefore be used to study the effect of hierarchical, domain-decomposition-induced attention. The introduction of hierarchy in attention has been an active area of research and has allowed long contexts in LLMs; also see the discussion in Section 9. Thus, our study may be relevant more broadly for one-dimensional sequence models, where local interactions and long-range couplings have to be represented simultaneously. The application of overlapping Schwarz attention to NLP is future work. Recent work has investigated the decay of token influence with distance in NLP (Brändel et al., 2026), helping to bridge the gap to settings in partial differential equations where such decay is known.*

3 Softmax-Free Attention as Low-Rank Approximate Inverse

The baseline for our hierarchical attention is the global low-rank linear attention applied to operator learning,

$$M_{\theta,\text{global}}^{-1} = QK^T, \qquad Q, K \in \mathbb{R}^{(n-1) \times r_g}. \tag{8}$$

Applied to a right-hand side f, the predicted solution is

$$u_\theta = QK^T f; \tag{9}$$

see (6). The operator's rank is limited by the rank parameter denoted r_g.

Remark 2. *Since A^{-1} is symmetric positive definite, one could restrict to a symmetric factorization BB^T. We deliberately do not impose this constraint here. Both the global and the domain-decomposition models use independent factors Q and K. This gives the optimizer a less constrained parameterization while still allowing the learned operator to approximate a symmetric inverse.*

Remark 3. *Although the approximate inverse is written as QK^T, the dense matrix QK^T is typically not formed explicitly. In all computations, the action on a right-hand side f can be evaluated as $Q(K^T f)$, which costs $O((n-1)r_g)$ for a single right-hand side instead of explicitly forming the $(n-1) \times (n-1)$ matrix (QK^T).*

4 Hierarchical Attention by Two-Level Overlapping Schwarz Domain Decomposition

4.1 Overlapping Subdomains and Coarse Hat Functions

The subdomain construction used in our implementation is based on a decomposition of the edges of the one-dimensional chain graph. Each edge corresponds to a line element connecting two neighboring degrees of freedom. Thus, the partition is element-based rather than degree-of-freedom-based. Consequently, neighboring nonoverlapping subdomains share an interface degree of freedom before overlap is added. This follows the standard finite element viewpoint. Figure 1a shows the nonoverlapping partition of the line elements resulting in two index sets $\mathcal{I}_1$ and $\mathcal{I}_2$ defining two nonoverlapping subdomains and the interface.

In standard overlapping Schwarz methods, often generous overlap is introduced to reduce boundary effects. In all our numerical experiments, however, we use a relatively small overlap of $n_\delta = 2$ since this seemed to be sufficient. Hence, two neighboring overlapping subdomains have $2n_\delta + 1 = 5$ common grid points; Figure 1b illustrates the corresponding overlapping index sets for overlap two.

Let $\mathcal{I}_i$ be the index set associated with the i-th overlapping subdomain and $n_i = |\mathcal{I}_i|$. Then $R_i \in \mathbb{R}^{n_i \times (n-1)}$ denotes the Boolean restriction matrix that extracts the degrees of freedom in $\mathcal{I}_i$ from a global vector in $\mathbb{R}^{n-1}$. Equivalently, $R_i u$ is the subvector of u associated with the overlapping subdomain $\mathcal{I}_i$, while R_i^T extends a local vector by zero to the global index set.

The coarse space used in our experiments is spanned by interface-centered hat functions. More precisely, the coarse degrees of freedom are placed at the interface nodes of the nonoverlapping partition, and the corresponding hat functions attain their maxima at these nodes while decreasing linearly in the adjacent subdomains.

(a) Nonoverlapping edge partition. The node index sets meet in the interface p_5.

(b) Overlap two: each subdomain is enlarged by two neighboring graph edges. The common nodes are $p_3, \ldots, p_7$; the original interface node is p_5.

Figure 1: Nonoverlapping and overlapping node index sets for two subdomains.

We also investigated piecewise constant partition-of-unity basis functions. Such basis functions perform a uniform averaging over each subdomain and are closely related to mean pooling, one of the simplest token aggregation mechanisms in Transformer models (Reimers and Gurevych, 2019). They are also conceptually related to the coarse token representations employed in hierarchical Transformer architectures such as MoBA and FCA (Lu et al., 2025; Zhao et al., 2022). In contrast, the interface-centered hat basis performs a distance-weighted averaging. Since these alternative coarse bases did not outperform the interface-hat basis in our experiments, they are not considered further.

4.2 Partition of Unity in the Overlap

In the overlap, several subdomains may cover the same degree of freedom. Let m_j be the number of overlapping subdomains containing grid point j. On subdomain i, define the diagonal weight matrix

$$D_i = \text{diag}\left(1/m_j : j \in \mathcal{I}_i\right). \tag{10}$$

In the decompositions used in the experiments below, each grid point in an overlap region is covered by two neighboring subdomains, so that $m_j = 2$ there, while $m_j = 1$ outside the overlap regions.

Then the weights form a discrete partition of unity: $\sum_{i=1}^{N} R_i^T D_i R_i = I_{n-1}$. In the experiments below we use the symmetric overlap weighting

$$R_i^T D_i^{1/2} G_i D_i^{1/2} R_i. \tag{11}$$

4.3 Local Attention Blocks

On each of the N overlapping subdomains, we use a local low-rank attention operator

$$G_i = Q_i K_i^T, \qquad Q_i, K_i \in \mathbb{R}^{n_i \times r_\ell}, \tag{12}$$

where r_ℓ denotes the rank of the local attention blocks. The corresponding fine-level operator is

$$M_{\theta,\text{loc}}^{-1} = \sum_{i=1}^{N} R_i^T D_i^{1/2} Q_i K_i^T D_i^{1/2} R_i. \tag{13}$$

This operator is sparse in the sense that each learned block acts only on an overlapping subdomain.

4.4 Coarse Attention Block

In Poisson problems, local blocks alone cannot represent global low-frequency components. We therefore add a coarse attention space. Let

$$\Phi \in \mathbb{R}^{(n-1) \times n_0} \tag{14}$$

be a coarse interpolation matrix, i.e., Φ interpolates coarse coefficients to the fine grid. Its transpose Φ^T is used as the corresponding restriction to the coarse space.

In the experiments below, Φ consists of interface hat functions; see Figure A.8 in the lower rightmost panel. For N subdomains this gives $n_0 = N - 1$ coarse basis functions, one associated with each pair of neighboring disjoint index sets.

We denote the rank of the coarse attention by r_0. The coarse attention operator is

$$G_0 = Q_0 K_0^T, \qquad Q_0, K_0 \in \mathbb{R}^{n_0 \times r_0}. \tag{15}$$

Interpolated to the fine grid, the coarse contribution is

$$M_{\theta,\text{coarse}}^{-1} = \Phi Q_0 K_0^T \Phi^T. \tag{16}$$

4.5 Two-Level Additive Hierarchical Attention Mechanism

Combining the fine and coarse levels gives the proposed hierarchical attention operator

$$M_{\theta,\text{Schwarz}}^{-1} = \Phi Q_0 K_0^T \Phi^T + \sum_{i=1}^{N} R_i^T D_i^{1/2} Q_i K_i^T D_i^{1/2} R_i. \tag{17}$$

This is the central construction of the paper. It can be interpreted as a two-level additive Schwarz-inspired attention layer. The term "hierarchical" refers to the coexistence of local fine-scale attention blocks and a global coarse attention mechanism. We refer to the proposed architecture as two-level overlapping Schwarz attention, or Schwarz attention for short.

5 Training Procedure

5.1 Loss Function

For a batch of right-hand sides $f^{(b)}$, the exact solutions are computed as $u^{(b)} = A^{-1} f^{(b)}$. The model prediction is $u_\theta^{(b)} = M_\theta^{-1} f^{(b)}$. A plain mean-squared error (MSE) tends to underweight examples whose true solutions have small amplitude. For Poisson problems, high-frequency right-hand sides produce solutions whose amplitudes are damped by the inverse Laplacian. We therefore use a sample-wise weighted MSE (wMSE)

$$\mathcal{L}_{\text{wMSE}}(\theta) = \frac{1}{B} \sum_{b=1}^{B} \left((n-1)^{-1} \left\| u_\theta^{(b)} - u^{(b)} \right\|_2^2 \right) / \left(\max \left\{ (n-1)^{-1} \left\| u^{(b)} \right\|_2^2, \varepsilon \right\} \right). \tag{18}$$

where B denotes the batch size and $u_\theta^{(b)}$ and $u^{(b)}$ denote the predicted and exact solutions for sample b, respectively. All our experiments use this loss, setting $\varepsilon = 1e - 30$. Without this weighting, good approximations are not achieved for high-frequency right-hand sides. Unless stated otherwise, all experiments use a batch size of $B = 256$.

5.2 Initialization of the Attention Factors

For the random initialization we use a resolution- and rank-aware scaling of the factor matrices. The entries of the trainable factors Q and K are first drawn randomly. An entry of QK^T is an inner product of length r of a row of Q with a row of K, see (2).

We then multiply both factors by $(h/4)^{1/2} r^{-1/4}, h = \frac{1}{n}$. Thus the product QK^T is scaled by $(h/4) r^{-1/2}$. The factor $r^{-1/2}$ compensates the growth of the random inner products with the rank, while the factor h matches the natural size of the inverse one-dimensional Laplacian, whose largest entries are of order $h/4$.

5.3 Synthetic Right-Hand Sides

The training data are generated on the fly; no finite stored training set is used. We sample right-hand sides from a mixed Fourier family and normalize each generated right-hand side to unit Euclidean norm. The

experiments use the first 16 sine modes and also the first 16 cosine modes on the interior grid points. The mixed Fourier generator combines two types of right-hand sides in each batch. One half of the batch consists of pure Fourier modes: a single normalized sine or cosine mode is selected and multiplied by a random sign. These pure modes are not damped by a decay factor. The other half consists of random Fourier combinations. In this part, sine and cosine modes $m = 1, \ldots, 16$ are combined, with higher modes damped by the factor $m^{-1.5}$. After concatenating the two parts, the batch is shuffled and every right-hand side is normalized.

The global attention model and the hierarchical domain-decomposition attention model see the same sequence of training right-hand sides. We use 16 evaluation right-hand sides in the solution plots; they are generated once with a fixed test seed and are then used for all models. For each generated right-hand side, the reference solution is computed by applying the exact discrete inverse,

$$u^{(b)} = A^{-1} f^{(b)}.$$

Section A.1 of the Appendix defines the generator used for our mixed Fourier right-hand sides.

Remark 4. *The distribution of right-hand sides is an essential part of our operator-learning problem. A low-rank attention operator cannot be expected to approximate the inverse Poisson operator uniformly well for all possible right-hand sides if the chosen ranks are much smaller than the problem dimension. The mixed Fourier distribution used here is therefore a controlled test class. The goal is not to learn a uniformly accurate inverse on the complete space $\mathbb{R}^{n-1}$, but to compare global low-rank attention and Schwarz attention on a given class of right-hand sides with both local and global structure.*

6 First Experimental Setup

Our first numerical experiments consist of learning-rate sweeps for a problem size of $n = 256$ line elements, corresponding to 255 active degrees of freedom, and $N = 8$ subdomains; we always use an overlap of $n_\delta = 2$, and the local ranks are set to $r_\ell = 4$, the coarse rank is set to $r_0 = N - 1 = 7$. The coarse basis is the interface-hat basis; see Section 4.1.

For $n = 256$, $N = 8$, and overlap two, the nonoverlapping partition consists of eight subdomains with 32 line elements each. After adding two overlap elements on each interior side, the six interior overlapping subdomains contain 36 elements, corresponding to 37 active degrees of freedom. The two boundary subdomains contain 34 elements each; after eliminating the Dirichlet boundary values, they contain 34 active degrees of freedom. Hence $\sum_{i=1}^{8} n_i = 2 \cdot 34 + 6 \cdot 37 = 290$. With local rank $r_\ell = 4$, the local factors therefore contain $2r_\ell \sum_{i=1}^{8} n_i = 2 \cdot 4 \cdot 290 = 2320$ trainable parameters. The coarse space has $N - 1 = 7$ interface hat functions. Using rank $r_0 = 7$ for the coarse attention block adds $2(N-1)r_0 = 2 \cdot 7 \cdot 7 = 98$ parameters. Thus, the total number of trainable parameters for the overlapping Schwarz attention is 2418.

We use AdamW (Loshchilov and Hutter, 2019) with zero weight decay, $\beta_1 = 0.9$, $\beta_2 = 0.999$, and $\varepsilon = 10^{-8}$ and batch size 256. Since the weight decay is zero, the resulting updates are equivalent to those of Adam. We use a `ReduceLROnPlateau` scheduler with reduction factor 0.5 and patience 200.

6.1 Learning-Rate Sweep for the Overlapping Schwarz Attention

Figure 2 shows two representative histories. The more aggressive value $\eta = 3 \cdot 10^{-3}$ attains one of the lowest losses in the sweep, but exhibits a visible spike. We decided to use $\eta = 10^{-3}$ as a conservative default in the following experiments. The full learning-rate sweep is reported in Section A.2 of the Appendix; the comparison with global attention over the complete sweep is given in Section A.3.

6.2 Comparison of Schwarz Attention and Global Attention

We now perform a comparison of the Schwarz attention with the standard global attention. The rank of the global attention operator, which is our baseline, is set to $r_g = 39$. This is a fair comparison with respect to the rank of the operator since the rank of the Schwarz attention operator is bounded by $Nr_\ell + r_0 = 8 \times 4 + 7 = 39$. However, the Schwarz attention has only 2418 trainable parameters; see Section 6. The corresponding global

(a) $\eta = 10^{-3}$

(b) $\eta = 3 \cdot 10^{-3}$

Figure 2: Representative learning-rate histories for the two-level overlapping Schwarz attention. The conservative choice $\eta = 10^{-3}$ reaches the same low-error regime as the more aggressive choice $\eta = 3 \cdot 10^{-3}$, while avoiding the strongest transient fluctuations. The full learning-rate sweep for Schwarz attention is reported in Section A.2 of the Appendix. The comparison with global attention over the complete sweep is given in Section A.3.

Learning rate η	Model	Final train wMSE	Final val. wMSE	$\|M_\theta^{-1} - A^{-1}\|_F$	$\min_{\mathrm{rank}(B) \le r} \|B - A^{-1}\|_F$
10^{-4}	Schwarz attention	$2.587 \cdot 10^{-2}$	$2.612 \cdot 10^{-2}$	0.0712	$2.488 \cdot 10^{-4}$
10^{-4}	Global attention, rank 5	$6.149 \cdot 10^{-1}$	$6.086 \cdot 10^{-1}$	0.263	$4.504 \cdot 10^{-3}$
10^{-4}	Global attention, rank 39	$5.466 \cdot 10^{-2}$	$5.403 \cdot 10^{-2}$	0.244	$2.488 \cdot 10^{-4}$
$3 \cdot 10^{-4}$	Schwarz attention	$1.408 \cdot 10^{-3}$	$1.270 \cdot 10^{-3}$	0.0697	$2.488 \cdot 10^{-4}$
$3 \cdot 10^{-4}$	Global attention, rank 5	$3.150 \cdot 10^{-1}$	$3.151 \cdot 10^{-1}$	0.294	$4.504 \cdot 10^{-3}$
$3 \cdot 10^{-4}$	Global attention, rank 39	$2.564 \cdot 10^{-3}$	$2.549 \cdot 10^{-3}$	0.226	$2.488 \cdot 10^{-4}$
10^{-3}	Schwarz attention	$6.293 \cdot 10^{-4}$	$5.594 \cdot 10^{-4}$	0.0585	$2.488 \cdot 10^{-4}$
10^{-3}	Global attention, rank 5	$2.419 \cdot 10^{-1}$	$2.429 \cdot 10^{-1}$	0.193	$4.504 \cdot 10^{-3}$
10^{-3}	Global attention, rank 39	$8.630 \cdot 10^{-4}$	$8.527 \cdot 10^{-4}$	0.154	$2.488 \cdot 10^{-4}$
$3 \cdot 10^{-3}$	Schwarz attention	$1.321 \cdot 10^{-4}$	$2.082 \cdot 10^{-4}$	0.0474	$2.488 \cdot 10^{-4}$
$3 \cdot 10^{-3}$	Global attention, rank 5	$2.477 \cdot 10^{-1}$	$2.326 \cdot 10^{-1}$	0.11	$4.504 \cdot 10^{-3}$
$3 \cdot 10^{-3}$	Global attention, rank 39	$3.102 \cdot 10^{-4}$	$3.189 \cdot 10^{-4}$	0.116	$2.488 \cdot 10^{-4}$
10^{-2}	Schwarz attention	$1.604 \cdot 10^{-4}$	$2.258 \cdot 10^{-4}$	0.0462	$2.488 \cdot 10^{-4}$
10^{-2}	Global attention, rank 5	$2.391 \cdot 10^{-1}$	$2.361 \cdot 10^{-1}$	0.0722	$4.504 \cdot 10^{-3}$
10^{-2}	Global attention, rank 39	$3.097 \cdot 10^{-2}$	$2.980 \cdot 10^{-2}$	0.265	$2.488 \cdot 10^{-4}$
$3 \cdot 10^{-2}$	Schwarz attention	$6.487 \cdot 10^{-4}$	$5.899 \cdot 10^{-4}$	0.0733	$2.488 \cdot 10^{-4}$
$3 \cdot 10^{-2}$	Global attention, rank 5	$2.489 \cdot 10^{-1}$	$2.548 \cdot 10^{-1}$	0.144	$4.504 \cdot 10^{-3}$
$3 \cdot 10^{-2}$	Global attention, rank 39	$6.592 \cdot 10^{-1}$	$6.567 \cdot 10^{-1}$	0.868	$2.488 \cdot 10^{-4}$

Table 1: Learning-rate sweep summary for $n = 256$ and $N = 8$. Each row reports the last logged training wMSE, validation wMSE, and absolute operator Frobenius error after 2000 training steps. The final column gives the Frobenius error of the best rank-r approximation of A^{-1}. Here, $r = 5$ for the global rank-5 model and $r = 39$ for the global rank-39 model; for Schwarz attention, $r = R_{\text{total}} = 39$ is the corresponding rank bound.

low-rank attention with rank 39 has $2 \cdot 255 \cdot 39 = 19890$ trainable parameters, since the two Dirichlet boundary values are eliminated and the global operator acts on 255 active degrees of freedom, i.e., more than eight times as many parameters as the Schwarz attention model. A parameter-comparable global baseline is obtained by choosing rank 5 for the global attention, which gives $2 \cdot 255 \cdot 5 = 2550$ parameters. This is close to the 2418 parameters of the Schwarz attention model and is therefore the parameter-matched global baseline.

Figure 3: Comparison of the Schwarz attention with the standard global attention for $n = 256$, $N = 8$, and $\eta = 10^{-3}$. The full set of training curves is shown in Section A.3 of the Appendix.

Figure 3 compares the Schwarz attention model with our two global low-rank baselines using our default learning rate $\eta = 10^{-3}$. The Schwarz attention reaches a lower error level than both global low-rank baselines. The global rank-5 baseline is roughly comparable in parameter count but stagnates at a much higher loss, whereas the substantially larger global rank-39 baseline still does not match the Schwarz model. The complete learning-rate sweep is given in Section A.3 of the Appendix; it shows that the Schwarz attention consistently outperforms the global attention.

Table 1 summarizes the final values after 2000 optimization steps for all learning rates in the sweep. In addition to the final training and validation wMSE, we report the operator error $|M_\theta^{-1} - A^{-1}|_F$. This quantity measures the approximation quality of the learned inverse operator itself. The final column reports the Frobenius error of the best rank-r approximation of A^{-1}. Since A^{-1} is symmetric positive definite, this approximation can equivalently be obtained by truncating its spectral decomposition.

The results show that the ordering observed in the wMSE curves is also reflected at the operator level. The parameter-matched global rank-5 model remains far from the operator baseline and yields substantially larger Frobenius errors. Increasing the global rank to 39 improves the global model considerably, but the Schwarz attention model still attains smaller operator errors over the relevant range of learning rates. This indicates that the advantage of the Schwarz construction is not only visible on sampled right-hand sides, but also in the learned operator approximation. The best values for Schwarz attention are obtained in the moderate range around 10^{-3} to 10^{-2}.

Remark 5. *We emphasize that the Frobenius error of the full operator is reported in Table 1 only as an additional diagnostic quantity. It is different from the training objective, which minimizes a sample-wise weighted forward error. In particular, the learned operators are not computed as best rank-r approximations of A^{-1} in the Frobenius norm. Hence a comparatively large Frobenius error does not contradict small relative solution errors on the right-hand sides used for evaluation.*

These results indicate that the domain-decomposition structure is highly effective for learning the inverse Poisson operator in our context. The combination of local low-rank attention blocks with a coarse attention space yields both higher approximation accuracy and substantially improved parameter efficiency.

For the comparison in the next sections, we use the conservative learning rate $\eta = 10^{-3}$.

6.3 Approximation Quality on Fixed Visualization Examples

Figure 4 shows an example of the learned approximations for the overlapping Schwarz attention, global attention with rank 39, and global attention with rank 5. While the Schwarz attention and the rank-39 global attention perform well, the parameter-matched rank-5 global attention shows poor approximation quality in this example.

(a) Overlapping Schwarz attention. (b) Global attention with rank $r = 39$. (c) Global attention with rank $r = 5$.

Figure 4: Sample solutions for (a) Schwarz attention, (b) global attention with rank 39, and (c) global attention with rank 5 after 2000 iterations with learning rate $\eta = 0.001$. In each panel, the exact solution is plotted in black and the model prediction as a dashed red line. Additional sample solutions are shown in Section A.4 of the Appendix.

n	N	#Params	Final val. wMSE	$\|M_\theta^{-1}-A^{-1}\|_F$	$\min\limits_{\mathrm{rank}(B)\leq r}\|B-A^{-1}\|_F$	Rank bound R_{total}
256	8	2418	$5.594 \cdot 10^{-4}$	$5.846 \cdot 10^{-2}$	$2.488 \cdot 10^{-4}$	39
512	16	5138	$6.054 \cdot 10^{-4}$	$4.414 \cdot 10^{-2}$	$8.719 \cdot 10^{-5}$	79
1024	32	11346	$4.373 \cdot 10^{-4}$	$5.906 \cdot 10^{-2}$	$3.069 \cdot 10^{-5}$	159
2048	64	26834	$2.348 \cdot 10^{-4}$	$7.984 \cdot 10^{-2}$	$1.083 \cdot 10^{-5}$	319
4096	128	70098	$6.347 \cdot 10^{-4}$	$1.363 \cdot 10^{-1}$	$3.824 \cdot 10^{-6}$	639
8192	256	205778	$3.248 \cdot 10^{-3}$	$2.194 \cdot 10^{-1}$	$1.351 \cdot 10^{-6}$	1279

Table 2: Results for increasing problem size $n = 256, \ldots, 8192$ and a proportionally increasing number of local attention blocks. Each row reports the final weighted MSE, the absolute operator Frobenius error, and the Frobenius error of the best rank-r approximation of A^{-1}, where $r = R_{\mathrm{total}} = Nr_\ell + r_0$ is the rank bound of the Schwarz attention operator.

7 Increasing the Number of Local Attention Blocks

Figure 5: Final weighted MSE in the subdomain-scaling experiment. The problem size n and the number of subdomains N are increased proportionally, while the local rank is kept fixed at $r_\ell = 4$. The error remains in the range 10^{-4}–10^{-3} up to $n = 4096$ and increases for the largest case $n = 8192$.

We perform additional experiments, inspired by parallel weak scaling in supercomputing, i.e., we increase the problem size $n = 256, 512, 1024, 2048, 4096$, and 8192 while also proportionally increasing the number of local attention blocks $N = 8, 16, 32, 64, 128$, and 256. Thus, the size of each nonoverlapping subdomain remains essentially constant. The number of trainable parameters grows approximately linearly with the number of subdomains, apart from the contribution of the coarse block.

We use local ranks $r_\ell = 4$ for the local attention blocks, and a coarse rank $r_0 = N - 1$ for the coarse attention block. Again, we use AdamW combined with a `ReduceLROnPlateau` scheduler with reduction factor 0.5 and patience 200. The initial learning rate for AdamW is $\eta = 10^{-3}$. We use mixed Fourier right-hand sides, a batch size of 256, and 2000 training steps. The results are shown in Table 2 and Figure 5; the corresponding training histories are shown in Figure A.7.

The final error is not completely scale-independent: the largest case, $n = 8192$ and $N = 256$, is visibly more difficult. Nevertheless, the optimization still reaches a final weighted MSE of order 10^{-3} while using fixed local rank and hundreds of local attention blocks.

8 Rank-Based Frobenius-Norm Bounds

The exact discrete solution operator is A^{-1}. Since A is symmetric positive definite, we can write

$$A = V\Lambda V^T, \qquad A^{-1} = V\Lambda^{-1}V^T,$$

where the eigenvalues of A satisfy

$$0 < \lambda_1 \le \lambda_2 \le \cdots \le \lambda_{n-1}.$$

For the one-dimensional finite-difference Poisson matrix with homogeneous Dirichlet boundary conditions,

$$\lambda_k = \frac{4}{h^2}\sin^2\left(\frac{k\pi}{2n}\right), \qquad k = 1, \ldots, n - 1.$$

Thus the eigenvalues of A^{-1} are λ_k^{-1}. Since A^{-1} is symmetric positive definite, these are also its singular values, ordered decreasingly.

Theorem 1 (Global low-rank attention). *Let $M_{\theta,\mathrm{global}}^{-1} = QK^T$, with $Q, K \in \mathbb{R}^{(n-1)\times r_g}$.*

Then

$$\inf_{Q,K\in\mathbb{R}^{(n-1)\times r_g}}\|A^{-1} - QK^T\|_F^2 = \sum_{k=r_g+1}^{n-1}\lambda_k^{-2}.$$

Equivalently,

$$\frac{\inf_{Q,K\in\mathbb{R}^{(n-1)\times r_g}}\|A^{-1} - QK^T\|_F}{\|A^{-1}\|_F} = \left(\frac{\sum_{k=r_g+1}^{n-1}\lambda_k^{-2}}{\sum_{k=1}^{n-1}\lambda_k^{-2}}\right)^{1/2}.$$

The infimum is attained by the truncated spectral decomposition

$$QK^T = \sum_{k=1}^{r_g}\lambda_k^{-1}v_k v_k^T.$$

Theorem 2 (Rank bound for Schwarz attention). *Every $S \in \mathcal{S}_{\mathrm{Schwarz}}$ satisfies*

$$\mathrm{rank}(S) \le R_{\mathrm{total}} := \min\{r_0, \mathrm{rank}(\Phi)\} + \sum_{i=1}^{N}\min\{r_i, n_i\}.$$

Consequently,

$$\inf_{S\in\mathcal{S}_{\mathrm{Schwarz}}}\|A^{-1} - S\|_F \ge \left(\sum_{k=R_{\mathrm{total}}+1}^{n-1}\lambda_k^{-2}\right)^{1/2},$$

with the convention that the sum is zero if $R_{\mathrm{total}} \ge (n-1)$. In relative form,

$$\frac{\inf_{S\in\mathcal{S}_{\mathrm{Schwarz}}}\|A^{-1} - S\|_F}{\|A^{-1}\|_F} \ge \left(\frac{\sum_{k=R_{\mathrm{total}}+1}^{n-1}\lambda_k^{-2}}{\sum_{k=1}^{n-1}\lambda_k^{-2}}\right)^{1/2}.$$

The second theorem is only a rank-based lower benchmark. It does not use the structure of the Schwarz-attention architecture. The proofs are given in Section A.6 of the Appendix.

9 Discussion

The experiments support three observations. First, the proposed two-level domain-decomposition attention operator provides an effective hierarchical representation of the Poisson inverse. The local blocks are designed to capture strong short-range interactions, while the coarse block represents weaker long-range interactions. This mirrors the role of fine and coarse spaces in classical two-level Schwarz methods for elliptic partial differential equations. Second, the proposed model is substantially more parameter-efficient than a global low-rank attention baseline. In the representative configuration, the global baseline uses 19890 trainable parameters, while the domain-decomposition model uses 2418.

Despite using far fewer parameters, the domain-decomposition model reaches low errors in fewer optimization steps and achieves slightly more accurate approximations in the reported experiments. Third, the approach remained effective for up to $N = 256$ local attention blocks, although a slight deterioration in the final wMSE was observed. Overall, these results suggest that hierarchical attention derived from domain decomposition provides an effective inductive bias for operator learning. Extending this framework to other contexts is future work.

There are several limitations. The experiments are restricted to a one-dimensional Poisson problem and synthetic Fourier right-hand sides. The model is linear and softmax-free. This is intentional for the present study: it isolates the effect of domain-decomposition structure.

Extending the approach to standard softmax attention (Vaswani et al., 2017) is non-trivial, because the row-wise softmax operation generally requires access to the full attention scores. A naive implementation would therefore require assembling the Schwarz attention scores into a dense matrix, or otherwise performing a global normalization across the local and coarse contributions, which could substantially increase computational and memory costs. Nevertheless, core advantages of the hierarchical parameterization would likely persist: the model would still require significantly fewer trainable parameters than a global low-rank baseline, and the structured factorization may continue to facilitate faster and more stable optimization.

However, applying a single softmax normalization to a mixture of fine and coarse tokens may be undesirable. A possible direction for an adapted softmax variant would therefore be to apply softmax separately on the fine-level subdomain blocks and on the coarse level, treating the interface-hat functions as pooling or summary tokens. Related ideas of combining attention mechanisms for long documents at different granularities appear in Longformer (Beltagy et al., 2020). Related ideas of processing representations at multiple spatial granularities appear in the Swin Transformer (Liu et al., 2021).

Extensions to softmax attention, as well as to other PDEs, higher-dimensional problems, nonlinear attention architectures and parallel aspects of our approach remain future work. We note that the overlapping Schwarz algorithm is highly parallelizable (Jolivet et al., 2012; Heinlein et al., 2022) and may therefore provide a route toward parallel attention mechanisms across multiple GPUs. Such methods have received considerable attention in recent years for long-context Transformer models (Sun et al., 2025; Acharya et al., 2025; Lu et al., 2025; Tang et al., 2024).

This work does not involve human subjects or use personal data, nor does it target a safety-critical or socially sensitive application. We are not aware of specific societal harms arising directly from the proposed method in the setting studied here.

10 Conclusion

We introduced a hierarchical attention mechanism inspired by two-level overlapping Schwarz domain decomposition. The method replaces a dense global low-rank attention operator by a sum of local overlapping attention blocks and a coarse attention block. For the one-dimensional Poisson inverse, this construction gives a compact and interpretable operator-learning model. The numerical results suggest that domain-decomposition structure can improve both parameter efficiency and training behavior in softmax-free operator learning, relative to a global attention baseline.

References

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Andrea Toselli and Olof Widlund. *Domain Decomposition Methods – Algorithms and Theory*, volume 34 of *Springer Series in Computational Mathematics*. Springer, Berlin, Heidelberg, 2005.

Barry F. Smith, Petter E. Bjørstad, and William D. Gropp. *Domain Decomposition: Parallel Multilevel Methods for Elliptic Partial Differential Equations*. Cambridge University Press, Cambridge, 1996.

Pierre-Louis Lions. On the Schwarz alternating method. I. In Roland Glowinski, Gene H. Golub, Gérard A. Meurant, and Jacques Périaux, editors, *First International Symposium on Domain Decomposition Methods for Partial Differential Equations*, Philadelphia, PA, 1988. SIAM.

Jae Yong Lee, Seungchan Ko, and Youngjoon Hong. Finite element operator network for solving elliptic-type parametric PDEs. *SIAM Journal on Scientific Computing*, 47(2):C501–C528, 2025. doi:10.1137/23M1623707. URL https://doi.org/10.1137/23M1623707.

Lu Lu, Pengzhan Jin, Guofei Pang, Zhongqiang Zhang, and George Em Karniadakis. Learning nonlinear operators via DeepONet based on the universal approximation theorem of operators. *Nature Machine Intelligence*, 3:218–229, 2021. doi:10.1038/s42256-021-00302-5.

Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Fourier neural operator for parametric partial differential equations. In *International Conference on Learning Representations*, 2021.

Pierre Jolivet, Frédéric Hecht, Frédéric Nataf, and Christophe Prud'homme. Scalable domain decomposition preconditioners for heterogeneous elliptic problems. In *Proceedings of the International Conference on High Performance Computing, Networking, Storage and Analysis (SC '12)*, Washington, DC, USA, 2012. IEEE Computer Society. doi:10.1109/SC.2012.80.

Alexander Heinlein, Oliver Rheinbach, and Friederike Röver. Parallel scalability of three-level FROSch preconditioners to 220000 cores using the Theta supercomputer. *SIAM Journal on Scientific Computing*, 44(4):C253–C278, 2022. doi:10.1137/21M1431205.

Simone Deparis, Davide Forti, Gwenol Grandperrin, and Alfio Quarteroni. Facsi: A block parallel preconditioner for fluid–structure interaction in hemodynamics. *Journal of Computational Physics*, 327:700–718, 2016. doi:10.1016/j.jcp.2016.10.005. https://doi.org/10.1016/j.jcp.2016.10.005.

Xiao-Chuan Cai, William D. Gropp, David E. Keyes, Robin G. Melvin, and David P. Young. Parallel newton–krylov–schwarz algorithms for the transonic full potential equation. *SIAM Journal on Scientific Computing*, 19(1):246–265, 1998. doi:10.1137/S1064827596304046. https://doi.org/10.1137/S1064827596304046.

Yutao Sun, Tianzhu Ye, Li Dong, Yuqing Xia, Jian Chen, Yizhao Gao, Shijie Cao, Jianyong Wang, and Furu Wei. Rectified sparse attention, 2025. URL https://arxiv.org/abs/2506.04108.

Shantanu Acharya, Fei Jia, and Boris Ginsburg. Star attention: Efficient llm inference over long sequences, 2025. URL https://arxiv.org/abs/2411.17116.

Enzhe Lu, Zhejun Jiang, Jingyuan Liu, Yulun Du, Tao Jiang, Chao Hong, Shaowei Liu, Weiran He, Enming Yuan, Yuzhi Wang, Zhiqi Huang, Huan Yuan, Suting Xu, Xinran Xu, Guokun Lai, Yanru Chen, Huabin Zheng, Junjie Yan, Jianlin Su, Yuxin Wu, Neo Y. Zhang, Zhilin Yang, Xinyu Zhou, Mingxing Zhang, and Jiezhong Qiu. Moba: Mixture of block attention for long-context llms, 2025. URL https://arxiv.org/abs/2502.13189.

Jiaming Tang, Yilong Zhao, Kan Zhu, Guangxuan Xiao, Baris Kasikci, and Song Han. Quest: Query-aware sparsity for efficient long-context llm inference, 2024. URL https://arxiv.org/abs/2406.10774.

Saeed Amizadeh, Sara Abdali, Yinheng Li, and Kazuhito Koishida. Hierarchical self-attention: Generalizing neural attention mechanics to multi-scale problems. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. doi:10.48550/arXiv.2509.15448. arXiv:2509.15448.

Chengxi Han, Chen Wu, Haonan Guo, Meiqi Hu, and Hongruixuan Chen. HANet: A hierarchical attention network for change detection with bi-temporal very-high-resolution remote sensing images. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 16:3867–3883, 2023. doi:10.1109/JSTARS.2023.3264802.

Paul Hongsuck Seo, Zhe Lin, Scott Cohen, Xiaohui Shen, and Bohyung Han. Progressive attention networks for visual attribute prediction. *arXiv preprint arXiv:1606.02393*, 2016. doi:10.48550/arXiv.1606.02393.

Haoyu He, Markus Flicke, Jan Buchmann, Iryna Gurevych, and Andreas Geiger. HDT: Hierarchical document transformer. *arXiv preprint arXiv:2407.08330*, 2024. doi:10.48550/arXiv.2407.08330. Published at COLM 2024.

Ilias Chalkidis, Xiang Dai, Manos Fergadiotis, Prodromos Malakasiotis, and Desmond Elliott. An exploration of hierarchical attention transformers for efficient long document classification. *arXiv preprint arXiv:2210.05529*, 2022. doi:10.48550/arXiv.2210.05529.

Yongli Hu, Puman Chen, Tengfei Liu, Junbin Gao, Yanfeng Sun, and Baocai Yin. Hierarchical attention transformer networks for long document classification. In *2021 International Joint Conference on Neural Networks (IJCNN)*, pages 1–7, 2021. doi:10.1109/IJCNN52387.2021.9534365.

Zichao Yang, Diyi Yang, Chris Dyer, Xiaodong He, Alex Smola, and Eduard Hovy. Hierarchical attention networks for document classification. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1480–1489, San Diego, California, 2016. Association for Computational Linguistics. doi:10.18653/v1/N16-1174.

Shuhao Cao. Choose a transformer: Fourier or Galerkin. In *Advances in Neural Information Processing Systems*, volume 34, pages 24924–24940, 2021. URL https://proceedings.neurips.cc/paper/2021/file/d0921d442ee91b896ad95059d13df618-Paper.pdf. arXiv:2105.14995.

Matthias Brändel, Stephan Köhler, and Oliver Rheinbach. How token influence decays with distance: A green-function view of trained language models, 2026. URL https://arxiv.org/abs/2606.29139.

Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992. Association for Computational Linguistics, 2019. doi:10.18653/v1/D19-1410.

Jing Zhao, Yifan Wang, Junwei Bao, Youzheng Wu, and Xiaodong He. Fine- and coarse-granularity hybrid self-attention for efficient BERT. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4314–4326. Association for Computational Linguistics, 2022. doi:10.18653/v1/2022.acl-long.330.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019.

Iz Beltagy, Matthew E. Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*, 2020. doi:10.48550/arXiv.2004.05150.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 10012–10022, 2021. doi:10.1109/ICCV48922.2021.00986.

A   Supplementary Material

A.1   Construction of the Right-Hand Sides

The code in Figure A.1 shows how the right-hand sides are constructed.

```python
def normalize_rows(v: torch.Tensor, eps: float = 1.0e-12) -> torch.Tensor:
    return v / (v.norm(dim=-1, keepdim=True) + eps)

def fourier_basis(x: torch.Tensor, modes: int) -> torch.Tensor:
    """Rows are normalized sine/cosine Fourier modes without decay."""
    rows = []
    for m in range(1, modes + 1):
        rows.append(torch.sin(math.pi * m * x))
        rows.append(torch.cos(math.pi * m * x))
    return normalize_rows(torch.stack(rows, dim=0))

def sample_mixed_fourier_rhs(batch_size: int, x: torch.Tensor) -> torch.Tensor:
    """Mixed Fourier RHS: half pure modes, half random decaying combinations."""
    n_dof = x.numel()

    def pure_modes(bs: int) -> torch.Tensor:
        B = fourier_basis(x, MODES)
        idx = torch.randint(0, B.shape[0], (bs,), device=DEVICE)
        signs = 2.0 * torch.randint(0, 2, (bs, 1), device=DEVICE, dtype=DTYPE) - 1.0
        return signs * B[idx, :]

    def random_combinations(bs: int) -> torch.Tensor:
        f = torch.zeros(bs, n_dof, device=DEVICE, dtype=DTYPE)
        for m in range(1, MODES + 1):
            scale = 1.0 / (m ** DECAY)
            a = torch.randn(bs, 1, device=DEVICE, dtype=DTYPE) * scale
            b = torch.randn(bs, 1, device=DEVICE, dtype=DTYPE) * scale
            f = f + a * torch.sin(math.pi * m * x)[None, :]
            f = f + b * torch.cos(math.pi * m * x)[None, :]
        return f

    b1 = batch_size // 2
    b2 = batch_size - b1
    f = torch.cat([pure_modes(b1), random_combinations(b2)], dim=0)
    f = f[torch.randperm(batch_size, device=DEVICE)]
    return normalize_rows(f)
```

Figure A.1: The code was extracted from our more general implementation and subsequently verified to produce identical results.

A.2   Full Learning Rate Sweep for the Overlapping Schwarz Attention

Figure A.2 shows the training curves for the six learning rates

$$\eta \in \left\{ 10^{-4},\ 3 \cdot 10^{-4},\ 10^{-3},\ 3 \cdot 10^{-3},\ 10^{-2},\ 3 \cdot 10^{-2} \right\}.$$

For the initialization of the attention factors, we use the method described in Section 5.2.

Figure A.2 shows that the training behavior is not highly sensitive to the precise choice of the learning rate over a fairly broad range. The smallest learning rates lead to stable but slower convergence, while the larger learning rates reach low errors more rapidly but show more pronounced transient fluctuations. In particular,

Figure A.2: Learning-rate sweep for $n = 256$ and $N = 8$ for the two-level overlapping Schwarz attention using a rank $r_\ell = 4$ for the local attention blocks and rank $r_0 = 7$ for the coarse attention. Each panel shows the weighted training MSE and the weighted validation MSE. We use AdamW and a plateau scheduler.

$\eta = 3 \cdot 10^{-3}$ attains one of the lowest final losses in this sweep, but also exhibits a visible intermediate spike. We therefore use $\eta = 10^{-3}$ as a conservative default in our experiments: it reaches essentially the same error regime, avoids the strongest transients, and provides a robust compromise between convergence speed and stability.

The validation wMSE is computed on 256 independently sampled right-hand sides drawn from the same distribution as the training data. The training and validation curves are almost indistinguishable throughout the sweep. Since the validation right-hand sides are independently sampled from the same distribution as the training data, this should be interpreted as in-distribution validation. The agreement indicates that the observed optimization behavior is not specific to the sampled training batch, but is representative for independently sampled right-hand sides from the same problem class.

A.3 Full Learning-Rate Sweep: Schwarz Attention vs. Global Attention

Figure A.3: Learning-rate sweep for global low-rank attention and hierarchical domain-decomposition attention for $n = 256$ and $N = 8$. Each panel shows the weighted training wMSE on the current training batch. The same training right-hand-side sequence is used for both models. The Schwarz attention uses local rank 4 and coarse rank 7, thus the rank is bounded by $8 \times 4 + 7 = 39$. The global attention uses rank 39. The global attention with rank 5 is roughly comparable to the Schwarz attention with respect to the number of parameters.

Across the learning-rate sweep $\eta \in \{10^{-4}, 3 \cdot 10^{-4}, 10^{-3}, 3 \cdot 10^{-3}, 10^{-2}, 3 \cdot 10^{-2}\}$, Schwarz attention consistently outperforms the parameter-matched rank-5 baseline and reaches substantially lower weighted MSE values; see Figure A.3. This shows that the improvement is not merely a consequence of using more parameters.

The comparison with the rank-39 global model is more stringent, since this baseline has many more trainable parameters. Nevertheless, Schwarz attention reaches lower final errors for the learning rates considered and exhibits a more stable optimization behavior. The global rank-39 model can reduce the loss substantially compared with rank 5, but its curves show stronger sensitivity to the learning rate and more pronounced

transient spikes. The advantage of Schwarz attention is most visible for moderate learning rates, in particular around $\eta = 10^{-3}$ and $3 \cdot 10^{-3}$, where it combines rapid convergence with low final error.

The parameter-matched global rank-5 baseline behaves qualitatively differently from both Schwarz attention and the global rank-39 model. It decreases the loss initially, but then stagnates at a substantially higher error level and does not reach the low-MSE regime attained by the two higher-rank models. Thus, the rank-5 comparison shows the limitation of a purely global low-rank approximation under a comparable parameter budget. In contrast, Schwarz attention reaches the accuracy regime of the much larger rank-39 global model, and in the relevant learning-rate range even improves upon it.

A.4 Additional Fixed Visualization Examples

Figures A.4, A.5, and A.6 show the learned approximations for 12 sample right-hand sides for the overlapping Schwarz attention, global attention with rank 39, and global attention with rank 5. These right-hand sides are sampled from the same prescribed distribution as the training right-hand sides, but using a different random seed, and are kept fixed in order to make the visual comparison reproducible.

The purpose of these plots is not to assess out-of-distribution generalization. Instead, they provide a diagnostic view of the learned operator on representative samples from the training distribution, analogous to the weighted MSE values shown in the training curves in Figure A.3.

The sample solutions in Figure A.4 – A.6 illustrate the quantitative findings. Schwarz attention and global attention with rank 39 both give accurate reconstructions on the displayed validation examples; the predicted and exact solution curves are often nearly indistinguishable. By contrast, the parameter-matched global rank-5 model shows visible errors, particularly for more oscillatory right-hand sides. This confirms that the rank-5 global model lacks the expressive power needed to reach the low-error regime, whereas the Schwarz construction achieves accuracy comparable to the much larger rank-39 global model with far fewer parameters.

Figure A.4: Sample solutions for overlapping Schwarz attention after 2000 iterations with learning rate $\eta = 0.001$. The exact solution is plotted in black and the model prediction as a dashed red line. The right-hand side is shown in green and was rescaled to fit the plotting range.

Figure A.5: Sample solutions for global attention with rank $r = 39$ after 2000 iterations with learning rate $\eta = 0.001$. The exact solution is plotted in black and the model prediction as a dashed red line. The right-hand side is shown in green and was rescaled to fit the plotting range.

Figure A.6: Sample solutions for global attention with rank $r = 5$ after 2000 iterations with learning rate $\eta = 0.001$. The exact solution is plotted in black and the model prediction as a dashed red line. The right-hand side is shown in green and was rescaled to fit the plotting range.

A.5 Training Curves for Increasing Numbers of Local Attention Blocks

Figure A.7: Training and validation loss (wMSE) over 2000 training steps for an increasing problem size and number of local attention blocks.

In Figure A.7, the final weighted MSE remains small over the full range $n = 256, \ldots, 8192$. Up to $n = 4096$, the final errors stay in the range of about 10^{-4} to 10^{-3}, and even for $n = 8192$ the method still reaches a weighted MSE of order 10^{-3}. This indicates that the two-level Schwarz attention construction remains trainable as the number of local blocks is increased substantially, without increasing the local rank.

A.6 Proofs of Theorems 1 and 2

Proof of Theorem 1. The product QK^T can represent any matrix of rank at most r_g. Since A^{-1} is symmetric positive definite, its singular values are λ_k^{-1}. The result follows from the Eckart–Young–Mirsky theorem. $\square$

For the Schwarz-attention operator $M_{\theta,\text{Schwarz}}^{-1}$ defined in (17), we use the already introduced local and coarse blocks

$$G_0 = Q_0 K_0^T, \qquad G_i = Q_i K_i^T, \qquad i = 1, \ldots, N.$$

Assume that

$$\text{rank}(G_0) \le r_0, \qquad \text{rank}(G_i) \le r_i, \qquad i = 1, \ldots, N.$$

Let n_i denote the number of degrees of freedom on the i-th overlapping subdomain, and let $\mathcal{S}_{\text{Schwarz}}$ denote the set of all Schwarz-attention operators of the form (17) satisfying these rank bounds.

Proof of Theorem 2. The rank of the coarse contribution is bounded by

$$\text{rank}(\Phi G_0 \Phi^T) \le \min\{r_0, \text{rank}(\Phi)\}.$$

Similarly,

$$\text{rank}\left(R_i^T D_i^{1/2} G_i D_i^{1/2} R_i\right) \le \min\{r_i, n_i\}.$$

The rank estimate follows by subadditivity of the rank. Since the best unstructured rank-R_{total} approximation of A^{-1} has Frobenius error

$$\left(\sum_{k=R_{\text{total}}+1}^{n-1} \lambda_k^{-2}\right)^{1/2},$$

no operator in $\mathcal{S}_{\text{Schwarz}}$, whose rank is bounded by R_{total}, can have a smaller Frobenius error. $\qquad\square$

A.7 Visualization of the Learned Operators

The learned operator structure can be inspected by visualizing the global operator, the local domain-decomposition contribution, the coarse contribution, and the full learned operator; see Figure A.8. Figure A.8 also visualizes the interface hat functions in the lower rightmost panel. In Figure A.9 the learned attention blocks are visualized. Figure A.10 visualizes the Φ^T-matrix, which collects the hat functions as its rows.

Figure A.8: Visualization of the learned hierarchical domain-decomposition attention operator. Top row, from left to right: sum of the local overlapping Schwarz contribution $M_{\mathrm{loc}} = \sum_i R_i^T D_i^{1/2} G_i D_i^{1/2} R_i$, the coarse contribution $M_0 = \Phi G_0 \Phi^T$, and the full learned operator $M_\theta^{-1} = M_{\mathrm{loc}} + M_0$. Bottom row, from left to right: the exact inverse A^{-1}, the normalized error $(M_\theta^{-1} - A^{-1})/\|A^{-1}\|_\infty$, and the interface-hat coarse basis functions ϕ_j used in the interpolation matrix Φ. The local contribution is block-local due to the subdomain restrictions, whereas the coarse contribution introduces global coupling; hence the assembled two-level operator is generally dense.

Figure A.9: Example of learned local low-rank attention blocks $G_i = Q_i K_i^T$ and coarse block $G_0 = Q_0 K_0^T$ for 8 subdomains and a coarse attention of size 7.

Figure A.10: Interface-hat coarse basis used in the restriction matrix Φ^T. For the decomposition into eight disjoint index sets, one hat function is associated with each pair of neighboring index sets, giving seven coarse basis functions. These functions span the coarse space on which the coarse attention block $G_0 = Q_0 K_0^T$ acts before being lifted to the fine grid as $\Phi G_0 \Phi^T$.