Supplementary for TaMMa: Target-driven Multi-subscene Mobile Manipulation

Jiawei Hou, Tianyu Wang, Tongying Pan, Shouyan Wang,
Xiangyang Xue, Yanwei Fu

A Setups

In this section, we illustrate the physical setup of the environment, robotic, and the target objects. Moreover, we list the parameters and settings of the employed models in detail.

A.1 Physical Setup

Robotic Setup. The construction of mobile base is shown in Fig.A1. The mobile base mainly carries a Franka Panda arm and a PC which takes control of the mobile base and arm. The maximum velocity of mobile base is set to $1m/s$ and the Franka arm is controlled by MoveIt library. The linear velocity is set to $0.2m/s$, and gripper force is set to $5N$. The robotic is placed initially about $1m$ away from the main experimental environment. A Realsense D435 camera is employed and attached to the robotic arm end effector and calibrated with the easy-hand-eye package. The gripper is a 3D-printed model with a length of 5 cm. For the mobile base, we employ the SLAMTEC Hermes, equipped with a laser radar for simplified mapping, localization, obstacle avoidance, and navigation. A comparison of the robotic setup with other related works is listed in Tab. 1 which shows our versatility and simplicity.

Methods	Camera	Robotic Arm	Robotic Base
CLIP-Fields[1]	iPhone 13Pro with LiDAR	Hello Robot Stretch (not used)	Hello Robot Stretch
F3RM[2]	RealSense D415	Franka Panda Arm	-
OK-Robot[3]	RealSense D435	Hello Robot Stretch	Hello Robot Stretch
Mobile ALOHA[4]	Logitech C922x Pro Stream Webcam * 4	ViperX 300 Robot Arm 6DOF * 2 WidowX 250 Robot Arm 6DOF * 2	Self-constructed
AMM.[5]	RealSense D435 RealSense T265	xArm	AgileX Ranger Mini 2
TeleMoMa[6]	RealSense	Tiago++ robot	Tiago++ robot
TaMMa(Ours)	RealSense D435	Franka Panda Arm	SLAMTEC Hermes

Table 1: Comparison of robotic setups with representative previous works.

Environment Setup. The subscenes taken as an experiment example in our paper is a multi-tabletop scene in a big room. We set up 3 tables of different sizes in the scene, arranged in a triangular pattern, with an average distance of 1 m between the tables, as shown in the diagram. The objects on the tables can be categorized as (1) daily-used containers, such as cups, bottles, plates, baskets, pen holders, and a sink, (2) geometric objects like cubes, (3) challenging objects for grasping, such as rubber toys, irregular toy models, and transparent objects. The arrangement of objects on the tables is relatively random.

8th Conference on Robot Learning (CoRL 2024), Munich, Germany.

Figure A1: The construction of the robotic setup. The mobile base mainly carries a Franka Panda arm and a PC which takes control of the mobile base and arm.

A.2 Experiment Setup

As for task evaluation:

1) Pick & Place. The task is thought to be completed when robotic successfully catch the target object from a subscene, move to another subscene and put down it on the destination point without falling on the first attempt.

2) Stacking. The task is thought to be successful when robotic collects objects from different scenes and stacks them as instructed on the first attempt, during which no object falling happens and the stacked objects won't fall over without external forces.

3) Tidy-up. The task is successful when robotic recognizes all the objects needed to be rearranged and carries them to the target destination without leftover.

4) Pouring. We prepare $300ml$ water in a plastic bottle. We consider the task successful if robotic could carry the bottle from one subscene to another subscene without falling and pour the water into the target cup more than $150ml$.

A.3 Model Setup

Gaussian Reconstruction. For the Gaussian-Splatting-based scene reconstruction, we employ the widely-used open-source 3DGS[7] code base. The initial point clouds used as the Gaussian initialization are downsampled by a factor of 5. The rendering process generates results as the origin image resolution of 640×480. Subsequently, Gaussians are optimized for 30,000 iterations across all scenes, utilizing the same loss function, Gaussian density, schedule, and hyperparameters as specified in the original implementation, which includes a learning rate dynamically adjusts based on the iteration number and a densification process that starts early in training and continues until the specified iteration threshold. The densification parameters are finely tuned, with densification performed every 100 iterations, an opacity reset interval of 1,000 iterations, and a gradient threshold for densification set to 0.01.

Depth Completion. The depth inpainting process is powered by a diffusion model which is built upon Latent Diffusion Models (LDMs) [8, 9, 10, 11] using a pre-trained Variational Auto-Encoder (VAE) and a U-Net-based[12] denoising architecture. Utilizing the frozen VAE, we encode both the color image and the depth map into a latent space, forming the basis for training our conditional denoiser. The depth map is repeated at channels to form a tri-channel input as an RGB image and is normalized. A composite feature map is constructed by concatenating the encoded depth and image elements. The denoising step is set to 20 at inference as default to trade off the time consumption and the effect. The U-Net-based denoising architecture iteratively refines the depth latent by predicting and removing noise at each timestep, which is managed by the DDIM[10] scheduler to ensure that noise is progressively reduced in control.

Gaussian Merging and Fine-tuning. With the corresponding camera pose and obtained depth map of the inpainted image, the 2D inpainted data is unprojected into a 3D colored point cloud from image space. Then, features from the original and inpainted Gaussian point clouds are merged by concatenating their poses, features, and opacities. To remove floaters at the edges of the mask, the minimum number of points within a radius of 0.1 for a point to be considered not an outlier is set to 100 as default. The following fine-tuning process optimizes the model using a combination of L1 loss and D-SSIM (Differentiable Structural Similarity Index) to ensure that the final rendered results closely match the inpainted reference images. The weight parameters are set to 0.8 and 0.2 respectively, reflecting the emphasis on maintaining a balance between pixel-wise accuracy and perceptual similarity. The optimization is performed over 150 iterations to achieve the final Gaussian model.

B Task Videos

We provide videos illustrating our cross-subscene fine-grained manipulation ability on 4 tasks. Each of the interacting objects can be located in the arbitrary sub-scenes.

Pick and Place. The input query is in the form of "Move the [A] to the [B]", where [A] and [B] are objects in the whole scene. For example, in the video, we set "Move the pink cup to the white plate", in which objects lie on 2 separate tables.

Stacking. The input query is in the form of "Stack the [A] onto the [B]", where [A] are objects to be stacked and [B] is the target place. In the video, we show the result of applying "Stack the orange cubes onto the blue cube". In this case, orange cubes on different tables will be collected and placed on the blue one.

Pouring. The query is in the form of "Pour the liquid in the [A] into the [B]", where [A] is the container that has liquid in it and [B] is the target container. We show the result of "Pour the liquid in the bottle into the white cup". In this example, the robotic carries the bottle smoothly to the cup and rotates the bottle to pour.

Tidy-up. The query is in the form of "Tidy up the table with [A]", where [A] is the representative objects of a subscene. For example, the video shows the result of "Tidy up the table with toys and cups". In this example, the small objects on the table with toys and cups will be rearranged into a basket.

Long term tasks in complex environment with obstacles and more than 3 subscenes. To demonstrate the manageability of our approach in a complex environment with multi-subscenes beyond toy-example tabletops, we conduct an experiment instructed by "Pour the water from the shelf bottle into the pot, discard the bottle, and place the cleaning sponge in the pot." The environment is conducted with 4 subscenes: shelf, sink, table1, and table2, including obstacles on the way. The subscene setting is just like the daily look as shown in Fig.B1.

C Mobile Manipulation

Point Cloud Extraction To extract a scene-wide point cloud for manipulation, we reconstructed the entire scene based on 3D Gaussian Splatting [7] and performed depth completion using diffusions [10, 8]. Starting from the completed depth map, we performed back-projection to obtain point clouds of several sub-scenes. Subsequently, we transformed the point clouds into the robot's working coordinate system , and executed specific navigation or manipulation tasks based on the transformation matrices of the movement base and end-effector relative to the working coordinate system.

Navigation and Manipulation The navigation process is finished by employing the API provided by the SLAMTEC mobile base. Specifically, a 2D topdown occupancy map is built for the environment as the scene map. Based on the occupancy map, the trajectory planning and obstacles avoidance is completed by querying the map with the target position and the current position. By

| Sink | Sink & Table1 | Table1 | Table1 & Table2 |
| Obstacles | Table2 | Table2 & Shelf | Shelf |

Figure B1: The complex environment setup with obstacles and more than 3 subscenes, which is conducted to demonstrate the manageability of our proposed method.

generating a set of waypoints, the mobile base is guided to the target position. As for manipulation, Franka Panda Arm is operated through the MoveIt! library [13]. We provide the 6 DoF pose of the target and employ the movement API to approach and operate the gripper to close and open depending on the width of the estimated target objects.

Motion Planning based on 6D Pose Some fine-grained robotic manipulations mainly rely on the 6D pose of the target for motion planning [14]. In the motion planning process of TaMMa, we integrated a depth-only pose estimation method, as the state of objects in 3D space is crucial for determining meaningful manipulation points across various tasks. Specifically, since the poses of intra-category instances are pre-normalized [15], it becomes highly advantageous to define task-relevant category-level grasping poses. These defined grasping poses are then transformed from object coordinates to camera coordinates using the estimated 6D object poses. The robot subsequently performs motion planning to move its gripper to the target grasping pose to accomplish each task. Based on the poses of different category-level objects and the tasks to be performed (e.g., pouring, stack), we utilized MoveIt! [13] to set up target-driven action sequences. Therefore, the success rate of robotic manipulation heavily depends on the accuracy of pose estimation. Fig. C1 presents the qualitative results of pose estimation across different scenes. The top row of Fig. C1 demonstrates the excellent poses in most cases. However, there are instances where the results are suboptimal, often due to inaccurate depth data. This can be observed in the bottom two rows. When we attempt to acquire the pose of the "black pen," the original depth (left column) and the completed depth (right column) are both unsatisfactory, affecting the subsequent pose estimation process.

D   Failure Cases

Capture Failures. Accurate camera pose is crucial for scene reconstruction. During the experimentation process, we discovered that the jittering and offset errors of the mobile base and robotic arm could result in inaccurate camera poses used for scene reconstruction. Consequently, this leads to errors in the initialization and optimization processes of Gaussians, resulting in issues such as ghosting in the reconstructed scene. One possible solution is to reduce the movement speed of the base and robotic arm, capture data only when they are stable, and minimize frequent movements of the chassis as much as possible. The visualization of comparison is shown in Fig. D1.

Segmentation Failures. Our experiments have shown that when using a segmentation model based on SAM[16] as a mask for image inpainting and depth completion, the inaccuracy of the mask can result in incomplete object editing, leaving behind edges or blurry traces. A more precise mask can

Figure C1: The qualitative results of pose estimation under different scenes. The top row shows the excellent poses under the corresponding views. The two bottom rows show unmet poses ("Pen") with depth. In these bottom rows, the left column presents the original depths acquired by the depth camera, while the right column shows the depths completed using our method.

Figure D1: The comparison of reconstruction failure caused by camera jittering and the successful results.

Figure D2: The comparison of inpainting failures caused by inaccurate masks and the successfully inpainted Gaussians results.

achieve better visual effects. The comparison inpainting results between using inaccurate masks and refined masks are shown in Fig. D2.

E   Detailed Illustration of Limitations

Monocular Depth Estimation. In practical applications of robotic arm manipulation, it is common to use the depth values directly captured by a depth camera as the input for scene modeling and object pose estimation. This is because the depth values provided by a depth camera are absolute depth values, which differ from the relative depth typically obtained through monocular depth estimation. This absolute depth information is highly valuable for practical operations. However, depth camera captured results often exhibit errors and significant uncertainty, particularly at the edges of the camera's field of view and when dealing with transparent or reflective objects. These factors raise issues in performing operations in challenging scenarios. In this paper, we utilize a diffusion-based depth completion method to partially address the discontinuities and errors present in the depth camera

results. However, the completed depth results still contain certain errors compared to the original absolute depth input. How to leverage depth maps from multiple viewpoints to supplement depth maps from a single viewpoint and obtain a dense and reliable point cloud remains an open question. What's more, the object occlusion may also cause depth completion failure. As mentioned above, even the diffusion-based method is also unable to solve the depth prediction problem for objects with severe occlusion. Additionally, for transparent objects, objects located behind them can also affect depth and pose estimation. To manage this issue in 3D space, amodal-based method will be our future work direction.

3D Objects Inpainting. Calculating precise poses for robotic arm manipulation has always been an open and challenging problem, especially in scenarios lacking constraints. For example, it is difficult for a robotic arm to place a cup in the exact middle of the plate to achieve the same level of precision as a human. Similarly, stacking blocks together is challenging for a robotic arm to achieve a perfect appearance. These results stem from two main reasons: the difficulty of endowing the robotic arm with real-time adjustment capabilities and the inability of the arm to obtain accurate pose information of the target location. Through a comparison with existing successful robotic arm grasping tasks, we observed that while the estimation of graspable object poses can now yield fairly accurate results, it remains challenging to estimate the precise poses required for tasks such as placing a cup in the center of a plate or achieving perfect block stacking. Consequently, we propose using inpainting techniques, employing a "think before you do it" approach, to address this issue. We first edit the images and depth maps, followed by editing Gaussians to create a 3D representation of the desired task-completed scenario. We then estimate the poses of the target objects in this scene to obtain a more accurate target pose for interaction. However, implementing this approach still presents difficulties. The current Gaussians inpainting methods perform well for editing relatively planar objects but struggle with editing voluminous and complex-shaped objects. Therefore, our future research direction will focuse on how to edit objects in 3D space to obtain accurate results that can be used for interactive operations.

More Complex and Larger-scale Scenes. We have successfully evaluated our approach in an environment at about $200m^2$ with about 10 subscenes. The obstacles set on the way are boxes, chairs, and objects with regular geometry with widths larger than $5cm$. Each obstacle is observed by about 3 frames from the camera when recording the environment. As for environments with a larger number of subscenes, the whole scene is represented with united Gaussians, and subscenes are divided by humans according to the distribution of optional interactive objects. We consider a part as a subscene when there are many objects that need careful perception. The number of subscenes doesn't affect the Gaussians optimization. However, more sampled images are needed for better results when there are more objects. As for the movement and manipulation, the target object localization takes a text query as input and outputs a coarse 3D position, while manipulation takes a task query as input and outputs manipulation strategy. The above steps are totally free from the number of subscenes. Consequently, the number of subscenes does not affect our approach. As for environments with larger scales and areas, this mainly affects the computation and memory that build the Gaussians of the environment. Taking advantage of our coarse-to-fine approach, the point cloud initialization of the Gaussians could be sub-sampled to an appropriate scale, and further optimization could be conducted on the subscene with more interests. Further to this end, lots of recent works have made great progress on expanding the Gaussians application to un-constrained and larger scenes. This would be one of our future directions to optimize the Gaussians for application in a larger-scale scene.

Transparent, Reflective, and Complex Shape Objects. The challenging objects' appearance mainly affects the depth estimation and the inpainting process. Reflective and transparent objects hesitate in their optical characteristics, making it difficult for depth cameras to capture precise depths, thus affecting subsequent depth completion processes. Transparent objects are easily influenced by other objects when occluding or being occluded, causing depth estimation to be affected, resulting in phenomena like depth truncation. Similarly, in complex backgrounds, similar phenomena may occur. Reflective objects are prone to distortion and pseudo-shadow phenomena in depth.

Figure E3: The example of inpainting transparent objects and objects with complex shapes. Current model can handle a number of these challenging objects but some blurs, shadows, and noise still exist.

Objects with complex shapes affect the accuracy of depth estimation, with depth cameras showing differences in attention to detail, and small parts being easily overlooked during depth estimation. Furthermore, for object inpainting, errors in depth estimation and the complex relationship between shapes, textures, and backgrounds can lead to a decrease in inpainting effects. Fig.E4 and E3 show some examples of objects with transparent ones and complex shapes, demonstrating our model's ability to manage a number of challenging objects. However, such challenging situations can cause blurs, shadows, and noises. Therefore, one of our future research directions is to optimize the depth and pose estimation of challenging objects in 3D space under multi-view observations and introduce various shape priors for common shapes to further enhance the representation accuracy of objects.

F   Implementation Details of Comparison Methods

For the cross-subscene mobile manipulation task, only a few works have been open-sourced. In this paper, we choose F3rm[2] and HomeRobot[17] as the comparison methods. To enable them with the cross-subscene ability in our environment, we re-implement and fine-tune these methods for the aiming tasks. Regarding real-world robotic tasks, we conduct evaluations across ten distinct scenes per task, each featuring novel objects from various categories in arbitrary poses. We ensure that the scenes are reset to approximately the same configuration for each method being compared.

F3rm. We implement F3rm to expand its workspace to the cross-subscene environment. For the data source, the same images from RealSense D435 are used as input, and to be fair, the depth images are also employed to train the implicit representation as an additional loss. The camera poses come from the calibrated camera on the robotic arm. As the environment expands, the need for VRAM increases obviously. Fairly, we maximize the VRAM usage of the RTX 3090 by employing a smaller feature resolution, as mentioned in F3rm, and ignoring the regions out of the tabletop workspace. As for the manipulation process, we first drive the mobile base to ensure the manipulation targets are reachable for the robotic arm and optimize the target pose for manipulation.

HomeRobot. We implement HomeRobot in our environment for the cross-subscene task. The provided Detic and Grounded-SAM libraries are employed to get semantics. The exploration of the environment is replaced by feeding the recorded RGB-D sequences to the HomeRobot, and the navigation and planning of the mobile base is implemented in the same way as our proposed *TaMMa*.

(a) View-1 of Transparent objects

(b) View-2 of Transparent objects

(c) View-3 of Transparent objects

Figure E4: The qualitative results of transparent objects from multiple views. (a) and (b) illustrate the pose estimation of the same object ("Transparent Bottle") from different viewpoints. The top trow presents the results based on the original depth, while the bottom row shows the results based on the enhanced depth. (c) shows the different bottle from another view, where a satisfactory pose estimation result is achieved even with the raw depth.

For mobile manipulation, the mobile base is first guided to approach the target, ensuring the targets are reachable, and the Contact Graspnet is employed to generate the 6 DoF grasp pose of the target. The pose of the receptacle, the location on which the object is placed, comes from adjusting from a reference object. For example, to put the cup on a plate, we optimize the pose of the plate and add a bias on the y-axis to get the target pose of the cup.

G   Supplementary Pseudocode

Diffusion based Depth Completion. Algorithm 1 outlines the process for diffusion based depth completion, which provides a structured approach to filling in missing depth information with multiple views of RGB-D inputs, addressing common challenges in depth sensing tasks such as incomplete data or occlusions. Utilizing a diffusion process that leverages latent diffusion models (LDMs), the algorithm mainly consists of three steps: Initialize Diffusion Process, Perform Depth Diffusion, Refine Depth Maps. Finally, the algorithm outputs the refined and completed depth maps, which can be used for the following 6D Pose Estimation task to enhance the effect of its depth-based estimation method.

Algorithm 1 Diffusion based Depth Completion

1: **Input:**
2:     I_{RGB}: Set of RGB images of sub-scenes
3:     D_{init}: Set of initial depth maps
4:     M: Set of masks delineating the target completion region
5: **Output:**
6:     D_{enh}: Set of completed depth maps
7: **Step 1: Initialize Diffusion Process**
8: **for** each $d_j \in D_{init}$ and $i_j \in I_{RGB}$ and $m_j \in M$ **do**
9:     Apply a linear normalization via an affine transformation to d_j
10:     Leverage the frozen VAE encoder to encode normalized depth d'_j and i_j into latent space, which produces a 4-channel feature map z_j
11:     Resize m_j to align with the dimensions of z_j, yielding downsampled m'_j
12:     Create a composite feature map z_t by applying random noise to the above latent code
13: **end for**
14: **Step 2: Perform Depth Diffusion**
15: **for** each z_t **do**
16:     **for** $t = 1$ to T **do**
17:         Initialize U-Net with trained weights for depth completion and feed z_t into the U-Net-based denoiser
18:         Denoise and complete the depth map with interpolated depth values in uncertain areas
19:     **end for**
20:     Derive d^j_{enh} from the latent representation decoded by the VAE decoder
21: **end for**
22: **Step 3: Refine Depth Maps**
23: **for** each $d_{enh} \in D_{enh}$ **do**
24:     Apply channel-wise averaging to smooth the depth map d_{enh} for post-processing
25: **end for**
26: **Return** D_{enh}

Fine-grained 6D Pose Estimation based Manipulation. Algorithm 2 outlines the process for fine-grained 6D pose estimation based manipulation, which aims to precisely estimate the pose and size of objects within a scene and subsequently generate appropriate action sequences for cross-subscene manipulation tasks. The algorithm mainly consists of four primary steps: Grounded Visual Perception, Depth-based Category-Level Pose Estimation, Coordinate Transformation, Generate Target-driven Action Sequences. Finally, the algorithm returns the estimated 6D poses, 3D sizes, and the generated action sequences, which collectively enable precise and efficient manipulation across multi-subscenes.

Algorithm 2 Fine-grained 6D Pose Estimation based Manipulation

---

1: **Input:**
2: I_{RGB}: Set of RGB images of sub-scenes
3: D_{enh}: Set of depth-enhanced depth maps
4: Q: Set of attributes of instances as queries
5: T: Specific types of manipulation tasks
6: **Output:**
7: P_{6D}: Estimated 6D pose for each instance
8: S_{3D}: Estimated 3D size for each instance
9: A: Target-driven action sequences based on estimated poses
10: **Step 1: Grounded Visual Perception**
11: **for** each $q \in Q$ **do**
12: **for** each $I \in I_{RGB}$ **do**
13:    Apply Grounded-Light-HQSAM to obtain mask $M_{I,q}$ for query q from I
14: **end for**
15: **end for**
16: **Step 2: Depth-based Category-Level Pose Estimation**
17: **for** each $M_{I,q}$ and $D \in D_{enh}$ **do**
18: Back-project the depth map D and mask $M_{I,q}$ into point clouds in the observed view
19: Utilize MVPoseNet6D to estimate 6D pose P_{6D}^i and 3D size S_{3D}^i for each instance i from the point clouds
20: **end for**
21: **Step 3: Coordinate Transformation**
22: **for** each P_{6D}^i **do**
23: Transform pose P_{6D}^i from the object coordinates to the camera coordinates
24: Transform pose P_{6D}^i from the camera coordinates to the robotic arm base coordinates
25: **end for**
26: **Step 4: Generate Target-driven Action Sequences**
27: **for** each P_{6D}^i **do**
28: Based on manipulation task type T, integrate each target pose P_{6D}^i
29: Invoke MoveIt! to generate the action sequence A_i
30: **end for**
31: **Return** P_{6D}, S_{3D}, A

Acknowledgments

Blabla

References

[1] N. M. M. Shafiullah, C. Paxton, L. Pinto, S. Chintala, and A. Szlam. Clip-fields: Weakly supervised semantic fields for robotic memory. *arXiv preprint arXiv:2210.05663*, 2022.

[2] W. Shen, G. Yang, A. Yu, J. Wong, L. P. Kaelbling, and P. Isola. Distilled feature fields enable few-shot language-guided manipulation. *arXiv preprint arXiv:2308.07931*, 2023.

[3] P. Liu, Y. Orru, C. Paxton, N. M. M. Shafiullah, and L. Pinto. Ok-robot: What really matters in integrating open-knowledge models for robotics. *arXiv preprint arXiv:2401.12202*, 2024.

[4] Z. Fu, T. Z. Zhao, and C. Finn. Mobile aloha: Learning bimanual mobile manipulation with low-cost whole-body teleoperation. *arXiv preprint arXiv:2401.02117*, 2024.

[5] H. Xiong, R. Mendonca, K. Shaw, and D. Pathak. Adaptive mobile manipulation for articulated objects in the open world. *arXiv preprint arXiv:2401.14403*, 2024.

[6] S. Dass, W. Ai, Y. Jiang, S. Singh, J. Hu, R. Zhang, P. Stone, B. Abbatematteo, and R. Martin-Martin. Telemoma: A modular and versatile teleoperation system for mobile manipulation. *arXiv preprint arXiv:2403.07869*, 2024.

[7] B. Kerbl, G. Kopanas, T. Leimkühler, and G. Drettakis. 3d gaussian splatting for real-time radiance field rendering. *ACM Transactions on Graphics*, 42(4), July 2023. URL https://repo-sam.inria.fr/fungraph/3d-gaussian-splatting/.

[8] R. Rombach, A. Blattmann, D. Lorenz, P. Esser, and B. Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10684–10695, 2022.

[9] A. Blattmann, R. Rombach, H. Ling, T. Dockhorn, S. W. Kim, S. Fidler, and K. Kreis. Align your latents: High-resolution video synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 22563–22575, 2023.

[10] J. Ho, A. Jain, and P. Abbeel. Denoising diffusion probabilistic models. *arXiv preprint arxiv:2006.11239*, 2020.

[11] D. Podell, Z. English, K. Lacey, A. Blattmann, T. Dockhorn, J. Müller, J. Penna, and R. Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis. *arXiv preprint arXiv:2307.01952*, 2023.

[12] O. Ronneberger, P. Fischer, and T. Brox. U-net: Convolutional networks for biomedical image segmentation. In *Medical image computing and computer-assisted intervention–MICCAI 2015: 18th international conference, Munich, Germany, October 5-9, 2015, proceedings, part III 18*, pages 234–241. Springer, 2015.

[13] S. Chitta, I. Sucan, and S. Cousins. Moveit![ros topics]. *IEEE Robotics & Automation Magazine*, 19(1):18–19, 2012.

[14] S. Stevšić, S. Christen, and O. Hilliges. Learning to assemble: Estimating 6d poses for robotic object-object manipulation. *IEEE Robotics and Automation Letters*, 5(2):1159–1166, 2020.

[15] H. Wang, S. Sridhar, J. Huang, J. Valentin, S. Song, and L. J. Guibas. Normalized object coordinate space for category-level 6d object pose and size estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2642–2651, 2019.

[16] T. Wang, Y. Li, H. Lin, X. Xue, and Y. Fu. Wall-e: Embodied robotic waiter load lifting with large language model. *arXiv preprint arXiv:2308.15962*, 2023.

[17] S. Yenamandra, A. Ramachandran, K. Yadav, A. Wang, M. Khanna, T. Gervet, T.-Y. Yang, V. Jain, A. W. Clegg, J. Turner, et al. Homerobot: Open-vocabulary mobile manipulation. *arXiv preprint arXiv:2306.11565*, 2023.