Reference-based MRI Reconstruction Using Texture Transformer

Abstract

Deep Learning (DL) based methods for magnetic resonance (MR) image reconstruction have been shown to produce superior performance. However, previous methods either only leverage under-sampled data or require a paired fully-sampled auxiliary MR sequence to perform guidance-based reconstruction. Consequently, existing approaches neglect to explore attention mechanisms that can transfer texture from reference data to under-sampled data within a single MR sequence, which either limits the performance of these approaches or increases the difficulty of data acquisition. In this paper, we propose a novel **T**exture **T**ransformer **M**odule (**TTM**) for the reference-based MR image reconstruction. The TTM facilitates joint feature learning across under-sampled and reference data, so feature correspondences can be discovered by attention and accurate texture features can be leveraged during reconstruction. Notably, TTM can be stacked on prior MRI reconstruction methods to improve their performance. In addition, a **R**ecurrent **T**ransformer **R**econstruction backbone (**RTR**) is proposed to further improve the performance in a unified framework. Extensive experiments demonstrate the effectiveness of TTM and show that RTR can achieve the state-of-the-art results on multiple datasets. Implementation code and pretrained weights will be made public after the review process.

Keywords: MRI Reconstruction, Deep Learning, Transformer.

1. Introduction

Magnetic resonance imaging (MRI) is one of the most widely used noninvasive medical imaging techniques. However, due to the acquisition hardware limitation, the relatively slow data acquisition process of MRI impedes its development in many clinical applications. In addition to the exploitation of advanced hardware and parallel imaging (Pruessmann et al., 1999; Taouli et al., 2004; Niendorf and Sodickson, 2006), a common approach that can shorten the image acquisition time is Compressed Sensing (CS) (Haldar et al., 2010) where MR images are reconstructed from under-sampled k-space data. Though CS reconstruction methods are able to recover images, they lack the ability of recovering noise-like textures and introduce high-frequency oscillatory artifacts when large errors are not properly reduced during optimization (Ravishankar and Bresler, 2010).

Recently, DL-based methods have significantly improved the quality of recovered images in MRI reconstruction. Previous approaches are essentially based on two paradigms – single image reconstruction (SIR), and guidance-based image reconstruction (GIR). The SIR problem aims to recover a fully-sampled image from a single under-sampled k-space data, as shown in Fig. 1(a). Several SIR methods (Ronneberger et al., 2015; Eo et al., 2018; Schlemper et al., 2017; Wang et al., 2019; Guo et al., 2021a) have demonstrated superior

Figure 1: The schematics of different MRI reconstruction paradigms. It is worth noting that the matched reference in the proposed paradigm can be from another subject.

performance over the CS-based methods. However, in challenging cases, SIR methods often result in blurry artifacts, since the anatomic textures have been excessively degraded by the k-space under-sampling process. Several methods (Dar et al., 2020; Guo et al., 2020; Wang et al., 2020; Guo et al., 2021b; Zhou and Zhou, 2020) have focused on GIR, which explores feature correspondences from a paired fully-sampled auxiliary MR sequence to produce visually pleasing results. However, those approaches require a multi-modal dataset for training. For example, as shown in Fig. 1(b), reconstructing a T_2-weighted image requires a paired fully-sampled T_1-weighted image from the same subject as the reference, which significantly increases the difficulty of data acquisition and impedes the practicality of GIR methods.

To address these issues and inspired by the success of reference-based image restoration tasks (Yang et al., 2020; Vaswani et al., 2017), we propose a novel Texture Transformer Module (TTM) for MR image reconstruction. Specifically, we formulate the extracted features from the under-sampled image and the matched reference image as the query and key in a transformer. The produced attention maps are used to transfer the features from the reference image into the features extracted from the under-sampled data. As shown in Fig. 1(c), instead of relying on a paired auxiliary sequence as required by previous GIR methods, reconstructing a T_2-weighted image in the proposed paradigm only demands a matched fully-sampled T_2-weighted image from the reference data split, which can considerably alleviate the difficulty of data acquisition in case where subjects do not have paired auxiliary MR sequences. It is worth noting that exploring feature correspondences between different subjects is non-trivial, since human anatomy shares common radiographic patterns (Giedd et al., 2009). To the best of our knowledge, the proposed TTM is the the first attempt to explore relevance and transfer of texture features within a single MR sequence using a transformer.

In summary, the following are our key contributions: **1.** A new reference-based MRI reconstruction paradigm is formulated and the proposed TTM introduces a powerful way to promote joint feature learning across under-sampled and reference data within a single MR sequence. **2.** A recurrent transformer model, namely RTR, is further proposed for improving the reconstruction fidelity. **3.** Experiments on multiple datasets with different acceleration

Figure 2: (a) An overview of the proposed texture transformer module. (b) A schematic of unrolled iterations of the proposed RTR. STL consists of the Swin Transformer Layers.

factors show that TTM significantly boosts the performance of existing backbones in the proposed paradigm and the superiority of RTR in MRI reconstruction.

2. Methodology

Accelerated MRI reconstruction is an inverse problem in which the objective is to reconstruct a fully-sampled image from under-sampled k-space data. The data acquisition process can be formulated as follows:

$$x = F^{-1}(F_D y + \epsilon), \tag{1}$$

where x denotes the observed under-sampled image, y is the fully-sampled image, and ϵ denotes the noise. F and F^{-1} are the Fourier transform matrix and its inverse, respectively. F_D represents the under-sampling Fourier encoding matrix that is defined as the multiplication of the Fourier transform matrix F with a binary undersampling mask matrix D. The goal is to estimate y from the observed under-sampled reconstruction x.

2.1. Texture Transformer Module

Fig. 2(a) shows an overview of the proposed texture transformer module. x, x_{ref}, and y_{ref} represent the input under-sampled image, the under-sampled reference image, and the fully-sampled reference image, respectively. Since we apply the same under-sampling operations, x_{ref} is domain-consistent with x. The proposed TTM consists of five components as follows: feature extractor, relevance embedding module, hard attention module for feature transfer, soft attention module for feature synthesis, and a convolutional block for generating output. TTM takes x, x_{ref}, and y_{ref} as input, and outputs a synthesized under-sampled image $\bar{x}$, which contains real and imaginary channels and can be further used to generate the fully-sampled prediction $\bar{y}$ by a reconstruction backbone. In what follows, we describe different parts of TTM in detail.

Feature Extractor. Extracting accurate and proper texture information plays an essential role to facilitate the downstream fully-sampled MR image reconstruction. To encourage joint feature learning, we introduce a learnable feature extractor whose parameters are updated during training. Query (Q), Key (K), and Value (V) are three basic elements of the attention mechanism in a transformer (Vaswani et al., 2017), which are formulated as follows:

$$Q = FE(x), \quad K = FE(x_{\text{ref}}), \quad V = FE(y_{\text{ref}}), \tag{2}$$

where $FE(\cdot)$ denotes the output of feature extractor. The proposed feature extractor consists of 4 convolutional blocks. To enable high flexibility at expressing the structure of input data, the channel dimension of the output of feature extractor is set to 64.

Relevance Embedding Module. To embed the relevance between x and x_{ref}, the similarity between Q and K is estimated by the relevance embedding module. Q and K are unfolded into patches with size of 16×16 and we denote them as q_i and k_j, where i and j indicate the spatial locations of patches. For each patch pair between Q and K, we can calculate the relevance score $r_{i,j}$ by the normalized inner product as follows:

$$r_{i,j} = \left\langle \frac{q_i}{\|q_i\|}, \frac{k_j}{\|k_j\|} \right\rangle. \tag{3}$$

The obtained relevance scores are used to generate hard and soft attention maps.

Hard Attention Module. Hard attention module is designed to search the most relevant fully-sampled texture features from V. Rather than taking a weighted sum of V for each query q_i, only the most relevant feature in V is transferred for corresponding query q_i. Such design can prevent blurry outputs and promote the accuracy of transferring full-sampled texture features (Yang et al., 2020). Specifically, the i-th element h_i of the hard-attention map H can be calculated as follows:

$$h_i = \underset{j}{\text{argmax}}\, r_{i,j}. \tag{4}$$

Each h_i can be treated as a hard index which indicates the most relevant position in y_{ref} to the i-th position in x. Also, $V = FE(y_{\text{ref}})$ is unfolded into patches with size of 16×16 and the transferred texture features T from y_{ref} are selected by using H as the indices in Eq. 4. Let t_i denote the patch of T in the i-th position. Then, t_i is selected from the h_i-th position of V and can be expressed as $t_i = V_{h_i}$.

Soft Attention Module. Soft attention module aims to generate the synthesized features Z using the transferred texture features T and extracted features X from the input under-sampled image x. To take confidence of the transferred texture features into account during the synthesis process, a soft attention map S is calculated as follows:

$$s_i = \max_j r_{i,j}, \tag{5}$$

where s_i is the i-th position of the soft-attention map S which represents the confidence of the transferred texture features in this position. To avoid losing information from the input image, T and X are first fused, then the fused features are element-wise multiplied by the soft attention map S and added back to X to produce the synthesized features Z. This synthesis process can be expressed as follows:

$$Z = X + \text{Conv}(X \otimes T) \odot S, \tag{6}$$

where Conv represents a convolutional layer. $\otimes$ and $\odot$ denote the channel-wise concatenation and the element-wise multiplication, respectively. Finally, the channel dimension of the synthesized features Z is reduced to 2 (*i.e.*, real and imaginary channels) by a convo-

lutional block. The synthesized under-sampled image $\bar{x}$ containing the transferred texture features can be further used as the input of image reconstruction backbones. We use *mutual information* as the metric to create input-reference matches. More details of this matching process can be found in Appendix A.

2.2. Recurrent Transformer for MRI Reconstruction

Inspired by previous iterative MRI reconstruction approaches (Guo et al., 2021a; Qin et al., 2018; Wang et al., 2019) and recent advancements in transformer models (Liang et al., 2021; Liu et al., 2021), we propose a novel recurrent transformer model RTR for reference-based MRI reconstruction. Figure 2(b) shows the unrolled RTR iterations. RTR consists of a texture transformer module (TTM), two reconstruction blocks (RBs) and a fusion module (FM). Each RB contains a shallow feature extractor (SFE), Swin transformer layers (STL) (Liu et al., 2021) for deep feature extraction, and a reconstruction module (RM). SFE, RM, and FM are built based on convolution layers for efficient learning and stable optimization (Xiao et al., 2021). The last layer of RM is a data consistency layer that produces a linear combination between the network prediction and the original measurement for reinforcing the data consistency in the k-space (Schlemper et al., 2017). To avoid losing high-resolution information during reconstitution, two RBs map input to the original dimension but perform different down-sampling operations (*i.e.,* $\times 2$ and $\times 1$) controlled by SFE for multi-scale perception. Let RB_i denote the i-th reconstruction block. At each time step t, the hidden state $h_{RB_i}^{(t)}$ in RB_i is updated recursively as follows:

$$h_{RB_i}^{(t)} = SFE(\bar{x}^{(t)}) + STL(h_{RB_i}^{(t-1)}). \tag{7}$$

Then reconstruction module takes the updated hidden state to produce the output of RB_i. The workflow of RTR in the t-th iteration can be described as follows:

$$\bar{x}^{(t)} = TTM(\bar{y}^{(t-1)}, x_{ref}, y_{ref}),$$

$$\bar{y}_{RB_1}^{(t)} = RB_1(\bar{x}^{(t)}, h_{RB_1}^{(t-1)}),$$

$$\bar{y}_{RB_2}^{(t)} = RB_2(\bar{y}_{RB_1}^{(t)}, h_{RB_2}^{(t-1)}), \tag{8}$$

$$\bar{y}^{(t)} = FM(\bar{y}_{RB_1}^{(t)} \otimes \bar{y}_{RB_2}^{(t)}),$$

where $\otimes$ denotes the channel-wise concatenation. FM fuses outputs of two reconstruction blocks to produce the intermediate reconstruction result $\bar{y}^{(t)}$, which also servers as the input for the next recurrent iteration. As shown in Eq. 8, the proposed RTR is also able to perform conventional single image reconstruction by simply removing the stacked TTM. The detailed network configuration can be found in the Appendix B.

3. Experiments and Results

Dataset. Experiments are conducted on the IXI (brain development.org, 2015) and fastMRI (Knoll et al., 2020) datasets. 135 T_2-weighted axial brain MRI scans from IXI are analyzed. The training, validation, reference, and testing data splits are as 100/10/10/15. Each scan approximately provides 130 images. The fastMRI dataset contains 1,172 complex-valued single-coil coronal proton density (PD)-weighted knee MRI scans. The training, reference, and testing data splits are as 923/50/199. Each scan approximately provides 35

Figure 3: Visual comparison of different MRI reconstruction methods (AF=8) on (a) IXI and (b) fastMRI among 3 strategies. The second column of each sub-figure shows the absolute difference between the reconstructed image and the ground-truth.

Table 1: PSNR/SSIM comparisons among different strategies. AVG. Gain represents the performance changes compared to the Backbone. AF is the acceleration factor.

IXI (AF=4)						
Strategy	Reconstruction Backbone					AVG. Gain
	U-net	KIKI-Net	D5C5	OUCR	RTR (Ours)	
Backbone	33.49/0.9131	34.73/0.9456	36.61/0.9656	37.41/0.9736	38.16/0.9767	-
Ref+Backbone	33.52/0.9134	34.70/0.9438	36.38/0.9624	37.40/0.9735	37.89/0.9756	$-$ 0.10/$-$ 0.0012
TTM+Backbone	34.25/0.9238	36.91/0.9682	38.23/0.9744	38.22/0.9772	**38.90/0.9799**	$+$ 1.22/$+$ 0.0098
IXI (AF=8)						
Strategy	Reconstruction Backbone					AVG. Gain
	U-net	KIKI-Net	D5C5	OUCR	RTR (Ours)	
Backbone	28.65/0.8461	28.75/0.8628	29.35/0.8838	30.40/0.9089	30.97/0.9187	-
Ref+Backbone	28.61/0.8447	28.77/0.8652	29.29/0.8899	30.22/0.9062	30.69/0.9153	$-$ 0.11/$+$ 0.0003
TTM+Backbone	29.51/0.8636	30.21/0.9010	30.70/0.9160	31.38/0.9242	**32.39/0.9363**	$+$ 1.21/$+$ 0.0242
fastMRI (AF=4)						
Strategy	Reconstruction Backbone					AVG. Gain
	U-net	KIKI-Net	D5C5	OUCR	RTR (Ours)	
Backbone	31.78/0.7134	31.92/0.7180	32.18/0.7234	32.37/0.7282	32.48/0.7331	-
Ref+Backbone	31.81/0.7139	31.94/0.7180	32.14/0.7238	32.34/0.7278	32.47/0.7323	$-$ 0.01/$-$ 0.0001
TTM+Backbone	32.02/0.7188	32.16/0.7238	32.35/0.7271	32.52/0.7336	**32.61/0.7346**	$+$ 0.19/$+$ 0.0044
fastMRI (AF=8)						
Strategy	Reconstruction Backbone					AVG. Gain
	U-net	KIKI-Net	D5C5	OUCR	RTR (Ours)	
Backbone	29.65/0.6393	29.26/0.6387	29.57/0.6432	30.07/0.6535	30.40/0.6615	-
Ref+Backbone	29.66/0.6351	29.27/0.6377	29.58/0.6435	30.10/0.6539	30.33/0.6585	$-$ 0.01/$-$ 0.0015
TTM+Backbone	29.98/0.6481	29.70/06471	30.05/0.6531	30.39/0.6605	**30.72/0.6673**	$+$ 0.38/$+$ 0.0080

knee images. Since these two datasets originally lack the reference data split, we randomly sample scans as the reference data.

Implementation Details. All models were trained using the ℓ_1 loss with Adam optimizer based on the following hyperparameters: initial learning rate of 1.5×10^{-4} then reduced

Figure 4: Boxplots of reconstruction performance on IXI among five methods. ①, ②, and ③ represent Backbone, Ref+Backbone, and TTM+Backbone, respectively.

by a factor of 0.9 every 5 epochs; 50 maximum epochs; batch size of 8; the number of recurrent iterations T of 3 (if applicable). The sampling mask function with $4\times$ and $8\times$ accelerations is used for simulating the complex-valued k-space measurements. Structural Similarity Index Measure (SSIM) and Peak Signal-to-Noise Ratio (PSNR) are used as the evaluation metrics for comparisons. We implement the proposed model using PyTorch on Nvidia RTX8000 GPUs.

Reconstruction Results. To evaluate the effectiveness of the proposed TTM, we observe the performance change of adding TTM to five MRI reconstruction methods, including U-net (Ronneberger et al., 2015), KIKI-Net (Eo et al., 2018), D5C5 (Schlemper et al., 2017), OUCR (Guo et al., 2021a), and the proposed RTR. For a fair comparison, U-net (Ronneberger et al., 2015) is modified for data with real and imaginary channels and a data consistency (DC) layer is added at the end of the network. Table 1 shows the results corresponding to five reconstruction methods evaluated on different acceleration factors (AF). We first compare the performance of different methods without any modifications and denote them as **Backbone**. It is also possible to naively leverage information provided by the reference images. In this case, we just concatenate the reference image with the input as additional channels. The results corresponding to this strategy are shown in Table 1 under the label **Ref+Backbone**. It is worth noting that TTM is removed from our proposed RTR for fair comparisons in the above two scenarios. Finally, we can obtain models that use the proposed TTM to transfer texture information to facilitate reconstruction backbones. These experiments are denoted as **TTM+Backbone**.

From Table 1, we can make the following observations: (i) The proposed RTR achieves the best performance across three training strategies for all acceleration factors. The superior performance of RTR demonstrates the merit of the proposed transformer architecture. (ii) Naively treating the reference image as an additional input cannot improve the reconstruction performance. Due to the lack of an efficient mechanism of searching and transferring the texture information in the reference images, it results in slightly lower performance across four different methods. For example, the AVG. Gain of Ref+Backbone strategy is -0.10 dB and -0.11 dB on IXI for AF=4 and AF=8, respectively. (iii) By using the proposed TTM, we are able to achieve obvious improvements as compared to the models that naively use the reference images and the original backbones. As shown in Table 1, the AVG. Gain is about 1.2 dB in experiments of two accelerations on IXI. (iv) The effectiveness of TTM is consistent across different reconstruction methods, acceleration factors, and datasets. Even for the powerful iterative methods (*i.e.*, OUCR (Guo et al., 2021a) and our proposed RTR), the proposed TTM still can improve the reconstruction quality by 0.32

dB on fastMRI for AF=8 (the most challenging scenario). As shown in Appendix C, all reported improvements achieved by RTR are statistically significant ($p < 0.05$).

Fig. 4 shows the boxplots of reconstruction quality in different strategies. We can observe that the overall spread of metrics is shifted to the right in TTM+Backbone, which implies the effectiveness of our proposed TTM for the most test cases. Fig. 3 shows the qualitative performance of different methods. As can be seen from the error maps, the proposed RTR yields the reconstructed images with remarkable visual similarity to the GT images compared to the other methods across two datasets. Meanwhile, all models that make use of TTM exhibit a better ability of suppressing the overall errors (see error maps in Figure 3), which is consistent with our quantitative results.

Table 2: Ablation study of proposed modules Table 3: Ablation study of proposed modules in TTM. in RTR.

Method	HA	SA	PSNR/SSIM
Base			33.49/0.9131
SA+Base		✓	33.86/0.9156
HA+Base	✓		34.07/0.9172
TTM+Base	✓	✓	34.25/0.9238

Method	RB_1	RB_2	FM	TTM	PSNR/SSIM
RB_1	✓				36.02/0.9589
RB_1 +RB_2	✓	✓			37.38/0.9707
RTR	✓	✓	✓		38.16/0.9764
TTM+RTR	✓	✓	✓	✓	38.90/0.9799

Ablation Study. The contribution of the proposed TTM is demonstrated by comparisons between three training strategies in Table 1. Moreover, we conduct a detailed ablation study on IXI (AF=4) to analyze the effectiveness of different components in the proposed TTM. In this case, we use U-net (Ronneberger et al., 2015) as our base model. On top of the base model, we progressively add hard attention module (HA) and soft attention module (SA). Ablation results are shown in Table 2. As one can see, both HA and SA show positive contributions in term of the reconstruction quality. After adding SA, relevant texture features are enhanced and the less relevant ones are suppressed during feature synthesis. When HA is added, PSNR is improved from 33.49dB to 34.07dB, which demonstrates the effectiveness of HA in feature transformation. It is worth noting that the structure of TTM is compact, so it only introduces a few extra trainable parameters. In addition, Table 3 shows the ablation study of the proposed modules in RTR. The ablation study regarding the robustness to reference images of different similarity and additional visualizations can be found in Appendix D.

4. Conclusion

In this paper, we proposed a novel TTM for the MR image reconstruction task which is able to transfer texture features from the reference image to the under-sampled image. Unlike previous guidance-based MRI reconstruction methods, TTM is able to explore the reference images within a single MR sequence and does not require paired auxiliary MR sequences. Moreover, the proposed TTM can be directly stacked on the existing MRI reconstruction methods to further improve their performance. In addition, RTR is further proposed to reconstruct high-quality MR images in a unified framework. Recurrent transformer-based design in RTR leads to outstanding performance in both single image reconstruction and the proposed reference-based reconstruction paradigms. Experimental results demonstrate the effectiveness of the proposed TTM in multiple MRI reconstruction approaches as well as the promising potential of applying transformer-based models in the MRI reconstruction task.

References

brain development.org. IXI dataset, 2015. URL https://brain-development.org/ixi-dataset/.

Salman UH Dar, Mahmut Yurt, Mohammad Shahdloo, Muhammed Emrullah Ildız, Berk Tınaz, and Tolga Çukur. Prior-guided image reconstruction for accelerated multi-contrast mri via generative adversarial networks. *IEEE Journal of Selected Topics in Signal Processing*, 14(6):1072–1087, 2020.

Taejoon Eo, Yohan Jun, Taeseong Kim, Jinseong Jang, Ho-Joon Lee, and Dosik Hwang. Kiki-net: cross-domain convolutional neural networks for reconstructing undersampled magnetic resonance images. *Magnetic resonance in medicine*, 80(5):2188–2201, 2018.

Jay N Giedd, Francois M Lalonde, Mark J Celano, Samantha L White, Gregory L Wallace, Nancy R Lee, and Rhoshel K Lenroot. Anatomical brain magnetic resonance imaging of typically developing children and adolescents. *Journal of the American Academy of Child and Adolescent Psychiatry*, 48(5):465, 2009.

Pengfei Guo, Puyang Wang, Jinyuan Zhou, Vishal M Patel, and Shanshan Jiang. Lesion mask-based simultaneous synthesis of anatomic and molecular mr images using a gan. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 104–113. Springer, 2020.

Pengfei Guo, Jeya Maria Jose Valanarasu, Puyang Wang, Jinyuan Zhou, Shanshan Jiang, and Vishal M. Patel. Over-and-under complete convolutional rnn for mri reconstruction. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 13–23. Springer, 2021a. ISBN 978-3-030-87231-1.

Pengfei Guo, Puyang Wang, Rajeev Yasarla, Jinyuan Zhou, Vishal M. Patel, and Shanshan Jiang. Anatomic and molecular mr image synthesis using confidence guided cnns. *IEEE Transactions on Medical Imaging*, 40(10):2832–2844, 2021b. doi: 10.1109/TMI.2020.3046460.

Justin P Haldar, Diego Hernando, and Zhi-Pei Liang. Compressed-sensing mri with random encoding. *IEEE transactions on Medical Imaging*, 30(4):893–903, 2010.

Florian Knoll et al. fastmri: A publicly available raw k-space and dicom dataset of knee images for accelerated mr image reconstruction using machine learning. *Radiology: Artificial Intelligence*, 2(1):e190007, 2020.

Jingyun Liang, Jiezhang Cao, Guolei Sun, Kai Zhang, Luc Van Gool, and Radu Timofte. Swinir: Image restoration using swin transformer. In *IEEE International Conference on Computer Vision Workshops*, 2021.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. *International Conference on Computer Vision (ICCV)*, 2021.

Thoralf Niendorf and Daniel K Sodickson. Parallel imaging in cardiovascular mri: methods and applications. *NMR in Biomedicine: An International Journal Devoted to the Development and Application of Magnetic Resonance In vivo*, 19(3):325–341, 2006.

Klaas P Pruessmann, Markus Weiger, Markus B Scheidegger, and Peter Boesiger. Sense: sensitivity encoding for fast mri. *Magnetic Resonance in Medicine: An Official Journal of the International Society for Magnetic Resonance in Medicine*, 42(5):952–962, 1999.

Chen Qin, Jo Schlemper, Jose Caballero, Anthony N Price, Joseph V Hajnal, and Daniel Rueckert. Convolutional recurrent neural networks for dynamic mr image reconstruction. *IEEE transactions on medical imaging*, 38(1):280–290, 2018.

Saiprasad Ravishankar and Yoram Bresler. Mr image reconstruction from highly undersampled k-space data by dictionary learning. *IEEE transactions on medical imaging*, 30 (5):1028–1041, 2010.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

Jo Schlemper, Jose Caballero, Joseph V Hajnal, Anthony N Price, and Daniel Rueckert. A deep cascade of convolutional neural networks for dynamic mr image reconstruction. *IEEE transactions on Medical Imaging*, 37(2):491–503, 2017.

Bachir Taouli, Alastair J Martin, Aliya Qayyum, Raphael B Merriman, Daniel Vigneron, Benjamin M Yeh, and Fergus V Coakley. Parallel imaging and diffusion tensor imaging for diffusion-weighted mri of the liver: preliminary experience in healthy volunteers. *American Journal of Roentgenology*, 183(3):677–680, 2004.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *arXiv preprint arXiv:1706.03762*, 2017.

Puyang Wang, Eric Z Chen, Terrence Chen, Vishal M Patel, and Shanhui Sun. Pyramid convolutional rnn for mri reconstruction. *arXiv preprint arXiv:1912.00543*, 2019.

Puyang Wang, Pengfei Guo, Jianhua Lu, Jinyuan Zhou, Shanshan Jiang, and Vishal M Patel. Improving amide proton transfer-weighted mri reconstruction using t2-weighted images. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 3–12. Springer, 2020.

Tete Xiao, Piotr Dollar, Mannat Singh, Eric Mintun, Trevor Darrell, and Ross Girshick. Early convolutions help transformers see better. *Advances in Neural Information Processing Systems*, 34, 2021.

Fuzhi Yang, Huan Yang, Jianlong Fu, Hongtao Lu, and Baining Guo. Learning texture transformer network for image super-resolution. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5791–5800, 2020.

Bo Zhou and S Kevin Zhou. Dudornet: learning a dual-domain recurrent network for fast mri reconstruction with deep t1 prior. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4273–4282, 2020.

Appendix A. Mutual Information-Based Matching.

We match input under-sampled image x with a corresponding under-sampled reference image x_{ref} and consequently find the the fully-sampled reference image y_{ref} from the reference data split during data preprocessing. It is important to accurately identify the matched slices between under-sampled images and the reference data in the proposed paradigm. We exploit a simple yet effective mutual information(MI)-based slice matching algorithm that can find the closest corresponding slice in reference data.

Let $\mathcal{X}_{\mathrm{ref}} = \{x_{\mathrm{ref}}^k | i = 1, 2, \ldots, n\}$ be a set that contains n under-sampled slices of reference data, where $x_{\mathrm{ref}}^k = F^{-1}(F_D y_{\mathrm{ref}}^k + \epsilon)$ and $x = F^{-1}(F_D y + \epsilon)$ have the same under-sampling operation F_D. The MI between x and x_{ref}^k can be calculated as follows:

$$\mathrm{MI}_k = H(x) + H(x_{\mathrm{ref}}^k) - H(x, x_{\mathrm{ref}}^k), \tag{9}$$

where $H(x)$ is the individual entropy of x and $H(x, x_{\mathrm{ref}}^k)$ is the joint entropy between x and x_{ref}^k. The matched index indicates the most relevant slice in reference data can be found by solving:

$$\underset{k}{\mathrm{argmax}}\ \mathrm{MI}_k. \tag{10}$$

Appendix B. Additional Implementation Detials.

Table 4: Configuration of TTM. TTM only consists of 0.7M trainable parameters, which are negligible compared to reconstruction backbones.

Block	Layer	In Chanel	Out Chanel	Kernel size	Stride	Padding
Feature Extractor	Conv	2	64	3	1	1
	ReLu	64	64	-	-	-
	Conv	64	64	3	1	1
	ReLu	64	64	-	-	-
	Conv	64	64	3	1	1
	ReLu	64	64	-	-	-
Conv Block	ResBlock	64	64	3	1	1
	ResBlock	64	64	3	1	1
	ResBlock	64	64	3	1	1
	ResBlock	64	2	3	1	1

Table 5: Configuration of RTR. Swin is a Swin Transformer Layer.

Module	Block	Layer	kernel size	Stride	Padding	In chanels	Out chanels
RB$_1$	SFE	Conv	3	1	1	2	96
		ReLu	-	-	-	96	96
		Conv	4	2	1	96	96
	STL	Swin	-	-	-	96	96
		Swin	-	-	-	96	96
		Swin	-	-	-	96	96
		Swin	-	-	-	96	96
	RM	TransposeConv	4	2	1	96	96
		ReLu	-	-	-	96	96
		TransposeConv	3	1	1	96	2
RB$_2$	SFE	Conv	3	1	1	2	48
		ReLu	-	-	-	48	48
		Conv	3	1	1	48	48
	STL	Swin	-	-	-	48	48
		Swin	-	-	-	48	48
	RM	TransposeConv	3	1	1	48	48
		ReLu	-	-	-	48	48
		TransposeConv	3	1	1	48	2

Appendix C. Statistical Significance Tests.

Table 6: The p values of statistical significance among different methods. To investigate the performance improvement of the proposed RTR, we conduct paired t-test based on the PSNR of the reconstructed images between RTR and other methods.

Strategy	IXI (AF=4)					IXI (AF=8)				
	U-net	KIKI-Net	D5C5	OUCR	RTR	U-net	KIKI-Net	D5C5	OUCR	RTR
Backbone	5.73e-14	2.72e-14	4.01e-15	3.19e-15	-	7.56e-11	2.11e-11	2.02e-14	3.77e-12	-
Ref+Backbone	9.73e-14	2.48e-14	2.53e-16	1.88e-13	-	1.83e-10	7.52e-12	2.03e-14	1.85e-11	-
TTM+Backbone	2.68e-14	2.09e-14	7.28e-13	1.38e-15	-	1.87e-12	1.41e-14	2.99e-16	4.62e-16	-
Strategy	fastMRI (AF=4)					fastMRI (AF=8)				
	U-net	KIKI-Net	D5C5	OUCR	RTR	U-net	KIKI-Net	D5C5	OUCR	RTR
Backbone	1.81e-68	8.42e-59	2.21e-55	6.63e-83	-	8.65e-62	2.38e-50	9.55e-50	8.91e-52	-
Ref+Backbone	1.28e-69	3.01e-56	6.88e-61	1.05e-77	-	1.16e-67	1.74e-51	1.73e-52	1.60e-46	-
TTM+Backbone	3.19e-62	2.05e-50	2.20e-48	1.35e-39	-	1.99-57	7.25e-47	1.45e-50	2.69e-51	-

Appendix D. Additional Results.

Table 7: Ablation study about reference images of different similarity on IXI (AF=4). "random" means that we randomly pick a image from the reference data split. "noise" means that we generate a random noise image as the reference. Oracle indicates the models without TTM. Since human anatomy shares a lot of common patterns, even with a randomly picked full-sampled reference data, TTM can still utilize these common patterns and improve the reconstruction performance.

Level	Similarity	Methods	
		TTM+OUCR	TTM+RTR
L1	$\underset{k}{\operatorname{argmax}} \operatorname{MI}_k$	38.22	38.90
L2	random	38.14	38.88
L3	$\underset{k}{\operatorname{argmin}} \operatorname{MI}_k$	38.01	38.79
L4	noise	37.39	38.01
Oracle	-	37.41	38.16

Figure 5: Visual comparison of different MRI reconstruction methods (AF=4) on (a) IXI and (b) fastMRI among 3 strategies. The second column of each sub-figure shows the absolute difference between the reconstructed image and the ground truth.