Continual Auxiliary Task Learning

Abstract

Learning auxiliary tasks, such as multiple predictions about the world, can provide many benefits to reinforcement learning systems. A variety of off-policy learning algorithms have been developed to learn such predictions, but as yet there is little work on how to adapt the behavior to gather useful data for those off-policy predictions. In this work, we investigate a reinforcement learning system designed to learn a collection of auxiliary tasks, with a behavior policy learning to take actions to improve those auxiliary predictions. We highlight the inherent non-stationarity in this continual auxiliary task learning problem, for both prediction learners and the behavior learner. We develop an algorithm based on successor features that facilitates tracking under non-stationary rewards, and prove the separation into learning successor features and rewards provides convergence rate improvements. We conduct an in-depth study into the resulting multi-prediction learning system.

1   Introduction

In never-ending learning systems, the agent often faces long periods of time when the external reward is uninformative. A smart agent should use this time to practice reaching subgoals, learning new skills, and refining model predictions. Later, the agent should use this prior learning to efficiently maximize external reward. The agent engages in this self-directed learning during times when the primary drives of the agent (e.g., hunger) are satisfied. Other times, the agent might have to trade-off directly acting towards internal auxiliary learning objectives and taking actions that maximize reward.

In this paper we investigate how an agent should select actions to balance the needs of several auxiliary learning objectives in a *no-reward setting* where no external reward is present. In particular, we assume the agent's auxiliary objectives are to learn a diverse set of value functions corresponding to a set of fixed policies. Our solution at a high-level is straightforward. Each auxiliary value function is learned in parallel and off-policy, and the behaviour selects actions to maximize learning progress. Prior work investigated similar questions in a state-less bandit like setting, where both off-policy learning and function approximation are not required [Linke et al., 2020].

Otherwise, the majority of prior work has focused on how the agent could make use of auxiliary learning objectives, not how behaviour could be used to improve auxiliary task learning. Some work has looked at defining (predictive) features, such successor features and a bases of policies [Barreto et al., 2018, Borsa et al., 2018, Barreto et al., 2020, 2019]; universal value function approximators [Schaul et al., 2015]; and features based on value predictions [Schaul and Ring, 2013, Schlegel et al., 2021]. The other focus has been exploration, using auxiliary learning objectives to generate bonuses to aid exploration on the main task [Pathak et al., 2017, Stadie et al., 2015, Puigdomènech Badia et al., 2020, Burda et al., 2018]; using a given set of policies in a call-return fashion for scheduled auxiliary control [Riedmiller et al., 2018]; and discovering subgoals in environments where it is difficult for the agent to reach particular parts of the state-action space [Machado et al., 2017, Colas et al., 2019, Zhang et al., 2020, Andrychowicz et al., 2017, Pong et al., 2019]. In all of these works, the behavior was either fixed or optimized for the main task.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

The problem of adapting the behaviour to optimize many auxiliary predictions in the absence of external reward is sufficiently complex to merit study in isolation. It involves several inter-dependent learning mechanisms, multiple sources of non-stationarity, and high-variance due to off-policy updating. If we cannot design learning systems that efficiently learn their auxiliary objectives in isolation, then the agent is unlikely to learn its auxiliary tasks while additionally balancing external reward maximization.

Further, understanding how to efficiently learn a collection of auxiliary objectives is complementary to the goals of using those auxiliary objectives. It could amplify the auxiliary task effect in UNREAL [Jaderberg et al., 2016], improve the efficiency and accuracy of learning successor features and universal value function approximators, and improve the quality of the sub-policies used in scheduled auxiliary control. It can also benefit the numerous systems that discover options, skills, and subgoals [Gregor et al., 2016, Eysenbach et al., 2018, Veeriah et al., 2019, Pitis et al., 2020, Nair et al., 2020, Pertsch et al., 2020, Colas et al., 2019, Eysenbach et al., 2019], by providing improved algorithms to learn the resulting auxiliary tasks. For example, for multiple discovered subgoals, the agent can adapt its behavior to efficiently learn policies to reach each subgoal.

In this paper we introduce an architecture for parallel auxiliary task learning. As the first such work to tackle this question in reinforcement learning with function approximation, numerous algorithmic challenges arise. We first formalize the problem of learning multiple predictions as a reinforcement learning problem, and highlight that the rewards for the behavior policy are inherently non-stationary due to changes in learning progress over time. We develop a strategy to use successor features, to exploit the stationarity of the dynamics whilst allowing for fast tracking of changes in the rewards, and prove that this separation provides a faster convergence rate than standard value function algorithms like temporal difference learning. We empirically show that this separation facilitates tracking both for prediction learners with non-stationary targets as well as the behavior.

2   Problem Formulation

We consider the *multi-prediction problem*, in which an agent continually interacts with an environment to obtain accurate predictions. This interaction is formalized as a Markov decision process (MDP), defined by a set of states $\mathcal{S}$, a set of actions $\mathcal{A}$, and a transition probability function $\mathcal{P}(s, a, s')$. The agent's goal, when taking actions, is to gather data that is useful for learning N predictions, where each prediction corresponds to a general value function (GVF) [Sutton et al., 2011].

A GVF question is formalized as a three tuple (π, γ, c), where the target is the expected return of the cumulant, defined by $c : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$, when following policy $\pi : \mathcal{S} \times \mathcal{A} \to [0, 1]$, discounted by $\gamma : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to [0, 1]$. More precisely, the target is the action-value

$$Q(s, a) \stackrel{\text{def}}{=} \mathbb{E}_\pi \left[G_t | S_t = s, A_t = a \right] \quad \text{for } G_t \stackrel{\text{def}}{=} C_{t+1} + \gamma_{t+1} G_{t+1}$$

where $C_{t+1} \stackrel{\text{def}}{=} c(S_t, A_t, S_{t+1})$ and $\gamma_{t+1} \stackrel{\text{def}}{=} \gamma(S_t, A_t, S_{t+1})$. The extension of γ to transitions allows for a broader class of problems, including easily specifying termination, without complicating the theory [White, 2017a]. The expectation is under policy π, with transitions according to $\mathcal{P}$. The prediction targets could also be state-value functions; we assume the target are action-values in this work to provide a unified discussion of successor features for both the GVF and behavior learners.

At each time step, the agent produces N predictions, a $\hat{Q}_t^{(j)}(S_t, A_t)$ for prediction j with true targets $Q_t^{(j)}(S_t, A_t)$. We assume the GVF question can change over time, and so Q can change with time. The goal is to have low error in the prediction, in terms of the root mean-squared value error (RMSVE), under state-action weighting $d : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$

$$\text{RMSVE}(\hat{Q}, Q) \stackrel{\text{def}}{=} \sqrt{\sum_{s \in \mathcal{S}} \sum_{a \in \mathcal{A}} d(s, a)(\hat{Q}(s, a) - Q(s, a))^2} \tag{1}$$

The total error up to time step t, across all predictions, is TE $\stackrel{\text{def}}{=} \sum_{i=1}^{t} \sum_{j=1}^{N} \text{RMSVE}(\hat{Q}_i^{(j)}, Q_i^{(j)})$.

The agent's goal is to gather data and update its predictions to make its total error small. This goal can itself be formalized as a reinforcement learning problem, by defining rewards for the behavior policy that depend on the agent's predictions. Such rewards are often called *intrinsic rewards*. For example,

if we could directly measure the RMSVE, one potential intrinsic reward would be the decrease in the RMSVE after taking action A_t from state S_t and transitioning to S_{t+1}. This reflects the agent's learning progress—how much it was able to learn—due to that new experience. The reward is high if the action generated data that resulted in substantial learning. However, while the RMSVE is the most direct measure of learning progress, it cannot be calculated without the true values.

Many intrinsic rewards have been considered to estimate the learning progress of predictions. A recent work provided a thorough survey of different options, as well as an empirical study [Linke et al., 2019]. Their conclusion was that, for reasonable GVF learners, simple learning progress measures—like the change in weights—was effective for producing effective data gathering. We rely on this conclusion here, and formalize the problem using the ℓ_1 norm on the change in weights. Other intrinsic rewards could be swapped into the framework, but as our focus is on the non-stationarity in the system and empirically we also found this intrinsic reward to be effective, we opt for this simple choice upfront.

We provide the generic pseudocode for a multi-prediction reinforcement learning system, in Algorithm 1. Note that the behavior agent also has a separate transition-based γ, which enables us to encode both continuing and episodic problems. For example, the pseudo-termination for a GVF could be a particular state in the environment, such as a doorway. The discount for the GVF would be zero in that state, even though it is not a true terminal state; the behavior discount would not be zero.

Algorithm 1 Multi-Prediction Learning System

Input: N GVF questions

Initialize behavior policy parameters θ_0
  and GVF learners $w_0^{(1)}, \ldots, w_0^{(N)}$
Obtain initial observation S_0
for $t = 0, 1, \ldots$ **do**
  Choose an action A_t according to $\pi_{\theta_t}(\cdot | S_t)$
  Observe next state vector S_{t+1} and γ_{t+1}
  // Update predictions with new data
  for $j = 1$ **to** N **do**
    $c \leftarrow c^{(j)}(S_t, A_t, S_{t+1})$
    $\gamma \leftarrow \gamma^{(j)}(S_t, A_t, S_{t+1})$
    Update $w_t^{(j)}$ with $(S_t, A_t, c, S_{t+1}, \gamma)$
  // Compute intrinsic reward, update behavior
  $r \leftarrow 0$
  for $j = 1$ **to** N **do**
    $r \leftarrow r + \|w_{t+1}^{(j)} - w_t^{(j)}\|_1$
  Update θ_t with $(S_t, A_t, r, S_{t+1}, \gamma_{t+1})$

---

3 Nonstationarity Induced by Learning

On the surface, the multi-prediction problem outlined in the previous section is a relatively straightforward reinforcement learning problem. The behavior policy learns to maximize cumulative reward, and simultaneously learns predictions about its environment. Many RL systems incorporate prediction learning, either as auxiliary tasks or to learn a model. However, unlike standard RL problems, the rewards for the behavior are non-stationary when using intrinsic rewards, even under stationary dynamics. Further, the prediction problems themselves are non-stationary due to a changing behavior.

To understand this more deeply, consider first the behavior rewards. On each time step, the predictions are updated. Progressively, they get more and more accurate. Imagine a scenario where they can become perfectly accurate, such as in the tabular setting with stationary cumulants. The behavior rewards are high in early learning, when predictions are inaccurate. As predictions become more and more accurate, the change in weights gets smaller until eventually the behavior rewards are near zero. This means that when the behavior revisits a state, the reward distribution has actually changed. More generally, in the function approximation setting, the behavior rewards will continue to change with time, not necessarily decay to zero.

The prediction problems are also non-stationary for two reasons. First, the cumulants themselves might be non-stationary, even if the transition dynamics are stationary. For example, the cumulant could correspond to the amount of food in a location in the environment, that slowly gets depleted. Or, the cumulant could depend on a hidden variable, that makes the outcome appear nonstationary. The overall conclusion is that we need an algorithm for the behavior that accounts for this non-stationarity.

Even with a stationary cumulant, the prediction learning problem can be non-stationary due to a changing behavior policy. As the behavior policy changes, the state distribution changes. Implicitly, when learning off-policy, the predictions are minimizing an objective weighted by the state visitation under the behavior policy. As the behavior changes, the underlying objective is actually changing, resulting in a non-stationary prediction problem.

Though there has been some work on learning under non-stationarity in RL and bandits, none to our knowledge has addressed the multi-prediction setting in MDPs. There has been some work developing reinforcement learning algorithms for non-stationary MDPs, but largely for the tabular setting [Sutton and Barto, 2018, Da Silva et al., 2006, Abdallah and Kaisers, 2016, Cheung et al., 2020] or assuming periodic shifts [Chandak et al., 2020a,b, Padakandla et al., 2020]. There has also been some work in the non-stationary multi-armed bandit setting [Garivier and Moulines, 2008, Koulouriotis and Xanthopoulos, 2008, Besbes et al., 2014]. The non-stationary rewards for the behavior, that decay over time, have been considered for the bandit setting, under rotting bandits [Levine et al., 2017, Seznec et al., 2019]; these algorithms do not obviously extend to the RL setting.

4 Handling the Nonstationarity in a Multi-prediction System

In this section, we describe a unified approach to handle non-stationarity in both the GVF and behavior learners, using successor features. We first discuss how to use successor features to learn under non-stationary cumulants, for prediction. Then we discuss using successor features for control, allows us to leverage this approach for nonstationary rewards for the behavior. We then discuss state-reweightings, and how to mitigate nonstationarity due to a changing behavior.

4.1 Successor Features for Non-stationary Rewards

Successor features provide an elegant way to learn value functions under nonstationarity. The separation of learning stationary successor features and rewards enables more effective tracking of non-stationary rewards, as we explain in this section and formally prove in Section 5.

Assume that there is a weight vector $\mathbf{w}^* \in \mathbb{R}^d$ and features $\mathbf{x}(s, a) \in \mathbb{R}^d$ for each state and action (s, a) such that $r(s, a) = \langle \mathbf{x}(s, a), \mathbf{w}^* \rangle$. Recursively define

$$\boldsymbol{\psi}(s, a) = \mathbb{E}_\pi [\mathbf{x}(S_t, A_t) + \gamma_{t+1} \boldsymbol{\psi}(S_{t+1}, A_{t+1}) | S_t = s, A_t = a]$$

$\boldsymbol{\psi}(s, a)$ is the *successor features*, the discounted cumulative sum of feature vectors, if we follow policy π. For $\boldsymbol{\psi}_t \overset{\text{def}}{=} \boldsymbol{\psi}(S_t, A_t)$ and $\mathbf{x}_t \overset{\text{def}}{=} \mathbf{x}(S_t, A_t)$, we can see $Q(s, a) = \langle \boldsymbol{\psi}(s, a), \mathbf{w}^* \rangle$

$$\langle \boldsymbol{\psi}(s, a), \mathbf{w}^* \rangle = \mathbb{E}_\pi [\langle \mathbf{x}_t, \mathbf{w}^* \rangle | S_t = s, A_t = a] + \mathbb{E}_\pi [\gamma_{t+1} \langle \boldsymbol{\psi}_{t+1}, \mathbf{w}^* \rangle | S_t = s, A_t = a]$$
$$= r(s, a) + \mathbb{E}_\pi [\gamma_{t+1} \langle \mathbf{x}_{t+1}, \mathbf{w}^* \rangle | S_t = s, A_t = a] + \mathbb{E}_\pi [\gamma_{t+1} \gamma_{t+2} \langle \boldsymbol{\psi}_{t+2}, \mathbf{w}^* \rangle | S_t = s, A_t = a]$$
$$= r(s, a) + \mathbb{E}_\pi [\gamma_{t+1} r_{t+1} | S_t = s, A_t = a] + \mathbb{E}_\pi [\gamma_{t+1} \gamma_{t+2} \langle \boldsymbol{\psi}_{t+2}, \mathbf{w}^* \rangle | S_t = s, A_t = a]$$
$$= \quad \dots \quad = \mathbb{E}_\pi [r(s, a) + \gamma_{t+1} r_{t+1} + \gamma_{t+1} \gamma_{t+2} r_{t+2} + \dots | S_t = s, A_t = a] \quad = Q(s, a).$$

If we have features $\mathbf{x}(s, a) \in \mathbb{R}^d$ which allow us to represent the immediate reward, then successor features provide a good representation to approximate the GVF.

Typically, however, we cannot explicitly maintain a separate $\boldsymbol{\psi}(s, a)$ for each (s, a) and instead must approximate $\boldsymbol{\psi}(s, a)$. Conveniently, $\boldsymbol{\psi}(s, a)$ can be approximated using any TD method, as each entry corresponds to a cumulative discounted sum. For approximation $\hat{\boldsymbol{\psi}}(s, a; w_\psi) \in \mathbb{R}^d$ with parameters w_ψ, the successor features are defined as $\hat{\boldsymbol{\psi}}(s, a; w_\psi) = [\hat{\boldsymbol{\psi}}_1(s, a; w_\psi), ..., \hat{\boldsymbol{\psi}}_d(s, a; w_\psi)]^\top$, where $\hat{\boldsymbol{\psi}}_m(s, a; w_\psi)$ denotes the cumulative discounted sum of features for dimension $m \in [1, d]$. The parameters w_ψ can be updated using any GVF learning algorithm. In Algorithm 2 we show Expected Sarsa for prediction [Sutton and Barto, 2018] for simplicity; in our experiments we use

---

Algorithm 2 Successor Features for Nonstationary Rewards (SF-NR)

Input: $(S_t, A_t, S_{t+1}, C_{t+1}, \gamma_{t+1}), \pi, w_\psi, w_c$

$\quad \mathbf{x} \leftarrow \mathbf{x}(S_t, A_t)$
$\quad \hat{\boldsymbol{\psi}} \leftarrow \hat{\boldsymbol{\psi}}(S_t, A_t; w_\psi)$
$\quad \hat{\boldsymbol{\psi}}' \leftarrow \sum_{a'} \pi(a'|S_{t+1}) \hat{\boldsymbol{\psi}}(S_{t+1}, a'; w_\psi)$
$\quad \Delta \leftarrow 0$
$\quad \textbf{for } m = 1 \textbf{ to } d \textbf{ do}$
$\quad \quad \delta_m \leftarrow \mathbf{x}_m + \gamma_{t+1} \hat{\boldsymbol{\psi}}'_m - \hat{\boldsymbol{\psi}}_m$
$\quad \quad \Delta \leftarrow \Delta + \delta_m \nabla \hat{\boldsymbol{\psi}}_m$
$\quad w_\psi \leftarrow w_\psi + \alpha \Delta$
$\quad w_c \leftarrow w_c + \alpha (C_{t+1} - \langle \mathbf{x}, w_c \rangle) \mathbf{x}$

Tree-Backup [Precup, 2000] because it reduces variance from off-policy learning and provide the pseudocode in Appendix D.

To use successor features to estimate the value function, we learn another set of parameters that directly predict the immediate cumulant (or reward). The parameters $w_c \in \mathbb{R}^d$ for cumulant approximation $\langle \mathbf{x}(s, a), w_c \rangle \approx c(s, a)$ are updated using a standard regression update. The value estimate is $\hat{Q}(s, a) = \langle \hat{\boldsymbol{\psi}}(s, a; w_\psi), w_c \rangle$. This algorithm, SF-NR, is summarized in Algorithm 2.

The advantage of this separation is two fold. First, it easily allows different or changing cumulants to be used, for the same policy, using the same successor features. The transition dynamics summarized in the stationary successor features can be learned slowly to high accuracy and re-used. This re-use property is why these representations have been used for transfer [Barreto et al., 2017, 2018, 2020]. This property is pertinent for us, because it allows us to more easily track changes in the cumulant. The regression updates can quickly update the parameters w_c, and exploit the already learned successor features to more quickly track value estimates. Small changes in the rewards can result in large changes in the values; without the separation, therefore, it can be more difficult to directly track the value estimates.

Second, the separation allows us to take advantage of online regression algorithms with strong convergence guarantees. Many optimizers and accelerations are designed for a supervised setting, rather than for temporal difference algorithms. Once the successor features are learned, the prediction problem reduces to a supervised learning problem. We can therefore even further improve tracking by leveraging these algorithms to learn and track the immediate cumulant. We formalize the convergence rate improvements, from this separation, in Section 5.

4.2   GPI with Successor Features for Control

In this section we outline a control algorithm under non-stationary rewards. We leverage SF-NR provides a mechanism for changing rewards, which is needed for the behavior for the multi-prediction problem. But the SF-NR only provides a mechanism to efficiently track action-values for a fixed policy, not for a changing policy. Instead, we turn to the idea of learning SFs for a collection of policies, and use the specific form of General Policy Improvement (GPI), called policy-constrained greedification (PCG), where behavior greedifies only over these policies rather than actions.

For our system, this is particularly natural, as we are already learning successor features for a collection of policies. Let us start there, where we assume our set of policies is $\Pi = \{\pi_1, \ldots, \pi_N\}$. Assume also that we have learned the successor features for these policies, $\hat{\psi}(s, a; w_\psi^{(j)})$, and that we have weights $\theta_r \in \mathbb{R}^d$ such that $\langle \mathbf{x}(s, a), \theta_r \rangle \approx \mathbb{E}[R_{t+1}|S_t = s, A_t = a]$ for behavior reward R_{t+1}. Then on each step, the behavior policy takes the following greedy action

$$\pi_b(s) = \operatorname*{argmax}_a \max_{j \in \{1, \ldots, N\}} \hat{Q}_r^{(j)}(s, a) = \operatorname*{argmax}_a \max_{j \in \{1, \ldots, N\}} \langle \hat{\psi}(s, a; w_\psi^{(j)}), \theta_r \rangle$$

PCG guarantees policy improvement: in every state the new policy has a value at least as good as any of the policies in the set [Barreto et al., 2017, Theorem 1]. Later work also showed sampled efficiency of GPI with PCG when combining known reward weights to solve novel tasks [Barreto et al., 2020].

The use of successor features has similar benefits as discussed above, because the estimates can adapt more rapidly the rewards change, due to learning progress changing over time. The separation is even more critical here, as we know the rewards are constantly drifting, and tracking quickly is even more critical. We could even more aggressively adapt to these non-stationary rewards, by anticipating trends. For example, instead of a regression update, we can model the trend (up or down) in the reward for a state and action. If the reward has been decreasing over time, then likely it will continue to decrease. Stochastic gradient descent will put more weight on recent points, but would likely predict a higher expected reward than is actually observed. For simplicity here, we still choose to use stochastic gradient descent, as it is a reasonably effective tracking algorithm, but note that performance improvements could likely be obtained by exploiting this structure in this problem.

We can consider a different set of policies for GVFs and behavior. However, the two are naturally coupled. First, the PCG theory shows that greedifying over a larger collection of policies provides better policies. It is sensible then to at least include the GVF policies into the set for the behavior. Second, the behavior needs to learn the successor features for the additional policies. Arguably, it should try to gather data to learn these well, so as to facilitate its own policy improvement. It should therefore also incorporate the learning progress for these successor features, into the intrinsic reward.

4.3   Interest and prior corrections for the changing state distribution

The final source of non-stationarity is in the state distribution. As the behavior π_b changes, the state-action visitation distribution $d_{b_t} : \mathcal{S} \times \mathcal{A} \to [0, 1]$ changes. When updating online, the state distribution implicitly weights the relative importance of states in the GVF objective, which is called

the projected Bellman error (PBE). Correspondingly, the optimal SF solution could be changing, since the objective is changing.

We can actually completely remove this source of nonstationary by using *prior corrections*. These are products of importance sampling ratios, that reweight the trajectory to match the probability of seeing that trajectory under the target policy π. Namely, it modifies the state weighting to d_π, the state-action visitation distribution under π. We explicitly show this in Appendix C. Unfortunately, prior corrections can be highly problematic in a system where the behavior policy takes exploratory actions and target policies are nearly deterministic. It is likely that these corrections will often either be zero, or near zero, resulting in almost no learning.

A practical alternative is to use interest functions that restrict state weighting and emphatic weights [Sutton et al., 2016]. Emphatic weightings are a prior correction method, used under the excursions model [Patterson et al., 2021]. They reweight to a discounted state-action visitation under π when starting from states proportionally to d_b. They also facilitate using an interest function $i(s, a)$, allowing some state weightings to be zero. The combination of interest and shifting state-action weighting to visitation under π means that we mitigate much of the non-stationarity in the state-action weighting. We provide the pseudocode for this Emphatic TB (ETB) algorithm in Appendix D.

5   Sample Efficiency of SF-NR

As suggested in Section 4.1, the use of successor features makes SF-NR particularly well-suited to our multi-prediction problem setting. The reason for this is simple: given access to an accurate SF matrix, value function estimation reduces to a *fundamentally simpler* linear prediction problem. Indeed, access to an accurate SF enables one to sidestep known lower-bounds on PBE estimation.

For simplicity, we prove the result for value functions; the result easily extends to action-values. Denote by $\mathbf{v}^\pi \in \mathbb{R}^{|\mathcal{S}|}$ the vector with entries $v^\pi(s)$, $\mathbf{r}^\pi \in \mathbb{R}^{|\mathcal{S}|}$ the vector of expected immediate rewards in each state, and $\mathbf{P} \in \mathbb{R}^{|\mathcal{S}| \times |\mathcal{S}|}$ the matrix of transition probabilities. The following lemma, proven in Appendix A.1, relates mean squared value error (VE) to one-step reward prediction error.

Lemma 1 *Assume there exists a* $\mathbf{w}^* \in \mathbb{R}^d$ *such that* $\mathbf{r}^\pi = \mathbf{X}\mathbf{w}^*$. *Let* $\hat{\mathbf{r}} \stackrel{def}{=} \mathbf{X}\mathbf{w}$ *for some* $\mathbf{w} \in \mathbb{R}^d$, *and let* $\mathbf{D} = Diag(\{d(s)\}_{s \in \mathcal{S}})$ *for distribution* d *fully supported on* $\mathcal{S}$, *with* $\|\cdot\|_{\mathbf{D}}$ *the weighted norm under* $\mathbf{D}$. *Then the value estimate* $\hat{\mathbf{v}} \stackrel{def}{=} \Psi\mathbf{w}$ *satisfies* $\frac{1}{2}\|\mathbf{v}^\pi - \hat{\mathbf{v}}\|_{\mathbf{D}}^2 \leq \frac{\|\mathbf{r}^\pi - \hat{\mathbf{r}}\|_{\mathbf{D}}^2}{2(1-\gamma)^2}$.

Thus we can ensure that $\mathrm{VE}(\mathbf{v}^\pi, \hat{\mathbf{v}}) \leq \varepsilon$ by ensuring that $\|\mathbf{r}^\pi - \hat{\mathbf{r}}\|_{\mathbf{D}}^2 \leq \varepsilon(1-\gamma)^2$. This is promising, as this latter expression is readily expressed as the objective of a linear regression problem. To illustrate the utility of this, let's look at a concrete example: suppose the agent has an accurate SF matrix Ψ and that the reward function changes at some point in the agent's deployment. Suppose access to a batch of transitions $\mathcal{D} \stackrel{def}{=} \{S_t, A_t, S_t', r_t, \rho_t\}_{t=1}^T$ with which we can correct our estimate of v^π, where each $(s, a, s', \rho) \in \mathcal{D}$ is such that $s \sim d_b$ for some known behavior policy π_b, $A_t \sim \pi(\cdot|s)$, $s' \sim P(\cdot|s, a)$ and $r = r(s, a, s')$. Assume for simplicity that $\rho_t \leq \rho_{\max}$, $\|\phi(S_t)\|_\infty \leq L$, $r_t \leq R_{\max}$ for some finite $\rho_{\max}, R_{\max}, L \in \mathbb{R}_+$. Then we can get the following result, proven in Appendix A.2, that is a straightforward application of Orabona [2019, Theorem 7.26].

Proposition 1 *Define* $\ell_t(w) \stackrel{def}{=} \frac{\rho_t}{2}(r_t - \langle x(S_t), w \rangle)^2$. *Suppose we apply a basic recursive least-squares estimator to minimize regret on this loss sequence, producing a sequence of iterates* w_t. *Let* $\overline{w}_T \stackrel{def}{=} \frac{1}{T}\sum_{t=1}^T w_t$ *denote the average iterate. For* $\hat{v}(s) = \langle \psi(s), \overline{w}_T \rangle$, *we have that*

$$\|\mathbf{v}^\pi - \hat{\mathbf{v}}\|_{\mathbf{D}}^2 \leq O\left(\frac{d\rho_{\max}R_{\max}^2 \log\left(1 + \rho_{\max}L^2 T\right)}{(1-\gamma)^2 T}\right). \tag{2}$$

In contrast, without the SF we are faced with minimizing a harder objective: the PBE. It can be shown that minimizing the PBE is equivalent to a stochastic saddle-point problem, and the convergence to the saddle-point of this problem has an unimprovable rate of $O\left(\frac{\tau}{T^2} + \frac{(1+\gamma)\rho_{\max}L^2 d}{T} + \frac{\sigma}{\sqrt{T}}\right)$ where τ is the maximum eigenvalue of the covariance matrix and σ bounds gradient stochasticity [Liu et al., 2018a, Proposition 5]. This convergence rate translates into the performance bound $\frac{1}{2}\|\mathbf{v}^\pi - \hat{\mathbf{v}}\|_{\mathbf{D}}^2 \leq O\left(\sqrt{\frac{\tau}{T^2} + \frac{(1+\gamma)\rho_{\max}L^2 d}{T} + \frac{\sigma}{\sqrt{T}}}\right)$. Comparing with Equation 3, we observe an additional dependence of $O(\sqrt{\tau}/T)$ as well as the worse dependence of at least $O(1/\sqrt{T}) \geq (\log(T)/T)$ on all other quantities of interest, reinforcing the intuition that access to the SF enables us to more efficiently re-evaluate the value function.

6 A First Experiment Testing the Multi-prediction System

Figure 1: **Tabular TMaze** with 4 GVFs, with cumulants of zero except in the goals. The right plot shows the cumulants in the goals. G2 and G4 have constant cumulants, G1 has a distractor cumulant and G4 a drifter.

In this section, we investigate the utility of using SF-NR under nonstationary cumulants and rewards, both for prediction in control. We conduct the experiment in a TMaze environment, inspired by the environments used to test animal cognition [Tolman and Honzik, 1930]. The environment, depicted in Figure 1, has four GVFs where each policy takes the fastest route to its corresponding goal. The cumulants are zero everywhere except at the goals. The cumulant can be of three types; a constant fixed value (**constant**), a fixed-mean and but high variance value (**distractor**), or a non-stationary zero-mean random walk process with a low variance (**drifter**). Exact formulas for these cumulants are in Appendix E.1.

Utility of SF-NR for a Fixed Policy

We start by testing the utility of SF-NR for GVF learning, under a fixed policy that provides good data coverage for every GVF. The *Fixed-Behavior Policy* is started from random states in the TMaze, and moves towards the closest goal, with a 50/50 chance of going either direction if there is a tie. This policy is like a round robin policy, in that one of the GVF policies is executed each episode and, in expectation, all four policies are executed the same number of times.

We compare an agent that uses SF-NR and one that learns the approximate GVFs using Tree Back-Up (TB). TB is an off-policy temporal difference (TD) algorithm, that reduces variance in the eligibility trace. We also use TB to learn the successor features in SF-NR. Both use $\lambda = 0.9$ and a stepsize method called Auto [Mahmood et al., 2012] designed for online learning. We sweep the initial stepsize and meta stepsizes for Auto. For further details about the agents and optimizer, see Appendix D. We additionally compare to least squares TD (LSTD), with $\lambda = 0.9$, particularly as it computes a matrix similar to the SF, but does not separate out cumulant learning (see Appendix B for this connection).

In Figure 2a, we can see SF-NR allows for much more effective learning, particularly later in learning when it more effectively tracks the non-stationary signals. LSTD performs much more poorly, likely because it corresponds to a closed-form batch solution, which uses old cumulants that are no longer reflective of the current cumulant distribution.

Investigating GPI for Learning the Behavior

Next we investigate if SF-NR improves learning of the whole system, both for the GVFs and for the behavior policy. We use SF-NR and TB for the GVF learners, and Expected Sarsa (Sarsa) and GPI with PCG for the behavior. GPI uses the GVF policies to condition the learned SF for greedification but always learns a seperate estimator for the reward. In cases where the reward features themselves differ between GPI and SF-NR, GPI learns its own SF.

The results highlight that SF for the GVFs is critical for effective learning, though GPI and Sarsa perform similarly, as shown in Figure 3b. The utility of SF is even greater here, with TB GVF learners inducing much worse performance than SF GVF learners. GPI and Sarsa are similar, which is likely due to the fact that Sarsa uses traces with tabular features, which allow states along the trajectory to the drifter goal to update quickly. In following sections, we find a bigger distinction between the two.

We visualize the goal visitation of GPI in Figure 2c. Once the GVF learners have a good estimate for the *constant* cumulant signals and the *distractor* cumulant signal, the agent behaviour should switch to visiting only the *drifter* cumulant as that is the only goal where visiting would improve the GVF prediction. When using SF GVF learners, this behavior emerges, but under TB GVF learners the agent incorrectly focuses on the distractor. This is even more pronounced for Sarsa (see Appendix F.2).

7 Experiments under Function Approximation

We evaluate our system in a similar fashion to the last section, but now under function approximation. We use a benchmark problem at the end of this section, but start with experiments in the TMaze mod-

Figure 2: Performance in **Tabular TMaze**, with averages over 30 runs. **(a)** and **(b)** show average off-policy prediction RMSE, with standard errors, where the error is weighted by (a) the state distribution d_b for the Fixed-Behavior policy and (b) a uniform state weighting when learning the behavior. **(c)** Goal visitation plots for GPI with SF and TB.

Figure 3: Performance in **Continuous TMaze**, with averages over 30 runs. **(a)** and **(b)** show average off-policy prediction RMSE, with standard errors, where the error is weighted by (a) the state distribution d_b for the Fixed-Behavior policy and (b) a uniform state weighting when learning the behavior. **(c)** RMSE in Continuous TMaze with a Fixed Behavior when incorporating replay.

ified to be a continuous environment, with full details described in Appendix E.1. The environment observation $o_t \in \mathbb{R}^2$ corresponds to the xy coordinates of the agent. We use tile coded features of 2 tilings of 8 tiles for the state representation, both for TB and to learn the SF.

The reward features for the GVF learners can be much simpler than the state-action features because they only need to estimate the cumulants, which are zero in every state except the goals. The reward features are a one-hot encoding of if s' in the tuple of (s, a, s') is in the pseudo-termination goals of the GVFs. For the 1D TMaze, this gives a 4 dimensional vector. The reward features for GPI is state aggregation applied along the one dimensional line components. Appendix E.1 contains more details on the reward features for the GVF and behaviour learners.

Due to space constraints, we include results investigating the impact of interest in Appendix F.3. Those results show the utility of focusing the state-action weighting for the GVF learners. All the experiments in this work used a combined compute usage of approximately five CPU months.

Results for a Fixed Behavior and Learned Behaviors

Under function approximation, SF-NR continues to enable more effective tracking of the cumulants than the other methods. For control, GPI is notably better than Sarsa, potentially because under function approximation eligibility traces are not as effective at sweeping back changes in behavior rewards and so the separation is more important. We include visitations plots in Appendix F.1, which are similar to the tabular setting.

Note that the efficacy of SF-NR and GPI relied on having reward features that did not overly generalize. The SF learns the expected feature vector when following the target policy. For the GVF learners, if states on the trajectory share features with states near the goal, then the value estimates will likely be higher for those states. The rewards are learned using squared error, which unlike other losses, is likely only to bring cumulant estimates to near zero. These small non-zero cumulant estimates are accumulated by the SF for the entire trajectory, resulting in higher error than TB. We demonstrate this in Appendix F.4. We designed reward features to avoid this problem for our experiments, knowing that effective reward features can and have been learned for SF [Barreto et al., 2020].

(a) RMSE for each GVF   (b) GVF#2 goal visits: left hill top   (c) GVF#1 goal visits: right hill top

Figure 4: Performance in **Mountain Car** averaged over 30 runs, with standard errors. **(a)** Learning curves for RMSE, with a uniform weighting over states and actions. **(b)**, **(c)** show the number of times that the agent reached the termination for each GVF.

Results using Replay

The above results using completely online learning, with eligibility traces. A natural question is if the more modern approach of using replay could significantly change the results. In fact, early versions of the system included replay but had surprisingly negative results, which we later realized was due to the inherent nonstationarity in the system. Replaying old cumulants and rewards, that have become outdated, actually harms performance of the system. Once we have the separation with the SF, however, we can actually benefit from replay for this stationary component.

We demonstrate this result in Figure 3c. We use $\lambda = 0$ for this result, because we use replay. The settings are otherwise the same as above, and we resweep hyperparameters for this experiment. SF-NR benefits from replay, because it only uses it for its stationary component: the SF. TB, on the other hand, actually performs more poorly with replay. As before, LSTD which similarly uses old cumulants, also performs poorly.

Validation of the Multi-Prediction System in a Standard Benchmark Problem

Finally, we investigate multi-prediction learning in an environment not obviously designed for this setting: Mountain Car. The goal here is to show that multi-prediction learning is natural in many problem settings, and to show results in a standard benchmark not designed for our setting that has more complex transition dynamics. In the usual formulation the agent must learn to rock back and fourth building up momentum to reach the top of the hill on the right—a classic cost to goal problem. This is a hard exploration task where a random agent requires thousands of steps to reach the top of the hill from the bottom of the valley. Here we use mountain car to see if our approach can learn about more than just getting out of the valley quickly. We specified a GVF whose termination and policy focuses on reaching top of the left hill, and a second GVF about reaching the top of the other side. The full details of the GVFs and setup of this task can be found in the Appendix E.3.

Figure 4a shows how GPI and Sarsa compare against a baseline random policy. GPI provides much better data for GVF learning than the random policy and ESarsa, significantly reducing the RMSE of the learned GVFs. The goal visitation plots show GPI explores the domain and visits both GVFs goal far more often than random, and more effectively than Sarsa.

8   Conclusion

In this work, we provide insights towards building an effective multi-prediction learning system. We highlight the inherent nonstationarity in the problem and design algorithms based on successor features (SF) to better adapt to this nonstationarity. We provide several diagnostic experiments highlighting that (1) SF significantly improve robustness to nonstationarity and improve sample efficiency, both for prediction and control; (2) replay actually exacerbates the issue with nonstationarity for standard temporal difference (TD) algorithms, whereas it can benefit SF. This work demonstrates the utility of several new ideas in RL that are conceptually compelling, but as yet have not seen common use in RL systems, namely SF and GVFs, GPI using policy constrained greedification with SF for control, meta-descent step-size adaption, and interest functions. The hidden journey in this work involved successive failures using classic algorithms in RL, like replay, and discovering the utility in these newer ideas. It highlights the importance of starting to build and analyze complete RL systems, where the interacting parts necessitate incorporating these conceptually important ideas. Solving these integration problems represents the next big step for RL research.

References

Sherief Abdallah and Michael Kaisers. Addressing environment non-stationarity by repeating q-learning updates. *The Journal of Machine Learning Research*, 17(1):1582–1612, 2016.

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. *arXiv preprint arXiv:1707.01495*, 2017.

André Barreto, Will Dabney, Rémi Munos, Jonathan J Hunt, Tom Schaul, Hado P van Hasselt, and David Silver. Successor features for transfer in reinforcement learning. In *Advances in neural information processing systems*, pages 4055–4065, 2017.

Andre Barreto, Diana Borsa, John Quan, Tom Schaul, David Silver, Matteo Hessel, Daniel Mankowitz, Augustin Zidek, and Remi Munos. Transfer in deep reinforcement learning using successor features and generalised policy improvement. In *International Conference on Machine Learning*, pages 501–510. PMLR, 2018.

Andre Barreto, Diana Borsa, Shaobo Hou, Gheorghe Comanici, Eser Aygün, Philippe Hamel, Daniel Toyama, Jonathan hunt, Shibl Mourad, David Silver, and Doina Precup. The option keyboard: Combining skills in reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

André Barreto, Shaobo Hou, Diana Borsa, David Silver, and Doina Precup. Fast reinforcement learning with generalized policy updates. *Proceedings of the National Academy of Sciences*, 117 (48):30079–30087, 2020.

Omar Besbes, Yonatan Gur, and Assaf Zeevi. Stochastic multi-armed-bandit problem with non-stationary rewards. In *Advances in neural information processing systems*, pages 199–207, 2014.

Diana Borsa, André Barreto, John Quan, Daniel Mankowitz, Rémi Munos, Hado van Hasselt, David Silver, and Tom Schaul. Universal successor features approximators. *arXiv preprint arXiv:1812.07626*, 2018.

Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. *arXiv preprint arXiv:1810.12894*, 2018.

Yash Chandak, Scott M Jordan, Georgios Theocharous, Martha White, and Philip S Thomas. Towards safe policy improvement for non-stationary mdps. *Advances in Neural Information Processing Systems*, 2020a.

Yash Chandak, Georgios Theocharous, Shiv Shanka, Martha White, Sridhar Mahadevan, and Philip S Thomas. Optimizing for the future in non-stationary mdps. *International Conference on Machine Learning*, 2020b.

Wang Chi Cheung, David Simchi-Levi, and Ruihao Zhu. Reinforcement learning for non-stationary markov decision processes: The blessing of (more) optimism. *International Conference on Machine Learning*, 2020.

Cédric Colas, Pierre Fournier, Mohamed Chetouani, Olivier Sigaud, and Pierre-Yves Oudeyer. Curious: intrinsically motivated modular multi-goal reinforcement learning. In *International conference on machine learning*, pages 1331–1340. PMLR, 2019.

Bruno C Da Silva, Eduardo W Basso, Filipo S Perotto, Ana L C. Bazzan, and Paulo M Engel. Improving reinforcement learning with context detection. In *Proceedings of the fifth international joint conference on Autonomous agents and multiagent systems*, pages 810–812, 2006.

Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. *arXiv preprint arXiv:1802.06070*, 2018.

Benjamin Eysenbach, Ruslan Salakhutdinov, and Sergey Levine. Search on the replay buffer: Bridging planning and reinforcement learning. *arXiv preprint arXiv:1906.05253*, 2019.

Aurélien Garivier and Eric Moulines. On upper-confidence bound policies for non-stationary bandit problems. *arXiv preprint arXiv:0805.3415*, 2008.

Karol Gregor, Danilo Jimenez Rezende, and Daan Wierstra. Variational intrinsic control. *arXiv preprint arXiv:1611.07507*, 2016.

Assaf Hallak and Shie Mannor. Consistent on-line off-policy evaluation. *International Conference on Machine Learning*, pages 1372–1383, 2017.

Max Jaderberg, Volodymyr Mnih, Wojciech Marian Czarnecki, Tom Schaul, Joel Z Leibo, David Silver, and Koray Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. *arXiv preprint arXiv:1611.05397*, 2016.

Dimitris E Koulouriotis and A Xanthopoulos. Reinforcement learning and evolutionary algorithms for non-stationary multi-armed bandit problems. *Applied Mathematics and Computation*, 196(2): 913–922, 2008.

Nir Levine, Koby Crammer, and Shie Mannor. Rotting bandits. *Advances in Neural Information Processing Systems*, 2017.

Cam Linke, Nadia M. Ady, Martha White, Thomas Degris, and Adam White. Adapting behaviour via intrinsic reward: A survey and empirical study. *CoRR*, abs/1906.07865, 2019. URL http://arxiv.org/abs/1906.07865.

Cam Linke, Nadia M Ady, Martha White, Thomas Degris, and Adam White. Adapting behavior via intrinsic reward: A survey and empirical study. *Journal of Artificial Intelligence Research*, 69: 1287–1332, 2020.

Bo Liu, Ian Gemp, Mohammad Ghavamzadeh, Ji Liu, Sridhar Mahadevan, and Marek Petrik. Proximal gradient temporal difference learning: Stable reinforcement learning with polynomial sample complexity. *Journal of Artificial Intelligence Research*, 2018a.

Qiang Liu, Lihong Li, Ziyang Tang, and Dengyong Zhou. Breaking the Curse of Horizon: Infinite-Horizon Off-Policy Estimation. *Advances in Neural Information Processing Systems*, page 11, 2018b.

Yao Liu, Adith Swaminathan, Alekh Agarwal, and Emma Brunskill. Off-Policy Policy Gradient with Stationary Distribution Correction. *Uncertainty in Artificial Intelligence*, pages 1180–1190, 2020.

Marlos C Machado, Marc G Bellemare, and Michael Bowling. A laplacian framework for option discovery in reinforcement learning. In *International Conference on Machine Learning*, pages 2295–2304. PMLR, 2017.

Ashique Rupam Mahmood, Richard S Sutton, Thomas Degris, and Patrick M Pilarski. Tuning-free step-size adaptation. In *2012 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 2121–2124. IEEE, 2012.

Ashvin Nair, Shikhar Bahl, Alexander Khazatsky, Vitchyr Pong, Glen Berseth, and Sergey Levine. Contextual imagined goals for self-supervised robotic learning. In *Conference on Robot Learning*, pages 530–539. PMLR, 2020.

Francesco Orabona. A modern introduction to online learning. *CoRR*, abs/1912.13213, 2019. URL http://arxiv.org/abs/1912.13213.

Sindhu Padakandla, Prabuchandran K. J., and Shalabh Bhatnagar. Reinforcement learning algorithm for non-stationary environments. *Appl. Intell.*, 50(11):3590–3606, 2020. doi: 10.1007/s10489-020-01758-5. URL https://doi.org/10.1007/s10489-020-01758-5.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, pages 2778–2787. PMLR, 2017.

Andrew Patterson, Adam White, Sina Ghiassian, and Martha White. A generalized projected bellman error for off-policy value estimation in reinforcement learning. *arXiv preprint arXiv:2104.13844*, 2021.

Karl Pertsch, Oleh Rybkin, Frederik Ebert, Shenghao Zhou, Dinesh Jayaraman, Chelsea Finn, and Sergey Levine. Long-horizon visual planning with goal-conditioned hierarchical predictors. *Advances in Neural Information Processing Systems*, 33, 2020.

Silviu Pitis, Harris Chan, Stephen Zhao, Bradly Stadie, and Jimmy Ba. Maximum entropy gain exploration for long horizon multi-goal reinforcement learning. In *International Conference on Machine Learning*, pages 7750–7761. PMLR, 2020.

Vitchyr H Pong, Murtaza Dalal, Steven Lin, Ashvin Nair, Shikhar Bahl, and Sergey Levine. Skew-fit: State-covering self-supervised reinforcement learning. *arXiv preprint arXiv:1903.03698*, 2019.

Doina Precup. Eligibility traces for off-policy policy evaluation. *Computer Science Department Faculty Publication Series*, page 80, 2000.

Adrià Puigdomènech Badia, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, Bilal Piot, Steven Kapturowski, Olivier Tieleman, Martín Arjovsky, Alexander Pritzel, Andew Bolt, et al. Never give up: Learning directed exploration strategies. *arXiv e-prints*, pages arXiv–2002, 2020.

Martin Riedmiller, Roland Hafner, Thomas Lampe, Michael Neunert, Jonas Degrave, Tom Wiele, Vlad Mnih, Nicolas Heess, and Jost Tobias Springenberg. Learning by playing solving sparse reward tasks from scratch. In *International Conference on Machine Learning*, pages 4344–4353. PMLR, 2018.

Tom Schaul and Mark B Ring. Better generalization with forecasts. In *IJCAI*, pages 1656–1662, 2013.

Tom Schaul, Dan Horgan, Karol Gregor, and David Silver. Universal value function approximators. In *International Conference on Machine Learning*, 07 2015.

Bruno Scherrer. Improved and generalized upper bounds on the complexity of policy iteration. *Mathematics of Operations Research*, 2016.

Matthew Schlegel, Andrew Jacobsen, Zaheer Abbas, Andrew Patterson, Adam White, and Martha White. General value function networks. *Journal of Artificial Intelligence Research*, 70:497–543, 2021.

Julien Seznec, Andrea Locatelli, Alexandra Carpentier, Alessandro Lazaric, and Michal Valko. Rotting bandits are no harder than stochastic ones. *International Conference on Artificial Intelligence and Statistics*, 2019.

Bradly C Stadie, Sergey Levine, and Pieter Abbeel. Incentivizing exploration in reinforcement learning with deep predictive models. *arXiv preprint arXiv:1507.00814*, 2015.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. A Bradford Book, Cambridge, MA, USA, 2018. ISBN 0262039249.

Richard S Sutton, Joseph Modayil, Michael Delp, Thomas Degris, Patrick M Pilarski, Adam White, and Doina Precup. Horde: A scalable real-time architecture for learning knowledge from unsupervised sensorimotor interaction. In *The 10th International Conference on Autonomous Agents and Multiagent Systems-Volume 2*, pages 761–768, 2011.

Richard S Sutton, A Rupam Mahmood, and Martha White. An emphatic approach to the problem of off-policy temporal-difference learning. *The Journal of Machine Learning Research*, 17(1): 2603–2631, 2016.

Edward Chace Tolman and Charles H Honzik. Introduction and removal of reward, and maze performance in rats. *University of California publications in psychology*, 1930.

Vivek Veeriah, Matteo Hessel, Zhongwen Xu, Richard Lewis, Janarthanan Rajendran, Junhyuk Oh, Hado van Hasselt, David Silver, and Satinder Singh. Discovery of useful questions as auxiliary tasks. *arXiv preprint arXiv:1909.04607*, 2019.

Martha White. Unifying task specification in reinforcement learning. In *International Conference on Machine Learning*, pages 3742–3750. PMLR, 2017a.

Martha White. Unifying task specification in reinforcement learning. In *International Conference on Machine Learning*, 2017b.

Tianren Zhang, Shangqi Guo, Tian Tan, Xiaolin Hu, and Feng Chen. Generating adjacency-constrained subgoals in hierarchical reinforcement learning. *arXiv preprint arXiv:2006.11485*, 2020.