Heavy Tails in SGD and Compressibility of Overparametrized Neural Networks

Abstract

Neural network compression techniques have become increasingly popular as they can drastically reduce the storage and computation requirements for very large networks. Recent empirical studies have illustrated that even simple pruning strategies can be surprisingly effective, and several theoretical studies have shown that compressible networks (in specific senses) should achieve a low generalization error. Yet, a theoretical characterization of the underlying cause that makes the networks amenable to such simple compression schemes is still missing. In this study, we address this fundamental question and reveal that the dynamics of the training algorithm has a key role in obtaining such compressible networks. Focusing our attention on stochastic gradient descent (SGD), our main contribution is to link compressibility to two recently established properties of SGD: (i) as the network size goes to infinity, the system can converge to a *mean-field* limit, where the network weights behave independently, (ii) for a large step-size/batch-size ratio, the SGD iterates can converge to a *heavy-tailed* stationary distribution. In the case where these two phenomena occur *simultaneously*, we prove that the networks are guaranteed to be 'ℓ_p-compressible', and the compression errors of different pruning techniques (magnitude, singular value, or node pruning) become arbitrarily small as the network size increases. We further prove generalization bounds adapted to our theoretical framework, which indeed confirm that the generalization error will be lower for more compressible networks. Our theory and numerical study on various neural networks show that large step-size/batch-size ratios introduce heavy-tails, which, in combination with overparametrization, result in compressibility.

1 Introduction

With the increasing model sizes in deep learning and with its increasing use in low-resource environments, network compression is becoming ever more important. Among many network compression techniques, network pruning has been arguably the most commonly used method [O'N20], and it is rising in popularity and success [BOFG20]. Though various pruning methods are successfully used in practice and their theoretical implications in terms of generalization are increasingly apparent [AGNZ18], a thorough understanding of *why* and *when* neural networks are compressible is lacking.

A common conclusion in pruning research is that overparametrized networks can be greatly compressed by pruning with little to no cost at generalization, including with simple schemes such as magnitude pruning [BOFG20, O'N20]. For example, research on *iterative magnitude pruning* [FC19] demonstrated the possibility of compressing trained deep learning models by iteratively eliciting a much sparser substructure. While it is known that the choice of training hyperparameters such as learning rate affects the performance of such pruning strategies [FDRC20, HJRY20, RFC20], usually such observations are low in granularity and almost never theoretically motivated. Overall, the field lacks a framework to understand why or when a pruning method should be useful [O'N20].

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Another strand of research that highlights the importance of understanding network compressibility includes various studies [AGNZ18, SAM$^+$20, SAN20, HJTW21, KLG$^+$21] that presented generalization bounds and/or empirical evidence that imply that the more compressible a network is, the more likely it is to generalize well. The aforementioned bounds are particularly interesting since classical generalization bounds increase with the dimension and hence become irrelevant in high dimensional deep learning settings, and fall short of explaining the generalization behavior of overparametrized neural networks. These results again illustrate the importance of understanding the conditions that give rise to compressibility given their implications regarding generalization.

In this paper, we develop a theoretical framework to address (i) *why and when modern neural networks can be amenable to very simple pruning strategies* and (ii) *how this relates to generalization.* Our theory lies in the intersection of two recent discoveries regarding deep neural networks trained with the stochastic gradient descent (SGD) algorithm. The first one is the emergence of *heavy-tailed* stationary distributions, which appear when the networks are trained with large learning rates and/or small batch-sizes [HM20, GSZ20]. The second one is the *propagation of chaos* phenomenon, which indicates that, as the network size goes to infinity, the network weights behave *independently* [MMN18, SS20, DBDFS20].

We show that, under the setting described above, fully connected neural networks will be provably compressible in a precise sense, and the compression errors of (i) unstructured global or layer-wise magnitude pruning, (ii) pruning based on singular values of the weight matrices, (iii) and node pruning can be made arbitrarily small for any compression ratio as the dimension increases. Our formulation of network compressibility in terms of 'ℓ_p-compressibility' enables us to access results from *compressed sensing* literature [GCD12, AUM11] to be used in neural network analysis. Moreover, we prove generalization bounds adapted to our theoretical framework that agree with existing compression-based generalization bounds [AGNZ18, SAM$^+$20, SAN20] and confirm that compressibility implies improved generalization. We conduct experiments on fully connected and convolutional neural networks and show that the results are in strong accordance with our theory.

Our study reveals an interesting phenomenon: depending on the algorithm hyperparameters, such as learning rate and batch-size, the resulting neural networks might possess different compressibility properties. When the step-size/batch-size ratio is large, heavy-tails emerge, and when combined with the decoupling effect of propagation of chaos that emerges with overparametrization, the networks become compressible in a way that they are amenable to simple pruning strategies. Finally, when compressible, the networks become likely to generalize better. In this sense, our results also provide an alternative perspective to the recent theoretical studies that suggest that heavy-tails can be beneficial in terms of generalization [SSDE20, ZFM$^+$20].

2 Preliminaries and Technical Background

Notation. Matrices and vectors are denoted by upper- and lower-case bold letters, respectively, *e.g.* $\mathbf{X}$ and $\mathbf{x}$. A sequence of n scalars $x_1, \ldots, x_n$ is shown as $\{x_i\}_{i=1}^n$. Similar notations are used for sequences of matrices $\{\mathbf{X}_i\}_{i=1}^l$ and vectors $\{\mathbf{x}_i\}_{i=1}^l$, whose entries are indexed with convention $\mathbf{X}_i = [\mathbf{X}_i]_{m,n}$ and $\mathbf{x}_i = (x_{i,1}, x_{i,2}, \ldots, x_{i,n})$, respectively. The set of integers $\{m, \ldots, n\}$ is denoted by $[\![m, n]\!]$. We denote the ℓ_p (semi-)norm of a vector $\mathbf{x} \in \mathbb{R}^d$ as $\|\mathbf{x}\|_p = (\sum_{i=1}^d |x_i|^p)^{1/p}$ for all $p \in (0, \infty)$ and $\|\mathbf{x}\|$ implies $\|\mathbf{x}\|_2$. For a matrix $\mathbf{A} \in \mathbb{R}^{n \times m}$, $\|\mathbf{A}\|$ denotes its Frobenius norm.

Fully connected neural networks. In the entirety of the paper, we consider a multi-class classification setting. We denote the space of data points by $\mathcal{Z} = \mathcal{X} \times \mathcal{Y}$, where $\mathcal{X} \subset \mathbb{R}^{d_X}$ is the space of features and $\mathcal{Y} = \{1, 2, \ldots, d_Y\}$ is the space of the labels. Similar to prior art (e.g., [NBS17]), we focus our attention on the bounded feature domain $\mathcal{X} = \mathcal{X}_B := \{\mathbf{x} \in \mathbb{R}^{d_X}; \|\mathbf{x}\| \leq B\}$.

We denote a *fully connected neural network* with L layers by a collection of *weight matrices* $\{\mathbf{W}_l\}_{l=1}^L$, such that $\mathbf{W}_l \in \mathbb{R}^{h_l \times h_{l-1}}$, where h_l denotes the number of hidden units at layer l with $h_0 = d_X$ and $h_L = d_Y$. Accordingly, the *prediction function* $f_{\mathbf{w}}(\mathbf{x}) : \mathcal{X}_B \mapsto \mathcal{Y}$ corresponding to the neural network is defined as follows:

$$f_{\mathbf{w}}(\mathbf{x}) = \mathbf{W}_L \phi(\mathbf{W}_{L-1} \phi(\cdots \phi(\mathbf{W}_1 \mathbf{x}))), \tag{1}$$

where $\phi : \mathbb{R} \to \mathbb{R}$ is the rectified linear unit (ReLU) activation function, *i.e.*, $\phi(x) = \max(0, x)$, and it is applied element-wise when its input is a vector. For notational convenience, let us define $d_l := h_l \times h_{l-1}$ and $d := \sum_{l=1}^L d_l$. Furthermore, let $\mathbf{w}_l$ denote the *vectorized* weight matrix of layer

l, *i.e.*, $\mathbf{w}_l := \mathbf{vec}(\mathbf{W}_l) \in \mathbb{R}^{d_l}$, where **vec** denotes vectorization. Finally, let $\mathbf{w}$ be the concatenation of all the vectorized weight matrices, *i.e.*, $\mathbf{w} := [\mathbf{w}_1, \ldots, \mathbf{w}_L] \in \mathbb{R}^d$. We assume that $L \geq 2$.

Risk minimization and SGD. In order to assess the quality of a neural network represented by its weights $\mathbf{w}$, we consider a loss function $\ell : \mathcal{Y} \times \mathcal{Y} \mapsto \mathbb{R}_+$, such that $\ell(y, f_{\mathbf{w}}(\mathbf{x}))$ measures the loss incurred by predicting the label of $\mathbf{x}$ as $f_{\mathbf{w}}(\mathbf{x})$, when the true label is y. By following a standard statistical learning theoretical setup, we consider an unknown *data distribution* μ_Z over $\mathcal{Z}$, and a *training dataset* with n elements, *i.e.*, $S = \{\mathbf{z}_1, \ldots, \mathbf{z}_n\}$, where each $\mathbf{z}_i =: (\mathbf{x}_i, y_i) \overset{\text{i.i.d.}}{\sim} \mu_Z$. We then denote the *population* and *empirical risks* as $\mathcal{R}(\mathbf{w}) := \mathbb{E}_{(\mathbf{x},y)\sim\mu_Z}[\ell(y, f_{\mathbf{w}}(\mathbf{x}))]$ and $\widehat{\mathcal{R}}(\mathbf{w}) := \frac{1}{n}\sum_{i=1}^{n} \ell(y_i, f_{\mathbf{w}}(\mathbf{x}_i))$.

Since μ_Z is unknown, we cannot directly attempt to minimize $\mathcal{R}$ in practice. One popular approach to address this problem is the *empirical risk minimization* strategy, where the goal is to solve the following optimization problem: $\min_{\mathbf{w}\in\mathbb{R}^d} \widehat{\mathcal{R}}(\mathbf{w})$. To tackle this problem, SGD has been one of the most popular optimization algorithms, which is based on the following simple recursion:

$$\mathbf{w}^{\{k+1\}} = \mathbf{w}^{\{k\}} - \eta\nabla\widetilde{\mathcal{R}}_{k+1}(\mathbf{w}^{\{k\}}), \text{ where } \nabla\widetilde{\mathcal{R}}_k(\mathbf{w}) := (1/b)\sum_{i\in\Omega_k} \nabla\ell(y_i, f_{\mathbf{w}}(\mathbf{x}_i)). \quad (2)$$

Here, $\mathbf{w}^{\{k\}}$ denotes the weight vector at iteration $k \in \mathbb{N}^+$, $\eta > 0$ is the step-size (or learning rate), $\nabla\widetilde{\mathcal{R}}_k(\cdot)$ is the stochastic gradient, and Ω_k is the mini-batch with size b, drawn with or without replacement from $[\![1, n]\!]$.

Heavy-tailed distributions and the α-stable family. In this study, we will mainly deal with heavy-tailed random variables. While there exist different definitions of heavy-tails in the literature, here, we call a random variable heavy-tailed if its distribution function has a *power-law* decay, *i.e.*, $\mathbb{P}(X \geq x) \sim cx^{-\alpha}$ as $x \to \infty$, for some $c > 0$ and $\alpha \in (0, 2)$. Here, the *tail-index* α determines the tail thickness of the distribution, *i.e.*, as α get smaller, the distribution becomes heavier-tailed.

An important subclass of heavy-tailed distributions is the family of stable distributions. A random variable X has symmetric α-stable distribution, denoted by $\mathcal{S}\alpha\mathcal{S}(\sigma)$, if its characteristic function is equal to $\mathbb{E}[\exp(iwX)] = \exp(-|\sigma w|^{\alpha})$, where $\alpha \in (0, 2]$ is again the tail-index and $\sigma \in (0, \infty)$ is the scale parameter. An important property of $\mathcal{S}\alpha\mathcal{S}$ is that whenever $\alpha < 2$, $\mathbb{E}|X|^p$ is finite if and only if $p < \alpha$. This implies that the distribution has infinite variance as soon as $\alpha < 2$. In addition to their wide use in applied fields [Nol20], recently, $\mathcal{S}\alpha\mathcal{S}$ distributions have also been considered in deep learning theory [SSG19, PFF20, ZFM$^+$20, SSDE20].

3 Compressibility and the Heavy-Tailed Mean-Field Regime

In this section, we will present our first set of theoretical results. We first identify a sufficient condition, then we prove that, under this condition, the compression errors of different pruning techniques become arbitrarily small as the network size increases.

3.1 The heavy-tailed mean-field regime

Due to the peculiar generalization behavior of neural networks trained with SGD, recent years have witnessed an extensive investigation of the theoretical properties of SGD in deep learning [Lon17, DR17, KL17, ZLZ19, AZLL19, SSDE20, Neu21]. We will now mention two recently established theoretical properties of SGD, and our main contribution is the observation that these two seemingly unrelated 'phenomena' are closely linked to compressibility.

The heavy-tail phenomenon. Several recent studies [MM19, SSG19, ZFM$^+$20, ZKV$^+$20] have empirically illustrated that neural networks can exhibit heavy-tailed behaviors when optimized with SGD. Theoretically investigating the origins of this heavy-tailed behavior, [HM20] and [GSZ20] later proved several theoretical results on online SGD, with rather surprising implications: due to the 'multiplicative' structure of the gradient noise (*i.e.*, $\nabla\widetilde{\mathcal{R}}_k(\mathbf{w}) - \nabla\widehat{\mathcal{R}}(\mathbf{w})$), as $k \to \infty$, the distribution of the SGD iterates $\mathbf{w}^{\{k\}}$ can converge to a heavy-tailed distribution with *infinite second-order moment*, and perhaps more surprisingly, this behavior can even emerge in simple linear regression with Gaussian data. The authors of [GSZ20] further showed that, in the linear regression setting, the tail index α is *monotonic* with respect to the step-size η and batch-size b: larger η and/or smaller b result in smaller α (*i.e.*, heavier tails).

Propagation of chaos and mean-field limits. Another interesting property of SGD appears when the size of the network goes to infinity. Recently, it has been shown that, under an appropriate scaling of step-sizes, the empirical distribution of the network weights converges to a fixed *mean-field* distribution, and the SGD dynamics can be represented as a *gradient flow* in the space of probability measures [MMN18, CB18, SS20, DBDFS20]. Moreover, [DBDFS20] showed that a *propagation of chaos* phenomenon occurs in this setting, which indicates that when the network weights are initialized independently (*i.e.,* a-priori chaotic behavior), *the weights stay independent* as the algorithm evolves over time (*i.e.*, the chaos propagates) [Szn91].

Our interest in this paper is the case where both of these phenomena occur *simultaneously*: as the size of the network goes to infinity, the SGD iterates keep being *independent* and their distribution converges to a *heavy-tailed* distribution. To formalize this setting, let us introduce the required notations. For an integer $m_l < d_l$, let $\mathbf{w}_{l,(1:m_l)}$ denote the first m_l coordinates of $\mathbf{w}_l$, and for $m_l \geq d_l$ set $\mathbf{w}_{l,(1:m_l)} = \mathbf{w}_l$. Furthermore, parametrize the dimension of each layer d_l with a parameter $\rho \in \mathbb{R}$, i.e., $d_l = d_l(\rho)$, such that for all $l = 1, \ldots, L$, we have:

$$d_l(\rho) \in \mathbb{N}_+, \quad \text{and} \quad \lim_{\rho \to \infty} d_l(\rho) = \infty. \tag{3}$$

This construction enables us to take the dimensions of each layer to infinity simultaneously [NP20].

Definition 1 (The heavy-tailed mean-field limit property)**.** *The SGD recursion* (2) *possesses the heavy-tailed mean-field limit (HML) property, if the dimensions obey* (3) *and if there exist heavy-tailed probability measures* $\{\mu_l^\star\}_{l=1}^L$ *on* $\mathbb{R}$ *with tail-indices* $\{\alpha_l\}_{l=1}^L$*, such that* $\mu_l^\star(\{0\}) = 0$ *for all* l *and for any* $m_1, \ldots, m_L \in \mathbb{N}_+$*, the joint distribution of*

$$\left(\mathbf{w}_{1,(1:m_1)}^{\{k\}}, \ldots, \mathbf{w}_{L,(1:m_L)}^{\{k\}} \right) \quad \text{weakly converges to} \quad (\mu_1^\star)^{\otimes m_1} \otimes \cdots \otimes (\mu_L^\star)^{\otimes m_L}, \tag{4}$$

as $\rho, k \to \infty$*, where* $\mu \otimes \nu$ *denotes the product measure and* $\mu^{\otimes n}$ *denotes the* n*-fold product measure.*

Informally, the HML property states that in the infinite size and infinite iteration limit, the entries of the weight matrices will become independent, and the distribution of the elements within the same layer will be identical and heavy-tailed. We will briefly illustrate this behavior empirically in Section 5. Note that, in (4), the particular form of independence in the limit is not crucial and we will discuss weaker alternatives in Section 3.3.

We further note that [DBDFS20] proved that a similar form of (4) indeed holds for SGD applied on single hidden-layered neural networks, where the limiting distributions possess second-order moments (*i.e.*, not heavy-tailed) and the independence is column-wise. Recently, [PFF20] investigated the infinite width limits of fully connected networks initialized from a $\mathcal{S}\alpha\mathcal{S}$ distribution and proved heavy-tailed limiting distributions. On the other hand, heavy-tailed propagation of chaos results have been proven in theoretical probability [JMW08, LMW19]; however, their connection to SGD has not been yet established. We believe that (4) can be shown to hold under appropriate conditions, which we leave as future work.

3.2 Analysis of compression algorithms

In this section, we will analyze the compression errors of three different compression schemes when the HML property is attained. All three methods are based on *pruning*, which we formally define as follows. Let $\mathbf{x}$ be a vector of length d, and consider its sorted version in descending order with respect to the magnitude of its entries, *i.e.*, $|x_{i_1}| \geq |x_{i_2}| \geq \cdots \geq |x_{i_d}|$, where $\{i_1, \ldots, i_d\} = \{1, \ldots, d\}$. For any $k \leq d$, the k-best term approximation of $\mathbf{x}$, denoted as $\mathbf{x}^{(k)} = (x_1^{(k)}, \ldots, x_d^{(k)})$, is defined as follows: for $l \in [\![1, \lceil k \rceil]\!], x_{i_l}^{(k)} := x_{i_l}$ and for $l \notin [\![1, \lceil k \rceil]\!], x_{i_l}^{(k)} := 0$. Informally, we keep the k-largest entries of $\mathbf{x}$ with the largest magnitudes, and 'prune' the remaining ones. Current results pertain to one-shot pruning with no fine-tuning; other settings are left for future work (cf. [EKT20]).

In this section, we consider that we have access to a sample from the stationary distribution of the SGD, *i.e.* $\mathbf{w}^{\{\infty\}}$, and for conciseness we will simply denote it by $\mathbf{w}$. We then consider a *compressed network* $\widehat{\mathbf{w}}$ (that can be obtained by different compression schemes) and measure the performance of the compression scheme by its 'relative ℓ_p-compression error' (cf. [AUM11, GCD12]), defined as: $\|\widehat{\mathbf{w}} - \mathbf{w}\|_p / \|\mathbf{w}\|_p$. Importantly for the following results, in the supplement, we further prove that a small compression error also implies a small perturbation on the network output.

Magnitude pruning. Magnitude pruning has been one of the most common and efficient algorithms among all the network pruning strategies [HPTD15, BOFG20, KLG+21]. In this section, we consider the global and layer-wise magnitude pruning strategies under the HML property.

More precisely, given a network weight vector $\mathbf{w} \in \mathbb{R}^d$ and a *remaining parameter ratio* $\kappa \in (0,1)$, the global pruning strategy compresses $\mathbf{w}$ by using $\mathbf{w}^{(\kappa d)}$, *i.e.*, it prunes the smallest (in magnitude) $(1-\kappa)d$ entries of $\mathbf{w}$. Also, note that $1/\kappa$ corresponds to the frequently used metric *compression rate* [BOFG20]. On the other hand, the layer-wise pruning strategy applies the same approach to each layer separately, *i.e.*, given layer-wise remaining parameter ratios $\kappa_l \in (0,1)$, we compress each layer weight $\mathbf{w}_l \in \mathbb{R}^{d_l}$ by using $\mathbf{w}_l^{(\kappa_l d_l)}$. The following result shows that the compression error of magnitude pruning can be made arbitrarily small as the network size grows.

Theorem 1. *Assume that the recursion* (2) *has the HML property.*

(i) $\quad$ *Global magnitude pruning: if the weights of all layers have identical asymptotic distributions* $\mu_l^\star \equiv \mu^\star$ *with tail-index* $\alpha_l^\star = \alpha$, *for all* $l \in [\![1, L]\!]$, *then for every* $\epsilon > 0$, $\varepsilon > 0$, $\kappa \in (0,1)$, *and* $p \geq \alpha$, *there exists* $d_0 \in \mathbb{N}$, *such that* $\|\mathbf{w}^{(\kappa d)} - \mathbf{w}\|_p \leq \varepsilon \|\mathbf{w}\|_p$ *holds with probability at least* $1 - \epsilon$, *for* $d \geq d_0$.

(ii) $\quad$ *Layer-wise magnitude pruning: for every* $\epsilon > 0$, $\varepsilon_l > 0$ *and* $\kappa_l \in (0,1)$, *where* $l \in [\![1, L]\!]$, *and* $p \geq \max_l \alpha_l$, *there exists* $d_{l,0} \in \mathbb{N}$, *such that* $\|\mathbf{w}_l^{(\kappa_l d_l)} - \mathbf{w}_l\|_p \leq \varepsilon_l \|\mathbf{w}_l\|_p$ *holds with probability at least* $1 - \epsilon$, *for* $d_l \geq d_{l,0}$.

This result shows that any pruning ratio of the weights is achievable as long as the network size is sufficiently large and the network weights are close enough to an i.i.d. heavy-tailed distribution. Empirical studies report that global magnitude pruning often works better than layer-wise magnitude pruning [BOFG20], except when it leads to over-aggressive pruning of particular layers [WZG20].

The success of this strategy under the HML property is due to a result from compressed sensing theory, concurrently proven in [GCD12, AUM11], which informally states that for a large vector of i.i.d. heavy-tailed random variables, the norm of the vector is mainly determined by a small fraction of its entries. We also illustrate this visually in the supplementary document.

An important question here is that, to achieve a fixed relative error ε_l, how would the smallest κ_l would differ with varying tail-indices α_l, *i.e.*, whether "heavier-tails imply more compression". In our experiments, we illustrate this behavior positively: heavier-tailed weights are indeed more compressible. We partly justify this behavior for a certain range of p in the supplement; however, a more comprehensive theory is needed, which we leave as future work.

Singular value pruning. In recent studies, it has been illustrated that the magnitudes of the eigenvalues of the sample covariance matrices (for different layers) can decay quickly, hence pruning the singular values of the weight matrices, *i.e.*, only keeping the largest singular values and corresponding singular vectors, is a sensible pruning method. Exploiting the low-rank nature of fully connected and convolutional layer weights in network compression has been investigated theoretically and empirically [AGNZ18, YLWT17]. Here we will present a simple scheme to demonstrate our results.

More precisely, for the weight matrix at layer l, $\mathbf{W}_l$, consider its singular value decomposition, $\mathbf{W}_l = \mathbf{U}\boldsymbol{\Sigma}\mathbf{V}^\top$, and then, with a slight abuse of notation, define $\mathbf{W}_l^{[\kappa_l h_{l-1}]} := \mathbf{U}\boldsymbol{\Sigma}^{(\kappa_l h_{l-1})}\mathbf{V}^\top$, where $\boldsymbol{\Sigma}^{(\kappa_l h_{l-1})}$ is the diagonal matrix whose diagonal entries contain the $\lceil \kappa_l h_{l-1} \rceil$ largest singular values (*i.e.*, prune the diagonal of $\boldsymbol{\Sigma}$). Accordingly, denote $\mathbf{w}_l^{[\kappa_l h_{l-1}]} := \mathbf{vec}(\mathbf{W}_l^{[\kappa_l h_{l-1}]})$.

The next theorem shows that under the HML property with an additional requirement that the limiting distributions are $\mathcal{S}\alpha\mathcal{S}$, the eigenvalues of the (properly normalized) sample covariance matrices will be indeed compressible and the pruning strategy achieves negligible errors as the network size grows.

Theorem 2. *Assume that the recursion* (2) *has the HML property,* $L \geq 3$, *and for all* $l \in [\![2, L-1]\!]$, $\mu_l^\star \equiv \mathcal{S}\alpha_l\mathcal{S}(\sigma_l)$ *with some* $\sigma_l > 0$. *Then, for every* $\epsilon > 0$, $\varepsilon_l > 0$, *and* $\kappa_l \in (0,1)$, *there exists* $\{h_{l,0}\}_{l=1}^L$, *such that the following inequalities hold for every* $h_l \geq h_{l,0}$ *and* $p \geq \max_l \alpha_l/2$:

$$\|\boldsymbol{\lambda}_l^{(\kappa_l h_{l-1})} - \boldsymbol{\lambda}_l\|_p \leq \varepsilon_l^2 \|\boldsymbol{\lambda}_l\|_p, \quad \text{and} \quad \|\mathbf{w}_l^{[\kappa_l h_{l-1}]} - \mathbf{w}_l\| \leq \varepsilon_l \|\mathbf{w}_l\|, \tag{5}$$

with probability at least $1 - \epsilon$, *where* $\boldsymbol{\lambda}_l \in \mathbb{R}^{h_{l-1}}$ *denotes the vector of eigenvalues corresponding to the sample covariance matrix* $h_l^{-2/\alpha_l}\mathbf{W}_l^\top \mathbf{W}_l$.

We shall note that the proof of Theorem 2 in fact only requires the limiting distributions to be 'regularly varying' [TTR+20] and symmetric around zero, which covers a broad range of heavy-tailed distributions beyond the α-stable family [BDM+16]. The sole reason why we require the $\mathcal{S}\alpha\mathcal{S}$ condition here is to avoid introducing further technical notation.

Node pruning. The last pruning strategy that we consider is a structured pruning strategy, that corresponds to the removal of the whole columns of a fully connected layer weight matrix. Even though below we consider pruning based on the norms of the weight layer columns, the same arguments apply for pruning rows.

The idea in column pruning is that, for a given layer l, we first sort the columns of the weight matrix $\mathbf{W}_l \in \mathbb{R}^{h_l \times h_{l-1}}$ with respect to their ℓ_p-norms for a given $p \geq \max_l \alpha_l$. Then, we remove the *entire columns* that have the smallest ℓ_p-norms. More precisely, let $\mathbf{W}_l(i) \in \mathbb{R}^{h_l}$ be the i-th column of $\mathbf{W}_l$, for $i \in [\![1, h_{l-1}]\!]$, and suppose that $\|\mathbf{W}_l(i_1)\|_p \geq \|\mathbf{W}_l(i_2)\|_p \geq \cdots \geq \|\mathbf{W}_l(i_{h_{l-1}})\|_p$, where $\{i_1, \ldots, i_{h_{l-1}}\} = \{1, \ldots, h_{l-1}\}$. Then, we define the k-best column approximation of $\mathbf{W}_l$, denoted as $\mathbf{W}_l^{\{k\},p} \in \mathbb{R}^{h_l \times h_{l-1}}$, as follows: for $j \in [\![1, \lceil k \rceil]\!]$, $\mathbf{W}_l^{\{k\},p}(i_j) := \mathbf{W}_l(i_j)$ and for $j \notin [\![1, \lceil k \rceil]\!]$, $\mathbf{W}_l^{\{k\},p}(i_j) := 0$. Denote also $\mathbf{w}_l^{\{k\},p} := \mathbf{vec}\left(\mathbf{W}_l^{\{k\},p}\right)$.

Theorem 3. *Assume that the recursion* (2) *has the HML property. Then, for every* $\epsilon > 0$, $\varepsilon_l > 0$, $\kappa_l \in (0, 1)$, *where* $l \in [\![2, L]\!]$, *and* $p \geq \max_l \alpha_l$, *there exists* $h_{l-1,0} \in \mathbb{N}$, *such that* $\|\mathbf{w}_l^{\{\kappa_l h_{l-1}\},p} - \mathbf{w}_l\|_p \leq \varepsilon_l \|\mathbf{w}_l\|_p$ *holds with probability at least* $1 - \epsilon$, *for every* $h_{l-1} \geq h_{l-1,0}$.

This theorem indicates that we can remove entire columns in each layer, without considerably affecting the network weights, as long as the network is large enough. In other words, effectively the widths of the layers can be reduced. Structured pruning schemes are commonly used in CNNs where filters, channels, or kernels can be pruned by norm-based or other criteria [LKD+17, HZS17, HPTD15].

3.3   A note on the limiting independence structure in the HML property

We conclude this section by discussing the particular independence condition in the limit, which appears in Definition 1. We shall underline that the element-wise independence is not a necessity and under weaker conditions, we can still obtain Theorems 1-3 with identical or almost identical proofs. For instance, the proof of Theorem 3 remains the same when the columns of $\mathbf{W}_l$ are i.i.d. vectors with *dependent* components; hence, the element-wise independence is indeed not needed, but is used for the clarity of presentation. More generally, in all three theorems, the main requirement is to ensure a *weak dependence* between the components of the weight vector. More precisely, for Theorems 1, 2, 3, we respectively need (1) the entries of $\mathbf{W}_l$ or (2) its singular values, or (3) the ℓ_p-norms of its columns to be *stationary* and *ergodic* with a heavy-tailed distribution. Under this condition, the same proof strategies will still work by invoking [SD15, Theorem 1], instead of [GCD12, Proposition 1].

4   Generalization Bounds

So far, we have shown that the heavy-tailed behavior in the weights of a network together with their independence result in compressibility. In this section, we further show that these phenomena bring forth a better generalization performance in the network. More precisely, we show that if a network is more compressible, then the corresponding compressed network has a smaller generalization error. Throughout the section, we will focus on layer-wise magnitude pruning; yet, our results can be easily extended to the other pruning strategies. Note that similar results have already been proven in [AGNZ18, SAM+20, SAN20, HJTW21]; yet, they cannot be directly used in our specific setting, hence, we prove results that are customized to our setup.

Our generalization bounds are derived by applying the previously developed techniques as in [AGNZ18, NBS17]. In particular, we follow the approach of [AGNZ18] by further adapting the technique for the magnitude pruning strategy and allowing the compressed network weights to take unbounded continuous values. As in [AGNZ18], we consider the 0-1 loss function with *margin* $\gamma \geq 0$, $\ell_\gamma \colon \mathcal{Y} \times \mathcal{Y} \mapsto \{0, 1\}$, for the multiclass classifier $f_\mathbf{w}$, given as follows:

$$\ell_\gamma(y, f_\mathbf{w}(\mathbf{x})) = \begin{cases} 1, & \text{if } f_\mathbf{w}(\mathbf{x})[y] - \max_{j \neq y} f_\mathbf{w}(\mathbf{x})[j] \leq \gamma, \\ 0, & \text{otherwise.} \end{cases} \tag{6}$$

Still denoting $\mathbf{w} = \mathbf{w}^{\{\infty\}}$, the population and empirical risks associated with ℓ_γ are denoted as $\mathcal{R}_\gamma(\mathbf{w})$ and $\widehat{\mathcal{R}}_\gamma(\mathbf{w})$, respectively. By having the dataset $S \sim \mu_Z^{\otimes n}$, we assume the weights $\mathbf{w}$ are sampled according to the stationary distribution $P_{\mathbf{w}|S}$ of SGD. Denote the joint distribution of $(S, \mathbf{w})$ by $P_{S,\mathbf{w}} := \mu_Z^{\otimes n} P_{\mathbf{w}|S}$.

In the following theoretical results, we will assume that we have access to a random compressible neural network that is amenable to the layer-wise magnitude pruning strategy with high probability. This assumption is essentially the outcome of Theorem 1 under the HML property together with an additional uniformity requirement on $d_{l,0}$ over S.[1]

H 1. *For $\varepsilon \geq 0$, $\epsilon > 0$, and $\{\kappa_l\}_{l=1}^L$: $\kappa_l \in (0,1)$, there exists $\{d_{l,0}\}_{l=1}^L$: $d_{l,0} \in \mathbb{N}$ independent of S, such that for $d_l \geq d_{l,0}$, $l \in [\![1, L]\!]$, the relation $\|\widehat{\mathbf{w}}_l - \mathbf{w}_l\| \leq \varepsilon\|\mathbf{w}_l\|$ holds for all $l \in [\![1, L]\!]$ simultaneously with probability at least $1 - \epsilon$, where $\widehat{\mathbf{w}}_l := \mathbf{w}_l^{(\kappa_l d_l)}$ and the probability is w.r.t. $P_{S,\mathbf{w}}$.*

In the following result, we relate the population risk of the compressed network to the empirical margin risk of the original (uncompressed) network. For notational convenience, for $\delta, \tau > 0$, let

$$R(\delta) := \inf\{R : \mathbb{P}(\|\mathbf{w}\| \geq R) \leq \delta\}, \text{ and } \mathcal{L}(\tau, \delta) := \sqrt{2}BL\Big(2R(\delta)/\sqrt{L}\Big)^{L-1}/\tau, \qquad (7)$$

where the probability is with respect to the joint distribution $P_{S,\mathbf{w}}$.

Theorem 4. *Assume H1 holds. Then for n: $n/\log(n) \geq 10L$, $\{d_l\}_{l=1}^L$: $d_l \geq d_{l,0}$, and any $\delta, \tau > 0$, with probability at least $1 - 2e^{-\kappa d/2} - \delta - \epsilon$,*

$$\mathcal{R}_0(\widehat{\mathbf{w}}) \leq \widehat{\mathcal{R}}_{\gamma(\delta,\tau)}(\mathbf{w}) + \Big(12\mathcal{L}(\tau,\delta)R(\delta) + \sqrt{d}\Big)\sqrt{(\kappa + \epsilon_\kappa)\log(n)/n}, \qquad (8)$$

where $R(\delta)$ and $\mathcal{L}(\tau,\delta)$ are defined in (7), $\kappa := \frac{1}{d}\sum_{l=1}^L \lceil \kappa_l d_l \rceil$,[2]

$$\epsilon_\kappa := (2h_b(\kappa) - \kappa\log(\kappa))/\log(n), \text{ and } \gamma(\delta,\tau) := \tau + \frac{\sqrt{2}B}{\tau}\Big(R(\delta)/\sqrt{L}\Big)^L\big((1+\varepsilon)^L - 1\big).$$

This result shows that, for a fixed relative compression error ε, if a network is more compressible, *i.e.* if κ is smaller, then its corresponding compressed network has a smaller generalization error bound, as the bound is scaled by the factor $\approx \sqrt{\kappa}$.

In our proof, we prove an intermediate result, inspired by [NTS15] and stated in the supplement, which bounds the perturbation of the network output after compression. This guarantees that the risks of the original and pruned networks can be made arbitrarily close, as long as the relative compression error is small enough.

To have a better understanding of the constants in Theorem 4, in the next result, we consider a special case where the weights follow a stable distribution, and we make the above bound more explicit.

Corollary 1. *Assume that for $l \in [\![1, L]\!]$ and $i \in [\![1, d_l]\!]$, the conditional distribution of $w_{l,i} \overset{i.i.d.}{\sim} \mathcal{S}\alpha_l\mathcal{S}(\sigma_l)$ with $\alpha_l \in (1,2)$. Further, assume that the scale parameters satisfy the following property:*

$$\sigma^2 := \sum_{l=1}^L (d_l/d)(\sigma_l/\sigma_{\alpha_l})^2 = \Big[(4^{-1/\alpha}\sqrt{L}/3)\sigma_0 d^{-(1/2+1/\alpha)}\Big]^2, \qquad (9)$$

where $\sigma_{\alpha_l} := (2\Gamma(-\alpha_l)\cos((2-\alpha_l)\pi/2))^{1/\alpha_l}$, $\alpha := \min_l \alpha_l$, and σ_0 is a constant, and also $\{\alpha_l\}_{l=1}^L$ and σ are independent from S. Then, for every $\varepsilon > 0$ and $\kappa_l \in (0,1)$, $l \in [\![1, L]\!]$, there exists $d_{l,0} \in \mathbb{N}$, such that for $d_l \geq d_{l,0}$, n: $n/\log(n) \geq 10L$, and every $\tau > 0$, with probability at least $1 - 3d^{-\alpha/(2L)}$,

$$\mathcal{R}_0(\widehat{\mathbf{w}}) \leq \hat{\mathcal{R}}_\gamma(\mathbf{w}) + \big(a\sigma_0^L/\tau + 1\big)\sqrt{(\kappa + \epsilon_\kappa)d\log(n)/n}, \qquad (10)$$

where $\{\widehat{\mathbf{w}}_l\}_l = \{\mathbf{w}_l^{(\kappa_l d_l)}\}_l$, $\gamma := \tau + b_\varepsilon\sigma_0^L\sqrt{d}/\tau$, $a := 6\sqrt{2}B2^LL^{3/2}$, and $b_\varepsilon := \sqrt{2}B\big((1+\varepsilon)^L - 1\big)$.

To simplify our presentation, we have set the 'scale' of the distribution as a decreasing function of dimension, which intuitively states that the typical magnitude of each entry of the network will get smaller as the network grows. We observe that for a fixed ε and d, the bound improves as pruning ratio, $1 - \kappa$, increases. This result is of interest in particular since it is observed experimentally (and in part, theoretically) that heavier-tailed weights are more compressible, and hence due to this result have better generalization bounds. This provides an alternative perspective to the recent bounds that aim at linking heavy tails to generalization through a geometric approach [SSDE20].

Finally, in the supplement, we further show that the uncompressed network also inherits this good generalization performance, which is consistent with the results of [HJTW21, KLG$^+$21].

---

[1]Note that the uniformity assumption is mild and can be avoided by combining Theorem 1 with Egoroff's theorem with additional effort, as in [SSDE20].

[2]The binary entropy $h_b(\kappa)$ (in nats) is defined as $-\kappa\log(\kappa) - (1-\kappa)\log(1-\kappa)$ for $\kappa \in [0,1]$, with the convention $h_b(0) = h_b(1) = 0$. Note that $0 \leq h_b(\kappa) \leq \log(2)$.

Figure 1: Mean estimated tail index ($\hat{\alpha}$) vs. η/b for each trained model. x-axes are log-scaled.

5 Experiments

In this section, we present experiments conducted with neural networks to investigate our theory. We use three different model architectures: a fully connected network with 4 hidden layers (FCN4), a fully connected network with 6 hidden layers (FCN6), and a convolutional neural network with 8 convolutional layers (CNN). Hidden layer widths were 2048 for both FCN models. All networks include ReLU activation functions and none include batch normalization, dropout, residual layers, or any explicit regularization term in the loss function. Each model is trained on MNIST and CIFAR10 datasets under various hyperparameter settings, using the default splits for training and evaluation. The total number of parameters were approximately $14M$ for FCN4-MNIST, $19M$ for FCN4-CIFAR10, $23M$ for FCN6-MNIST, $27M$ for FCN6-CIFAR10, and $9M$ for both CNN models. All models were trained with SGD until convergence with constant learning rates and no momentum. The convergence criteria comprised 100% training accuracy and a training negative log-likelihood less than 5×10^{-5}. The training hyperparameter settings include two batch sizes ($b = 50, 100$) and various learning rates (η) to generate a large range of η/b values. See the supplement for more details.

By invoking [GSZ20, Corollary 11] which shows the ergodic average of heavy-tailed SGD iterates converges to a multivariate stable distribution, after convergence, we kept running SGD for 1000 additional iterations to obtain the average of the parameters to be used in this estimation. The tail index estimations were made by the estimator proposed in [MMO15, Corollary 2.4], which has been used by other recent studies that estimate tail index in neural network parameters [SSDE20, GSZ20, ZFM$^+$20]. In all pruning methods, the parameters were centered before pruning is conducted with the median value to conform with the tail index estimation.

Training hyperparameters and layer statistics. We first verify that models trained with higher learning rate to batch size ratio (η/b) lead to heavier-tailed parameters, replicating the results presented in [GSZ20]. For each trained model, we compute the mean of separately estimated tail indices for all layers, so that each model is represented by a single value. This averaging is a heuristic without a clear theoretical meaning, and has been also used by recent works in the literature [GSZ20, MM19]. Results

Figure 2: Empirical distribution of a CNN layer trained on MNIST. (Left) Overlaid histograms of a random partition of the weights, showing an identical distribution. (Right) Comparing the network weights to samples simulated i.i.d. from a symmetric α-stable distribution with the same tail index $\alpha \approx 1.95$. y-axes are log-scaled.

presented in Figure 1 demonstrates confirm that higher η/b leads to heavier tails (lower $\hat{\alpha}$).

Also of interest are the distribution of the resulting parameters from training. Figure 2 (left) demonstrates a representative example of the parameters from an CNN layer trained on MNIST, where two overlaid histograms representing empirical distributions of a random partition of the parameters are almost identical. On the right in the same figure, this distribution is compared to a simulated symmetric α-stable distribution that has the same tail index (≈ 1.95). The figure demonstrates that the two distributions have similar qualitative properties.

Figure 3: Estimated tail index ($\hat{\alpha}$) vs. pruning ratio ($1 - \kappa$), for relative compression error $= 0.1$

Figure 4: Relative test accuracy vs. pruning ratio for layer-wise magnitude pruning. Color: mean $\hat\alpha$.

Figure 5: Relative test accuracy vs. pruning ratio for singular value pruning. Color: mean $\hat\alpha$.

Tail index and prunability. In this section we examine whether networks with heavier-tailed layers, trained with higher η/b ratios, are more prunable and whether they generalize better. As a baseline test, we first examine whether neural network layers which are heavier-tailed can be pruned more given a fixed maximum relative compression error. Figure 3 demonstrates for an error of 0.1 that this is indeed the case. We next test our hypothesis that posit models with heavy-tailed parameters to be more prunable. Both the results pertaining to layer-wise magnitude pruning and singular value pruning, demonstrated in Figures 4 and 5 show that this is indeed the case. Here, relative test accuracy stands for test accuracy after pruning / unpruned test accuracy. The results show that models with heavier-tailed parameters (shown with darker colors) are starkly more robust against pruning. Similar results with global magnitude pruning can be seen in the supplement.

For structured pruning, we prune 3×3 kernel parameters in CNN models. The results (Figure 6) show a similar, hypothesis conforming pattern. Results for FCNs, presented in the supplement, were underwhelming; perhaps unsurprisingly as structured pruning is not as commonly used in FCNs [O'N20]. More successful attempts could be due to alternative scoring methods [SAM⁺20]; our approach might require wider layers to conform with theoretical conditions.

Figure 6: Rel. test accuracy vs. pruning ratio for structured pruning. Color: $\hat\alpha$.

Tail index and generalization. Following our theoretical results, we examine whether the heavier-tailed networks lead to better generalization performance. Consistent with our hypothesis, Figure 7 shows that models with the highest tail index have consistently the worst test performances. The same conclusion applies to generalization performance as training accuracy is 100% for all models.

Figure 7: Test accuracy vs. mean estimated tail index ($\hat\alpha$) for each model. Color: training η/b ratio.

6   Conclusion

We investigated the conditions and the mechanism through which various pruning strategies can be expected to work, and confirmed the relationship between pruning and generalization from our theoretical approach. Future directions (hence our limitations) include a formal proof for the convergence of the weights to a mean-field distribution in the heavy-tailed setting, eliciting the relationship between $\hat\alpha$ and κ more clearly, and further examination of structured pruning in FCNs. Other pruning strategies would also benefit from our analyses, e.g. gradient-based pruning [BOFG20]. Recently it has been observed that gradients also exhibit heavy-tailed behavior [ŞGN⁺19, ZKV⁺20, ZFM⁺20]; we suspect that our theory might be applicable in this case as well.

References

[AGNZ18]   Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, pages 254–263. PMLR, 10–15 Jul 2018.

[AUM11]   Arash Amini, Michael Unser, and Farokh Marvasti. Compressibility of deterministic and random infinite sequences. *IEEE Transactions on Signal Processing*, 59(11):5193–5201, 2011.

[AZLL19]   Zeyuan Allen-Zhu, Yuanzhi Li, and Yingyu Liang. Learning and generalization in overparameterized neural networks, going beyond two layers. In *Advances in neural information processing systems*, pages 6155–6166, 2019.

[BDM⁺16]   Dariusz Buraczewski, Ewa Damek, Thomas Mikosch, et al. *Stochastic models with power-law tails*. Springer, 2016.

[Bha97]   Rajendra Bhatia. *Matrix Analysis*, volume 169. Springer, 1997.

[BLM20]   Witold M. Bednorz, Rafał M. Łochowski, and Rafał Martynek. On tails of symmetric and totally asymmetric α-stable distributions, 2020.

[BOFG20]   Davis Blalock, Jose Javier Gonzalez Ortiz, Jonathan Frankle, and John Guttag. What is the state of neural network pruning?, 2020.

[CB18]   Lénaïc Chizat and Francis Bach. On the global convergence of gradient descent for over-parameterized models using optimal transport. In *Advances in Neural Information Processing Systems*, volume 31, pages 3036–3046, 2018.

[DBDFS20]   Valentin De Bortoli, Alain Durmus, Xavier Fontaine, and Umut Simsekli. Quantitative propagation of chaos for SGD in wide neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[DR17]   Gintare Karolina Dziugaite and Daniel M Roy. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. *arXiv preprint arXiv:1703.11008*, 2017.

[EKT20]   Bryn Elesedy, Varun Kanade, and Yee Whye Teh. Lottery tickets in linear models: An analysis of iterative magnitude pruning. *arXiv preprint arXiv:2007.08243*, 2020.

[FC19]   Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *International Conference on Learning Representations*, 2019.

[FDRC20]   Jonathan Frankle, Gintare Karolina Dziugaite, Daniel Roy, and Michael Carbin. Linear mode connectivity and the lottery ticket hypothesis. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 3259–3269. PMLR, 13–18 Jul 2020.

[Gal68]   Robert G. Gallager. *Information Theory and Reliable Communication*. John Wiley & Sons, Inc., USA, 1968.

[GCD12]   Rémi Gribonval, Volkan Cevher, and Mike E Davies. Compressible distributions for high-dimensional statistics. *IEEE Transactions on Information Theory*, 58(8):5016–5034, 2012.

[GSZ20]   Mert Gurbuzbalaban, Umut Simsekli, and Lingjiong Zhu. The heavy-tail phenomenon in SGD. *arXiv preprint arXiv:2006.04740*, 2020.

[HJRY20]   Hattie Zhou, Janice Lan, Rosanne Liu, and Jason Yosinski. Deconstructing lottery tickets: zeros, signs, and the supermask. *arXiv:1905.01067 [cs, stat]*, March 2020. arXiv: 1905.01067.

[HJTW21] Daniel Hsu, Ziwei Ji, Matus Telgarsky, and Lan Wang. Generalization bounds via distillation. In *International Conference on Learning Representations*, 2021.

[HM20] Liam Hodgkinson and Michael W Mahoney. Multiplicative noise and heavy tails in stochastic optimization. *arXiv preprint arXiv:2006.06293*, 2020.

[HPTD15] Song Han, Jeff Pool, John Tran, and William Dally. Learning both weights and connections for efficient neural network. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015.

[HZS17] Yihui He, Xiangyu Zhang, and Jian Sun. Channel pruning for accelerating very deep neural networks. *arXiv:1707.06168 [cs]*, August 2017. arXiv: 1707.06168.

[JMW08] Benjamin Jourdain, Sylvie Méléard, and Wojbor A Woyczynski. Nonlinear sdes driven by lévy processes and related pdes. *Alea*, 4:1–29, 2008.

[KL17] Ilja Kuzborskij and Christoph H Lampert. Data-dependent stability of stochastic gradient descent. *arXiv preprint arXiv:1703.01678*, 2017.

[KLG+21] Lorenz Kuhn, Clare Lyle, Aidan N. Gomez, Jonas Rothfuss, and Yarin Gal. Robustness to pruning predicts generalization in deep neural networks, 2021.

[LKD+17] Hao Li, Asim Kadav, Igor Durdanovic, Hanan Samet, and Hans Peter Graf. Pruning filters for efficient ConvNets. *arXiv:1608.08710 [cs]*, March 2017. arXiv: 1608.08710.

[LMW19] Mingjie Liang, Mateusz B Majka, and Jian Wang. Exponential ergodicity for sdes and mckean-vlasov processes with levy noise. *arXiv preprint arXiv:1901.11125*, 2019.

[Lon17] Ben London. A pac-bayesian analysis of randomized learning with application to stochastic gradient descent. In *Advances in Neural Information Processing Systems*, pages 2931–2940, 2017.

[LWZ81] Raoul LePage, Michael Woodroofe, and Joel Zinn. Convergence to a stable distribution via order statistics. *The Annals of Probability*, 9(4):624 – 632, 1981.

[MM19] Charles H Martin and Michael W Mahoney. Traditional and heavy-tailed self regularization in neural network models. In *ICML*, 2019.

[MMN18] Song Mei, Andrea Montanari, and Phan-Minh Nguyen. A mean field view of the landscape of two-layer neural networks. *Proceedings of the National Academy of Sciences*, 115(33):E7665–E7671, 2018.

[MMO15] Mohammad Mohammadi, Adel Mohammadpour, and Hiroaki Ogata. On estimating the tail index and the spectral measure of multivariate α-stable distributions. *Metrika*, 78(5):549–561, 2015.

[NBS17] Behnam Neyshabur, Srinadh Bhojanapalli, and Nathan Srebro. A pac-bayesian approach to spectrally-normalized margin bounds for neural networks. *arXiv preprint arXiv:1707.09564*, 2017.

[Neu21] Gergely Neu. Information-theoretic generalization bounds for stochastic gradient descent. In *Conference on Learning Theory*, 2021.

[Nol20] John P. Nolan. *Univariate Stable Distributions: Models for Heavy Tailed Data*. Springer, Switzerland, 2020.

[NP20] Phan-Minh Nguyen and Huy Tuan Pham. A rigorous framework for the mean field limit of multilayer neural networks. *arXiv preprint arXiv:2001.11443*, 2020.

[NTS15] Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. Norm-based capacity control in neural networks. In *Conference on Learning Theory*, pages 1376–1401, 2015.

[O'N20] James O'Neill. An overview of neural network compression. *arXiv:2006.03669 [cs, stat]*, August 2020. arXiv: 2006.03669.

[PFF20]   Stefano Peluchetti, Stefano Favaro, and Sandra Fortini. Stable behaviour of infinitely wide deep neural networks. In *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108, pages 1137–1146, 2020.

[RFC20]   Alex Renda, Jonathan Frankle, and Michael Carbin. Comparing rewinding and fine-tuning in neural network pruning. *arXiv:2003.02389 [cs, stat]*, March 2020. arXiv: 2003.02389.

[Rob55]   Herbert Robbins. A remark on stirling's formula. *The American Mathematical Monthly*, 62(1):26–29, 1955.

[SAM+20]   Taiji Suzuki, Hiroshi Abe, Tomoya Murata, Shingo Horiuchi, Kotaro Ito, Tokuma Wachi, So Hirai, Masatoshi Yukishima, and Tomoaki Nishimura. Spectral pruning: Compressing deep neural networks via spectral analysis and its generalization error. In *International Joint Conference on Artificial Intelligence*, pages 2839–2846, 2020.

[SAN20]   Taiji Suzuki, Hiroshi Abe, and Tomoaki Nishimura. Compression based bound for non-compressed network: unified generalization error analysis of large compressible deep neural network. In *International Conference on Learning Representations*, 2020.

[SD15]   Jorge F Silva and Milan S Derpich. On the characterization of ℓ_p-compressible ergodic sequences. *IEEE Transactions on Signal Processing*, 63(11):2915–2928, 2015.

[ŞGN+19]   Umut Şimşekli, Mert Gürbüzbalaban, Thanh Huy Nguyen, Gaël Richard, and Levent Sagun. On the heavy-tailed theory of stochastic gradient descent for deep neural networks. *arXiv preprint arXiv:1912.00018*, 2019.

[SS20]   Justin Sirignano and Konstantinos Spiliopoulos. Mean field analysis of neural networks: A central limit theorem. *Stochastic Processes and their Applications*, 130(3):1820–1852, 2020.

[SSDE20]   Umut Simsekli, Ozan Sener, George Deligiannidis, and Murat A. Erdogdu. Hausdorff Dimension, Heavy Tails, and Generalization in Neural Networks . In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[SSG19]   Umut Simsekli, Levent Sagun, and Mert Gurbuzbalaban. A tail-index analysis of stochastic gradient noise in deep neural networks. In *ICML*, 2019.

[Szn91]   Alain-Sol Sznitman. Topics in propagation of chaos. In *Ecole d'été de probabilités de Saint-Flour XIX—1989*, pages 165–251. Springer, 1991.

[TTR+20]   Asma Teimouri, Mahbanoo Tata, Mohsen Rezapour, Rafal Kulik, and Narayanaswamy Balakrishnan. Asymptotic behavior of eigenvalues of variance-covariance matrix of a high-dimensional heavy-tailed lévy process. *Methodology and Computing in Applied Probability*, pages 1–23, 2020.

[Wu20]   Yihong Wu. Lecture notes on information-theoretic methods for high-dimensional statistics, 2020.

[WZG20]   Chaoqi Wang, Guodong Zhang, and Roger Grosse. Picking winning tickets before training by preserving gradient flow. *arXiv:2002.07376 [cs, stat]*, August 2020. arXiv: 2002.07376.

[YLWT17]   Xiyu Yu, Tongliang Liu, Xinchao Wang, and Dacheng Tao. On compressing deep models by low rank and sparse decomposition. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 67–76, Honolulu, HI, July 2017. IEEE.

[ZFM+20]   Pan Zhou, Jiashi Feng, Chao Ma, Caiming Xiong, Steven Chu Hong Hoi, and Weinan E. Towards theoretically understanding why SGD generalizes better than ADAM in deep learning. *Advances in Neural Information Processing Systems (NeurIPS)*, 33, 2020.

[ZKV+20]   Jingzhao Zhang, Sai Praneeth Karimireddy, Andreas Veit, Seungyeon Kim, Sashank Reddi, Sanjiv Kumar, and Suvrit Sra. Why are adaptive methods good for attention models? *Advances in Neural Information Processing Systems (NeurIPS)*, 33, 2020.

[ZLZ19]   Yi Zhou, Yingbin Liang, and Huishuai Zhang. Understanding generalization error of sgd in nonconvex optimization. *stat*, 1050:7, 2019.